

217.

A COMPARISON OF X-RAY FLUORESCENCE AND WET CHEMICAL ANALYSIS OF AIR FILTERS FROM A SCRAP LEAD SMELTING OPERATION.

M. Harper, M. Andrew, NIOSH, Morgantown, WV; T. Hallmark, Mississippi Space Services, John C. Stennis Space Center, MS.

Personal and area air samples were taken at a scrap lead smelter operation at a bullet manufacturer using the 37-mm styrene/acrylonitrile filter cassette, the 37-mm GSP or "cone" sampler, the 25-mm Institute of Occupational Medicine (IOM) inhalable sampler, and the 25-mm Button sampler (developed by the University of Cincinnati). Pure, homopolymer, polyvinylchloride filters were used to capture lead particulate. The filters were pre- and post-weighed, and analyzed for lead content using a portable x-ray fluorescence (XRF) analyzer. The filters were then extracted with dilute nitric acid in a sonic bath and the solutions analyzed by inductively coupled plasma optical emission spectroscopy (ICP-OES). The 25-mm filters were analyzed using a single XRF reading, while three readings on different parts of the filter were taken from the 37-mm filters in accordance with current NIOSH/OSHA methodology. The single reading from the 25-mm filters was adjusted for the nominal area of the filter to obtain the mass loading, while the three readings from the 37-mm filters were inserted into two different algorithms for calculating the mass loadings, one from NIOSH and one from OSHA, and the algorithms were compared. The IOM is the only sampler where material collected in the sampler, but not caught on the filter, is intended to be part of the sampler. Therefore, the cassettes were rinsed separately to determine how this might bias the on-filter analysis, but ICP analysis found only insignificant amounts of lead, in line with other studies. All four samplers gave very good correlations between the two analytical methods above the limit of quantification of the XRF procedure, although the limit was lower for the 25-mm filters (3 μg) than for the 37-mm filters (10 μg). For both types of 37-mm filter, the OSHA algorithm gave results closer to the ICP values than the NIOSH algorithm.

218.

POTENTIAL WORKPLACE EXPOSURES FROM METAL CASTING PROCESS EMISSIONS.

C. Glowacki, J. Stone, Technikon LLC, McClellan, CA.

Workplace exposure to hazardous materials in the metal casting industry has been the topic of many publications and presentations over the last 30 years. Most have focused on physical hazards such as heat and physical stress, inorganic chemicals such as silica, and a limited number of organic compounds. The Casting Emission Reduction Program (CERP), a public/private cooperative research and development program, has identified numerous com-

pounds emitted from a variety of metal casting processes that greatly increase the potential for excessive workplace exposures. Many of these compounds and the method(s) of their formation and release to the environment have not been reported in the literature. The CERP target analyte list contains over 100 specific compounds that are routinely measured to concentrations of 10 to 100 parts per billion. This presentation will detail those organic compounds emitted from major metal casting processes such as core making, mold making, and pouring, cooling, and shakeout activities. The information will be subdivided by the type of metal being cast, the chemistry of the binder system used to prepare the core or mold, and the type of molding or core making process. The specific compounds found in each scenario will be ranked in order of the amount of compound emitted compared to the weight of metal cast, sand used, and/or binder used.

219.

INVESTIGATION OF A VOLATILE PRE-IMPREGNATE FOR USE IN A SELF-VALIDATING DIFFUSIVE SAMPLER.

M. Reed, Trident Technical College, Charleston, SC; D. Underhill, C. Feigley, University of South Carolina, Columbia, SC.

The diffusive sampler is a valid air sampling device which can be used to measure airborne contaminants in the workplace. The primary limitation to the diffusive sampler is the uncertainty in the determination of the diffusivity coefficient as the diffusivity coefficient varies with environmental factors that affect complete sample uptake and retention. Accurate determination of the airflow rate cannot always be achieved due to the uncertainty of the diffusivity coefficient affected by these factors. Our objective was to improve the accuracy and assess abuse or misuse of the diffusive sampler by developing a self-validating diffusive sampler that will significantly improve the quality of air sampling data. A volatile pre-impregnate was investigated with adsorptive properties that will result in reverse diffusion under ambient conditions and that has a chemical half-life. The properties of the volatile pre-impregnate include: (1) a sufficiently high vapor pressure such that significant desorption will occur if the sampler is allowed to desorb after the sampling period; (2) easy detection so that only trace levels of the volatile pre-impregnate need to be placed onto the adsorbent; (3) not commonly present in the workplace so that uptake of the volatile pre-impregnate from the atmosphere will not be a confounding factor; (4) chemically stable; (5) readily available; and (6) low in toxicity. Diffusive samplers were exposed to the volatile pre-impregnate in a chamber, allowed to reach equilibrium, exposed to the ambient atmosphere, and desorbed with chlorobenzene. The volatile pre-impregnate was analyzed by gas chromatography with a flame ionization detector and confirmed by gas chro-

matography with mass spectrometry. There are very few chemical compounds that have the physical and chemical characteristics suitable for use as a volatile pre-impregnate in a self-validating diffusive sampler. Chloromethane meets the criteria and appears to be the most promising volatile pre-impregnate.

220.

PROBLEMATIC EFFICIENCY OF MDI SAMPLING.

L. Saarinen, Finnish Institute of Occupational Health, Helsinki, Finland.

Methylene bisphenyl diisocyanate (MDI) is atomised and evaporated during the exothermic polymerisation process. The data on the relationship between exposure to MDI and the effects it induces are scarce. This may be due to the complex etiology of the effects and/or in the shortcomings of exposure measurements. Sampling methods for MDI were compared in pairs to identify problems.

In the test chamber, the MDI aerosol was produced with a Liu-Lee aerosol generator without a polyol component, and a vapor-aerosol mixture was generated in the polymerisation process. The aerosols were characterized with a scanning electron microscope and a particle size counter. Solvent absorption and variable coated filters were used in the tests. 1-(2-methoxyphenyl)piperazine (MPP) was the derivative reagent. The filters were coated with 20 or 2 μmol MPP in toluene. The samples were collected under variable airflows and analysed with a high-performance liquid chromatograph.

The collection efficiency for solvent absorption methods was mainly a function of flowrate. The sampling efficiency was poor for particles under 1 μm in size. The loss depended also on the slowness of the reaction rate both in the glassware and on the coated filters. The collection efficiency in the solid-state system of coated filters depended on sampling rate, amount of applied reagent, diffusion, and porosity.

All the tested sampling methods were incomplete, and underestimated the actual concentrations of fast curing MDI present as a mixture of aerosol and vapor. To minimize the underestimation, complementary methods for determining the exposure to MDI are recommended to be used simultaneously. The detection limit of analysis restricts the measurement of very short but high exposure peaks. It was therefore difficult to assess the actual exposure and dosage. Alternating efficiencies under variable sampling conditions impede the establishing of the dose-response relationship.

221.

COMPARISON OF SAMPLERS FOR COLLECTING WOOD-DUST AEROSOL.

M. Harper, M. Andrew, NIOSH, Morgantown, WV; Z. Akbar, University of Alabama at Birmingham, Birmingham, AL; B. Muller, Honda Manufacturing of Alabama LLC, Lincoln, AL.

Particle size distributions in the inhalable size range collected by different personal samplers for wood dust were compared. Samples were collected over a short sampling period (<2 hours) on PVC filters, removed, suspended, and re-deposited evenly on a MCE filter, which was then cleared, and portions examined by optical microscopy. The aerodynamic equivalent diameter (AED) of particles was calculated from their dimensions, shape factor, and density. This method is particularly appropriate to wood-dust particles which are generally large and close to rectangular prisms in shape. Personal samples were collected using the traditional 37-mm closed-face polystyrene/acrylonitrile cassette (CFC), the Institute of Occupational Medicine (IOM) inhalable sampler, and the Button sampler developed by the University of Cincinnati. Total mass concentration results from the method described above were in approximately the same ratios as those from traditional long-term gravimetric samples, but about an order of magnitude higher. The particulate mass appears to be concentrated in the range 10–70 μm AED, but with contributions from particles larger than 100 μm AED in 65% of the IOM samples, 42% of the CFC samples, and 32% of the Button samples. Where present, these "ultra-large" particles dominated the mass collected, contributing an average 53% (range 10–95%), but significant differences were still found even after accounting for their effect. The IOM and CFC samplers appeared to operate in accordance with previous laboratory studies, as they both collected similar quantities of particles at the smaller size-ranges, up to about 30–40 μm AED, and for larger size-ranges the CFC collection was reduced compared to the IOM. The Button sampler collected significantly less than the IOM at most particle sizes. The Button sampler appears to sample less than the CFC at smaller particle diameters, consistent with some, but not all, relevant laboratory studies.

222.

COMPARISON OF REAL-TIME AEROSOL MEASUREMENTS AGAINST THE TIME-INTEGRATED SAMPLING METHODS IN A WOOD WORKING FACILITY. S. Erdal, L. Brown, S. Freels, L. Conroy, N. Esmen, University of Illinois at Chicago, Chicago, IL.

Exposure to wood dust has been associated with a number of health outcomes including respiratory irritation and nasopharyngeal cancer. It is important to measure wood dust concentrations that are encountered in a workplace to determine compliance and to provide necessary input to health effects studies. The customary exposure assessment tools used for aerosol monitoring involve samplers, which provide time-integrated measures of exposure. However, samplers with the near real-time capability have the ability to significantly improve our understanding of temporal distri-

bution of workplace exposures. They also allow assessment of specific activities in the workplace, which result in high exposures. This information is very useful for exposure reduction and risk management purposes. We conducted a wood dust exposure assessment study in a mid-size wood working facility using a number of exposure assessment tools at a static sampling location in the middle of the facility. For time-integrated measures of exposure, 37-mm closed-cassette and a Marple Cascade Impactor were used. For near real-time measurements, MIE's Personal DataRam (pDR-1200) was used. Sampling for total dust was performed on 10 different days in which different activities by the workers were performed (e.g., sawing, sanding, cutting). Sampling duration was four hours in each sampling event. While the MIE total dust measurements varied from 0.5 to 2.8 mg/m^3 , the 37-mm measurements at the same location were in the range of 0.2 to 1.3 mg/m^3 . The comparison of the time-integrated data against the near real-time data for total wood dust revealed the importance of obtaining information on temporal distribution of exposure, thus the need for development of reliable real-time monitoring tools and instruments for aerosol monitoring in the workplace.

Podium 128. Physical Agents: Ionizing/Nonionizing Radiation/Heat Stress

Papers 223–230

223.

DENVER RADIUM STREETS PROJECT.

T. Mustard, Parsons, Denver, CO; A. Soque, City and County of Denver, Denver, CO.

During the early 1900s, Denver, Colo., was home to a radium processing industry. The production process created waste "tailings," which were left in large piles near the processing plants. In the 1920s, radium processing was discontinued and the tailings piles were abandoned. Over the years some of these piles were used as fill and aggregate in street construction. In the late 1970s, the U.S. Environmental Protection Agency identified several Denver streets that had been constructed using the radioactive tailings. Denver's Radium Streets Project is comprised of nine street segments totaling approximately 22 city blocks that contain low-level radioactive contamination in residential areas near downtown Denver.

The contaminants primarily consist of natural radium, thorium, uranium, and associated daughter products including radon gas. The contamination associated with these streets is bound in the asphalt and poses a minimal threat to nearby residents. It is a concern, however, to city workers and contractors who must excavate the streets for underground utility projects.

The first phase of demolition and reconstruction of two of the street segments (totaling 10 blocks) was initiated in 2003. The project involved the removal of radium-contaminated

asphalt, curbs, and gutters; removal of manholes and storm drains; and the removal of up to two inches of subgrade below all radium-contaminated paving. The excavated contaminated material was containerized and transported via trucks and rail cars to a licensed disposal site in Idaho. The project work also included air monitoring, soil sampling, site monitoring, site security, traffic controls, installing barrier fence, surveying, and repaving.

Protection of neighborhood residents as well as site workers was a primary concern during this project. This paper describes the safety procedures implemented to protect the site workers and nearby residents during street demolition and reconstruction.

224.

IONIZING RADIATION WEB-BASED TRAINING. C. Duffield, U.S. Geological Survey, Reston, VA.

The Nuclear Regulatory Commission and the Occupational Safety and Health Administration Training require employers to train employees who are occupationally exposed to ionizing radiation. The U.S. Geological Survey and the Department of the Interior University developed interactive web-based training as a cost-effective method of providing training for a variety of ionizing radiation users in many locations. Employees take a basic module and one to four additional modules in X-ray machines, naturally occurring radioactive materials, general licensed materials, or specific licensed materials. The program tracks performance and maintains the training records.

225.

UV RADIATION INCIDENT. O. Azpuru, Boston University, Boston, MA.

Situation: In April 2002, the Boston University Office of Environmental Health and Safety (OEHS) received a call from the BU Occupational Health Center alleging that several members of the women's volleyball team had developed redness and irritation on their face, eyes, and upper shoulder area after practicing in an indoor gymnasium. Upon further investigation, OEHS determined that members of other sports teams had also experienced these symptoms after spending time in this gymnasium; the Fencing Team did not seem affected. All equipment was kept in a common storage room and was routinely cleaned using a "scrub-free" cleanser. The teams were advised to stop using this cleanser.

Suspecting contact dermatitis, OEHS observed a full practice of the women's volleyball team in an attempt to identify the cause. No cause was found that day; however, redness and irritation were observed on several team members. Samples were collected for bioaerosols, total dust, VOCs, etc; all were inconclusive. Non-chemical/biological causes began to be explored, including the gymnasium lighting.

*The Premier Conference and Exposition for Occupational
and Environmental Health and Safety Professionals*

May 8-13, 2004 • Georgia World Congress Center, Atlanta, GA

Promoting OEHS Excellence

AIHce

2004 Abstracts



American Industrial Hygiene
Conference & Expo 2004



Sponsored by
The American Industrial Hygiene Association
and ACGIH®