

gram that teaches mine operators how to recognize, evaluate, and control dust and noise hazards, MSHA and NSSGA have trained approximately 250 participants at 24 hands-on workshops since the December 1997 inception of the program. Attendees learn how to conduct on-site exposure monitoring, coordinate with an analytical laboratory, interpret the exposure data, keep appropriate records, and identify corrective measures. MSHA provides experienced instructors, classroom materials, and sampling equipment for hands-on training. NSSGA recruits the students and provides logistical support. Each workshop occurs at an NSSGA-member quarry. MSHA uses the course curriculum as a model for training metal and nonmetal inspectors, miners, and operators in other types of mining operations (e.g., gold, salt, iron ore). The materials developed and the techniques used could easily be adapted to train workers in similar industries, or by other agencies and educational institutions that wish to develop training with a strong hands-on component. The partnership with NSSGA has provided MSHA with a framework for working with other industry and labor organizations in similar joint ventures. The success of the MSHA and NSSGA cooperative training program is highlighted by collaborative development, innovative implementation, and significant achievement. Both organizations continue to demonstrate a strong commitment to the partnership.

36.

LIMITATIONS OF INTEGRATING IMPULSIVE NOISE WHEN USING DOSIMETERS. C. Kardous, R. Willson, C. Hayden, NIOSH, Cincinnati, OH

The National Institute for Occupational Safety and Health (NIOSH) conducted a noise-exposure assessment of the indoor firing range at the National Firearms Unit of the Immigration and Naturalization Service (INS). The purpose was to identify salient acoustic parameters associated with typical live firing activities and to provide noise abatement recommendations. Live fire measurements were obtained at 11 different positions throughout the firing range and adjacent areas using two different instrumentation systems. The first system used a Bruel and Kjaer (B&K) type 4136 1/4" microphone, a B&K type 2615 pre-amplifier, and a B&K type 2807 power supply that fed a Panasonic Model SV-255 DAT recorder. The second group of measurements was obtained with 11 dosimeters (Quest Model Q400). Spectral analysis of the DAT recordings was performed using MATLAB software routines. Analysis of the signals revealed that the dosimeter readings were nearly always in error. In some cases, the peak level from the weapons (as much as 163 dB SPL) exceeded the nominal input limit of the dosimeter (146 dB SPL). The Q400 dosimeters "clipped" the impulses by acting as if the gunfire had a maximum level of 146 dB SPL. In other cases, however, some peak levels (e.g., 108 dB SPL)

were below the dosimeter input limit, but the dosimeters still showed a peak level of 146 dB SPL. While the OSHA standard requires and NIOSH recommends that sound levels from 80 to 140 dBA be integrated in the calculation of dose, the present data suggest this criterion may be inadequate. These results have found that some instruments are incapable of providing accurate measures of impulse sounds that may be commonly encountered because of their electroacoustic limitations. The authors will recommend electroacoustic criteria for systems intended for use in measuring impulsive sounds such as gunfire.

37.

RESULTS AND RECOMMENDATIONS OF NOISE SURVEYS OF PORTABLE TOOLS. E. Leslie, J. Reeder, Solutia, Inc., Greenwood, SC

Noise surveys of pneumatic tools, a drum vacuum, sandblasting and chipping were taken during field use to determine hearing protection device (HPD) requirements. Single HPD was required of the operator but no formal survey had been conducted to determine adequacy or if nearby employees also needed single HPD. A sound level survey was conducted and the Inverse Square Law was used to determine hearing protection requirements. The Inverse Square Law was used because not all of the distances were accessible or safe for the person taking the measurements while the various job tasks were being performed. The employees were notified of these findings and practices were put into place for the HPD requirements. As a result of this study, Solutia personnel are now adequately protected from noisy tasks when following recommended HPD practices.

38.

THE ATTENUATION OF HEARING PROTECTORS IN EXTREME CONDITIONS. E. Toppila, J. Starck, Finnish Institute of Occupational Health, Helsinki, Finland; I. Pyykkö, Karolinska Institute, Stockholm, Sweden

WITHDRAWN

PF 107. Exposure Assessment Strategies I

Papers 39-46

39.

RETROSPECTIVE EXPOSURE ASSESSMENT IN A NICKEL SMELTER USING BAYESIAN METHODS. G. Ramachandran, University of Minnesota, Minneapolis, MN

A Bayesian framework was used for retrospective exposure assessment of workers in a nickel smelter. The reconstruction of exposure in epidemiological studies relies on piecing together information from work histories, occupational exposure data, and knowledge of the work environment. Typically, actual exposure data are sparse or nonexistent for many

etiologically relevant periods. Exposure assessment strategies, measurement criteria, instruments, and analysis methods for nickel have changed over the past several decades. Using only sparsely available historical measurements resulted in estimates with large uncertainties. However, additional information, in the form of expert judgments informed by knowledge of historical plant conditions, and physical modeling based on these expert inputs, can be brought to bear on this process. The experts, who are experienced industrial hygiene professionals and aerosol scientists, were provided with an information packet that contained historical process information, process throughput levels for each year, the dimensions of the workplace, ventilation records, and task descriptions for each job category. Based on this information, the experts provided subjective prior probability distributions for input parameters (aerosol emission rate, ventilation flowrate, mixing efficiency, aerosol removal by mechanisms such as settling) to a general ventilation model that predicts building concentrations. Expert input was also obtained from a plant industrial hygienist, in the form of probability distributions, regarding the amounts of time spent by each job category in different locations in the building. Monte-Carlo sampling, from the "prior" probability distributions of concentrations in different micro-environments and the probability distributions of time spent by each job category in those micro-environments, was used to obtain worker exposures using a time-weighted averaging model. These priors were synthesized with the historical measurements using Bayes theorem. The prior distributions of exposures were updated using the average measured exposures (historical measurements) and their associated variances to obtain the posterior probability distributions for worker exposures.

40.

EXPOSURE ASSESSMENT FOR THE GLOBAL BURDEN OF OCCUPATIONAL INJURIES. D. Nelson, M. Concha, A. Pruess, J. Leigh, M. Fingerhut, C. Corvalan, WHO, Geneva, Switzerland

As part of the WHO project on Comparative Risk Assessment (CRA) of the major risk factors contributing to the Global Burden of Disease and Injuries, we have estimated probability of exposure to potentially hazardous conditions which may result in occupational injuries, by gender and CRA region. (CRA regions are comprised of countries with similar geography, epidemiology, infrastructure and economic situations.) According to the CRA methodology, estimates of exposure prevalence to a specific risk factor are combined with the associated relative risks to estimate the resulting attributable fraction of deaths and/or disabilities.

For each CRA region, the distribution of employment was determined by occupation (office, services, manual). The proportion of

The Premier Conference for Occupational and Environmental Health
and Safety Professionals

POWERFUL PARTNERSHIPS

Leveraging the power of collaboration to expand knowledge



ABSTRACTS



American Industrial Hygiene Conference & Expo

Cosponsored by AIHA and ACGIH®

June 1–6, 2002, San Diego Convention Center, San Diego, California

NIOSH LIBRARY SYSTEM

ALICE HAMILTON LIBRARY
4676 COLUMBIA PARKWAY
CINCINNATI, OH 45226

2002 Abstract Index by Session Topic



Platform Session Topic	Abstract No.	Platform Session Topic	Abstract No.
Aerosols	157-164	Management/Leadership	224-231
Agricultural Health and Safety	1-6	Occupational Epidemiology	25-31
Air Sampling Instrument Performance	79-86	Occupational Ergonomics: Training and Risk Assessment	7-12
Bioaerosols	165-173	Occupational Medicine/Occupational Epidemiology	148-156
Biological Monitoring	56-66	Personal Protective Clothing and Equipment	133-139
Community Environmental Health and Safety Issues and Social Concerns	121-126	Regulating the Right Hazards Rightly	19-24
Computer Applications in Industrial Hygiene	270-280	Respiratory Protection	185-195
Construction and Equipment	218-223	Risk Assessment in Industry and of Terrorism's Aftermath	196-202
Contaminant Control	140-147	Testing for Air Quality in the Garage	73-78
Current Topics in Noise and Hearing Loss	32-38	Toxicology and Toxicology Models (BPBK and QSAR)	47-53, 53,1-55
Dermal Exposures	174-184	Ventilation	95-102
Ergonomics Intervention	67-72		
Exposure Assessment Strategies I	39-46	Poster Sessions	Abstract No.
Exposure Assessment Strategies II	210-217	Poster Session 501	327-356
Gas & Vapor Detection	127-132	Poster Session 502	357-384
Health Care	112-120	Poster Session 503	385-413
Indoor Environmental Quality	242-250	Poster Session 504	414-442
Industrial Hygiene General Practice	251-262		
International Occupational Hygiene	232-241	Case Study Sessions	Abstract No.
Investigating Community Air Quality	203-209	Case Study 301	281-292
Ionizing and Nonionizing Radiation Risks: Measuring the Exposure	13-18	Case Study 302	293-303
Laboratory Health and Safety	87-94	Case Study 303	304-310
Lead I	103-111	Case Study 304	311-314, 317-318
Lead II	263-269	Case Study 305	319-326

PF 101 Agricultural Health and Safety

Papers 1-6

1. RELATIONSHIPS BETWEEN WORK EXPOSURE AND RESPIRATORY OUTCOMES IN POULTRY WORKERS.

S. Kirychuk, J. Dosman, P. Willson, L. Dwernychuk, University of Saskatchewan, Saskatoon, SK, Canada; J. Feddes, A. Senthilselvan, C. Ouellette, University of Alberta, Edmonton, AB, Canada

A pilot study was conducted on 74 poultry barn workers in Western Canada during the winters of 1998-2000. General respiratory health, current, chronic and work related respiratory symptoms; general work duties, and work-site factors were ascertained, pre-exposure, by questionnaire. Personal airborne exposure levels and changes in symptoms and lung function were measured across the work-shift for all workers. Workers were classified according to the type of poultry operation (floor based, n=53; cage based, n=13) in which they worked. There was no significant difference in daily hours spent in the barn between those who worked with caged poultry (5.41±2.35 hours) and those who worked with floor-based poultry (4.42±2.48 hours). Age of birds was 47.10±58.36 days for floor based versus 155.91±63.01 days for cage based facilities.

There were no significant differences in personal environmental measurements between cage-based and floor-based facilities (ammonia 13.22±13.70 ppm, 17.34±16.35 ppm; total dust 5.74±4.85mg/m³, 10.01 ±8.84 mg/m³; endotoxin 6046±6089 EU/m³, 5457±5934 EU/m³ respectively). There were no significant differences in across work-shift change in pulmonary function indices between workers from cage and floor-based operations. For the entire sample total dust dose (work hours/day x total dust) significantly correlated with across-shift change in FEV₁, whereas endotoxin dose and ammonia dose did not. Stocking density was significantly correlated with average ammonia (ppm, p=0.002) and ammonia dose (ppm x work hours/day; p=0.004) in floor based operations and with total dust (particles/ml, p=0.002) in cage based populations. Stocking density was also significantly correlated with chronic cough (p=0.003) and across work-shift cough (p=0.05) and chest tightness (p=0.06) for workers from floor based operations; and with phlegm when working (p=0.018) and chest tightness across the work-shift (p=0.004) for workers from cage based operations. Type of poultry production operation and therefore type of work exposures appear to significantly impact symptoms experienced by workers exposed to these atmospheres.

2. DUST GENERATION SYSTEM FOR AGRICULTURAL SOIL DUST. K. Lee, R. Domingo-Neumann, R. Southard, UC Davis, Davis, CA

Agricultural workers are prone to exposure to mixed dust of inorganic and organic compounds. Diverse working conditions and operations in agriculture make direct measurements of the mixed dust exposure difficult. This study was conducted to develop a new dust generation system to determine possible exposure potency indicators of soil samples. The dust generator consists of a blower, a rotating chamber and a settling chamber. The rotating chamber has inner baffles to provide sufficient agitation of the samples while the chamber is rotating. A blower provides air into the rotating chamber, and the suspended dust is moved to the settling chamber through a perforated pipe. A small fan inside the settling chamber helps maintain suspension of the dust. Various size fractions of dust are sampled on filters suspended in the chamber via outlet ports and attached pumps. Air pressure is released through a filter plate mounted on the wall of the settling chamber. Various operating conditions were evaluated: air intake from blower, speed of rotation, soil mass and sampling time. To evaluate the characteristics of dust from the system, we collected dust samples from agricultural fields while the soil was prepared for