NIOSH/OSHA

Occupational Health Guidelines for Chemical Hazards

Editors
Frank W. Mackison
National Institute for Occupational Safety and Health
R. Scott Stricoff
Lawrence J. Partridge, Jr.
A. D. Little, Inc.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service
Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

January 1981

DHHS (NIOSH) Publication No. 81-123

Abstract

Occupational Health Guidelines for Chemical Hazards summarizes information on permissible exposure limits, chemical and physical properties, and health hazards. It provides recommendations for medical surveillance, respiratory protection, and personal protection and sanitation practices for specific chemicals that have Federal occupational safety and health regulations. These recommendations reflect good industrial hygiene and medical surveillance practices, and their implementation will assist development and maintenance of an effective occupational health program.

Acknowledgements

These guidelines were prepared by Arthur D. Little, Inc. under NIOSH contract No. 210-76-0161 from data compiled, evaluated, and reviewed under the joint NIOSH/OSHA Standards Completion Program. Frank W. Mackison was the NIOSH Project Officer responsible for management and technical direction. R. Scott Stricoff was responsible for management and technical direction of the project for the contractor. NIOSH gratefully acknowledges the extensive effort performed by the many individuals who worked on the Standards Completion Program in assembling and evaluating the technical data contained in these guidelines. Thanks are also due to those who reviewed and commented on these guidelines during their development. Special recognition is due to David J. Francato, who reviewed the drafts for NIOSH; to Scott Merkle and Nancy Hughes, who reviewed them for OSHA; to Ana M. Stricoff, editor for Arthur D. Little, Inc.; to Russell Hinton, NIOSH Printing Officer, and Richard Lutz, Printing Specialist, U.S. Public Health Service, for their advice and assistance in producing the document using the U.S. Government Printing Office photocomposition facilities.

TABLE OF CONTENTS

Acetaldehyde
Acetic Acid
Acetic Anhydride
Acetone*
Acetonitrile
2-Acetylaminofluorene*
Acetylene Tetrabromide
Acrolein
Acrylamide
Acrylonitrile*
Aldrin*
Allyl Alcohol
Allyl Chloride
Allyl Glycidyl Ether*
4-Aminobiphenyl*
2-Aminopyridine
Ammonia
Ammonium Sulfamate
n-Amyl Acetate
sec-Amyl Acetate
Aniline
Anisidine, Ortho and Para Isomers
Antimony*
ANTU
Arsenic*, Inorganic
Arsine*
Asbestos*
Azinphos-Methyl

Barium, Soluble Compounds
Benzene*
Benzidine
Benzoyl Peroxide
Benzyl Chloride*
Beryllium*
Boron Oxide
Boron Trifluoride
Bromine
Bromoform
Butadiene
2-Butanone*
2-Butoxy Ethanol
Butyl Acetate
sec-Butyl Acetate
tert-Butyl Acetate
Butyl Alcohol
sec-Butyl Alcohol
tert-Butyl Alcohol

*Guidelines for these subjects are not included in this edition.

TABLE OF CONTENTS (Continued)

B (Continued)

Butyl Cellusolve
tert-Butyl Chromate as CrO3
n-Butyl Glycidyl Ether*
Butyl Mercaptan*
Butylamine
p-tert-Butyltoluene

C

Cadmium Dust
Cadmium Fume
Calcium Arsenate*
Calcium Oxide
Camphor
Carbaryl (Sevin)®
Carbon Black*
Carbon Dioxide
Carbon Disulfide
Carbon Monoxide
Carbon Tetrachloride
Chlordane
Chlorinated Camphene
Chlorinated Diphenyl Oxide
Chlorine
Chlorine Dioxide
Chlorine Trifluoride
Chloroacetaldehyde
alpha-Chloroacetophenone
Chlorobenzene
o-Chlorobenzylidene Malononitrile
Chlorobromomethane
Chlorodiphenyl, 42% Chlorine
Chlorodiphenyl, 54% Chlorine
Chloroform
bis-Chloromethyl ether*
1-Chloro-1-Nitropropane
Chloropicrin
Chloroprene
Chromic Acid and Chromates
Chromium, Metal and Insoluble Salts
Chromium, Soluble Chromic and Chromous Salts as Cr
Coal Tar Pitch Volatiles
Cobalt, Metal Fume and Dust
Copper Dusts and Mists
Copper Fume
Cotton Dust, Raw*
Crag Herbicide® (Sesone)
Cresol, all Isomers*

TABLE OF CONTENTS (Continued)

C (Continued)

Crotonaldehyde
Cumene
Cyanide as CN
Cyclohexane
Cyclohexanol
Cyclohexanone*
Cyclohexene
Cyclopentadiene

D

2,4-D
DDT*
Decaborane
Demeton® (Systox)
Diacetone Alcohol*
Diazomethane
Diborane
Dibromochloropropane*
Dibutyl Phosphate
Dibutylphthalate
o-Dichlorobenzene
p-Dichlorobenzene
3,3-Dichlorobenzidine*
1,3-Dichloro-5,5-Dimethylhydantoin
1,1-Dichloro-1-Nitroethane
Dichlorodifluoromethane
1,1-Dichloroethane
Dichloroethyl Ether
1,2-Dichloroethylene
Dichloromonofluoromethane
Dichlorotetrafluoroethane
Dichlorvos
Dieldrin*
Diethylamine
Diethylamino Ethanol
Difluorodibromomethane
Diglycidyl Ether*
Diisobutyl Ketone*
Diisopropylamine
Dimethyl Acetamide
4-Dimethylaminoazobenzene*
Dimethyl Formamide
Dimethyl-1,2-Dibromo-2-2-Dichloroethyl Phosphate
Dimethylamine
Dimethylaniline
1,1-Dimethylhydrazine*
Dimethylphthalate
Dimethylsulfate

D (Continued)
Dinitrobenzene, all Isomers
Dinitro-o-Cresol*
Dinitrotoluene
Dioxane
Diphenyl
Dipropylene Glycol Methyl Ether

E
Endrin
Epichlorohydrin
EPN
Ethanolamine
2-Ethoxyethanol
2-Ethoxyethylacetate
Ethyl Acetate
Ethyl Acrylate
Ethyl Benzene
Ethyl Bromide
Ethyl Butyl Ketone
Ethyl Chloride
Ethyl Ether
Ethyl Formate
Ethyl Mercaptan*
Ethyl Silicate
Ethylamine
Ethylene Chlorohydrin
Ethylene Dibromide
Ethylene Dichloride*
Ethylene Glycol Dinitrate and/or Nitroglycerin*
Ethyleneimine*
Ethylene Oxide*
Ethylenediamine
n-Ethylmorpholine

F
Ferbam
Ferrovanadium Dust
Fluoride Dust (as F)
Fluorine
Fluorotrichloromethane
Formaldehyde*
Formic Acid
Furfural
Furfuryl Alcohol*

G
Glycidol
Graphite, Natural

H

Hafnium
Heptachlor
Heptane
Hexachloroethane
Hexachloronaphthalene
Hexane
2-Hexanone*
Hexone*
sec-Hexyl Acetate
Hydrazine*
Hydrogen Bromide
Hydrogen Chloride
Hydrogen Cyanide
Hydrogen Fluoride
Hydrogen Peroxide, 90%
Hydrogen Selenide
Hydrogen Sulfide
Hydroquinone*

I

Iodine
Iron Oxide Fume
Isoamyl Acetate
Isoamyl Alcohol
Isobutyl Acetate
Isobutyl Alcohol
Isophorone*
Isopropyl Acetate
Isopropyl Alcohol
Isopropyl Glycidyl Ether*
Isopropylamine
Isopropylether

J

K

Ketene

L

Lead and Inorganic Lead Compounds*
Lead Arsenate*
Lindane
Lithium Hydride
LPG (Liquefied Petroleum Gas)

M

Magnesium Oxide Fume
Malathion
Maleic Anhydride
Manganese
Mercury
Mesityl Oxide*
Methoxychlor
o-Methylcyclohexanone
Methyl (n-Amyl) Ketone*
5-Methyl-3-Heptanone
Methyl Acetate
Methyl Acetylene
Methyl Acetylene-Propadiene Mixture
Methyl Acrylate
Methyl Alcohol
Methyl Bromide
Methyl Cellosolve
Methyl Cellosolve Acetate
Methyl Chloride
Methyl Chloroform
Methylchloromethyl Ether*
Methyl Formate
Methyl Iodide
Methyl Isobutyl Carbinol
Methyl Isocyanate
Methyl Mercaptan*
Methyl Methacrylate
alpha-Methyl Styrene
Methylal
Methylamine
Methylcyclohexane
Methylcyclohexanol
Methylene Bisphenyl Isocyanate (MDI)
Methylene Chloride
Mica
Molybdenum: Insoluble Compounds
Molybdenum: Soluble Compounds
Monomethyl Aniline
Monomethyl Hydrazine*
Morpholine

N

Naphthalene
Naphtha, Coal Tar
alpha-Naphthylamine*
beta-Naphthylamine*
Nickel Carbonyl
Nickel, Metal and Soluble Compounds as Ni

TABLE OF CONTENTS (Continued)

N (Continued)
Nicotine
Nitric Acid
Nitric Oxide
p-Nitroaniline
Nitrobenzene
p-Nitrochlorobenzene
Nitroethane
Nitrogen Dioxide
Nitrogen Trifluoride
Nitromethane
1-Nitropropane
2-Nitropropane*
n-Nitrosodimethylamine*
Nitrotoluene

O
Octachloronaphthalene
Octane
di-sec-Octyl Phthalate*
Oil Mist, Mineral
Organo (Alkyl) Mercury
Osmium Tetroxide
Oxalic Acid
Oxygen Difluoride
Ozone

P
Paraquat
Parathion
Pentaborane
Pentachloronaphthalene
Pentachlorophenol
Pentane
2-Pentanone*
Perchloromethyl Mercaptan
Perchloryl Fluoride
Petroleum Distillates
Phenol
Phenyl Ether
Phenyl Ether-Biphenyl Vapor Mixture
Phenyl Glycidyl Ether*
p-Phenylene Diamine
Phenylhydrazine*
Phosdrin
Phosgene
Phosphine
Phosphoric Acid
Phosphorus Pentachloride
Phosphorus Pentasulfide

P (Continued)
Phosphorus Trichloride
Phosphorus, Yellow
Phthalic Anhydride
Picric Acid
Pival®
Platinum, Soluble Salts as Pt
Portland Cement
Propane
beta-Propiolacetone*
n-Propyl Acetate
Propyl Alcohol
n-Propyl Nitrate
Propylene Dichloride
Propylene Imine
Propylene Oxide
Pyrethrum
Pyridine

Q
Quinone

R
Rhodium, Metal Fume and Dusts as Rh
Rhodium, Soluble Salts
Ronnel
Rotenone

S
Selenium Compounds as Se
Selenium Hexafluoride
Silica, Amorphous including Natural Diatomaceous Earth
Silica, Crystalline (Quartz)
Silver, Metal and Soluble Compounds
Soapstone
Sodium Fluoroacetate
Sodium Hydroxide
Stibine
Stoddard Solvent
Strychnine
Styrene
Sulfur Dioxide
Sulfur Monochloride
Sulfur Pentafluoride
Sulfuric Acid
Sulfuryl Fluoride

T

2,4,5-T
Talc, Non-asbestos Form
Tantalum
TEDP
Tellurium
Tellurium Hexafluoride
TEPP
Terphenyls
1,1,2,2-Tetrachloro-1,2-Difluoroethane
1,1,1,2-Tetrachloro-2,2-Difluoroethane
1,1,2,2-Tetrachloroethane
Tetrachloroethylene
Tetrachloronaphthalene
Tetraethyl Lead as Pb
Tetrahydrofuran
Tetramethyl Lead as Pb
Tetramethyl Succinonitrile*
Tetranitromethane
Tetryl
Thallium, Soluble Compounds
Thiram®
Tin, Inorganic Compounds
Tin, Organic Compounds
Titanium Dioxide
Toluene
Toluene-2,4-Diisocyanate*
o-Toluidine
Tributyl Phosphate
1,1,2-Trichloroethane
Trichloroethylene*
Trichloronaphthalene
1,2,3-Trichloropropane
1,1,2-Trichloro-1,2,2-Trifluoroethane
Triethylamine
Trifluoromonobromomethane
Trinitrotoluene
Triorthocresyl Phosphate
Triphenyl Phosphate
Turpentine

U

Uranium, Insoluble Compounds
Uranium, Soluble Compounds

V

Vanadium, Pentoxide Dust
Vanadium, Pentoxide Fume
Vinyl Chloride*
Vinyl Toluene

W

Warfarin

X

Xylene
Xylidine

Y

Yttrium

Z

Zinc Chloride Fume
Zinc Oxide Fume
Zirconium Compounds as Zr

Preface

Under the Occupational Safety and Health Act of 1970, NIOSH and OSHA are responsible for ensuring, insofar as possible, that every working man and woman is provided with a safe and healthful working environment.

In 1974, NIOSH and OSHA jointly began to develop a series of complete occupational health standards for substances with existing permissible exposure limits. This project, the Standards Completion Program (SCP), involved several contractors and personnel from NIOSH and OSHA. The resulting substance-specific draft technical standards, with supporting documentation, contain technical information and recommendations to provide a basis for promulgation of new occupational health regulations.

Each draft technical standard was evaluated several times. Peer reviews were conducted by representatives from industry, professional associations, and the NIOSH/OSHA SCP steering committee. These reviews ensured that each document was internally consistent in format and that the technical recommendations reflected the best data available.

SCP data came from a variety of sources. These include recognized textbooks in industrial hygiene, medicine, toxicology, and analytical chemistry, and articles from technical journals. In addition, there were personal communications with representatives of industry and labor, meetings with industry associations, and interviews with individuals knowledgeable about specific industries, operations and processes, and associated occupational health problems. The information collected was organized for convenient use by the SCP Working Groups and resulted in an extensive data base, most of which has been reproduced in these guidelines. The protocol for data collection and evaluation is explained in *The Standards Completion Program Draft Technical Standards Analysis and Decision Logics*, available from the National Technical Information Service, Springfield, Virginia 22161, as publication PB-282 989.

Occupational Health Guidelines for Chemical Hazards is being published to disseminate technical information assembled under the SCP project and the recommendations resulting from that effort. This document is intended primarily for the industrial hygienist and medical surveillance personnel responsible for initiating and maintaining an occupational health program. It may also be used by others, including workers, for obtaining summary information about specific chemical substances found at the worksite. Each guideline includes data on chemical names and synonyms, permissible exposure limits, chemical and physical properties, and signs and symptoms of overexposure, as well as recommendations for environmental and medical monitoring procedures, respiratory and personal protective equipment use, control measures, and procedures for emergency treatment and conditions. These recommendations reflect good industrial hygiene and medical surveillance practices, and their implementation will assist in achieving a sound occupational health program.

Information in these guidelines has been edited and reformatted from the SCP draft technical standards and various working documents used during the development. In some instances, the original draft technical standards have been updated. This is particularly true of those substances for which NIOSH has recommended an occupational health standard under its criteria document program or for which OSHA

has completed rulemaking on a specific chemical. Each substance for which NIOSH has completed a criteria document is listed in Table 1, and identified by a notation in the Permissible Exposure Limit section of the appropriate guideline. The health hazard information in that guideline has been updated to reflect NIOSH's recommendations. For more detailed information, readers may obtain individual criteria documents from: Technical Information Branch, Division of Criteria Documentation and Standards Development, NIOSH, 4676 Columbia Parkway, Cincinnati, Ohio 45226. Where OSHA has completed rulemaking on a chemical, the recommendations in the affected guideline reflect the regulations promulgated since 1972 (listed in Table 2). In some cases pending court action filed at later dates may alter individual regulations.

Every attempt has been made to include all known effects resulting from exposure to the chemicals included in these guidelines and to provide up-to-date recommendations for medical surveillance and industrial hygiene practices. However, information on effects is rapidly changing as a result of recent research or reviews of the literature more indepth than those in the Standards Completion Program. This is particularly true for chronic effects, especially carcinogenic effects and some chemicals have only recently been shown or considered prime candidates to be carcinogenic. To assist in identifying these chemicals several sources that have reviewed their carcinogenic potential in more depth have been consulted.

These sources of information were: OSHA's "List of Substances Which May be Candidates of Further Scientific Review and Possible Identificaion, Classification, and Regulation as Potential Carcinogens," the "Candidate List" published in the *Federal Register*, August 12, 1980; evidence of carcinogenic effects of chemicals, received by the Environmental Protection Agency (EPA) under section 8(e) of the Toxic Substances Control Act; the EPA's Carcinogen Assessment Group's (CAG) List of Carcinogens, July 14, 1980; and the Monographs of the International Agency for Research on Cancer (IARC), Volumes 1-23, 1972-1980. When a chemical appeared in one or more of these information sources, a "Special Note" is included in the guideline to identify the source. Since the EPA CAG list has been included as part of the OSHA "Candidate List," it can be assumed that those chemicals with a reference to the OSHA "Candidate List" are also of concern to EPA. For IARC notations, only those substances listed in the NIOSH Registry of Toxic Effects of Chemical Substances as positive for humans or animals or as suspect carcinogens are included. Where the guidelines refer to several chemicals as one designation (e.g., chromium compounds), the notation indicates that evidence of carcinogenicity exists for at least one of the substances. Where readers are aware of information that would assist in further evaluation of the toxicity of these chemicals they are urged to provide us with the data so that it may be considered for inclusion in future updates of these guidelines. In this regard, NIOSH is initiating a project to systematically review and update the guidelines published and to add new subjects to the list.

Because some SCP information requires updating before it can be published, approximately 100 subjects having OSHA regulations are not included in this volume of the guidelines. These subjects are identified by an asterisk after the chemical name in the Table of Contents. Guidelines for these are being revised and will be issued as supplements at a later date.

Although every effort is made to prepare each guideline as accurately as possible, errors can and do occur. Readers are requested to use the enclosed reader response card to notify the editor of errors so they can be corrected in future editions.

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Acetylene	July 1, 1976	2,500-ppm (10% of lower explosive limit)	No exposure in excess of 2,500-ppm (2,662 mg/cu m)	Indirect asphyxia	Employers to check for, and inform employees of contaminants such as arsine and phosphine
Acrylamide	October 21, 1976	0.3 mg/cu m, 8-hr TWA (skin)	0.3 mg/cu m TWA	Skin,eye, nervous system effects	Skin and eye contact to be prevented

*Table 1 provides a summary of the major environmental and medical recommendations found in the criteria documents published by the National Institute for Occupational Safety and Health (NIOSH). The intent of the table is to provide, in rapid-reference form, the recommendations as well as the current Federal standard and the date of transmittal to the Department of Labor of each document. In addition, the significant health effect or effects that were considered in the derivation of the recommendations is presented. Other information that may be pertinent to the substance or hazard is included under comments.

It should be noted that no attempt is made to provide all those details necessary for a complete understanding of the documents in the table. Reference to the full criteria document is recommended for those wishing to have further elements of the recommended standard such as work practices and sampling and analytic methods. These elements are also summarized in the occupational health guidelines for invididual chemicals.

Copies of Criteria Documents can be obtained from:

Technical Information Branch
NIOSH
4676 Columbia Parkway
Cincinnati, Ohio 45226

**NIOSH TWA recommendations based on up to a 10-hr exposure unless otherwise noted.

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Acrylonitrile	September 28, 1977	2-ppm, 8-hr TWA; 10-ppm ceiling (15-minute)(skin)	Not greater than 4-ppm by recommended method (8.7 mg/cu m)	Lung and bowel cancer	Chest x-ray required. First aid and medical kits to be available during use. Hazardous liquid, skin. Federal standard promulgated October 3, 1978
Aldrin/Dieldrin (Special Hazard Review)	September 7, 1978	0.25 mg/cu m, 8-hr TWA (skin)	Lowest reliably detectable level; 0.15 mg/cu m TWA by NIOSH validated method. Skin contact to be prevented	Cancer	
Alkanes (C5-C8)	March 29, 1977	1000-ppm, 8-hr TWA, pentane; 500-ppm, 8-hr TWA, n-hexane, n-heptane, octane	350 mg/cu m TWA (approx. 120-ppm pentane; 100-ppm hexane; 85-ppm heptane; 75-ppm octane) Mixtures to be not greater than 350 mg/cu m TWA; 1800 mg/cu m ceiling singly or mixtures (15-minute)	Skin and nervous system effects	Action level defined as 200 mg/cu m for these substances
Allyl chloride	September 21, 1976	1-ppm, 8-hr TWA	1-ppm TWA (3.1 mg/cu m); 3-ppm ceiling (9.3 mg/cu m) (15-minute)	Liver, kidney, lung effects	Urine, blood, and pulmonary function testing required

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Ammonia	July 15, 1974	50-ppm; 8-hr TWA	50-ppm ceiling (34.8 mg/cu m) (5-minute)	Airway irritation	Hazardous liquid eye damage
Antimony	September 28, 1978	0.5 mg/cu m, 8-hr TWA	0.5 mg/cu m TWA	Irritation; heart and lung effects	Chest x-ray, pulmonary function, and electrocardiogram testing required
Arsenic inorganic	January 21, 1974 Revised June 23, 1975	10 µg/cu m, 8-hr TWA	2 µg As/cu m ceiling (15-minute)	Dermatitis, lung and lymphatic cancer	Chest X-rays required. Federal standard promulgated May 5, 1978
Asbestos	January 21, 1972 Revised December 15, 1976	2,000,000 fibers/cu m 8-hr TWA 10,000,000 fibers/cu m ceiling	100,000 fibers/cu m over 5 microns TWA; 500,000 fibers/cu m over 5 microns ceiling; (15-minute)	Asbestosis, lung cancer	Federal standard promulgated July 7, 1972; TWA lowered July 1, 1976
Asphalt fumes	September 27, 1977	2.5 mg/cu m	5 mg/cu m ceiling (15-minute)	Eye and respiratory irritation	Hazardous substance, skin
Benzene	July 24, 1974 Revised July 25, 1977 ***	1-ppm, 8-hr TWA; 5-ppm ceiling (15-minute)(skin)	1-ppm ceiling (3.2 mg/cu m) (60-minute)	Blood changes including leukemia	Blood testing required. Federal standard promulgated February 10, 1978

***Recommendation revised as a part of NIOSH testimony at OSHA hearing

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Benzidine-Based Dyes (Special Hazard Review)	November 16, 1979	Not controlled as such	Stringent work practices and controls; replacement with less toxic materials	Cancer	Urinary monitoring suggested
Benzoyl peroxide	June 7, 1977	5 mg/cu m, 8-hr TWA	5 mg/cu m TWA	Airway and eye irritation, skin effects	
Benzyl chloride	August 22, 1978	1-ppm (5 mg/cu m) 8-hr TWA	5 mg/cu m ceiling (15-minute)	Irritation; skin and eye effects	Chest x-ray and pulmonary function testing required
Beryllium	June 30, 1972 Revised August 19, 1977	2 µg/cu m, 8-hr TWA 5 µg/cu m acceptable ceiling; 25 µg/cu m maximum ceiling (30-minute)	0.5 µg/cu m (130-minute)	Lung cancer	Pulmonary function chest x-ray, and sputum cytology required
Boron Trifluoride	December 15, 1976	1-ppm Ceiling	None recommended	Respiratory system effects	Adequate procedures for sampling and analysis not available; pulmonary function testing required

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Cadmium	August 23, 1976	0.1 mg/cu m, 8-hr TWA; 0.3 mg/cu m ceiling (fume; erroneously published as 3 mg/cu m) 0.2 mg/cu m, 8-hr TWA; 0.6 mg/cu m ceiling (dust)	40 µg/ cd/cu m TWA; 200 µg cd/cu m ceiling (15-minute)	Lung and kidney effects	Urine and pulmonary function testing required
Carbaryl	September 30, 1976	5 mg/cu m, 8-hr TWA	5 mg/cu m TWA	Nervous and reproductive system effects	Medical warnings of possible effects on reproductive system and minimum exposure during pregnancy required; skin and eye contact to be prevented
Carbon black	September 7, 1978	3.5 mg/cu m, 8-hr TWA	3.5 mg/cu m TWA; 0.1 mg/cu m TWA in presence of polycyclic aromatic hydrocarbons	Lung, heart, and skin effects; cancer	Chest x-rays, pulmonary function testing, ECG, and sputum cytology required
Carbon dioxide	August 11, 1976	5,000-ppm, 8-hr TWA	10,000-ppm TWA (18,000 mg/cu m) 30,000-ppm ceiling (54,000 mg/cu m) (10-minute)	Respiratory effects	

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Carbon disulfide	May 4, 1977	20-ppm, 8-hr TWA; 30-ppm acceptable ceiling; 100-ppm maximum ceiling	1-ppm TWA (3 mg/cu m); 10-ppm ceiling (30 mg/cu m) (15-minute)	Heart, nervous and reproductive system effects	Employees to be advised of potential effects on reproductive system
Carbon monoxide	August 3, 1972	50-ppm, 8-hr TWA	35-ppm TWA (40 mg/cu m); 200-ppm ceiling (229 mg/cu m)	Heart effects	
Carbon tetrachloride	December 22, 1975 Revised June 9, 1976	10-ppm, 8-hr TWA 25-ppm acceptable ceiling; 200-ppm maximum ceiling (5-minute in 4 hours)	2-ppm ceiling (12.6 mg/cu m) (60-minute)	Liver cancer	
Chlorine	May 25, 1976	1-ppm, 8-hr TWA	0.5-ppm ceiling (1.45 mg/cu m) (15-minute)	Eye/airway irritation	Chest x-rays required
Chloroform	September 11, 1974 Revised June 9, 1976	50-ppm ceiling	2-ppm ceiling (9.78 mg/cu m) (60-minute)	Liver or kidney tumors and central nervous system effects	Current federal standard should be TWA: published as "C" in error

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Chloroprene	August 12, 1977	25-ppm, 8-hr TWA	1-ppm ceiling (3.6 mg/cu m) (15-minute)	Reproductive effects; potential for cancer	Chest x-ray and pulmonary function testing required; medical warnings to workers concerning reproductive effects in animals; pregnant workers to be counseled about continuing work with chloroprene
Chromic acid	July 17, 1973	1 mg/10 cu m ceiling	0.05 mg CrO3/cu mTWA 0.1 mg CrO3/cu m ceiling (15-minute)	Nasal ulceration	
Chromium (VI)	December 1, 1975	100 µg/cu m ceiling	1 µg/cu m for carcinogenic Cr (VI); 25 µg/cu m TWA for other Cr(VI); 50 µg/cu m ceiling (15-minute)	Lung cancer, skin ulcers, lung irritation	Employer must demonstrate absence of carcinogenic Cr(VI); X-ray required
Chrysene (Special Hazard Review)	June 2, 1978	None	To be controlled as an occupational carcinogen	Cancer	Control recommendations also included for polycyclic aromatic hydrocarbons

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Coal Gasification Plants	September 7, 1978	Existing Federal occupational exposure limits or NIOSH recommended limits for specific hazards to be enforced		Various effects depending on substances present. Carcinogenic potential	Extensive work practice and Control procedures recommended. Document limited to those technologies most likely to be operational in the U.S.
Coal tar products	September 27, 1977	None	0.1 mg/cu m TWA, (cyclohexane-extractable fraction)	Lung and skin cancer	Includes coal tar, creosote, and coal tar pitch. Pulmonary function testing, chest x-rays, and sputum cytology required
Coke oven emissions	February 28, 1973	150 µg/cu m, 8-hr TWA	Work practices to minimize exposure to emissions	Lung cancer	Sputum cytology and chest X-ray required. Federal standard promulgated Oct. 22, 1976
Working in Confined Spaces	January 2, 1980	Numerous sections under 29 CFR 1910 (General Industry Safety and Health Standards)	Various recommendations including a permit-entry system to prevent worker injury and death	Injury and death	

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Cotton dust	September 26, 1974	200 µg/cu m, 8-hr TWA (yarn manufacturing); 750 µg/cu m, 8-hr TWA (slashing and weaving operations); 500 µg/cu m, 8-hr TWA (all other operations)	200 µg/cu m lint-free cotton dust	Pulmonary disease (byssinosis)	Pulmonary function testing required. Federal standard promulgated June 23, 1978
Cresol	February 28, 1978	22 mg/cu m 8-hr TWA "skin"	10 mg/cu m TWA	Skin, liver, kidney, and pancreas effects	Applies to mixtures of cresols and cresylic acid. Hazardous substance, skin and eyes. Possible delayed effects
Cyanide, hydrogen and cyanide salts	October 4, 1976	10-ppm, 8-hr TWA (alkali cyanides) cyanide 5 mg CN/ cu m (skin)	5 mg CN/cu m ceiling (4.7-ppm) (10-minute)	Thyroid, blood, respiratory system effects	Concurrent measurment required for HCN when measuring for cyanide salt; trained first-aid personnel and first-aid kits to be available during use. Hazardous liquid, skin and eye

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
DDT (Special Hazard Review)	September 7, 1978	1 mg/cu m, 8-hr TWA (skin)	Lowest reliably detectable level; 0.5 mg/cu m TWA by NIOSH validated method. Skin contact to be avoided	Cancer	
Decomposition products of fluorocarbon	September 26, 1977	None	None recommended	Lung effects, polymer fume fever	Workroom air to be monitored for inorganic fluorides and hydrogen fluoride
Dibromochloro-propane	September 2, 1977	1-ppb, 8-hr TWA; Eye and skin contact to be avoided	10-ppb ceiling (0.1 mg/cu m) (30-minute)	Sterility; renal and liver effects	Medical warnings to workers of reproductive system abnormalities including sterility, and notice of findings of cancer in animals following direct gastric application. Federal standard promulgated March 17, 1978

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Diisocyanates	September 27, 1978	0.02-ppm (0.14 mg/cu m) ceiling (TDI); 0.02-ppm (0.2 mg/cu m) ceiling (MDI)	ALL VALUES ARE IN (µg/cu m) toluene diisocyanate (TDI): 35 TWA, 140 ceiling; diphenylmethane diisocyanate (MDI): 50 TWA, 200 ceiling; hexamethylene diisocyanate (HDI): 35 TWA, 140 ceiling; napthalene diisocyanate (NDI): 40 TWA, 170 ceiling; isophorene diisocyanate (IPDI): 45 TWA, 180 ceiling; dicyclohexylmethane 4,4'-diisocyanate (hydrogenated MDI): 55 TWA, 210 ceiling; Other diisocyanates to be controlled to 20-ppb ceiling and 5-ppb TWA	Respiratory effects and sensitization; irritation	Chest x-ray and pulmonary function testing required
Dinitro-ortho-cresol	February 28, 1978	0.1 mg/cu m 8-hr TWA "skin"	0.2 mg/cu m TWA	CNS and metabolic effects	Blood and urine monitoring required. Hazardous substance, skin and eyes. Possible delayed effects

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Dioxane	September 1, 1977	100-ppm, 8-hr TWA (skin)	1-ppm ceiling (3.6 mg/cu m) (30-minute)	Liver and kidney effects; cancer	Blood and urine testing required; hazardous liquid, skin
Emergency Egress from Elevated Workstations	December 1, 1975	Sections under Subpart E, General Industry standards and Subpart R, 29 CFR 1910.261	Various recommendations concerning means and availability of egress from high and low hazard situations	Trauma and injury	
Epichlorohydrin	September 17, 1976	5-ppm, 8-hr TWA (20 mg/cu m)	2 mg/cu m TWA; 19 mg/cu m ceiling (15-minute)	Skin, kidney, liver, and respiratory system effects	Medical warning infertility effects required; hazardous liquid, skin
Ethylene dibromide	August 25, 1977	20-ppm, 8-hr TWA; 30-ppm acceptable ceiling; 50-ppm maximum peak (5-minute)	1 mg/cu m ceiling (0.13-ppm) (15-minute)	Damage to skin, eyes, heart, liver, spleen, respiratory and central nervous systems. Potential for cancer and mutagenesis	Medical warnings to workers of potential reproductive abnormalities and cancer following direct administration in animals; hazardous liquid, contact to be prevented

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Ethylene dichloride	March 9, 1976 Revised September 29, 1978 (Special Hazard Review)	50-ppm, 8-hr TWA; 100-ppm acceptable ceiling; 200-ppm maximum ceiling (5-minutes in 3 hours)	1 ppm TWA (4 mg/cu m); 2-ppm ceiling (2 mg/cu m) (15-minute)	Cancer; nervous system, respiratory, heart and liver effects	Nursing infants at risk
Ethylene oxide (Special Hazard Review)	September 9, 1977	90 mg/cu m (50-ppm), 8-hr TWA	90 mg/cu m (50-ppm) TWA; 135 mg/cu m (75-ppm) ceiling (15-minute)	Mutagenesis; cancer	Recommendations for blood monitoring and medical counseling concerning mutations found in animal tests
Ethylene thiourea (Special Hazard Review)	October 13, 1978	None	Use of encapsulated form in industry; Worker exposure to be minimized	Carcinogenesis and teratogenesis	Workers to be informed of carcinogenic and teratogenic hazards. Special attention to be given to thyroid function tests
Fibrous glass	April 15, 1977	15 mg/cu m total dust; 5 mg/cu m respirable fraction (nuisance dust)	3,000,000 fibers/cu m TWA (fibers & 3.5 microns diameter and & 10 microns length); 5 mg/cu m TWA (total fibrous glass)	Eye, skin and airway effects	NIOSH recommends this limit also apply to other man-made fibers
Fluorides, inorganic	June 30, 1975	2.5 mg/cu m, 8-hr TWA	2.5 mg F/cu m TWA	Kidney and bone effects	Urine monitoring required

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Formaldehyde	December 30, 1976	3-ppm, 8-hr TWA; 5-ppm acceptable ceiling; 10-ppm maximum ceiling (30-minute)	1.2 mg/cu m ceiling (1-ppm) (30-minute)	Irritation, lung effects	Hazardous liquid, skin
Furfuryl Alcohol	March 1, 1979	50-ppm, 8-hr TWA	50-ppm (200 mg/cu m) TWA	Respiratory System Effects	
Glycidyl ethers	June 30, 1978	45 mg/cu m, ceiling (Allylglycidyl ether); 270 mg/cu m, 8-hr TWA (n-butyl glycidyl ether); 2.8 mg/cu m, 8-hr TWA (di2,3-epoxypropyl ether); 240 mg/cu m 8-hr TWA (isopropyl glycidyl ether); 60 mg/cu m 8-hr TWA, (phenyl glycidyl ether)	45 mg/cu m (AGE); 30 mg/cu m (BGE); 1 mg/cu m (DGE); 240 mg/cu m (IGE); 5 mg/cu m (PGE); all ceiling values (15-minute)	Skin, mucous membrane effects, sensitization potential. Tumorigenesis and mutagenesis	Possible additive effects with mixtures
Hot Environments	June 30, 1972	None	Action Levels: 79 degrees F WBGT (men) 76 degrees F WBGT (women); sliding scale limits for unimpaired mental performance	Heat Illnesses	Factors recommended include acclimatization, work practices, and employee protection

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Hydrazines	June 30, 1978	1.3 mg/cu m(hydrazine), 1.0 mg/cu m (1,1-dimethyl-hydrazine), 22 mg/cu m (phenyl-hydrazine) as 8-hr TWA values; 0.35 mg/cu m ceiling (methyl-hydrazine)	0.04 mg/cu m (hydrazine), 0.15 mg/cu m (1,1-dimethyl-hydrazine), 0.6 mg/cu m (phenyl-hydrazine), 0.08 mg/cu m (methyl-hydrazine). All as ceiling values (120-minute)	Liver, blood, eye, skin effects; cancer	Blood and urine monitoring, chest x-ray required. Bowel examination required for some workers
Hydrogen fluoride	March 9, 1976	3-ppm, 8-hr TWA	2.5 mg F/cu m TWA (approx. 6-ppm); 5.0 mg/cu m ceiling (approx. 12-ppm) (15-minute, fluoride ion)	Skin/eye/airway irritation; bone effects	Pelvic x-ray (male) and urine testing required
Hydrogen sulfide	May 4, 1977	20-ppm acceptable ceiling; 50-ppm maximum ceiling (10-minute)	15 mg/cu m ceiling (approx. 10-ppm) (10-minute)	Irritation; severe acute effects, nervous and respiratory systems	Continuous monitoring required if potential exists for exposure to 70 mg/cu m or greater; evacuation required at this level
Hydroquinone	April 21, 1978	2 mg/cu m, 8-hr TWA	2 mg/cu m ceiling (15-minute)	Eye and skin effects	Special provisions for darkroom use

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Identification System for Occupationally Hazardous Materials	December 20, 1974	Not Applicable	Components of a complete system for hazardous materials		Includes definition, safety data sheets, alert symbols, and label statements
Isopropyl alcohol	March 9, 1976	400-ppm, 8-hr TWA	400-ppm TWA, (984 mg/cu m); 800-ppm ceiling (1968 mg/cu m) (15-minute)	Mucous membrane irritation; possible cancer threat in manufacturing process	More stringent work practices and medical surveillance for manufacturing workers
Kepone	January 27, 1976	None	1 µg/cu m ceiling (15-minute)	Nervous system effects; liver cancer	Liver function testing required

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Ketones	June 30, 1978	Acetone 2,400 mg/cu m	590 mg/cu m TWA	Irritation; liver, kidney and nervous system effects	Urinalysis required. Warning of nervous system effects in workers exposed to methyl n-butyl ketone
		Methyl ethyl Ketone 590 mg/cu m	590 mg/cu m TWA		
		Methyl n-propyl Ketone 700 mg/cu m	530 mg/cu m TWA		
		Methyl n-butyl Ketone 410 mg/cu m	4 mg/cu m TWA		
		Methyl n-amyl Ketone 465 mg/cu m	465 mg/cu m TWA		
		Methyl isobutyl Ketone 410 mg/cu m	200 mg/cu m TWA		
		Methyl isoamyl Ketone None	230 mg/cu m TWA		
		Diisobutyl Ketone 290 mg/cu m	140 mg/cu m TWA		
		Cyclohexanone 200 mg/cu m	100 mg/cu m TWA		
		Mesityl oxide 100 mg/cu m	40 mg/cu m TWA		
		Diacetone alcohol 240 mg/cu m	240 mg/cu m TWA		
		Isophorone 140 mg/cu m	23 mg/cu m TWA		
		ALL VALUES 8-hr TWA			

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Lead, inorganic	January 5, 1973	50 µg/cu m, 8-hr TWA;	Less than 100 µg/cu m	Kidney, blood, and nervous system effects	Air level to be maintained so that worker blood lead remains at or below 0.060 mg/100g; blood monitoring required. Federal standard promulgated November 14, 1978
	March, 1977***	Over 8-hr. exposure to be determined by formula		Nervous system effects	
Logging-From felling to first haul	July 1, 1976	Not Applicable	Extensive work practice and personal protection recommendations	Primarily trauma and falls	Immunization and first-aid programs to be instituted
Malathion	July 1, 1976	15 mg/cu m, 8-hr TWA	15 mg/cu m TWA	Nervous system effects	Skin contact to be prevented; blood monitoring required
Mercury, inorganic	January 5, 1973	0.1 mg/cu m ceiling	0.05 mg/cu m TWA	Central nervous system and mental effects	

***Recommendation revised as a part of NIOSH testimony at OSHA hearing

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Methyl alcohol	March 22, 1976	200-ppm TWA	200-ppm TWA (262 mg/cu m); 800-ppm ceiling (1048 mg/cu m) (15-minute)	Blindness; metabolic acidosis	
4,4'-Methylene-bis(2-Chloro-aniline) (Special Hazard Review)	September 7, 1978	None - standard remanded by court	3 µg/cu m TWA; Skin contact to be avoided	Cancer	Chest x-ray, blood and urine testing required
Methyl parathion	September 30, 1976	None	0.2 mg/cu m TWA	Nervous system effects	Skin contact to be prevented; blood monitoring required
Methylene chloride	March 9, 1976	500-ppm, 8-hr TWA; 1000-ppm acceptable ceiling; 2000-ppm maximum (5-minutes in 2 hours)	75-ppm TWA (261 mg/cu m); 500-ppm ceiling (1740 mg/cu m) to be lowered in presence of carbon monoxide	Central nervous system effects; carbon monoxide toxicity	Blood monitoring required
Nickel carbonyl (Special Hazard Review)	May 27, 1977	7 µg/cu m (1-ppb), 8-hr TWA	7 µg/cu m (1-ppb) TWA	Cancer	Recommendations for chest x-ray, pulmonary function, and urine monitoring
Nickel, inorganic and compounds	May 13, 1977	1 mg/cu m, 8-hr TWA	15 µg Ni/cu m TWA	Skin effects; lung and nasal cancer	Chest x-ray and pulmonary function testing required

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Nitric acid	March 9, 1976	2-ppm, 8-hr TWA	2-ppm TWA (5 mg/cu m)	Dental erosion, nasal/lung irritation	Hazardous liquid, eyes and skin. Chest x-ray required
Nitriles	September 27, 1978	70 mg/cu m (40-ppm), 8-hr TWA (acetonitrile); 3 mg/cu m (0.5-ppm), 8-hr TWA, "skin" (tetramethyl-succinonitrile)	To be TWA values: acetonitrile: 34 mg/cu m,(20-ppm); n-butyronitrile: 22 mg/cu m,(8-ppm); isobutyronitrile: 22 mg/cu m,(8-ppm); propionitrile: 14 mg/cu m,(6-ppm); malononitrile: 8 mg/cu m,(3-ppm); adiponitrile: 18 mg/cu m,(4-ppm); succinonitrile: 20 mg/cu m,(6-ppm) To be ceiling values (15-minute): acetone cyanohydrin: 4 mg/cu m,(1-ppm); glycolonitrile: 5 mg/cu m,(2-ppm); tetramethyl succinonitrile: 6 mg/cu m,(1-ppm) When present as mixtures or with other sources of cyanide, exposure to be considered	Hepatic, renal, respiratory, cardiovascular, gastrointestinal and nervous system effects	Chest x-ray and pulmonary function testing required. Trained personnel and first-aid kits to be available during use. Hazardous substances, skin and eyes

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
			additive and environmental limit to be calculated		
Nitrogen, Oxides	March 22, 1976	NO2: 5-ppm,8-hr TWA	NO2: 1-ppm (1.8 mg/cu m) ceiling (15-minute)	Airway effects	Pulmonary function testing required
		NO: 25-ppm, 8-hr TWA	NO: 25-ppm TWA (30 mg/cu m)	Blood effects	
Nitroglycerin: Ethylene Glycol Dinitrate	June 30, 1978	2 mg/cu m (skin) 8-hr TWA (nitroglycerin); 1 mg/cu m (skin) ceiling, (EDGN)	0.1 mg/cu m ceiling (20-minute)	Circulatory system effects	Skin contact to be prevented; recommended limit for either substance alone or mixtures
Noise	August 10, 1972	90 dBA, 8-hr TWA	85 dBA TWA; 115 dBA ceiling	Hearing damage	
Organotin compounds	November 12, 1976	0.1 mg tin/cu m 8-hr TWA	0.1 mg tin/cu m TWA	Eye, skin, liver, nervous system, and heart effects	Chest X-ray, blood and urine monitoring, eye tests, heart examination, and nervous system testing required liquid, skin and eyes

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Parathion	June 30, 1976	0.11 mg/cu m TWA	0.05 mg/cu m TWA	Nervous system effects	Skin contact to be prevented; blood monitoring required
Pesticide Manufacturing and Formulation	July 17, 1978	Current OSHA or previously recommended NIOSH levels to be followed. Stringent workpractice and medical surveillance requirements to be instituted. Pesticides considered in 3 groups based on toxicity. Skin contact to be prevented.		Wide range of toxicities considered. Nervous and reproductive system effects. Cancer	Blood monitoring required for some groups. Medical warning of reproductive system effects in some compounds.
Phenol	June 30, 1976	5-ppm, 8-hr TWA (skin)	20 mg/cu m TWA (5.2 ppm); 60 mg/cu m ceiling (15.6 ppm) (15-minute)	Skin, eye, CNS, liver, and kidney effects	Hazardous substance, skin and eyes
Phosgene	February 23, 1976	0.1-ppm, 8-hr TWA	0.1-ppm TWA (0.4 mg/cu m); 0.2-ppm ceiling (0.8 mg/cu m) (15-minute)	Airway effects	Pulmonary function testing and x-ray required
Polychlorinated Biphenyls	September 27, 1977	1 mg/cu m, 8-hr TWA (42% chlorine); 0.5 mg/cu m, 8-hr TWA (54% chlorine)	1 µg/cu m TWA	Cancer; skin, liver, and reproductive effects	Blood testing required. Medical warning of adverse effects to be given to women workers of childbearing age and nursing mothers

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Refined Petroleum Solvent	July 19, 1977	500-ppm, 8-hr TWA (2950 mg/cu m) (stoddard solvents)	350 mg/cu m TWA; 1800 mg/cu m ceiling (15-minute)	Skin, lung, and nerve irritation	Blood and urine monitoring required. Action level for petroleum ether, rubber solvent, naptha to be 200 mg/cu m TWA; action level for mineral spirits and Stoddard solvent to be 350 mg/cu m TWA; action level for kerosene to be 100 mg/cu m TWA. Hazardous substance skin
Silica, crystalline	November 11, 1974	250/%SiO + 5 in mppcf, or 10 mg/cu m/%SiO+2 (respirable quartz)	50 µg/cu m TWA, respirable free silica	Chronic lung disease (Silicosis)	X-ray, pulmonary function testing required
Sodium hydroxide	September 16, 1975	2 mg/cu m, 8-hr TWA	2 mg/cu m ceiling (15-minute)	Airway irritation	Hazardous liquid, eyes and skin
Sulfur dioxide	February 11, 1974 Revised May 12, 1977 ***	5-ppm, 8-hr TWA	0.5-ppm TWA (1.3 mg/cu m)	Respiratory effects	Pulmonary function testing required
Sulfuric acid	June 6, 1974	1 mg/cu m, 8-hr TWA	1 mg/cu m TWA	Pulmonary irritation	Hazardous liquid, eye and skin

***Recommendation revised as a part of NIOSH testimony at OSHA hearing

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
1,1,2,2-Tetrachloroethane	December 17, 1976	5-ppm; 8-hr TWA (skin)	1-ppm TWA (6.87 mg/cu m)	Liver, gastrointestinal, and nervous system effects	Skin contact to be prevented. Blood monitoring required
Tetrachloroethylene	July 2, 1976	100-ppm, 8-hr TWA; 200-ppm acceptable maximum ceiling; 300-ppm maximum ceiling (5-minutes in 3 hours)	50-ppm TWA (339 mg/cu m); 100-ppm ceiling (678 mg/cu m) (15-minute)	Nervous system, heart, respiratory, liver effects	Medical warning of possible congenital abnormalities required
Thiols: n-alkane mono,cyclohexane, and benzene	September 26, 1978	10-ppm, 8-hr TWA (butylmercaptan); 10-ppm ceiling (methyl and ethyl mercaptan)	Ceilings 15-minute: benzenethiol: 0.5 mg/cu m,(0.1-ppm); 1-methanethiol: 1.0 mg/cu m,(0.5-ppm); 1-ethanethiol: 1.3 mg/cu m,(0.5-ppm); 1-propanethiol: 1.6 mg/cu m,(0.5-ppm); 1-butanethiol: 1.8 mg/cu m,(0.5-ppm); 1-pentanethiol: 2.1 mg/cu m,(0.5-ppm); 1-hexanethiol: 2.4 mg/cu m,(0.5-ppm); 1-heptanethiol: 2.7 mg/cu m,(0.5-ppm); 1-octanethiol: 3.0 mg/cu m,(0.5-ppm); 1-nonanethiol: 3.3 mg/cu m,(0.5-ppm); 1-decanethiol: 3.6 mg/cu m,(0.5-ppm); 1-undecanethiol:	Irritation, eye, skin, blood, and nervous system effects	Hazardous substance, skin. Blood and urine monitoring required

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
			3.9 mg/cu m,(0.5-ppm); 1-dodecanethiol: 4.1 mg/cu m,(0.5-ppm); 1-hexadecanethiol: 5.3 mg/cu m,(0.5-ppm); 1-octadecanethiol: 5.9 mg/cu m,(0.5-ppm); cyclohexanethiol: 2.4 mg/cu m,(0.5-ppm); Mixtures of thiols to be controlled by calculation of equivalent concentrations		
o-Tolidine	August 11, 1978	None	20 µg/cu m ceiling Skin contact to be prevented	Nasal irritation; cancer	Urine testing required; quarterly urine monitoring recommended
Toluene	July 23, 1973	200-ppm, 8-hr TWA; 300-ppm acceptable ceiling; 500-ppm maximum ceiling (10-minute)	100-ppm TWA (375 mg/cu m); 200-ppm ceiling (750 mg/cu m) (10-minute)	Central nervous system depressant	
Toluene diisocyanate	July 13, 1973 Revised September 27, 1978	0.02-ppm ceiling	0.005-ppm TWA (0.035 mg/cu m); 0.02-ppm ceiling (0.14 mg/cu m) (20-minute)	Airway effects	Chest x-rays blood tests, pulmonary function testing required. Recommendations revised - See Diisocyanates

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
1,1,1,-Trichloroethane	July 2, 1976	350-ppm, 8-hr TWA	350-ppm ceiling (1910 mg/cu m) (15-minute)	Nervous system, liver, and heart effects	Action level set at 200-ppm TWA; medical warning of possible congenital abnormalities required
Trichloroethylene	July 23, 1973 Revised February 28, 1978 (Special Hazard Review)	100-ppm, 8-hr TWA; 200-ppm acceptable ceiling; 300-ppm maximum ceiling (5-minute in any 2 hours)	25-ppm (134 mg/cu m) TWA	Central nervous system depressant; cancer	Workers to be warned of hazards
Tungsten and cemented tungsten carbide	September 26, 1977	None	Insoluble tungsten: 5 mg/cu m TWA; soluble tungsten: 1 mg/cu m TWA; Dust of cemented tungsten carbide (& 2% cobalt): 0.1 mg cobalt/cu m TWA: Dust of cemented Tungsten carbide (& 0.3% nickel): 15 micrograms nickel/ cu m TWA	Lung and skin effects	Pulmonary function testing and chest x-ray required
Ultraviolet radiation	December 20, 1972	10 mW/cm averaged over any 1-hr period	1.0 mW/cm for over 1000 sec.; 100 mW sec/cm for periods under 1000 sec.	Skin and eye effects	

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Vanadium	August 23, 1977	Vanadium pentoxide (dust): 0.5 mg/cu m ceiling; (fume) 0.1 mg/cu m ceiling Ferrovanadium: 1 mg/cu m, 8-hr TWA	Vanadium compounds: 0.05 mg/cu m ceiling (15-minute); metallic vanadium and vanadium carbide: 1 mg/cu m TWA	Eye, skin, and lung effects	Pulmonary function testing and chest x-ray required
Vinyl acetate	September 7, 1978	None	15 mg/cu m (4-ppm) ceiling (15-minute)	Irritation	
Vinyl chloride	March 11, 1974	1-ppm, 8-hr TWA; 5-ppm ceiling, (15-minute sample)	Minimum detectable level; 1-ppm ceiling (2.55 mg/cu m) (15-minute)	Liver cancer	Standard promulgated October 4, 1974 liver function testing required
Vinyl halides	September 12, 1978	1-ppm, 8-hr TWA; 5-ppm ceiling (15-minute)	As promulgated for vinyl chloride in 29 CFR 1910.1017 with eventual goal of zero exposure	Cancer	Document includes vinyl chloride, vinylidene chloride, vinyl bromide, vinyl fluoride, and vinylidene fluoride monomers
Waste anesthetic gases and vapors	March 4, 1977	None for substances when used as anesthetic agents	2-ppm ceiling (halogenated anesthetic agents) (1-hour); 25-PPM TWA during periods of use (nitrous oxide)	Reproductive effects and audiovisual performance decrements	Employees to be advised of potential effects; abnormal outcome of pregnancies of employees and spouse to be documented

Table 1
SUMMARY OF NIOSH RECOMMENDATIONS FOR OCCUPATIONAL HEALTH STANDARDS, January 1981

Substance	Transmitted to OSHA	Current OSHA Environmental Standard	NIOSH Recommendation for Environmental Exposure Limit**	Health Effect Considered	Comments
Xylene	May 23, 1975	100-ppm, 8-hr TWA	100-ppm TWA (434 mg/cu m); 200-ppm ceiling (868 mg/cu m) (10-minute)	Central nervous system depressant; airway irritation	
Zinc oxide	October 10, 1975	5 mg/cu m, 8-hr TWA	5 mg/cu m TWA, 15 mg/cu m ceiling (15-minute)	Metal fume fever	

TABLE 2
CHEMICAL SUBJECTS FOR WHICH OSHA HAS COMPLETED RULEMAKING 1972-1980

Chemical	Publication Date	29CFR Section
2-Acetylaminofluorene	June 1974	1910.1014
Acrylonitrile	October 1978	1910.1045
alpha-Naphthylamine	June 1974	1910.1004
4-Aminodiphenyl	June 1974	1910.1011
Arsenic	May 1978	1910.1018
Asbestos	June 1978	1910.1001
Benzene	1978 (invalidated)	1910.1028
Benzidine	June 1974	1910.1010
beta-Naphthylamine	June 1974	1910.1009
beta-Propiolactone	June 1974	1910.1013
bis-Chloromethyl ether	June 1974	1910.1008
Coke Oven Emissions	October 1976	1910.1029
Cotton Dust	June 1978	1910.1043
Cotton Dust (in cotton Gins)	June 1978	1910.1046
Dibromochloropropane	March 1978	1910.1044
3,3'-Dichlorobenzidine (and its Salts)	June 1974	1910.1007
4-Dimethylaminoazobenzene	June 1974	1910.1015
Ethyleneimine	June 1974	1910.1012
Lead	November 1978	1910.1025
Methyl chloromethyl ether	June 1974	1910.1006
4,4'-Methylene-bis	June 1974	1910.1005
4-Nitrobiphenyl	June 1974	1910.1003
N-Nitrosodimethylamine	June 1974	1910.1016
Vinyl Chloride	October 1974	1910.1017

Occupational Health Guideline for Acetaldehyde

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3CHO
- Synonyms: Ethanal; acetic aldehyde
- Appearance and odor: Colorless liquid or gas with a penetrating fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for acetaldehyde is 200 parts of acetaldehyde per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 360 milligrams of acetaldehyde per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for acetaldehyde a Threshold Limit Value of 100 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Acetaldehyde can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It may also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Acetaldehyde vapors may cause irritation of the eyes, nose, and throat. Inhalation of high concentrations of acetaldehyde vapor may cause drowsiness, dizziness, and unconsciousness. The liquid splashed in the eyes may cause irritation and burning. Swallowing acetaldehyde may cause drowsiness, dizziness, unconsciousness, kidney damage, and severe breathing difficulties which may be delayed in onset.

2. Long-term Exposure: Repeated or prolonged exposure to acetaldehyde may cause an irritation of the eyes and skin. An allergic skin rash may also result from repeated exposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to acetaldehyde.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to acetaldehyde at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from acetaldehyde exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of acetaldehyde might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although acetaldehyde is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Acetaldehyde ingestion has caused albuminuria in humans. The importance of this organ in the elimination of toxic subtances justifies special consideration in those with impaired renal function.

—Skin disease: Acetaldehyde can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

31

• **Summary of toxicology**

Acetaldehyde vapor is an irritant of the eyes and mucous membranes and at high concentrations causes narcosis and delayed pulmonary edema. In rats the LC50 for 30 minutes was approximately 20,000 ppm; the animals developed pronounced excitement followed by an anesthesia-like state; the principal autopsy finding was pulmonary edema. Symptoms of narcosis occur in humans at very high exposure levels or by parenteral injection; the irritant effects of the vapor at lower concentrations, such as cough and a burning sensation in the nose, throat, and eyes, usually prevent sufficient exposure to cause narcosis. Human volunteers exposed for 15 minutes to 200 ppm had red eyes due to transient conjunctivitis, while at 50 ppm a majority had mild eye irritation. The liquid splashed in the eyes causes a burning sensation, lacrimation, and blurred vision. The liquid on the skin for a prolonged period causes erythema and burns; repeated contact may result in dermatitis, due either to primary irritation or to sensitization. Ingestion produces central nervous system depression, sometimes with pulmonary edema and albuminuria.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 44.05
2. Boiling point (760 mm Hg): 20.4 C (68.7 F)
3. Specific gravity (water = 1): 0.78
4. Vapor density (air = 1 at boiling point of acetaldehyde): 1.52
5. Melting point: −123.5 C (−190.3 F)
6. Vapor pressure at 20 C (68 F): 750 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): 49.1

• **Reactivity**

1. Conditions contributing to instability: Prolonged contact with air may cause formation of peroxides that may explode and burst container.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with acids, bases, alcohols, ammonia and amines, phenols, ketones, hydrogen cyanide and hydrogen sulfide may cause violent reactions with liberation of much heat and bursting of containers.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving acetaldehyde.
4. Special precautions: Liquid acetaldehyde will attack some forms of plastics, rubbers, and coatings.

• **Flammability**

1. Flash point: −37.8 C (−36 F) (closed cup)
2. Autoignition temperature: 175 C (347 F)
3. Flammable limits in air, % by volume: Lower: 4; Upper: 60
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* reports an odor threshold of 2.3 ppm, May reports 0.031 ppm, and Stern reports 0.066 ppm.
2. Eye Irritation Level: Grant states that "irritation of the human eye is detectable at a concentration of 50 ppm in air and becomes excessive for chronic industrial exposure above 200 ppm. Higher concentration and extended exposure may injure the corneal epithelium, causing persistent lacrimation, photophobia, and foreign body sensation."
3. Evaluation of Warning Properties: Since the odor threshold for acetaldehyde is such a small fraction of the permissible exposure limit, odor is not considered a good warning of excessive exposures. Because of its irritant effects, however, acetaldehyde is judged to have adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of acetaldehyde. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

An analytical method for acetaldehyde is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for

operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid acetaldehyde.

• Clothing wet with liquid acetaldehyde should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of acetaldehyde from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the acetaldehyde, the person performing the operation should be informed of acetaldehyde's hazardous properties.

• Any clothing which becomes wet with liquid acetaldehyde should be removed immediately and not reworn until the acetaldehyde is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid acetaldehyde contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid acetaldehyde, an eye-wash facility should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes wet with liquid acetaldehyde should be promptly washed or showered to remove any acetaldehyde.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to acetaldehyde may occur and control methods which may be effective in each case:

Operation	Controls
Production of intermediates during synthesis of acetic acid, acetic anhydride, aldol compounds.	Process enclosure; local exhaust ventilation; personal protective equipment
Use during manufacture of synthetic resins; synthesis of intermediates in production of pesticides and pharmaceuticals; synthesis of rubber processing chemicals	Process enclosure; local exhaust ventilation; personal protective equipment
Use in coating operations in the manufacture of mirrors	Process enclosure; local exhaust ventilation; personal protective equipment
Use as hardening agent in photography and in manufacture of gelatin, glue, casein products	Process enclosure; local exhaust ventilation; personal protective equipment
Use as preservative in food products and leather	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid acetaldehyde gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid acetaldehyde gets on the skin, flush the contaminated skin with water. If acetaldehyde soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of acetaldehyde, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When acetaldehyde has been swallowed, and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an uncon-

scious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If acetaldehyde is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak to disperse gas.
3. If in gaseous form, stop flow of gas.
4. If in the liquid form, for small quantities absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for vapors to completely clear hood ductwork, then burn the paper in a location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. Acetaldehyde should not be allowed to enter a confined space such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of acetaldehyde vapors are permitted.

• Waste disposal method:

Liquid acetaldehyde may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Acetaldehyde," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Acetaldehyde," *Hygienic Guide Series*, Detroit, Michigan, 1955.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products5(3rd ed.), Williams and Wilkins, Baltimore, 1969.*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-43, Acetaldehyde,* Washington, D.C., 1952.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Chemical Company Guide – Acetaldehyde*, New York, 1963.

RESPIRATORY PROTECTION FOR ACETALDEHYDE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Gas or Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
10,000 ppm or less	A gas mask with a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10,000 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of acetaldehyde; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 10,000 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Acetic Acid

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3COOH
- Synonyms: Glacial acetic acid; methane carboxylic acid; ethanoic acid; vinegar acid
- Appearance and odor: Colorless liquid or solid with a strong vinegar-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for acetic acid is 10 parts of acetic acid per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 25 milligrams of acetic acid per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Acetic acid can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Acetic acid vapors cause irritation of the eyes, nose, throat, and lungs. Inhalation of concentrated vapors may cause serious damage to the lining of the nose, throat, and lungs. Delayed breathing difficulties can occur. Contact with concentrated acetic acid may cause severe damage to the skin. Contact with concentrated acetic acid may very rapidly cause severe eye damage which may be followed by loss of sight. Swallowing concentrated acetic acid may cause severe injury or death.

2. Long-term Exposure: Repeated or prolonged exposure to acetic acid may cause a darkening or irritation of the skin, erosion of exposed front teeth, and chronic inflammation of the nose, throat, and bronchial tubes.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to acetic acid.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to acetic acid at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from acetic acid exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of acetic acid might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Acetic acid is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Acetic acid is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Acetic acid vapor is a severe irritant of the eyes, mucous membranes, and skin. In mice and guinea pigs the lethal concentration for 1-hour exposure was about 5000 ppm; irritation of the eyes and respiratory tract occurred above 100 ppm. Exposure to 50 ppm or more is intolerable to most persons and results in intense lacrimation and irritation of the eyes, nose, and throat, with pharyngeal edema and chronic bronchitis. Unacclimatized humans experience extreme eye and nasal irritation at concentrations in excess of 25 ppm; con-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

junctivitis from concentrations below 10 ppm has been reported. In a study of five workers exposed for 7 to 12 years to concentrations of 80 to 200 ppm at peaks, the principal findings were blackening and hyperkeratosis of the skin of the hands, conjunctivitis (but no corneal damage), bronchitis and pharyngitis, and erosion of the exposed teeth (incisors and canines). Glacial (100%) acetic acid caused severe injury when applied to the eyes of rabbits; in humans it has caused permanent corneal opacification. A splash of vinegar (4 to 10% acetic acid solution) in the human eye causes immediate pain and conjunctival hyperemia, sometimes with injury of the corneal epithelium. On the guinea pig skin, the liquid in concentrations in excess of 80% produces severe burns; concentrations of 50 to 80% produce moderate to severe burns; solutions below 50% cause relatively mild injury; no injury is produced by 5 to 10% solution. Skin sensitization is rare but has been reported. Although ingestion is unlikely to occur in industrial use, as little as 1.0 ml of glacial acetic acid has resulted in perforation of the esophagus.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 60.05
  2. Boiling point (760 mm Hg): 118 C (244 F)
  3. Specific gravity (water = 1): 1.05
  4. Vapor density (air = 1 at boiling point of acetic acid): 2.1
  5. Melting point: 16.6 C (62 F)
  6. Vapor pressure at 20 C (68 F): 11 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 0.97
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers (especially chromic acid, sodium peroxide, and nitric acid) may cause fires and explosions. Contact with strong caustics will cause violent spattering.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving acetic acid.
  4. Special precautions: Liquid acetic acid will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 40 C (104 F) (closed cup)
  2. Autoignition temperature: 427 C (800 F)
  3. Flammable limits in air, % by volume at 100 C (212 F): Lower; 5.4; Upper: 16.0
  4. Extinguishant: Carbon dioxide, dry chemical, alcohol foam
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold of 24 ppm; Patty reports 10 ppm; the Manufacturing Chemists Association reports 1 ppm; Gleason reports 0.2 to 1 ppm.
  2. Eye Irritation Level: Grant reports that "the vapor of acetic acid is irritating to the eyes and nose, causing lacrimation and hyperemia." Patty reports that workers exposed to 80 to 200 ppm for 7 to 12 years suffered "conjunctivitis (but no corneal damage)." The *Documentation of TLV's* states that "Baldi reported conjunctival irritation from concentrations below 10 ppm." It notes that the TLV of 10 ppm is suggested in order to "prevent undue irritation." The AIHA *Hygienic Guide* also states that eye irritation occurs at 10 to 15 ppm.
  3. Other Information: Grant reports that the vapor of acetic acid is irritating to the nose. Also, workers exposed to 80 to 200 ppm for 7 to 12 years experienced congestion of the pharynx. No other quantitative information is given. The *Hygienic Guide* states that "unacclimatized humans experience extreme eye and nasal irritation at concentrations in excess of 25 ppm. Effects at 50 ppm are intolerable and usually result in immediate running from the area." Nasal irritation occurs at 10 to 15 pmm," according to the *Hygienic Guide*.
  4. Evaluation of Warning Properties: Since the odor of acetic acid can be detected at a level either below or slightly above the permissible exposure limit, and since the *Documentation of TLV's* reports that eye irritation has been noted at a concentration below 10 ppm, acetic acid is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for acetic acid is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted

are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solid or liquid acetic acid or solutions containing 50% or more of acetic acid by weight and to prevent repeated or prolonged skin contact with solutions containing 10% or more but less than 50% of acetic acid by weight.

• Clothing contaminated with acetic acid should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of acetic acid from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the acetic acid, the person performing the operation should be informed of acetic acid's hazardous properties.

• Where there is any possibility of exposure of an employee's body to solid or liquid acetic acid or solutions containing 50% or more of acetic acid by weight, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with solid or liquid acetic acid or solutions containing 50% or more of acetic acid by weight should be removed immediately and not reworn until the acetic acid is removed from the clothing.

• Non-impervious clothing which becomes contaminated with solutions containing less than 50% but greater than 10% of acetic acid by weight should be removed promptly and not reworn until the acetic acid is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid acetic acid or solutions containing acetic acid contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solid or liquid acetic acid or solutions containing 50% or greater acetic acid by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with solid or liquid acetic acid or solutions containing 50% or more of acetic acid by weight should be immediately washed or showered to remove any acetic acid.

• Skin that becomes contaminated with solutions containing less than 50% but greater than 10% acetic acid by weight should be promptly washed or showered to remove any acetic acid.

• Employees who handle solid or liquid acetic acid or solutions containing acetic acid should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to acetic acid may occur and control methods which may be effective in each case:

Operation	Controls
Use in production of acetic anhydride for cellulose acetate, fibers, plastics, and aspirin; use in production of vinyl acetate for polymers, coatings, and adhesives	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in production of acetic esters for solvents in plastics, coatings, and pharmaceutical industries	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in chemical industry as an esterifying agent, acetylating agent, solvent, and reaction medium; as an acidifying and neutralizing agent	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in food canning industries as a food additive or flavorant for pickles, fish, meat, candy, and glazes	General dilution ventilation; personal protective equipment
Use in manufacture and processing of acetic acid; use in textile and dye industries as a solvent, acidifying and neutralizing agent, intermediate in production of dyestuffs, dye catalysts, textile finishing, dye after-treatment, and production of nylon and acrylic fibers	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

Operation	Controls
Use in photographic industry in manufacture of photographic chemicals; constituent of photographic fixing baths, hardeners, hypotest solutions, and constituent of microfilm cements	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in pharmaceutical industry in production of vitamins, antibiotics, hormones, and reaction solvent	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in rubber industry in manufacture of rubber chemicals, accelerators, and coagulant of natural latex	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in dry cleaning and laundry industries to remove rust from garments; laundry sour to adjust pH in final operations	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a laboratory reagent in chemical and biochemical analysis; in field testing of lead fume, vinyl chloride determination, uric acid in urine, analine vapors, and separation of gases	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in miscellaneous applications for etching compounds for engraving; deliming agent during leather tanning, solvent for organic compounds, and oil well acidizer	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solid or liquid acetic acid or solutions containing acetic acid get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately.

[illegible] this chemical.

• **Skin Exposure**

If solid or liquid acetic acid or solutions containing acetic acid get on the skin, immediately flush the contaminated skin with water. If solid or liquid acetic acid or solutions containing acetic acid penetrate through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of acetic acid, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If solid or liquid acetic acid or strong solutions of acetic acid have been swallowed and the person is conscious, give him large quantities of water immediately to dilute the acetic acid. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If acetic acid is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. If in the liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber, or diluted, and then neutralized with caustic solution and flushed into a sewer. Unneutralized, combustible acetic acid should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.
4. If in the solid form, collect in the most safe and convenient manner for reclamation or allow to melt and collect as in (3) above.

• Waste disposal method:

Acetic acid may be disposed of by atomizing in a suitable combustion chamber, or diluted and then neutralized with caustic solution and flushed into a sewer.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Acetic Acid," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Acetic Acid," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-41, Acetic Acid*, Washington, D.C., 1973.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List IV," *Archives of Industrial Hygiene*, 4:12, pp. 119-121, 1951.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Acetic Acid*, New York, 1963.

RESPIRATORY PROTECTION FOR ACETIC ACID

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
500 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
1000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Acetic Anhydride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3CO)_2O$
- Synonyms: Ethanoic anhydride; acetic acid anhydride; acetyl oxide
- Appearance and odor: Colorless liquid with a characteristic sharp odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for acetic anhydride is 5 parts of acetic anhydride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 20 milligrams of acetic anhydride per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for acetic anhydride a Threshold Limit Value of 5 ppm as a ceiling value.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Acetic anhydride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to the vapors of acetic anhydride may cause irritation of the nose and throat and coughing. Exposure to high concentrations of the vapor can result in severe damage to the lungs. Delayed breathing difficulties may occur. Acetic anhydride liquid does not cause a severe burning sensation when it comes in contact with the skin. If it is not removed by washing, the skin may become reddened and later turn white and wrinkled but may not be painful. Skin burns may appear later. Contact with the liquid or vapor may produce a serious eye burn. Immediately after contact, a burning sensation of the eyes with tearing occurs. This may be followed later by impairment of vision. After exposure to acetic anhydride, there may be a delay in the appearance of the severe eye burns.

2. Long-term Exposure: Repeated and prolonged exposure to acetic anhydride may cause irritation of the skin and chronic eye irritation. Allergic sensitization of the skin may occur.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to acetic anhydride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to acetic anhydride at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from acetic anhydride exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of acetic anhydride might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Acetic anhydride is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Acetic anhydride is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

41

• **Summary of toxicology**

Acetic anhydride vapor is a severe irritant of the eyes, mucous membranes, and skin. Rats exposed to 2000 ppm for 4 hours died, but 1000 ppm for 4 hours was not lethal. Humans exposed to undetermined but high vapor concentrations complained immediately of severe conjunctival and naso-pharyngeal irritation, harsh cough, and dyspnea. Workmen exposed to vapors from a boiling mixture complained of severe eye irritation and lacrimation. The immediate effect of exposure to vapor concentrations above 5 ppm is acute irritation of the eyes and upper respiratory tract; inhalation of high vapor concentrations may produce ulceration of the nasal mucosa and, in some instances, bronchospasm. In the rabbit eye, direct application of the liquid caused severe injury. Both the liquid and the vapor can cause severe damage to the human eye; this is characterized by immediate burning, followed some hours later by an increasing severity of reaction, with corneal and conjunctival edema. Interstitial corneal opacity may develop over a period of several days due to progression of tissue infiltration; in mild cases, this condition is reversible, but permanent opacification with loss of vision may also occur. Workmen exposed to acetic anhydride vapor may show evidence of conjunctivitis with associated photophobia. Severe burns and vesiculation of human skin have been reported from liquid splashes; concentrated vapor produces primary irritation. Generalized skin reactions in guinea pigs sensitized to acetic anhydride have been demonstrated, and skin sensitization in humans has been reported. While ingestion of the liquid is unlikely in ordinary industrial use, the highly corrosive nature of the substance may be expected to produce serious mucous-membrane burns of the mouth and esophagus.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 102.1
2. Boiling point (760 mm Hg): 140 C (284 F)
3. Specific gravity (water = 1): 1.08
4. Vapor density (air = 1 at boiling point of acetic anhydride): 3.52
5. Melting point: −73 C (−99 F)
6. Vapor pressure at 20 C (68 F): 4 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 12, then reacts slowly
8. Evaporation rate (butyl acetate = 1): 0.46

• **Reactivity**

1. Conditions contributing to instability: Water, particularly if the heat liberated by the slow reaction with water cannot escape so that the reaction becomes progressively more violent.
2. Incompatibilities: Contact with water, alcohols, strong oxidizers (especially chromic acid) or amines may cause violent reaction. Contact with strong caustics will cause violent reaction and spattering.
3. Hazardous decomposition products: Toxic gases and vapors (such as acetic acid and carbon monoxide) may be released in a fire involving acetic anhydride.
4. Special precautions: Liquid acetic anhydride will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 49 C (120 F) (closed cup)
2. Autoignition temperature: 390 C (734 F)
3. Flammable limits in air, % by volume: Lower: 2.9; Upper: 10.3
4. Extinguishant: Carbon dioxide, dry chemical, alcohol foam

• **Warning properties**

1. Odor Threshold: The Coast Guard's *CHRIS Hazard Chemical Data Handbook* reports an odor threshold for acetic anhydride of 0.14 ppm.
2. Eye Irritation Level: The AIHA *Hygienic Guide* reports that "the immediate effect of exposure to vapor concentrations above 5 ppm is that of acute irritation of the eyes and the mucous membranes of the respiratory tract. Conjunctivitis, photophobia, lacrimation, and irritation of the nose and throat may occur."
3. Evaluation of Warning Properties: Through its odor and irritant effects, acetic anhydride can be detected at concentrations below and at the permissible exposure limit. Acetic anhydride, therefore, has good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of acetic anhydride. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of acetic anhydride in a bubbler containing hydroxyl amine, followed by reaction with ferric chloride, and colorimetric analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure acetic anhydride may be used. An analytical method for acetic anhydride is in

the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid acetic anhydride, where skin contact may occur.

• Clothing contaminated with acetic anhydride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of acetic anhydride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the acetic anhydride, the person performing the operation should be informed of acetic anhydride's hazardous properties.

• Where exposure of an employee's body to liquid acetic anhydride may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with acetic anhydride should be removed immediately and not reworn until the acetic anhydride is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid acetic anhydride or solutions containing acetic anhydride contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid acetic anhydride or solutions containing more than 1% acetic anhydride by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with acetic anhydride should be immediately washed or showered to remove any acetic anhydride.

• Employees who handle liquid acetic anhydride should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to acetic anhydride may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of cellulose esters and in manufacture of fibers, plastics, lacquers, protective coating solutions, photographic films, cigarette filters, magnetic tape, and thermoplastic molding compositions	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of pharmaceuticals and pharmaceutical intermediates	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis as an acetylating agent, bleaching agent, and dehydrating agent; use in synthesis of perfume chemicals, explosives, and weed killers; use in acetylation of animal and vegetable oils; acetylating agent and dehydrating agent in textile dyeing, chemical treatment of paper, and chemical analysis	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If acetic anhydride gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If acetic anhydride gets on the skin, immediately flush the contaminated skin with water. If acetic anhydride soaks through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of acetic anhydride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If acetic anhydride has been swallowed and the person is conscious, give him large quantities of water immediately to dilute the acetic anhydride. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If acetic anhydride is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Acetic anhydride should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Acetic anhydride may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Acetic Anhydride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Acetic Anhydride," *Hygienic Guide Series*, Detroit, Michigan, 1971.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Department of Transportation: *CHRIS Hazardous Chemical Data*, CG-446-2, U.S. Government Printing Office, Washington, D.C., January 1974.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-42, Acetic Anhydride*, Washington, D.C., 1962.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List IV," *Archives of Industrial Hygiene*, 4:2, pp. 119-121, 1951.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Acetic Anhydride*, New York, 1963.

RESPIRATORY PROTECTION FOR ACETIC ANHYDRIDE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
250 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Acetonitrile

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3CN
- Synonyms: Methylcyanide
- Appearance and odor: Colorless liquid with an ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for acetonitrile is 40 parts of acetonitrile per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 70 milligrams of acetonitrile per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Acetonitrile can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Acetonitrile may cause a slight flushing of the face and a feeling of chest tightness. Inhaling acetonitrile may cause irritation of the nose and throat. High concentrations may cause such effects as nausea, vomiting, respiratory depression, weakness, chest or abdominal pain, vomiting blood, convulsions, shock, unconsciousness, and death. The effects may come on several hours after exposure has ceased. Splashes of the liquid in the eyes may cause irritation.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to acetonitrile.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to acetonitrile at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the kidneys, liver, cardiovascular system, and central nervous system should be stressed. The skin sould be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Acetonitrile vapor is an asphyxiant due to its inhibitory action on metabolic enzyme systems. Effects are delayed and may be due to slow formation of cyanide ion. In male rats the LC50 was 7500 ppm for a single 8-hour exposure; there was prostration followed by convulsive seizures; at autopsy there was pulmonary hemorrhage. Rats repeatedly exposed to 665 ppm for 7 hours daily developed pulmonary inflammation, and there were minor changes in the liver and kidneys in some animals. Of 16 painters exposed to the vapor of a mixture containing 30 to 40% acetonitrile for two consecutive workdays, 10 developed symptoms ranging in severity from nausea, headache, and lassitude to vomiting, respiratory depression, extreme weakness, and stupor. Five of the victims were hospitalized, and of these one died; this worker experienced the onset of chest pain 4 hours after leaving the job on the second day of exposure, followed shortly by massive hematemesis, convulsions, shock, and coma, with death occurring 14 hours after cessation of exposure. At autopsy, cyanide ion concen-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

trations (in ug%) were: blood 796, urine 215, kidney 204, spleen 318 and lung 128; cyanide ion was not detected in the liver. Two human subjects inhaled 160 ppm for 4 hours; one of them experienced a slight flushing of the face 2 hours later, and a slight feeling of bronchial tightness 5 hours later. A week prior to this, the same two subjects had inhaled 80 ppm with no effects. Humans accidentally inhaling 500 ppm for brief periods reported some irritation of nose and throat. In the rabbit eye, a drop of the liquid caused superficial injury. The liquid on the belly of a rabbit caused a faint erythema of short duration.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 41.05
  2. Boiling point (760 mm Hg): 82 C (179 F)
  3. Specific gravity (water = 1): 0.79
  4. Vapor density (air = 1 at boiling point of acetonitrile): 1.3
  5. Melting point: −45.7 C (−50 F)
  6. Vapor pressure at 20 C (68 F): 73 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 5.79
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving acetonitrile.
  4. Special precautions: Liquid acetonitrile will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 5.6 C (42 F) (closed cup)
  2. Autoignition temperature: 524 C (975 F)
  3. Flammable limits in air, % by volume: Lower: 4.4; Upper: 16.0
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: The AIHA *Hygienic Guide* reports that "three human subjects detected the odor at 40 ppm. Olfactory fatigue occurred in 2 to 3 hours."
  2. Eye Irritation Level: Acetonitrile is not known to be an eye irritant.
  3. Other Information: The *Hygienic Guide* reports that "humans accidentally inhaling 500 ppm for brief periods reported some irritation of nose and throat."
  4. Evaluation of Warning Properties: Since the odor of acetonitrile is detectable at the permissible exposure limit and since olfactory fatigue does not occur rapidly, acetonitrile is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of acetonitrile vapors using an adsorption tube with subsequent desorption with benzene and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure acetonitrile may be used. A detailed analytical method for acetonitrile may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22161, under the title "NIOSH Analytical Methods for Set L" (order number PB 250 159).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid acetonitrile.
- Clothing wet with liquid acetonitrile should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of acetonitrile from the clothing. If the clothing is to be

laundered or otherwise cleaned to remove the acetonitrile, the person performing the operation should be informed of acetonitrile's hazardous properties.

• Where exposure of an employee's body to liquid acetonitrile may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Any clothing which becomes wet with or non-impervious clothing which becomes contaminated with acetonitrile should be removed immediately and not reworn until the acetonitrile is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid acetonitrile may contact the eyes.

SANITATION

• Skin that becomes contaminated with acetonitrile should be immediately washed or showered to remove any acetonitrile.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to acetonitrile may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent for extractive distillation in manufacture of butadiene and isoprene	Process enclosure; local exhaust ventilation; personal protective equipment
Use as an extractive solvent in separation of fatty acids from fish liver oils; removal of phenol, tar, and color from petroleum hydrocarbons; recovery of various alcohols, acids, and dark wood rosin; and chemical analysis	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent and reaction medium for preparation of pharmaceuticals, water-proofing compounds, antistatic agents, detergents, polymers, dyestuff intermediates, and for chemical research	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a solvent for recrystallization and purification of salts and metals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a spinnning solvent for synthetic fibers; use as a solvent for epoxy resin coatings	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis in preparation of vitamins, perfumes, water softeners, and plasticizers	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a catalyst to promote ionization reactions and for preparation of catalysts	Process enclosure; local exhaust ventilation; personal protective equipment
Use in low-temperature batteries for electrochemical properties; use in electrokinetic transducers and angular accelerometers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in miscellaneous operations for cyanide dyes, brighteners for metal, and deordorizers for specialty naphthas	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during thermal decomposition of flexible polyurethane foams	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If acetonitrile gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If acetonitrile gets on the skin, immediately flush the contaminated skin with water. If acetonitrile soaks through the clothing, remove the clothing immediately and wash the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of acetonitrile, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When acetonitrile has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

• **Special First Aid Procedures**

First aid kits containing an adequate supply of amyl nitrite pearls (ampoules) should be maintained at each site where acetonitrile is used. When a person is suspected of receiving an overexposure to acetonitrile, immediately remove him from the contaminated area using established rescue procedures. Contaminated clothing should be removed and the acetonitrile washed from the skin immediately. Artificial respiration should be started at once if breathing has stopped. If the person is unconscious, amyl nitrite may be used as an antidote by a properly trained individual in accordance with established emergency procedures. Medical aid should be obtained immediately.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If acetonitrile is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Acetonitrile should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Acetonitrile may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• Amdur, M. L.: "Accidental Group Exposure to Acetonitrile," *Journal of Occupational Medicine*, 1:627-633, 1959.

• American Conference of Governmental Industrial Hygienists: "Acetonitrile," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Acetonitrile," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kimura, E. T., et al.: "Acute Toxicity and Limits of Solvent Residue for Sixteen Organic Solvents," *Toxicology and Applied Pharmacology*, 19:699-704, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Pozzani, U. C., et al.: "An Investigation of the Mammalian Toxicity of Acetonitrile," *Journal of Occupational Medicine*, 1:634-642, 1959.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Acetonitrile*, New York, 1965.

• Wolfsie, J. H.: "Treatment of Cyanide Poisoning in Industry," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 4:417-425, 1951.

RESPIRATORY PROTECTION FOR ACETONITRILE

Condition	Minimum Respiratory Protection* Required Above 40 ppm
Vapor Concentration	
400 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
1000 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
4000 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Acetylene Tetrabromide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CHBr_2CHBr_2$
- Synonyms: Tetrabromoethane; symmetrical tetrabromoethan 1,1,2,2-tetrabromoethane
- Appearance and odor: Pale yellow liquid with a pungent odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for acetylene tetrabromide is 1 part of acetylene tetrabromide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 14 milligrams of acetylene tetrabromide per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Acetylene tetrabromide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Acetylene tetrabromide may cause eye and nose irritation, headache, loss of appetite, nausea, abdominal pain, kidney and liver damage with such symptoms as dark urine and yellow jaundice. Breathing high concentrations of this chemical might damage the lungs.

2. Long-term Exposure: Prolonged or repeated contact with acetylene tetrabromide might cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to acetylene tetrabromide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to acetylene tetrabromide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver should be stressed.

—Liver function tests: Acetylene tetrabromide may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Acetylene tetrabromide vapor is severely hepatotoxic. Guinea pigs exposed for 90 minutes to vapors in a near saturated atmosphere as low as 14 ppm became comatose, seemed to recover, but died after several days. Some animals exposed at 4 ppm for 180 days showed slight fatty degeneration of the liver; at 1.1 ppm no adverse effects were noted. The liquid instilled in the rabbit eye caused slight to moderate pain, conjunctival irritation, and corneal injury which disappeared after 24 hours. When bandaged onto the shaved abdomen of the rabbit for 72 hours, moderate redness, edema, and blistering were observed. A chemist working with the substance for 7-½ hours with no local exhaust ventilation developed severe, nearly fatal, liver damage and was hospitalized for 9 weeks; his estimated exposure during most of the work shift prior to the onset of symptoms was 1 to 2 ppm, although he had a single 10-minute period exposure to approximately 16 ppm. He

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

51

complained first of headache, anorexia, and nausea within hours of the exposure, and within five days developed abdominal pain with bilirubinuria and a monocytosis of 17%. He apparently recovered. Other workers in the same laboratory complained only of slight eye and nose irritation, with headache and lassitude.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 345.7
  2. Boiling point (760 mm Hg): 239 C (462 F)
  3. Specific gravity (water = 1): 2.97
  4. Vapor density (air = 1 at boiling point of acetylene tetrabromide): 11.9
  5. Melting point: – 1 C (30 F)
  6. Vapor pressure at 20 C (68 F): Less than 0.1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.065
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Reacts with chemically active metals or with strong caustics. In the presence of steam, contact with hot iron, aluminum, and zinc may cause formation of toxic vapors.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen bromide, carbonyl bromide, brominated solvents and carbon monoxide) may be released when acetylene tetrabromide decomposes.
  4. Special precautions: Acetylene tetrabromide will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**

Even though acetylene tetrabromide is known to have a sweet, chloroformlike odor, Patty states that "the odor is not distinctive enough to be considered a good warning property." Since no quantitative data are available relating other warning properties to air concentrations of this substance, acetylene tetrabromide should be treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using a silica gel adsorption tube with subsequent desorption with tetrahydrofuran and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure acetylene tetrabromide may be used. An analytical method for acetylene tetrabromide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid acetylene tetrabromide.
- Non-impervious clothing which becomes contaminated with liquid acetylene tetrabromide should be removed promptly and not reworn until the acetylene tetrabromide is removed from the clothing.
- Clothing wet with acetylene tetrabromide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of acetylene tetrabromide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the acetylene tetrabromide, the person performing the operation should be informed of acetylene tetrabromide's hazardous properties.

tetrabromide may contact the eyes.

SANITATION

• Skin that becomes contaminated with acetylene tetrabromide should be promptly washed or showered with soap or mild detergent and water to remove any acetylene tetrabromide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to acetylene tetrabromide may occur and control methods which may be effective in each case:

Operation	Controls
Use as a catalyst or catalytic initiator in synthetic fibers; as polymer additive in flame-proof, flame-retardant polystyrenes, polyurethanes, and polyolefins	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as a flotation agent in processing and separation of mineral oils	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as mercury substitute in manufacture of gauges and balancing equipment; use as refractive index liquid in microscopy	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If acetylene tetrabromide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If acetylene tetrabromide gets on the skin, promptly flush the contaminated skin with water. If acetylene tetrabromide soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Inhalation**

If acetylene tetrabromide has been inhaled, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When acetylene tetrabromide has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If acetylene tetrabromide is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Acetylene tetrabromide may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tetrabromoethane (Acetylene Tetrabromide)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Hollingsworth, R. L., et al.: "Toxicity of Acetylene Tetrabromide Determined on Experimental Animals," *American Industrial Hygiene Association Journal*, 24:28-35, 1963.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Van Haaften, A. B.: "Acute Tetrabromoethane (Acetylene Tetrabromide) Intoxication in Man," *American Industrial Hygiene Association Journal*, 30:251-256, 1969.

54

RESPIRATORY PROTECTION FOR ACETYLENE TETRABROMIDE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
10 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 10 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Acrolein

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2=CHCHO$
- Synonyms: Acrylic aldehyde; acrylaldehyde; propenal; allylaldehyde
- Appearance and odor: Clear, colorless, or yellowish liquid with a piercing, disagreeable odor that causes tears

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for acrolein is 0.1 part of acrolein per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.25 milligram of acrolein per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Acrolein can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Acrolein may cause irritation of the eyes, nose, throat, lungs, and skin. It may cause skin burns. It may also cause a feeling of pressure in the chest, headache, dizziness, and upset stomach. Death can rapidly take place if high concentrations are breathed.

2. Long-term Exposure: Chronic effects of exposure to acrolein are skin irritation and occasionally skin allergy appearing as hives or a rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to acrolein.

- **Recommended medical surveillance**

The following medical examinations should be made available to each employee who is exposed to acrolein at potentially hazardous levels:

1. Initial Medical Examination:

—A complete medical history and physical examination with emphasis on the heart and lungs: The purpose is to detect pre-existing medical conditions which might place the exposed employee at increased risk from a reported effects, and to establish a baseline for future health monitoring. Examination of the heart and lungs should be stressed.

—14" x 17" chest roentgenogram: Acrolein may cause lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Acrolein is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

The main toxic effects of acrolein are severe irritation of the eyes, skin, upper respiratory tract, and lungs, leading to pulmonary edema. Systemic absorption is unlikely because of the severe irritant effect. Hypersensitivity has been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 56
2. Boiling point (760 mm Hg): 51.7 C (125 F)
3. Specific gravity (water = 1): 0.84
4. Vapor density (air = 1 at boiling point of acro-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

lein): 1.94

5. Melting point: −87 C (−125 F)

6. Vapor pressure at 20 C (68 F): 214 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): 22

8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Acrolein is stabilized by a polymerization inhibitor (usually hydroquinone). If this is not present in adequate concentration, acrolein can polymerize and explode its container. The polymerization is also speeded up by temperatures at or above 200 C (392 F). Another type of polymerization, also liberating much heat, is caused by alkalies or strong acids.

2. Incompatibilities: Contact with oxidizing agents, acids, alkalies, and ammonia may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide and peroxides) may be released in a fire involving acrolein.

4. Special precautions: None

• **Flammability**

1. Flash point: −26 C (−15 F) (closed cup)

2. Autoignition temperature: 235 C (455 F)

3. Flammable limits in air, % by volume: Lower: 2.8; Upper: 31

4. Extinguishant: Dry chemical, carbon dioxide, or alcohol foam

• **Warning properties**

1. Odor Threshold: Summer reports an odor threshold of 15 ppm; Stern reports 1.8 ppm; May reports 1.5 and 0.2 ppm; and the AIHA *Hygienic Guide* reports 0.4 ppm.

2. Eye Irritation Level: Grant states that "for human beings, exposure to 5.5 ppm of acrolein in air is intolerable in the first minute. Exposure to 1 ppm induces lacrimation and becomes intolerable in 4 to 5 minutes. Even the U.S. maximum allowable industrial concentration of 0.5 ppm is said to be more than enough to produce warning sensation of irritation." Grant also notes that "the vapor causes a burning sensation in the eyes at low concentration and is violently irritant and lacrimatory at high concentrations."

3. Evaluation of Warning Properties: Through its irritant effects, acrolein can be detected at or near the permissible exposure limit. The *Documentation of TLV's* notes that "the 0.1 ppm limit is sufficiently low to minimize, but not entirely prevent, irritation to all exposed animals."

For the purposes of this guideline, acrolein is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of acrolein in an impinger containing sodium bisulfide, followed by treatment with trichloroacetic acid, and colorimetric analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure acrolein may be used. An analytical method for acrolein is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 1, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00267-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid acrolein.

• Clothing wet with liquid acrolein should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of acrolein from the clothing. If the clothing is to be laundered or

otherwise cleaned to remove the acrolein, the person performing the operation should be informed of acrolein's hazardous properties.

- Where there is any possibility of exposure of an employee's body to liquid acrolein, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes wet with liquid acrolein or non-impervious clothing which becomes contaminated with liquid acrolein should be removed immediately and not reworn until the acrolein is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid acrolein contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid acrolein, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with liquid acrolein should be immediately washed or showered to remove any acrolein.
- Eating and smoking should not be permitted in areas where liquid acrolein is handled, processed, or stored.
- Employees who handle liquid acrolein should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to acrolein may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during organic synthesis of 1,2,6-hexanetriol, methionine, glutaraldehydes, acrylates, artificial resins, synthetic fibers, and polyurethane foams	Local exhaust ventilation
Liberation during heat cracking of animal and some vegetable fats; liberation during synthesis of glycerine	Local exhaust ventilation
Use as a fungicide to prevent slime	Personal protective equipment
Liberation during welding of metal coated with surface-protecting fluids	Local exhaust ventilation; personal protective equipment
Liberation during use of internal combustion engines in confined spaces	General dilution ventilation
Use as a herbicide to control aquatic weeds in drainage and irrigation channels	Personal protective equipment
Use as a denaturant in alcohol	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If acrolein gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If acrolein gets on the skin, immediately flush the contaminated skin with water. If acrolein soaks through the clothing, remove the clothing immediately and flush the skin with water. When there are chemical burns or evidence of skin irritation, get medical attention promptly.

- **Breathing**

If a person breathes in large amounts of acrolein, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When acrolein has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If acrolein is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. For large quantities, cover with sodium bisulfite ($NaHSO_3$), add a small amount of water and mix. Then, after one hour, flush with large amounts of water and wash the site with soap solution. Liquid acrolein should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Acrolein may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. For small quantities, by absorbing it in vermiculite, dry sand, earth, or a similar material and disposing of in a suitable combution chamber.
3. For large quantities, by mixing with a flammable liquid (such as acetone) and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Acrolein," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Acrolein," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products5(3rd ed.), Williams and Wilkins, Baltimore, 1969.*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-85, Acrolein*, Washington, D.C., 1

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Acrolein*, New York, 1971.

RESPIRATORY PROTECTION FOR ACROLEIN

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Vapor Concentration	
5 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a full facepiece providing protection against organic vapors. Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of acrolein; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 5 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Acrylamide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2=CHCONH_2$
- Synonyms: Propenamide; acrylamide monomer; acrylic amide
- Appearance: Colorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for acrylamide is 0.3 milligram of acrylamide per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended a permissible exposure limit of 0.3 mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week. The NIOSH Criteria Document for Acrylamide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Acrylamide can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to acrylamide causes drowsiness, a tingling sensation, fatigue, weakness, a stumbling type of walking, slurred speech, and shaking. It may also cause irritation of the skin and eyes.
2. Long-term Exposure: Repeated or prolonged skin contact with acrylamide may cause irritation of the skin. It may also cause the legs to feel numb.
3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to acrylamide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to acrylamide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the skin, eyes, and central and peripheral nervous systems should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Emphasis should be placed on informing the employee to report any symptoms associated with acrylamide toxicity.

- **Summary of toxicology**

Acrylamide dust absorption produces severe neuropathy. Acrylamide poisoning has been studied in mice, rats, rabbits, cats, dogs, baboons, and monkeys. In chronic poisoning, symptoms appear with a latency depending on the severity of the poisoning. Muscular weakness develops and increases to paralysis, at first in the hind limbs, then in the forelimbs. Experiments have shown decreases in the amplitude and velocity of nerve action potentials, demyelination and degeneration of both sensory and motor nerve fibers, loss of tendon reflexes, and some indications of CNS involvement. Workers exposed to acrylamide have developed symptoms after one month to one year, exhibiting muscular weakness, ataxia, erythemia, and excessive sweating of the hands and arms, cold fingers and hands, peeling of the skin, numbness and paresthesia, fatigue and signs of CNS involvement. Individual differences in susceptibility have been noted. When contact with acrylamide

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

ceases, recovery is good, often complete, but the rate of recovery depends upon the severity of the exposure. In these cases poor work practices had allowed excessive skin contact, and it was concluded that significant absorption had occurred through the skin. No cases were seen in work situations where care had been taken to avoid excessive skin contact. Aqueous solutions are mildly irritating to the eyes and skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 71.1
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.12
4. Vapor density (air = 1 at boiling point of acrylamide): 2.4
5. Melting point: 84 C (183 F)
6. Vapor pressure at 20 C (68 F): 0.007 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 216
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Acrylamide decomposes above 175 C (347 F). Violent polymerization may occur when heated.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as ammonia, hydrogen, and carbon monoxide) may be released when acrylamide decomposes.
4. Special precautions: None

- **Flammability**

1. Flash point: Data not available
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Foam, carbon dioxide, dry chemical

- **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of acrylamide.
2. Eye Irritation Level: Grant reports that "acute testing of solutions of acrylamide on the eyes of rabbits has shown that a 10% aqueous solution causes immediate slight pain and conjunctival irritation, but no corneal injury ... :d the eyes are all normal in 24 hours. A 40% aqueous solution allowed to remain in contact for only 30 seconds caused more pain but no greater injury. When 40% solution was applied and not washed off, superficial corneal injury resulted but healed completely within 24 hours." Kirk and Othmer also note that acrylamide is an eye irritant.

No quantitative information is available concerning the air concentrations of acrylamide which produce eye irritation.

3. Evaluation of Warning Properties: Since no quantitative data are available relating warning properties to air concentrations of acrylamide, this substance is treated as a material with poor warning properties. The concentration of acrylamide in saturated air at 20 C could result in a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

A detailed analytical method for acrylamide is suggested in the NIOSH Criteria Document for Acrylamide.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with acrylamide or solutions containing acrylamide.
- If employees' clothing may have become contaminated with acrylamide or solutions containing acrylamide, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with acrylamide should be placed in closed containers for storage until it can be

discarded or until provision is made for the removal of acrylamide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the acrylamide, the person performing the operation should be informed of acrylamide's hazardous properties.

- Where exposure of an employee's body to acrylamide or solutions containing acrylamide may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with acrylamide should be removed immediately and not reworn until the acrylamide is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where acrylamide or solutions containing acrylamide may contact the eyes.

SANITATION

- Skin that becomes contaminated with acrylamide should be immediately washed or showered to remove any acrylamide.
- Workers subject to skin contact with acrylamide or solutions containing acrylamide should wash any areas of the body which may have contacted acrylamide at the end of each work day.
- Eating and smoking should not be permitted in areas where acrylamide or solutions containing acrylamide are handled, processed, or stored.
- Employees who handle acrylamide or solutions containing acrylamide should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to acrylamide may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of copolymers and polyacrylamides for use as flocculating and thickening agents in pulp and paper industries, oil production, mining, textile, surface coating, adhesives, dyes, photography, and water and waste treatment	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a grouting material in drilling of oil well drill holes, basements, tunnels, mine shafts, caissons, and dams	General dilution ventilation; personal protective equipment
Use in miscellaneous processes of monomer acrylamide as curing agents and in organic synthesis	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If acrylamide or solutions containing acrylamide get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If acrylamide or solutions containing acrylamide get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If acrylamide or solutions containing acrylamide penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of acrylamide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When acrylamide has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If acrylamide is spilled, the following steps should be taken:

1. Ventilate area of spill.

2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Acrylamide may be disposed of:

1. By making packages of acrylamide in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving acrylamide in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Acrylamide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fullerton, P. M., and Barnes, J. M.: "Peripheral Neuropathy in Rats Produced by Acrylamide," *British Journal of Industrial Medicine*, 23:210-221, 1966.

• Garland, T. O., and Patterson, M. W. H.: "Six Cases of Acrylamide Poisoning," *British Medical Journal*, 4:134-138, 1967.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Leswing, R. J., and Ribelin, W. E.: "Physiologic and Pathologic Changes in Acrylamide Neuropathy," *Archives of Environmental Health*, 18:22-29, 1969.

• McCollister, D. D., et al.: "Toxicology of Acrylamide," *Toxicology and Applied Pharmacology*, 6:172-181, 1964.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Acrylamide*, HEW Publication No. (NIOSH) 77-112, GPO No. 017-033-00185-5, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR ACRYLAMIDE

Condition	Minimum Respiratory Protection* Required Above 0.3 mg/m³
Particulate and Vapor Concentration	
15 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
600 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 600 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Allyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2=CHCH_2OH$
- Synonyms: 2-Propenol; 2-propen-1-ol; vinyl carbinol
- Appearance and odor: Colorless liquid with an odor like mustard.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for allyl alcohol is 2 parts of allyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 5 milligrams of allyl alcohol per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Allyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

Overexposure to allyl alcohol may cause irritation of the eyes, nose, and skin. Absorption through the skin or eyes may cause deep-seated pain in the region where the absorption occurred. Severe eye burns may occur from eye contact with this chemical. Burns of the skin may also occur. Exposure to high air concentrations of allyl alcohol may cause irritation of the lungs, nausea, and vomiting.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to allyl alcohol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to allyl alcohol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from allyl alcohol exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of allyl alcohol might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Allyl alcohol can cause skin burns. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although allyl alcohol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although allyl alcohol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Eye disease: Because allyl alcohol is reported to cause eye injury, those with pre-existing eye diseases may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The vapor of allyl alcohol is highly irritating to the eyes and nose of human subjects. At 25 ppm, lacrimation, retrobulbar pain, photophobia, and blurring of vision have been reported. The lethal concentration for rats of 150 ppm produces pathologic changes in the lungs and liver. Skin absorption produces injury to the liver and kidneys in animals. In man, skin contact causes burns, and absorption through the skin results in pain in the

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

underlying tissue and gastrointestinal symptoms. Contamination of the eye with the liquid produces corneal damage. No cases of systemic intoxication in humans have been reported, although there is a risk of delayed pulmonary edema following the inhalation of high concentrations of the vapor.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 58
2. Boiling point (760 mm Hg): 97 C (206 F)
3. Specific gravity (water = 1): 0.9
4. Vapor density (air = 1 at boiling point of allyl alcohol): 2.0
5. Melting point: −129 C (−200 F)
6. Vapor pressure at 20 C (68 F): 17.2 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving allyl alcohol.
4. Special precautions: Allyl alcohol will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 21 C (70 F) (closed cup)
2. Autoignition temperature: 378.4 C (713 F)
3. Flammable limits in air, % by volume: Lower: 2.5; Upper: 18.0
4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide

- **Warning properties**

1. Odor Threshold: Patty reports that the odor threshold of allyl alcohol is less than 0.75 ppm. He also states that 5 out of 10 "human volunteers reported a definite odor . . . when exposed to 2 ppm of allyl alcohol for 1 to 3 minutes."
2. Eye Irritation Level: Patty reports that slight eye irritation occurs at 6.25 ppm and moderate irritation at 25 ppm.
3. Other Information: According to Patty, the threshold of nasal irritation is below 0.78 ppm. Moderate nasal irritation occurs at 12.5 ppm. The threshold of pulmonary discomfort is greater than 25 ppm.
4. Evaluation of Warning Properties: Since allyl alcohol can be detected at a concentration below the permissible exposure limit through its odor and irritant (nasal) effects, this substance is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of allyl alcohol vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure allyl alcohol may be used. An analytical method for allyl alcohol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid allyl alcohol.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact

with allyl alcohol vapor at or above a concentration of 25 ppm.

- Clothing contaminated with liquid allyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of allyl alcohol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the allyl alcohol, the person performing the operation should be informed of allyl alcohol's hazardous properties.
- Where there is any possibility of exposure of an employee's body to liquid allyl alcohol, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes wet with or non-impervious clothing which becomes contaminated with liquid allyl alcohol should be removed immediately and not reworn until the allyl alcohol is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid allyl alcohol may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid allyl alcohol should be immediately washed or showered to remove any allyl alcohol.
- Eating and smoking should not be permitted in areas where liquid allyl alcohol is handled, processed, or stored.
- Employees who handle liquid allyl alcohol should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to allyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of various allyl esters which serve as monomers and prepolymers; use in preparation of chemical derivatives used in perfumes, flavorings, and pharmaceuticals	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a fungicide, herbicide, and nematicide	Personal protective equipment
Use in refining and dewaxing of mineral oil	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If allyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If allyl alcohol gets on the skin, immediately flush the contaminated skin with water. If allyl alcohol soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention promptly.

- **Breathing**

If a person breathes in large amounts of allyl alcohol, move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist the affected person by administering oxygen. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When allyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If allyl alcohol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Allyl alcohol should not be allowed to

enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Allyl alcohol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Allyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Allyl Alcohol," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

RESPIRATORY PROTECTION FOR ALLYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 2 ppm
Vapor Concentration	
100 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
150 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 150 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of allyl alcohol; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 150 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Allyl Chloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2=CHCH_2Cl$
- Synonyms: 3-Chloroprene; 1-chloro-2-propene
- Appearance and odor: Colorless, yellow, or purple liquid with an unpleasant, pungent odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for allyl chloride is 1 part of allyl chloride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 3 milligrams of allyl chloride per cubic meter of air (mg/m^3). NIOSH has recommended that a ceiling level of 3 ppm (9 mg/m^3) be adopted to supplement the existing permissible exposure limit. The NIOSH Criteria Document for Allyl Chloride should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Allyl chloride can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Allyl chloride vapors may cause nose, throat, lung, and eye irritation (with eye pain) and injury to the liver and kidney. Lung injuries may appear several hours after exposure. Liquid allyl chloride may cause a chemical burn and deep-seated eye pain on contact with the eyes. It may also irritate the skin and be absorbed through the skin.

2. Long-term Exposure: Repeated or prolonged exposure to allyl chloride by inhalation or skin contact may cause injury to the kidneys or liver. Prolonged skin contact may burn the skin and may also produce a delayed deep muscle ache described as "deepbone" ache.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to allyl chloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to allyl chloride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of respiratory system, eyes, liver and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—FVC and FEV (1 sec): Allyl chloride is a severe pulmonary irritant in animals.

—14" x 17" chest roentgenogram: Allyl chloride may cause lung damage. Surveillance of the lungs is indicated.

—Liver function tests: Allyl chloride may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Urinalysis: Since kidney damage may occur, a urinalysis should be obtained to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—A complete blood count: A complete blood count should be performed, including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing.

• **Summary of toxicology**

Allyl chloride vapor is a respiratory irritant, and in animals has caused damage to the liver and kidneys. Rats did not survive when exposed for more than 15 minutes to 29,300 ppm, or longer than 3 hours to 290 ppm; they suffered alveolar hemorrhage in the lungs and severe kidney injury. Several species of animals exposed to 8 ppm for 7 hours daily for 1 month showed no apparent ill effects, but histopathologic examination revealed focal necrosis in the liver and necrosis of the convoluted tubules of the kidney; at 3 ppm for 6 months, rats showed slight centri-lobular degeneration in the liver. The most frequent effects in man following overexposure have been conjunctival irritation and eye pain with photophobia; eye irritation occurs between 50 and 100 ppm. Irritation of the nose occurs at levels below 25 ppm. This substance is a skin irritant and may be absorbed through the skin, causing deep-seated pain. If splashed in the eye, severe irritation would be expected. Systemic intoxication of humans has not been reported.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 76.5
2. Boiling point (760 mm Hg): 44.6 C (112 F)
3. Specific gravity (water = 1): 0.94
4. Vapor density (air = 1 at boiling point of allyl chloride): 2.6
5. Melting point: −134.5 C (−209 F)
6. Vapor pressure at 20 C (68 F): 295 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.36
8. Evaporation rate (butyl acetate = 1): 7 (approximately)

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers, acids, aluminum, zinc, amines, peroxides, and chlorides of iron and aluminum may cause violent polymerizations, fires, and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving allyl chloride.
4. Special precautions: Allyl chloride will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: −31.7 C (−25 F) (closed cup)
2. Autoignition temperature: 391 C (737 F)
3. Flammable limits in air, % by volume: Lower: 3.3; Upper: 11.1
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

• **Warning properties**

Both the odor threshold and the irritation thresholds of allyl chloride are well above the permissible exposure level, as stated in Patty. Allyl chloride, therefore, is treated as a material with poor warning properties. Allyl chloride is an eye irritant, according to Patty, at concentrations of 50 to 100 ppm. Grant reports that only slight eye irritation has been observed in guinea pigs and albino rats exposed to 10 mg/l (3190 ppm) allyl chloride.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Peak Above Ceiling Evaluation**

Measurements to determine peak employee exposure should be taken during periods of maximum expected airborne concentration of allyl chloride. Each measurement should consist of a 30-minute sample or a series of consecutive samples totalling 30 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with benzene and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure allyl chloride may be used. An analytical method for allyl chloride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed

vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid allyl chloride.

• Where exposure of an employee's body to liquid allyl chloride may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Any clothing which becomes wet with allyl chloride or non-impervious clothing which becomes contaminated with liquid allyl chloride should be removed immediately and not reworn until the allyl chloride is removed from the clothing.

• Clothing wet with liquid allyl chloride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of allyl chloride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the allyl chloride, the person performing the operation should be informed of allyl chloride's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where liquid allyl chloride may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid allyl chloride should be immediately washed or showered to remove any allyl chloride.

• Eating and smoking should not be permitted in areas where liquid allyl chloride is handled, processed, or stored.

• Employees who handle liquid allyl chloride should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to allyl chloride may occur and control methods which may be effective in each case:

Operation	Controls
Use during manufacture of glycerin, epichlorohydrin, allyl alcohol, allylamines, allyl silanes, allyl ethers of starch, 1,2,3-trichloropropane, and pharmaceuticals	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If allyl chloride gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If allyl chloride gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If allyl chloride soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of allyl chloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When allyl chloride has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If allyl chloride is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Allyl chloride should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Allyl chloride may be disposed of by atomizing in a suitable combustion chamber equipped with an effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Allyl Chloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Allyl Chloride," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dow Chemical Company: *Material Safety Data Sheet - Allyl Chloride*, Midland, Michigan, 1972.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-99, Allyl Chloride*, Washington, D.C., 1973.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Allyl Chloride*, HEW Publication No. (NIOSH) 76-204, GPO No. 017-033-00186-3, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Torkelson, T. R., et al.: "Vapor Toxicity of Allyl Chloride as Determined on Laboratory Animals," *American Industrial Hygiene Association Journal*, 20:217-223, 1959.

RESPIRATORY PROTECTION FOR ALLYL CHLORIDE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
50 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
300 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 300 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 2-Aminopyridine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $NH_2C_5H_4N$
- Synonyms: Alpha-aminopyridine
- Appearance and odor: Colorless solid with a characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 2-aminopyridine is 0.5 part of 2-aminopyridine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2 milligrams of 2-aminopyridine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

2-Aminopyridine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: 2-Aminopyridine may cause headache, dizziness, nausea, and weakness. It may also cause flushing of the arms and legs, convulsions, and death.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 2-aminopyridine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 2-aminopyridine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 2-aminopyridine exposure.

—Convulsive disorders: 2-Aminopyridine causes convulsion. Persons with a history of convulsive disorders may be more susceptible to the effects of this agent.

—Liver disease: Although 2-aminopyridine is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although 2-aminopyridine is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 2-aminopyridine might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

2-Aminopyridine in aqueous solution is a central nervous system excitant and convulsant. The LD50 in mice by intraperitoneal injection was 35 mg/kg; lethal doses in animals produced excitement, tremors, convulsions, tetany, and death. Fatal doses were readily absorbed through the skin. In industrial experience, intoxication has occurred from inhalation of the dust or vapor, or by skin absorption following direct contact. Fatal intoxication occurred in a chemical worker who spilled a solution of 2-aminopyridine on his clothing during a

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

distillation; he continued to work in contaminated clothing for 1-½ hours. Two hours later, he developed dizziness, headache, respiratory distress, and convulsions that progressed to respiratory failure and death; it is probable that skin absorption was a contributing factor in this case. A non-fatal intoxication from exposure to an undetermined concentration of 2-aminopyridine in air resulted in severe headache, weakness, convulsions, and a stuporous state that lasted several days. A chemical worker exposed to an estimated air concentration of 20 mg/m³ (5.2 ppm) developed severe pounding headache, nausea, flushing of the extremities, and elevated blood pressure, but he recovered fully within 24 hours. An aqueous solution dropped in a rabbit's eye was only mildly irritating.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 94.1
  2. Boiling point (760 mm Hg): 210 C (410 F)
  3. Specific gravity (water = 1): Greater than 1
  4. Vapor density (air = 1 at boiling point of 2-aminopyridine): 3.2
  5. Melting point: 56 C (133 F)
  6. Vapor pressure at 20 C (68 F): Low
  7. Solubility in water, g/100 g water at 20 C (68 F): Greater than 100
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving 2-aminopyridine.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 68 C (154 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Carbon dioxide, dry chemical, alcohol foam
- **Warning properties**
  1. Odor threshold: No information is available concerning the odor threshold of 2-aminopyridine.
  2. Eye Irritation Level: Grant reports that "2-aminopyridine tested in 0.02M aqueous solution at pH 9.4 by dropping on a rabbit's cornea from which the epithelium had been removed caused only transient corneal haze and slight delay in return to normal." The vapor of 2-aminopyridine is not specifically stated as being an eye irritant, but since Patty reports that this compound is a strong base and that it is soluble in water, it is treated as an eye irritant for the purposes of this guideline. In addition, Patty points out that most of the amino pyridines "cause rather intense skin and eye irritation."
  3. Evaluation of Warning Properties: Since there are no quantitative data relating warning properties to air concentrations of 2-aminopyridine, this substance is treated as a material with poor warning properties. Its concentration in saturated air could result in a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- Method

An analytical method for 2-aminopyridine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with 2-aminopyridine or solutions containing 2-aminopyridine, where skin contact may occur.
- If employees' clothing may have become contaminated with 2-aminopyridine or solutions containing 2-aminopyridine, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with 2-aminopyridine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 2-aminopyridine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 2-aminopyridine, the person performing the operation should be informed of 2-aminopyridine's hazardous properties.

• Where exposure of an employee's body to 2-aminopyridine or solutions containing 2-aminopyridine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with 2-aminopyridine should be removed immediately and not reworn until the 2-aminopyridine is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where 2-aminopyridine or solutions containing 2-aminopyridine may contact the eyes.

SANITATION

• Skin that becomes contaminated with 2-aminopyridine should be immediately washed or showered to remove any 2-aminopyridine.

• Workers subject to skin contact with 2-aminopyridine or solutions containing 2-aminopyridine should wash any areas of the body which may have contacted 2-aminopyridine at the end of each work day.

• Eating and smoking should not be permitted in areas where 2-aminopyridine or solutions containing 2-aminopyridine are handled, processed, or stored.

• Employees who handle 2-aminopyridine or solutions containing 2-aminopyridine should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 2-aminopyridine may occur and control methods which may be effective in each case:

Operation	Controls
Use in production of chemical intermediates for manufacture of pharmaceuticals; use in manufacture of dyes, lubricant antioxidants, and herbicides	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 2-aminopyridine or solutions containing 2-aminopyridine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 2-aminopyridine or solutions containing 2-aminopyridine get on the skin, immediately flush the contaminated skin with water. If 2-aminopyridine or solutions containing 2-aminopyridine penetrate through the clothing, remove the clothing immediately and wash the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 2-aminopyridine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 2-aminopyridine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If 2-aminopyridine is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

2-Aminopyridine may be disposed of:

1. By making packages of 2-aminopyridine in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving 2-aminopyridine in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "2-Aminopyridine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR 2-AMINOPYRIDINE

Condition	Minimum Respiratory Protection* Required Above 0.5 ppm
Vapor Concentration	
5 ppm (20 mg/m³) or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5 ppm (20 mg/m³) or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ammonia

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: NH_3
- Synonyms: Anhydrous ammonia
- Appearance and odor: Colorless gas with a penetrating, pungent, suffocating odor; it can be a liquid under pressure.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ammonia is 50 parts of ammonia per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 35 milligrams of ammonia per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be changed to a ceiling of 50 ppm ammonia (35 mg/m^3) averaged over a five-minute period. The NIOSH Criteria Document for Ammonia should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ammonia can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It may also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Ammonia is a severe irritant of the eyes, respiratory tract, and skin. It may cause burning and tearing of the eyes, runny nose, coughing, chest pain, cessation of respiration, and death. It may cause severe breathing difficulties which may be delayed in onset. Exposure of the eyes to high gas concentrations may produce temporary blindness and severe eye damage. Exposure of the skin to high concentrations of the gas may cause burning and blistering of the skin. Contact with liquid ammonia may produce severe eye and skin burns. Contact of the eyes, nose, throat, and skin with solutions of ammonia may produce severe burns.

2. Long-term Exposure: Repeated exposure to ammonia gas may cause chronic irritation of the eyes and upper respiratory tract.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ammonia.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ammonia at potentially hazardous levels:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes and respiratory tract should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Ammonia causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Ammonia is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examinations: The above medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Ammonia vapor is a severe irritant of the eyes, especially the cornea, the respiratory tract, and skin. Inhalation of concentrations of 2500 to 6500 ppm causes dyspnea,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

80

September 1978

bronchospasm, chest pain and pulmonary edema which may be fatal; production of pink frothy sputum often occurs. Consequences can include bronchitis or pneumonia; some residual reduction in pulmonary function has been reported. In a human experimental study which exposed 10 subjects to various vapor concentrations for 5 minutes, 134 ppm caused irritation of the eyes, nose, and throat in most subjects and 1 person complained of chest irritation; at 72 ppm, several reported the same symptoms; at 50 ppm, 2 reported nasal dryness and at 32 ppm only 1 reported nasal dryness. In a survey of 8 workers in a blueprint shop, ammonia concentrations of 4 to 29 ppm caused "barely noticeable" to "moderate" eye irritation; no respiratory irritation was reported. Tolerance to usually irritating concentrations of ammonia may be acquired by adaptation, a phenomenon frequently observed among workers who became inured to the effects of exposure; no data are available on concentrations that are irritating to workers who are regularly exposed to ammonia and who presumably have a higher irritation threshold. Liquid anhydrous ammonia in contact with the eyes may cause serious eye injury or blindness; on the skin it causes first- and second-degree burns which are often severe, and if extensive, may be fatal. Vapor concentrations of 10,000 ppm are mildly irritating to the moist skin, while 30,000 ppm or greater causes a stinging sensation and may produce skin burns and vesiculation. Increased cancer has been reported in workers exposed to high levels of ammonia and amines, although lack of details makes evaluation difficult.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 17
  2. Boiling point (760 mm Hg): −33.4 C (-28 F)
  3. Specific gravity (water = 1): Liquid 0.67 at boiling point
  4. Vapor density (air = 1 at boiling point of ammonia): 0.6
  5. Melting point: −77.7 C (-108 F)
  6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
  7. Solubility in water, g/100 g water at 20 C (68 F): 51
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: Elevated temperatures may cause containers to explode.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with calcium, hypochlorite bleaches, gold, mercury, and silver may form highly explosive products. Contact with halogens may cause violent spattering.
  3. Hazardous decomposition products: None.
  4. Special precautions: Liquid ammonia will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: Not applicable
  2. Autoignition temperature: 651 C (1204 F)
  3. Flammable limits in air, % by volume: Lower: 16; Upper: 25
  4. Extinguishant: Stop flow of gas.
- **Warning properties**
  1. Odor Threshold: The AIHA *Hygienic Guide* states that "ammonia is a colorless gas with a characteristic odor detectable at 1 to 5 ppm."
  2. Eye Irritation Level: Grant states that "ammonia is slightly irritant to human eyes at a concentration of 140 ppm in air and immediately irritating at 700 ppm."
  3. Other Information: The *Hygienic Guide* states that "irritation of the respiratory tract in workers inhaling 100 ppm has been found, but 55 ppm was unobjectionable."
  4. Evaluation of Warning Properties: Because of its low thresholds of odor and irritation, ammonia is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of ammonia. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with a subsequent chemical analysis of the adsorption tube. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ammonia may be used. An analytical method for ammonia is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid anhydrous ammonia or aqueous solutions of ammonia containing more than 10% by weight of ammonia and to prevent the skin from becoming frozen from contact with vessels containing liquid anhydrous ammonia.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solutions containing 10% or less by weight of ammonia.

• Where there is any possibility of exposure of an employee's body to liquid anhydrous ammonia or aqueous solutions containing more than 10% ammonia by weight, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with anhydrous ammonia or aqueous solutions containing more than 10% ammonia by weight should be removed immediately and not reworn until the ammonia is removed from the clothing.

• Non-impervious clothing which becomes wet with solutions containing 10% ammonia by weight or less should be removed promptly and not reworn until the ammonia is removed from the clothing.

• Clothing wet with liquid anhydrous ammonia or aqueous solutions of ammonia should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ammonia from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ammonia, the person performing the operation should be informed of ammonia's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid anhydrous ammonia or aqueous solutions containing more than 10% ammonia by weight contacting the eyes.

• Employees should be provided with and required to use splash-proof safety goggles where solutions containing 10% ammonia by weight or less may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid anhydrous ammonia or aqueous solutions containing more than 10% ammonia by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid anhydrous ammonia or solutions containing more than 10% ammonia by weight should be immediately washed or showered to remove any ammonia.

• Skin that becomes wet with solutions containing 10% ammonia by weight or less should be promptly washed or showered to remove any ammonia.

• Employees who handle liquid anhydrous ammonia or aqueous solutions of ammonia should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ammonia may occur and control methods which may be effective in each case:

Operation	Controls
Use as a chemical in manufacture of fertilizers, as solvent in manufacture of textiles, leather, and pulp and paper processing; as a stabilizer in rubber manufacture	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

Operation	Controls
Use in organic and inorganic synthesis of nitric acid, urea, plastics, fibers, synthetic resins, pharmaceuticals, pesticides, explosives, rocket fuels, cyanides, amides, dyestuffs, amines, flame retardants, and household cleaners	Process enclosure; local exhaust ventilation; personal protective equipment
Use in mining/ metallurgy ore extraction and purification, treatment of scrap metal, annealing, atomic hydrogen welding, electronics, nitriding steel	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in petroleum refining as a neutralizing agent; manufacture and recovery of cracking catalysts; and in dewaxing of lubrication oils	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a refrigerant in food installations, production of ice, cold-storage, food lockers, deicing	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during blueprinting and photography, electroplating, and as a laboratory reagent	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid anhydrous ammonia, solutions containing ammonia, or high concentrations of ammonia gas get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid anhydrous ammonia, strong solutions of ammonia, or high concentrations of ammonia gas get on the skin, immediately flush the contaminated skin with water. If liquid anhydrous ammonia, strong solutions containing ammonia, or high concentrations of ammonia gas penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation or burns are present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of ammonia, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ammonia has been swallowed and the person is conscious, give the person large quantities of water immediately to dilute the ammonia. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ammonia is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak to disperse gas.
2. If in gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
3. If in liquid form, allow to vaporize.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ammonia," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ammonia," *Hygienic Guide Series*, Detroit, Michigan, 1971.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• "Exposure to Ammonia, Proposed Standards," *Federal Register*, 40:54684-54693, November 25, 1975.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-8, Ammonia*, Washington, D.C., 1960.
• Matheson Company: *Anhydrous Ammonia Data Sheets*.
• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Ammonia*, HEW Publication No. (NIOSH) 74-136, GPO No. 017-033-00036, U.S. Government Printing Office, Washington, D.C., 1974.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

RESPIRATORY PROTECTION FOR AMMONIA

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Gas Concentraton	
100 ppm or less	Any chemical cartridge respirator with an ammonia cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
300 ppm or less	A chemical cartridge respirator with a full facepiece and an ammonia cartridge(s).
500 ppm or less	A gas mask with a chin-style or a front- or back-mounted ammonia canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 500 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against ammonia. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of ammonia; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 500 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Ammonium Sulfamate (Ammate)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $NH_2SO_3NH_4$
- Synonyms: Ammate herbicide
- Appearance and odor: Colorless, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ammonium sulfamate is 15 milligrams of ammonium sulfamate per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for ammonium sulfamate a Threshold Limit Value of 10 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ammonium sulfamate can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

There are no known effects.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ammonium sulfamate.

- **Recommended medical surveillance**

Routine medical examinations should be made available to each employee who is exposed to ammonium sulfamate at potentially hazardous levels.

- **Summary of toxicology**

Ammonium sulfamate is of low toxicity. In rats, the intraperitoneal injection of 0.8 g/kg caused the death of 6 of 10 animals; effects were stimulation of respiration and prostration. Repeated application of a 4% solution to the anterior surface of one arm of each of five human subjects for 5 days caused no skin irritation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 114.1
2. Boiling point (760 mm Hg): Decomposes at 200 C (392 F)
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of ammonium sulfamate): Not applicable
5. Melting point: 131 C (268 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 200
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Elevated temperatures cause highly exothermic reaction with water; steam may cause container to burst.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with hot water may cause formation of large amounts of steam.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and sulfur and carbon monoxide) may be released when ammonium sulfamate decomposes.
4. Special precautions: None

- **Flammability**

1. Not combustible

- **Warning properties**

Ammonium sulfamate is not known to be an eye irritant. Grant states that "ammonium sulfamate (Ammate) is a bright yellow-orange crystalline solid employed princi-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

pally as a weed killer. Tested by instillation of 0.5 ml of a 4% solution in water in the conjunctival sac of rabbits, it produced no irritation."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for ammonium sulfamate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ammonium sulfamate may occur and control methods which may be effective in each case:

Operation	Controls
Application as a herbicide for control of woody plants	Personal protective equipment
Use in manufacture of fire-retardant compositions for flame-proofing textiles and paper products	Process enclosure/ segregation; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in generation of nitrous oxide gas; use in manufacture of electroplating solutions	Process enclosure/ segregation; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during formulation for use as an herbicide	Process enclosure; exhaust ventilation; personal protective equipment
Liberation during manufacture for use in herbicide compositions	Process enclosure/ segregation; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of electroplating solutions	Process enclosure/ segregation; general dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ammonium sulfamate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ammonium sulfamate or liquids containing ammonium sulfamate get on the skin, promptly wash the contaminated skin using soap or mild detergent and water.

• **Breathing**

If a person breathes in large amounts of ammonium sulfamate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• Swallowing

When ammonium sulfamate or liquids containing ammonium sulfamate have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If ammonium sulfamate is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing ammonium sulfamate should be absorbed in vermiculite, dry sand, earth, or a similar material.

ADDITIONAL INFORMATION

To find additional information on ammonium sulfamate, look up ammonium sulfamate in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• Ambrose, A. M.: "Studies on the Physiological Effects of Sulfamic Acid and Ammonium Sulfamate," *Journal of Industrial Hygiene and Toxicology*, 25:26-28, 1943.

• American Conference of Governmental Industrial Hygienists: "Ammonium Sulfamate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

RESPIRATORY PROTECTION FOR AMMONIUM SULFAMATE (AMMATE)

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Particulate Concentration	
75 mg/m³ or less	Any dust and mist respirator.
150 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for n-Amyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOC_5H_{11}$
- Synonyms: 1-Pentanol acetate; n-amyl acetate (mixed isomers)
- Appearance and odor: Colorless liquid with a banana oil odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for n-amyl acetate is 100 parts of n-amyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 525 milligrams of n-amyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

n-Amyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to n-amyl acetate may cause irritation of the eyes, nose, and throat. Severe overexposure may cause weakness, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure to n-amyl acetate may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to n-amyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to n-amyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from n-amyl acetate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of n-amyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although n-amyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although n-amyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: n-Amyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Irritation of the upper respiratory tract and the eyes is the first response to exposure to n-amyl acetate vapor. At very high concentrations there may be depression of the central nervous system; narcosis occurred in guinea pigs at 5000 ppm, but not at 2000 ppm. These animals showed injury to the lungs, liver, and kidney. This substance is a defatting agent, and prolonged exposure may cause irritation of the skin. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 130
  2. Boiling point (760 mm Hg): 146 C (295 F)
  3. Specific gravity (water = 1): 0.88
  4. Vapor density (air = 1 at boiling point of n-amyl acetate): 4.5
  5. Melting point: −70.8 C (−95.4 F)
  6. Vapor pressure at 20 C (68 F): 4 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.2
  8. Evaporation rate (butyl acetate = 1): 0.42
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, or strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving n-amyl acetate.
  4. Special precautions: n-Amyl acetate will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash po[illegible] 25 C (77 F) (closed cup)
  2. Autoign[illegible] temperature: 360 C (680 F)
  3. Flammable limits in air, % by volume: Lower: 1.1; Upper: 7.5
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold for n-amyl acetate of 0.08 ppm.
  2. Eye Irritation Level: Since the AIHA *Hygienic Guide* states that a "concentration of 200 ppm (amyl acetate) vapor caused mild eye and nose irritation in human subjects in 3 to 5 minutes," n-amyl acetate is treated as an eye irritant for the purposes of this guideline.
  3. Evaluation of Warning Properties: Since the odor threshold of n-amyl acetate is well below the permissible exposure limit, n-amyl acetate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of n-amyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure n-amyl acetate may be used. An analytical method for n-amyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid n-amyl acetate.
- Clothing wet with liquid n-amyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of n-amyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the n-amyl acetate, the person performing the operation should be informed of n-amyl acetate's hazardous properties.
- Any clothing which becomes wet with liquid n-amyl acetate should be removed immediately and not reworn until the n-amyl acetate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid n-amyl acetate may contact the eyes.

SANITATION

- Skin that becomes wet with liquid n-amyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any n-amyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to n-amyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during spray application of paints and lacquers	Spray booths with proper ventilation; personal protective equipment
Liberation during coating application of textile finishing products	Local exhaust ventilation; general dilution ventilation
Liberation during brush and hand application of lacquers, lacquer thinners, paints, film cement, and general-purpose cellulose nitrate cements	General dilution ventilation
Use as a vehicle solvent during manufacture of cellulose nitrate lacquers, lacquer thinners, adhesives, nail enamel, nail enamel removers, and paint	General dilution ventilation
Liberation of vapor during manufacture of textile finishing compounds	General dilution ventilation
Use as an extractant of penicillin from fermentation broth during production of antibiotics	General dilution ventilation
Liberation during manufacture of quick-drying inks, metallic inks, and transfer inks	General dilution ventilation
Use as vehicle solvent during molding operations in manufacture of cellulose nitrate plastics, toys, eyeglass frames, combs, and novelties	General dilution ventilation; local exhaust ventilation
Liberation during manufacture of photographic film	General dilution ventilation; local exhaust ventilation
Liberation during manufacture of furniture polish, leather polish, and shoe polish	General dilution ventilation
Use in pre-spotting and spotting department in dry cleaning industry	General dilution ventilation; personal protective equipment
Liberation during manufacture of artificial fruit-flavoring agents	General dilution ventilation
Use as a vehicle solvent of lacquer and stiffening agent in manufacture of straw hats	General dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If n-amyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If n-amyl acetate gets on the skin, promptly flush the contaminated skin with water. If n-amyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of n-amyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When n-amyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If n-amyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. n-Amyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

n-Amyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "n-Amyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "n-Amyl Acetate," *Hygienic Guide Series*, Detroit, Michigan, 1955.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – n-Amyl Acetate*, New York, 1971.

RESPIRATORY PROTECTION FOR N-AMYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
4000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any self-contained breathing apparatus with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for sec-Amyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOCH(CH_3)(CH_2)_2CH_3$
- Synonyms: 2-Pentanol acetate
- Appearance and odor: Clear, colorless liquid with a fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sec-amyl acetate is 125 parts of sec-amyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 650 milligrams of sec-amyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

sec-Amyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to sec-amyl acetate may cause irritation of the eyes, nose, and throat. Overexpsoure may also cause headache, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sec-amyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sec-amyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from sec-amyl acetate exposure.

—Kidney disease: Although sec-amyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of sec-amyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although sec-amyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Skin disease: sec-Amyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Irritation of the eyes and upper respiratory tract is the first response to exposure to the vapor in humans and may occur at concentrations above 300 ppm. At very high concentrations there may be depression of the central nervous system; narcosis occurred in guinea pigs at 5000 ppm, but not at 2000 ppm. These animals showed injury to the lungs, liver, and kidneys. This substance is a defatting agent, and prolonged exposure

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

may cause irritation of the skin. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 130
  2. Boiling point (760 mm Hg): 134 C (273 F)
  3. Specific gravity (water = 1): 0.9
  4. Vapor density (air = 1 at boiling point of sec-amyl acetate): 4.5
  5. Melting point: −100 C (-148 F) (estimated)
  6. Vapor pressure at 20 C (68 F): 7 mm Hg (estimated)
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.2
  8. Evaporation rate (butyl acetate = 1): 0.9
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving sec-amyl acetate.
  4. Special precautions: sec-Amyl acetate may soften or dissolve plastics.
- **Flammability**
  1. Flash point: 31.7 C (89 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Lower: 1.0 (estimated)
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: By analogy to n-amyl acetate, which has an odor threshold of 0.082 ppm (May), the odor threshold of sec-amyl acetate is assumed to be below the permissible exposure limit.
  2. Eye Irritation Level: According to the *Handbook of Organic Industrial Solvents*, sec-amyl acetate produces a response similar to that produced by the commercial grade. Amyl acetate (commercial) causes noticeable throat irritation "below (the) threshold limit, becoming severe as this level is reached. Eye and nose irritation indicates presence of threshold concentration."
  3. Evaluation of Warning Properties: Since the odor threshold of sec-amyl acetate is assumed to be below the permissible exposure limit, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of sec-amyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure sec-amyl acetate may be used. An analytical method for sec-amyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid sec-amyl acetate.
- Clothing wet with liquid sec-amyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of sec-amyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the sec-amyl acetate, the person performing the operation should be informed of sec-amyl acetate's hazardous properties.
- Any clothing which becomes wet with liquid sec-amyl acetate should be removed immediately and not

reworn until the sec-amyl acetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid sec-amyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid sec-amyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any sec-amyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sec-amyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Use and liberation during spray application of lacquers, varnishes, enamels, and metallic paints	Local exhaust ventilation; personal protective equipment
Use and liberation during hand and dip applications of lacquers, varnishes, enamels, and metallic paints	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during use of textile-sizing and printing compounds; during use of leather finishes	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent for chlorinated rubber	General dilution ventilation; personal protective equipment
Use in manufacture of lacquers, varnishes, enamels, and metallic paints	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during repair of motion picture film	General dilution ventilation
Use in preparation of specialty products, including nail polishes, fine perfumes, and pearlescent coatings	General dilution ventilation; personal protective equipment
Liberation during build-up of pearlescent coatings on artificial pearls	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If sec-amyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If sec-amyl acetate gets on the skin, promptly flush the contaminated skin with water. If sec-amyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of sec-amyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When sec-amyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If sec-amyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. sec-Amyl acetate should not be al-

lowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

sec-Amyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "sec-Amyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Amyl Acetate," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR SEC-AMYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 125 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
9000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 9000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Aniline*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5NH_2$
- Synonyms: Aminobenzene; phenylamine; aniline oil
- Appearance and odor: Colorless to brown, oily liquid with a weak amine odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for aniline is 5 parts of aniline per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 19 milligrams of aniline per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for aniline a Threshold Limit Value of 2 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Aniline can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It is readily absorbed through the skin, either as a liquid or vapor. Even a small amount absorbed from the clothes or shoes may cause toxic symptoms.

- **Effects of overexposure**

1. Short-term Exposure: Aniline affects the ability of the blood to carry oxygen. Moderate exposure to aniline may cause only a bluish discoloration of the skin. As oxygen deficiency increases, the blue discoloration may be associated with headache, weakness, irritability, drowsiness, shortness of breath, and unconsciousness. If treatment is not given promptly, death can occur. Aniline is irritating to the eyes and may cause eye damage. The onset of symptoms may be delayed.

2. Long-term Exposure: Repeated skin or respiratory exposure to aniline may cause headache, irritability, insomnia, dizziness, decreased appetite, paleness, and anemia.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to aniline.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to aniline at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, cardiovascular system, liver, and kidneys should be stressed.

—A complete blood count: Aniline has been shown to cause methemoglobinemia. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Aniline absorption, whether from inhalation of the vapor or skin absorption of the liquid, causes anoxia due to the formation of methemoglobin. Rats exposed to 5 ppm of vapor daily for 6 months showed no effects other than slight methemoglobinemia. Human exposure to vapor concentrations of 7 ppm has been observed to cause slight symptoms. Rapid absorption through the intact skin is frequently the main route of entry; a small amount absorbed from contaminated clothing or shoes may cause intoxication, characterized by cyanosis. Following skin absorption, the onset of symptoms may be delayed for up to 4 hours. Headache is commonly the first symptom and may become quite intense as the

---

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

severity of methemoglobinemia progresses. Cyanosis develops early in the course of intoxication, first in the lips, nose, and ear lobes, and is usually recognized by fellow workers. Cyanosis occurs when the methemoglobin concentration is 15% or more. The individual usually feels well, has no complaints, and may insist that nothing is wrong, although cyanosis is evident to observers. until the methemoglobin concentration approaches approximately 40%. At methemoglobin concentrations of over 40%, there usually is weakness and dizziness; up to 70% concentration, there may be ataxia, dyspnea on mild exertion, and tachycardia. The development of intravascular hemolysis and anemia due to aniline-induced methemoglobinemia has been postulated, but neither is often observed in industrial practice despite careful and prolonged study of numerous cases. Occasional deaths from asphyxiation caused by severe aniline intoxication are said to have occurred. Liquid aniline is mildly irritating to the eyes and may cause corneal damage.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 93.1
  2. Boiling point (760 mm Hg): 184 C (364 F)
  3. Specific gravity (water = 1): 1.022
  4. Vapor density (air = 1 at boiling point of aniline): 3.22
  5. Melting point: −6.2 C (21 F)
  6. Vapor pressure at 20 C (68 F): 0.6 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 3.5
  8. Evaporation rate (butyl acetate = 1): Less than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact of liquid aniline with strong acids will cause violent spattering. Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving aniline.
  4. Special precautions: Liquid aniline will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 70 C (158 F) (closed cup)
  2. Autoignition temperature: 615 C (1139 F)
  3. Flammable limits in air, % by volume: Lower: 1.3; Upper: Data not available
  4. Extinguishant: Carbon dioxide, alcohol foam, dry chemical
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold for aniline of 7 ppm; the MCA reports that "the odor of aniline can usually be detected without difficulty in concentrations of 0.5 ppm," and Thienes and Haley report an odor threshold of 1 ppm.
  2. Eye Irritation Level: The MCA reports that "aniline is mildly irritating to the eyes and may cause corneal damage," but no quantitative information is given. Grant reports that "many years ago workers chronically exposed to crude aniline vapors had irritation of the eyes, photophobia, and impairment of vision," but he suggests that the disturbances of the cornea and conjunctiva which were observed might have been caused by "quinonelike oxidation products." Based upon the information reported by MCA, aniline is treated as an eye irritant for the purposes of this guideline.
  3. Evaluation of Warning Properties: Since the odor threshold ranges from a concentration well below the permissible exposure limit to a concentration only slightly greater than the permissible exposure limit, aniline is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of aniline in an adsorption tube containing silica gel, followed by desorption with ethanol and gas chromatographic analysis. An analytical method for aniline is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid aniline, where contact may occur.

• Clothing contaminated with aniline should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of aniline from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the aniline, the person performing the operation should be informed of aniline's hazardous properties.

• Where exposure of an employee's body to liquid aniline may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with aniline should be removed immediately and not reworn until the aniline is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid aniline may contact the eyes.

SANITATION

• Skin that becomes contaminated with aniline should be immediately washed or showered with soap or mild detergent and water to remove any aniline.

• Eating and smoking should not be permitted in areas where liquid aniline is handled, processed, or stored.

• Employees who handle liquid aniline should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to aniline may occur and control methods which may be effective in each case:

Operation	Controls
Use in chemical synthesis and intermediates for rubber processing; use in production of MDI and PMPPI in manufacture of rigid polyurethanes; use in synthesis of dyestuffs and intermediates for dyestuffs	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of pharmaceuticals and intermediates for pharmaceuticals; synthesis of hydroquinone for photographic processing; synthesis of intermediates for agricultural chemicals	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of inks, for cloth marking inks, indelible inks, and lithographic and other printing inks	Process enclosure; local exhaust ventilation; personal protective equipment
Use in production of PACM monomer in nylon fiber manufacture; use in synthesis of resins	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of intermediates for artificial sweetening agents	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of catalysts and stabilizers for hydrogen peroxide and cellulose; use in synthesis of corrosion inhibitors	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If aniline gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If aniline gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If

aniline soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of aniline, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When aniline has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If aniline is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Aniline may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Aniline," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Aniline," *Hygienic Guide Series*, Detroit, Michigan, 1955.

• Carpenter, C. P., Smyth, H. F., and Rozzani, V. C.: "The Assay of Acute Vapor Toxicity, and the Grading and Interpretation of Results on 96 Chemical Compounds," *Journal of Industrial Hygiene and Toxicology*, 31:343, 1949.

• Casciano, A. D.: "Acute Methemoglobinemia Due to Aniline - A Report of a Case," *Journal of the Medical Society of New Jersey*, 49:4, pp. 141-42, 1952.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dutkiewicz, T.: "Aniline Vapor Absorption in Man," *Medyeyna Pracy*, Warsaw, Poland, pp. 1-11, February 1961.

• H. M. Factory Inspectorate, "Methods for the Detection of Toxic Substances in Air - Aniline Vapour," *Booklet No. 11*, Department of Employment of Productivity, H. M. Stationery Office, P. O. Box 569, London SEI, 1968.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Jenkins, F. P., et al., "The No-Effect Dose of Aniline in Human Subjects and a Comparison of Aniline Toxicity in Man and the Rat," *Food and Cosmetics Toxicology*, 10:671-79, 1972.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-17, Aniline*, Washington, D.C., 1963.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Scarpa, C., and Ferrea, E.: "Group Variation in Reactivity to Common Contact Allergens," *Archives of Dermatology*, 94:589-91, 1966.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.
• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volumes 4 and 7, 1974.

RESPIRATORY PROTECTION FOR ANILINE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
100 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Anisidine (o,p-Isomers)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $NH_2C_6H_4OCH_3$
- Synonyms: o-Methoxyaniline; p-methoxyaniline
- Appearance and odor: Ortho: Cololorless to pink liquid with a characteristic amine odor; Para: Light red-brown solid with a characteristic amine odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for anisidine is 0.5 milligram of anisidine per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Anisidine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to anisidine may affect the ability of the blood to carry oxygen. The earliest effect may be a bluish color of the skin, especially the lips. If the lack of oxygen becomes severe, a person may have drowsiness, headache, nausea, and vomiting. If oxygen lack is very severe, it may cause unconsciousness and even death.

- **Reporting Signs and Symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to anisidine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to anisidine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, kidneys, liver, and cardiovascular system should be stressed.

—A complete blood count: Anisidine has been shown to cause methemoglobinemia and the formation of erythrocytic inclusion bodies. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

The absorption of the ortho or para isomer of anisidine, whether from inhalation of the vapor or dust or from skin absorption, causes anoxia due to the formation of methemoblobin. The peroral LD50 in rats was 1.4 g/kg. Mice repeatedly exposed to concentrations of 10 to 30 mg/m^3 for 2 hours daily showed a decrease in the excitability of nerves at the end of 1 month of exposure; after 12 months of exposure there was anemia and reticulocytosis. Workers exposed to a concentration of 1.9 mg/m3 for 3-½ hours per day for 6 months did not develop anemia or specific signs of intoxication; there were some cases of headache and vertigo, which may have been related to the observation of increased methemoglobin and sulfhemoglobin; the presence of erythrocytic inclusions, or Heinz bodies, was observed.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 123

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

2. Boiling point (760 mm Hg): Ortho: 225 C (436 F); Para: 243 C (470 F)

3. Specific gravity (water = 1): 1.1 (both isomers)

4. Vapor density (air = 1 at boiling point of anisidine, ortho and para isomers): 4.25

5. Melting point: Ortho: 6.2 C (43 F); Para: 58.5 C (137 F)

6. Vapor pressure at 20 C (68 F): Less than 0.1 mm Hg (both isomers)

7. Solubility in water, g/100 g water at 20 C (68 F): Ortho: 1.3; Para: moderate

8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released when anisidine decomposes.

4. Special precautions: Liquid anisidine will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: Para: 30 C (86 F) (closed cup)

2. Autoignition temperature: Data not available

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Foam, carbon dioxide, dry chemical

• **Warning properties**

Anisidine (o,p-isomers) is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for anisidine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with solid or liquid anisidine or liquids containing anisidine, where skin contact may occur.

• If employees' clothing may have become contaminated with solid or liquid anisidine or liquids containing anisidine, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with anisidine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of anisidine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the anisidine, the person performing the operation should be informed of anisidine's hazardous properties.

• Where exposure of an employee's body to solid or liquid anisidine or liquids containing anisidine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with anisidine should be removed immediately and not reworn until the anisidine is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where solid or liquid anisidine or liquids containing anisidine may contact the eyes.

SANITATION

• Skin that becomes contaminated with anisidine should be immediately washed or showered with soap or mild detergent and water to remove any anisidine.

• Eating and smoking should not be permitted in areas where solid or liquid anisidine or liquids containing anisidine are handled, processed, or stored.

• Employees who handle solid or liquid anisidine or liquids containing anisidine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to anisidine may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of azo or triphenylmethane dyes and intermediates; use in preparation of organic compounds; in synthesis of gusicol	General dilution ventilation; personal protective equipment
Use in synthesis of hair dyes; as corrosion inhibitors for steel storage; as an antioxidant for some polymercaptan resins; and as a dyeing assist	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If anisidine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid or liquid anisidine or liquids containing anisidine get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If solid or liquid anisidine or liquids containing anisidine penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of anisidine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When solid or liquid anisidine or liquids containing anisidine have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If anisidine is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquids containing anisidine should be absorbed in vermiculite, dry sand, earth, or a similar material. Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal method:

Anisidine may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Anisidine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Jenkins, L. P., et al.: "The No-Effect Dose of Aniline in Human Subjects and a Comparison of Aniline Toxicity in Man and the Rat," *Food and Cosmetics Toxicology*, 10:671-679, August, 1972.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet, Anisidine*, Washington, D.C.

• National Institute for Occupational Safety and Health: "Hazard Entry No. 15 — Aniline," *Hazard Process Index*.

• Pacseri, I., et al.: "Threshold and Toxic Limits of Some Amino and Nitro Compounds," *A.M.A. Archives of Industrial Health*, 18:1-8, 1958.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR ANISIDINE (o,p-ISOMERS)

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate or Vapor Concentration	
2.5 mg/m³ or less	Any dust and mist respirator, except single-use.
5 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	Any high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
50 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 50 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for ANTU

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{11}H_{10}N_2S$
- Synonyms: alpha-Naphthyl thiourea; alpha-naphthylthiocarbamide; N-1-naphthyl-thiourea; 1-(1-naphthyl)-2-thiourea
- Appearance and odor: Colorless, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ANTU is 0.3 milligrams of ANTU per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

ANTU can affect the body if it is inhaled. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Swallowing ANTU may cause vomiting, shortness of breath, and a bluish discoloration of the skin. ANTU is a rat poison causing death in rats by excessive secretion in the lungs which produce severe breathing difficulties. It also upsets the blood sugar levels in rats.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ANTU.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ANTU at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ANTU exposure.

—Chronic respiratory disease: ANTU causes pulmonary damage in animals. In persons with impaired pulmonary function, the ingestion of ANTU might cause exacerbation of symptoms.

—Liver disease: ANTU causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

ANTU (alpha-naphthyl-thiourea) dust causes pulmonary edema and pleural effusion in certain animal species, especially rats. Oral administration to rats of 35 mg/kg was fatal to 60% of the animals; effects were labored respiration and muscular weakness; autopsy revealed pleural and pericardial effusion, as well as mild liver damage. Tolerance to the acute toxicity of ANTU was induced in rats by administration of progressively increasing doses at 3- to 4-day intervals; daily doses of 20% of the median lethal dose in rabbits were cumulative, causing death within 5 to 6 days. In humans, the lethal dose by ingestion is estimated to be approximately 4 g/kg. In one instance of human intoxication by ANTU, 80 g of a rat poison containing 30% ANTU was ingested along with a considerable amount of ethanol; signs attributable to ANTU were prompt transient vomiting, dyspnea, cyanosis, and coarse pulmonary rales; no pleural effusion occurred, and the pulmonary

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

signs gradually cleared. ANTU is stated to be nonirritating to the human skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 202.3
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): Greater than 1
  4. Vapor density (air = 1 at boiling point of ANTU): Not applicable
  5. Melting point: 198 C (388 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.06
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide, oxides of nitrogen, and carbon monoxide) may be released in a fire involving ANTU.
  4. Special precautions: None
- **Flammability**
  1. Flash point: Data not available
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Water
- **Warning properties**

ANTU is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for ANTU is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- If employees' clothing may have become contaminated with ANTU, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with ANTU should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ANTU from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ANTU, the person performing the operation should be informed of ANTU's hazardous properties.

SANITATION

- Eating and smoking should not be permitted in areas where ANTU or liquids containing ANTU are handled, processed, or stored.
- Employees who handle ANTU or liquids containing ANTU should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ANTU may occur and control methods which may be effective in each case:

Operation	Controls
Use as a rodenticide in locations where rats feed, water, or travel	General dilution ventilation; personal protective equipment
Manufacture of ANTU	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If ANTU or liquids containing ANTU get into the eyes, wash eyes immediately with large amounts of water,

lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ANTU or liquids containing ANTU get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If ANTU or liquids containing ANTU soak through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water.

• **Breathing**

If a person breathes in large amounts of ANTU, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ANTU or liquids containing ANTU have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If ANTU is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

ANTU may be disposed of:

1. By making packages of ANTU in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving ANTU in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "ANTU," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• McClosky, W. T., and Smith, M. I.: "Studies on the Pharmacologic Action and the Pathology of Alphanaphthylthiourea (ANTU). I. Pharmacology," *Public Health Reports*, 60:1101-1113, 1945.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Sobonya, R. E., and Kleinerman, J.: "Recurrent Pulmonary Edema Induced by alpha-Naphthyl Thiourea," *American Review of Respiratory Disease*, 108:926-932, 1973.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

RESPIRATORY PROTECTION FOR ANTU

Condition	Minimum Respiratory Protection* Required Above 0.3 mg/m³
Particulate Concentration	
3 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
15mg/m³ or less	A chemical cartridge respirator with a full facepiece and organic vapor cartridge(s), and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode. A powered chemical cartridge respirator with an organic vapor cartridge and a high efficiency filter, including pesticide respirators which meet the requirements of this class.
Greater than 100 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Azinphos-Methyl

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_{12}N_3O_3PS_2$
- Synonyms: Guthion; O,O-dimethyl-S-(4-oxo-1,2,3-benzotriazin-3-(4H)-yl-methyl)phosphorodithioate
- Appearance: Brown waxy solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for azinphos-methyl is 0.2 milligram of azinphos-methyl per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Azinphos-methyl can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: The sequence of the development of effects varies with the route of entry. After inhalation of azinphos-methyl, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of vision, tearing, runny nose, headache, and watering of the mouth. After swallowing azinphos-methyl, loss of appetite, nausea, vomiting, abdominal cramps, and diarrhea may appear within two hours. After skin absorption, sweating and twitching in the area of absorption may occur usually within 15 minutes to four hours. With severe intoxication by all routes, in addition to all the above symptoms, weakness, generalized twitching and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, irregular or slow heart beat, convulsions, and coma may occur.

2. Long-term Exposure: Repeated exposure to levels of azinphos-methyl may make a person more susceptible to the effects of this and related chemicals. Repeated exposure to concentrations which are too small to produce symptoms after a single exposure may result in the onset of symptoms.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to azinphos-methyl.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to azinphos-methyl at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system, and attention to the cholinesterase levels in the blood should be stressed. The skin should be examined for evidence of chronic disorders.

—Cholinesterase determination: Azinphos-methyl causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the serum and erythrocytes should be determined by using medically acceptable biochemical tests prior to any new period of exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

basis, with the exception of the cholinesterase determination which should be performed quarterly or at any time overexposure is suspected or signs and symptoms of toxicity occur.

• **Summary of toxicology**

Azinphos-methyl (Guthion) is an anticholinesterase agent; absorption may occur from inhalation of the dust or mist; from skin absorption of solutions, or from ingestion. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nervous system, skeletal and smooth muscles, and secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms occurs promptly and almost always within 12 hours. After inhalation respiratory and ocular effects are the first to appear, often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects, such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption, localized sweating and muscular fasciculations in the immediate area occur, usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures, and is increased by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels, and cardiac irregularities including complete heart block may occur; these effects may sometimes be reversed by establishing adequate pulmonary ventilation. Complete symptomatic recovery usually occurs within 1 week; increased susceptibility to the effects of anticholinesterase agents persists for weeks after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects. In a study of eight workers engaged in the formulation of a Guthion wettable powder and exposed to concentrations up to 9.6 mg/m³, the lowest activity of cholinesterase in blood serum was 78% of the value before exposure, and there were no signs or symptoms of illness.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 317.3
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.4
4. Vapor density (air = 1 at boiling point of azinphos-methyl): Not applicable
5. Melting point: 73 C (163 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.003
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: High temperatures cause gas evolution and may develop pressure in sealed containers.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide, oxides of nitrogen, phosphoric acid mist, and carbon monoxide) may be released in a fire involving azinphos-methyl.
4. Special precautions: None

• **Flammability**

1. Flash point: Data not available
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Water

• **Warning properties**

Since azinphos-methyl has a negligible vapor pressure, warning properties are not considered. Azinphos-methyl is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for azinphos-methyl had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may

be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with azinphos-methyl or liquids containing azinphos-methyl, where skin contact may occur.

• If employees' clothing has had any possibility of being contaminated with azinphos-methyl or liquids containing azinphos-methyl, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with azinphos-methyl should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of azinphos-methyl from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the azinphos-methyl, the person performing the operation should be informed of azinphos-methyl's hazardous properties.

• Where exposure of an employee's body to azinphos-methyl or liquids containing azinphos-methyl may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with azinphos-methyl should be removed immediately and not reworn until the azinphos-methyl is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where azinphos-methyl or liquids containing azinphos-methyl may contact the eyes.

SANITATION

• Skin that becomes contaminated with azinphos-methyl should be immediately washed or showered with soap or mild detergent and water to remove any azinphos-methyl.

• Workers subject to skin contact with azinphos-methyl or liquids containing azinphos-methyl should wash with soap or mild detergent and water any areas of the body which may have contacted azinphos-methyl at the end of each work day.

• Eating and smoking should not be permitted in areas where azinphos-methyl or liquids containing azinphos-methyl are handled, processed, or stored.

• Employees who handle azinphos-methyl or liquids containing azinphos-methyl should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to azinphos-methyl may occur and control methods which may be effective in each case:

Operation	Controls
Application as an insecticide and acaricide on field crops, fruit, vegetables, cotton, tobacco, and sugar cane	Personal protective equipment; product substitution
Formulation for use as an insecticide	Personal protective equipment; product substitution
Manufacture of azinphos-methyl	Product substitution; local exhaust ventilation; process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If azinphos-methyl, or liquids or mists containing azinphos-methyl get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If azinphos-methyl, or liquids or mists containing azinphos-methyl get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If azinphos-methyl, or liquids or mists containing azinphos-methyl penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of azinphos-methyl, move the exposed person to fresh air at once. If

breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• Swallowing

When azinphos-methyl or liquids containing azinphos-methyl have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If azinphos-methyl is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Azinphos-methyl may be disposed of:

1. By making packages of azinphos-methyl in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving azinphos-methyl in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Azinphos-Methyl (Guthion)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Parathion," *Hygienic Guide Series*, Detroit, Michigan, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products5(3rd ed.), Williams and Wilkins, Baltimore, 1969.*

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Jegier, Z.: "Exposure to Guthion During Spraying and Formulating," *Archives of Environmental Health*, 8:565-569, 1964.

• Koelle, G. B. (ed.): *Cholinesterases and Anticholinesterase Agents*, Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Simpson, G. R.: "Exposure to Guthion During Formulation," *Archives of Environmental Health*, 10:53-54, 1965.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

RESPIRATORY PROTECTION FOR AZINPHOS-METHYL

Condition	Minimum Respiratory Protection* Required Above 0.2 mg/m³
Particulate Concentration	
2 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of azinphos-methyl; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 5 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Soluble Barium Compounds (as Barium)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all soluble barium compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Barium nitrate

- Formula: $Ba(NO_3)_2$
- Synonyms: None
- Appearance and odor: Odorless white solid.

Barium oxide

- Formula: BaO
- Synonyms: None
- Appearance and odor: Odorless white solid.

Barium carbonate

- Formula: $BaCO_3$
- Synonyms: None
- Appearance and odor: Odorless white solid.

Barium chloride

- Formula: $BaCl_2$
- Synonyms: None
- Appearance and odor: Odorless white solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for soluble barium compounds is 0.5 milligram of soluble barium compounds per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Soluble barium compounds can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Soluble barium compounds may cause local irritation of the eyes, nose, throat, bronchial tubes, and skin. Soluble barium compounds may also cause severe stomach pains, slow pulse rate, irregular heart beat, ringing of the ears, dizziness, convulsions, and muscle spasms. Death may occur.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to soluble barium compounds.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to soluble barium compounds at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the heart, lungs, and nervous system should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Soluble barium compounds cause human lung damage. Surveillance of the lungs is indicated.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

—FVC and FEV (1 sec): Soluble barium compounds are respiratory irritants. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Electrocardiogram: Barium compounds may cause cardiac arrhythmias and may have a direct effect on the cardiac muscle. Periodic surveillance of the heart is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

• **Summary of toxicology**

Soluble barium salts cause severe gastroenteritis and systemic effects by ingestion. Intravenous injection of barium compounds in animals causes a strong, prolonged stimulation of muscle resulting in hyperperistalsis, bladder contraction, vasoconstriction, and irregular contraction of the heart followed by arrest in systole. Animals also exhibit stimulation of the central nervous system followed by paralysis. Ingestion of barium carbonate by humans causes gastroenteritis, muscular paralysis, slow pulse rate, extrasystoles, and hypokalemia. Heavy industrial exposure to dusts of barium sulfate or barium oxides may produce a benign pneumoconiosis, termed baritosis. It results in no impairment of ventilatory function, although signs of mild bronchial irritation may occur. Characteristic x-ray changes are those of small, dense, circumscribed nodules evenly distributed throughout the lung fields, reflecting the radio-opacity of the barium dust. Bronchial irritation has been reported from the inhalation of barium carbonate dust. Barium hydroxide and barium oxide are strongly alkaline in aqueous solution, causing severe burns of the eye and irritation of the skin.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Barium nitrate**

1. Molecular weight: 261.4
2. Boiling point (760 mm Hg): Greater than 592 C (greater than 1098 F) (decomposes)
3. Specific gravity (water = 1): 3.24
4. Vapor density (air = 1 at boiling point of barium nitrate): Not applicable
5. Melting point: 592 C (1098 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 9.2
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Barium oxide**

1. Molecular weight: 153.3
2. Boiling point (760 mm Hg): 2000 C (3632 F)
3. Specific gravity (water = 1): 5.72
4. Vapor density (air = 1 at boiling point of barium oxide): Not applicable
5. Melting point: 1921 C (3490 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Barium carbonate**

1. Molecular weight: 197.3
2. Boiling point (760 mm Hg): 1300 C (2372 F) (decomposes)
3. Specific gravity (water = 1): 4.25
4. Vapor density (air = 1 at boiling point of barium carbonate): Not applicable
5. Melting point: Decomposes at 1300 C (2372 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0022
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Barium chloride**

1. Molecular weight: 208.3
2. Boiling point (760 mm Hg): 1560 C (2840 F)
3. Specific gravity (water = 1): 3.86
4. Vapor density (air = 1 at boiling point of barium chloride): Not applicable
5. Melting point: 963 C (1765 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 36
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: For barium nitrate, elevated temperatures may cause melting and decomposition; for the other compounds, none hazardous.
2. Incompatibilities: Contact of barium oxide with water, carbon dioxide, or hydrogen sulfide may cause fires and explosions. Contact of barium carbonate with acids causes formation of carbon dioxide gas that may cause suffocation in enclosed spaces. Contact of barium nitrate with organic matter and combustible materials may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving barium nitrate.
4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: For barium nitrate, data not available; for the the other compounds, not applicable.
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Large amounts of water should be used on adjacent fires.

• **Warning properties**

According to Grant, barium chloride causes "considerable iritis, which subsides in a few days" when "tested

in neutral 0.08 to 0.1 M solution on rabbit eyes by injection into the cornea or by dropping for 10 minutes on the eye after the corneal epithelium was removed to facilitate penetration." Grant states that "both the oxide and hydroxide are capable of causing severe alkali burns of the eye, similar to those produced by calcium hydroxide."

MONITORING AND MEASUREMENT PROCEDURES

• General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Method

Sampling and analyses may be performed by collection on a cellulose membrane filter followed by leaching in hot water, solution of sample in acid, and analysis in an atomic absorption spectrophotometer. An analytical method for soluble barium compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with barium carbonate, barium chloride, barium nitrate, or liquids containing these compounds.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with barium oxide or liquids containing barium oxide, where skin contact may occur.

• If employees' clothing has had any possibility of being contaminated with barium carbonate, barium chloride, barium nitrate, barium oxide, or liquids containing these compounds, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with barium carbonate, barium chloride, barium nitrate, or barium oxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of contaminant from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the contaminant, the person performing the operation should be informed of contaminant's hazardous properties.

• Where exposure of an employee's body to barium oxide or liquids containing barium oxide may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with barium carbonate, barium chloride, barium nitrate, or barium oxide should be removed promptly and not reworn until the contaminant is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of barium oxide or liquids containing barium oxide contacting the eyes.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where barium carbonate, barium chloride, barium nitrate, or liquids containing these compounds may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to barium oxide or liquids containing barium oxide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Workers subject to skin contact with barium oxide or liquids containing barium oxide should wash any areas of the body which may have contacted barium oxide at the end of each work day.

• Skin that becomes contaminated with barium carbonate, barium chloride, or barium nitrate should be promptly washed or showered to remove any contaminant. In the case of barium carbonate, employees should use soap or mild detergent and water for washing purposes.

• Skin that becomes contaminated with barium oxide should be promptly washed or showered to remove any barium oxide from the skin after all obvious amounts of barium oxide have been removed by other means (e.g., by use of oil or vaseline). Employees who are being burned by barium oxide should immediately utilize quick drenching facilities without first removing barium oxide by other means.

• Eating and smoking should not be permitted in areas where solid barium carbonate, barium chloride, barium nitrate, or barium oxide, or liquids containing these compounds are handled, processed, or stored.

• Employees who handle barium carbonate, barium chloride, barium nitrate, barium oxide, or liquids containing these compounds should wash their hands thoroughly before eating, smoking, or using toilet facilities. In the case of barium carbonate, employees should use soap or mild detergent and water for washing purposes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to soluble barium compounds may occur and control methods which may be effective in each case:

Operation	Controls
Manufacture and distribution of soluble barium compounds	Process enclosure; local exhaust ventilation
Use in manufacture of pressed and blown glassware and flint and crown optical glass; manufacture of ceramic products; use in electronics industry in manufacture of magnets, vacuum tubes, cathodes, x-ray fluorescent screens, TV picture tubes, and dry cell depolarizers	Process enclosure; local exhaust ventilation
Use in manufacture of photographic papers, dyes, and chemicals	Process enclosure; local exhaust ventilation
Use as pesticides, rodenticides, and disinfectants; use in manufacture of explosives, matches, and pyrotechnics as igniter compositions and fireworks	Process enclosure; local exhaust ventilation
Use as an additive in manufacture of grease, and manufacture of lubricating oils; use in refining of vegetable and animal oils	Process enclosure; local exhaust ventilation
Use in case-hardening of steel in metallurgy; in welding aluminum; in electroplating; and in aluminum and sodium refining	Process enclosure; local exhaust ventilation
Use in water treatment and boiler compounds for softening water; use as catalysts, analytical reagents, and purifying agents	Process enclosure; local exhaust ventilation
Use for treatment of textiles, leather, and rubber; use in manufacture of paper and cellulose as a bleaching agent; use in manufacture of pigments, colors, and lakes	Process enclosure; local exhaust ventilation
Use as a depilatory in processing of hides; as a fire-proof and extinguishing agent; in embalming; in sugar refining; in gas and solvent drying; in marble substitutes; in valve manufacture; and as a smoke suppressant in diesel fuels	Process enclosure; local exhaust ventilation
Use in manufacture of pigments, paints, enamels, and printing inks	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solutions of barium compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If solutions of barium compounds get on the skin, immediately flush the contaminated skin with water. If solutions of barium compounds soak through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of soluble barium compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When soluble barium compounds have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If soluble barium compounds are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquids containing soluble barium compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Soluble barium compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Barium and Compounds (as Ba.)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Barium and Its Inorganic Compounds," *Hygienic Guide Series*, Detroit, Michigan, 1962

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR SOLUBLE BARIUM COMPOUNDS (AS BARIUM)

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate Concentration	
2.5 mg/m³ or less	Any dust and mist respirator, except single-use.**
5 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
250 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode. A powered air-purifying respirator with a high efficiency particulate filter.
Greater than 250 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Benzoyl Peroxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_6H_5CO)_2O_2$
- Synonyms: Dibenzoyl peroxide
- Appearance and odor: Colorless, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for benzoyl peroxide is 5 milligrams of benzoyl peroxide per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be changed to 5 mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week. The NIOSH Criteria Document for Benzoyl Peroxide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Benzoyl peroxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Benzoyl peroxide causes irritation of the eyes, nose, throat, and skin.

2. Long-term Exposure: Repeated exposure may cause an allergic skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to benzoyl peroxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to benzoyl peroxide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the skin and respiratory system should be stressed.

—Skin disease: Benzoyl peroxide is a primary skin irritant and a skin sensitizer. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of benzoyl peroxide might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated at least every 3 years. Emphasis should be placed on informing the employee to report any symptoms associated with benzoyl peroxide toxicity.

- **Summary of toxicology**

Benzoyl peroxide dust causes primary irritation of skin and mucous membranes and sensitization dermatitis. Application to the face as a lotion for acne treatment in two individuals caused facial erythema and edema; patch tests with benzoyl peroxide were positive. In contact with the eyes it may produce irritation, and if allowed to remain on the skin it may produce inflammation. Workers exposed to 12.2 mg/m^3 experienced pronounced irritation of the nose and throat. When repeatedly applied to the skin of mice, it was not carcinogenic.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 242
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 1.33
4. Vapor density (air = 1 at boiling point of benzoyl peroxide): Not applicable
5. Melting point: 103 C (217 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Much less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Less than 1
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Benzoyl peroxide decomposes when heated above 75 C (167 F) and will explode when subjected to shock and friction.
2. Incompatibilities: Benzoyl peroxide is a powerful oxidizer and contact with wood, paper, and other combustible substances may cause fires and explosions. Contact with oxidizable materials such as lithium aluminum hydride may also cause fires and explosions. In the dry state, benzoyl peroxide is highly flammable. At elevated temperatures it can be unstable and is spontaneously explosive.
3. Hazardous decomposition products: Toxic gases and vapors (such as benzoic acid smoke and carbon monoxide) may be released in a fire involving benzoyl peroxide.
4. Special precautions: Benzoyl peroxide will attack some forms of plastics, rubber, and coatings; fires and explosions may result.

- **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: 103 C (217 F) (ignites and/or explodes)
3. Flammable limits in air, % by volume: Not available
4. Extinguishant: Water

- **Warning properties**

According to Grant, "the dust irritates the eyes, respiratory mucous membranes, and skin. Applied experimentally to animal eyes, it produces superficial opacities in the cornea and inflammation of the conjunctiva, according to one investigator, but according to another no injury results from single application of a 93% pure powder or a 50% paste in dimethyl phthalate to rabbit eyes."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of benzoyl peroxide on a filter, followed by colorimetric analysis. An analytical method for benzoyl peroxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with benzoyl peroxide or liquids containing benzoyl peroxide.
- Employees using or handling pure benzoyl peroxide should be provided with and required to wear fire-resistant clothing treated with an antistatic agent.
- Non-impervious clothing which becomes contaminated with benzoyl peroxide should be removed promptly and not reworn until the benzoyl peroxide is removed from the clothing.
- If employees' clothing may have become contaminated with solid benzoyl peroxide, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with benzoyl peroxide should be placed in closed cor. ners for storage until it can be discarded or until provision is made for the removal of benzoyl peroxide from the clothing. If the clothing is to

be laundered or otherwise cleaned to remove the benzoyl peroxide, the person performing the operation should be informed of benzoyl peroxide's hazardous properties.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where benzoyl peroxide or liquids containing benzoyl peroxide may contact the eyes.

SANITATION

• Skin that becomes contaminated with benzoyl peroxide should be promptly washed or showered with soap or mild detergent and water to remove any benzoyl peroxide.

• Eating and smoking should not be permitted in areas where solid benzoyl peroxide is handled, processed, or stored.

• Employees who handle benzoyl peroxide or liquids containing benzoyl peroxide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to benzoyl peroxide may occur and control methods which may be effective in each case:

Operation	Controls
Use as free radical initiator for polymerization of many vinyl monomers in manufacture of a variety of plastics; use in manufacture of polyester resins as initiator for polymerization of unsaturated polyesters; room temperature curing agent for polyester resins, for auto-repair kits, optical and dental castings, and other molding applications	Local exhaust ventilation; personal protective equipment
Use in vulcanization of natural and synthetic rubber for rubber cements, silicone rubbers and polyester rubbers; use in textile manufacture as a burn-out agent for cellulose acetate in mixed fabrics with viscose, silk, or cotton to produce lace-like appearance; use in printing paste	Local exhaust ventilation; personal protective equipment
Use as a bleaching agent for flour, cheese, fats, oils, and waxes; use in manufacture of pharmaceuticals as ingredient of skin creams for burns, dermatitis, poisoning, and external wounds	Local exhaust ventilation; personal protective equipment
Use in manufacture of special fast-drying printing inks for printing on plastic surfaces; use as initiator for addition and substitution reactions in organic synthesis	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If benzoyl peroxide or liquids containing benzoyl peroxide get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If benzoyl peroxide or liquids containing benzoyl peroxide get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If benzoyl peroxide or liquids containing benzoyl peroxide penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Swallowing**

When benzoyl peroxide or liquids containing benzoyl peroxide have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and cloth-

ing should be restricted from areas of spills until cleanup has been completed.

• If benzoyl peroxide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Submerge in excess of water. Treat small portions of the slurry at a time with about ten times its weight of 10% sodium hydroxide solution. This slurry can then be disposed in a secured sanitary landfill.
3. Do not use spark generating or cellulosic materials (paper, wood, etc). for sweeping or handling spilled benzoyl peroxide.
4. Or, for liquids containing benzoyl peroxide, add vermiculite or perlite to spill in at least equal weight to the spill. Drain off water and burn carefully in a suitable unconfined (open) combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal method:

See above.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Benzoyl Peroxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Eaglstein, W. H.: "Allergic Contact Dermatitis to Benzoyl Peroxide - Report of Cases," *Archives of Dermatology*, 97:527, 1968.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-81, Benzoyl Peroxide*, Washington, D.C., 1960.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Benzoyl Peroxide*, HEW Publication No. (NIOSH) 77-166, GPO No. 017-033-00221-5, U.S. Government Printing Office, Washington, D.C., 1977.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Van Duuren, B. L., et al.: "Carcinogenicity of Epoxides, Lactones, and Peroxy Compounds," *Journal of the National Cancer Institute*, 31:41-55, 1963.

RESPIRATORY PROTECTION FOR BENZOYL PEROXIDE

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
25 mg/m³ or less**	Any dust and mist respirator containing non-oxidizable sorbents, except single-use respirators.***
50 mg/m³ or less**	Any dust and mist respirator containing non-oxidizable sorbents, except single-use or quarter-mask respirator.*** Any fume or high efficiency particulate respirator containing non-oxidizable sorbents.*** Any supplied-air respirator. Any self-contained breathing apparatus.
250 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece containing non-oxidizable sorbents.*** Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 mg/m³ or less	A powered air-purifying respirator with a full facepiece, helmet, or hood and high efficiency particulate filter containing non-oxidizable sorbents.*** A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator containing non-oxidizable sorbents, except single-use respirator.*** Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

***Benzoyl peroxide is a strong oxidizer and should not come in contact with oxidizable materials. Some cartridges and canisters may contain activated charcoal and should not be used to provide protection against benzoyl peroxide. Only non-oxidizable sorbents are recommended.

Occupational Health Guideline for Boron Oxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: B_2O_3
- Synonyms: Anhydrous boric acid; boric anhydride; boric oxide
- Appearance and odor: Colorless glassy granules or flakes with no odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for boron oxide is 15 milligrams of boron oxide per cubic meter of air (mg/m³) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for boron oxide a Threshold Limit Value of 10 mg/m³.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Boron oxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to boron oxide has caused irritation of the eyes, nose, and skin of animals. It may have the same effects on humans.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to boron oxide.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to boron oxide at potentially hazardous levels.

- **Summary of toxicology**

Boron oxide aerosol is of low toxicity; at high levels, it is mildly irritating to the mucous membranes of animals. Repeated exposure of rats to an aerosol at a concentration of 470 mg/m³ for 10 weeks caused only mild nasal irritation; repeated exposure of rats to 77 mg/m³ for 23 weeks resulted in elevated creatinine and boron content of the urine, in addition to increased urinary volume. Conjunctivitis resulted when the dust was applied to the eyes of rabbits, probably the result of the exothermic reaction of boron oxide with water to form boric acid; topical application of boron oxide dust to the clipped backs of rabbits produced erythema that persisted for 2 to 3 days.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 69.9
  2. Boiling point (760 mm Hg): 2550 C (4622 F)
  3. Specific gravity (water = 1): 1.84
  4. Vapor density (air = 1 at boiling point of boron oxide): Not applicable
  5. Melting point: 450 C (842 F) (approximate)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 2.77
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

• **Warning properties**
Grant states that boron oxide "tested on rabbit eyes in the form of a dust has been found to cause almost immediate irritation of the conjunctiva."

MONITORING AND MEASUREMENT PROCEDURES

• **General**
Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).
• **Method**
Sampling and analyses may be performed by collection of boron oxide on a filter, followed by gravimetric analysis. An analytical method for boron oxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with boron oxide or liquids containing boron oxide.
• Non-impervious clothing which becomes contaminated with boron oxide should be removed promptly and not reworn until the boron oxide is removed from the clothing.
• Employees should be provided with and required to use dust- and splash-proof safety goggles where boron oxide or non-aqueous liquids containing boron oxide may contact the eyes.

SANITATION

• Skin that becomes contaminated with boron oxide should be promptly washed or showered with soap or mild detergent and water to remove any boron oxide.
• Employees who handle boron oxide or non-aqueous liquids containing boron oxide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to boron oxide may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of metal borates and in preparation of fluxes; use in manufacture of glass for heat-resistance	Process enclosure; local exhaust ventilation; personal protective equipment
Application as a herbicide	Personal protective equipment
Use in production of surface coatings as fire-resistant additive in enamel and paints	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If boron oxide or non-aqueous liquids containing boron oxide get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If boron oxide or liquids containing boron oxide get on the skin, promptly flush the contaminated skin with water. If boron oxide or liquids containing boron oxide penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of boron oxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration.

Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When boron oxide or non-aqueous liquids containing boron oxide have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If boron oxide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in sealed containers in a secured sanitary landfill.

• Waste disposal method:

Boron oxide may be disposed of in sealed containers in a secured sanitary landfill.

• Respiratory Protection for Chemical Hazards

• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Boron Oxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Wilding, J. L., et al.: "The Toxicity of Boron Oxide," *American Industrial Hygiene Association Journal*, 20:284-289, 1959.

RESPIRATORY PROTECTION FOR BORON OXIDE

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Dust Concentration	
75 mg/m³ or less**	Any dust respirator, except single-use.
150 mg/m³ or less**	Any dust respirator, except single-use or quarter-mask respirator.
Dust or Fume Concentration	
150 mg/m³ or less**	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
7500 mg/m³ or less	A powered air-purifying respirator with a full facepiece, helmet, or hood and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 7500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Boron Trifluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: BF_3
- Synonyms: None
- Appearance and odor: Colorless gas which fumes in moist air and has a pungent, irritating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for boron trifluoride is a ceiling level of 1 part of boron trifluoride per million parts of air (ppm). This may also be expressed as 3 milligrams of boron trifluoride per cubic meter of air (mg/m^3). NIOSH has completed a criteria document for boron trifluoride but, due to the unavailability of a reliable measurement method, an environmental limit has not been recommended. For more detailed information, consult the NIOSH Criteria Document for Boron Trifluoride.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Boron trifluoride can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Boron trifluoride may cause nasal irritation and severe irritation of the eyes and skin. Animals exposed to elevated levels of boron trifluoride have developed pneumonia and kidney damage.

2. Long-term Exposure: Repeated or prolonged exposure to boron trifluoride may cause nasal dryness and nose bleeding.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to boron trifluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to boron trifluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system and kidneys should be stressed. The skin and eyes should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Boron trifluoride causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Boron trifluoride is a severe pulmonary irritant in animals. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when signs and symptoms of respiratory disease occur.

- **Summary of toxicology**

Boron trifluoride gas is a severe irritant of the lungs, eyes, and skin. Exposure of six animal species to 100 ppm, 4 to 7 hours/day, 5 days/week in a 30-day experiment killed all animals, most within the test period. Guinea pigs were the most susceptible, with 40 dead in two days. Dogs were the least susceptible, all dying after the test period. The primary site of damage was the lung, with severe irritation leading to death by pneumonia. Kidney damage, leading to nephritis, also occurs. Morbidity and mortality at lower levels of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

exposure were proportionate to the concentration time. Bronchitis, kidney damage, retarded growth, and fibrosis of teeth and bones occur in surviving animals. Exposure of 6 animal species to 100 ppm for 30 days resulted in a high mortality rate. Exposure of animals to a concentration of 42 mg/m³ (approximately 15 ppm) for an unspecified time period was fatal in some cases; autopsy findings were pneumonitis and degenerative changes in the renal tubules. Repeated exposure of mice to 15 ppm for 30 days resulted in mortality of 19% due to pulmonary irritation; rats similarly exposed for 2 weeks developed hypoplasia of the teeth and deposition of fluoride up to 25 times normal levels, both in the incisors and in femoral epiphyses. Three species of animals repeatedly exposed to levels of 12.8, 7.7, or 3 ppm for periods up to 6 months developed pneumonitis and evidence of dental fluorosis; high concentrations caused deaths in guinea pigs. In humans, the gas in high concentration produces burns of the eyes and skin similar to those caused by hydrogen fluoride, but less severe. Workers exposed to concentrations of up to 90 mg/m³ (approximately 32 ppm) for 10 to 15 years developed dryness of the nasal mucous membranes and epistaxis (nosebleed).

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 67.8
  2. Boiling point (760 mm Hg): −100.4 C (−149 F)
  3. Specific gravity (water = 1): 1.6 (liquid)
  4. Vapor density (air = 1 at boiling point of boron trifluoride): 2.3
  5. Melting point: −127 C (−197 F)
  6. Vapor pressure at 20 C (68 F): Greater than 1 atm.
  7. Solubility in water, g/100 g water at 20 C (68 F): Dissolves with evolution of heat (369 g/100 g water at 6 C (42.8 F))
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Boron trifluoride reacts with alkalies. It fumes strongly in moist air forming particulates which may reduce visibility.
  3. Hazardous decomposition products: Toxic gases and vapors (such as boric acid and fluoroboric acid) may be released when boron trifluoride decomposes.
  4. Special precautions: Boron trifluoride will attack some forms of plastics, rubber, and coatings. See 29 CFR 1910.101 for specific regulations on storage of compressed gas cylinders.
- **Flammability**
  1. Not combustible
- **Warning properties**
  1. Odor Threshold: Stauden states that "boron trifluoride, BF_3, is a colorless gas in a dry atmosphere, but it fumes in the presence of moisture, producing a dense white smoke. Upon hydrolysis, it generates an acidic, pungent odor that is irritating but not appreciably toxic." No quantitative information is available concerning the odor threshold of boron trifluoride.
  2. Eye Irritation Level: The ILO states that "the principal feature in the acute action of this substance is the irritation of the mucous membranes of the respiratory tract and eyes." No quantitative information is available concerning the levels which produce eye irritation.
  3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of boron trifluoride, this gas is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of boron trifluoride. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

At the time of publication of this guideline, no measurement method for boron trifluoride had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to boron trifluoride may occur and control methods which may be effective in each case:

Operation	Controls
Use as a Lewis acid catalyst for alkylation of aromatic compounds; use in polymer technology in manufacture of phenolic and epoxy resins	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protection equipment
Use in synthesis of other boron-containing organic and inorganic compounds; use in purification of hydrocarbons to remove unsaturates and sulfur-, nitrogen-, and oxygen-containing compounds	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protection equipment
Use in nuclear technology for separation of boron isotopes; as a filling gas for neutron counters	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protection equipment
Use in metallurgy as flux and antioxidant; use as flame-coloring agent for liquefied petroleum gas	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protection equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If strong concentrations of boron trifluoride gas get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If strong concentrations of boron trifluoride gas contact the skin, immediately flush the contaminated skin with water. If strong concentrations of boron trifluoride gas penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of boron trifluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If boron trifluoride is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse the gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• Allied Chemical Corporation: *Material Safety Data Sheet - Boron Trifluoride*, Morristown, New Jersey.

• American Conference of Governmental Industrial Hygienists: "Boron Trifluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Dibbell, D. G., et al.: "Hydrofluoric Acid Burns of the Hand," *Journal of Bone and Joint Surgery*, 52A:931-936, 1970.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Levinskas, G. J.: *Boron, Metallo-Boron Compounds and Boranes*, ed. by R. M. Adams, Interscience, New York, 1964, p. 726.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Boron Trifluoride*, HEW Publi-

cation No. (NIOSH) 77-122, GPO No. 017-033-00178-2, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Vol. 9, Interscience, New York, 1972.

• Torkelson, T.R., et al.: "The Toxicity of Boron Trifluoride when Inhaled by Laboratory Animals," *AmericanIndustrial Hygiene Association Journal*, 22:263-270, 1961.

• Voegtlin, C., and Hodge, H. C.: *Pharmacology and Toxicology of Uranium Compounds*, Vol. 4, Mc-Graw Hill, New York, 1953.

RESPIRATORY PROTECTION FOR BORON TRIFLUORIDE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Gas Concentration	
10 ppm or less**	Any supplied-air respirator. Any self-contained breathing apparatus.
50 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 100 ppm*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against boron trifluoride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of boron trifluoride; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 100 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Bromine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Br_2
- Synonyms: None
- Appearance and odor: Heavy, red-brown, fuming liquid. The vapor has an irritating odor and causes choking and lacrimation.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for bromine is 0.1 part of bromine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.7 milligram of bromine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Bromine can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Bromine vapor is a severe irritant of the respiratory tract and eyes. Severe breathing difficulties may occur. These breathing difficulties may be delayed in onset. Pneumonia may be produced. Dizziness, headache, nose bleeds, and cough may occur, followed some hours later by abdominal pain, diarrhea, and sometimes a measles-like rash. The liquid or concentrated vapor in contact with the eyes will cause severe painful burns. If liquid bromine gets on the skin and is not removed immediately, severe burns may result, leading to the development of deep-seated ulcers which heal slowly.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to bromine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to bromine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system and eyes should be stressed. The skin should be examined for evidence of chronic disorders.

—FVC and FEV (1 sec): Bromine is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—14" x 17" chest roentgenogram: Bromine may cause human lung damage. Surveillance of the lungs is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when signs and symptoms of respiratory disease occur.

- **Summary of toxicology**

Bromine vapor is a severe respiratory and eye irritant, and the liquid causes skin burns. Exposure of three animal species to 180 ppm for 7 hours caused severe eye irritation with clouding of the cornea, severe irritation of the respiratory tract, dyspnea, and some fatalities. In humans, 10 ppm is intolerable, causing severe irritation of the upper respiratory tract; lacrimation occurs at levels below 1 ppm. Symptoms in humans also include dizziness, headache, epistaxis, and coughing, followed some hours later by abdominal pain, diarrhea, and sometimes by a measles-like eruption on the face, trunk,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

and extremities. Pulmonary edema and pneumonia may be a delayed complication of severe exposures. The liquid or concentrated vapor in contact with the eye will cause severe and painful burns. Liquid bromine spilled on the skin causes a mild cooling sensation on first contact followed by a burning sensation. If bromine is not removed from the skin immediately, deep surface burns result; brown discoloration appears, leading to the development of deep-seated ulcers which heal slowly.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 159.8
2. Boiling point (760 mm Hg): 58.8 C (138 F)
3. Specific gravity (water = 1): 3.12
4. Vapor density (air = 1 at boiling point of bromine): 5.5
5. Melting point: −7.3 C (19 F)
6. Vapor pressure at 20 C (68 F): 175 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 3.5
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat may rupture containers.
2. Incompatibilities: Contact of bromine with combustible organic or other readily oxidizable materials may cause fires and explosions. Contact of bromine liquid with aqueous ammonia may cause violent reactions. Anhydrous bromine will react violently with aluminum, titanium, mercury, and potassium. Wet bromine also reacts with other metals.
3. Hazardous decomposition products: None
4. Special precautions: Bromine will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible by itself, but it is a strong oxidizing material reactive with many substances.

- **Warning properties**

1. Odor Threshold: Both Patty and the Pennsylvania Department of Environmental Resources, Occupational Health Division, report that odor threshold is 3.5 ppm; May reports an odor threshold of 1 ppm; Thienes and Haley report 0.05 ppm. The 0.05 ppm was confirmed by Leohardos and Kendall in the *Journal of the Air Pollution Control Association*, Vol. 19, 1969. For the purposes of this guideline, bromine is treated as a substance with adequate warning properties.
2. Irritation Levels: According to the *Hygienic Guide* of the Pennsylvania Department of Environmental Resources, bromine "is a primary irritant of the mucous membranes, and irritation to the eyes and upper and lower respiratory tracts is generally produced." Both the Manufacturing Chemists Association and the AIHA *Hygienic Guide* note that exposure to a concentration below 1 ppm bromine causes lacrimation. The AIHA *Hygienic Guide* points out that "undisturbed work is possible when the concentration is 0.15 to 0.3 ppm and impossible at 0.6 ppm."
3. Evaluation of Warning Properties: Based upon the information given above, it appears that bromine can be detected below the threshold limit value. Therefore, for the purposes of this guideline, bromine is treated as a substance with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for bromine had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid bromine.
- Where there is any possibility of exposure of an employee's body to liquid bromine, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with bromine should be removed immediately and not reworn until the bromine is removed from the clothing.
• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid bromine contacting the eyes.
• Where there is any possibility that employees' eyes may be exposed to liquid bromine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with bromine should be immediately washed or showered with soap or mild detergent and water to remove any bromine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to bromine may occur and control methods which may be effective in each case:

Operation	Controls
Use during synthesis of ethylene dibromide; use in manufacture of pesticides	Process enclosure; local exhaust ventilation
Use as a laboratory reagent; use as a sanitizing, disinfecting, and bleaching agent	Local exhaust ventilation; personal protective equipment
Use in preparation of flame retardants in plastics and fiber industry; use in manufacture of organic and inorganic compounds for use in photography, pharmaceuticals, fungicides, intermediates, dyes and dyestuffs, war gas, and bleaching agents	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If liquid bromine or strong concentrations of bromine vapor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid bromine gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid bromine soaks through the clothing, remove the clothing immediately and flush the skin using soap or mild detergent and water. If irritation or burns are present after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of bromine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When liquid bromine has been swallowed and the person is conscious, give the person large quantities of water immediately to dilute the bromine. Do not attempt to make the person vomit. Get medical attention immediately. (If milk is immediately available, give the person milk instead of water).
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If bromine is spilled or leaked, the following steps should be taken:
1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material or pour sodium thiosulfate or lime water over small spills.
• Waste disposal method:
Bromine may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in sealed containers in a secured sanitary landfill.

ADDITIONAL INFORMATION

To find additional information on bromine, look up bromine in the following documents:
• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards
These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Bromine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Bromine," *Hygienic Guide Series*, Detroit, Michigan, 1958.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dow Chemical Company: *Material Safety Data Sheet - Bromine*, Midland, Michigan, 1971.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• *Hygienic Information Guide No. 52 - Bromine*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Leohardos, G., and Kendall, D. A.: "Odor Threshold Determinations of 53 Odorant Chemicals," *Journal of the Air Pollution Control Association*, 19:91, 1969.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-49, Bromine*, Washington, D.C., 1968.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR BROMINE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Vapor Concentration	
5 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) containing non-combustible sorbents and providing protection against bromine. A gas mask with a chin-style or a front- or back-mounted canister containing non-combustible sorbents and providing protection against bromine. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-combustible sorbents and providing protection against bromine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Bromoform

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CHBr_3$
- Synonyms: Tribromomethane
- Appearance and odor: Colorless to yellow liquid with an odor like chloroform.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for bromoform is 0.5 part of bromoform per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 5 milligrams of bromoform per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Bromoform can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Bromoform can cause irritation of the eyes, nose, and throat. Swallowing bromoform may also cause dizziness, disorientation and slurred speech, unconsciousness, and death.

2. Long-term Exposure: Bromoform may cause liver damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to bromoform.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to bromoform at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from bromoform exposure.

—Skin disease: Bromoform can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Bromoform has been reported to be a liver toxin in animals, and justifies consideration before exposing persons with impaired liver function.

—Kidney disease: Although bromoform is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of bromoform might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Bromoform vapor is a respiratory irritant, a narcotic, and an hepatotoxin. A saturated atmosphere of 7000 ppm or more produced anesthesia in dogs in 8 minutes and death in 60 minutes, with evidence of respiratory irritation and liver damage. Human exposure to the vapor causes irritation of the eyes and throat. Accidental ingestion of the liquid by children produced central nervous system depression with coma and loss of reflexes; smaller doses led to listlessness, headache, and vertigo. Chronic effects have not been reported from

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

industrial exposure. Skin absorption is said to have been demonstrated.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 252.8
  2. Boiling point (760 mm Hg): 148 C (298 F)
  3. Specific gravity (water = 1): 2.85
  4. Vapor density (air = 1 at boiling point of bromoform): 8.7
  5. Melting point: 7.8 C (46 F)
  6. Vapor pressure at 20 C (68 F): 5 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.1
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Bromoform reacts with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, and magnesium, and strong caustics.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen bromide and bromine) may be released in a fire involving bromoform.
  4. Special precautions: Liquid bromoform will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**

According to Patty, bromoform has a chloroformlike odor and is highly irritating. Since the TLV for bromoform was determined by taking into consideration its irritant effects, for the purposes of this guideline, bromoform is treated as a material with adequate warning properties.

Bromoform is an eye irritant, according to the *Documentation of TLV's.*

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of bromoform vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure bromoform may be used. An analytical method for bromoform is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid bromoform.
- Non-impervious clothing which becomes contaminated with liquid bromoform should be removed promptly and not reworn until the bromoform is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid bromoform may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid bromoform should be promptly washed or showered with soap or mild detergent and water to remove any bromoform.
- Eating and smoking should not be permitted in areas where bromoform is handled, processed, or stored.
- Employees who handle bromoform should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to bromoform may occur and control methods which may be effective in each case:

Operation	Controls
Use as a heavy liquid flotation agent in mineral separation-sedimentary petrographical surveys, geological assays, and purification of materials such as quartz	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in chemical and pharmaceutical synthesis in condensation reactions, and source of free radicals to initiate transformation of various compounds	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an industrial solvent in liquid-solvent extractions in nuclear magnetic resonance studies	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a flame retardant in compositions for cellulose and in microencapsulation	General dilution ventilation
Use as a catalyst, initiator, or sensitizer in polymer production, irradiation reactions, and vulcanization of rubber	Local exhaust ventilation; general dilution ventilation
Use as an ingredient in pharmaceuticals or medicinal products	Material substitution

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If bromoform gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If bromoform gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If bromoform soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of bromoform, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When bromoform has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If bromoform is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Bromoform may be disposed of by absorbing it in vermiculte, dry sand, earth, or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Bromoform," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chloroform," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR BROMOFORM

Condition	Minimum Respiratory Protection* Required Above 0.5 ppm
Vapor Concentration	
25 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Butadiene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2 = CHCH = CH_2$
- Synonyms: 1,3-Butadiene; divinyl; butadiene-1,3; biethylene; erythrene
- Appearance and odor: Colorless gas with a mildly aromatic odor at temperatures above −4.7 C (23.5 FBelow −4.7 C (23.5 F) butadiene is a colorless liquid with a mildly aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for butadiene is 1000 parts of butadiene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2200 milligrams of butadiene per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Butadiene can affect the body if it is inhaled or if the liquid comes in contact with the eyes or skin.

- **Effects of overexposure**

Overexposure to butadiene may cause irritation of the eyes, nose, and throat. It may also cause drowsiness and lightheadedness. Exposure to very high concentrations may cause unconsciousness and death. Spilled on the skin, it may cause frostbite and irritation.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to butadiene.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to butadiene at potentially hazardous levels.

- **Summary of toxicology**

Butadiene vapor is a narcotic at very high concentrations, with mild irritant properties. Deep anesthesia was induced in rabbits in 8 to 10 minutes at 200,000 to 250,000 ppm, although death occurred in 23 minutes at 250,000 ppm. Recovery from brief periods of anesthesia occurred within 2 minutes of terminating the exposure; no tissue changes were detectable microscopically after daily induction of anesthesia as many as 34 times. Daily exposure of various small animal species at 6700 ppm over 8 months resulted in no significant chronic effects. Human subjects tolerated 8000 ppm for 8 hours without apparent effect, other than slight irritation of the eyes and upper respiratory tract. No cases of serious illness arising from its industrial use have been reported. Contact of liquid butadiene with the skin causes a freezing burn.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 54.1
2. Boiling point (760 mm Hg): −4.7 C (23.5 F)
3. Specific gravity (water = 1): 0.62
4. Vapor density (air = 1 at boiling point of butadiene): 1.87
5. Melting point: −108.9 C (−164 F)
6. Vapor pressure at 20 C (68 F): 910 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.05
8. Evaporation rate (butyl acetate = 1): Greater than 25

- **Reactivity**

1. Conditions contributing to instability: Heat. Peroxides are formed when inhibitor concentration is not maintained at proper level. At elevated temperatures, such as in fire conditions, polymerization may take

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

place.

2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions. Contact with copper and copper alloys may cause formation of explosive copper compounds.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving butadiene.

4. Special precautions: Butadiene will attack some forms of plastics, rubber, and coatings. Butadiene in storage should be checked for proper inhibitor content, for self-polymerization, and for formation of peroxides that form when in contact with air and iron. Piping carrying butadiene may become plugged by formation of rubbery polymer.

• **Flammability**

1. Flash point: Not applicable (considered a gas for fire purposes)

2. Autoignition temperature: 450 C (842 F)

3. Flammable limits in air, % by volume: Lower: 2.0; Upper: 11.5

4. Extinguishant: Stop flow of gas.

• **Warning properties**

1. Odor Threshold: May reports an odor threshold of 0.16 ppm.

2. Eye Irritation Level: Grant states that "allegedly workmen exposed to vapors of butadiene (concentration or purity unspecified) have complained of irritation of eyes, nasal passages, throat, and lungs. However, a precise quantitative study has shown that even a concentration of 8000 ppm in air produces no symptoms in human beings. Dogs and rabbits exposed experimentally to as much as 6700 ppm 7-½ hours a day for 8 months have developed no histologically demonstrable abnormality in any part of the eyes."

3. Evaluation of Warning Properties: Since the odor threshold of butadiene is well below the permissible exposure limit, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of butadiene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure butadiene may be used. An analytical method for butadiene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6). Methods for Set G" (order number PB 265 026).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid butadiene or from contact with vessels containing liquid butadiene.

• Any clothing which becomes wet with liquid butadiene should be removed immediately and not reworn until the butadiene has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid butadiene may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to butadiene may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during molding and vulcanizing operations in processing of rubber products from styrene-butadiene (SBR) elastomer; polybutadiene elastomer into rubber products; manufacture of high-impact polystyrene containing SBR/polybutadiene elastomer and manufacture of SBR foams; processing into products of ABS resins and styrene-butadiene copolymer resins; processing of neoprene elastomers into rubber products; processing of nitrile elastomer into nitrile latexes and rubbers; processing of nitrile elastomer and PVC-nitrile polyblends into rubber products and calendered plastic products	General dilution ventilation; local exhaust ventilation
Use in manufacture of SBR elastomer, polybutadiene elastomer, neoprene elastomer, nitrile elastomer, and SB copolymer and ABS resins	General dilution; local exhaust ventilation; personal protective equipment
Use in manufacture of adiponitrile, cyclo-olefins, 1,4-hexadiene tetramethylene sulfone, and tetrahydrophthalic anhydride	General dilution; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid butadiene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid butadiene gets on the skin, immediately flus the contaminated skin with water. If liquid butadien soaks through the clothing, remove the clothing imme diately and flush the skin with water. Do not use hc water for flushing. If irritation persists after washing get medical attention.

• **Breathing**

If a person breathes in large amounts of butadiene move the exposed person to fresh air at once. I breathing has stopped, perform artificial respiration Keep the affected person warm and at rest. Get medica attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure If the exposed person has been overcome, notify some one else and put into effect the established emergency rescue procedures. Do not become a casualty. Under stand the facility's emergency rescue procedures an know the locations of rescue equipment before the nee arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and cloth ing should be restricted from areas of spills or leaks unti cleanup has been completed.

• If butadiene is spilled or leaked, the following step should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. If in liquid form, for small quantities, absorb on pape towels. Evaporate in a safe place (such as a fume hood) Allow sufficient time for evaporating vapors to com pletely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials Large quantities can be collected and atomized in a suitable combustion chamber.
4. If in gaseous form, stop flow of gas. If source of leal is a cylinder and the leak cannot be stopped in place remove the leaking cylinder to a safe place in the ope air and repair the leak or allow the cylinder to empty

• Waste disposal methods:

Butadiene may be disposed of:

1. If in liquid form, by atomizing in a suitable combus tion chamber.
2. If in gaseous form, by burning in a safe location or i a suitable combustion chamber.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Butadiene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- American Industrial Hygiene Association: "Butadiene," *Hygienic Guide Series*, Detroit, Michigan, 1963.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-55, Butadiene*, Washington, D.C., 1974.
- May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR BUTADIENE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
5000 ppm or less	A gas mask with a chin-style canister providing protection against butadiene.
8000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
20,000 ppm or less	A gas mask with a front- or back-mounted canister providing protection against butadiene. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 20,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against butadiene. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be us-

Occupational Health Guideline for 2-Butoxy Ethanol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_4H_9OCH_2CH_2OH$
- Synonyms: Butyl "Cellosolve"; ethylene glycol monobutyl ether; Dowanol EB; butyl oxitol; Jeffersol EB; Ektasolve EB
- Appearance and odor: Colorless liquid with a mild odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 2-butoxy ethanol is 50 parts of 2-butoxy ethanol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 240 milligrams of 2-butoxy ethanol per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for 2-butoxy ethanol from 50 ppm to 25 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

2-Butoxy ethanol can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin. It may enter the body through the skin.

- **Effects of overexposure**

Overexposure to high air levels of 2-butoxy ethanol may cause irritation of the eyes, nose, and throat. It may also cause a person to have dark red urine.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 2-butoxy ethanol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 2-butoxy ethanol at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver, kidneys, and lymphoid system should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: This compound has been shown to increase erythrocyte fragility in animals exposed repeatedly to 2-butoxy ethanol vapors. A complete blood count should be performed before exposure including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin, hematocrit, clotting time determinations, and red blood cell fragility test.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

2-Butoxy ethanol irritates the eyes and upper respiratory tract and is a hemolytic agent. The LC50 for mice was 700 ppm, with death due to lung and kidney injury. Repeated exposures of 100 to 400 ppm were non-lethal but caused visceral effects in animals: at the higher concentrations rats exhibited greatly increased erythrocyte fragility, hemoglobinuria and hematuria, pulmonary hemorrhage, and liver injury; at lower concentrations, increased red-cell fragility was the most sensitive criterion of effect, however transitory. The substance is metabolized to butoxyacetic acid, which appears in the urine of animals and man promptly following exposure,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

both are hemolytic agents. Human subjects inhaling 2-butoxy ethanol at 200 ppm for 8 hours had discomfort of the eyes, nose, and throat, although there were no objective signs of injury or increase in erythrocytic fragility; some individuals complained of discomfort at 100 ppm. This substance penetrates the skin readily, and this may account for more absorption than does inhalation in some cases. The liquid is damaging to the eye, producing pain, conjunctival irritation, and transitory injury to the cornea. Chronic systemic effects have not been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 118.2
  2. Boiling point (760 mm Hg): 171 C (340 F)
  3. Specific gravity (water = 1): 0.9
  4. Vapor density (air = 1 at boiling point of 2-butoxy ethanol): 4.1
  5. Melting point: −70 C (−94 F)
  6. Vapor pressure at 20 C (68 F): 0.6 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions below 48 C (118 F)
  8. Evaporation rate (butyl acetate = 1): 0.1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions. Contact with strong caustics may cause decomposition.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving 2-butoxy ethanol.
  4. Special precautions: 2-Butoxy ethanol will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 61 C (141 F) (closed cup)
  2. Autoignition temperature: 244 C (472 F)
  3. Flammable limits in air, % by volume: Lower: 1.1; Upper: 10.6
  4. Extinguishant: Carbon dioxide, dry chemical, alcohol foam
- **Warning properties**
  1. Odor Threshold: According to Patty, 2-butoxy ethanol has a mild ethereal odor, but no quantitative information is available concerning the odor threshold of this material.
  2. Eye Irritation Level: Browning reports that "in some investigations by Carpenter et al. on volunteer subjects, those inhaling 113 ppm for 4 hours reported nasal and ocular (irritation) with a slight increase in nasal discharge and occasional eructation."
  3. Other Information: Browning also reports that "in a second experiment a year later three subjects inhaled 195 ppm for two 4-hour periods separated by an interval of 30 min .... They all noted immediate irritation of the nose and throat and later of the eyes, and disturbed taste." Patty points out that in sensitive individuals 100 ppm can cause eye, nose, and throat irritation.
  4. Evaluation of Warning Properties: Through its irritant effects, 2-butoxy ethanol can be detected at concentrations only a few times the permissible exposure limit. For the purposes of this guideline, therefore, 2-butoxy ethanol is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of 2-butoxy ethanol vapors using an adsorption tube with subsequent desorption with methylene chloride and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 2-butoxy ethanol may be used. An analytical method for 2-butoxy ethanol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 2-butoxy ethanol.

• Clothing contaminated with liquid 2-butoxy ethanol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 2-butoxy ethanol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 2-butoxy ethanol, the person performing the operation should be informed of 2-butoxy ethanol's hazardous properties.

• Where exposure of an employee's body to liquid 2-butoxy ethanol may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with liquid 2-butoxy ethanol should be removed immediately and not reworn until the 2-butoxy ethanol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid 2-butoxy ethanol may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid 2-butoxy ethanol should be immediately washed or showered to remove any 2-butoxy ethanol.

• Employees who handle liquid 2-butoxy ethanol should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 2-butoxy ethanol may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from spray and brush application of lacquers, varnishes, and enamels	Process enclosure; local exhaust ventilation; personal protective equipment
Use in preparation of esters for textile treatment to produce "scroop"	Process enclosure; general dilution ventilation; personal protective equipment
Application as an industrial solvent	General dilution ventilation; personal protective equipment
Use in production of plasticizers for polyvinyl chloride and acetate	Process enclosure; general dilution ventilation; personal protective equipment
Use as a stabilizing agent in metal cleaners and liquid household cleaners	General dilution ventilation; personal protective equipment
Use in hydraulic fluids, insecticides, herbicides, and rust removers	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 2-butoxy ethanol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention if discomfort persists. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 2-butoxy ethanol gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 2-butoxy ethanol soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water.

• **Breathing**

If a person breathes in large amounts of 2-butoxy ethanol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 2-butoxy ethanol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 2-butoxy ethanol is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evapo-

rate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber.

• Waste disposal methods:

2-Butoxy ethanol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "2-Butoxy Ethanol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Carpenter, C. P., et al.: "Toxicity of Butyl Cellosolve Solvent," *A.M.A. Archives of Industrial Health*, 14:114-131, 1956.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Shell Chemical Company: *Material Safety Data Sheet - 2-Butoxy Ethanol.*

RESPIRATORY PROTECTION FOR 2-BUTOXY ETHANOL

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
700 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 700 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of 2-butoxy ethanol; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 700 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Butyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COO(CH_2)_3CH_3$
- Synonyms: n-Butyl acetate; butyl ethanoate; acetic acid butyl ester
- Appearance and odor: Colorless liquid with a fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for butyl acetate is 150 parts of butyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 710 milligrams of butyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Butyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to butyl acetate may cause irritation of the eyes, nose, and throat. Severe overexposure may cause weakness, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to butyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to butyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from butyl acetate exposure.

—Skin disease: Butyl acetate is a mild defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although butyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of butyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although butyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The principal effect of overexposure to butyl acetate is irritation of the eyes and nose, which occurs at 200 to 300 ppm and is marked at concentrations over 3000 ppm. Butyl acetate splashed in the eye causes marked irritation, but recovery is rapid. Anesthetic effects have been observed in animals at very high concentrations. Levels of 400 to 600 ppm in exposures of 2 to 3 hours' duration did not cause anesthetic effects in man. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 116
  2. Boiling point (760 mm Hg): 126 C (260 F)
  3. Specific gravity (water = 1): 0.88
  4. Vapor density (air = 1 at boiling point of butyl acetate): 4.0
  5. Melting point: −74 C (−101 F)
  6. Vapor pressure at 20 C (68 F): 10 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.68
  8. Evaporation rate (butyl acetate = 1): 1.0
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving butyl acetate.
  4. Special precautions: Butyl acetate will dissolve many plastics and resins.
- **Flammability**
  1. Flash point: 22 C (72 F) (closed cup)
  2. Autoignition temperature: 425 C (797 F)
  3. Flammable limits in air, % by volume: Lower: 1.7; Upper: 7.6
  4. Extinguishant: Dry chemical, carbon dioxide, foam
- **Warning properties**
  1. Odor Threshold: Summer and May report odor thresholds for butyl acetate of 7 ppm and 20 ppm, respectively.
  2. Eye Irritation Level: Grant reports that the vapor of butyl acetate "causes irritation of the eyes and nose, first noticeable to human beings at a concentration of 300 ppm in air, and objectionable at 3300 ppm; higher concentrations cause tearing and hyperemia of the conjunctiva."
  3. Evaluation of Warning Properties: Butyl acetate can be detected below the TLV through its odor, and at a concentration of only twice the TLV through its irritant effects. For the purposes of this guideline, therefore, butyl acetate is considered to have good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of butyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure butyl acetate may be used. An analytical method for butyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid butyl acetate.
- Clothing wet with liquid butyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of butyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the butyl acetate, the person performing the operation should be informed of butyl acetate's hazardous properties.
- Any clothing which becomes wet with liquid butyl acetate should be removed immediately and not reworn until the butyl acetate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid butyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid butyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any butyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to butyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Use during application of nitrocellulose by spraying, brushing, or dipping	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during application of surface coatings other than nitrocellulose lacquers, including paper coatings, leather coatings, and airplane dope enamel	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during manufacture of nitrocellulose lacquers	Local exhaust ventilation
Liberation during production of lacquer thinner	General dilution ventilation
Liberation during use as a solvent for oils, pitch, camphor, ethyl cellulose acetate, and chlorinated rubber	General dilution ventilation
Liberation during use as a solvent in production of artificial leather	General dilution ventilation
Liberation during use of protective coatings in automobile industry	Local exhaust ventilation
Liberation during use as a solvent for vinyl, polystyrene, and methacrylate plastics	Local exhaust ventilation
Liberation during manufacture of safety glass; during production of flavorings and perfumes; during manufacture of cosmetics, adhesives, shoe polishes, and stain removers	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If butyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If butyl acetate gets on the skin, promptly flush the contaminated skin with water. If butyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of butyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When butyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If butyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Butyl acetate should not be allowed to

enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Butyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Butyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 57 - Butyl Acetate*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Butyl Acetate*, New York, 1969.

• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters: Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 21:28-65, 1960.

RESPIRATORY PROTECTION FOR BUTYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 150 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
7500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for sec-Butyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOCH(CH_3)C_2H_5$
- Synonyms: 1-Methylpropyl acetate
- Appearance and odor: Colorless liquid with a pleasant odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sec-butyl acetate is 200 parts of sec-butyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 950 milligrams of sec-butyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

sec-Butyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to sec-butyl acetate may cause irritation of the eyes, nose, and throat. Severe overexposure may cause weakness, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sec-butyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sec-butyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from sec-butyl acetate exposure.

—Skin disease: sec-Butyl acetate is a mild defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although sec-butyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of sec-butyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although sec-butyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The principal effects of overexposure to sec-butyl acetate are irritation of the eyes and nose and narcosis at high concentrations. No chronic systemic effects have been reported in humans. Anesthetic effects were not observed in man at levels of 400 to 600 ppm in exposures of 2 to 3 hours.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 116
  2. Boiling point (760 mm Hg): 112 C (234 F)
  3. Specific gravity (water = 1): 0.86
  4. Vapor density (air = 1 at boiling point of sec-butyl acetate): 4.0
  5. Melting point: −95 C (−146 F)
  6. Vapor pressure at 20 C (68 F): 10 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.8
  8. Evaporation rate (butyl acetate = 1): 2.0
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving sec-butyl acetate.
  4. Special precautions: sec-Butyl acetate will soften and dissolve many plastics.
- **Flammability**
  1. Flash point: 16.7 C (62 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Lower: 1.7; Upper: 9.8
  4. Extinguishant: Dry chemical, carbon dioxide, foam
- **Warning properties**
  1. Odor Threshold: Both May and Summer report odor thresholds for isobutyl acetate and for butyl acetate of 4 ppm and 7 ppm, respectively. Although no quantitative information is available concerning the odor threshold of sec-butyl acetate, by analogy to isobutyl acetate and to butyl acetate, the odor of sec-butyl acetate is assumed to be detectable below the TLV (200 ppm). According to the *Documentation of TLVs*, however, "the odor of sec-butyl acetate is reportedly milder than that of the primary isomers."
  2. Eye Irritation Level: The TLV was recommended to prevent eye and respiratory tract irritation. No quantitative information is available, however, concerning the air concentrations of sec-butyl acetate which produce this irritation.
  3. Evaluation of Warning Properties: Since by analogy with isobutyl acetate and butyl acetate, the odor threshold of sec-butyl acetate is assumed to be below the TLV (200 ppm), sec-butyl acetate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of sec-butyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure sec-butyl acetate may be used. An analytical method for sec-butyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid sec-butyl acetate.
- Clothing wet with liquid sec-butyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of sec-butyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the sec-butyl acetate, the person performing the operation should be informed of sec-butyl acetate's hazardous properties.
- Any clothing which becomes wet with liquid sec-butyl acetate should be removed immediately and not

reworn until the sec-butyl acetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid sec-butyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid sec-butyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any sec-butyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sec-butyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during use as a solvent for coating paper or leather	Local exhaust ventilation; general dilution ventilation
Use as a solvent for artificial leather material	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during spray applications of lacquers	Local exhaust ventilation; general dilution ventilation
Liberation during dip and brush applications of lacquers; during preparation of celluloid products; during preparation of lacquers	Process enclosure; general dilution ventilation
Liberation during application of adhesives	Local exhaust ventilation; general dilution ventilation
Liberation during manufacture of adhesives	Process enclosure; local exhaust ventilation; general dilution ventilation
Liberation during application of textile sizing	Local exhaust ventilation; general dilution ventilation
Liberation during manufacture of photographic film	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If sec-butyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If sec-butyl acetate gets on the skin, promptly flush the contaminated skin with water. If sec-butyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of sec-butyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When sec-butyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If sec-butyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. sec-Butyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

sec-Butyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

ADDITIONAL INFORMATION

To find additional information on sec-butyl acetate, look up sec-butyl acetate in the following documents:

- Medical Surveillance for Chemical Hazards
- Respiratory Protection for Chemical Hazards
- Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "sec-Butyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
- Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
- Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.
- Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – sec-Butyl Acetate*, New York, 1969.

RESPIRATORY PROTECTION FOR SEC-BUTYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
10,000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for tert-Butyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOC(CH_3)_3$
- Synonyms: Acetic acid, tert-butyl ester
- Appearance and odor: Colorless liquid with a fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tert-butyl acetate is 200 parts of tert-butyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 950 milligrams of tert-butyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

tert-Butyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to tert-butyl acetate may cause irritation of the eyes, nose, and throat. Severe overexposure may cause weakness, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tert-butyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tert-butyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from tert-butyl acetate exposure.

—Kidney disease: Although tert-butyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of tert-butyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although tert-butyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Skin disease: tert-Butyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Central nervous system depression may occur on exposure to high concentrations of tert-butyl acetate, producing narcosis. Irritation of the eyes, skin, and upper respiratory tract may occur.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 116
  2. Boiling point (760 mm Hg): 98 C (208 F)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

3. Specific gravity (water = 1): 0.87

4. Vapor density (air = 1 at boiling point of tert-butyl acetate): 4.0

5. Melting point: Data not available

6. Vapor pressure at 20 C (68 F): Data not available

7. Solubility in water, g/100 g water at 20 C (68 F): Data not available

8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving tert-butyl acetate.

4. Special precautions: tert-Butyl acetate may soften or dissolve plastics.

• **Flammability**

1. Flash point: Between 17 to 22 C (62 to 72 F) (estimated)

2. Autoignition temperature: Data not available

3. Flammable limits in air, % by volume: Lower: 1.5 (estimated)

4. Extinguishant: Dry chemical, foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: Both May and Summer report odor thresholds for isobutyl acetate and for butyl acetate of 4 ppm and 7 ppm, respectively. Although no quantitative information is available concerning the odor threshold of tert-butyl acetate, its odor is also assumed to be detectable below the TLV.

2. Eye Irritation Level: According to the *Documentation of TLV's*, "the irritative . . . effects of the the acetates appear to be related to their physical properties, the higher boiling members being the more toxic. tert-Butyl acetate has the lowest boiling point of the four isomers of this ester."

'A limit of 200 ppm, slightly higher than that for the normal isomer, is recommended to prevent significant irritation of the eyes and respiratory passages."

3. Evaluation of Warning Properties: By analogy with isobutyl acetate and butyl acetate, which have odor thresholds of 4 and 7 ppm respectively, for the purposes of this guideline, the odor threshold of tert-butyl acetate is assumed to be below the TLV (200 ppm). Therefore, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of tert-butyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure tert-butyl acetate may be used. An analytical method for tert-butyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid tert-butyl acetate.

• Clothing wet with liquid tert-butyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tert-butyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tert-butyl acetate, the person performing the operation should be informed of tert-butyl acetate's hazardous properties.

• Any clothing which becomes wet with liquid tert-butyl acetate should be removed immediately and not

reworn until the tert-butyl acetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid tert-butyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid tert-butyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any tert-butyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tert-butyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during use as a dry cleaning agent	General dilution ventilation
Liberation during spray application on surface coatings	Process enclosure; general dilution ventilation
Liberation during formulation of paint systems	Local exhaust ventilation
Liberation during use as an additive to improve antiknock properties of leaded aliphatic gasoline	Process enclosure; general dilution ventilation
Liberation during use as an activator in alkaline polymerization of caprolactam	Process enclosure; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If tert-butyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If tert-butyl acetate gets on the skin, promptly flush the contaminated skin with water. If tert-butyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of tert-butyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When tert-butyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If tert-butyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. tert-Butyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

tert-Butyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "tert-Butyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

RESPIRATORY PROTECTION FOR TERT-BUTYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
8000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Butyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CH_2CH_2CH_2OH$
- Synonyms: 1-Butanol; propylcarbinol; n-butanol; n-butyl alcohol; NBA
- Appearance and odor: Colorless liquid with a strong, characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for butyl alcohol is 100 parts of butyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 300 milligrams of butyl alcohol per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has recommended for butyl alcohol a Threshold Limit Value of 50 ppm as a ceiling value and with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Butyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to butyl alcohol may cause irritation of the eyes, nose, and throat, headache, dizziness, and drowsiness. The overexposed person may also experience blurred vision and a burning sensation of the eyes, which may last for several days.

2. Long-term Exposure: Drying and cracking of the skin may result from prolonged skin exposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to butyl alcohol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to butyl alcohol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from butyl alcohol exposure.

—Skin disease: Butyl alcohol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although butyl alcohol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although butyl alcohol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Eye disease: Because butyl alcohol is reported to cause eye injury, those with pre-existing eye disease may be at increased risk.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of butyl alcohol might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Butyl alcohol is an eye and mucous membrane irritant, and the vapor has a narcotic effect on animals at concentrations in excess of 6000 to 8000 ppm. Also,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

cases of vacuolar keratitis have been reported in humans. Mild narcotic effects have been observed in humans exposed to high concentrations. Mild skin irritation occurs due to defatting action. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 74
  2. Boiling point (760 mm Hg): 118 C (244 F)
  3. Specific gravity (water = 1): 0.8
  4. Vapor density (air = 1 at boiling point of butyl alcohol): 2.6
  5. Melting point: −89 C (−128 F)
  6. Vapor pressure at 20 C (68 F): 4.2 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 7.7
  8. Evaporation rate (butyl acetate = 1): 0.46
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fire and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving butyl alcohol.
  4. Special precautions: Butyl alcohol will attack some forms of plastics, rubber, and coatings. Butyl alcohol may react with metallic aluminum at high temperatures.
- **Flammability**
  1. Flash point: 28.9 C (84 F) (closed cup)
  2. Autoignition temperature: 365 C (689 F)
  3. Flammable limits in air, % by volume: Lower: 1.4; Upper: 11.2
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Summer and May report an odor threshold of 11 ppm. Patty reports that "Scherberger, Happ, Miller, and Fassett determined that the minimum concentration with identifiable odor of butyl alcohol was 15 ppm."
  2. Eye Irritation Level: The *Documentation of TLV's* states that "Tabershaw et al. reported eye irritation in workmen in concentrations above 55 ppm . . . ." According to Patty, Nelson reported mild eye irritation at 25 ppm. Sterner and associates, however, "revealed little or no irritation or complaints among workers when the average concentration was 100 ppm."
  3. Other Information: Patty states that "Nelson et al. reported mild irritation of the nose, throat, and eyes of subjects briefly exposed to 25 ppm and stated that exposure to 50 ppm was objectionable because it produced irritation of the throat in all subjects and mild headaches in some instances."
  4. Evaluation of Warning Properties: Because of its odor and irritant effects, butyl alcohol is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of butyl alcohol. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of butyl alcohol vapors using an adsorption tube with subsequent desorption with 2-propanol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure butyl alcohol may be used. An analytical method for butyl alcohol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which

includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid butyl alcohol.
- Clothing wet with liquid butyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of butyl alcohol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the butyl alcohol, the person performing the operation should be informed of butyl alcohol's hazardous properties.
- Any clothing which becomes wet with liquid butyl alcohol should be removed immediately and not reworn until the butyl alcohol is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid butyl alcohol may contact the eyes.

SANITATION

- Skin that becomes wet with liquid butyl alcohol should be promptly washed or showered to remove any butyl alcohol.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to butyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Use and liberation in spray applications of surface coatings	Local exhaust ventilation; personal protective equipment
Use during brush or dip application of surface coatings	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in adhesives and as a solvent adhesive in manufacture of garments from fabric coated with polyvinyl butyral	General dilution ventilation; personal protective equipment
Use in leather industry	Local exhaust ventilation; general dilution ventilation
Liberation during manufacture of safety glass; during manufacture of derivatives of butyl alcohol, including chemicals, herbicides, ore flotation agents, urea and melamine formaldehyde resins, and pharmaceuticals	Local exhaust ventilation; general dilution ventilation
Use as a solvent or diluent in manufacture of brake fluids, perfumes, detergents, adhesives, denatured alcohol, and surface coatings	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during photographic processing operations	Local exhaust ventilation; general dilution ventilation
Use as a swelling agent in textiles	General dilution ventilation
Use as an azeotrophic dehydrating agent and blending agent in laboratory analysis; liberation as a by-product in furfural tetrahydrofuran conversion	General dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If butyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If butyl alcohol gets on the skin, promptly flush the contaminated skin with water. If butyl alcohol soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of butyl alcohol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When butyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If butyl alcohol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Butyl alcohol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Butyl alcohol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Butyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Butyl Alcohol," *Hygienic Guide Series*, Detroit, Michigan, 1955.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

RESPIRATORY PROTECTION FOR BUTYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
8000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for sec-Butyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CHOHCH_2CH_3$
- Synonyms: 2-Butanol; methyl ethyl carbinol; butylene hydrate; 2-hydroxybutane
- Appearance and odor: Colorless liquid with a strong, pleasant odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sec-butyl alcohol is 150 parts of sec-butyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 450 milligrams of sec-butyl alcohol per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for sec-butyl alcohol from 150 ppm to 100 ppm.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sec-butyl alcohol is 150 parts of sec-butyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 450 milligrams of sec-butyl alcohol per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

sec-Butyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to sec-butyl alcohol may cause irritation of the eyes, nose, and throat, headache, dizziness, and drowsiness.

2. Long-term Exposure: Drying and cracking of the skin may result from prolonged skin exposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sec-butyl alcohol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sec-butyl alcohol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from sec-butyl alcohol exposure.

—Skin disease: sec-Butyl alcohol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although sec-butyl alcohol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although sec-butyl alcohol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

sec-Butyl alcohol has a narcotic effect at high vapor concentrations. Rats exposed to 16,000 ppm for 4 hours died. Mice exposed to 5,330 ppm were narcotized but

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

survived, while mice exposed to 1650 ppm for 7 hours showed no signs of intoxication. The substance is regarded as an eye irritant, chiefly by analogy to n-butyl alcohol, since no symptoms or signs have been observed in workers exposed regularly at levels of 100 ppm. No chronic systemic effects have been reported in humans. Mild skin irritation may occur due to defatting action.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 74
  2. Boiling point (760 mm Hg): 99 C (211 F)
  3. Specific gravity (water = 1): 0.8
  4. Vapor density (air = 1 at boiling point of sec-butyl alcohol): 2.6
  5. Melting point: − 115 C (- 175 F)
  6. Vapor pressure at 20 C (68 F): 12.5 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 15.4
  8. Evaporation rate (butyl acetate = 1): 1.3
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving sec-butyl alcohol.
  4. Special precautions: sec-Butyl alcohol will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 24 C (75 F) (closed cup)
  2. Autoignition temperature: 405 C (761 F)
  3. Flammable limits in air, % by volume: Lower: 1.7; Upper: 9.8
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold for sec-butyl alcohol of 43 ppm.
  2. Eye Irritation Level: The *Documentation of TLV's* states that "no information is available on eye irritation from the vapor of sec-butyl alcohol. Liquid sec-butyl alcohol was less injurious to the eyes than n-butanol, however. This relatively meager information suggests that sec-butyl alcohol is somewhat less toxic and irritating than n-butanol. Many years of industrial experience with exposures approximating 100 ppm associated with manufacture have resulted in no difficulties. A threshold limit of 150 ppm is recommended, therefore, to prevent narcotic and irritative effects."
  3. Evaluation of Warning Properties: Since the odor threshold of sec-butyl alcohol is well below the permissible exposure limit, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of sec-butyl alcohol vapors using an adsorption tube with subsequent desorption with 2-propanol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure sec-butyl alcohol may be used. An analytical method for sec-butyl alcohol is in the *NIOSH Manuel of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid sec-butyl alcohol.
- Clothing wet with liquid sec-butyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of sec-butyl alcohol from the clothing. If the clothing is to

be laundered or otherwise cleaned to remove the sec-butyl alcohol, the person performing the operation should be informed of sec-butyl alcohol's hazardous properties.

• Any clothing which becomes wet with liquid sec-butyl alcohol should be removed immediately and not reworn until the sec-butyl alcohol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid sec-butyl alcohol may contact the eyes.

SANITATION

• Skin that becomes wet with liquid sec-butyl alcohol should be promptly washed or showered to remove any sec-butyl alcohol.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sec-butyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during spray application of ethyl cellulose-based surface coatings; during open-tank mixing of surface coatings, dyes, oils, etc.	Local exhaust ventilation; personal protective equipment
Liberation during use of industrial cleaning compounds	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during use of paint removers; during hand application of ethyl cellulose and nitrocellulose surface coatings	General dilution ventilation
Liberation during use of adhesives in manufacture of plywood; during manufacture of MEK, sec-butyl acetate, and xanthate; during mixing of hydraulic fluids, paint removers, perfumes, etc. in closed vessels	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If sec-butyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If sec-butyl alcohol gets on the skin, promptly flush the contaminated skin with water. If sec-butyl alcohol soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of sec-butyl alcohol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When sec-butyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If sec-butyl alcohol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. sec-Butyl alcohol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

sec-Butyl alcohol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "sec-Butyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

RESPIRATORY PROTECTION FOR SEC-BUTYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 150 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
7500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for tert-Butyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_3COH$
- Synonyms: 2-Methyl-2-propanol; TBA; trimethylcarbinol
- Appearance and odor: Colorless liquid or solid with a camphor-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tert-butyl alcohol is 100 parts of tert-butyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 300 milligrams of tert-butyl alcohol per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

tert-Butyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to tert-butyl alcohol may cause irritation of the eyes, nose, and throat, headache, dizziness, and drowsiness.

2. Long-term Exposure: Drying and cracking of the skin may result from prolonged skin exposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tert-butyl alcohol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tert-butyl alcohol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from tert-butyl alcohol exposure.

—Skin disease: tert-Butyl alcohol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although tert-butyl alcohol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although tert-butyl alcohol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of tert-butyl alcohol might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Experimental and clinical observations have been limited, but tert-butyl alcohol is regarded primarily as a narcotic, with the potential of causing drowsiness from exposure to high concentrations of the vapor. Repeated daily narcotic doses were not fatal to animals, and no injurious effects resulted from a long-continued dosage. It is also considered to be a mild skin irritant. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 74
  2. Boiling point (760 mm Hg): 83 C (181 F)
  3. Specific gravity (water = 1): 0.8
  4. Vapor density (air = 1 at boiling point of tert-butyl alcohol): 2.6
  5. Melting point: 25 C (77 F)
  6. Vapor pressure at 20 C (68 F): 31 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 1.05
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Strong mineral acids can cause decomposition to flammable isobutylene gas. Strong hydrochloric acid reacts with tert-butyl alcohol to form tert-butyl chloride, a volatile liquid.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide and isobutylene) may be released in a fire involving tert-butyl alcohol.
  4. Special precautions: tert-Butyl alcohol will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 11 C (52 F) (closed cup)
  2. Autoignition temperature: 480 C (896 F)
  3. Flammable limits in air, % by volume: Lower: 2.4; Upper: 8
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold of 73 ppm.
  2. Eye Irritation Level: tert-Butyl alcohol is not specifically known to be an eye irritant, but by analogy to the other butyl alcohols, which produce eye irritation at 100 ppm, it is treated as an eye irritant.
  3. Evaluation of Warning Properties: Since the odor threshold of tert-butyl alcohol is below the permissible exposure limit, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of tert-butyl alcohol vapors using an adsorption tube with subsequent desorption with 2-butanone in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure tert-butyl alcohol may be used. An analytical method for tert-butyl alcohol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid or solid tert-butyl alcohol.
- Clothing wet with liquid tert-butyl alcohol or heavily contaminated with solid tert-butyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tert-butyl alcohol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tert-butyl alcohol, the person performing the operation should be informed of tert-butyl alcohol's hazardous properties.
- Any clothing which becomes wet with liquid tert-butyl alcohol or heavily contaminated with solid tert-butyl alcohol should be removed immediately and not reworn until the tert-butyl alcohol is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where liquid or solid tert-butyl alcohol may contact the eyes.

SANITATION

• Skin that becomes wet with liquid tert-butyl alcohol or heavily contaminated with solid tert-butyl alcohol should be promptly washed or showered to remove any tert-butyl alcohol.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tert-butyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during vapor application of lacquer surface coatings; during use of industrial cleaning compounds	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a chemical intermediate in manufacture of tert-butyl chloride and tert-butyl phenol	Local exhaust ventilation; general dilution ventilation
Liberation during mixing of perfumes, lacquers, and denatured alcohol in open-surface tanks	Local exhaust ventilation; general dilution ventilation
Use as a solvent for drug extraction, water removal, wax solvent, extraction of hypochlorous acid lube oil, and laboratory procedures	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If tert-butyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If tert-butyl alcohol gets on the skin, promptly flush the contaminated skin with water. If tert-butyl alcohol soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of tert-butyl alcohol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When tert-butyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If tert-butyl alcohol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. tert-Butyl alcohol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

tert-Butyl alcohol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "tert-Butyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

RESPIRATORY PROTECTION FOR TERT-BUTYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
8000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for tert-Butyl Chromate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $((CH_3)_3CO)_2CrO_2$
- Synonyms: Chromic acid, di-tert-butyl ester; bis(tert-butyl) chromate
- Appearance: Liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tert-butyl chromate is a ceiling level of 0.1 milligram of tert-butyl chromate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

tert-Butyl chromate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Animal experiments suggest that tert-butyl chromate may cause lung changes, drowsiness, staggering gait, muscular weakness, and burns of the skin and eyes. Inorganic hexavalent chromium compounds may cause cancer of the lungs and sinuses. Delayed breathing difficulties may occur.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tert-butyl chromate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tert-butyl chromate at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory tract, liver, central nervous system, and eyes should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Because inorganic hexavalent chromium salts cause lung cancer in humans, surveillance of the lungs is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

tert-Butyl chromate has been reported to be an irritant of the eyes, lungs, and skin and a mild narcotic in animals. Rats repeatedly exposed daily for 30-60 minutes to an unspecified but lethal concentration of vapor of a mixture of tert-butyl chromate and butyl alcohol displayed lacrimation, drowsiness, ataxia, prostration, muscular weakness and twitching, weight loss, rapid superficial respiration, and necrosis of skin and subcutaneous tissues. Autopsy revealed extensive epithelial exudation in the lung alveoli, and hemorrhage and fat deposition in the liver. In separate inhalation experiments, tert-butyl chromate caused mild narcosis and rapid respiration, while butyl alcohol caused rapid narcosis and slow respiration with no lacrimation or pulmonary irritation. A laboratory assistant engaged in packing metal articles in paraffin-impregnated paper containing 5% tertiary butyl chromate complained of giddiness and abdominal discomfort. The significance of this is unknown. Since tert-butyl chromate contains hexavalent chromium, it may be a human carcinogen by analogy to other hexavalent chromium compounds,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

which have been shown to cause lung and sinus cancer in man.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 230.3
  2. Boiling point (760 mm Hg): Data not available
  3. Specific gravity (water = 1): Data not available
  4. Vapor density (air = 1 at boiling point of tert-butyl chromate): 7.9
  5. Melting point: −5 to 0 C (23 to 32 F)
  6. Vapor pressure at 20 C (68 F): Data not available
  7. Solubility in water, g/100 g water at 20 C (68 F): Data not available
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Reducing agents, moisture
  3. Hazardous decomposition products: Toxic gases and vapors (such as chromium compounds and carbon monoxide) may be released when tert-butyl chromate decomposes.
  4. Special precautions: None
- **Flammability**
  1. Flash point: Data not available
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Data not available
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold.
  2. Eye Irritation Level: Since Grant reports that "chromium compounds (e.g., chromic acid, chromium chloride, potassium chromate, and potassium dichromate) are known to cause . . . ulcers of the skin and mucous membranes," tert-butyl chromate, for the purposes of this guideline, is treated as an eye irritant.
  3. Evaluation of Warning Properties: Since there is no quantitative information relating warning properties to air concentrations of tert-butyl chromate, it is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of tert-butyl chromate. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

At the time of publication of this guideline, no measurement method for tert-butyl chromate had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate.
- Clothing contaminated with tert-butyl chromate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tert-butyl chromate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tert-butyl chromate, the person performing the operation should be informed of tert-butyl chromate's hazardous properties.
- Where there is any possibility of exposure of an employee's body to solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with tert-butyl chromate should be removed immediately and not reworn until the tert-butyl chromate is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with tert-butyl chromate should be immediately washed or showered with soap or mild detergent and water to remove any tert-butyl chromate.

• Workers subject to skin contact with solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate should wash with soap or mild detergent and water any areas of the body which may have contacted tert-butyl chromate at the end of each work day.

• Eating and smoking should not be permitted in areas where solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate are handled, processed, or stored.

• Employees who handle solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tert-butyl chromate may occur and control methods which may be effective in each case:

Operation	Controls
Use in oxidation of steroids as a means of identification on paper chromatography	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of catalysts used for the polymerization of olefins (possible commercial use)	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of tert-butyl chromate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When solid or liquid tert-butyl chromate or liquids containing tert-butyl chromate have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If tert-butyl chromate is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

tert-Butyl chromate may be disposed by absorbing in vermiculite, dry sand, earth, or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "tertiary-Butyl Inorganic Hexavalent Chromium," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "tert-Butyl Chromate," *Hygienic Guide Series*, Detroit,

Michigan, 1957.
• Committee on Medical and Biologic Effects of Environmental Pollutants, Division of Medical Sciences, National Research Council: *Chromium*, National Academy of Sciences, Washington, D.C., 1974, pp. 35-73, 125-145.
• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Roubal, J., and Krivucova, M.: "Hygienische Probleme bei Verwendung von tertiarem Butyl-chromat als Passivierungsinhibitor der Metallkorrosion," *Archiv fur Gewerbepathologie und Gewerbehygiene*, 17:589-596, 1960.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR tert-BUTYL CHROMATE

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Butylamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_4H_9NH_2$
- Synonyms: n-Butylamine; 1-aminobutane
- Appearance and odor: Colorless liquid with an odor like ammonia or fish.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for butylamine is a ceiling level of 5 parts of butylamine per million parts of air (ppm). This may also be expressed as 15 milligrams of butylamine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Butylamine can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Butylamine vapor is irritating to the nose, throat, and eyes. Inhalation of concentrations slightly above the permissible exposure may produce mild headache and flushing of the skin and face. Contact with the liquid may produce severe damage to the skin and eyes.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to butylamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to butylamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from butylamine exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of butylamine might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Butylamine is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Butylamine is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Butylamine vapor irritates the upper respiratory tract and eyes. It is a known histamine release agent. In rats exposed to 3000 to 5000 ppm there was an immediate irritant response, labored breathing, pulmonary edema, and death within minutes to hours. The liquid produced severe eye damage and skin burns in animals. In man, the liquid on the skin causes severe primary irritation and second-degree burns with vesiculation. Workers exposed daily to 5 to 10 ppm complained of irritation of the nose, throat, and eyes, and, in some instances, headache and flushing of the skin of the face. Concentrations of 10 to 25 ppm are unpleasant and even intolerable to some subjects for exposures of more than a few minutes; daily exposures of workers to less than 5 ppm (usually 1 to 2 ppm) resulted in no symptoms.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 73.14
  2. Boiling point (760 mm Hg): 77.8 C (172 F)
  3. Specific gravity (water = 1): 0.74
  4. Vapor density (air = 1 at boiling point of butylamine): 2.5
  5. Melting point: −49 C (-56 F)
  6. Vapor pressure at 20 C (68 F): 82 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 7.3
- **Reactivity**
  1. Conditions contributing to instability: Heat.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids will cause spattering.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving butylamine.
  4. Special precautions: Liquid butylamine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: − 12 C (10 F) (closed cup)
  2. Autoignition temperature: 312 C (594 F)
  3. Flammable limits in air, % by volume: Lower: 1.7; Upper: 9.8
  4. Extinguishant: Alcohol, foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Patty reports that "the odor of butylamine is slight at less than 1 ppm, noticeable at 1 to 2 ppm, moderately strong at 2 to 5 ppm, strong at 5 to 10 ppm, and strong and irritating at concentrations exceeding 10 ppm."
  2. Eye Irritation Level: Grant reports that n-butylamine vapor is only a mild eye irritant. The concentrations producing eye irritation are not given.
  3. Other Information: The AIHA *Hygienic Guide* reports that the vapor of n-butylamine is an upper respiratory tract irritant, and Stecher reports that the vapor is a mucous membrane irritant. The *Hygienic Guide* states that "10 to 15 ppm is highly irritating for short exposure."
  4. Evaluation of Warning Properties: Since the odor threshold of n-butylamine is below the permissible exposure limit, this material is considered to have adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of butylamine. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

An analytical method for butylamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid butylamine.
- Clothing contaminated with liquid butylamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of butylamine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the butylamine, the person performing the operation should be informed of butylamine's hazardous properties.
- Where there is any possibility of exposure of an employee's body to liquid butylamine, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes wet with or nonimpervious clothing which becomes contaminated with liquid butylamine should be removed immediately and not reworn until the butylamine is removed from the

clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid butylamine contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid butylamine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid butylamine should be immediately washed or showered to remove any butylamine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to butylamine may occur and control methods which may be effective in each case:

Operation	Controls
Use as a vulcanizing accelerator and reaction initiator in rubber and polymer industries	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as chemical intermediate in production of emulsifying agents	Process enclosure; local exhaust ventilation; general dilution ventilation
Use in chemical synthesis of developers for photography, pharmaceuticals, antioxidants for gasoline, synthetic tanning materials, curing agent for siloxane elastomers, gum inhibitors, ultraviolet absorber for plastics	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as acid neutralizer as corrosion inhibitor in metal, alkyd, and urea enamel pH control, stabilizer of aviation fuels	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use on stored agricultural crops as fungicide to prevent decay	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in polymer industry as a catalyst, accelerator, telomer, and reaction initiator	Process enclosure; local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid butylamine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If butylamine gets on the skin, immediately flush the contaminated skin with water. If butylamine soaks through the clothing, remove the clothing immediately and flush the skin If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of butylamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When butylamine has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If butylamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable

location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Butylamine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of butylamine vapors are permitted.

• Waste disposal method:

Butylamine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Butylamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Butylamine," *Hygienic Guide Series*, Detroit, Michigan, 1960.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck & Co., Inc., Rahway, New Jersey, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Butylamine*, New York, 1971.

• Virginia Chemicals Company: "Amines," Bulletin 1003.

RESPIRATORY PROTECTION FOR BUTYLAMINE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
250 ppm or less	A chemical cartridge respirator with a full facepiece and a cartridge(s) providing protection against butylamine. A gas mask with a chin-style or a front- or back-mounted canister providing protection against butylamine. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against butylamine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of butylamine; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 2000 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for p-tert-Butyltoluene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: p-$CH_3C_6H_4C_4H_9$
- Synonyms: 1-Methyl-4-tert-butylbenzene
- Appearance and odor: Colorless liquid with an aromatic odor somewhat like gasoline.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for p-tert-butyltoluene is 10 parts of p-tert-butyltoluene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 60 milligrams of p-tert-butyltoluene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

p-tert-Butyltoluene can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: p-tert-Butyltoluene may cause irritation of the eyes, nose, throat, and skin; it may also cause nausea, headache, and weakness.

2. Long-term Exposure: p-tert-Butyltoluene may cause heart changes, blood changes, and skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to p-tert-butyltoluene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to p-tert-butyltoluene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed person at increased risk, and to establish a baseline for future health monitoring. Examination of the cardiovascular and the central nervous systems should be stressed. The skin should be examined for evidence of chronic disorders.

—An electrocardiogram: This compound has been observed to cause an unusual cardiovascular syndrome in some workmen after occupational exposure. This consisted of decreased blood pressure, increased pulse rate, and failure to respond to the Master's test of cardiac fitness in a satisfactory manner.

—A complete blood count: This compound has been shown to cause depression of the bone marrow in rats exposed repeatedly to vapor in concentrations of up to 30 ppm. A complete blood count should be performed prior to exposure, including a differential count of a stained smear, as well as hemoglobin, hematocrit, and clotting time determinations.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

The main toxic effects of p-tert-butyltoluene are irritation of the skin and respiratory tract. If absorbed, it may depress the central nervous system and the bone marrow. In some exposed employees a cardiovascular syndrome characterized by decreased blood pressure, increased pulse rate, and abnormal response to the Master's exercise test has been observed.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 148

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

2. Boiling point (760 mm Hg): 193 C (380 F)
3. Specific gravity (water = 1): 0.86
4. Vapor density (air = 1 at boiling point of p-tert-butyltoluene): 5.1
5. Melting point: −52.5 C (-62 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Very low

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving p-tert-butyltoluene.
4. Special precautions: None

• **Flammability**

1. Flash point: 68 C (155 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Foam, carbon dioxide, dry chemical

• **Warning properties**

1. Odor Threshold: Patty reports that olfactory recognition is immediate at concentrations of 5 ppm.
2. Eye Irritation Level: The ILO states that slight conjunctival irritation occurs after exposure to 5 to 8 ppm.
3. Other Information: Sax states that inhalation of the vapors causes irritation of the lungs.
4. Evaluation of Warning Properties: Through its odor and irritant effects, p-tert-butyltoluene can be detected at concentrations below the permissible exposure limit. p-tert-Butyltoluene has good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of p-tert-butyltoluene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure p-tert-butyltoluene may be used. An analytical method for p-tert-butyltoluene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid p-tert-butyltoluene.

• Clothing wet with liquid p-tert-butyltoluene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of p-tert-butyltoluene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the p-tert-butyltoluene, the person performing the operation should be informed of p-tert-butyltoluene's hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid p-tert-butyltoluene should be removed promptly and not reworn until the p-tert-butyltoluene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid p-tert-butyltoluene may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid p-tert-butyltoluene should be promptly washed or showered with soap or mild detergent and water to remove any p-tert-butyltoluene.

• Employees who handle liquid p-tert-butyltoluene should wash their hands thoroughly with soap or mild

detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to p-tert-butyltoluene may occur and control methods which may be effective in each case:

Operation	Controls
Use and preparation of resins dissolved in p-tert-butyltoluene	Local exhaust ventilation; personal protective equipment
Use as a primary intermediate in chemical and pharmaceutical industries	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If p-tert-butyltoluene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If p-tert-butyltoluene gets on the skin, promptly flush the contaminated skin with water. If p-tert-butyltoluene soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of p-tert-butyltoluene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If p-tert-butyltoluene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If p-tert-butyltoluene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Combustion may be improved by mixing with a more flammable liquid. Liquid p-tert-butyltoluene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

p-tert-Butyltoluene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber. Combustion may be improved by mixing with a flammable liquid.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "p-tert-Butyltoluene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Hine, C. H., et al.: "Toxicological Studies on p-tert-Butyltoluene." *Archives of Industrial Hygiene and Occupational Health*, 9:227-243, 1954.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR P-TERT-BUTYLTOLUENE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
500 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
1000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Cadmium Dust (as Cadmium)*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all cadmium dust. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Cadmium metal dust

- Formula: Cd
- Synonyms: None
- Appearance and odor: Odorless, gray powder.

Cadmium oxide dust

- Formula: CdO
- Synonyms: None
- Appearance and odor: Odorless, brown solid or blue-black solid.

Cadmium sulfide dust

- Formula: CdS
- Synonyms: Greenockite
- Appearance: Yellow-orange solid.

Cadmium chloride dust

- Formula: $CdCl_2$
- Synonyms: None
- Appearance: White solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cadmium dust is 0.2 milligram of cadmium dust per cubic meter of air (mg/m³) averaged over an eight-hour work shift, with a ceiling level of 0.6 mg/m³. NIOSH has recommended that the permissible exposure limit be reduced to 40 micrograms of cadmium per cubic meter of air (μg/m³) averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 200 μg/m³ averaged over a 15-minute period. The recommendations in this guideline supplement the recommendations in the NIOSH Criteria Document for Cadmium, which should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cadmium dust can affect the body if it is inhaled. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Cadmium dust may cause irritation of the nose and throat. If enough has been inhaled, after a delay of several hours, a person may also develop cough, chest pain, sweating, chills, shortness of breath, and weakness. Death may occur. Ingestion of cadmium dust may cause nausea, vomiting, diarrhea, and abdominal cramps.

2. Long-term Exposure: Repeated or prolonged exposure to cadmium dust may cause loss of sense of smell, ulceration of the nose, shortness of breath (emphysema), kidney damage, and mild anemia. Exposure to cadmium has also been reported to cause an increased incidence of cancer of the prostate in man. Injections of cadmium sulfate in animals have been reported to cause malformation in their offspring.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cadmium dust.

- **Recommended medical surveillance**

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

The following medical procedures should be made available to each employee who is exposed to cadmium dust at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, liver, kidneys, prostate, and blood should be stressed.

—Urinalysis: Since kidney damage has been observed in humans exposed to cadmium, a urinalysis should be obtained to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centrifuged sediment. In addition, the urine should be examined for low molecular weight proteins by use of 3% sulfosalicylic or other acceptable techniques.

—14" x 17" chest roentgenogram: Cadmium causes human lung damage. Surveillance of the lungs is indicated.

—Liver function tests: Cadmium may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—FVC and FEV (1 sec): Cadmium is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease. Urine protein measurements should be made available every four months.

• **Summary of toxicology**

Cadmium dust causes both acute and chronic effects. It is less toxic than cadmium fume, because dust has a larger particle size than fume; at high concentrations of the dust, physiologic effects similar to those arising from fume exposure could be expected. The acute effects primarily involve the lungs but may also affect other organ systems. Most acute intoxications have been caused by inhalation of cadmium fume at concentrations which did not provide warning symptoms of irritation. The average concentrations of fume responsible for fatalities have been 40 to 50 mg/m³ for 1 hour, or 9 mg/m³ for 5 hours. Non-fatal pneumonitis has been reported from concentrations of 0.5 to 2.5 mg/m³, while relatively mild cases have been attributed to even lower concentrations. Following an asymptomatic latent period of 4 to 10 hours, there is characteristical nasopharyngeal irritation followed by a feeling of chest constriction or substernal pain, with persistent cough and dyspnea; there may also be headache, chills, muscle aches, nausea, vomiting, and diarrhea. Pulmonary edema may then develop and progress rapidly, with decreased vital capacity and markedly reduced carbon monoxide diffusing capacity. Cyanosis may be intense. In about 20% of the cases the dyspnea is progressive, accompanied by wheezing or hemoptysis, and may result in death within 7 to 10 days after exposure; at autopsy the lungs are markedly congested, and there is an intra-alveolar fibrinous exudate, as well as alveolar cell metaplasia. Among survivors, the subsequent course is unpredictable: most cases resolve slowly, but respiratory symptoms may linger for several weeks, while impairment of pulmonary function may persist for months. In experimental animals, cadmium exposure has caused pulmonary fibrosis, but this has not been documented in humans. In one fatal human case, in addition to lung abnormalities, there was renal cortical necrosis. Absorbed cadmium is retained to a large extent by the body, and excretion is very slow. Continued exposure to low levels of cadmium in air has resulted in chronic poisoning characterized by irreversible lung injury of an emphysematous type, with abnormal lung function and urinary excretion of a specific low-molecular-weight protein which may be associated with renal dysfunction. Clinical evidence of the cumulative effects of cadmium may appear after exposure has terminated; the disease then tends to be progressive. The frequency of occurrence of proteinuria increases with length of exposure: those exposed to cadmium compounds for less than 2 years had no proteinuria, whereas most of those exposed for 12 years or more had proteinuria with little other evidence of renal damage. The urinary excretion of cadmium bears no known relationship to the severity or duration of exposure and is only a confirmation of absorption. Other consequences of cadmium exposure are rhinitis, occasional ulceration of the nasal septum, damage to the olfactory nerve, and anosmia. The long-term ingestion of water, beans, and rice contaminated with cadmium has been proposed as the probable cause of a crippling condition among Japanese women who have had multiple pregnancies; severe pain in the back and joints, a waddly gait, osteomalacia, spontaneous fractures, and occasional fatal renal failure are characteristics of the disorder, which has been termed "itai-itai." Subcutaneous injection of cadmium metal suspended in fowl serum produced rhabdomyosarcomata in rats; cadmium sulfate in sterile distilled water produced sarcomata; and cadmium chloride solution produced pleomorphic sarcomata at the injection site. Increased incidence of prostatic cancer has been reported following occupational exposure to cadmium. Cadmium sulfate injected into the lingual vein of female hamsters on day 8 of pregnancy caused a hig.. incidence of resorption and malformed offsprin- acute necrosis of rat testes follows large doses orally or parenterally, but testicular effects have not been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data—Cadmium metal dust**

1. Molecular weight: 112.4
2. Boiling point (760 mm Hg): 767 C (1412 F)
3. Specific gravity (water = 1): 8.642
4. Vapor density (air = 1 at boiling point of cadmium metal dust): Not applicable
5. Melting point: 321 C (609 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Physical data—Cadmium oxide dust**

1. Molecular weight: 128.4
2. Boiling point (760 mm Hg): 900 C (1652 F) (sublimes and decomposes)
3. Specific gravity (water = 1): 6.95 or 8.15
4. Vapor density (air = 1 at boiling point of cadmium oxide dust): Not applicable
5. Melting point: 900 C (1652 F) (sublimes and decomposes)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0005
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Physical data—Cadmium sulfide dust**

1. Molecular weight: 144.5
2. Boiling point (760 mm Hg): Sublimes in N_2 at 980 C (1796 F)
3. Specific gravity (water = 1): 4.82
4. Vapor density (air = 1 at boiling point of cadmium sulfide dust): Not applicable
5. Melting point: 1750 C (3182 F) at 100 atm.
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0001
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Physical data—Cadmium chloride dust**

1. Molecular weight: 183
2. Boiling point (760 mm Hg): 960 C (1760 F)
3. Specific gravity (water = 1): 4.047
4. Vapor density (air = 1 at boiling point of cadmium chloride dust): Not applicable
5. Melting point: 568 C (1054 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 140
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: None hazardous
2. Incompatibilities: Contact of cadmium metal dust with strong oxidizers or with elemental sulfur, selenium, and tellurium may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as cadmium oxide fume) may be released in a fire involving cadmium dust.
4. Special precautions: None

- **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: 250 C (482 F) (layer) (cadmium metal dust)
3. Minimum explosive dust concentration: Data not available
4. Extinguishant: Dry powder for metal fires

- **Warning properties**

Grant states that "cadmium is a very toxic metal which gives off fumes when burned or heated strongly. Characteristically these fumes cause dryness and irritation of the throat, followed in a few hours by nausea and diarrhea. Smarting of the eyes occurs relatively infrequently, and no injury to the eyes of human beings has been reported. Neither eye nor respiratory irritation is enough to prevent exposures which may cause serious systemic poisoning and damage to the lungs."

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taker in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of cadmium dust. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of cadmium dust on a filter, followed by treatment with nitric acid, solution in hydrochloric acid, and atomic absorption spectrophotometric analysis. An analytical method for cadmium dust is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• If employees' clothing has had any possibility of being contaminated with cadmium dust, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with cadmium dust should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of cadmium dust from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the cadmium dust, the person performing the operation should be informed of cadmium dust's hazardous properties.

• Employees should be provided with and required to use dust-resistant safety goggles where there is any possibility of cadmium chloride dust contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to cadmium chloride dust, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Workers subject to skin contact with cadmium dust should wash with soap or mild detergent and water any areas of the body which may have contacted cadmium dust at the end of each work day.

• Eating and smoking should not be permitted in areas where cadmium dust is handled, processed, or stored.

• Employees who handle cadmium dust should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cadmium dust may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from fabrication of cadmium-plated marine, aircraft, and motor vehicle equipment for corrosion-resistant coatings	Local exhaust ventilation; personal protective equipment
Liberation during processing of cadmium metal	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation in synthesis of cadmium compounds	Process enclosure; local exhaust ventilation
Liberation in manufacture and fabrication of cadmium alloys; recovery from flue dusts during smelting of lead and zinc operations	Local exhaust ventilation; personal protective equipment
Liberation during manufacture of nuclear reactor rods	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If cadmium dust gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If cadmium dust gets on the skin, wash the contaminated skin using soap or mild detergent and water. Be sure to wash the hands well before eating or smoking and at the close of work.

• **Breathing**

If a person breathes in large amounts of cadmium dust, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When cadmium dust or liquids containing cadmium dust have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the

person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.

• If cadmium dust is released in hazardous concentrations, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of release.
3. Collect released material in the most convenient and safe manner for reclamation or for disposal in sealed conainers in a secured sanitary landfill.

• Waste disposal method:

Cadmium dust may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Cadmium Dust," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Cadmium," *Hygienic Guide Series*, Detroit, Michigan, 1962.

• *American National Standard Acceptable Concentrations - Cadmium Dust*: ANSI-Z37.5-1970, American National Standards Institute, Inc., New York, 1970.

• Bonnell, J. A.: "Cadmium Poisoning," *Annals of Occupational Hygiene*, 8:45-49, 1965.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Dunphy, B.: "Acute Occupational Cadmium Poisoning: A Critical Review of the Literature," *Journal of Occupational Medicine*, 9:22-26, 1967.

• Emmerson, B. T.: "'Ouch-Ouch' Disease: The Osteomalacia of Cadmium Nephropathy," *Annals of Internal Medicine*, 73:854-855, 1970.

• Fassett, D. W.: "Cadmium: Biological Effects and Occurrence in the Environment," *Annual Review of Pharmacology*, 15:425-435, 1975.

• Friberg, L., et al.: *Cadmium in the Environment*, (2nd ed.), CRC Press, Cleveland, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Gunn, S. A., et al.: "Specific Response of Mesenchymal Tissue to Cancerigenesis by Cadmium," *Archives of Pathology*, 83:493-499, 1967.

• Haddow, A., et al.: "Cadmium Neoplasia: Sarcomata at the Site of Injection of Cadmium Sulphate in Rats and Mice," *British Journal of Cancer*, 18:667-673, 1964.

• Heath, J. C., et al.: "Cadmium as a Carcinogen," *Nature*, 193:592-593, 1962.

• Holmberg, R. E., Jr., and Ferm, V. H.: "Interrelationships of Selenium, Cadmium, and Arsenic in Mammalian Teratogenesis," *Archives of Environmental Health*, 18:873-877, 1969.

• Karolinska Institute: *Cadmium in the Environment, II*, PB-221 198, prepared for Environmental Protection Agency, National Technical Information Service, Springfield, Virginia, 1973.

• Louria, D. B., et al.: "The Human Toxicity of Certain Trace Elements," *Annals of Internal Medicine*, 76:307-319, 1972.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Cadmium*, HEW Publication No. (NIOSH) 76-192, GPO No. 017-033-00206-1, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stauden, A. (ex. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology*, (2nd ed.), Interscience, New York, 1972.

• Tsuchiya, K.: "Proteinuria of Workers Exposed to Cadmium Fume," *Archives of Environmental Health*, 14:875-880, 1967.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on these chemicals and has concluded that they cause cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 2, 1973, and Volume 11, 1976.

RESPIRATORY PROTECTION FOR CADMIUM DUST (AS CADMIUM)

Condition	Minimum Respiratory Protection* Required Above 0.2 mg/m³
Dust Concentration	
1 mg/m³ or less	Any dust respirator, except single-use.
2 mg/m³ or less	Any dust respirator, except single-use or quarter-mask respirator. Any high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
10 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
40 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 40 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Cadmium Fume

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Cd/CdO
- Synonyms: None
- Appearance: Finely divided solid particles dispersed in air.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cadmium fume is 0.1 milligram of cadmium fume per cubic meter of air (mg/m³) averaged over an eight-hour work shift, with an acceptable ceiling level of 0.3 mg/m³. NIOSH has recommended that the permissible exposure limit be reduced to a time-weighted average of 40 micrograms cadmium per cubic meter (ug/m³) with a ceiling level of 200 ug cadmium/m³ for a 15-minute period. The NIOSH Criteria Document for Cadmium should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cadmium fume can affect the body if it is inhaled.

- **Effects of overexposure**

1. Short-term Exposure: Cadmium fume causes irritation of the nose and throat. If enough has been inhaled, after a delay of several hours, a person may also develop cough, chest pain, sweating, chills, shortness of breath, and weakness. Death may occur.

2. Long-term Exposure: Repeated or prolonged exposure to cadmium fume may cause loss of sense of smell, ulceration of the nose, shortness of breath (emphysema), kidney damage, and mild anemia. Exposure to cadmium fume has also been reported to cause an increased incidence of cancer of the prostate in men. Injections of cadmium sulfate in animals have been reported to cause malformation in their offspring. This effect has not been reported in humans.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cadmium fume.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to cadmium fume at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, kidneys, and blood should be stressed.

—Urinalysis: Since kidney damage has been observed in humans exposed to cadmium, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment. The urine should be examined for the specific protein.

—14" x 17" chest roentgenogram: Cadmium causes human lung damage. Surveillance of the lungs is indicated.

—Liver function tests: Cadmium may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—FVC and FEV (1 sec): Cadmium is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Urine protein measurements should be made available every four months.

• **Summary of toxicology**

Cadmium fume (cadmium oxide) is a severe pulmonary irritant that has caused fatal pulmonary edema in workers; chronic exposures may lead to severe pulmonary emphysema. Cadmium sulfide produces malignant tumors in animals by injection, suggesting that cadmium is carcinogenic. Most acute intoxications have been caused by inhalation of cadmium fume at concentrations which did not provide warning symptoms of irritation. The average concentrations of fume responsible for fatalities have been 40 to 50 mg/m³ for 1 hour, or 9 mg/m³ for 5 hours. Non-fatal pneumonitis has been reported from concentrations of 0.5 to 2.5 mg/m³, while relatively mild cases have been attributed to even lower concentrations. Following an asymptomatic latent period of 4 to 10 hours, there is characteristically nasopharyngeal irritation, followed by a feeling of chest constriction or substernal pain, with cough and dyspnea; there also may be headache, chills, muscle aches, nausea, vomiting, and diarrhea. Pulmonary edema may then develop rapidly, with decreased vital capacity and markedly reduced carbon monoxide diffusing capacity. In about 20% of the cases the dyspnea is progressive, accompanied by wheezing or hemoptysis, and may result in death within 7 to 10 days of exposure; at autopsy the lungs are markedly congested, and there is an intra-alveolar fibrinous exudate, as well as alveolar cell metaplasia. Among survivors, the subsequent course is unpredictable: most cases resolve slowly, but respiratory symptoms may linger for several weeks, while impairment of pulmonary function may persist for months. In experimental animals, cadmium exposure has caused pulmonary fibrosis, but this has not been documented in humans. In one fatal human case, in addition to lung abnormalities, there was renal cortical necrosis. Continued exposure to lower levels of cadmium in air has resulted in chronic poisoning characterized by irreversible lung injury of emphysematous type, with abnormal lung function and urinary excretion of a specific low-molecular-weight protein which may be associated with evidence of renal dysfunction. Clinical evidence of the cumulative effects of cadmium may appear after exposure has terminated; the disease then tends to be progressive. The frequency of occurrence of proteinuria increases with length of exposure: those exposed to cadmium compounds for less than 2 years had no proteinuria, whereas most of those exposed for 12 years or more had proteinuria with little other evidence of renal damage. Cadmium absorbed by any route is, to a very large extent, retained by the body. Excretion is very slow. The urinary excretion of cadmium bears no known relationship to the severity or duration of exposure and is only a confirmation of absorption. Other consequences of cadmium exposure are rhinitis, occasional ulceration of the nasal septum, damage to the olfactory nerve, and anosmia. The long-term ingestion of beans, rice and water contaminated with cadmium has been proposed as the probable cause of a crippling condition among Japanese women who have had multiple pregnancies; pain in the back and joints, an unsteady gait, osteomalacia, bone fractures, and occasional renal failure are characteristics of the disorder. Rats, injected subcutaneously with cadmium metal suspended in fowl serum, produced rhabdomyosarcomata; with cadmium sulfate in sterile distilled water, sarcomata; and with cadmium chloride solution, pleomorphic sarcomas at the injection site, suggesting that cadmium is carcinogenic. Cadmium sulfate injected into the lingual vein of female hamsters on day 8 of pregnancy caused a high incidence of resorption and malformed offspring. Increased prostatic and lung cancer has been reported in humans exposed to cadmium oxide. Acute necrosis of the rat testis follows large doses orally or parenterally.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 112 – 128
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): Not applicable
4. Vapor density (air = 1 at boiling point of cadmium fume): Not applicable
5. Melting point: Not applicable
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Not applicable

• **Flammability**

1. Not applicable

• **Warning properties**

Grant reports that "smarting of the eyes occurs relatively infrequently (upon exposure to cadmium fume), and no injury to the eyes of human beings has been reported. Neither eye nor respiratory tract irritation is enough to prevent exposures which may cause serious systemic poisoning and damage to the lungs."

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected

airborne concentrations of cadmium fume. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Method

Sampling and analyses may be performed by collection of cadmium fume on a cellulose membrane filter, followed by treatment with nitric acid, solution in acid, and analysis with an atomic absorption spectrophotometer. An analytical method for cadmium fume is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

SANITATION

• Eating and smoking should not be permitted in areas where fumes may be generated in the handling or processing of cadmium.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cadmium fume may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during smelting and refining of ores where it is a by-product of zinc, lead, and copper-bearing ores	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during recovery of metal by processing of scrap; during melting and pouring of cadmium metal; during casting of alloys for cadmium-copper, cadmium-lead, cadmium-bismuth, cadmium-silver, cadmium-nickel, cadmium-lead-silver, cadmium-lead-silver-nickel, cadmium-lead-bismuth-tin, and cadmium-gold products used for coating telephone cables, trolley wires, welding electrodes, automatic sprinkling systems, steam boilers, fire alarms, high-pressure/temperature bearings, starting switches, aircraft relays, light-duty circuit breakers, low-temperature solder, and jewelry	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during fabrication of metal, alloys, or plated steel	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during casting and use of solders; during melting of cadmium ingots for paint and pigment manufacture used for coloring of plastics and ceramic glazes, electroplating, and in chemical synthesis	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during coating on metals by hot dipping or spraying	Process enclosure; local exhaust ventilation; personal protective equipment

Liberation during manufacture of nickel-cadmium batteries for use in radio-portable telephones, convenience appliances, and vented cells used in air planes, heliocopters, and stand-by power and lighting	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of cadmium fume, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.

• If potentially hazardous amounts of cadmium fume are inadvertently released, ventilate the area of the release to disperse the fume.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Cadmium and Compounds as Cd," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Cadmium," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Bonnell, J. A.: "Cadmium Poisoning," *Annals of Occupational Hygiene*, 8:45-50, 1965.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Dunphy, B.: "Acute Occupational Cadmium Poisoning: A Critical Review of the Literature," *Journal of Occupational Medicine*, 9:22-26, 1967.

• Emmerson, B. T.: "'Ouch-Ouch' Disease: The Osteomalacia of Cadmium Nephropathy," *Annals of Internal Medicine*, 73:854-855, 1970.

• Fassett, D. W.: "Cadmium: Biological Effects and Occurrence in the Environment," *Annual Review of Pharmacology*, 15:425-435, 1975.

• Fleischer, M., et al.: "Environmental Impact of Cadmium: A Review by the Panel on Hazardous Trace Substances," *Environmental Health Perspectives*, 253-323, May 1974.

• Friberg, L., et al.: *Cadmium in the Environment*, (2nd ed.), CRC Press, Cleveland, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Gunn, S. A., et al.: "Specific Response of Mesenchymal Tissue to Cancerigenesis by Cadmium," *Archives of Pathology*, 83:493-499, 1967.

• Haddow, A., et al.: "Cadmium Neoplasia: Sarcomata at the Site of Injection of Cadmium Sulphate in Rats and Mice," *British Journal of Cancer*, 18:667-673, 1964.

• Heath, J. C., et al.: "Cadmium as a Carcinogen," *Nature*, 193:592-593, 1962.

• Holmberg, E. R., Jr., and Ferm, V. H.: "Interrelationships of Selenium, Cadmium, and Arsenic in Mammalian Teratogenesis," *Archives of Environmental Health*, 18:873-877, 1969.

• Louria, D. B., et al.: "The Human Toxicity of Certain Trace Elements," *Annals of Internal Medicine*, 76:307-319, 1972.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Cadmium*, HEW Publication No. (NIOSH) 76-192, GPO No. 017-033-00206-1, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Tsuchiya, K.: "Proteinuria of Workers Exposed to Cadmium Fume," *Archives of Environmental Health*, 14:875-880, 1967.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 2, 1973, and Volume 11, 1976.

RESPIRATORY PROTECTION FOR CADMIUM FUME

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
1 mg/m³ or less	Any fume respirator or high efficiency particulate respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
40 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 40 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator with a full facepiece. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Calcium Oxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CaO
- Synonyms: Quicklime; pebble lime
- Appearance and odor: White or gray odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for calcium oxide is 5 milligrams of calcium oxide per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for calcium oxide a Threshold Limit Value of 2 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Calcium oxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Calcium oxide causes irritation of the eyes, nose, throat, and skin. Severe burns may result from contact with this chemical. It may also cause bronchitis and pneumonia.

2. Long-term Exposure: Repeated or prolonged exposure to calcium oxide may cause irritation of the skin and ulceration and perforation of the nasal septum.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to calcium oxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to calcium oxide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from calcium oxide exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of calcium oxide might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Calcium oxide is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Calcium oxide dust irritates the eyes and upper respiratory tract. The irritant effects are probably due primarily to its alkalinity, but dehydrating and thermal effects also may be contributing factors. Inflammation of the respiratory passages, ulceration, and perforation of the nasal septum, and pneumonia have been attributed to inhalation of calcium oxide dust; severe irritation of the upper respiratory tract ordinarily causes persons to avoid serious inhalation exposure. Particles of calcium oxide have caused severe burns of the eyes; prolonged or repeated contact with skin could cause dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 56.1
  2. Boiling point (760 mm Hg): 2850 C (5162 F)
  3. Specific gravity (water = 1): 3.30

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

4. Vapor density (air = 1 at boiling point of calcium oxide): Not applicable

5. Melting point: 2570 C (4658 F)

6. Vapor pressure at 20 C (68 F): 0 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): Reacts to form slaked lime

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Moisture

2. Incompatibilities: Contact with water causes violent spattering and heat liberated may cause ignition of combustible substances.

3. Hazardous decomposition products: Slaked lime

4. Special precautions: Calcium oxide will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Grant states that "burns of the eye caused by particles of calcium oxide are severe and of the same nature as those caused by calcium hydroxide."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection on a cellulose membrane filter followed by treatment with nitric and perchloric acids, solution in hydrochloric acid, and analysis with an atomic absorption spectrophotometer. An analytical method for calcium oxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with calcium oxide, where skin contact may occur.

• If employees' clothing may have become contaminated with calcium oxide, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with calcium oxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of calcium oxide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the calcium oxide, the person performing the operation should be informed of calcium oxide's hazardous properties.

• Where exposure of an employee's body to calcium oxide may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with calcium oxide should be removed promptly and not reworn until the calcium oxide is removed from the clothing.

• Employees should be provided with and required to use dust-resistant safety goggles where there is any possibility of calcium oxide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to calcium oxide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Workers subject to skin contact with calcium oxide should wash with soap or mild detergent and water any areas of the body which may have contacted calcium oxide at the end of each work day.

• Skin that becomes contaminated with calcium oxide should be promptly washed or showered with soap or mild detergent and water to remove any calcium oxide.

• Eating and smoking should not be permitted in areas where calcium oxide is handled, processed, or stored.

• Employees who handle calcium oxide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to calcium oxide may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of lime; use in manufacture of Portland cement, mortar, stucco, and plaster	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during weighing and mixing of construction bonding agents	Personal protective equipment
Use during manufacture of construction, insulation, and refractory materials	Process enclosure; local exhaust ventilation; personal protective equipment
Use for preparation and mixing with soil, lime, and water in soil and sub-base stabilization	Personal protective equipment
Use in manufacture of iron and steel in wire-drawing; during metal refining and smelting as a flux	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a softening, purifying, coagulating, and suspending compound in water treatment and purification; use in sewage and waste treatment in steel fabrication, waste plants, chemical, pharmaceutical, and explosives industry; sulfur removal in petroleum refining	Personal protective equipment
Use in synthesis of chemicals, dye intermediates, paint pigments, and pharmaceuticals; during Kraft pulp processing of paper; during food processing including cane and beet sugar refining	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of silicate and non-silicate glass; during liming of hides in leather manufacture; in manufacture of pesticides and fungicides, and in cleaning operations as bleach, disinfectant, deodorizer, sewer, cesspool, and septic tank cleaners	Process enclosure; local exhaust ventilation; personal protective equipment
Handling and application of agricultural lime and mixing of agricultural fungicides	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If calcium oxide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If calcium oxide gets on the skin, immediately flush the contaminated skin with large amounts of water. If calcium oxide penetrates through the clothing, remove the clothing immediately and flush the skin with large amounts of water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of calcium oxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If calcium oxide has been swallowed and the person is conscious, give him large quantities of water immediately to dilute the calcium oxide. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Under-

stand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If calcium oxide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill.

- Waste disposal method:

Calcium oxide may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Calcium Oxide (Lime)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.
- Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
- von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR CALCIUM OXIDE

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
25 mg/m³ or less	Any dust and mist respirator.**
50 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator.** Any fume respirator or high efficiency particulate respirator.** Any supplied-air respirator.** Any self-contained breathing apparatus.**
250 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 250 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator with a full facepiece. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Camphor (Synthetic)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_{16}O$
- Synonyms: 2-Camphanone; synthetic camphor; gum camphor; laurel camphor
- Appearance and odor: Colorless, glassy solid with a penetrating, characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for camphor is 2 milligrams of camphor per cubic meter of air (mg/m^3) averaged over an eight-hour work shift (*Federal Register*, Vol. 43, No. 237, pp. 57601-03, 8 December 1978).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Camphor can affect the body if it is inhaled, comes in contact with the eyes, nose, throat, or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Camphor may cause eye irritation, sore throat, nausea, vomiting, headache, and dizziness. It may also cause confusion, excitement, irrational behavior, and convulsions. A person may have a fever, bluish lips, pale face, and become unconscious. It may also affect the kidneys.

2. Long-term Exposure: Repeated overexposure to camphor may cause a loss of the sense of smell.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to camphor.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to camphor at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from camphor exposure.

—Convulsive seizures: Camphor is a central nervous system stimulant. Those with pre-existing convulsive disorders may be at increased risk.

—Eye disease: Camphor is reported to be a mild eye irritant. Those with pre-existing eye disease may be at increased risk.

—Skin disease: Because camphor is a rubefacient, those with pre-existing skin disorders may be more susceptible to exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of camphor might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Kidney disease: Although camphor is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although camphor is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Camphor is mainly a local irritant. Overexposure to camphor produces irritation of the eyes and nose, with a risk of loss of sense of smell. Very large exposures affect

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

the central nervous system, resulting in nausea, vomiting, dizziness, agitation, and convulsions. Camphor may be either oxidized to carbonyl derivatives or conjugated with glucuronic acid. Most of the absorbed camphor and its metabolites are excreted by the kidneys. Complete recovery from overexposure is usually within 48 hours.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 152
  2. Boiling point (760 mm Hg): 207.4 C (405 F)
  3. Specific gravity (water = 1): 1.00
  4. Vapor density (air = 1 at boiling point of camphor): 5.3
  5. Melting point: 180 C (356 F)
  6. Vapor pressure at 20 C (68 F): 0.18 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.12
  8. Evaporation rate (butyl acetate = 1): Less than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with oxidizing materials, especially chromic anhydride, may form explosive mixtures.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving camphor.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 66 C (150 F) (closed cup)
  2. Autoignition temperature: 466 C (871 F)
  3. Flammable limits in air, % by volume: Lower: 0.6; Upper: 3.5
  4. Extinguishant: Foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: The following odor thresholds have been reported for camphor: 16 ppm (Summer); 0.018 and 1.6 ppm (May). According to an unpublished report of the Pennsylvania Department of Health, at camphor concentrations ranging from 35 to 194 mg/m^3, anosmia occurs in approximately one hour.
  2. Eye Irritation Level: Grant reports that "camphor may be expected to be somewhat irritating on contact with the eye, but no serious injuries have been reported from it. An instance of industrial exposure to camphor vapors resulted in several cases of superficial keratitis with temporary loss of corneal epithelium, but mixed with the camphor vapor were formaldehyde and acetic acid, which may have been responsible for the injuries." Sax also reports that camphor is a local irritant. No quantitative information is available, however.
  3. Other Information: According to the *Documentation of TLV's*, camphor causes nose irritation. The permissible exposure limit of 12 mg/m^3 "is proposed to prevent irritation of the eyes and nose and anosmia."
  4. Evaluation of Warning Properties: Through its odor camphor can be detected at concentrations near the permissible exposure limit. For the purposes of this guideline, camphor is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of camphor. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of camphor vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure camphor may be used. An analytical method for camphor is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid camphor or liquids containing camphor.
• If employees' clothing may have become contaminated with solid camphor, employees should change into uncontaminated clothing before leaving the work premises.
• Clothing contaminated with solid camphor or liquids containing camphor should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of camphor from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the camphor, the person performing the operation should be informed of camphor's hazardous properties.
• Non-impervious clothing which becomes contaminated with solid camphor or liquids containing camphor should be removed promptly and not reworn until the camphor is removed from the clothing.
• Employees should be provided with and required to use dust- and splash-proof safety goggles where solid camphor or liquids containing camphor may contact the eyes.

SANITATION

• Skin that becomes contaminated with solid camphor or liquids containing camphor should be promptly washed or showered with soap or mild detergent and water to remove any camphor.
• Eating and smoking should not be permitted in areas where solid camphor or liquids containing camphor are handled, processed, or stored.
• Employees who handle solid camphor or liquids containing camphor should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to camphor may occur and control methods which may be effective in each case:

Operation	Controls
Use during mixing and blending of cellulose nitrate for photographic film	Local exhaust ventilation; personal protective equipment
Use during preparation and loading of explosives and devices	Natural ventilation; local exhaust ventilation; personal protective equipment
Use during mixing and liberation during packaging of cosmetics (perfume); during mixing and canning of embalming fluid	Local exhaust ventilation; personal protective equipment
Liberation during preparation and packing of pharmaceuticals	Local exhaust ventilation
Use during mixing and liberation during packaging of moth and insect repellants; during mixing of disinfectants	Local exhaust ventilation; personal protective equipment
Use as a catalyst or chemical intermediate in manufacturing of cumene and sulfuryl chloride	Local exhaust ventilation; personal protective equipment
Use in mixing and blending of certain lacquers and varnishes; during preparation and packaging of certain foods and tobacco	Local exhaust ventilation; personal protective equipment
Liberation during spray application of certain lacquers and varnishes	Process enclosure with local exhaust ventilation; personal protective equipment
Liberation during brush application of certain lacquers and varnishes; during embalming procedures	Local or general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If camphor dust or solution gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If camphor dust or solution gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If solid camphor or liquids containing camphor penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. When there is evidence of skin irritation, get medical attention as soon as possible.

• **Breathing**

If a person breathes in large amounts of camphor, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When camphor has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If camphor is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Camphor may be disposed of:

1. By making packages of camphor in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving camphor in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Camphor," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, unpublished report.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• *Federal Register*, Vol. 43, No. 237, pp. 57601-03, 8 December 1978.

• Ginn, H. E., et al.: "Camphor Intoxication Treated by Lipid Dialysis," *Journal of American Medical Association*, 10:203-230, 1968.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Gronka, P. A., et al.: "Camphor Exposures in a Packaging Plant," *American Industrial Hygiene Association Journal*, May-June 1969, pp.276-299.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Prentiss Drug and Chemical Company, Inc.: *Camphor*.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

RESPIRATORY PROTECTION FOR CAMPHOR (SYNTHETIC)

Condition	Minimum Respiratory Protection* Required Above 2 mg/m³
Vapor Concentration	
200 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Carbaryl (Sevin (R))*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{12}H_{11}NO_2$
- Synonyms: 1-Naphthyl N-methylcarbamate; alpha-naphthyl N-methylcarbamate
- Appearance: Colorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for carbaryl is 5 milligrams of carbaryl per cubic meter of air (mg/m³) averaged over an eight-hour work shift. NIOSH has recommended a permissible exposure limit of 5 mg/m³ averaged over a work shift of up to 10 hours per day, 40 hours per week. The NIOSH Criteria Document for Carbaryl should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Carbaryl can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to carbaryl may cause small pupils, watering of the eyes, excessive discharge from the nose, mouth watering, sweating, abdominal cramps, nausea, vomiting, diarrhea, shaking, a blue color of the skin, and convulsions. Concentrated solutions on the skin may cause irritation and systemic intoxication. Carbaryl, when given to several species of pregnant animals, has caused defects in their offspring.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to carbaryl.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to carbaryl at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, cardiovascular system, and central nervous system should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Carbaryl may cause kidney damage. A urinalysis should be performed to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Medical warning: Employees should be informed of animal studies showing reproductive effects resulting from exposure to carbaryl. Exposure should be minimized during pregnancy.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Carbaryl (Sevin) dust is a short-acting anticholinesterase agent, with the important characteristic of rapid reversibility of enzyme inhibition. It inactivates cholinesterase, resulting in the accumulation of acetylcholine at synapses in the nervous system, at neuromuscular junctions of the skeletal and smooth muscles, and secretory glands. Signs and symptoms of overexposure may include miosis, blurred vision, lacrimation, excessive nasal discharge or salivation, sweating, abdominal cramps, nausea, vomiting, diarrhea, tremor, cyanosis, and convulsions. The rapid reversibility of cholinesterase inhibition by carbamates such as carbaryl is of significance in monitoring exposure: measurements of

These recommendations reflect good industrial hygene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

this enzyme are likely to give clinically misleading values in the normal range of activity and will not reflect the true magnitude of exposure; carbaryl is also rapidly metabolized, which further diminishes the severity of its effect. A single dose of 250 mg (approximately 2.8 mg/kg) ingested by an adult man resulted in moderate poisoning; after 20 minutes, there was sudden onset of abdominal pain followed by profuse sweating, lassitude, and vomiting; one hour after ingestion, and following a total of 3 mg atropine sulfate, the subject felt better and completely recovered after another hour. In a study of 59 workers exposed to concentrations ranging from 0.23 to 31 mg/m³ during a 19-month period, there were no signs or symptoms of anticholinesterase activity; in the most heavily exposed workers, relatively large amounts of 1-naphthol (a metabolite of carbaryl) were excreted in the urine, and the blood cholinesterase activity was slightly depressed. It was concluded that an excretion level of total (free plus conjugated) 1-naphthol significantly above 400 ug/100 ml of urine indicates absorption and metabolism of carbaryl. On the skin, concentrated solutions may cause irritation and systemic intoxication. Carbaryl administered orally during organogenesis was teratogenic in guinea pigs at a dose of 300 mg/kg and in beagle dogs at a dose of 25 mg/kg. The dog has been shown to metabolize carbaryl differently from other animal species, which may explain the anomalous teratogenicity. Of 60 male mongrel rats given 30 mg/kg orally twice weekly, 12 were alive after 22 months of treatment; 2 of the 12 had fibrosarcomata, 1 had a polymorphonuclear sarcoma, and 1 had an osteosarcoma with numerous metastases; of 48 rats receiving 20 mg in a paraffin pill implanted subcutaneously, 10 were alive after 22 months, and 2 of the 10 had fibrosarcomata; 46 of 48 control animals were alive in the eleventh month when a fibrosarcoma was discovered in 1 rat; although not stated, there were apparently no further deaths or tumors in control rats during the 22 months of the study.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 201.2
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): 1.23
  4. Vapor density (air = 1 at boiling point of carbaryl): Not applicable
  5. Melting point: 142 C (288 F)
  6. Vapor pressure at 20 C (68 F): 0.005 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.004
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen, methylamine, and carbon monoxide) may be released in a fire involving carbaryl.
  4. Special precautions: None
- **Flammability**
  1. Flash point: Data not available
  2. Minimum ignition temperature: Data not available
  3. Minimum explosive concentration: Data not available
  4. Extinguishant: Water
- **Warning properties**
  1. Odor Threshold: The American National Standards Institute states that carbaryl is "essentially odorless."
  2. Eye Irritation Level: Grant states that "splash contact of an insecticide liquid containing both carbaryl and dimethoate in one patient on two different occasions caused transient injury of the corneal epithelium and much swelling of the lids, but recovery was rapid and complete. This suggests that carbaryl is not particularly dangerous to the eye."
  3. Evaluation of Warning Properties: No quantitative data are available relating warning properties to air concentrations of carbaryl. The concentration in saturated air at 20 C could present a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of carbaryl on a filter, followed by colorimetric analysis. An analytical method for carbaryl is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to

be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with carbaryl or liquids containing carbaryl.

• If employees' clothing may have become contaminated with carbaryl, employees should change into uncontaminated clothing before leaving the work premises.

• Non-impervious clothing which becomes contaminated with carbaryl should be removed promptly and not reworn until the carbaryl is removed from the clothing.

• Clothing contaminated with carbaryl should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of carbaryl from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the carbaryl, the person performing the operation should be informed of carbaryl's hazardous properties.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where carbaryl or liquids containing carbaryl may contact the eyes.

SANITATION

• Skin that becomes contaminated with carbaryl should be promptly washed or showered with soap or mild detergent and water to remove any carbaryl.

• Eating and smoking should not be permitted in areas where solid carbaryl is handled, processed, or stored.

• Employees, including those in agricultural operations, who handle carbaryl or liquids containing carbaryl should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to carbaryl may occur and control methods which may be effective in each case:

Operation	Controls
Use as a pesticide and acaricide for field crops, fruit, vegetables, ornamentals, livestock, poultry, pets, domestic dwellings, medical facilities, schools, commercial and industrial areas, urban and rural outdoor areas, and sewage treatment plants	Personal protective equipment
Formulation and manufacture of carbaryl	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If carbaryl or liquids containing carbaryl get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If carbaryl or liquids containing carbaryl get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If carbaryl or liquids containing carbaryl penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of carbaryl, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When carbaryl or liquids containing carbaryl have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If carbaryl is spilled, the following steps should be taken:

1. Ventilate area of spill.

2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Carbaryl may be disposed of:

1. By making packages of carbaryl in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving carbaryl in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Carbaryl (Sevin)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• *American National Standard Acceptable Concentrations - Carbaryl (Sevin)*: ANSI-Z62.38-1962, American National Standards Institute, Inc., New York, 1962.

• Andrianova, M. M., and Alekseev, I. V.: "On the Problem of Carcinogenous Properties of the Pesticides Sevine, Maneb, Ciram and Cineb, *Voprosy Pitaniia*, 29:71-74, 1970.

• Best, E. M., Jr., and Murray, B. L.: "Observations on Workers Exposed to Sevin Insecticide: A Preliminary Report," *Journal of Occupational Medicine*, 10:507-517, 1962.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Carbaryl*, HEW Publication No. (NIOSH) 77-107, GPO No. 017-033-00196-1, U.S. Government Printing Office, Washington, D.C., 1976.

• Robens, J. F.: "Teratologic Studies of Carbaryl, Diazinon, Norea, Disulfiram, and Thiram in Small Laboratory Animals," *Toxicology and Applied Pharmacology*, 15:152-163, 1969.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smalley, H. E., et al.: "Teratogenic Action of Carbaryl in Beagle Dogs," *Toxicology and Applied Pharmacology*, 13:392-403, 1968.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 12, 1976.

RESPIRATORY PROTECTION FOR CARBARYL (SEVIN (R))

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate or Vapor Concentration	
50 mg/m³ or less	Any supplied-air respirator.** Any self-contained breathing apparatus.**
250 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
625 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 625 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If an employee informs his employer that he is experiencing eye irritation from carbaryl while wearing a half- or quarter-mask respirator, the employer should provide an equivalent respirator with a full facepiece, helmet, or hood.

Occupational Health Guideline for Carbon Dioxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CO_2
- Synonyms: Carbonic acid gas; "Dry Ice"; CO_2
- Appearance and odor: Primarily a colorless, odorless gas; however, it can be a liquid or a solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for carbon dioxide is 5000 parts of carbon dioxide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 9000 milligrams of carbon dioxide per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be changed to 10,000 ppm averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling of 30,000 ppm averaged over a 10-minute period. The NIOSH Criteria Document for Carbon Dioxide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Carbon dioxide can affect the body if it is inhaled. Solid carbon dioxide (dry ice) and compressed carbon dioxide gas from a cylinder can affect the body if it comes in contact with the eyes, skin, or mouth.

- **Effects of overexposure**

Inhaling carbon dioxide may cause rapid breathing, rapid beating of the heart, headache, sweating, shortness of breath, dizziness, mental depression, visual disturbances, shaking, unconsciousness, and death. Skin, eye, or mouth contact with solid carbon dioxide (dry ice) may cause frostbite. Similar effects may occur from carbon dioxide as it is being released from a cylinder.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to carbon dioxide.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to carbon dioxide at potentially hazardous levels.

- **Summary of toxicology**

Carbon dioxide gas is an asphyxiant, a potent respiratory stimulant, and both a stimulant and depressant of the CNS. Respiratory volume is doubled at 4% CO_2 and redoubled at 5%. Increases in heart rate and blood pressure have been noted at 7.6% and dyspnea, headache, dizziness, and sweating occur if exposure at that level is prolonged. At 10% and above, prolonged exposure can result in unconsciousness. Above 11%, unconsciousness occurs in 1 minute or less. Numerous human fatalities have occurred after persons entered fermentation vats, wells, and silos where oxygen had been largely replaced by carbon dioxide. Exposure to very high concentrations, 25 to 30%, may cause convulsions. Carbon dioxide at room temperature will not injure the skin, but frostbite may result from contact with the solid or the liquid phases.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 44
2. Boiling point (760 mm Hg): −78.5 C (−109 F) (sublimation point)
3. Specific gravity (water = 1): 1.02 (liquid)
4. Vapor density (air = 1 at boiling point of carbon dioxide): 1.52
5. Melting point: −78.5 C (-109 F) (sublimation point)
6. Vapor pressure at 20 C (68 F): Greater than 1

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

atmosphere

7. Solubility in water, g/100 g water at 20 C (68 F): 0.14

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None

2. Incompatibilities: Contact with chemically active metals such as sodium, potassium, or hot titanium may cause fire.

3. Hazardous decomposition products: None

4. Special precautions: Liquid or solid carbon dioxide will attack some forms of plastics, rubber, and coatings. See 29 CFR 1910.101 for specific regulations on storage of compressed gas cylinders.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that carbon dioxide is an odorless gas.

2. Irritation Levels: Grant states that "carbon dioxide at high concentration in air causes a stinging sensation in the eyes, nose, and throat . . . ."

3. Evaluation of Warning Properties: Since carbon dioxide has no odor, and since no quantitative information is available relating its irritant effects of to air concentrations, this gas has been treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of carbon dioxide. Each measurement should consist of a ten (10) minute sample or series of consecutive samples totalling ten (10) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of carbon dioxide in a gas sampling bag, followed by gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure carbon dioxide may be used. An analytical method for carbon dioxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible; when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with solid carbon dioxide or from contact with vessels containing carbon dioxide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to carbon dioxide may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from fermentation in manholes, mine floors, wells, shipwells, brewery vats, garbage dumps, and fruit storage facilities	General dilution ventilation; local exhaust ventilation; personal protective equipment

Operation	Controls
Use in cooling and refrigerating for storage, preparation and transfer of foods; use as an inert gas in fire extinguishers; for protection of flammable materials during manufacture; in shielded arc welding; and in canned food production	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as an inert pressure medium for aerosol packaging; pressure spraying, spray painting, gas-operated firearms, purging tanks and pipelines, inflating liferafts, manufacture of plastic foam	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of carbonated beverages	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a neutralizing agent in textile processing and treatment of leather hides; use as shattering agent for coal mining; in fracturing and acidizing treatment of oil and gas wells	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use during water treatment for neutralizing alkaline waste waters; carbonating water to prevent scaling; use for chemical synthesis and pH control in manufacture of urea, asprin, carbonates and bicarbonates, beer, and sugar	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in miscellaneous operations for enrichment of greenhouse air, antiseptic, industrial solvent extraction, medical use, in foundries, cement curing, and in animal slaughter	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If solid carbon dioxide (dry ice) or carbon dioxide as it is being released from a cylinder gets into the eyes, get medical attention.

- **Skin or Mouth Exposure**

If solid carbon dioxide (dry ice) or carbon dioxide as it is being released from a cylinder comes in contact with the skin or mouth, stop the exposure immediately. If frostbite has occurred, get medical attention.

- **Breathing**

If a person breathes in large amounts of carbon dioxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.
- If carbon dioxide is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Carbon Dioxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Carbon Dioxide," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Cullen, D. J., and Eger, E. I.: "Cardiovascular Effects of Carbon Dioxide in Man," *Anesthesiology*, 41:345-349, 1974.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Carbon Dioxide.* HEW Publication No. (NIOSH) 76-194, GPO No. 017-033-00199-5, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Schulte, J. H.: "Sealed Environments in Relation to Health and Disease," *Archives of Environmental Health*, 8:438-452, 1964.

• Williams, H. I.: "Carbon Dioxide Poisoning - Report of Eight Cases, with Two Deaths," *British Medical Journal*, 2:1012-1014, 1958.

RESPIRATORY PROTECTION FOR CARBON DIOXIDE

Condition	Minimum Respiratory Protection* Required Above 5000 ppm
Gas Concentration	
50,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 50,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Carbon Disulfide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CS_2
- Synonyms: Carbon bisulfide
- Appearance and odor: Colorless to faintly yellow liquid with a strong, disagreeable or sweetish odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for carbon disulfide is 20 parts of carbon disulfide per million parts of air (ppm) averaged over an eight-hour work shift, with a ceiling level of 30 ppm, and an acceptable peak of 100 ppm for 30 minutes in an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be reduced to 1 ppm averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling of 10 ppm averaged over a 15-minute period. The NIOSH Criteria Document for Carbon Disulfide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Carbon disulfide can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation of carbon disulfide vapor may cause headache, nausea, drop in blood pressure, dizziness, unconsciousness, and death. Liquid carbon disulfide and high concentrations of the vapor may cause irritation of the skin, eyes, and nose. If the liquid is trapped under clothing, it may cause a burn. Swallowing carbon disulfide may cause loss of consciousness and convulsions. If small amounts are swallowed, vomiting, diarrhea, and headache may occur.

2. Long-term Exposure: Prolonged or repeated exposure to carbon disulfide may damage the nervous system and cause muscle weakness, numbness, feelings of pins and needles, unsteady walking, and difficulty in swallowing. Palsy, speech difficulty, and muscle spacticity may also occur. In addition, memory loss, headache, difficulty in sleeping, nervousness, fatigue, irritability, depression, suicidal tendencies, and psychosis may occur. Eye damage may occur with such symptoms as blind spots, narrowing of vision, and decreased ability to see in the dark. Increased arteriosclerosis may occur which may cause or increase damage to the heart and other organs. High blood pressure, kidney damage, liver damage, and stomach problems may occur. Repeated or prolonged exposure of the skin to carbon disulfide may cause a skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to carbon disulfide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to carbon disulfide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central and peripheral nervous systems, eyes, cardiovascular system, kidneys, and liver should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney damage has been observed in humans exposed to carbon disulfide, a urinalysis

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

should be obtained to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Since liver damage has been observed in humans exposed to carbon disulfide, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

—An electrocardiogram: Carbon disulfide has caused arrhythmias and electrocardiographic changes in humans. Periodic surveillance is indicated.

—Ophthalmic examination: Carbon disulfide has caused ocular changes in humans. An ophthalmic examination should be performed, including visual acuity.

—Medical warning: Workers should be informed of potential undesirable effects of exposure to carbon disulfide on reproduction (such as spermatic deficiences, menstrual disorders, and spontaneous abortions).

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Carbon disulfide vapor causes narcosis at high concentrations; repeated exposure to low concentrations causes damage to the central and peripheral nervous systems and may accelerate the development of or worsen coronary heart disease. Exposure of humans to 1150 ppm causes serious symptoms, and 4800 ppm for 30 minutes may be fatal. Carbon disulfide intoxication can involve all parts of the central and peripheral nervous systems, including damage to the cranial nerves and development of polyneuritis with paresthesias and muscle weakness in the extremities, unsteady gait, and dysphagia. In extreme cases of intoxication, a Parkinson-like syndrome may result, characterized by speech disturbances, muscle spasticity, tremor, memory loss, mental depression, and marked psychic symptoms; permanent disability is likely. Reproductive disorders occur, such as aspermia, menstrual irregularities, and spontaneous abortion. Psychosis and suicide are established risks of overexposure to carbon disulfide. Other reported effects of exposure to carbon disulfide are ocular changes (retinal degeneration, corneal opacities, disturbances of color vision, corneal anesthesia, diminished pupillary reflexes, microscopic aneurysms in the retina), gastrointestinal disturbances (chronic gastritis and achlorhydria), renal impairment (albuminuria, microhematuria, elevated blood urea nitrogen, diastolic hypertension), and liver damage. Effects commonly caused by repeated exposure to carbon disulfide vapor are exemplified by a group of workers with a time-weighted average (TWA) exposure of 11.2 ppm (range 0.9 to 127 ppm) who complained of headaches and dizziness; in other workers with a TWA of 186 ppm (range 23 to 378 ppm) complaints also included sleep disturbances, fatigue, nervousness, anorexia, and weight loss; the end-of-day exposure coefficient of the iodine azide test on urine was a good indicator of workers who were or had been symptomatic. Overexposure to carbon disulfide has long been regarded as potentially atherogenic for cerebral, renal, and coronary arteries; recent epidemiologic studies of viscose rayon workers have confirmed a 2.5- to 5-fold increase in risk of death from coronary heart disease as compared with the experience of unexposed workers. Other cardiovascular effects observed in workers repeatedly exposed to carbon disulfide are bradycardia, tachycardia, arrhythmias, and electrocardiographic changes consistent with both nonspecific and ischemic wave changes. Splashes of the liquid in the eyes cause immediate and severe irritation; dermatitis and vesiculation may result from skin contact with the vapor or the liquid. Although ingestion is unlikely to occur, it may cause coma and convulsions.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 76.1
2. Boiling point (760 mm Hg): 46.3 C (115 F)
3. Specific gravity (water = 1): 1.27
4. Vapor density (air = 1 at boiling point of carbon disulfide): 2.6
5. Melting point: −111.5 C (-169 F)
6. Vapor pressure at 20 C (68 F): 300 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.2
8. Evaporation rate (butyl acetate = 1): 22.6

• **Reactivity**

1. Conditions contributing to instability: Containers may burst when heated.
2. Incompatibilities: Contact with strong oxidizers, and chemically active metals (such as sodium, potassium, and zinc), azides, and organic amines may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide and carbon monoxide) may be released in a fire involving carbon disulfide.
4. Special precautions: Liquid carbon disulfide will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: −30 C (-22 F) (closed cup)
2. Autoignition temperature: 90 C (194 F)
3. Flammable limits in air, % by volume: Lower: 1.3; Upper: 50
4. Extinguishant: Dry chemical, carbon dioxide for small fires

• **Warning properties**

1. Odor Threshold: The *Handbook of Organic Industrial Solvents* states that at less than 1 ppm, carbon disulfide has a disagreeable odor. Summer gives an odor threshold of 7.7 ppm, and May gives 0.0011 ppm and 0.0081 ppm. The AIHA *Hygienic Guide* gives an odor threshold of 1.2 ppm.
2. Eye Irritation Level: Carbon disulfide is not known to be an eye irritant.
3. Evaluation of Warning Properties: Since the odor threshold of carbon disulfide is below the permissible

exposure limit, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of carbon disulfide. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Peak Above Ceiling Evaluation**

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of carbon disulfide. Each measurement should consist of a 30-minute sample or a series of consecutive samples totalling 30 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of carbon disulfide vapors using an adsorption tube with subsequent desorption with benzene and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure carbon disulfide may be used. An analytical method for carbon disulfide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017 033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid carbon disulfide, where skin contact may occur.

• Non-impervious clothing which becomes contaminated with carbon disulfide should be removed promptly and not reworn until the carbon disulfide is removed from the clothing.

• Any clothing which becomes wet with liquid carbon disulfide should be removed immediately and not reworn until the carbon disulfide is removed from the clothing.

• Clothing wet with liquid carbon disulfide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of carbon disulfide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the carbon disulfide, the person performing the operation should be informed of carbon disulfide's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where liquid carbon disulfide may contact the eyes.

SANITATION

• Skin that becomes contaminated with carbon disulfide should be promptly washed or showered with soap or mild detergent and water to remove any carbon disulfide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to carbon disulfide may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of viscose rayon during xanthation of cellulose and spinning and cutting operations; use as a xanthating agent in manufacture of cellophane; use during manufacture of pesticides	Process enclosure; local exhaust ventilation; general dilution ventilation; temperature control; personal protective equipment
Use as a fumigant and spray application on grains, and space fumigation of agricultural premises	General dilution ventilation; temperature control; personal protective equipment
Use in synthesis of carbon tetrachloride	Process enclosure; local exhaust ventilation; general dilution ventilation; temperature control; personal protective equipment
Use in synthesis of intermediates and manufacture of dyes, pharmaceuticals, rubber chemicals, pesticides, and flotation agents	Process enclosure; local exhaust ventilation; general dilution ventilation; temperature control; personal protective equipment
Liberation during destructive distillation of coal in manufacture of coal gas and coal tar	Process enclosure; local exhaust ventilation; general dilution ventilation; temperature control; personal protective equipment
Use as a solvent in dry spinning of polyvinyl chloride; as a solvent in oil wells; use in manufacture of optical glass	Process enclosure; local exhaust ventilation; general dilution ventilation; temperature control; personal protective equipment
Use during rubber manufacture in cold curing operations; during extraction processing of oils, fats, resins, and waxes; use in manufacture of matches	Process enclosure; local exhaust ventilation; general dilution ventilation; temperature control; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid carbon disulfide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid carbon disulfide gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid carbon disulfide soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of carbon disulfide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid carbon disulfide has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If carbon disulfide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Carbon disulfide should not be allowed to enter a confined space, such as

a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of carbon disulfide vapors are permitted.

• Waste disposal method:

Carbon disulfide may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Carbon Disulfide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Carbon Disulfide," *Hygienic Guide Series*, Detroit, Michigan, 1956.

• *American National Standard Acceptable Concentrations - Carbon Disulfide*: ANSI-Z37.3-1968, American National Standards Institute, Inc., New York, 1968.

• Brieger, H.: "Chronic Carbon Disulfide Poisoning," *Journal of Occupational Medicine*, 14:123-124, 1972.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Davidson, M., and Feinleib, M.: "Carbon Disulfide Poisoning: A Review," *American Heart Journal*, 83:100-114, 1972.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Djuric, D., et al.: "Iodine-Azide Test on Urine of Persons Exposed to Carbon Disulphide," *British Journal of Industrial Medicine*, 22:321-323, 1965.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Graovac-Leposavic, L., et al.: "The Use of the Iodine-Azide Test for the Early Diagnosis of Carbon Disulphide Poisoning," in H. Brieger and J. Teisinger (eds.), *Toxicology of Carbon Disulfide - Proceedings*, Excerpta Medica Foundation, Amsterdam, 1967, pp. 62-69.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• Hanninen, H.: "Psychological Picture of Manifest and Latent Carbon Disulfide Poisoning," *British Journal of Industrial Medicine*, 28:374-381, 1971.

• Hernberg, S., et al.: "Coronary Heart Disease among Workers Exposed to Carbon Disulphide," *British Journal of Industrial Medicine*, 27:313-325, 1970.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1974.

• Lauwerys, R.: "Biological Criteria for Selected Industrial Toxic Chemicals: A Review," *Scandinavian Journal of Work Environment and Health*, 1:139, 151, 162-163, 168, 170-171, 1975.

• Lieben, J., et al.: "Cardiovascular Effects of CS_2 Exposure," *Journal of Occupational Medicine*, *16:449-453. 1974.*

• Mancuso, T. F., and Locke, B. Z.: "Carbon Disulphide as a Cause of Suicide - Epidemiological Study of Viscose Rayon Workers," *Journal of Occupational Medicine*, 14:595-606, 1972.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-12, Carbon Disulfide*, Washington, D.C., 1967.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute of Health: "Carbon Disulfide: Its Toxicity and Potential Dangers," *Public Health Reports*, 56:574-581, 1941.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Carbon Disulfide*, HEW Publication No. (NIOSH) 77-156, GPO No. 017-033-00216-9, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Rosensteel, R. E., et al.: "Occupational Health Case Report - No. 1," *Journal of Occupational Medicine*, 16:22-32, 1974.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• Tolonen, M.: "Vascular Effects of Carbon Disulfide, A Review," *Scandinavian Journal of Work Environment and Health*, 1:63-77, 1975.

• World Health Organization: *Early Detection of Health Impairment in Occupational Exposure to Health Hazards*, Technical Report Series No. 571, Geneva, 1975.

• Zenz, C.: *Occupational Medicine - Principles and Practical Applications*, Year Book Medical Publishers, Chicago, 1975.

RESPIRATORY PROTECTION FOR CARBON DISULFIDE

Condition	Minimum Respiratory Protection* Required Above 20 ppm
Vapor Concentration	
200 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).
	Any supplied-air respirator.
	Any self-contained breathing apparatus.
500 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Carbon Monoxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CO
- Synonyms: Monoxide
- Appearance and odor: Colorless, odorless gas.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for carbon monoxide is 50 parts of carbon monoxide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 55 milligrams of carbon monoxide per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to 35 ppm averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling of 200 ppm. The NIOSH Criteria Document for Carbon Monoxide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Carbon monoxide can affect the body if it is inhaled or if liquid carbon monoxide comes in contact with the eyes or skin.

- **Effects of overexposure**

Exposure to carbon monoxide decreases the ability of the blood to carry oxygen to the tissues. Inhalation of carbon monoxide may cause headache, nausea, dizziness, weakness, rapid breathing, unconsciousness, and death. High concentrations may be rapidly fatal without producing significant warning symptoms. Exposure to this gas may aggravate heart disease and artery disease and may cause chest pain in those with pre-existing heart disease. Pregnant women are more susceptible to the effects of carbon monoxide exposure. The effects are also more severe in people who are working hard and in people who are working in places where the temperature is high or at altitudes above 2,000 feet. Skin exposure to liquid carbon monoxide may cause frostbite-type burns.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to carbon monoxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to carbon monoxide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of coronary heart disease, anemia, pulmonary heart disease, cerebrovascular disease, thyrotoxicosis, and smokers would be expected to be at increased risk from exposure. Pregnant women have an increased sensitivity to the effects of carbon monoxide. Examination of the cardiovascular system, the pulmonary system, the blood, and the central nervous system should be stressed.

—A complete blood count: Carbon monoxide affects the ability of the blood to carry oxygen. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, with the exception that a carboxyhemoglobin determination should be performed at any time overexposure is suspected or signs or symptoms of toxicity occur.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service . Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

• **Summary of toxicology**

Carbon monoxide (CO) gas causes tissue hypoxia by preventing the blood from carrying sufficient oxygen. CO combines reversibly with the oxygen-carrying sites on the hemoglobin molecule with an affinity ranging from 210 to 240 times greater than that of oxygen; the carboxyhemoglobin thus formed is unavailable to carry oxygen. In addition, carboxyhemoglobin interferes with the release of oxygen carried by unaltered hemoglobin. With exposure to high concentrations such as 4000 ppm and above, transient weakness and dizziness may be the only premonitory warnings before coma supervenes; the most common early aftermath of severe intoxication is cerebral edema. Exposure to concentrations of 500 to 1000 ppm causes the development of headache, tachypnea (rapid breathing), nausea, weakness, dizziness, mental confusion, and in some instances, hallucinations, and may result in brain damage. The affected person is commonly cyanotic. Concentrations as low as 50 ppm result in blood COHb levels up to 10% in an 8-hour day. This greatly increases the risk of angina pectoris and coronary infarctions by decreasing the oxygen supply in the blood and also in the myoglobin of the heart muscle. These effects are aggravated by heavy work, high ambient temperatures, and high altitudes. Pregnant women are especially susceptible to the effects of increased CO levels. Smoking also increases the risk: cigarette smoke contains 4% CO, which results in 5.9% COHb if a pack a day is smoked. The blood of persons not exposed to CO contains about 1% CO, probably as a result of normal heme metabolism. The diagnosis of CO intoxication depends primarily on the demonstration of significantly increased carboxyhemoglobin in the blood. Levels over 60% are usually fatal; 40% is associated with collapse and syncope; above 25% there may be electrocardiographic evidence of a depression of the S-T segment; between 15% and 25% there may be headache and nausea. The reaction to a given blood level of carboxyhemoglobin is extremely variable: some persons may be in coma with a carboxyhemoglobin level of 38% while others may maintain an apparently clear sensorium with levels as high as 55%. The blood of cigarette smokers contains 3 to 10% carboxyhemoglobin, and nonexposed persons have an average level of 1%, probably as a result of normal heme metabolism. Several investigators have suggested that the results of behavioral tests such as time discrimination, visual vigilance, choice response tests, visual evoked responses, and visual discrimination thresholds may be altered at levels of carboxyhemoglobin below 5%.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 28
2. Boiling point (760 mm Hg): −191.5 C (-313 F)
3. Specific gravity (water = 1): 0.79 (liquid at boiling point)
4. Vapor density (air = 1 at boiling point of carbon monoxide): 0.97
5. Melting point: −199 C (-326 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): 0.004
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause cylinders to explode.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: None
4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: 609 C (1128 F)
3. Flammable limits in air, % by volume: Lower: 12.5; Upper: 74
4. Extinguishant: Dry chemical. If flow of gas cannot be stopped, let fire burn.

• **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* points out that carbon monoxide is odorless.
2. Eye Irritation Level: Grant states that carbon monoxide is a non-irritating gas.
3. Evaluation of Warning Properties: Carbon monoxide is an odorless, non-irritating gas. It has no warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of carbon monoxide. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of carbon monoxide vapors using an adsorption tube with a subsequent chemical analysis of the adsorption

tube. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure carbon monoxide may be used. An analytical method for carbon monoxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid carbon monoxide or from contact with vessels containing liquid carbon monoxide.

• Any clothing which becomes wet with liquid carbon monoxide should be removed immediately and not reworn until the carbon monoxide has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid carbon monoxide may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to carbon monoxide may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from emissions in enclosed places from exhaust fumes of internal combustion engines; from metallurgic industry and foundries; from chemical industry for synthesis and emission as result of incomplete combustion	Local exhaust ventilation; respiratory protective device
Liberation during acetylene welding; from enclosed areas as mines or tunnels; from fire-damp explosions	Local exhaust ventilation; respiratory protective device
Liberation from industrial heating	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of carbon monoxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks or releases until cleanup has been completed.

• If carbon monoxide is leaked or released in hazardous concentrations, the following steps should be taken:

1. Ventilate area of leak or release to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Carbon Monoxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Carbon Monoxide," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Community Air Quality Guides: "Carbon Monoxide," *American Industrial Hygiene Association Journal*, 30:322-325, 1969.

• Goldsmith, J. R., and Aronow, W. S.: "Carbon Monoxide and Coronary Heart Disease: A Review," *Environmental Research*, 10:236-248, 1975.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Carbon Monoxide*, HEW Publication No. HSM 73-11000, GPO No. 017-033-00006, U.S. Government Printing Office, Washington, D.C., 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Zenz, C.: *Occupational Medicine - Principles and Practical Applications*, Year Book Medical, Inc., Chicago, 1975.

RESPIRATORY PROTECTION FOR CARBON MONOXIDE

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Gas Concentration	
500 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
1500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 1500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against carbon monoxide. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Carbon Tetrachloride*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CCl_4
- Synonyms: Tetrachloromethane
- Appearance and odor: Colorless liquid with an ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for carbon tetrachloride is 10 parts of carbon tetrachloride per million parts of air (ppm) averaged over an eight-hour work shift, with an acceptable ceiling concentration of 25 ppm and a maximum allowable peak of 200 ppm for up to 5 minutes in any four-hour period. NIOSH has recommended that the permissible exposure limit be reduced to a ceiling level of 2 ppm averaged over a one-hour period, and that carbon tetrachloride be regulated as an occupational carcinogen. The NIOSH Criteria Document for Carbon Tetrachloride should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Carbon tetrachloride can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to carbon tetrachloride may cause drowsiness, dizziness, incoordination, and unconsciousness. Delayed effects from short-term overexposure include damage to the heart, liver, and kidneys. Symptoms of liver damage include yellow jaundice and dark urine. Eye contact with liquid carbon tetrachloride causes burning and intense irritation.

2. Long-term Exposure: Prolonged or repeated exposure may cause liver and kidney damage. Repeated or prolonged contact of the liquid with the skin may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to carbon tetrachloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to carbon tetrachloride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of liver and kidneys should be stressed. The skin and eyes should be examined for evidence of chronic disorders.

—Liver function tests: Carbon tetrachloride causes liver damage. A profile of liver function should be obtained using a medically acceptable array of biochemical tests.

—Urinalysis: Since kidney damage has also been observed from exposure, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Carbon tetrachloride vapor is a narcotic and causes severe damage to the liver and kidneys. In animals the primary damage from intoxication is to the liver, but in humans the majority of fatalities have been the result of renal injury with secondary cardiac failure. In humans, liver damage occurs more often after ingestion of the

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

liquid than after inhalation of the vapor. Human fatalities from acute renal damage have occurred after exposure for @1/2 to 1 hour to concentrations of 1000 to 2000 ppm. Cardiac arrhythmias have been reported. Exposure to high concentrations results in symptoms of central nervous system depression, including dizziness, vertigo, incoordination, and mental confusion; abdominal pain, nausea, vomiting, and diarrhea are frequent. Polycythemia followed by anemia and hemodilution may occur. Within a few days, jaundice may appear and liver injury progress to toxic necrosis. At the same time, acute nephritis occurs, and albumin, red and white blood cells, and casts appear in the urine; there may be oliguria, anuria, and increased nitrogen retention resulting in the development of uremia. There are several reports of adverse effects in workmen who were repeatedly exposed to concentrations between 25 and 30 ppm; nausea, vomiting, dizziness, drowsiness, and headache were frequently noted. The effects of carbon tetrachloride in humans who are addicted to alcohol are more severe than usual. No adverse symptoms resulted from repeated exposure to 10 ppm. The liquid splashed in the eye causes pain and minimal injury to the conjunctiva. Prolonged or repeated skin contact with the liquid may result in skin irritation. It can be absorbed through the intact skin of animals and humans in toxic amounts. Hepatomas have been reported in several animal species and in man.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 153.8
  2. Boiling point (760 mm Hg): 76.8 C (170 F)
  3. Specific gravity (water = 1): 1.59
  4. Vapor density (air = 1 at boiling point of carbon tetrachloride): 5.3
  5. Melting point: −23 C (-9 F)
  6. Vapor pressure at 20 C (68 F): 91 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.08
  8. Evaporation rate (butyl acetate = 1): 12.8
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Carbon tetrachloride reacts with chemically active metals such as sodium, potassium, and magnesium.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, chlorine, phosgene, and carbon monoxide) may be released when carbon tetrachloride decomposes.
  4. Special precautions: Liquid carbon tetrachloride will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**
  1. Odor Threshold: Carbon tetrachloride has an odor threshold of approximately 50 ppm, according to the *Hygienic Guide.*
  2. Eye Irritation Level: Grant states that carbon tetrachloride is slightly irritating to the eyes, but does not mention the concentrations at which irritation occurs. In addition, carbon tetrachloride is "strongly suspected of causing retrobulbar neuritis, optic neuritis, and optic atrophy."
  3. Evaluation of Warning Properties: Since the odor threshold of carbon tetrachloride is well above the permissible exposure, and since no quantitative data are available relating its warning properties to air concentrations, carbon tetrachloride is considered as a substance with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of carbon tetrachloride. Each measurement to determine short-duration ceiling levels should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure. Each measurement to determine a one-hour ceiling should consist of a one-hour sample or a series of consecutive samples totalling one hour.

- **Peak Above Ceiling Evaluation**

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of carbon tetrachloride. Each measurement should consist of a 30-minute sample or a series of consecutive samples totalling 30 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure carbon tetrachloride may be used. An analytical method for carbon tetrachloride is in the

NIOSH Manual of Analytical Methods, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid carbon tetrachloride.
- Clothing wet with liquid carbon tetrachloride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of carbon tetrachloride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the carbon tetrachloride, the person performing the operation should be informed of carbon tetrachloride's hazardous properties.
- Non-impervious clothing which becomes contaminated with liquid carbon tetrachloride should be removed promptly and not reworn until the carbon tetrachloride is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid carbon tetrachloride may contact the eyes.

SANITATION

- Skin that becomes wet with liquid carbon tetrachloride should be promptly washed or showered with soap or mild detergent and water to remove any carbon tetrachloride.
- Eating and smoking should not be permitted in areas where carbon tetrachloride is handled, processed, or stored.
- Employees who handle liquid carbon tetrachloride should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.
- Areas in which exposure to carbon tetrachloride can occur should be identified by signs or other appropriate means, and access to these areas should be limited to authorized persons.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to carbon tetrachloride may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of fluorocarbons for aerosols, refrigerants, and fire extinguishants	Material substitution; process enclosure; local exhaust ventilation; personal protective equipment
Use as an agricultural grain fumigant and pesticide	Material substitution; personal protective equipment
Use in polymer technology as reaction medium, catalyst, chain transfer agent, and solvent for resins; in organic synthesis for chlorination of organic compounds in soap perfumery and insecticide industries	Process enclosure; local exhaust ventilation
Use as an industrial solvent for rubber cements, cable and semiconductor manufacture, separation of xylene isomers as components to reduce flammability	Material substitution; process enclosure; local exhaust ventilation; personal protective equipment
Use as a laboratory solvent	Material substitution; personal protective equipment
Use in metal recovery and catalyst regeneration	Process enclsoure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If carbon tetrachloride gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present

after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If carbon tetrachloride gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If carbon tetrachloride soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of carbon tetrachloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When carbon tetrachloride has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If carbon tetrachloride is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Carbon tetrachloride may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Carbon Tetrachloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Carbon Tetrachloride," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Fassett, D. W.: "Toxicology of Organic Compounds: A Review of Current Problems," *Annual Review of Pharmacology*, 3:267-274, 289-292, 1963.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 2 – Carbon Tetrachloride*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1973.

• International Agency for Research on Cancer: *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Vol. I, Lyon, France, 1972.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-3, Carbon Tetrachloride*, Washington, D.C., 1963.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Carbon Tetrachloride*, HEW Publication No. (NIOSH) 76-133, NTIS No. PB250424, U.S. Government Printing Office, Washington, D.C., 1976 (revised).

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stewart, R. D., and Dodd, H. C.: "Absorption of Carbon Tetrachloride, Trichloroethylene, Tetrachloroethylene, Methylene Chloride, and 1,1,1-Trichloroethane through the Human Skin," *Industrial Hygiene Journal*, September - October, 1964, p. 439.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 1, 1972.

RESPIRATORY PROTECTION FOR CARBON TETRACHLORIDE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
100 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
300 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 300 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chlordane*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_6Cl_8$ (approx.)
- Synonyms: 1,2,4,5,6,7,8,8-Octachloro-3a,4,7,7a-tetrahydro-4,7-methanoindane; 1,2,4,5,6,7,8,8-octachloro-2,3, 3a,4,7,7a-hexahydro-4,7-methanoindene
- Appearance and odor: Thick amber liquid with a characteristic chlorine-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlordane is 0.5 milligram of chlordane per cubic meter of air (mg/m³) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlordane can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to chlordane may cause shaking, blurred vision, irritability, confusion, delirium, staggering, convulsions, and death. Swallowing chlordane may also cause nausea, vomiting, and diarrhea. Chlordane exposure may cause kidney and liver damage. Absorption of chlordane through the skin is rapid and has resulted in death.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlordane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlordane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of convulsive disorders would be expected to be at increased risk from exposure. Examination of the nervous system, eyes, lungs, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney damage has been observed in humans exposed to chlordane, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Chlordane predominantly affects the central nervous system, causing irritability, tremors, and convulsions. Chronic effects are reported in animals. Repeated oral administration to rabbits indicated a cumulative action at daily doses above 5 mg/kg; autopsy revealed focal necrosis of the liver, degenerative changes in the proximal convoluted tubules, pulmonary exudates and gastrointestinal irritation. In humans, inhalation and skin absorption have resulted in blurred vision, cough, confusion, ataxia, and delirium; ingestion has caused abdominal pain, nausea, vomiting, and diarrhea; severe intoxication has caused irritability, tremor, convulsions, and death. A suicidal person who ingested 6 g (104 mg/kg) of chlordane in talc suffered burns of the mouth, severe gastritis, diffuse pneumonia, anuria, mania, and convulsions; death occurred after 9.5 days; autopsy findings were severe necrotizing bronchopneumonia

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

and degeneration of renal tubule epithelium. Skin absorption of chlordane is rapid; a worker who spilled a 25% suspension of chlordane on clothing, which was not removed, began having convulsions 40 minutes later and died shortly thereafter. Technical-grade chlordane is stated to be irritating to the skin and mucous membranes, but this may be due to the presence of unreacted chemical intermediates.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 409.8 (approx).
2. Boiling point (760 mm Hg): (Decomposes); 175 C (347 F) (at 2 mm Hg)
3. Specific gravity (water = 1): 1.57 – 1.67
4. Vapor density (air = 1 at boiling point of chlordane): 14
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): 0.00001 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Temperatures above 200 C (392 F) cause decomposition with formation of chlorine and hydrogen chloride gases.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, chlorine, phosgene, and carbon monoxide) may be released when chlordane decomposes.
4. Special precautions: Chlordane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible

- **Warning properties**

Since chlordane has such a low vapor pressure, warning properties are not considered. Grant describes certain effects produced by chlordane on the eyes, but these effects were caused by systemic poisoning. They were not local effects. Chlordane is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for chlordane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with chlordane.
- If employees' clothing has had any possibility of being contaminated with chlordane, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing which has had any possibility of being contaminated with chlordane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chlordane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chlordane, the person performing the operation should be informed of chlordane's hazardous properties.
- Where there is any possibility of exposure of an employee's body to chlordane, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with chlordane should be removed immediately and not reworn until the chlordane is removed from the clothing
- Employees should be provided with and required to use dust- and splash-proof safety goggles where chlor-

dane may contact the eyes.

SANITATION

- Skin that becomes contaminated with chlordane should be immediately washed or showered with soap or mild detergent and water to remove any chlordane.
- Workers subject to skin contact with chlordane should wash with soap or mild detergent and water any areas of the body which may have contacted chlordane at the end of each work day.
- Eating and smoking should not be permitted in areas where chlordane is handled, processed, or stored.
- Employees who handle chlordane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlordane may occur and control methods which may be effective in each case:

Operation	Controls
Application as an insecticide on pre-planting soil, fire ants, and harvester ants (banned by EPA in 1976)	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If chlordane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If chlordane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If chlordane soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

- **Breathing**

If a person breathes in large amounts of chlordane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When chlordane has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous area. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If chlordane is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

- Waste disposal method:

Chlordane may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Chlordane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
- Council on Pharmacy and Chemistry, American Medical Association: "The Present Status of Chlordane," *Journal of the American Medical Association*, 158:1364-1367, 1955.
- Derbes, V. J., et al.: "Fatal Chlordane Poisoning," *Journal of the American Medical Association*, 158:1367-1369, 1955.
- Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.
- *Hygienic Information Guide No. 70 - Chlordane*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health,

dane may contact the eyes.

SANITATION

- Skin that becomes contaminated with chlordane should be immediately washed or showered with soap or mild detergent and water to remove any chlordane.
- Workers subject to skin contact with chlordane should wash with soap or mild detergent and water any areas of the body which may have contacted chlordane at the end of each work day.
- Eating and smoking should not be permitted in areas where chlordane is handled, processed, or stored.
- Employees who handle chlordane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlordane may occur and control methods which may be effective in each case:

Operation	Controls
Application as an insecticide on pre-planting soil, fire ants, and harvester ants (banned by EPA in 1976)	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If chlordane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If chlordane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If chlordane soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

- **Breathing**

If a person breathes in large amounts of chlordane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When chlordane has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If chlordane is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

- Waste disposal method:

Chlordane may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Chlordane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
- Council on Pharmacy and Chemistry, American Medical Association: "The Present Status of Chlordane," *Journal of the American Medical Association*, 158:1364-1367, 1955.
- Derbes, V. J., et al.: "Fatal Chlordane Poisoning," *Journal of the American Medical Association*, 158:1367-1369, 1955.
- Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.
- *Hygienic Information Guide No. 70 - Chlordane*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health,

1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Plant, A. (ed.): *Chemical and Engineering News*, 22 December 1975.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Stohlman, E. F., et al.: "Toxic Action of Chlordane," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 1:13-19, 1950.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 20, 1979.

RESPIRATORY PROTECTION FOR CHLORDANE

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. A chin-style or front- or back-mounted pesticide gas mask. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode. A powered chemical cartridge respirator with an organic vapor cartridge and a high efficiency filter, including pesticide respirators which meet the requirements of this class.
Greater than 500 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of chlordane; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 500 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Chlorinated Camphene*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_{10}Cl_8$ (average)
- Synonyms: Toxaphene
- Appearance and odor: Waxy, amber-colored solid with a mild, turpentine-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorinated camphene is 0.5 milligram of chlorinated camphene per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorinated camphene can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin. It may enter the body through the skin.

- **Effects of overexposure**

Overexposure to chlorinated camphene may cause nausea, mental confusion, agitation, involuntary trembling, convulsions, and unconsciousness. Contact with chlorinated camphene solutions may cause irritation of the skin.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorinated camphene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorinated camphene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system and the skin should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Chlorinated camphene is primarily a strong stimulant to the central nervous system. Most fatal cases of poisoning have been due to accidental ingestion, resulting in convulsions, loss of consciousness, and respiratory failure. The minimal acute lethal oral dose for man is 2 to 7 g. Few cases of intoxication due to occcupational exposure have been reported. Two cases of pneumonitis in insecticide sprayers using chlorinated camphene in an emulsion containing kerosene and xylene have been reported, but the significance of this finding is questionable as it relates to the toxicity of chlorinated camphene exposure. In solution, the substance is absorbed through the skin and causes skin irritation. In man, a single dermal application of 46 grams, or daily application of 2.4 grams, is very dangerous. Animals given repeated oral doses show degenerative changes in the liver and kidneys. Chronic exposure results in the accumulation of the substance in the fatty tissues. It is metabolized in the liver and excreted in the urine, probably in a conjugated form. Laboratory testing has indicated that this substance causes cancer in laboratory animals.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

2:17

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 414 (average)
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.63
4. Vapor density (air = 1 at boiling point of chlorinated camphene): 14.3
5. Melting point: 70 to 95 C (158 to 203 F)
6. Vapor pressure at 20 C (68 F): 0.2 to 0.4 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0003
8. Evaporation rate (butyl acetate = 1): Data not available.

- **Reactivity**

1. Conditions contributing to instability: Heat, especially when in contact with iron.
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving chlorinated camphene.
4. Special precautions: Emulsifiable concentrates of chlorinated camphene in xylene may decompose with liberation of much heat if allowed to come in contact with iron or aluminum above 70 C (158 F).

- **Flammability**

1. Flash point: 135 C (275 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, carbon dioxide

- **Warning properties**

Chlorinated camphene is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of chlorinated camphene on a filter, followed by extraction with petroleum ether, and gas chromatographic analysis. An analytical method for chlorinated camphene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquids containing chlorinated camphene and to prevent repeated or prolonged skin contact with solid chlorinated camphene.
- If employees' clothing may have become contaminated with solid chlorinated camphene, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with solid chlorinated camphene or liquids containing chlorinated camphene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chlorinated camphene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chlorinated camphene, the person performing the operation should be informed of chlorinated camphene's hazardous properties.
- Where exposure of an employee's body to liquids containing chlorinated camphene may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with solid chlorinated camphene should be removed promptly and non-impervious clothing which becomes contaminated with liquids containing chlorinated camphene should be removed immediately and such clothing should not be reworn until the chlorinated camphene is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where solid

chlorinated camphene or liquids containing chlorinated camphene may contact the eyes.

SANITATION

- Skin that becomes contaminated with solid chlorinated camphene should be promptly washed or showered and skin that becomes contaminated with liquids containing chlorinated camphene should be immediately washed or showered with soap or mild detergent and water to remove any chlorinated camphene.
- Eating and smoking should not be permitted in areas where solid chlorinated camphene or liquids containing chlorinated camphene are handled, processed, or stored.
- Employees who handle solid chlorinated camphene or liquids containing chlorinated camphene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorinated camphene may occur and control methods which may be effective in each case:

Operation	Controls
Mixing and formulation of liquid, dust, powder, and granular insecticides	Personal protective equipment
Use in application of liquid, dust, powder, or granular insecticide formulations	Personal protective equipment
Manufacture and packaging of chlorinated camphene	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If chlorinated camphene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If chlorinated camphene gets on the skin, promptly wash the contaminated skin using soap or mild detergent. If liquids containing chlorinated camphene get on the skin, immediately wash the skin using soap or mild detergent. If liquids containing chlorinated camphene soak through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent.

- **Breathing**

If a person breathes in large amounts of chlorinated camphene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When chlorinated camphene has been swallowed, get medical attention immediately. If the chlorinated camphene is dissolved in a petroleum-based material, do not make the exposed person vomit. If medical attention is not immediately available and the chlorinated camphene is a powder or in a water base, get the person to vomit by having him touch the back of the throat with his finger or by giving him large amounts (one pint or more) of warm salt water (two tablespoons of salt per pint of water). Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If chlorinated camphene is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, use a procedure similar to that for small quantities.

- Waste disposal methods:

Chlorinated camphene may be disposed of:

1. By making packages of chlorinated camphene in paper or other flammable material and burning in a suitable combustion chamber.
2. By dissolving chlorinated camphene in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with afterburner and scrubber (alkali).

ADDITIONAL INFORMATION

To find additional information on chlorinated camphene, look up chlorinated camphene in the following documents:

- Medical Surveillance for Chemical Hazards
- Respiratory Protection for Chemical Hazards
- Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Chlorinated Camphene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
- Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
- Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.
- Hercules Product Bulletin: *Chlorinated Camphene - AP103.*
- McGee, L. C.: "Accidental Poisoning by Toxaphene," *Journal of the American Medical Association*, 149:1124-1126, 1952.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
- Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
- Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.
- Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.
- U.S. Department of Health, Education, and Welfare: *Bioassay of Toxaphene for Possible Carcinogenicity*, U.S. DHEW, National Cancer Institute, Publication No. (NIH) 79-837, 1979.
- Warraki, S.: "Respiratory Hazards of Chlorinated Camphene," *Archives of Environmental Health*, 7:137-140, 1963.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 20, 1979.

RESPIRATORY PROTECTION FOR CHLORINATED CAMPHENE

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Vapor Concentration	
5 mg/m³ or less	Any pesticide chemical cartridge respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	Any pesticide chemical cartridge respirator with a full facepiece. A chin-style or front- or back-mounted pesticide gas mask. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A powered air-purifying pesticide respirator. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of chlorinated camphene; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 200 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Chlorinated Diphenyl Oxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{12}H_4Cl_6O$
- Synonyms: Hexachlorodiphenyl oxide
- Appearance: Waxy solid or liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorinated diphenyl oxide is 0.5 milligram of chlorinated diphenyl oxide per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorinated diphenyl oxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed. Every effort should be made to prevent skin, eye, oral, or inhalation contact with this material.

- **Effects of overexposure**

Exposure to chlorinated diphenyl oxide may cause an acne-like skin eruption or irritation. It may also injure the liver, resulting in such effects as fatigue, dark urine, and yellow jaundice.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorinated diphenyl oxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorinated diphenyl oxide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Chlorinated diphenyl oxide may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Chlorinated diphenyl oxide vapor causes an acne-form dermatitis (chloracne). In laboratory animals, cumulative liver damage has resulted from repeated bodily intake and, in general, the toxicity increases with the degree of chlorination; in guinea pigs, a single oral dose of .05 to 0.1 g/kg of material containing 4 or more equivalents of chlorine resulted in death 30 days after administration. Limited experience with humans has shown that exposure to even small amounts of the higher chlorinated derivatives may result in appreciable acne-form dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 377
2. Boiling point (760 mm Hg): 230 to 260 C (446 to 500 F)
3. Specific gravity (water = 1): 1.60
4. Vapor density (air = 1 at boiling point of chlorinated diphenyl oxide): 13
5. Melting point: Data not available

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

6. Vapor pressure at 20 C (68 F): Less than 0.00006 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): 0.1

8. Evaporation rate (butyl acetate = 1): Not available

• **Reactivity**

1. Conditions contributing to instability: Heat.

2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving chlorinated diphenyl oxide.

4. Special precautions: None.

• **Flammability**

1. Flash point: None

2. Autoignition temperature: 627 C (1163 F)

3. Flammable limits in air, % by volume: Not available

4. Extinguishant: Carbon dioxide, dry chemical

• **Warning properties**

Since there are no quantitative data relating warning properties to air concentrations of chlorinated diphenyl oxide, this material is treated as a substance with poor warning properties. The concentration of chlorinated diphenyl oxide in saturated air at 20 C could result in a significant exposure relative to the permissible exposure. There is no available information which indicates that chlorinated diphenyl oxides produce eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of chlorinated diphenyl oxide on a filter with subsequent extraction with iso-octane and gas chromatographic analysis. An analytical method for chlorinated diphenyl oxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with chlorinated diphenyl oxide.

• If employees' clothing may have become contaminated with chlorinated diphenyl oxide, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with chlorinated diphenyl oxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chlorinated diphenyl oxide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chlorinated diphenyl oxide, the person performing the operation should be informed of chlorinated diphenyl oxide's hazardous properties.

• Non-impervious clothing which becomes contaminated with chlorinated diphenyl oxide should be removed promptly and not reworn until the chlorinated diphenyl oxide is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where chlorinated diphenyl oxide may contact the eyes.

SANITATION

• Workers subject to skin contact with chlorinated diphenyl oxide should wash with soap or mild detergent and water any areas of the body which may have contacted chlorinated diphenyl oxide at the end of each work day.

• Skin that becomes contaminated with chlorinated diphenyl oxide should be promptly washed or showered with soap or mild detergent and water to remove any chlorinated diphenyl oxide.

• Eating and smoking should not be permitted in areas where chlorinated diphenyl oxide is handled, processed, or stored.

• Employees who handle chlorinated diphenyl oxide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorinated diphenyl oxide may occur and control methods which may be effective in each case:

Operation	Controls
Use as intermediate in organic synthesis in manufacture of flame-inhibiting polymers; corrosion inhibitors, dry cleaning detergents, thermal lubricants, additives for soaps and lotions, manufacture of hydraulic fluids, pesticides, wood preservatives, and electric insulators (Literature review suggests that this compound is of little or no industrial significance).	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If chlorinated diphenyl oxide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If chlorinated diphenyl oxide gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid chlorinated diphenyl oxide or liquids containing chlorinated diphenyl oxide soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chlorinated diphenyl oxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When chlorinated diphenyl oxide has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chlorinated diphenyl oxide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. If in solid form, small quantities may be swept onto paper or other suitable material, placed in an appropriate container and burned in a safe place (such as a fume hood). Larger quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
4. If in the liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Chlorinated diphenyl oxide may be disposed of:

1. If in the solid form, by making packages of chlorinated diphenyl oxide in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device, or by dissolving in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. If in the liquid form, by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill, or by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

ADDITIONAL INFORMATION

To find additional information on chlorinated diphenyl oxide, look up chlorinated diphenyl oxide in the following documents:

- Medical Surveillance for Chemical Hazards
- Respiratory Protection for Chemical Hazards
- Personal Protection and Sanitation for Chemical Hazards

These documents are availeble through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR CHLORINATED DIPHENYL OXIDE

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate or Vapor Concentration	
5 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 5 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors, acid gases, and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chlorine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Cl_2
- Synonyms: None
- Appearance and odor: Amber liquid or greenish-yellow gas with a characteristic irritating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorine is a ceiling level of 1 part of chlorine per million parts of air (ppm) averaged over a 15-minute period (*Federal Register*, Vol. 43, No. 237, pp. 57601-03, 8 December 1978). This may also be expressed as 3 milligrams of chlorine per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to 0.5 ppm (1.5 mg/m^3) measured over a 15-minute period. The NIOSH Criteria Document for Chlorine should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorine can affect the body if it is inhaled, or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Chlorine gas may cause severe irritation of the eyes and respiratory tract with tearing, runny nose, sneezing, coughing, choking, and chest pain. Severe breathing difficulties may occur which may be delayed in onset. Pneumonia may result. Severe exposures may be fatal. In high concentrations chlorine may irritate the skin and cause sensations of burning and prickling, inflammation, and blister formation. Liquid chlorine may cause eye and skin burns on contact.

2. Long-term Exposure: Repeated or prolonged exposure to chlorine may cause corrosion of the teeth and skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorine at potentially hazardous levels:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory tract, cardiac status, and teeth should be stressed. The skin should be examined for evidence of chronic disorders. Simple tests of olfactory ability should be carried out.

—14" x 17" chest roentgenogram: Chlorine causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Chlorine is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The above medical examinations are to be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Chlorine gas is a severe irritant of the eyes, mucous membranes, and skin. The odor threshold for chlorine has been reported at various concentrations and appears to be between 0.02 and 0.2 ppm for most subjects. Nasal irritation and coughing occur at about 0.5 ppm. There is evidence that olfactory fatigue develops at these low concentrations and that some tolerance is built up in

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

chronic industrial exposures. An accidental exposure of humans to unmeasured but high concentrations for a brief period caused burning of the eyes with lacrimation, burning of the nose and mouth with rhinorrhea, cough, choking sensation and substernal pain. These symptoms were frequently accompanied by nausea, vomiting, headache, dizziness, and sometimes syncope. Of 33 of the victims who were hospitalized, all suffered tracheobronchitis, 23 progressed to pulmonary edema, and of those, 14 to pneumonitis. Respiratory distress and substernal pain generally subsided within the first 72 hours; cough increased in frequency and severity after 2 to 3 days and became productive of thick mucopurulent sputum; cough disappeared by the end of 14 days. Prolonged or repeated exposure to 5 ppm may cause respiratory complaints, corrosion of the teeth, and inflammation of the mucous membranes of the nose. It has been reported that chronic exposure may increase susceptibility to respiratory infections. In high concentrations, chlorine irritates the skin and causes sensations of burning and pricking, inflammation, and vesicle formation. Liquid chlorine causes eye and skin burns on contact.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 70.9
2. Boiling point (760 mm Hg): −34.1 C (−29.3 F)
3. Specific gravity (water = 1): 1.41 (liquid)
4. Vapor density (air = 1 at boiling point of chlorine): 2.5
5. Melting point: −101 C (−149 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): 0.7
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause cylinders to burst.
2. Incompatibilities: Contact with combustible substances (such as gasoline and petroleum products, turpentine, alcohols, acetylene, hydrogen, ammonia, and sulfur) and finely divided metals may cause fires and explosions.
3. Hazardous decomposition products: None.
4. Special precautions: Chlorine will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible, but is a strong oxidizer.
2. Compressed gas cylinders containing chlorine should be stored in accordance with 29 CFR 1910.101.

- **Warning properties**

1. Odor Threshold: The odor threshold for chlorine has been reported by several authors to be 0.01 ppm (Summer, May, and Stern).
2. Eye Irritation Level: Grant states that "exposure to concentrations of chlorine gas as low as 3 to 6 ppm in air causes sensation of stinging and burning of the eyes of some individuals, with associated blepharospasm, redness, and watering, but on continued exposure sensitivity may decrease and signs and symptoms diminish."

The ILO states that eye irritation may occur at 1 to 3 ppm.

3. Other Information: Patty states that "exposures to low concentrations, 10 to 20 mg/m^3 or 3 to 6 ppm, cause a stinging or burning sensation in the eyes, nose and throat, and sometimes headache due to irritation of the accessory nasal sinuses. There may be redness and watering of the eyes, sneezing, coughing, and huskiness or loss of the voice. Bleeding of the nose may occur, and sputum from the pharynx and trachea may be blood-tinged. There is little or no chest pain other than the muscular soreness associated with excessive coughing."
4. Evaluation of Warning Properties: Through its odor, chlorine can be detected below the permissible exposure limit, and through its irritant effects, chlorine can be detected within several times of the permissible exposure limit. For the purposes of this guideline, therefore, chlorine is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of chlorine. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with a subsequent chemical analysis of the adsorption tube. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure chlorine may be used. An analytical method for chlorine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 1, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00267-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may

be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid chlorine, and to prevent the skin from becoming frozen from contact with vessels containing liquid chlorine.

• Where there is any possibility of exposure of an employee's body to liquid chlorine, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with chlorine should be removed immediately and not reworn until the chlorine is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid chlorine contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid chlorine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with chlorine should be immediately washed or showered to remove any chlorine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorine may occur and control methods which may be effective in each case:

Operation	Controls
Use as chlorinating and oxidizing agent in organic synthesis, manufacture of solvents, automotive antifreeze and antiknock compounds, plastics, resins, elastomers, pesticides, refrigerants, bleaching, and inorganic chemicals	Process enclosure; local exhaust ventilation; personal protective equipment
Use as fluxing, purification, and extraction agent in metallurgy	Process enclosure; local exhaust ventilation
Use as bacteriostat, disinfectant, odor control, and demulsifier in treatment of water and sewage	Process enclosure; local exhaust ventilation
Use as a chlorinating agent in the rubber and coatings industry	Process enclosure; local exhaust ventilation
Use as bleaching agent, cleaning agent, and disinfectant in laundries, dishwashers, cleaning powders, cleaning dairy equipment, and bleaching cellulose	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid chlorine or high concentrations of chlorine gas get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid chlorine or high concentrations of chlorine gas get on the skin, immediately flush the contaminated skin with water. If liquid chlorine or high concentrations of chlorine gas penetrate through the clothing, remove the clothing and immediately flush the skin with water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chlorine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If chlorine is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty through a reducing agent, such as sodium bisulfide and sodium bicarbonate.

• Waste disposal method:

Chlorine may be disposed of by allowing gas to disperse at a safe location.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chlorine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Chasis, H., et al.: "Chlorine Accident in Brooklyn," *Occupational Medicine*, 4:152-176, 1947.

• *Federal Register*, Vol. 43, No. 237, pp. 57601-03, 8 December 1978.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kaufman, J., and Burkons, D.: "Clinical, Roentgenologic, and Physiologic Effects of Acute Chlorine Exposure," *Archives of Environmental Health*, 23:29-34, 1971.

• Kramer, C. G.: "Chlorine," *Journal of Occupational Medicine*, 9:193-196, 1967.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-80, Chlorine*, Washington, D.C., 1970.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chlorine*, HEW Publication No. (NIOSH) 76-170, GPO No. 017-033-00176-6, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

RESPIRATORY PROTECTION FOR CHLORINE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Gas Concentration	
25 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) providing protection against chlorine.**
	A gas mask with a chin-style or a front- or back-mounted canister providing protection against chlorine.**
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 25 ppm*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any full-facepiece gas mask providing protection against chlorine.**
	Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Chlorine is a strong oxidizer and should not come in contact with oxidizable materials.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of chlorine; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 25 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Chlorine Dioxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: ClO_2
- Synonyms: None
- Appearance and odor: Yellow-green to orange gas or liquid with a pungent, sharp odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorine dioxide is 0.1 part of chlorine dioxide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.3 milligram of chlorine dioxide per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorine dioxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Chlorine dioxide may cause irritation of the eyes, nose, throat, and lungs. It may produce coughing, wheezing, and severe breathing difficulties which may be delayed in onset.

2. Long-term Exposure: Repeated exposure to chlorine dioxide may cause chronic bronchitis.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorine dioxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorine dioxide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system and eyes should be stressed.

—14" x 17" chest roentgenogram: Chlorine dioxide causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Chlorine dioxide is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when signs and symptoms of respiratory disease occur.

- **Summary of toxicology**

Chlorine dioxide gas is a severe respiratory and eye irritant. Delayed deaths occurred in animals after exposure to 150 to 200 ppm for less than 1 hour. Rats repeatedly exposed to 10 ppm died after 10 to 13 days of exposure; there was nasal and ocular discharge and dyspnea; autopsy revealed purulent bronchitis. Exposure of a worker to 19 ppm for an unspecified time period was fatal. Repeated acute exposure of workers to undetermined concentrations is stated to have caused eye and throat irritation, nasal discharge, cough, wheezing, bronchitis, and delayed onset of pulmonary edema. Repeated exposure may cause chronic bronchitis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 67.5
  2. Boiling point (760 mm Hg): 11 C (52 F)
  3. Specific gravity (water = 1): 1.6 (Liquid at boiling point)
  4. Vapor density (air = 1 at boiling point of chlorine dioxide): 2.3
  5. Melting point: −59 C (-74 F)
  6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.8 (commercial solutions)
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: Temperatures above 130 C (266 F) cause rapid decomposition of gas. It will detonate if heated rapidly to 100 C (212 F).
  2. Incompatibilities: Contact with dust and other combustible materials such as organic matter and sulfur may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as chlorine gas) may be released when chlorine dioxide decomposes.
  4. Special precautions: Chlorine dioxide will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: Not applicable
  2. Self-accelerating decomposition temperature: 130 C (266 F)
  3. Explosive limits in air: Concentrations over 40 percent in air will sustain a decomposition wave set off by an electric spark. Gas is explosive at concentrations over 10 percent and can be ignited by almost any form of energy such as sunlight, heat, or sparks.
  4. Extinguishant: None known
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold for chlorine dioxide of 0.1 ppm.
  2. Eye Irritation Level: Grant states that "chlorine dioxide is a reddish yellow, poisonous gas which is very irritating to the respiratory tract. Industrially, men exposed to low concentrations of the gas in air have been noted occasionally to suffer from irritation of the eyes and to see haloes about lights, but these effects have been minor compared to respiratory irritation. The corneas of workers seeing haloes have not been examined to determine whether epithelial edema is present and responsible for this symptom." The *Documentation of TLV's* notes that "Elkins stated that a concentration of chlorine dioxide (ClO_2) of 5 ppm was definitely irritating."
  3. Evaluation of Warning Properties: Since the odor threshold of chlorine dioxide is at the permissible exposure limit, this substance could be treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for chlorine dioxide had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid chlorine dioxide.
- Where there is any possibility of exposure of an employee's body to liquid chlorine dioxide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with chlorine dioxide and any clothing which becomes wet with liquid chlorine dioxide should be removed immediately and not reworn until the chlorine dioxide is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any

possibility of liquid chlorine dioxide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid chlorine dioxide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with chlorine dioxide should be immediately washed or showered with soap or mild detergent and water to remove any chlorine dioxide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorine dioxide may occur and control methods which may be effective in each case:

Operation	Controls
Use as bleaching agent for wood pulp and paper and textiles	Process enclosure; local exhaust ventilation; personal protective equipment
Use in water treatment to remove tastes and odors by oxidation; use in bleaching fats and oils, and to improve product, and leather dressing	Process enclosure; local exhaust ventilation; personal protective equipment
Use as bleaching and maturing agent in flour for baking; use as bleaching, cleaning, and unhairing agent in leather manufacture	Process enclosure; local exhaust ventilation; personal protective equipment
Use in chemical synthesis as oxidizing agent; use in control of microorganisms in fruit and vegetable processing as oxidizing agent; and as bacteria and algae control in aquariums and packaged pharmaceuticals	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid chlorine dioxide or strong concentrations of chlorine dioxide vapor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid chlorine dioxide gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid chlorine dioxide penetrates through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation or burns are present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chlorine dioxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If liquid chlorine dioxide has been swallowed and the person is conscious, give him large quantities of water immediately to dilute the chlorine dioxide. Do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chlorine dioxide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. If in the gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
4. If in the liquid form, evacuate persons not wearing protective equipment from spill area. Allow chlorine dioxide to evaporate while providing all available ventilation.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Chlorine Dioxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- American Industrial Hygiene Association: "Chlorine Dioxide," *Hygienic Guide Series*, Detroit, Michigan, 1958.
- Dalhamn, T.: "Chlorine Dioxide-Toxicity in Animal Experiments and Industrial Risks," *A.M.A. Archives of Industrial Health*, 15:101-107, 1957.
- Gloemme, J., and Lundgren, K. D.: "Health Hazards from Chlorine Dioxide," *A.M.A. Archives of Industrial Health*, 16:169-176, 1957.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR CHLORINE DIOXIDE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Gas Concentration	
5 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) containing non-combustible sorbents and providing protection against chlorine dioxide. A gas mask with a chin-style or a front- or back-mounted canister containing non-combustible sorbents and providing protection against chlorine dioxide. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-combustible sorbents and providing protection against chlorine dioxide. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chlorine Trifluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: ClF_3
- Synonyms: None
- Appearance and odor: Greenish-yellow, almost colorless liquid or gas with a sweet, but irritating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorine trifluoride is a ceiling level of 0.1 part of chlorine trifluoride per million parts of air (ppm). This may also be expressed as 0.4 milligram of chlorine trifluoride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorine trifluoride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Effects on humans from exposure to chlorine trifluoride have not been reported. Animal experiments have shown that exposure to this chemical can cause severe irritation of the eyes and respiratory tract. Severe breathing difficulties have occurred. These difficulties may sometimes be delayed in onset. Severe burns of the eyes and skin have been produced in animals from contact with this chemical.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorine trifluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorine trifluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed. The skin and eyes should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Chlorine trifluoride causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Chlorine trifluoride is a severe pulmonary irritant in animals. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when signs and symptoms of respiratory disease occur.

- **Summary of toxicology**

Chlorine trifluoride gas is an extremely severe irritant of the eyes, respiratory tract, and skin. The injury caused by chlorine trifluoride can be extremely severe and, in part, attributed to its hydrolysis products including chlorine, hydrogen fluoride, and chlorine dioxide. Exposure of rats to 800 ppm for 15 minutes was fatal, but nearly all survived when exposed for 13 minutes. There was severe inflammation of all exposed mucosal surfaces, resulting in lacrimation, corneal ulceration, and burning of exposed areas of skin. In another study, exposure of rats to 480 ppm for 40 minutes or to 96 ppm

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

for 3.7 hours was fatal; in the latter group, there were pulmonary edema and marked irritation of the bronchial mucosa. Effects in humans have not been reported, but exposure may cause some effects; inhalation may be expected to cause pulmonary edema, and contact with eyes or skin may cause severe burns.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 92.5
2. Boiling point (760 mm Hg): 11.8 C (53 F)
3. Specific gravity (water = 1): 1.88 (liquid)
4. Vapor density (air = 1 at boiling point of chlorine trifluoride): 3.14
5. Melting point: −76.3 C (-105 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): Violent reaction to form chlorine gas and hydrofluoric acid
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Chlorine trifluoride decomposes above 220 C (428 F) and may explode container.
2. Incompatibilities: Chlorine trifluoride will cause most combustible materials to ignite spontaneously. The exceptions are dry. highly fluorinated polymers such as "Teflon" and "Kel-F," the metals used in storage containers (monel, copper, and stainless steel) or gaskets (teflon), nitrogen gas or air, and the inert gases (neon, etc.). Chlorine trifluoride reacts violently with water, sand, silicon-containing compounds, glass, and asbestos.
3. Hazardous decomposition products: Toxic gases and vapors (such as chlorine and hydrogen fluoride) may be released when chlorine trifluoride decomposes.
4. Special precautions: Chlorine trifluoride will attack all forms of plastics, rubber, and resins, except the higly fluorinated polymers "Teflon" and Kel-F."

- **Flammability**

1. Not combustible by itself, but is very reactive and may cause fire on contact with organic matter.

- **Warning properties**

Odor Threshold: Deichmann and Gerarde note that chlorine trifluoride has a "somewhat sweet odor." No quantitative information is available, however, concerning the odor threshold.

2. Irritation Level: Grant states that "chlorine trifluoride is an extremely reactive, corrosive and irritating gas which experimentally has been observed to cause a severe reaction in the lungs and in all exposed mucous membranes. It is highly irritating to the skin and eyes, and has caused severe corneal ulcers in dogs."
3. Evaluation of Warning Properties: Since no quantitative data are available relating warning properties to air concentrations of chlorine trifluoride, this gas is treated as a material with poor warning properties. In addition, since chlorine trifluoride is a powerful oxidizer, it should not be allowed to contact combustible materials.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of chlorine trifluoride. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

At the time of publication of this guideline, no measurement method for chlorine trifluoride had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid chl rine trifluoride.
- Where there is any possibility of exposure of an emp. ee's body to liquid chlorine trifluoride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes contaminated with chlorine trifluoride should be removed immediately and

not reworn until the chlorine trifluoride is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid chlorine trifluoride contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid chlorine trifluoride, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with chlorine trifluoride should be immediately washed or showered to remove any chlorine trifluoride.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorine trifluoride may occur and control methods which may be effective in each case:

Operation	Controls
use as a fluorinating agent in organic and inorganic chemical synthesis; use in the separation of uranium isomers	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a cutting agent for well castings in oil well drilling	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a rocket fuel oxidizer as an igniter and propellant in liquid propellant engines; use as an incendiary	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid chlorine trifluoride or strong concentrations of chlorine trifluoride vapor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid chlorine trifluoride or strong concentrations of chlorine trifluoride vapor get on the skin, immediately flush the contaminated skin with large quantities of water. If liquid chlorine trifluoride or strong concentrations of chlorine trifluoride vapor penetrate through the clothing, remove the clothing immediately and flush the skin with large amounts of water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of chlorine trifluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If liquid chlorine trifluoride has been swallowed and the person is conscious, give him large quantities of water immediately to dilute the chlorine trifluoride. Do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chlorine trifluoride is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If in the gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
3. If in the liquid form, evacuate persons not wearing protective equipment from spill area. Allow chlorine trifluoride to evaporate while providing all available ventilation.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chlorine Trifluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Boysen, J. E.: "Health Hazards of Selected Rocket Propellants," *Archives of Environmental Health*, 7:71-75, 1963.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York,

1969.
• Dibbell, D. G., et al.: "Hydrofluoric Acid Burns of the Hand," *Journal of Bone and Joint Surgery*, 52A:931-936, 1970.
• Dost, F. N., et al.: "Toxic Properties of Chlorine Trifluoride," *Toxicology and Applied Pharmacology*, 27:527-536, 1974.
• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Horn, H. J., and Weir, R. J.: "Inhalation Toxicology of Chlorine Trifluoride. I. Acute and Subacute Toxicity," *A.M.A. Archives of Industrial Health*, 12:515-521, 1955.
• Horn, H. J., and Weir, R. J.: "Inhalation Toxicology of Chlorine Trifluoride. II. Chronic Toxicity," *A.Archives of Industrial Health*, 13:340-345, 1956.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.
• National Fire Protection Association: "Combustible Solids, Dusts, and Explosives," Vol. 3 of *National Fire Codes*, NFPA 49, Boston, 1973.
• National Fire Protection Association: "Manual of Hazardous Chemical Reactions," in *National Fire Codes*, NFPA 491M, Boston, 1971.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR CHLORINE TRIFLUORIDE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Gas Concentration	
5 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
20 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 20 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A gas mask containing non-combustible sorbents and providing protection against chlorine trifluoride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of chlorine trifluoride; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 20 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Chloroacetaldehyde

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $ClCH_2CHO$
- Synonyms: 2-Chloroethanal; chloroacetaldehyde (40% aqueous)
- Appearance and odor: Colorless liquid with a very sharp, irritating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chloroacetaldehyde is a ceiling level of 1 part of chloroacetaldehyde per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 3 milligrams of chloroacetaldehyde per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chloroacetaldehyde can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

Chloroacetaldehyde causes skin burns, irritation of the throat, nose, and lungs, and serious irritation of the eyes.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chloroacetaldehyde.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chloroacetaldehyde at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from chloroacetaldehyde exposure.

—Eye disease: Chloroacetaldehyde is a potent eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

—Skin disease: Chloroacetaldehyde is a skin irritant and possibly a skin sensitizer. Those with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of chloroacetaldehyde might cause exacerbation of symptoms due to its irritant and potentially sensitizing properties.

—Kidney disease: Although chloroacetaldehyde is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although chloroacetaldehyde is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Overexposure to chloroacetaldehyde produces corrosive destruction and degradation of lipids and membrane structures, causing intense irritation and edema of the eyes, mucous membranes, respiratory tract, and skin. Prolonged exposure to the liquid causes tissue destruction, chemical burns, and residual scarring. Some permanent damage to the eye may occur. Chloroacetaldehyde and its metabolite, chloroacetic acid, are

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

excreted by the kidneys. The possibility of skin and respiratory sensitization should be considered.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 78.5
  2. Boiling point (760 mm Hg): 85 C (185 F)
  3. Specific gravity (water = 1): 1.19 for 40% aqueous solution
  4. Vapor density (air = 1 at boiling point of chloroacetaldehyde): 2.7 for 40% aqueous solution
  5. Melting point: −16.3 C (3 F) for 40% aqueous solution
  6. Vapor pressure at 45 C (113 F): 100 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with oxidizing materials and acids may cause fires or explosions. The compound reacts with water to form a hydrate with the evolution of some heat.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving chloroacetaldehyde.
  4. Special precautions: Chloroacetaldehyde forms a water-insoluble polymer in storage, especially in the presence of small amounts of acid.
- **Flammability**
  1. Flash point: 88 C (190 F)(closed cup) for 40% aqueous solution
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Carbon dioxide, dry chemical, or alcohol foam
- **Warning properties**
  1. Odor Threshold: By analogy to crotonaldehyde and acetaldehyde, both of which the *Handbook of Organic Industrial Solvents* states have odor thresholds less than 1 ppm, the odor threshold of chloroacetaldehyde is assumed to be less than 1 ppm.
  2. Irritation Levels: The *Documentation of TLV's* states that "chloroacetaldehyde presents a serious hazard from inhalation of its vapor, which is irritating to the eyes, nose, and throat . . . . This aldehyde is somewhat more irritating than formaldehyde."

According to Grant, formaldehyde causes "definite irritation of the eyes and lacrimation . . . at a concentration of 20 ppm in air. Even at concentrations from 0.5 to 0.005 ppm a sensation of eye irritation is detectable, and it (formaldehyde) can be sensed as low as 0.01 ppm by some people."

The *Documentation of TLV's*, in addition, states that a "threshold limit of 1 ppm (chloroacetaldehyde) is recommended to prevent irritative effects. Analogy with other aldehydes and practical experience suggest that the TLV will not prevent all complaints of irritation, and it should be used only with caution in continuous, repeated exposure situations."

3. Evaluation of Warning Properties: By analogy to other aldehydes, it is assumed that chloroacetaldehyde can be detected at the permissible exposure through its odor and irritant effects. For the purposes of this guideline, therefore, chloroacetaldehyde is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of chloroacetaldehyde. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

An analytical method for chloroacetaldehyde is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing

necessary to prevent any possibility of skin contact with chloroacetaldehyde at or above a concentration of 0.1%.

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solutions containing chloroacetaldehyde below a concentration of 0.1%.
- Clothing contaminated with chloroacetaldehyde should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chloroacetaldehyde from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chloroacetaldehyde, the person performing the operation should be informed of chloroacetaldehyde's hazardous properties
- Where there is any possibility of exposure of an employee's body to solutions containing in excess of 0.1% chloroacetaldehyde, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with chloroacetaldehyde should be removed immediately and not reworn until the chloroacetaldehyde is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid chloroacetaldehyde contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid chloroacetaldehyde, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with chloroacetaldehyde should be immediately washed or showered to remove any chloroacetaldehyde.
- Employees who handle liquid chloroacetaldehyde should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chloroacetaldehyde may occur and control methods which may be effective in each case:

Operation	Controls
Use during manufacture of 2-aminothiazole	Process enclosure; general dilution ventilation; personal protective equipment (with barrier creams)
Liberation during use in diethylacetal in acid media during chemical synthesis, such as p-aminothiazole	Process enclosure; general dilution ventilation; personal protective equipment
Use during control of algae, bacteria, and fungi in water	General dilution ventilation; personal protective equipment (with barrier creams)
Use as a spinning solution of poly B-alanine	General dilution ventilation; personal protective equipment (with barrier creams)
Liberation from intermediate steps in organic synthesis	Local exhaust ventilation
Use during debarking operations	Local exhaust ventilation; personal protective equipment
Use of diethylacetal in an acid media during chemical synthesis such as p-aminothiazole	Process enclosure; general dilution ventilation; personal protective equipment (with barrier creams)

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If chloroacetaldehyde gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible.

- **Skin Exposure**

If chloroacetaldehyde gets on the skin, immediately flush the contaminated skin with water. If chloroacetaldehyde soaks through the clothing, remove the clothing immediately and flush the skin with water. When there are chemical burns or evidence of skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of chloroacetaldehyde, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When chloroacetaldehyde has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chloroacetaldehyde is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Chloroacetaldehyde may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chloroacetaldehyde," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR CHLOROACETALDEHYDE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
50 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
250 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 250 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for alpha-Chloroacetophenone

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5COCH_2Cl$
- Synonyms: Phenyacyl chloride; omega=chloroacetophenone; chloroacetophenone; chloromethyl phenyl ketone; phenyl chloromethyl ketone; "tear gas"; CN
- Appearance and odor: Colorless to gray solid with a sharp, irritating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for alpha-chloroacetophenone is 0.05 part of alpha-chloroacetophenone per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.3 milligram of alpha-chloroacetophenone per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

alpha-Chloroacetophenone can cause irritation of the eyes and skin upon contact and irritation of the lungs if it is inhaled. It can also cause difficulty if it is swallowed.

- **Effects of overexposure**

alpha-Chloroacetophenone vapors may cause a tingling or runny nose, burning and/or pain of the eyes, blurred vision, and tears. Burning in the chest, difficult breathing, and nausea may occur. Skin irritation, rash, or burns may occur.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to alpha-chloroacetophenone.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to alpha-chloroacetophenone at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from alpha-chloroacetophenone exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of alpha-chloroacetophenone might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Skin disease: alpha-Chloroacetophenone is irritating to the skin, especially if moist. Persons with pre-existing skin diseases may be more susceptible to the effects of alpha-chloroacetophenone.

—Eye disease: alpha-Chloroacetophenone is a potent lacrimator and eye irritant and may cause corneal damage. Persons with pre-existing eye diseases may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

alpha-Chloroacetophenone is a highly irritating substance. Exposure to low concentrations produces lacrimation and irritation of the eyes and upper respiratory tract. Exposure to high concentrations produces marked conjunctivitis and may cause corneal damage. Pulmonary edema may occur, often delayed for some 12 hours after exposure. No chronic effects are reported.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

271

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 155
  2. Boiling point (760 mm Hg): 247 C (477 F)
  3. Specific gravity (water = 1): 1.32
  4. Vapor density (air = 1 at boiling point of alpha-chloroacetophenone): 5.2
  5. Melting point: 59 C (138 F)
  6. Vapor pressure at 20 C (68 F): 0.012 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Very much less than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Water or steam
  3. Hazardous decomposition products: Toxic and corrosive vapors are produced when combined with steam or water.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 118 C (244 F)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Not applicable
  4. Extinguishant: Carbon dioxide or dry chemical
- **Warning properties**
  1. Odor Threshold: According to the *Documentation of TLV's*, the odor threshold is 0.1 mg/m³.
  2. Irritation Levels: According to the *Documentation of TLV's*, "irritation thresholds range from 0.15 to 0.4 mg/m³, lacrimation thresholds from 0.3 to 0.4 mg/m³ . . ."
  3. Evaluation of Warning Properties: Through its odor and irritant effects, alpha-chloroacetophenone can be detected below the permissible exposure limit; therefore, it is considered to have adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for alpha-chloroacetophenone is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solid alpha-chloroacetophenone or liquids containing alpha-chloroacetophenone.
- If employees' clothing may have become contaminated with solid alpha-chloroacetophenone, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with alpha-chloroacetophenone should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of alpha-chloroacetophenone from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the alpha-chloroacetophenone, the person performing the operation should be informed of alpha-chloroacetophenone's hazardous properties.
- Non-impervious clothing which becomes contaminated with alpha-chloroacetophenone should be removed immediately and not reworn until the alpha-chloroacetophenone is removed from the clothing.
- Where there is any possibility that employees' eyes may be exposed to alpha-chloroacetophenone, an eyewash fountain should be provided within the immediate work area for emergency use.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid alpha-chloroacetophenone or liquids containing alpha-chloroacetophenone contacting the eyes.

SANITATION

• Skin that becomes contaminated with alpha-chloroacetophenone should be immediately washed or showered with soap or mild detergent and water to remove any alpha-chloroacetophenone.

• Eating and smoking should not be permitted in areas where solid alpha-chloroacetophenone is handled, processed, or stored.

• Employees who handle solid alpha-chloroacetophenone or liquids containing alpha-chloroacetophenone should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to alpha-chloroacetophenone may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during loading of solutions for aerosols for law enforcement and civilian protective devices	General dilution ventilation; respiratory protective equipment
Liberation during manufacture	Process enclosure; general dilution ventilation
Liberation during denaturing of industrial alcohol	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If alpha-chloroacetophenone gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If alpha-chloroacetophenone gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If alpha-chloroacetophenone soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. When there are chemical burns or evidence of skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of alpha-chloroacetophenone, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When alpha-chloroacetophenone has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If alpha-chloroacetophenone is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

alpha-Chloroacetophenone may be disposed of:

1. By making packages of alpha-chloroacetophenone in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving alpha-chloroacetophenone in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "alpha-Chloroacetophenone," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Macrae, W. G., Willensky, M. D., and Basu, P. K.: "Corneal Injury Caused by Aerosol Irritant Projectors," *Canadian Journal of Ophthalmology*, 5:1, pp. 3-11, 1970.

• Penneys, N. S., et al.: "Contact Dermatitis Due to 1-Chloroacetophenone and Chemical Mace," *New England Journal of Medicine*, 281:8, pp. 413-415, August 1969.

• Punte, C. L., et al.: "Inhalation Studies with Chloroacetophenone, Diphenylaminochlorarsine and Pelargonic Morpholide — II. Human Exposures," *American Industrial Hygiene Association Journal*, 23:199-202, 1962.

• Rothberg, S.: "Skin Sensitization Potential of the Riot Control Agents," *Military Medicine*, 135:552-556, July 1970.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR ALPHA-CHLOROACETOPHENONE

Condition	Minimum Respiratory Protection* Required Above 0.05 ppm
Particulate and Vapor Concentration	
15 mg/m³ (2.5 ppm) or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s) and high efficiency particulate filter(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister with a high efficiency particulate filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ (16 ppm) or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 100 mg/m³ (16 ppm) or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a full facepiece providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chlorobenzene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_6H_5Cl
- Synonyms: Monochlorobenzene; chlorobenzol; phenyl chloride; MCB
- Appearance and odor: Colorless liquid with a mild aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorobenzene is 75 parts of chlorobenzene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 350 milligrams of chlorobenzene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorobenzene can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Chlorobenzene may cause drowsiness, incoordination, and unconsciousness. It may also cause irritation of the eyes, nose, and skin. Exposure to high levels might also cause liver damage.

2. Long-term Exposure: Prolonged or repeated skin contact with chlorobenzene liquid may cause skin burns. Prolonged or repeated exposure to this chemical might also result in liver, kidney, or lung damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorobenzene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorobenzene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from chlorobenzene exposure.

—Skin disease: Chlorobenzene can cause dermatitis on exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Chlorobenzene is known as a liver toxin in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although chlorobenzene is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway disesses, the breathing of chlorobenzene might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Chlorobenzene vapor is a narcotic. Cats exposed to 8,000 ppm showed severe narcosis after ½ hour and died 2 hours after removal from exposure, but 660 ppm for 1 hour was tolerated. Exposed animals showed eye and nose irritation, drowsiness, incoordination, and coma followed by death from the most severe exposures. Several species of animals exposed to 1,000 ppm for 7 hours/day, 5 days/week over a period of 44 days showed histopathologic changes in the lungs, liver, and

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

kidneys, but at 475 ppm there was only slight liver histopathology in guinea pigs. Toxicologic studies and experience indicate that chlorobenzene does not cause the type of blood changes seen with benzene exposure. In man, eye and nasal irritation begin to occur at 200 ppm, and at that level the odor is pronounced and unpleasant; industrial experience indicates that occasional short exposures are not likely to result in more than minor skin irritation, but prolonged or frequently repeated contact may result in skin burns. In one case of accidental poisoning from ingestion of the liquid by a child there was pallor, cyanosis, and coma, followed by complete recovery. Occupational intoxication has not been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 112.5
  2. Boiling point (760 mm Hg): 132 C (270 F)
  3. Specific gravity (water = 1): 1.1
  4. Vapor density (air = 1 at boiling point of chlorobenzene): 3.9
  5. Melting point: −44 C (-47 F)
  6. Vapor pressure at 20 C (68 F): 8.8 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.05
  8. Evaporation rate (butyl acetate = 1): 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving chlorobenzene.
  4. Special precautions: Liquid chlorobenzene will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 28.9 C (84 F) (closed cup)
  2. Autoignition temperature: 638 C (1180 F)
  3. Flammable limits in air, % by volume: Lower: 1.3; Upper: 7.1
  4. Extinguishant: Carbon dioxide; dry chemical, foam
- **Warning properties**

According to both Deichmann and Gerarde and the AIHA *Hygienic Guide*, the odor of chlorobenzene is "barely perceptible" at 60 ppm, a concentration below that of the permissible exposure. Chlorobenzene is considered to have good warning properties. It is an eye irritant, as stated by Patty, but the exact concentrations at which this irritation occurs are not mentioned.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- Method

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure chlorobenzene may be used. An analytical method for chlorobenzene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid chlorobenzene.
- Clothing wet with liquid chlorobenzene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chlorobenzene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chlorobenzene, the person performing the operation should be informed of chlorobenzene's hazardous properties.
- Any clothing which becomes wet with liquid chlorobenzene should be removed immediately and not

reworn until the chlorobenzene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid chlorobenzene may contact the eyes.

SANITATION

• Skin that becomes wet with liquid chlorobenzene should be promptly washed or showered with soap or mild detergent and water to remove any chlorobenzene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorobenzene may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of phenol in synthesis of polymeric materials	Local exhaust ventilation
Use as an intermediate in manufacture of ortho- and para-nitrobenzenes for use in dye manufacture; manufacture of DDT, aniline, picric acid, beta-chloroanthraquinone, and other chemicals; manufacture of rubber adhesives and adhesives	Process enclosure
Use as fiber swelling agent and dye carrier in textile processing	Local exhaust ventilation
Use as tar and grease remover in cleaning and degreasing operations	Local exhaust ventilation
Use as solvent in surface coatings and surface coating removers	Process enclosure; local exhaust ventilation; personal protective equipment
Use as extractant in manufacture of diisocyanates, rubber, perfumes, and pharmaceuticals	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If chlorobenzene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If chlorobenzene gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If chlorobenzene soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chlorobenzene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If chlorobenzene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chlorobenzene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Chlorobenzene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of chlorobenzene vapors are permitted.

• Waste disposal method:

Chlorobenzene may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chlorobenzene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chlorobenzene," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR CHLOROBENZENE

Condition	Minimum Respiratory Protection* Required Above 75 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2400 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2400 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for o-Chlorobenzylidene Malononitrile

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_5ClN_2$
- Synonyms: OCBM; CS
- Appearance and odor: White solid with a pepper odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for o-chlorobenzylidene malononitrile is 0.05 part of o-chlorobenzylidene malononitrile per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.4 milligram of o-chlorobenzylidene malononitrile per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for o-chlorobenzylidene malononitrile from 0.05 ppm as a time-weighted average value to 0.05 ppm as a ceiling

HEALTH HAZARD INFORMATION

- **Routes of exposure**

o-Chlorobenzylidene malononitrile can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: o-Chlorobenzylidene malononitrile causes headache, eye irritation (with eye watering and burning), burning of the throat, sneezing, coughing, and a constricting sensation in the chest. There may be delayed breathing difficulties. Burning of the skin also occurs and is greatly increased by the presence of moisture. Heavy exposures may cause skin blistering.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to o-chlorobenzylidene malononitrile.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to o-chlorobenzylidene malononitrile at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from o-chlorobenzylidene malononitrile exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of o-chlorobenzylidene malononitrile might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: o-Chlorobenzylidene malononitrile is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: o-Chlorobenzylidene malononitrile is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

o-Chlorobenzylidene malononitrile aerosol is a potent lacrimator and respiratory irritant. In human experiments, concentrations ranging from 4.3 to 6.7 mg/m^3 were barely tolerated when reached gradually over a period of 30 minutes; a burning sensation and deep pain in the eyes persisted for 2 to 5 minutes following

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

202

cessation of exposure, severe conjunctival injection for 25 to 30 minutes, and erythema of the eyelids with some blepharospasm for 1 hour; there was a burning sensation in the throat with cough, followed by a constricting sensation in the chest; no therapy other than removal from exposure was necessary. At a concentration of 1.5 mg/m³, 3 of 4 men developed headache during a 90-minute exposure; one subject developed slight eye and nose irritation. On the skin, the powder caused a burning sensation which was greatly aggravated by moisture; erythema and vesiculation resembling second-degree burns were produced.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 188.5
  2. Boiling point (760 mm Hg): 310– 315 C (590–599 F)
  3. Specific gravity (water = 1): Greater than 1
  4. Vapor density (air = 1 at boiling point of o-chlorobenzylidene malononitrile): 6.5
  5. Melting point: 93 – 95 C (199 – 203 F)
  6. Vapor pressure at 20 C (68 F): Much less than 1
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, oxides of nitrogen, and carbon monoxide) may be released in a fire involving o-chlorobenzylidene malononitrile.
  4. Special precautions: None
- **Flammability**
  1. Flash point: Data not available
  2. Autoignition temperature: Data not available
  3. Minimum explosive concentration: 0.025 g/l
  4. Extinguishant: Carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: No information is available concerning the odor threshold of OCBM.
  2. Eye Irritation Level: According to the *Documentation of TLV's*, in an experiment with human volunteers, "one subject developed slight eye and nose irritation" during a 90-minute exposure to 1.5 mg/m³. Since the compound has such highly irritant properties, "concentrations ranging between 4.3 to 6.7 mg/m³ could not be tolerated unless the concentration was reached gradually over a period of 30 minutes."
  3. Other Information: Deichmann and Gerarde state that inhalation of o-chlorobenzylidene malononitrile causes "'burning' in the throat and progressing down the respiratory tract," but no quantitative information is given concerning the threshold of these irritant effects. Grant reports that humans exposed to concentrations greater than 10 mg/m³ experienced extreme burning and pain in the chest, as well as in the eyes.
  4. Evaluation of Warning Properties: Since information concerning the odor threshold of OCBM is not available, and since only slight eye irritation has been observed in only one human subject at a concentration several times greater than the permissible exposure, OCBM could be treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for o-chlorobenzylidene malononitrile is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile.

• If employees' clothing has had any possibility of being contaminated with o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of o-chlorobenzylidene malononitrile from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the o-chlorobenzylidene malononitrile, the person performing the operation should be informed of o-chlorobenzylidene malononitrile's hazardous properties.

• Non-impervious clothing which becomes contaminated with o-chlorobenzylidene malononitrile should be removed promptly and not reworn until the o-chlorobenzylidene malononitrile is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile may contact the eyes.

SANITATION

• Workers subject to skin contact with o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile should wash with soap or mild detergent and water any areas of the body which may have contacted o-chlorobenzylidene malononitrile at the end of each work day.

• Skin that becomes contaminated with o-chlorobenzylidene malononitrile should be promptly washed or showered with soap or mild detergent and water to remove any o-chlorobenzylidene malononitrile.

• Eating and smoking should not be permitted in areas where o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile are handled, processed, or stored.

• Employees who handle o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to o-chlorobenzylidene malononitrile may occur and control methods which may be effective in each case:

Operation	Controls
Use as a harassing agent in civil disturbances and wars	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If o-chlorobenzylidene malononitrile or liquids containing o-chlorobenzylidene malononitrile penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of o-chlorobenzylidene malononitrile, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When o-chlorobenzylidene malononitrile has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If o-chlorobenzylidene malononitrile is spilled, the following steps should be taken:

1. Ventilate area of spill.

2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

3. Decontaminate area of spill: (a) by washing with a 5% solution of sodium hydroxide in 50/50 ethyl alcohol/water; or (b) by adding flake sodium hydroxide to a solution or slurry of the spill in isopropyl alcohol; or (c) by covering the spill with a 10% solution of sodium hydroxide in 50/50 isopropyl alcohol/water and letting stand 20 minutes before flushing with water.

• Waste disposal and neutralization methods:

o-Chlorobenzylidene malononitrile may be disposed of:

1. By making packages of o-chlorobenzylidene malononitrile in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving o-chlorobenzylidene malononitrile in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

3. By mixing solid with 5 parts of a 10% solution of monoethanolamine in water containing 0.3% of nonionic detergent.

4. By stirring one pound of solid for 2 hours in one gallon of a 5— 15% solution of sodium hydroxide in ethylene glycol, ethyl alcohol, or methyl alcohol.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "o-Chlorobenzylidene Malononitrile," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Galli, A. F.: "Petroleum, Petroleum Derivatives, and Related Products," *Chemical Abstracts*, 69:68711-107714, 1968.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Punte, C. L., et al.: "Exposures to Ortho-Chlorobenzylidene Malononitrile," *Archives of Environmental Health*, 6:366-374, 1963.

• Punte, C. L., et al.: "Toxicologic Studies on o-Chlorobenzylidene Malononitrile," *Toxicology and Applied Pharmacology*, 4:656-62, 1962.

• U.S. Army, Edgewood Arsenal: "Safety Guide for Processing, Filling, Handling and Decontamination of CS and CS1," CML C SD 385-12, February 1961.

RESPIRATORY PROTECTION FOR o-CHLOROBENZYLIDENE MALONONITRILE

Condition	Minimum Respiratory Protection* Required Above 0.05 ppm
Particulate or Vapor Concentration	
2 mg/m³ (0.24 ppm) or less	A chemical cartridge respirator with a full facepiece and a combination organic vapor cartridge(s) with high efficiency particulate filters. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and high efficiency particulate filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2 mg/m³ (0.24 ppm) or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a full facepiece providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chlorobromomethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_2BrCl
- Synonyms: Bromochloromethane; methylene chlorobromide; CB; CBM; Halon 1011
- Appearance and odor: Colorless to pale yellow liquid with a characteristic, sweet odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorobromomethane is 200 parts of chlorobromomethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1050 milligrams of chlorobromomethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorobromomethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Chlorobromomethane may cause irritation of the eyes and throat. It may also cause mental confusion, dizziness, and unconsciousness.

2. Long-term Exposure: Prolonged or repeated skin exposure may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorobromomethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorobromomethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from chlorobromomethane exposure.

—Skin disease: Chlorobromomethane can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although chlorobromomethane is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although chlorobromomethane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of chlorobromomethane might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Chlorobromomethane vapor is a narcotic and a respiratory irritant. Concentrations near 30,000 ppm were fatal to mice and rats within 15 minutes; this level of exposure produced pulmonary edema and, in delayed deaths, interstitial pneumonitis. The LC50 for mice on 8-hour exposure was 3000 ppm; the predominant observation was narcosis. No toxic effects were observed in several species after repeated inhalation exposures at 1000 ppm for 14 weeks. The substance is a mild skin

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

irritant in animals. A reported exposure of three firefighters to unknown but very high vapor concentrations was characterized by disorientation, headache, nausea, and irritation of the eyes and throat; two of the three became comatose; of these, one had convulsive seizures and the other had respiratory arrest, from which he was resuscitated. Recovery was slow but complete. Some effects may have been due to the inhalation of thermal decomposition products.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 129.4
  2. Boiling point (760 mm Hg): 67.8 C (154 F)
  3. Specific gravity (water = 1): 1.93
  4. Vapor density (air = 1 at boiling point of chlorobromomethane): 4.5
  5. Melting point: −88 C (−126 F)
  6. Vapor pressure at 20 C (68 F): 117 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.9
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Chlorobromomethane reacts with chemically active metals such as calcium, powdered aluminum, zinc, and magnesium.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, carbon monoxide, and hydrogen bromide) may be released when chlorobromomethane decomposes.
  4. Special precautions: Liquid chlorobromomethane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**

Patty states that "chlorobromomethane has a distinctive odor at 400 ppm. It is a good warning at well before acutely hazardous concentration. The odor is distinctive at the acceptable concentration and so gives some warning, but it is not disagreeable enough to drive anyone from the area, and workmen may well tolerate a level well above the acceptable level for chronic exposure."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of chlorobromomethane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure chlorobromomethane may be used. An analytical method for chlorobromomethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid chlorobromomethane.
- Non-impervious clothing which becomes wet with liquid chlorobromomethane should be removed promptly and not reworn until the chlorobromomethane is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid chlorobromomethane may contact the eyes.

SANITATION

- Skin that becomes wet with liquid chlorobromomethane should be promptly washed or showered with soap or mild detergent and water to remove any chlorobromomethane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorobromomethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a fire extinguishing fluid in vaporizing fire extinguishers; use in manufacture of vaporizing liquid fire extinguishers	Material substitution
Use in mineral and salt separations for flotation	General dilution ventilation; personal protective equipment
Use as a grain fumigant	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If chlorobromomethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If chlorobromomethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If chlorobromomethane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chlorobromomethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When chlorobromomethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chlorobromomethane is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Chlorobromomethane may be disposed of by absorbing it in vermiculite, dry sand, earth, or a similar material, and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chlorobromomethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chlorobromomethane," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Rustein, H. R.: "Acute Chlorobromomethane Toxicity," *Archives of Environmental Health*, 7:440-444, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, H. F., Jr.: "Improved Communication—Hygienic Standards for Daily Inhalation," *American Industrial Hygiene Association Quarterly*, 17:151, 1956.

• Torkelson, T. R., et al.: "The Toxicity of Bromochloromethane (Methylene Chlorobromide) as Determined on Laboratory Animals," *American Industrial Hygiene Journal*, p. 275, August 1960.
• Van Stee, E. W.: *A Review of the Toxicology of Halogenated Fire Extinguishing Agents*, AMRL-TR-74-143, Aerospace Medical Research Laboratory, Wright-Patterson AFB, Ohio, 1974.
• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR CHLOROBROMOMETHANE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).
2000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chlorodiphenyl (42% Chlorine)*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{12}H_7Cl_5$ (approximately)
- Synonyms: Polychlorinated biphenyl; PCB
- Appearance and odor: Colorless to dark liquid with a mild hydrocarbon odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorodiphenyl (42% chlorine) is 1 milligram of chlorodiphenyl (42% chlorine) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit for polychlorinated biphenyls be reduced to 1.0 microgram per cubic meter of air averaged over a work shift of up to 10 hours per day, 40 hours per week, and that chlorodiphenyl (42% chlorine) be regulated as an occupational carcinogen. The NIOSH Criteria Document for Polychlorinated Biphenyls should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorodiphenyl (42% chlorine) can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin. Every effort should be made to prevent skin, eye, oral, or inhalation contact with this material.

- **Effects of overexposure**

Chlorodiphenyl (42% chlorine) may cause irritation of the eyes, nose, and throat, and an acne-like skin rash. It may also injure the liver, resulting in such effects as fatigue, dark urine, and yellow jaundice. Repeated skin contact with the liquid may cause skin irritation. The production of liver tumors and adverse reproductive effects has been demonstrated in experimental animals following ingestion of polychlorinated biphenyls. The relevance to humans of some of these studies has not yet been established.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorodiphenyl (42% chlorine).

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorodiphenyl (42% chlorine) at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver and skin should be stressed. The skin should be examined for evidence of chronic disorders. Women in the work force should be advised of the potential adverse effects of chlorodiphenyl (42% chlorine) on the unborn child. Those who have borne children and work with chlorodiphenyl (42% chlorine) should be counseled concerning the advisability of nursing their offspring.

—Liver function tests: Chlorodiphenyl (42% chlorine) may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Skin disease: Chlorodiphenyl (42% chlorine) is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

• **Summary of toxicology**

Chlorodiphenyl (42% chlorine) vapor is toxic to the liver and causes an acne-form dermatitis (chloracne). Guinea pigs died at intervals up to 21 days after the first of 11 daily applications of 34.5 mg to the skin and, at necropsy, the liver showed fatty degeneration and central atrophy; rats, however, survived 25 daily applications, and only slight changes in the liver were observed. The vapor and liquid are moderately irritating to eye tissues. Cases of mild to moderate skin irritation with an acne-form eruption have been reported in workers exposed to 0.1 mg/m³; levels of 10 mg/m³ were unbearably irritating. Several deaths due to atrophy of the liver have occurred among workers exposed to the fumes of chlorodiphenyls and chloronaphthalenes. The production of liver tumors and adverse reproductive effects has been demonstrated in experimental animals following ingestion of polychlorinated biphenyls. The relevance to humans of some of these studies has not yet been established.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 257.5 (approximately)
2. Boiling point (760 mm Hg): 325— 366 C (617—691 F)
3. Specific gravity (water = 1): 1.38
4. Vapor density (air = 1 at boiling point of chlorodiphenyl (42% chlorine)): 8.9
5. Melting point: —19 C (-2 F) (pour point)
6. Vapor pressure at 20 C (68 F): 0.001 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Much less than 1

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving chlorodiphenyl (42% chlorine).
4. Special precautions: Chlorodiphenyl (42% chlorine) will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 176 C (349 F)
2. Autoignition temperature: None to boiling point
3. Flammable limits in air, % by volume: Not available
4. Extinguishant: Foam, dry chemical, carbon dioxide

• **Warning properties**

According to the AIHA *Hygienic Guide*, chlorodiphenyl (42% chlorine) has a typical aromatic odor and causes eye irritation. For the purposes of this guideline, however, it is treated as a material with poor warning properties, as no quantitative data are available concerning its odor and irritation thresholds. As stated in the AIHA *Hygienic Guide*, the vapors of the chlorodiphenyls are "moderately irritating to eye tissues." The concentrations causing eye irritation are not mentioned.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of chlorodiphenyl (42% chlorine) on a glass fiber filter connected in a series with a midget bubbler containing iso-octane, followed by gas chromatographic analysis. A detailed analytical method for chlorodiphenyl (42% chlorine) may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22161, under the title "NIOSH Analytical Methods for Set 2" (order number PB 271

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid chlorodiphenyl (42% chlorine).

• Clothing contaminated with liquid chlorodiphenyl (42% chlorine) should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chlorodiphenyl (42% chlorine) from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chlorodiphenyl (42% chlorine), the person performing the operation should be informed of chlorodiphenyl's (42% chlorine) hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid chlorodiphenyl (42% chlorine) should be removed promptly and not reworn until the chlorodiphenyl (42% chlorine) is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid chlorodiphenyl (42% chlorine) may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid chlorodiphenyl (42% chlorine) should be promptly washed or showered with soap or mild detergent and water to remove any chlorodiphenyl (42% chlorine).

• Eating and smoking should not be permitted in areas where liquid chlorodiphenyl (42% chlorine) is handled, processed, or stored.

• Employees who handle liquid chlorodiphenyl (42% chlorine) should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

• Areas in which exposure to chlorodiphenyl (42% chlorine) may occur should be identified by signs or other appropriate means, and access to these areas should be limited to authorized persons.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorodiphenyl (42% chlorine) may occur and control methods which may be effective in each case:

Operation	Controls
Use as high-temperature transfer medium in chemical/food processing vessels and drying ovens	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a dielectric in manufacture of transformers, capacitors, resistors, and other electrical apparatus	General dilution ventilation; local exhaust ventilation; personal protective equipment
Application and formulation as plasticizer, flame-retardant, and adhesive and weatherizer in spray surface coatings; manufacture and application of impregnants for cloth, paper, fiberboard, wood, and asbestos; manufacture and application of natural and synthetic waxes and polishes; manufacture and application of hot-melt and other adhesives	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as non-flammable working fluid in vacuum pumps, hydraulic systems, and expansion systems	General dilution ventilation; local exhaust ventilation
Use during application of high-pressure, temperature, and moisture lubricants	Personal protective equipment
Use in compounding and processing of plastics for flame retardancy	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture and application for use as pesticides and fungicides	Personal protective equipment
Use as an intermediate or raw material in further organic synthesis	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as sealer for gaskets of natural rubber and synthetics	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as adhesive release on tapes and ink release on carbonless duplicating paper; as a pigment carrier in dyeing polyesters and paper	Personal protective equipment

Use as a pressure adhesive for sign backings, insect traps, and tapes	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in compounding mastics, and sealing and caulking materials; use in compounding of printing inks	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If chlorodiphenyl (42% chlorine) gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If chlorodiphenyl (42% chlorine) gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If chlorodiphenyl (42% chlorine) soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chlorodiphenyl (42% chlorine), move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When chlorodiphenyl (42% chlorine) has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chlorodiphenyl (42% chlorine) is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Chlorodiphenyl (42% chlorine) may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chlorodiphenyl (42% Chlorine)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chlorodiphenyls," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Polychlorinated Biphenyls*, HEW Publication No. (NIOSH) 77-225, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 7, 1974, and Volume 18, 1978.

RESPIRATORY PROTECTION FOR CHLORODIPHENYL (42% CHLORINE)

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Vapor Concentration	
10 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against pesticides. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of chlorodiphenyl (42% chlorine); however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 10 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Chlorodiphenyl (54% Chlorine)*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{12}H_5Cl_5$ (approximately)
- Synonyms: Polychlorinated biphenyl; PCB
- Appearance and odor: Pale yellow viscous liquid with a mild hydrocarbon odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chlorodiphenyl (54% chlorine) is 0.5 milligram of chlorodiphenyl (54% chlorine) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit for polychlorinated biphenyls be reduced to 1.0 microgram per cubic meter of air averaged over a work shift of up to 10 hours per day, 40 hours per week, and that chlorodiphenyl (54% chlorine) be regulated as an occupational carcinogen. The NIOSH Criteria Document for Polychlorinated Biphenyls should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chlorodiphenyl (54% chlorine) can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin. Every effort should be made to prevent skin, eye, oral, or inhalation contact with this material.

- **Effects of overexposure**

Chlorodiphenyl (54% chlorine) may cause irritation of the eyes, nose, and throat, and an acne-like skin rash. It may also injure the liver, resulting in such effects as fatigue, dark urine, and yellow jaundice. Repeated skin contact with the liquid may cause skin irritation.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chlorodiphenyl (54% chlorine). The production of liver tumors and adverse reproductive effects have been demonstrated in experimental animals following ingestion of polychlorinated biphenyls. The relevance to humans of some of these studies has not yet been established.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chlorodiphenyl (54% chlorine) at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver and skin should be stressed. Women in the work force should be advised of the potential adverse effects of chlorodiphenyl (54% chlorine) on the unborn child. Those who have borne children and work with chlorodiphenyl (54% chlorine) should be counseled concerning the advisability of nursing their offspring.

—Liver function tests: Chlorodiphenyl (54% chlorine) may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Skin disease: Chlorodiphenyl (54% chlorine) is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

• Summary of toxicology

Chlorodiphenyl (54% chlorine) vapor is toxic to the liver. Rats exposed to 5.4 mg/m³ for 7 hours daily for 4 months showed increased liver weight and injury to the liver cells; 1.5 mg/m³ for 7 months also produced histopathologic evidence of liver damage, which was considered to be of a reversible character. The vapor and the liquid are moderately irritating to the eye; contact with skin leads to removal of natural fats and oils with subsequent drying and cracking of the skin. Acne-form dermatitis (chloracne) due to exposure to chlorodiphenyl of 54% chlorine content has been reported but the period of exposure was not indicated. The production of liver tumors and adverse reproductive effects has been demonstrated in experimental animals following ingestion of polychlorinated biphenyls. The relevance to humans of some of these studies has not yet been established.

CHEMICAL AND PHYSICAL PROPERTIES

• Physical data

1. Molecular weight: 326 (approximately)
2. Boiling point (760 mm Hg): 365– 390 C (689–734 F)
3. Specific gravity (water = 1): 1.5
4. Vapor density (air = 1 at boiling point of chlorodiphenyl (54% chlorine)): 11.2
5. Melting point: 10 C (50 F) (pour point)
6. Vapor pressure at 20 C (68 F): 0.00006 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Much less than 1

• Reactivity

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving chlorodiphenyl (54% chlorine).
4. Special precautions: Chlorodiphenyl (54% chlorine) will attack some forms of plastics, rubber, and coatings.

• Flammability

1. Flash point: 222 C (432 F)
2. Autoignition temperature: None to boiling point
3. Flammable limits in air, % by volume: Not available
4. Extinguishant: Foam, dry chemical, carbon dioxide

• Warning properties

Although chlorodiphenyl (54% chlorine) has a typical aromatic odor and causes eye irritation, this substance is treated as a material with poor warning properties, as no quantitative information is available concerning its odor and irritation thresholds. The AIHA *Hygienic Guide* states that the vapors of the chlorodiphenyls are "moderately irritating to eye tissues," but the concentrations which cause irritation are not stated.

MONITORING AND MEASUREMENT PROCEDURES[4]

• General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Method

Sampling and analyses may be performed by collection of chlorodiphenyl on a filter with subsequent extraction with petroleum ether and gas chromatographic analysis. An analytical method for chlorodiphenyl (54% chlorine) is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid chlorodiphenyl (54% chlorine).

• Clothing contaminated with liquid chlorodiphenyl (54% chlorine) should be placed in closed containers for storage until it can be discarded or until provision is

made for the removal of chlorodiphenyl (54% chlorine) from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chlorodiphenyl (54% chlorine), the person performing the operation should be informed of chlorodiphenyl's (54% chlorine) hazardous properties.

- Non-impervious clothing which becomes contaminated with liquid chlorodiphenyl (54% chlorine) should be removed promptly and not reworn until the chlorodiphenyl (54% chlorine) is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid chlorodiphenyl (54% chlorine) may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid chlorodiphenyl (54% chlorine) should be promptly washed or showered with soap or mild detergent and water to remove any chlorodiphenyl (54% chlorine).
- Eating and smoking should not be permitted in areas where liquid chlorodiphenyl (54% chlorine) is handled, processed, or stored.
- Employees who handle liquid chlorodiphenyl (54% chlorine) should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.
- Areas in which exposure to chlorodiphenyl (54% chlorine) may occur should be identified by signs or other appropriate means, and access to these areas should be limited to authorized persons.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chlorodiphenyl (54% chlorine) may occur and control methods which may be effective in each case:

Operation	Controls
Use as high-temperature transfer medium in chemical/food processing vessels and drying ovens	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a dielectric in manufacture of transformers, capacitors, resistors, and other electrical apparatus	General dilution ventilation; local exhaust ventilation; personal protective equipment
Application and formulation as plasticizer, flame-retardant, and adhesive and weatherizer in spray surface coatings; manufacture and application of impregnants for cloth, paper, fiberboard, wood, and asbestos; manufacture and application of natural and synthetic waxes and polishes; manufacture and application of hot-melt and other adhesives	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as non-flammable working fluid in vacuum pumps, hydraulic systems and expansion systems	General dilution ventilation; local exhaust ventilation
Use during application of high-pressure, temperature, and moisture lubricants	Personal protective equipment
Use in compounding and processing of plastics for flame retardancy	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture and application for use as pesticides and fungicides	Personal protective equipment
Use as an intermediate or raw material in further organic synthesis	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as sealer for gaskets of natural rubber and synthetics	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as adhesive release on tapes and ink release on carbonless duplicating paper; as a pigment carrier in dyeing polyesters and paper	Personal protective equipment

Use as a pressure adhesive for sign backings, insect traps, and tapes	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in compounding mastics, and sealing and caulking materials; use in compounding of printing inks	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If chlorodiphenyl (54% chlorine) gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If chlorodiphenyl (54% chlorine) gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If chlorodiphenyl (54% chlorine) soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chlorodiphenyl (54% chlorine), move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When chlorodiphenyl (54% chlorine) has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chlorodiphenyl (54% chlorine) is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Chlorodiphenyl (54% chlorine) may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

ADDITIONAL INFORMATION

To find additional information on chlorodiphenyl (54% chlorine), look up chlorodiphenyl (54% chlorine) in the following documents:

• Medical Surveillance from the SCP
• Respiratory Protection from the SCP
• Personal Protection and Sanitation from the SCP
• NIOSH Criteria Document for Polychlorinated Biphenyls (September 1977)

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chlorodiphenyl (54% Chlorine)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chlorodiphenyls," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Polychlorinated Biphenyls*, HEW Publication No. (NIOSH) 77-225, U.S. Government Printing Office, Washington, D.C., 1977.

• Olivier, N.: "Chloracne," *Archives of Dermatology*, 99: 127-128, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 7, 1974, and Volume 18, 1978.

RESPIRATORY PROTECTION FOR CHLORODIPHENYL (54% CHLORINE)

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Vapor Concentration	
5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against pesticides. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of chlorodiphenyl (54% chlorine); however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 5 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Chloroform*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CHCl_3$
- Synonyms: Trichloromethane
- Appearance and odor: Colorless liquid with a pleasant, sweet odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chloroform is a ceiling level of 50 parts of chloroform per million parts of air (ppm). This may also be expressed as 240 milligrams of chloroform per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to a ceiling level of 2 ppm averaged over a one-hour period, and that chloroform be regulated as an occupational carcinogen. The NIOSH Criteria Document for Chloroform should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chloroform can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Chloroform vapor may cause headache, drowsiness, vomiting, dizziness, unconsciousness, irregular heart beat, and death. Liver and kidney damage may also result from exposure to chloroform vapor. When splashed in the eye, chloroform causes pain and irritation. Swallowing chloroform is followed immediately by severe burning of the mouth and throat, pain in the chest and abdomen, and vomiting. Depending on the amount swallowed, loss of consciousness and liver damage may follow.

2. Long-term Exposure: Prolonged exposure to chloroform may cause liver and kidney damage. Prolonged or repeated skin contact with the liquid may produce skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chloroform.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chloroform at potentially hazardous levels:

1. Initial Medical Examination:

— A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. A history of, or physical signs consistent with, chronic alcoholism probably constitutes such an increased risk. Examination of liver, kidneys, and heart should be stressed. The skin should be examined for evidence of chronic disorders.

— Liver function tests: A profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

— Urinalysis: Since kidney damage has also been observed from exposure, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Chloroform vapor is a central nervous system depressant and is toxic to the liver and kidneys. It has been largely abandoned as an anesthetic agent because of the frequency of cardiac arrest during surgery and of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

delayed death due to hepatic injury. An increased incidence of cardiac arrhythmias has been demonstrated during surgery in patients anesthetized with chloroform, as compared with other anesthetic agents; vapor concentrations were of the order of 22,500 ppm. Animals showed minor and reversible injury of liver and kidneys after repeated 7-hour exposures to concentrations of chloroform as low as 25 ppm, while 50 to 85 ppm produced more severe injury. Experimental human exposures showed that 14,000 to 16,000 ppm caused rapid loss of consciousness in man; 4100 ppm or less caused serious disorientation, while single exposures of 1000 ppm caused dizziness, nausea, and aftereffects of fatigue and headache. Prolonged exposure to 80 to 240 ppm caused lassitude, digestive disturbances, and mental dullness, while 20 to 70 ppm produced milder symptoms. Of 68 chemical workers exposed regularly to concentrations of 2 to 205 ppm for 1 to 4 years, some 25% had hepatomegaly. This group of 68 exposed workers were found to be more susceptible to viral hepatitis than the general population. The hepatotoxicity of several chlorinated hydrocarbons has been shown to be potentiated by prior exposure to some aliphatic alcohols. This phenomenon has been demonstrated in mice exposed first to isopropyl alcohol by gavage and then to chloroform by intraperitoneal injection. A potentiating effect of ethyl alcohol ingestion on the toxicity of chloroform vapor in the occupational setting is suspected, but has not been proven in industrial practice. High concentrations of vapor cause conjunctival irritation and blepharospasm. Liquid chloroform splashed in the eye causes immediate burning pain and conjunctival irritation; the corneal epithelium may be injured, but regeneration is prompt, and the eye returns to normal in 1 to 3 days. The liquid has a defatting effect on the skin and may produce chronic irritation with drying and cracking. Liver tumors have been reported in animals.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 119.4
2. Boiling point (760 mm Hg): 61 C (142 F)
3. Specific gravity (water = 1): 1.49
4. Vapor density (air = 1 at boiling point of chloroform): 4.1
5. Melting point: −63.5 C (−82 F)
6. Vapor pressure at 20 C (68 F): 160 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.8
8. Evaporation rate (butyl acetate = 1): 11.6

- **Reactivity**

1. Conditions contributing to instability: In the presence of air and light, chloroform slowly reacts to form toxic phosgene and hydrogen chloride gases.
2. Incompatibilities: Chloroform reacts with strong caustics and chemically active metals such as aluminum, magnesium powder, sodium, or potassium.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, chlorine, phosgene, and carbon monoxide) may be released when chloroform decomposes.
4. Special precautions: Liquid chloroform will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible

- **Warning properties**

1. Odor Threshold: Patty reports that the odor threshold of chloroform is approximately 200 to 300 ppm, and May reports an odor threshold of 200 ppm. The *Hygienic Guide*, however, gives an odor threshold of 50 ppm and states that "olfactory fatigue" occurs upon exposure.
2. Eye Irritation Level: Grant states that "in conscious individuals high concentrations of vapors of chloroform cause moderate sensation of stinging and irritation of the eyes, automatically inducing protective closure of the lids." The concentrations causing eye irritation are not mentioned. However, Patty does not give any indication that eye irritation occurs at concentrations even as high as 4096 ppm.
3. Evaluation of Warning Properties: Since there are no quantitative data relating the irritant effects of chloroform to air concentrations, and since olfactory fatigue occurs during exposure to chloroform, this material is treated as a substance with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **One-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average one-hour exposure is based on a single one-hour sample. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of chloroform. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure chloroform may be used. An

analytical method for chloroform is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid chloroform, where skin contact may occur.
- Clothing wet with liquid chloroform should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chloroform from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chloroform, the person performing the operation should be informed of chloroform's hazardous properties.
- Non-impervious clothing which becomes wet with liquid chloroform should be removed promptly and not reworn until the chloroform is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid chloroform may contact the eyes.
- Where there is any possibility that employees' eyes may be exposed to chloroform, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes wet with liquid chloroform should be promptly washed or showered with soap or mild detergent and water to remove any chloroform.
- Eating and smoking should not be permitted in areas where liquid chloroform is handled, processed, or stored.
- Employees who handle liquid chloroform should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.
- Areas in which exposure to chloroform may occur should be identified by signs or other appropriate means, and access to these areas should be limited to authorized persons.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chloroform may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of fluorocarbons for refrigerant propellants; manufacture of fluorocarbon resins	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as an extractant solvent in manufacure of pharmaceuticals, rubber, essential oils and flavors, sterols and alkaloids, and in the recovery of fat from waste products	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in chemical analysis and assays; veterinary uses, and in standard solutions as preservative and bactericide	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a general solvent in plastics, dyes, oils, waxes, rubber, cleaning and dry cleaning industries	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a chemical intermediate in dye, drug, and pesticide industries	Process enclosure; local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

Eye Exposure

If chloroform gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If burning is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If chloroform gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If chloroform soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chloroform, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When chloroform has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chloroform is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

ADDITIONAL INFORMATION

To find additional information on chloroform, look up chloroform in the following documents:

• Medical Surveillance for Chemical Hazards

• Respiratory Protection for Chemical Hazards

• Personal Protection and Sanitation for Chemical Hazards

• NIOSH Criteria Document for Chloroform (Revised June 1976)

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chloroform," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chloroform," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Dow Chemical Company: *Material Safety Data Sheet - Chloroform*, Midland, Michigan.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Agency for Research on Cancer: *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Vol. 1, Lyon, France, 1972.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• Lehman, K. B., and Schmidt-Kerl, L.: "The Thirteen Most Important Chlorinated Aliphatic Hydrocarbons from the Standpoint of Industrial Hygiene," *Archives of Hygiene*, 116:131-200, 1936 (Ger.)

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chloroform*, HEW Publication No. (NIOSH) 75-114, GPO No. 017-033-00045, U.S. Government Printing Office, Washington, D.C., 1976 (revised).

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Traiger, G. J., and Plaa, G. L.: "Chlorinated Hydrocarbon Toxicity," *Archives of Environmental Health*, 28:276-278, 1974.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 1, 1972.

RESPIRATORY PROTECTION FOR CHLOROFORM

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
500 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
1000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1-Chloro-1-Nitropropane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_3H_6CHClNO_2$
- Synonyms: None
- Appearance and odor: Colorless liquid with an unpleasant odor that causes tears.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1-chloro-1-nitropropane is 20 parts of 1-chloro-1-nitropropane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 100 milligrams of 1-chloro-1-nitropropane per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for 1-chloro-1-nitropropane from 20 ppm to 2 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1-Chloro-1-nitropropane can affect the body if it is inhaled or if it comes in contact with the eyes. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure of animals has produced severe irritation of the lungs with severe breathing difficulties which may be delayed in onset. Liver, heart, kidney, and blood vessel damage were also reported in animals. In addition, eye irritation has been reported in animals.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1-chloro-1-nitropropane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1-chloro-1-nitropropane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1-chloro-1-nitropropane exposure.

—Chronic respiratory disease: 1-Chloro-1-nitropropane causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1-chloro-1-nitropropane might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: 1-Chloro-1-nitropropane causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: 1-Chloro-1-nitropropane causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Cardiovascular disease: 1-Chloro-1-nitropropane causes heart damage in animals. In persons with impaired cardiovascular function, the inhalation of 1-chloro-1-nitropropane might cause exacerbation of pre-existing disorders.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1-Chloro-1-nitropropane is a pulmonary irritant and causes liver, kidney, and heart damage in animals. Exposure of rabbits to concentrations near 2600 ppm for

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

2 hours was fatal, but 2200 ppm for 1 hour was nonlethal; autopsy revealed pulmonary edema, cellular necrosis of the heart, liver, and kidneys, and cellular damage in the brain. At high concentrations there was lacrimation, nasal discharge, and pulmonary rales. No human experience has been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 123.5
  2. Boiling point (760 mm Hg): 140 C (285 F)
  3. Specific gravity (water = 1): 1.2
  4. Vapor density (air = 1 at boiling point of 1-chloro-1-nitropropane): 4.3
  5. Melting point: Data not available
  6. Vapor pressure at 20 C (68 F): 5.8 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Less than 0.8
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Overheating in closed containers may cause explosions.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen, hydrogen chloride, and carbon monoxide) may be released in a fire involving 1-chloro-1-nitropropane.
  4. Special precautions: Liquid 1-chloro-1-nitropropane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 62 C (144 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold of this substance.
  2. Eye Irritation Level: According to the *Handbook of Organic Industrial Solvents*, 1-chloro-1-nitropropane may irritate the eyes.
  3. Evaluation of Warning Properties: Since the TLV has been recommended only to "minimize" irritation, for the purposes of this guideline, 1-chloro-1-nitropropane is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for 1-chloro-1-nitropropane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 1-chloro-1-nitropropane.
- Clothing wet with liquid 1-chloro-1-nitropropane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1-chloro-1-nitropropane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1-chloro-1-nitropropane, the person performing the operation should be informed of 1-chloro-1-nitropropane's hazardous properties.
- Non-impervious clothing which becomes wet with liquid 1-chloro-1-nitropropane should be removed promptly and not reworn until the 1-chloro-1-nitropropane is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid 1-chloro-1-nitropropane may contact the eyes.

SANITATION

307

• Skin that becomes wet with liquid 1-chloro-1-nitropropane should be promptly washed or showered with soap or mild detergent and water to remove any 1-chloro-1-nitropropane.
• Eating and smoking should not be permitted in areas where 1-chloro-1-nitropropane is handled, processed, or stored.
• Employees who handle liquid 1-chloro-1-nitropropane should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following partial list includes some common operations in which exposure to 1-chloro-1-nitropropane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent and anti-gelling agent for rubber cements	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If liquid 1-chloro-1-nitropropane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid 1-chloro-1-nitropropane gets on the skin, wash the contaminated skin using soap or mild detergent and water. If liquid 1-chloro-1-nitropropane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of 1-chloro-1-nitropropane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When liquid 1-chloro-1-nitropropane has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If 1-chloro-1-nitropropane is spilled or leaked, the following steps should be taken:
1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. Mix spill of up to one gallon with soda ash, spray with water, let stand in bucket with water for two hours, neutralize with dilute hydrochloric acid, flush to sewer, and wash area of spill with detergent and solution.
• Waste disposal methods:
1-Chloro-1-nitropropane may be disposed of:
1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. If quantities of up to one gallon, by the treatment described above.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1-Chloro-1-Nitropropane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.
• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.
• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents, Technical Guide No. 6* (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Machle, W., et al.: "The Physiological Response of Animals to Certain Mononitroparaffins," *Journal of Industri ' Hygiene and Toxicology*, 27:95-102, 1945.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR 1-CHLORO-1-NITROPROPANE

Condition	Minimum Respiratory Protection* Required Above 20 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chloropicrin

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CCl_3NO_2
- Synonyms: Nitrotrichloromethane; trichloronitromethane; nitrochloroform
- Appearance and odor: Colorless, oily liquid with a sharp, penetrating odor that causes tears.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chloropicrin is 0.1 part of chloropicrin per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.7 milligram of chloropicrin per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chloropicrin can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Chloropicrin causes eye irritation and tearing. It also causes cough, nausea, and vomiting, and severe irritation of the skin. Breathing chloropicrin vapors may also cause delayed severe breathing difficulties and which may cause death.

2. Long-term Exposure: Overexposure to chloropicrin may cause increased susceptibility to future overexposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chloropicrin.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chloropicrin at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed. The skin should be examined for evidence of chronic disorders.

—FVC and FEV (1 sec): Chloropicrin is a severe respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure.

—14" x 17" chest roentgenogram: Chloropicrin may cause respiratory impairment. Persons with pre-existing pulmonary disease may be at increased risk.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Chloropicrin vapor is a severe irritant of the eyes, skin, and respiratory tract. A lethal exposure for humans is stated to be 119 ppm for 30 minutes, with death usually resulting from pulmonary edema; particular injury occurs in the medium and small bronchi. In addition to pulmonary irritation, human exposure results in lacrimation, cough, nausea, vomiting, and skin irritation; individuals injured by inhalation of chloropicrin vapor are said to be more susceptible to subsequent exposures. A concentration of 15 ppm could not be tolerated longer than 1 minute, even by persons acclimated to chloropicrin; exposure to 4 ppm for a few seconds is temporarily disabling, due to the irritant effects. Concentrations of 0.3 to 0.37 ppm resulted in painful eye irritation in 3 to 30 seconds. Chloropicrin is a severe skin irritant.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 164.4
  2. Boiling point (760 mm Hg): 112 C (234 F)
  3. Specific gravity (water = 1): 1.635
  4. Vapor density (air = 1 at boiling point of chloropicrin): 5.7
  5. Melting point: −64 C (−83 F)
  6. Vapor pressure at 20 C (68 F): 20 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.18
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: High temperatures or severe shock, particularly when involving containers of greater than 30 gallons capacity.
  2. Incompatibilities: Contact with strong oxidizers may cause fires or explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen, phosgene, nitrosyl chloride, chlorine, and carbon monoxide) may be released when chloropicrin decomposes.
  4. Special precautions: Liquid chloropicrin will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible, but with strong initiation, heated material under confinement will detonate.
  2. Fires involving chloropicrin should be fought from an explosion-resistant location.
- **Warning properties**
  1. Odor Threshold: Stern reports an odor threshold of 0.0073 mg/l (1.1 ppm)
  2. Eye Irritation Level: The *Documentation of TLV's* states that "according to Flury and Zernik, chloropicrin in concentrations of from 0.2 to 0.37 ppm resulted in painful irritation to the eyes in 3 to 30 seconds." Patty, however, reports that 1.3 ppm is the lowest irritant concentration, but that 0.3 to 3.7 ppm for 3 to 30 seconds causes "closing of the eyelids according to individual sensitivity."
  3. Evaluation of Warning Properties: Through its irritant effects on the eyes, chloropicrin can be detected within three times the permissible exposure limit, according to the *Documentation of TLV's*. For the purposes of this guideline, therefore, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for chloropicrin had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid chloropicrin.
- Clothing contaminated with chloropicrin should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chloropicrin from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chloropicrin, the person performing the operation should be informed of chloropicrin's hazardous properties.
- Where there is any possibility of exposure of an employee's body to liquid chloropicrin, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with chloropicrin should be removed immediately and not reworn until the chloropicrin is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid chloropicrin contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid chloropicrin, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with chloropicrin should be immediately washed or showered with soap or mild detergent and water to remove any chloropicrin.
- Eating and smoking should not be permitted in areas where liquid chloropicrin is handled, processed, or stored.
- Employees who handle liquid chloropicrin should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chloropicrin may occur and control methods which may be effective in each case:

Operation	Controls
Use as a soil fumigant, disinfectant, and sterilizer for control of fungi, nematodes, and other injurious organisms; liberation as a fumigant for stored grains, cereals, and fruits	Process enclosure; general dilution ventilation; personal protective equipment
Use as a rodenticide and insecticide for rats and insects	Process enclosure; general dilution ventilation; personal protective equipment
Use as a chemical intermediate in organic synthesis in dyes and as an oxidizing agent	Process enclosure; general dilution ventilation; personal protective equipment
Use as a warning agent in illuminating gas; use as a lacrimator, and as a nauseant in chemical warfare	General dilution ventilation; personal protective equipment
Use as a chemical sterilant without high temperature	General dilution ventilation; process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid chloropicrin or high concentrations of chloropicrin vapor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid chloropicrin gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid chloropicrin soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of chloropicrin, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When liquid chloropicrin has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If liquid chloropicrin is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

- Waste disposal method:

Chloropicrin may be disposed of by absorbing in vermiculite, dry sand, earth, or a similar material and disposing in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Chloropicrin," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
- Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
- Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.
- von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR CHLOROPICRIN

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Vapor Concentration	
4 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 4 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a full facepiece providing protection against organic vapors.
	Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of chloropicrin; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 4 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Chloroprene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2=CClCH=CH_2$
- Synonyms: 2-Chloro-1,3-butadiene; chlorobutadiene; beta-chloroprene
- Appearance and odor: Colorless liquid with an ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chloroprene is 25 parts of chloroprene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 90 milligrams of chloroprene per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to 3.6 mg/m^3 (1 ppm) measured over a 15-minute period, and that chloroprene be regulated as an occupational carcinogen. The NIOSH Criteria Document for Chloroprene should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chloroprene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

Exposure to chloroprene may irritate and damage the eyes. It may also irritate the nose and throat and cause a skin rash. In addition, it may cause nervousness, irritability, and temporary loss of hair. Exposure to chloroprene has been reported to cause cancer of the skin and the lung. It may also exert embryotoxic and fetatoxic effects and may interfere with reproductive processes.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chloroprene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chloroprene at potentially hazardous levels:

1. Initial Medical Examination:

--A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, skin, and eyes should be stressed. The skin should be examined for evidence of chronic disorders and cancer. A medical warning should be given to employees, noting that chloroprene exposure has been experimentally linked with reproduction abnormalities such as low sperm count and adverse effects on pregnancy. The relevance to humans of some of these findings has not yet been established.

—14" x 17" chest roentgenogram: Chloroprene may cause an increased incidence of lung cancer in workers. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Chloroprene may cause lung damage after long-term exposure. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Skin disease: Chloroprene is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Chloroprene is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

• **Summary of toxicology**

Chloroprene vapor irritates the mucous membranes and skin, and may have teratogenic and carcinogenic properties. Rats died from repeated daily exposure to 1.2 mg/l (330 ppm), with damage to lungs, liver, and kidneys. Higher concentrations caused anesthesia and respiratory paralysis. Daily animal exposures of 0.3 mg/l (83 ppm) were tolerated for 13 weeks. Chloroprene has been reported to have an effect on embryogenesis in animals; in rats and mice, there was an increase in total embryonal mortality and a reduction in the fetal weight of offspring of females exposed during pregnancy. Conjunctivitis and focal necrosis of the cornea have been reported in workers. Excessive nervousness and irritability have been observed. Skin exposures cause dermatitis and, occasionally, a peculiar focal alopecia of the scalp which is reversible. Two recent reports suggest that chloroprene exposure is associated with an increased incidence of cancer of the skin and of the lungs.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 88.5
2. Boiling point (760 mm Hg): 58.9 C (138 F)
3. Specific gravity (water = 1): 0.96
4. Vapor density (air = 1 at boiling point of chloroprene): 3.0
5. Melting point: −130 C (-202 F)
6. Vapor pressure at 20 C (68 F): 179 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Temperatures above −15 C (5 F)
2. Incompatibilities: Contact with peroxides and other oxidizers may cause polymerization with evolution of heat and rupture of containers.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving chloroprene.
4. Special precautions: Chloroprene will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: −20 C (-4 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Lower: 4.0; Upper: 20.0
4. Extinguishant: Foam, dry chemical, carbon dioxide

• **Warning properties**

No quantitative data are available relating the warning properties of chloroprene to air concentrations. Therefore, it is treated as a material with poor warning properties. Chloroprene is an irritant, as noted by Patty.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for chloroprene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid chloroprene.

• Clothing contaminated with liquid chloroprene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chloroprene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chloroprene, the person performing the operation should be informed of chloroprene's hazardous properties.

• Any clothing which becomes wet with liquid chloroprene should be removed immediately and not reworn until the chloroprene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid chloroprene may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid chloroprene should be promptly washed or showered with soap or mild detergent and water to remove any chloroprene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chloroprene may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of a variety of neoprene elastomers; use in manufacture of neoprene latex which might retain unpolymerized chloroprene	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If chloroprene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If chloroprene gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If chloroprene soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chloroprene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When chloroprene has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If chloroprene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Chloroprene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of chloroprene vapors are permitted.

• Waste disposal method:

Chloroprene may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chloroprene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Asmangulyan, T. A., and Badalyan, S. O.: *Chemical Abstracts*, Vol. 78, 67807x, p. 108, 1973.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Lloyd, J. W.: "Background Information on Chloroprene,", *Journal of Occupational Medicine*, 17:4, April 1975.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chloroprene*, HEW Publication No. (NIOSH) 77-210, U.S. Government Printing

Office, Washington, D.C., 1977.
• Office of Occupational Health Surveillance and Biometrics, National Institute for Occupational Safety and Health, "Background Information on Chloroprene," Rockville, Maryland, pp. 1-8, 20 January 1975.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR CHLOROPRENE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
400 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 400 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chromic Acid and Chromates*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all chromic acid and chromates. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Chromic acid

- Formula: CrO_3
- Synonyms: Chromic anhydride; chromium trioxide
- Appearance and odor: Dark red, deliquescent, odorless solid.

Sodium dichromate

- Formula: $Na_2Cr_2O_7 \cdot 2H_2O$
- Synonyms: Sodium bichromate (dihydrate)
- Appearance and odor: Red-orange, odorless solid.

Potassium chromate

- Formula: K_2CrO_4
- Synonyms: Chromate of potash
- Appearance and odor: Yellow, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chromic acid or chromates is a ceiling of 0.1 milligram of chromic acid or chromates per cubic meter of air (mg/m³). Certain forms of chromium (VI) have been found to cause increased respiratory cancer among workers. Certain other forms of chromium (VI) are currently believed to be non-carcinogenic: The non-carcinogenic forms include the monochromates and bichromates (dichromates) of hydrogen, lithium, sodium, potassium, rubidium, cesium, and ammonium, and chromium (VI) oxide (chromium acid anhydride). NIOSH has not conducted an in-depth study of the toxicity of chromium metal or compounds containing chromium in an oxidation state other than 6. NIOSH recommends that the permissible exposure limit for carcinogenic chromium (VI) compounds be reduced to 0.001 Cr (VI) mg/m³ and that thesecompounds be regulated as occupational carcinogens. NIOSH also recommends that the permissible exposure limit for non-carcinogenic chromium (VI) be reduced to 0.025 Cr (VI) mg/m³ averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 0.05 Cr (VI) mg/m³ averaged over a 15-minute period. It is further recommended that chromium (VI) in the workplace be considered carcinogenic, unless it has been demonstrated that only the non-carcinogenic chromium (VI) compounds mentioned above are present. The NIOSH Criteria Documents for Chromic Acid and Chromium (VI) should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chromic acid or chromates can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Chromic acid mist and chromate dusts may cause severe irritation of the nose, throat, bronchial tubes, and lungs. Chromic acid splashed in the eyes may cause severe injury. If swallowed, chromates and sodium and potassium dichromates may cause stomach and kidney problems. These

---

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

compounds, if swallowed, often cause vomiting. Skin exposure to chromic acid or chromates may cause ulceration of the skin.

2. Long-term Exposure: Repeated or prolonged exposure to chromic acid or chromate dust or mist may cause an ulceration and perforation of the nasal septum. Respiratory irritation may occur with symptoms resembling asthma. Liver damage with yellow jaundice has been reported. Prolonged or repeated exposure of the skin may cause a skin rash. Allergic skin rash may also occur. An increased amount of lung cancer has been found in employees in the chromate-producing industry.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chromic acid or chromates.

• Recommended medical surveillance

The following medical procedures should be made available to each employee who is exposed to chromic acid or chromates at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to chromic acid or chromates would be expected to be at increased risk from exposure. Examination of the respiratory system, blood, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Chromates have been shown to cause blood changes in humans. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—14" x 17" chest roentgenogram: Chromates may cause human lung damage and are associated with a high incidence of lung cancer. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Chromates are reported to cause decreased pulmonary function. Periodic surveillance is indicated.

—Urinalysis: Since chromates may cause kidney damage, a urinalysis should be obtained, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Chromates may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Skin disease: Chromates are defatting agents and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of these agents.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Emphasis should be placed on observation for changes in the mucous membranes of the upper respiratory tract, ulceration of the skin, and surveillance for malignancy of the respiratory tract and lungs.

• Summary of toxicology

Chromic acid mist and chromate dusts are severe irritants of the nasopharynx, larynx, lungs, and skin. Chromium compounds, especially the hexavalent compounds are associated with a high incidence of lung cancer in humans. Administered subcutaneously to rabbits and guinea pigs, chromates produce kidney damage, with albuminuria and cylindruria; fatal nephritis occurred in a human treated with chromic acid to cauterize a wound. Workers exposed to chromic acid or chromates in concentrations of 0.11 to 0.15 mg/m^3 developed ulcers of the nasal septum and irritation of the conjunctiva, pharynx and larynx, as well as asthmatic bronchitis. A worker exposed to unmeasured but massive amounts of chromic acid mist for 4 days developed severe frontal headache, wheezing, dyspnea, cough, and pain on inspiration; after 6 months there was still chest pain on inspiration and cough. In an industrial plant where the airborne chromic acid concentrations measured from 0.18 to 1.4 mg/m^3, moderate irritation of the nasal septum and turbinates was observed after 2 weeks of exposure, ulceration of the septum after 4 weeks, and perforation of the septum after 8 weeks. A worker exposed to an unmeasured concentration of chromic acid mist for 5 years developed jaundice and was found to be excreting significant amounts of chromium; liver function in four other workers with high urinary chromium excretion was mildly to moderately impaired. Other studies of chromate workers have not found any unusual incidence of liver diseases or other systemic diseases except for lung cancer. Erosion and discoloration of the teeth has been attributed to chromic acid exposure. Blood changes were observed in chromate plant workers, including leukocytosis or leukopenia, monocytosis, and eosinophilia. A markedly increased incidence of bronchogenic carcinoma occurs in workers exposed to chromate dust. The latent period is relatively short, suggesting the presence of a potent carcinogen. Calcium chromate and zinc chromate have been demonstrated to be carcinogenic in rats, and the risk of lung cancer is reportedly increased in chrome pigment workers. Papillomata of the oral cavity and larynx were found in 15 of 77 chrome platers exposed for an average of 6.6 years to chromic acid mist at air concentrations of chromium of 0.4 mg/m^3. There is no positive evidence that chromic acid in the workplace has contributed to an increase in lung cancer, neither is there definitive evidence that absolves chromic acid. A concentrated solution of chromic acid in the eye causes severe corneal injury; chronic exposure to the mist causes conjunctivitis. Chrome ulcer, a penetrating lesion of the skin, occurs chiefly on the hands and forearms where there has been a break in the epidermis; it is believed to be due to a direct necrotizing effect of the chromate ion. The ulcer is relatively painless, heals slowly, and produces a characteristic depressed scar.

Prolonged exposure to chromic acid mist causes dermatitis, which varies from a dry erythematous eruption to a weeping eczematous condition. Cutaneous sensitization to chromate compounds is a common problem in industrial practice.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data—Chromic acid**

1. Molecular weight: 100
2. Boiling point (760 mm Hg): Decomposes when it melts
3. Specific gravity (water = 1): 2.7
4. Vapor density (air = 1 at boiling point of chromic acid): Not applicable
5. Melting point: 197 C (387 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Data not available (very low)
7. Solubility in water, g/100 g water at 20 C (68 F): 63
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Physical data—Sodium dichromate**

1. Molecular weight: 298
2. Boiling point (760 mm Hg): 400 C (752 F) (decomposes)
3. Specific gravity (water = 1): 2.34
4. Vapor density (air = 1 at boiling point of sodium dichromate): Not applicable
5. Melting point: 357 C (674 F) (loses water at 85 C (185 F))
6. Vapor pressure at 20 C (68 F): Zero (except for water of crystallization)
7. Solubility in water, g/100 g water at 20 C (68 F): 236
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Physical data—Potassium chromate**

1. Molecular weight: 194
2. Boiling point (760 mm Hg): Data not available
3. Specific gravity (water = 1): 2.7
4. Vapor density (air = 1 at boiling point of potassium chromate): Not applicable
5. Melting point: 971 C (1780 F)
6. Vapor pressure at 20 C (68 F): Zero
7. Solubility in water, g/100 g water at 20 C (68 F): 39
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity—Chromic acid or chromates**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with any combustible, organic, or other readily oxidizable materials such as paper, wood, sulfur, aluminum, plastics, etc. may cause fires and explosions.
3. Hazardous decomposition products: None
4. Special precautions: Chromic acid or chromates will attack most forms of metals, cloth, leather, plastics, rubber, and coatings and may cause spontaneous ignition.

- **Flammability**

1. Chromic acid is not combustible in itself, but is a powerful, oxidizing material. It will ignite on contact with acetic acid and alcohol.

- **Warning properties**

Grant states that "contact with the solid material or with concentrated solution (of chromic acid) by splash in the eye causes severe corneal injury characterized by infiltration, vascularization, and opacification of the cornea.

"More commonly, exposure to chromic acid occurs in less serious form as a result of spraying of fine droplets into the air from electroplating baths or by transfer to the eyes on the fingers. After chronic exposure to such conditions, the ocular changes seen are chronic conjunctival inflammation, analogous to the well-known irritation of the nasal mucosa which leads to perforation of the nasal septum." In addition, Grant states that "dichromates (bichromates) as ammonium, sodium, or potassium salts are water-soluble, crystalline substances which have a peculiar injurious effect on the cornea, causing great swelling of the corneal stroma."

The *Documentation of TLV's* states that "Vigliani and Zurlo reported . . . irritation of the mucous membranes of the larynx, pharynx, and conjunctiva . . . in a group of workers allegedly exposed to chromates or chromic acid in concentrations ranging from 0.11 to 0.15 mg/m³."

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of chromic acid or chromates. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of chromic acid or chromates on a filter, followed by chemical treatment and colorimetric analysis. An analytical method for chromic acid and chromates is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental

concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solids or liquids containing chromic acid or chromates.

• If employees' clothing may have become contaminated with solids or liquids containing chromic acid or chromates, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with chromic acid or chromates should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of substance from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chromic acid or chromates, the person performing the operation should be informed of chromic acid or chromates' hazardous properties.

• Where there is any possibility of exposure of an employee's body to solids or liquids containing chromic acid or chromates, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with chromic acid or chromates should be removed immediately and not reworn until the substance is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solids or liquids containing chromic acid or chromates contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solids or liquids containing chromic acid or chromates, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with chromic acid or chromates should be immediately washed or showered with soap or mild detergent and water to remove any such substance.

• Workers subject to skin contact with solids or liquids containing chromic acid or chromates should wash with soap or mild detergent and water any areas of the body which may have contacted such a substance at the end of each work day.

• Eating and smoking should not be permitted in areas where solids or liquids containing chromic acid or chromates are handled, processed, or stored.

• Employees who handle solids or liquids containing chromic acid or chromates should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

• Areas in which exposure to a carcinogenic form of chromium (VI) may occur should be identified by signs or other appropriate means, and access to these areas should be limited to authorized personnel only.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chromic acid or chromates may occur and control methods which may be effective in each case:

Operation	Controls
Use in metal finishing in chrome plating, anodizing, conversion coatings, and for corrosion resistance	Local exhaust ventilation; personal protective equipment
Use in leather finishing for shoe uppers, glove and garment leathers, and bag leather	Local exhaust ventilation; personal protective equipment
Use as corrosion inhibitors in radiator coolants, internal combustion and gas turbine engines, refrigerator and air conditioning systems, and water-cooled nuclear reactors	Local exhaust ventilation; personal protective equipment
Use in photoreproduction processes as sensitizing agents for photoengraving, photography, lithography, and blueprinting	Local exhaust ventilation; personal protective equipment

Operation	Controls
Use as corrosion-inhibiting and coloring pigments, artists' colors, jointing pastes, inks, rubber, and ceramics, and color blending	Process enclosure; local exhaust ventilation; personal protective equipment
Use in dyeing of fur, leather, fabrics, wool, and nylon; oxidizing of dyes; aftertreating on cotton, and in textile and paper printing; use in manufacture of glue used in shoes, furniture, and packaging	Local exhaust ventilation; personal protective equipment
Use as fungicides; use in aqueous preservatives and fire retardants for wood; for protection of textiles and seed	Local exhaust ventilation; personal protective equipment
Use in battery manufacture to increase shelf life; to provide corrosion resistance and for battery depolarization	Local exhaust ventilation; personal protective equipment
Use in manufacture of safety matches and explosives	Local exhaust ventilation; personal protective equipment
Use as a chemical reagent, oxidizing agent, catalyst, indicator, in bleaching of fats, oils, and waxes, in chemical synthesis, and in analytical chemistry	Local exhaust ventilation; personal protective equipment
Use in manufacture and packaging of cement	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solids or liquids containing chromic acid or chromates get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If solids or liquids containing chromic acid get on the skin, immediately flush the contaminated skin with soap or mild detergent and water. If chromic acid soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention. If chromates get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If solids or liquids containing chromic acid or chromates penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of chromic acid or chromates, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When solids or liquids containing chromic acid or chromates have been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If chromic acid or chromates are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing chromic acid or chromates should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Chromic acid or chromates may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Government Industrial Hygienists: "Chromic Acid and Chromates," *Documentation of the Threshold Limit Values for Substances in*

Workroom Air (3rd ed., 2nd printing), Cincinnati, 1974.
• American Industrial Hygiene Association: "Chromic Acid," *Hygienic Guide Series*, Detroit, Michigan, 1956.
• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.
• Committee on Medical and Biologic Effects of Environmental Pollutants, Division of Medical Sciences, National Research Council: *Chromium*, National Academy of Sciences, Washington, D.C., 1974.
• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
• Enterline, P. E.: "Respiratory Cancer Among Chromate Workers," *Journal of Occupational Medicine*, 16:523-526, 1974.
• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.
• Mancuso, T. F.: "Occupational Cancer and Other Health Hazards in a Chromate Plant: A Medical Appraisal II. Clinical and Toxicologic Aspects," *Industrial Medicine and Surgery*, 20:393-407, 1951.
• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-44, Chromic Acid and Chromates*, Washington, D.C., 1952.
• National Institute for Occupational Safety and Health, Office of Occupational Health Surveillance and Biometrics, U.S. Department of Health, Education and Welfare: *Background Information on Chromate Pigments*, Rockville, Maryland, August 22, 1975.
• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chromic Acid*, HEW Publication No. HSM 73-11021, GPO No. 017-033-00020, U.S. Government Printing Office, Washington, D.C., 1973.
• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chromium (VI)*, HEW Publication No. (NIOSH) 76-129, GPO No. 017-033-00125-1, U.S. Government Printing Office, Washington, D.C., 1975.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd ed. rev.), Lea and Febiger, Philadelphia, 1957.

• SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on these chemicals and has concluded that they cause cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 2, 1973, and Volume 23, 1980.
• **Warning properties**

RESPIRATORY PROTECTION FOR CHROMIC ACID AND CHROMATES

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
30 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 30 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Chromium Metal and Insoluble Chromium Salts*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all chromium metal and insoluble chromium salts. Physical and chemical properties of some specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Metallic chromium

- Formula: Cr
- Synonyms: None
- Appearance and odor: Shiny, odorless metal.

Copper chromite

- Formula: $Cu_2Cr_2O_4$
- Synonyms: Cuprous chromite
- Appearance and odor: Greenish-blue, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for chromium metal or insoluble chromium salts is 1 milligram of chromium metal or insoluble chromium salts per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. Certain forms of chromium (VI) have been found to cause increased respiratory cancer among workers. Certain other forms of chromium (VI) are currently believed to be non-carcinogenic: The non-carcinogenic forms are the monochromates and bichromates (dichromates) of hydrogen, lithium, sodium, potassium, rubidium, cesium, and ammonium, and chromium (VI) oxide (chromium acid anhydride). NIOSH has not conducted an in-depth study of the toxicity of chromium metal or compounds containing chromium in an oxidation state other than 6. NIOSH recommends that the permissible exposure limit for carcinogenic chromium (VI) compounds be reduced to 0.001 Cr (VI) mg/m^3 and that these compounds be regulated as occupational carcinogens. NIOSH also recommends that the permissible exposure limit for non-carcinogenic chromium (VI) be reduced to 0.025 Cr (VI) mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 0.05 Cr (VI) mg/m^3 averaged over a 15-minute period. It is further recommended that chromium (VI) in the workplace be considered carcinogenic, unless it has been demonstrated that only the non-carcinogenic chromium (VI) compounds mentioned above are present. The NIOSH Criteria Documents for Chromic Acid and Chromium (VI) should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Chromium metal or insoluble chromium salts can affect the body if they are inhaled. They can also affect the body if they are swallowed.

- **Effects of overexposure**

Ferro chrome alloys have been associated with lung changes in workers exposed to these alloys. Chromite dust exposure may cause minor lung changes.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to chromium metal or insoluble chromium salts.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to chromium metal or insoluble chromium salts at potentially hazardous levels:

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed.

—14" x 17" chest roentgenogram: Chromium and its insoluble salts may cause human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Insoluble chromium salts are reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. *Periodic Medical Examination:* The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

The dusts of chromium metal and its insoluble salts, chiefly the chromites, are usually reported to be relatively nontoxic; this is debatable, since exposures associated with toxic effects are usually mixed exposures involving several hexavalent chromium compounds. Ferrochrome alloys have been associated with pulmonary disease in humans. Four workers engaged in the production of ferrochrome alloys developed a nodular type of pulmonary disease with impairment of pulmonary function; air concentrations of chromium in this study averaged 0.26 mg/m³, although other fumes and dusts were also present. This pulmonary problem may be one of hypersensitivity and thus reversible. Other reports state that chest roentgenograms have revealed only "exaggerated pulmonic markings" in workers exposed to chromite dust. The lungs of groups of workers exposed to chromite dust have been shown to be the seat of pneumoconiotic changes consisting of slight thickening of interstitial tissue and interalveolar septa, with histologic fibrosis and hyalinization. Chromite ore roast mixed with sheep fat implanted intrapleurally in rats produced squamous cell carcinomata coexisting with sarcomata of the lungs; the same material implanted in the thighs of rats produced fibrosarcomata. A refractory plant using chromite ore to make chromite brick had no excess of lung cancer deaths over a 14-year period, and it was concluded that chromite alone probably is not carcinogenic.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Metallic chromium**

1. Molecular weight: 52
2. Boiling point (760 mm Hg): 2640 C (4784 F)
3. Specific gravity (water = 1): 7.2
4. Vapor density (air = 1 at boiling point of metallic chromium): Not applicable
5. Melting point: 1900 C (3452 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Copper chromite**

1. Molecular weight: 295.1
2. Boiling point (760 mm Hg): Data not available
3. Specific gravity (water = 1): 5.24
4. Vapor density (air = 1 at boiling point of copper chromite): Not applicable
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Basic potassium zinc chromate**

1. Molecular weight: 873.8
2. Boiling point (760 mm Hg): Decomposes at red heat
3. Specific gravity (water = 1): 3.47
4. Vapor density (air = 1 at boiling point of basic potassium zinc chromate): Not applicable
5. Melting point: Loses water slowly above 100 C (212 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Chromium metal in contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: None listed.
4. Special precautions: None listed.

• **Flammability**

1. Flash point: Not applicable
2. Minimum ignition temperature (metal): 400 C (752 F) (layer); 580 C (1076 F) (cloud)
3. Minimum explosive dust concentration (metal): 230 grams/m³
4. Extinguishant: Dry sand, dry dolomite, dry graphite

• **Warning properties**

Chromium metal and insoluble salts are not known to be eye irritants.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected

airborne concentrations of chromium metal or insoluble chromium salts. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Method

Sampling and analyses may be performed by collection of chromium metal or insoluble chromium salts on a filter, followed by treatment with acid and atomic absorption spectrophotometric analysis. An analytical method for chromium metal and insoluble chromium salts is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solids or liquids containing insoluble chromium salts.

• Clothing contaminated with insoluble chromium salts should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of insoluble chromium salts from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the insoluble chromium salts, the person performing the operation should be informed of insoluble chromium salts's hazardous properties.

• Non-impervious clothing which becomes contaminated with insoluble chromium salts should be removed promptly and not reworn until the insoluble chromium salts are removed from the clothing.

• Employees should be provided with and required to use dust- and splashproof safety goggles where solids or liquids containing insoluble chromium salts may contact the eyes.

SANITATION

• Skin that becomes contaminated with insoluble chromium salts should be promptly washed or showered with soap or mild detergent and water to remove any insoluble chromium salts.

• Eating and smoking should not be permitted in areas where solids or liquids containing insoluble chromium salts are handled, processed, or stored.

• Employees who handle solids or liquids containing insoluble chromium salts should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to chromium metal or insoluble chromium salts may occur and control methods which may be effective in each case:

Operation	Controls
Use in fabrication of alloys	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in preparation of alloy steels to enhance corrosion- and heat-resistance	Local exhaust ventilation; general dilution ventilation
Use in fabrication of plated products for decoration or increased wear-resistance	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in production of non-ferrous alloys to impart special qualities to the alloys	Local exhaust ventilation; general dilution ventilation
Use in production and processing of insoluble salts	Local exhaust ventilation; general dilution ventilation; personal protective equipment

Operation	Controls
Use as chemical intermediates; use in textile industry in dyeing, silk treating, printing, and moth-proofing wool	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in leather industry in tanning; use in photograhic fixing baths	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as catalysts for halogenation, alkylation, and catalytic cracking of hydrocarbons	Local exhaust ventilation; general dilution ventilation
Use as fuel additives and propellant additives; in photogaphic fixing baths and in ceramics	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If chromium metal or solids or liquids containing insoluble chromium salts get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

- **Skin Exposure**

If solids or liquids containing insoluble chromium salts get on the skin, wash the contaminated skin using soap or mild detergent and water. If solids or liquids containing insoluble chromium salts penetrate through the clothing, remove the clothing and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of chromium metal or insoluble chromium salts, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When solids or liquids containing insoluble chromium salts have been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If chromium metal or insoluble chromium salts are spilled, the following steps should be taken:

1. Remove all ignition sources where metallic chromium has been spilled.
2. Ventilate area of spill.
3. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing chromium metal or insoluble chromium salts should be absorbed in vermiculite, dry sand, earth, or a similar material.

- Waste disposal method:

Chromium metal or insoluble chromium salts may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Chromium (as Cr)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.
- Committee on Medical and Biologic Effects of Environmental Pollutants, Division of Medical Sciences, National Research Council: *Chromium*, National Academy of Sciences, Washington, D.C., 1974.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- Hueper, W. C.: "Experimental Studies in Metal Cancerigenesis. X. Cancerigenic Effects of Chromite Ore Roast Deposited in Muscle Tissue and Pleural Cavity of Rats," *A.M.A. Archives of Industrial Health*, 18:284-291, 1958.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saunders, Philadelphia, 1960.
- Mancuso, T. F., and Hueper, W. C.: "Occupational Cancer and Other Health Hazards in a Chromate Plant: A Medical Appraisal - 1. Lung Cancer in Chromate

Workers," *Industrial Medicine and Surgery*, 20:358-363, 1951.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chromic Acid*, HEW Publication No. HSM 73-11021, GPO No. 017-033-00020, U.S. Government Printing Office, Washington, D.C., 1973.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chromium (VI)*, HEW Publication No. (NIOSH) 76-129, GPO No. 017-033-00125-1, U.S. Government Printing Office, Washington, D.C., 1975.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Princi, F., et al.: "Pulmonary Disease of Ferroalloy Workers," *Journal of Occupational Medicine*, 4:301-310, 1962.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on these chemicals and has concluded that they cause cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 2, 1973, and Volume 23, 1980.

• Method

Sampling and analyses may be performed by collection of chromium metal or insoluble chromium salts on a filter, followed by treatment with acid and atomic

RESPIRATORY PROTECTION FOR CHROMIUM METAL AND INSOLUBLE CHROMIUM SALTS (AS CHROMIUM)

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any dust and mist respirator.
10 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Soluble Chromic and Chromous Salts (as Chromium)*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all soluble chromic and chromous salts. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Chromic sulfate hydrate

- Formula: $Cr_2(SO_4)_3 \cdot 16H_2O$ (approximately)
- Synonyms: None
- Appearance and odor: Violet or green, odorless solid.

Chromic potassium sulfate

- Formula: $KCr(SO_4)_2 \cdot 12H_2O$
- Synonyms: Potassium chrome alum; potassium chromium (III) sulfate
- Appearance and odor: Red-violet, odorless solid.

Chromous chloride

- Formula: $CrCl_2$
- Synonyms: None
- Appearance and odor: Colorless to gray, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for soluble chromic or chromous salts is 0.5 milligrams of soluble chromic or chromous salts (as chromium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. Certain forms of chromium (VI) have been found to cause increased respiratory cancer among workers. Certain other forms of chromium (VI) are currently believed to be non-carcinogenic: They are the monochromates and bichromates (dichromates) of hydrogen, lithium, sodium, potassium, rubidium, cesium, and ammonium, and chromium (VI) oxide (chromium acid anhydride). NIOSH has not conducted an in-depth study of the toxicity of chromium metal or compounds containing chromium in an oxidation state other than 6. NIOSH recommends that the permissible exposure limit for carcinogenic chromium (VI) compounds be reduced to 0.001 mg/m^3 and that these compounds be regulated as occupational carcinogens. NIOSH also recommends that the permissible exposure limit for non-carcinogenic chromium (VI) be reduced to 0.025 Cr (VI) mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 0.05 Cr (VI) mg/m^3 averaged over a 15-minute period. It is further recommended that chromium (VI) in the workplace be considered carcinogenic, unless it has been demonstrated that only the non-carcinogenic chromium (VI) compounds mentioned above are present. The NIOSH Criteria Documents for Chromic Acid and Chromium (VI) should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Soluble chromic or chromous salts can affect the body if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

Exposure to certain soluble chromic or chromous salts have been reported to cause an allergic skin rash.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to soluble chromic or chromous salts.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

• **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to soluble chromic and chromous salts at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from soluble chromic and chromous salts exposure.

—Skin disease: Chromic salts may cause an allergic dermatitis. Persons with pre-existing skin disorders may be more susceptible to the effects of these agents.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

• **Summary of toxicology**

The soluble chromic and chromous salts have no established toxicity. Since exposures are often mixed, consideration should be given to the possible exposure to hexavalent chromium, which is a more toxic form. The compound hexaaquachromium trichloride has been found to react with protein in vitro, indicating that it is not biologically inert. Of 35 rats implanted with chromic acetate in the thigh muscle, 1 developed sarcoma; this was considered to be evidence of weak carcinogenicity of this soluble trivalent compound. When taken by mouth, the trivalent compounds do not give rise to local or systemic effects and are poorly absorbed; no specific effects are known to result from inhalation. Animals ingesting chromic salts showed one-ninth as much chromium in the tissues as did animals ingesting equal amounts of chromates. Dermatitis from some chromic salts has been reported. Some investigators believe that all persons sensitized to hexavalent chromium are also sensitive to the trivalent form, although this has not been firmly established.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Chromic sulfate hydrate**

1. Molecular weight: 680 (approximately)
2. Boiling point (760 mm Hg): Decomposes at red heat
3. Specific gravity (water = 1): 1.7
4. Vapor density (air = 1 at boiling point of chromic sulfate hydrate): Not applicable
5. Melting point: 90 C (194 F) Loses water, residue does not melt
6. Vapor pressure at 20 C (68 F): Essentially zero (except water of crystallization)
7. Solubility in water, g/100 g water at 20 C (68 F): 84— 120
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Chromic potassium sulfate**

1. Molecular weight: 499.4
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.83
4. Vapor density (air = 1 at boiling point of chromic potassium sulfate): Not applicable
5. Melting point: 89 C (192 F) Loses water, then melts at 400 C (752 F).
6. Vapor pressure at 20 C (68 F): Essentially zero (except water of crystallization)
7. Solubility in water, g/100 g water at 20 C (68 F): 19.6
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Chromous chloride**

1. Molecular weight: 122.9
2. Boiling point (760 mm Hg): 1300 C (2372 F)
3. Specific gravity (water = 1): 2.93
4. Vapor density (air = 1 at boiling point of chromous chloride): Not applicable
5. Melting point: 820 C (1508 F)
6. Vapor pressure at 20 C (68 F): Essentially zero (except water of crystallization)
7. Solubility in water, g/100 g water at 20 C (68 F): Very soluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Water (chromyl chloride)
3. Hazardous decomposition products: None
4. Special precautions: None

• **Flammability**

1. Most soluble chromic or chromous salts are not combustible. However, chromyl chloride reacts vigorously with water, forming chromic acid, chromic chloride, hydrochloric acid, and chlorine. Also, chromyl chloride causes ignition of ammonia, ethyl alcohol, turpentine, and other combustible materials.

• **Warning properties**

Grant states that "chromium compounds . . . are known to cause dermatitis, ulcers of the skin and mucous membranes, and perforation of the nasal septum." Chromium chloride is an example of the chromium compounds which Grant states produces these effects. Not all chromic and chromous salts produce eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of soluble chromic or chro-

mous salts. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Method

Sampling and analyses may be performed by collection of soluble chromic or chromous salts on a filter, followed by treatment with acid and atomic absorption spectrophotometric analysis. An analytical method for soluble chromic and chromous salts is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquids or solids containing soluble chromic or chromous salts.

• Clothing contaminated with soluble chromic or chromous salts should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of chromic or chromous salts from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the chromic or chromous salts, the person performing the operation should be informed of soluble chromic or chromous salts's hazardous properties.

• Non-impervious clothing which becomes contaminated with soluble chromic or chromous salts should be removed promptly and not reworn until the soluble chromic or chromous salts are removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of liquids or solids containing soluble chromic or chromous salts contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquids or solids containing soluble chromic or chromous salts, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with soluble chromic or chromous salts should be promptly washed or showered to remove any soluble chromic or chromous salts.

• Employees who handle liquids or solids containing soluble chromic or chromous salts should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to soluble chromic or chromous salts may occur and control methods which may be effective in each case:

Operation	Controls
Use in textile treatment in dyeing, printing, moth-proofing, and water-proofing; use in tanning of leather in gloves, garments, and shoe uppers	Local exhaust ventilation; personal protective equipment
Use in manufacture of pigments for green varnishes, inks, paints, and glazes	Local exhaust ventilation; personal protective equipment
Use for metal treatment and polishing	Local exhaust ventilation; personal protective equipment
Use in photographic fixing baths for hardening of emulsions; use as catalysts and in manufacture of catalysts	Local exhaust ventilation; personal protective equipment
Use in chemical synthesis; use as corrosion inhibitors	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquids or solids containing soluble chromic or chromous salts get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If liquids or solids containing soluble chromic or chromous salts get on the skin, promptly flush the contaminated skin with water. If liquids or solids containing soluble chromic or chromous salts penetrate through the clothing, remove the clothing promptly and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of soluble chromic or chromous salts, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquids or solids containing soluble chromic or chromous salts have been swallowed give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If soluble chromic or chromous salts are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing soluble chromic or chromous salts should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Soluble chromic or chromous salts may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Chromium (as Cr)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Barborik, M.: "The Problem of Harmful Exposures to Chromium Compounds," *Industrial Medicine*, 39:5, pp. 45-47, May, 1970.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Committee on Medical and Biologic Effects of Environmental Pollutants, Division of Medical Sciences, National Research Council: *Chromium*, National Academy of Sciences, Washington, D.C., 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• Hueper, N. C., and Payne, W. W.: "Experimental Studies in Metal Carcinogenesis," *Archives of EnvironmentaHealth*, 5:445-462, 1962.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chromic Acid*, HEW Publication No. HSM 73-11021, GPO No. 017-033-00020, U.S. Government Printing Office, Washington, D.C., 1973.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Chromium (VI)*, HEW Publication No. (NIOSH) 76-129, GPO No. 017-033-00125-1, U.S. Government Printing Office, Washington, D.C., 1975.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Pierce, J. O., and Scheel, L. D.: "Toxicity of Alloys of Chromium. I. Solubility of Chromium in Solutions of Water and Protein," *Archives of Environmental Health*, 10:870-876, 1965.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on these chemicals and has concluded that they cause cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 2, 1973, and Volume 23, 1980.

RESPIRATORY PROTECTION FOR SOLUBLE CHROMIC AND CHROMOUS SALTS (AS CHROMIUM)

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate Concentration	
2.5 mg/m³ or less	Any dust and mist respirator, except single-use.**
5 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator.** Any fume respirator or high efficiency particulate respirator.** Any supplied-air respirator.** Any self-contained breathing apparatus.**
25 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
250 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 250 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Coal Tar Pitch Volatiles

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

Anthracene

- Formula: $C_{14}H_{10}$
- Synonyms: None
- Appearance and odor: Pale green solid with a faint aromatic odor.

Phenanthrene

- Formula: $C_{14}H_{10}$
- Synonyms: None
- Appearance and odor: Colorless solid with a faint aromatic odor.

Pyrene

- Formula: $C_{16}H_{10}$
- Synonyms: None
- Appearance: Bright yellow solid

Carbazole

- Formula: $C_{12}H_9N$
- Synonyms: None
- Appearance and odor: Colorless solid with a faint aromatic odor.

Benzo(a)pyrene

- Formula: $C_{20}H_{12}$
- Synonyms: BaP, 3,4-benzopyrene
- Appearance and odor: Colorless solid with a faint aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for coal tar pitch volatiles is 0.2 milligram of coal tar pitch volatiles per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit for coal tar products be reduced to 0.1 mg/m^3 (cyclohexane-extractable fraction) averaged over a work shift of up to 10 hours per day, 40 hours per week, and that coal tar products be regulated as occupational carcinogens. The NIOSH Criteria Document for Coal Tar Products and NIOSH Criteria Document for Coke Oven Emissions should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Coal tar pitch volatiles can affect the body if they are inhaled or if they come in contact with the eyes or skin.

- **Effects of overexposure**

Repeated exposure to coal tar pitch volatiles has been associated with an increased risk of developing bronchitis and cancer of the lungs, skin, bladder, and kidneys. Pregnant women may be especially susceptible to exposure effects associated with coal tar pitch volatiles. Repeated exposure to these materials may also cause sunlight to have a more severe effect on a person's skin. In addition, this type of exposure may cause an allergic skin rash.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to coal tar pitch volatiles.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to coal tar pitch volatiles at potentially hazardous levels:

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the oral cavity, respiratory tract, bladder, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders, for premalignant and malignant lesions, and evidence of hyperpigmentation or photosensitivity.

—Urinalysis: Coal tar pitch volatiles are associated with an excess of kidney and bladder cancer. A urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment, as well as a test for red blood cells.

—Urinary cytology: Coal tar pitch volatiles are associated with an excess of kidney and bladder cancer. Employees having 5 or more years of exposure or who are 45 years of age or older should have a urinary cytology examination.

—Sputum cytology: Coal tar pitch volatiles are associated with an excess of lung cancer. Employees having 10 or more years of exposure or who are 45 years of age or older should have a sputum cytology examination.

—14" x 17" chest roentgenogram: Coal tar pitch volatiles are associated with an excess of lung cancer. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Coal tar pitch volatiles are reported to cause an excess of bronchitis. Periodic surveillance is indicated.

—A complete blood count: Due to the possibility of benzene exposure associated with coal tar pitch volatiles, a complete blood count is considered necessary to search for leukemia and aplastic anemia.

—Skin disease: Coal tar pitch volatiles are defatting agents and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of these agents.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, and semi-annually for employees 45 years of age or older or with 10 or more years' exposure to coal tar pitch volatiles.

• **Summary of toxicology**

Coal tar pitch volatiles (CTPV) are products of the destructive distillation of bituminous coal and contain polynuclear aromatic hydrocarbons (PNA's). These hydrocarbons sublime readily, thereby increasing the amounts of carcinogenic compounds in working areas. Epidemiologic evidence suggests that workers intimately exposed to the products of combustion or distillation of bituminous coal are at increased risk of cancer at many sites. These include cancer of the respiratory tract, kidney, bladder, and skin. In a study of coke oven workers, the level of exposure to CTPV and the length of time exposed were related to the development of cancer. Coke oven workers with the highest risk of cancer were those employed exclusively at topside jobs for 5 or more years, for whom the increased risk of dying from lung cancer was 10-fold; all coke oven workers had a 7-½-fold increase in risk of dying from kidney cancer. Although the causative agent or agents of the cancer in coke oven workers is unidentified, it is suspected that several PNA's in the CTPV generated during the coking process are involved. Certain industrial populations exposed to coal tar products have a demonstrated risk of skin cancer. Substances containing PNA's which may produce skin cancer also produce contact dermatitis; examples are coal tar, pitch, and cutting oils. Although allergic dermatitis is readily induced by PNA's in guinea pigs, it is only rarely reported in humans from occupational contact with PNA's; these have resulted largely from the therapeutic use of coal tar preparations. Components of pitch and coal tar produce cutaneous photosensitization; skin eruptions are usually limited to areas exposed to the sun or ultraviolet light. Most of the phototoxic agents will induce hypermelanosis of the skin; if chronic photodermatitis is severe and prolonged, leukoderma may occur. Some oils containing PNA's have been associated with changes of follicular and sebaceous glands which commonly take the form of acne. There is evidence that exposures to emissions at coke ovens and gas retorts may be associated with an increased occurrence of chronic bronchitis. Coal tar pitch volatiles may be associated with benzene, an agent suspected of causing leukemia and known to cause aplastic anemia.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Anthracene**

1. Molecular weight: 178.2
2. Boiling point (760 mm Hg): 340 C (644 F)
3. Specific gravity (water = 1): 1.24
4. Vapor density (air = 1 at boiling point of anthracene): 6.15
5. Melting point: 217 C (423 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Phenanthrene**

1. Molecular weight: 178.2
2. Boiling point (760 mm Hg): 340 C (644 F)
3. Specific gravity (water = 1): 1.18
4. Vapor density (air = 1 at boiling point of phenanthrene): 6.15
5. Melting point: 100.5 C (213 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Pyrene**

1. Molecular weight: 202.3
2. Boiling point (760 mm Hg): Greater than 360 C (greater than 680 F)

3. Specific gravity (water = 1): 1.28
4. Vapor density (air = 1 at boiling point of pyrene): 6.9
5. Melting point: 150.4 C (303 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• Physical data—Carbazole
1. Molecular weight: 167.2
2. Boiling point (760 mm Hg): 355 C (671 F)
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of carbazole): 5.8
5. Melting point: 246 C (475 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• Physical data—Benzo(a)pyrene
1. Molecular weight: 252.3
2. Boiling point (760 mm Hg): Greater than 360 C (greater than 680 F)
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of benzo(a)pyrene): 8.7
5. Melting point: 179 C (354 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• Reactivity
1. Conditions contributing to instability: None hazardous
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: None
4. Special precautions: None

• Flammability
1. Flash point: Anthracene: 121 C (250 F) (closed cup); Others: Data not available
2. Autoignition temperature: Anthracene: 540 C (1004 F); Others: Data not available
3. Flammable limits in air, % by volume: Anthracene: Lower: 0.6; Others: Data not available
4. Extinguishant: Foam, dry chemical, and carbon dioxide

• Warning properties

Grant states that "coal tar and its various crude fractions appear principally to cause reddening and squamous eczema of the lid margins, with only small erosions of the corneal epithelium and superficial changes in the stroma, which disappear in a month following exposure. Chronic exposure of workmen to tar fumes and dust has been reported to cause conjunctivitis and discoloration of the cornea in the palpebral fissure, either near the limbus or, in extreme cases, across the whole cornea. Occasionally, epithelioma of the lid margin has been attributed to contact with coal tar."

MONITORING AND MEASUREMENT PROCEDURES

• General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Method

Coal tar products may be sampled by collection on a glass fiber filter with subsequent ultrasonic extraction and weighing. An analytical method for coal tar pitch volatiles is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 1, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00267-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with condensed coal tar pitch volatiles, where skin contact may occur.

• If employees' clothing may have become contaminated with coal tar pitch volatiles, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with coal tar pitch volatiles

should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of coal tar pitch volatiles from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the coal tar pitch volatiles, the person performing the operation should be informed of coal tar pitch volatiles's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where condensed coal tar pitch volatiles may contact the eyes.

SANITATION

• Workers subject to skin contact with coal tar pitch volatiles should wash with soap or mild detergent and water any areas of the body which may have contacted coal tar pitch volatiles at the end of each work day.

• Employees who handle coal tar pitch volatiles should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

• Areas in which exposure to coal tar pitch volatiles may occur should be identified by signs or other appropriate means, and access to these areas should be limited to authorized persons.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to coal tar pitch volatiles may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from extraction and packaging from coal tar fraction of coking	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a binding agent in manufacture of coal briquettes used for fuel; use as a dielectric in the manufacture of battery electrodes, electric-arc furnace electrodes, and electrodes for alumina reduction	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of roofing felts and papers and roofing	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use for protective coatings for pipes for underground conduits and drainage; use as a coating on concrete as waterproofing and corrosion-resistant material; use in road paving and sealing	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture and repair of refractory brick; use in production of foundry cores; use in manufacture of carbon ceramic items	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If condensed coal tar pitch volatiles get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If condensed coal tar pitch volatiles get on the skin, wash the contaminated skin using soap or mild detergent and water. Be sure to wash the hands before eating or smoking and to wash thoroughly at the close of work.

• **Breathing**

If a person breathes in large amounts of coal tar pitch volatiles, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.

• If coal tar pitch volatiles are released in hazardous concentrations, the following steps should be taken:

1. Ventilate area of spill.

2. Collect released material in the most convenient and safe manner for reclamation or for disposal in sealed containers in a secured sanitary landfill.

• Waste disposal method:

Coal tar pitch volatiles may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Coal Tar Pitch Volatiles," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Bingham, E.: "Environmental Carcinogens," *Archives of Environmental Health*, 19:779-85, DES 1969.

• Bingham, E.: "Thresholds in Cancer Inductions," *Archives of Environmental Health*, 22:692-95, June 1971.

• "Coke Oven Emissions," *Federal Register*, 40:32268-32282, July 31, 1975.

• Committee on Biologic Effects of Atmospheric Pollutants, Division of Medical Sciences, National Research Council: *Particulate Polycyclic Organic Matter*, National Academy of Sciences, Washington, D.C., 1972.

• Fannick, N., et al.: "Exposure to Coal Tar Pitch Volatiles at Coke Ovens," *American Industrial Hygiene Association Journal*, 33:461-468, 1972.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hittle, D. C., and Stukel, J. J.: "Particle Size Distribution and Chemical Composition of Coal-Tar Fumes," *American Industrial Hygiene Association Journal*, 37:199-204, 1976.

• *Hygienic Information Guide No. 89 - Coal Tar Pitch Volatiles*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1972.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Lloyd, J. W.: "Long-Term Mortality Study of Steelworkers. V. Respiratory Cancer in Coke Plant Workers," *Journal of Occupational Medicine*, 13:53-68, 1971.

• Mazumdar, S., et al.: "An Epidemiological Study of Exposure to Coal Tar Pitch Volatiles among Coke Oven Workers," *Journal of the Air Pollution Control Association*, 25:382-389, 1975.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Coal Tar P ducts*, HEW Publication No. (NIOSH) 78-107, U.S. Government Printing Office, Washington, D.C., 1977.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Coke Oven Emissions*, HEW Publication No. HSM 73-11016, GPO No. 017-033-00015, U.S. Government Printing Office, Washington, D.C., 1973.

• Redmond, C. K., et al.: "Long-Term Mortality Study of Steelworkers. VI. Mortality from Malignant Neoplasms Among Coke Oven Workers," *Journal of Occupational Medicine*, 14:621-629, 1972.

• Scala, R. A.: "Toxicology of PPOM," *Journal of Occupational Medicine*, 17:784-788, 1975.

• Tye, R., and Stemmer, K. L.: "Experimental Carcinogenesis of the Lung. II. Influence of Phenols in the Production of Carcinoma," *Journal of the National Cancer Institute*, 39:175-179, 1967.

RESPIRATORY PROTECTION FOR COAL TAR PITCH VOLATILES

Condition	Minimum Respiratory Protection* Required Above 0.2 mg/m³
Particulate and Vapor Concentration	
2 mg/m³ or less	A chemical cartridge respirator with an organic vapor cartridge(s) and with a fume or high-efficiency filter. Any supplied-air respirator. Any self-contained breathing apparatus.
10 mg/m³ or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s) and with a fume or high-efficiency filter. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and with a full facepiece and a fume or high-efficiency filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode. A powered air-purifying respirator with an organic vapor cartridge and a high-efficiency particulate filter.
400 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 400 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Cobalt Metal Fume and Dust

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formulas of example compounds: Co/CoO/Co_2O_3/Co_3O_4
- Synonyms: None
- Appearance and odor: Odorless black solid or finely divided particulate dispersed in air.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cobalt metal fume and dust is 0.1 milligram of cobalt metal fume and dust per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for cobalt metal fume and dust a Threshold Limit Value of 0.05 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cobalt metal fume and dust can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

Cobalt metal fume and dust cause irritation of the nose and throat. They have also been reported to cause respiratory disease with symptoms ranging from cough and shortness of breath to permanent disability and death. The symptoms frequently go away when exposure is stopped, but sometimes the symptoms progress after exposure has ceased. Exposure to cobalt may cause an allergic skin rash.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cobalt metal fume and dust.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to cobalt metal fume and dust at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Cobalt may cause human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Cobalt is reported to decrease pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Cobalt metal fume and dust cause upper respiratory tract irritation, chronic interstitial pneumonitis, and skin sensitization. Rhabdomyosarcomata developed in rats injected intramuscularly with the powder of either pure cobalt metal or cobalt oxide. Animals were exposed to the repeated inhalation of the cobalt metal blend used by the cemented carbide industry: a concentration of 20 mg/m^3 of cobalt for 3 years produced hyperplasia of the bronchial epithelium and focal fibrotic lesions of the lungs with developing granulomata; daily inhalation of cobalt metal fume composed of approximately equal parts of cobalt, cobalt oxide, and cobaltic-cobaltous

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Con.
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

oxide did not elicit these reactions. Guinea pigs developed acute pneumonitis, often rapidly fatal, from the intratracheal injection of cobalt metal or repeated inhalation of a mixture of 75% tungsten carbide and 25% cobalt. Chronic interstitial pneumonitis has been reported in workers in the cemented carbide industry, and cobalt has been conditionally implicated as the etiologic agent by a process of elimination of the other materials used in the industry. Symptoms range from shortness of breath, cough, and dyspnea on exertion to permanent disability or death in some cases. Among 12 workers exposed to cobalt engaged in manufacture of, or grinding with, tungsten carbide tools, who developed interstitial lung disease, there were 8 fatalities; serial chest roentgenograms over a period of 3 to 12 years revealed gradually progressive densities of a linear and nodular nature which gradually involved major portions of both lungs; cough, dyspnea on exertion, and reduced pulmonary function occurred early in the course of the disease. The disease has features of hypersensitivity; only a small percentage of people exposed are affected and with little evidence of dose-response relationship. Cobalt and its compounds produce an allergic dermatitis of an erythematous papular type, which usually occurs in skin areas subjected to friction, such as the ankles, elbow flexures, and sides of the neck.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 58.93 to 181.9
  2. Boiling point (760 mm Hg): 3100 C (5612 F)
  3. Specific gravity (water = 1): 8.8
  4. Vapor density (air = 1 at boiling point of cobalt metal fume and dust): Not applicable
  5. Melting point: 1491 C (2715 F)
  6. Vapor pressure at 20 C (68 F): 0 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact of dust with strong oxidizers may cause fire and explosions.
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Flash point: Not applicable
  2. Autoignition temperature: Specially prepared (the form prepared by reducing the oxides in hydrogen) very fine cobalt dust will catch fire at room temperature in air.
  3. Flammable limits in air, % by volume: Not applicable
  4. Extinguishant: Dry sand, dry dolomite, dry graphite powder
- **Warning properties**

The AIHA *Hygienic Guide* states that "cobalt appears to be an eye irritant. One of the findings in the study of the tungsten carbide industry was a significant amount of conjunctivitis, presumably caused by the cobalt used as 'cement'." Contact with industry has indicated that workers in the cobalt-cemented tungsten industry have not experienced eye irritation to cobalt below 1 mg/m³.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of cobalt metal fume and dust on a cellulose membrane filter, followed by treatment with nitric acid, solution in acid, and analysis with an atomic absorption spectrophotometer. An analytical method for cobalt metal fume and dust is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 1, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00267-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact

with cobalt dust.

• If employees' clothing may have become contaminated with cobalt dust, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with cobalt dust should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of cobalt dust from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the cobalt dust, the person performing the operation should be informed of cobalt dust's hazardous properties.

• Non-impervious clothing which becomes contaminated with cobalt dust should be removed promptly and not reworn until the cobalt dust is removed from the clothing.

SANITATION

• Skin that becomes contaminated with cobalt dust should be promptly washed or showered with soap or mild detergent and water to remove any cobalt dust.

• Eating and smoking should not be permitted in areas where cobalt metal fume or dust are generated, handled, processed, or stored.

• Employees who handle cobalt metal fume or dust should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cobalt metal fume and dust may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during use as a binder in manufacture of cemented carbide items; during refining and concentration of ores; during preparation of alloys	Local exhaust ventilation; personal protective equipment
Liberation during manufacture of metal items from magnetic alloy; during manufacture of metal items from super- and high-temperature alloys	Local exhaust ventilation; personal protective equipment
Liberation during grinding and sharpening of cemented carbide and steel tools; during synthesis of cobalt compounds for use as pigments and as catalysts and driers; during refining and concentrations of ores	Local exhaust ventilation; personal protective equipment
Liberation during manufacture of metal items from cutting tool and tool steels; during manufacture of metal items from hard-facing alloys; during manufacture of items containing low-expansion alloys; during manufacture of metal items containing constant-modulus alloys; metal to glass seals in electric lamps, vacuum tubes, and x-ray tubes	Local exhaust ventilation; personal protective equipment
Liberation during manufacture of dental prosthetic and osteosynthetic items; during asbestos fiber processing	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If cobalt metal dust gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If cobalt metal dust get on the skin, wash the contaminated skin using soap or mild detergent and water. If cobalt metal dust penetrates through the clothing, remove the clothing and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If person breathes in large amounts of cobalt metal fume or dust, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respi-

ration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When cobalt metal dust has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or releases until cleanup has been completed.

• If cobalt dust is spilled or if potentially hazardous amounts of cobalt metal fume are inadvertently released, the following steps should be taken:

1. Ventilate area of spill.
2. Collect released material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Cobalt dust may be placed in sealed containers and disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Cobalt (Metal Dust and Fume) as Co," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Cobalt (Except the Carbonyls)," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Coates, E. O., and Watson, J. H. L.: "Diffuse Interstitial Lung Disease in Tungsten Carbide Workers," *Annof Internal Medicine*, 75:709-716, 1971.

• Delahant, A. B.: "An Experimental Study of the Effects of Rare Metals on Animal Lungs," *A.M.A. Archives of Industrial Health*, 12:116-120, 1955.

• Gilman, J. P. W., and Ruckerbauer, G. M.: "Metal Carcinogenesis - I. Observations on the Carcinogenicity of a Refinery Dust, Cobalt Oxide, and Colloidal Thorium Dioxide," *Cancer Research*, 22:152-157, 1962.

• Heath, J. C.: "The Histogenesis of Malignant Tumours Induced by Cobalt in the Rat," *British Journal of Cancer*, 14:478-482, 1960.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Miller, C. W., et al.: "Pneumoconiosis in the Tungsten-Carbide Tool Industry," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 8:453-465, 1953.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR COBALT METAL FUME AND DUST

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
0.5 mg/m³ or less	Any dust and mist respirator, except single-use.
1.0 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator.
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
20 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 20 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator with a full facepiece. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Copper Dusts and Mists

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formulas of example compounds: $CuSO_4 \cdot 5H_2O$; CuCl
- Example compounds: Copper sulfate dust or mist; cuprous chloride dust
- Appearance and odor: Odorless solids

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for copper dusts or mists is 1 milligram of copper dusts or mists per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Copper dusts or mists can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Powdered copper or dusts or mists of copper salts may cause a feeling of illness similar to the common cold with sensations of chills and stuffiness of the head. Small copper particles may enter the eye and cause irritation, discoloration, and damage.

2. Long-term Exposure: Repeated or prolonged exposure to copper dusts or mists may cause skin irritation or discoloration of the skin or hair.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to copper dusts or mists.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to copper dusts and mists at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from copper dusts and mists exposure.

—Chronic respiratory disease: Copper dusts or mists cause respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of copper dusts or mists might cause exacerbation of symptoms due to their irritant properties.

—Liver disease: Copper dusts or mists cause liver damage in animals. Persons with pre-existing liver disease may be more susceptible to the effects of these agents.

—Kidney disease: Copper dusts or mists cause kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: Skin sensitization in human subjects has occurred. Persons with pre-existing skin disorders may be more susceptible to the effects of these agents.

—Hematopoietic disorders: Anemia has occurred in animals given copper salts orally. Persons with pre-existing blood disorders may be more susceptible to the effects of these agents.

—Wilson's disease: Persons with pre-existing Wilson's disease may be more susceptible to the effects of these agents.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Inhalation of dusts and mists of copper and copper salts results in irritation of the upper respiratory tract, with occasional ulceration and perforation of the nasal septum. Inhalation of copper and its compounds by animals caused injury to the lungs and liver with

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

hemochromatosis. Access of sheep to salt licks containing 5 to 9% copper sulfate caused the sudden onset of hemolytic anemia, icterus, and hemoglobinuria followed by death in a day or two; at necropsy, the liver, kidneys, and spleen showed severe degenerative changes. Workers exposed to copper dust in concentrations of 0.075 to 0.120 mg/m^3 complained of mild nasal discomfort. Exposure to the dust of copper acetate produced sneezing, coughing, digestive disorders, and fever. Metal workers exposed to complex copper salts in dust form complained of metallic taste with irritation of nasal and oral mucosa; atrophic changes in the mucous membranes were noted in subjects exposed for long periods of time. On ingestion, copper salts act as irritants and cause nausea, vomiting, abdominal pain, hemorrhagic gastritis, and diarrhea. Copper salts splashed in the eye cause conjunctivitis, corneal ulceration, and turbidity, and may produce palpebral edema. Copper particles embedded in the eye result in pronounced foreign-body reaction with characteristic discoloration of ocular tissue. Allergic contact dermatitis due to copper exposure, although rare, has been reported. Greenish discoloration of the skin and hair of some copper workers has been observed. Although copper is an essential element for health, excessive amounts can produce harmful effects.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: $CuSO_4$: 249.7; $CuCl_2$: 99
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of copper dusts or mists): Not applicable
5. Melting point: Higher than 100 C (212 F). For example, copper sulfate = 150 C (302 F); cuprous chloride = 430 C (806 F)
6. Vapor pressure at 20 C (68 F): Not applicable
7. Solubility in water, g/100 g water at 20 C (68 F): Ranges from very low (e.g. cuprous chloride = 0.006) to high (e.g. copper sulfate = 35)
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Extreme heat
2. Incompatibilities: Copper dusts or mists may react with acetylene gas to form copper acetylides, which are solids that are sensitive to shock. Some copper mists may react with magnesium metal to form flammable hydrogen gas.
3. Hazardous decomposition products: None
4. Special precautions: None

- **Flammability**

1. Ignition temperature: Copper dusts = 700 C (1292 F)

- **Warning properties**

According to Grant, copper acetoarsenite, copper chloride, copper sulfate, copper carbonate and oxide, and copper metal all produce local irritant effects when in contact with the eye. The *Documentation of TLV's* also notes that copper salts on the eye may cause "conjunctivitis or even ulceration and turbidity of the cornea." Concentrations producing these effects are not given.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of copper dusts or mists on a cellulose ester membrane filter, followed by treatment with nitric acid, solution in hydrochloric acid, and atomic absorption spectrophotometric analysis. An analytical method for copper dusts or mists is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with copper salts or liquids containing copper salts.

• If employees' clothing may have become contaminated with powdered copper, copper salts, or liquids containing copper salts, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with copper salts should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of copper salts from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the copper salts, the person performing the operation should be informed of copper salts's hazardous properties.

• Non-impervious clothing which becomes contaminated with copper salts should be removed promptly and not reworn until the copper salts are removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where powdered copper or dusts, mists, or liquids containing copper salts may contact the eyes.

SANITATION

• Skin that becomes contaminated with copper salts should be promptly washed or showered with soap or mild detergent and water to remove any copper salts.

• Eating and smoking should not be permitted in areas where powdered copper, copper salts, or liquids containing copper salts are handled, processed, or stored.

• Employees who handle powdered copper, copper salts, or liquids containing copper salts should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to copper dusts or mists may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during mining, extracting, and refining copper ore; during fabrication and manufacture of copper rod, wire, piping, and tubing for use in electrical, plumbing, and building industries; during manufacture of domestic utensils; during manufacture of alloys	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation from production and application of fungicides, insecticides, and germicides for soil, feed, grain, textile, water and sewage treatments; during use of copper salts for paint pigments and coloring agents, electroplating baths, wood preservation, automotive emission controls, textile treatment, and organic synthesis	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If copper dusts or mists get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If copper salts or liquids containing copper salts get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If copper salts or liquids containing copper salts penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of copper dusts or mists, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When powdered copper, copper salts, or liquids containing copper salts have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of release until cleanup has been completed.

• If copper dusts or mists are spilled or released, the following steps should be taken:

1. Ventilate area of release.
2. Collect spilled material in the most convenient and safe manner for reclamation, or for disposal in a secured sanitary landfill. Liquid containing copper should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Copper dusts or mists and copper compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Copper as Cu," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Askergren, A., and Mellgren, M.: "Changes in the Nasal Mucosa after Exposure to Copper Salt Dust, a Preliminary Report," *Scandinavian Journal of Work, Environment and Health*, 1:45-49, 1975.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Cohen, S. R.: "A Review of the Health Hazards from Copper Exposure," *Journal of Occupational Medicine*, 16:621-624, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, R. P.: "Exposure to Copper Dust," *American Industrial Hygiene Association Journal*, 29:461-462, 1968.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Saltzer, E. I., and Wilson, J. W.: "Allergic Contact Dermatitis Due to Copper," *Archives of Dermatology*, 98:375-376, 1968.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR COPPER DUSTS AND MISTS

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Copper Fume

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $Cu/Cu_2O/CuO$
- Synonyms: None
- Appearance: Finely divided particulate dispersed in air.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for copper fume is 0.1 milligram of copper fume per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for copper fume a Threshold Limit Value of 0.2 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Copper fume can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- ***Effects of overexposure***

1. Short-term Exposure: Copper fume causes irritation of the eyes, nose, and throat, and a flu-like illness called metal fume fever. Symptoms of metal fume fever include fever, muscle aches, nausea, chills, dry throat, cough, and weakness. It may also cause a metallic or sweet taste in the mouth.

2. Long-term Exposure: Repeated or prolonged exposure to copper fume may cause the skin and hair to change color.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to copper fume.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to copper fume at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from copper fume exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of copper fume might cause exacerbation of symptoms due to its irritant properties.

—Hepatolenticular degeneration (Wilson's disease): Persons with pre-existing Wilson's disease may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Inhalation of copper fume results in irritation of the upper respiratory tract and an influenza-like illness termed metal fume fever. Signs and symptoms of metal fume fever include chills, muscle aches, nausea, fever, dry throat, cough, weakness, and lassitude. There is usually leucocytosis, which may amount to 12,000 to 16,000/ml; recovery is usually rapid, and there are no sequelae. Most workers develop an immunity to these attacks, but it is quickly lost; attacks tend to be more severe on the first day of the work-week. Other effects from copper fume are irritation of the upper respiratory tract, metallic or sweet taste, and in some instances discoloration of the skin and hair. Exposure of workers to concentrations of 1 to 3 mg/m^3 for short periods resulted in altered taste response but no nausea; levels of from 0.02 to 0.4 mg/m^3 produced no complaints. Transient irritation of the eyes has followed exposure to a

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

fine dust of oxidation products of copper produced in an electric arc.

CHEMICAL AND PHYSICAL PROPERTIES

- Physical data
  1. Molecular weight: 63.5 to 143.1
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): Not applicable
  4. Vapor density (air = 1 at boiling point of copper fume): Not applicable
  5. Melting point: Not applicable
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- Reactivity
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with acetylene gas may cause formation of copper acetylides that are sensitive to shock.
  3. Hazardous decomposition products: None
  4. Special precautions: None
- Flammability
  1. Not applicable
- Warning properties

Copper fume is not known to be a significant eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- Method

Sampling and analyses may be performed by collection of copper fume on a cellulose membrane filter, followed by treatment with nitric acid, solution in acid, and analysis with an atomic absorption spectrophotometer. An analytical method for copper fume is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to copper fume may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during construction and installation of materials fabricated from copper metal or copper alloys; during copper metal processing of castings, sheets, rods, tubing, and wire; during copper metal smelting and refining operations	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- Breathing

If a person breathes in large amounts of copper fume, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.
- If potentially hazardous amounts of copper fume are inadvertently released, ventilate the area of the release to disperse the fume.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Copper as Cu," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.
- Cohen, S. R.: "A Review of the Health Hazards from Copper Exposure," *Journal of Occupational Medicine*, 16:621-624, 1974.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois., 1974.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR COPPER FUME

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
1 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Crag Herbicide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $2,4\text{-}Cl_2C_6H_3OC_2H_4OSO_3Na$
- Synonyms: Sesone; Crag herbicide No. 1; sodium 2-(2,4-dichlorophenoxy)ethyl sulfate
- Appearance and odor: Colorless solid with no odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Crag herbicide is 15 milligrams of Crag herbicide per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for Crag herbicide a Threshold Limit Value of 10 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Crag herbicide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Animal experiments have shown that exposure to Crag herbicide may cause tremors, muscle spasms, and convulsions. It has also caused congestion of the lungs, liver, and kidneys in animals. A solution of Crag herbicide dropped in animal eyes caused damage. The solution applied to animal skin has caused skin irritation and damage.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Crag herbicide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Crag herbicide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from Crag herbicide exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of Crag herbicide might cause exacerbation of symptoms since it causes pulmonary hemorrhage in animals at lethal doses.

—Liver disease: Crag herbicide causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Crag herbicide causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: Crag herbicide is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Convulsive disorders: Crag herbicide (Sesone) causes convulsions in animals. Persons with a history of such disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Crag herbicide (Sesone) dust affects the nervous system in animals and causes convulsions. In rats the oral LD50 ranged from 0.73 to 1.09 g/kg; effects were a fine

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

358

muscular tremor, myotonus, a tendency to extend the hind feet caudally, and convulsions. Autopsy findings in animals that died were pulmonary hemorrhage, with mild liver and kidney damage. A 5% aqueous solution dropped in the eye of a rabbit caused corneal necrosis. The application of 0.01 ml of a 5% suspension of Sesone in acetone to the shaved rabbit belly resulted in edema and necrosis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 309
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): Greater than 1
  4. Vapor density (air = 1 at boiling point of Crag herbicide): Not applicable
  5. Melting point: 170 C (338 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 25
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, sulfur dioxide, and carbon monoxide) may be released when Crag herbicide decomposes.
  4. Special precautions: None.
- **Flammability**
  1. Not combustible.
- **Warning properties**

Union Carbide Corporation, in the *Chemical Company Guide* for Crag herbicide, states that "flooding the rabbit eye with a saturated solution of the chemical in propylene glycol caused a reaction similar to moderate inflammation. The dry powder can be expected to have an additional mechanical irritant action."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for Crag herbicide is in the *NIOSH Manual of Analytical Methods*, 2nd. Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with Crag herbicide or liquids containing Crag herbicide.
- If employees' clothing may have become contaminated with Crag herbicide or liquids containing Crag herbicide, employees should change into uncontaminated clothing before leaving the work premises.
- Non-impervious clothing which becomes contaminated with Crag herbicide should be removed promptly and not reworn until the Crag herbicide is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where Crag herbicide or liquids containing Crag herbicide may contact the eyes.

SANITATION

- Skin that becomes contaminated with Crag herbicide should be promptly washed or showered to remove any Crag herbicide.
- Employees who handle Crag herbicide or liquids containing Crag herbicide should wash their hands thoroughly before eating, smoking, or using toilet facilities.
- Eating and smoking should not be permitted in areas where solid Crag herbicide is handled, processed, or stored.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Crag herbicide may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of weedicides in agricultural operations	Process enclosure; local exhaust ventilation; personal protective equipment
Application of weedicides in agricultural operations	Personal protective equipment
Manufacture of Crag herbicide	Process enclosure; local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If Crag herbicide or liquids containing Crag herbicide get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If Crag herbicide or liquids containing Crag herbicide get on the skin, promptly wash the contaminated skin with water. If Crag herbicide or liquids containing Crag herbicide penetrate through the clothing, remove the clothing promptly and wash the skin with water. If irritation is present after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of Crag herbicide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When Crag herbicide or liquids containing Crag herbicide have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If Crag herbicide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing Crag herbicide should be absorbed in vermiculite, dry sand, earth, or a similar material.

- Waste disposal method:

Crag herbicide may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Crag Herbicide (Sesone)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Carpenter, C. P., et al.: "Mammalian Toxicity of Sesone Herbicide," *Agricultural and Food Chemistry*, 9:382-385, 1961.
- Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
- Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.
- Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
- Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies* – Crag Herbicide (Sesone), New York, 1958.

RESPIRATORY PROTECTION FOR CRAG HERBICIDE

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Particulate Concentration	
75 mg/m³ or less	Any dust and mist respirator, except single-use.
150 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Crotonaldehyde

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CH=CHCHO$
- Synonyms: Beta-methylacrolein; propylene aldehyde; crotonic aldehyde; 2-butenal
- Appearance and odor: Colorless to straw-colored liquid with an irritating, pungent, and suffocating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for crotonaldehyde is 2 parts of crotonaldehyde per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 6 milligrams of crotonaldehyde per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Crotonaldehyde can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Crotonaldehyde causes irritation of the eyes, nose, and throat. It may also cause an irritation of the skin and difficulty in breathing which may occur several hours after exposure.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to crotonaldehyde.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to crotonaldehyde at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from crotonaldehyde exposure.

—Chronic respiratory disease: Crotonaldehyde causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of crotonaldehyde might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Crotonaldehyde is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Crotonaldehyde vapor irritates the eyes and respiratory tract. Rats did not survive exposure to 1650 ppm for 10 minutes; there was respiratory distress, an excitatory stage, and terminal convulsions; autopsy revealed bronchiolar damage. Pulmonary edema has also been observed in rats dead of exposure to 1500 ppm for 30 minutes. Human subjects exposed to 45 ppm for a few seconds experienced conjunctival irritation; at 15 ppm there was no eye discomfort. The liquid when placed in the eyes of rabbits caused severe injury. In a series of eight cases of corneal injury from industrial exposure to crotonaldehyde, healing was complete in 48 hours; the severity of exposure was not specified. A case of apparent sensitization of undetermined nature to crotonaldehyde has been reported in a laboratory worker.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 70.1

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

2. Boiling point (760 mm Hg): 102 C (216 F)
3. Specific gravity (water = 1): 0.85
4. Vapor density (air = 1 at boiling point of crotonaldehyde): 2.4
5. Melting point: −75 C (−103 F)
6. Vapor pressure at 20 C (68 F): 30 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 15.5
8. Evaporation rate (butyl acetate = 1): 2.7

• **Reactivity**

1. Conditions contributing to instability: Heat may cause polymerization to occur and containers to burst.
2. Incompatibilities: Contact with caustics, ammonia, organic amines, and mineral acids may cause violent polymerization to occur. Contact with strong oxidizers may cause fires and explosions. Crotonaldehyde is readily converted by oxygen to peroxides and acids.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving crotonaldehyde.
4. Special precautions: Liquid crotonaldehyde will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 12.8 C (55 F) (closed cup)
2. Autoignition temperature: 232 C (450 F)
3. Flammable limits in air, % by volume: Lower: 2.1; Upper: 15.5
4. Extinguishant: Carbon dioxide, dry chemical, alcohol foam

• **Warning properties**

1. Odor Threshold: Stern and May report odor thresholds for crotonaldehyde of 0.062 and 0.035 ppm, respectively.
2. Eye Irritation Level: Both Grant and the *Documentation of TLV's* report that "humans have experienced "considerable eye discomfort" at 45 ppm for a brief exposure (a few seconds). Humans did not experience eye irritation during an exposure of a few seconds to 15 ppm. The threshold of eye irritation is not given, however.
3. Other Information: According to the *Documentation of TLV's*, crotonaldehyde is also a respiratory tract irritant. The threshold limit was recommended "to prevent irritation of eyes and respiratory passages."
4. Evaluation of Warning Properties: Since the odor threshold of crotonaldehyde is below the permissible exposure limit, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for crotonaldehyde is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid crotonaldehyde or liquids containing crotonaldehyde, where skin contact may occur.

• Clothing wet with liquid crotonaldehyde or liquids containing crotonaldehyde should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of crotonaldehyde from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the crotonaldehyde, the person performing the operation should be informed of crotonaldehyde's hazardous properties.

• Where exposure of an employee's body to liquid crotonaldehyde or liquids containing crotonaldehyde may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Any clothing which becomes wet with and non-impervious clothing which becomes contaminated with crotonaldehyde should be removed immediately and not reworn until the crotonaldehyde is removed from the clothing.

• Employees should be provided with and required to

use splash-proof safety goggles where there is any possibility of liquid crotonaldehyde or liquids containing crotonaldehyde contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid crotonaldehyde or liquids containing more than 1% of crotonaldehyde by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with crotonaldehyde should be immediately washed or showered to remove any crotonaldehyde.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to crotonaldehyde may occur and control methods which may be effective in each case:

Operation	Controls
Use an an intermdediate in manufacture of butyl alcohol; use in polymer technology as a reaction medium, formulator, adhesive, antioxidant, corrosion inhibitor, and stabilizer	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis in manufacture of dyestuffs, sedatives, pesticides, and flavoring agents	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent for purification of mineral and lubricating oils; use during manufacture of surface active agents as bactericides for petroleum well fluids, metal brighteners, and leather/paper sizing materials	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during manufacture as warning agent in fuel gases for locating breaks and leaks in pipes; use in leather tanning and preparation of tanning materials	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of rubber and rubber antioxidants and accelerators; use in manufacture of chemical warfare agents; use in photographic emulsion as a hardening agent for gelatin	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid crotonaldehyde or liquids containing crotonaldehyde get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid crotonaldehyde or liquids containing crotonaldehyde get on the skin, immediately flush the contaminated skin with water. If liquid crotonaldehyde or liquids containing crotonaldehyde soak through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of crotonaldehyde, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When crotonaldehyde has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If crotonaldehyde or liquids containing crotonaldehyde are spilled or leaked, the following steps should be take

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. Liquid crotonaldehyde should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of crotonaldehyde vapors are permitted.

• Waste disposal method:

Crotonaldehyde may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Crotonaldehyde (beta-Methyl Acrolein)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Henson, E. V.: "The Toxicology of Some Aliphatic Aldehydes," *Journal of Occupational Medicine*, pp. 457-461, August 1959.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Rinehart, W. E.: "The Effect on Rats of Single Exposures to Crotonaldehyde Vapor," *American Industrial Hygiene Association Journal*, 28:561-566, 1967.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Smyth, H. F., and Carpenter, C. P.: "The Place of the Range-Finding Test in the Industrial Toxicology Laboratory," *Journal of Industrial Hygiene and Toxicology*, 26:8, pp. 269-73, 1944.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List III," *Journal of Industrial Hygiene and Toxicology*, 31:1, pp. 60-62, 1949.

• Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Chemical Company Guide – Crotonaldehyde*, New York, 1967.

RESPIRATORY PROTECTION FOR CROTONALDEHYDE

Condition	Minimum Respiratory Protection* Required Above 2 ppm
Vapor Concentration	
100 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
400 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 400 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Cumene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5C_3H_7$
- Synonyms: Isopropylbenzene; 2-phenylpropane; cumol
- Appearance and odor: Colorless liquid with a sharp, penetrating, and aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cumene is 50 parts of cumene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 245 milligrams of cumene per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cumene can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Cumene may cause irritation of the skin and eyes. It may also cause dizziness, drowsiness, slight incoordination, and unconsciousness.

2. Long-term Exposure: Prolonged or repeated exposure to cumene may cause skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cumene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to cumene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from cumene exposure.

—Kidney disease: Although cumene is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of cumene might cause exacerbation of symptoms due to its irritant properties or pyschic reflex bronchospasm.

—Liver disease: Although cumene is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Skin disease: Cumene is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The main toxic effect of cumene is irritation of the eyes, skin, and upper respiratory tract. Narcosis has been reported to occur in animals on high exposure. There are no reports of systemic effects in man as a result of industrial exposure. Chronic exposure of rats above 500 ppm causes congestion of lungs, liver, and kidneys, but no bone marrow changes.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 120
  2. Boiling point (760 mm Hg): 152 C (306 F)
  3. Specific gravity (water = 1): 0.86
  4. Vapor density (air = 1 at boiling point of cumene): 4.14
  5. Melting point: −96 C (−141 F)
  6. Vapor pressure at 20 C (68 F): 8 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Very low
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving cumene.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 44 C (111 F) (closed cup)
  2. Autoignition temperature: 425 C (797 F)
  3. Flammable limits in air, % by volume: Lower: 0.9; Upper: 6.5
  4. Extinguishant: Water spray, dry chemical, foam, carbon dioxide
- **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* and the ILO both report that the odor of cumene is detectable at very low levels. May reports an odor threshold for cumene of 1.2 ppm.

2. Eye Irritation Level: The *Documentation of TLV's* notes that cumene is an eye irritant, but the concentrations producing irritation are not given.

3. Evaluation of Warning Properties: Since the odor threshold of cumene is below the permissible exposure limit, cumene is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of cumene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure cumene may be used. An analytical method for cumene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid cumene.
- Clothing wet with liquid cumene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of cumene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the cumene, the person performing the operation should be informed of cumene's hazardous properties.
- Non-impervious clothing which becomes wet with liquid cumene should be removed promptly and not reworn until the cumene is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid cumene may contact the eyes.

SANITATION

- Skin that becomes wet with liquid cumene should be promptly washed or showered with soap or mild detergent and water to remove any cumene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cumene may occur and control methods which may be effective in each case:

Operation	Controls
Use during organic synthesis, particularly the cumene route to phenol and 2-methyl styrene	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a constituent of solvents in 150 to 160 C boiling point; use during application of lacquers, paints, and enamels as thinner	General dilution ventilation; personal protective equipment
Use in petroleum distillates either alone or in solvent formulation and surface coating processes	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during mixing and blending of fuels, especially aviation	General dilution ventilation; personal protective equipment
Liberation during petroleum refining processes; during production of styrene by cracking	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If cumene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If cumene gets on the skin, promptly flush the contaminated skin with water. If cumene soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of cumene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If cumene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If cumene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Combustion may be improved by mixing with a flammable liquid. Cumene liquid should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Cumene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber. Combustion may be improved by mixing with a flammable liquid.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Cumene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Cumene," *Hygienic Guide Series*, Detroit, Michigan, 1958.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Gulf Oil Corporation: *Material Safety Data Sheet – Cumene*, Pittsburgh, Pennsylvania, March 1971.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
• Wolf, M. A., et al.: "Toxicological Studies of Certain Alkylated Benzenes and Benzene," *A.M.A. Archives of Industrial Health*, 14:4, pp 387-399, 1956.

RESPIRATORY PROTECTION FOR CUMENE

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
500 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).** Any supplied-air respirator.** Any self-contained breathing apparatus.**
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
8000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs at this level, a full facepiece respirator should be worn.

Occupational Health Guideline for Cyanide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all cyanides. Physical and chemical properties of two specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Potassium cyanide

- Formula: KCN
- Synonyms: None
- Appearance and odor: White solid with a faint almond odor.

Sodium cyanide

- Formula: NaCN
- Synonyms: None
- Appearance and odor: White solid with a faint almond odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cyanide is 5 milligrams of cyanide per cubic meter of air (mg/m³) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be changed to a ceiling of 5 milligrams cyanide per cubic meter of air averaged over a 10-minute period. The NIOSH Criteria Document for Hydrogen Cyanide and Cyanide Salts should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cyanide can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. Sufficient cyanide may be absorbed through the skin, especially if there are cuts to cause fatal poisoning.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation or ingestion of cyanide salts may be rapidly fatal. Larger doses by inhalation or swallowing may cause the person to rapidly lose consciousness, stop breathing, and die. In some cases, there are convulsions. At lower levels of exposure, the earlier symptoms include weakness, headache, confusion, nausea, and vomiting. These symptoms may be followed by unconsciousness and death. Occasionally, convulsions occur. Milder forms of intoxication may result only in weakness, dizziness, headache, and nausea. The dust of cyanide salts is irritating to the eyes. In the presence of tears, it may cause the symptoms of poisoning described above. The dust of cyanide salts may produce irritation of the nose and skin. Strong solutions of cyanide salts are corrosive and may produce ulcers.

2. Long-term Exposure: Effects from chronic exposure to cyanide are non-specific and rare.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cyanide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to cyanide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of fainting spells, such as occur in various types of cardiovascular and nervous disorders,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

and those unusually susceptible to effects of anoxia or with anemia would be expected to be at increased risk from exposure. Examination of the cardiovascular, nervous, and upper respiratory systems, and thyroid should be stressed. The skin should be examined for evidence of chronic disorders.

—Skin disease: Cyanide is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—14" x 17" chest roentgenogram: Cyanide causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Cyanide is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

3. First Aid Kits: First aid kits should be readily available in workplaces where there is a potential for the release of cyanide. These kits should contain a minimum of 48 ampules, each of 0.3 ml amyl nitrate, and complete instructions for use. In addition, 2 physician's kits should be immediately available to trained medical personnel. These kits should contain the above quantity of amyl nitrate as well as sterile sodium nitrite solution (3%) and sterile sodium thiosulfate solution (25%). All of the above drugs should be replaced at least biannually to ensure their potency.

• **Summary of toxicology**

The dust of cyanide salts, a source of cyanide ion, is an asphyxiant due to an inhibitory action on metabolic enzyme systems and can be rapidly fatal. Cyanide exerts this effect because it inactivates certain enzymes by forming very stable complexes with the metal in them. Cytochrome oxidase is probably the most important of these, since it occupies a fundamental position in the respiratory process and is involved in the ultimate electron transfer to molecular oxygen. Since cytochrome oxidase is present in practically all cells that function under aerobic conditions, and since the cyanide ion diffuses easily to all parts of the body, it is capable of suddenly bringing to a halt practically all cellular respiration. In the presence of even weak acids, hydrocyanic acid (HCN) gas is liberated from cyanide salts; a few inhalations of higher concentrations of HCN may be followed by almost instantaneous collapse and cessation of respiration; 270 ppm HCN is immediately fatal to humans, 181 ppm is fatal after 10 minutes, 135 ppm after 30 minutes, and 110 ppm may be fatal in 1 hour. The ingestion by humans of 50 to 100 mg of sodium or potassium cyanide may also be fatal. At lower levels of exposure to HCN, the earliest symptoms of intoxication may include weakness, headache, confusion, and occasionally nausea and vomiting; respiratory rate and depth is usually increased initially and at later stages becomes slow and gasping; if cyanosis is present, it usually indicates that respiration has either ceased or has been very inadequate for a few minutes. Humans tolerate 45 to 54 ppm for ½ to 1 hour without immediate or delayed effects, while 18 to 36 ppm may result in some symptoms after an exposure of several hours. Sodium cyanide dust is irritating to the eyes; in the presence of tears it may liberate HCN, which can be absorbed and cause systemic intoxication. Skin contact with dust may be irritating; strong solutions on the skin produce ulcers which are slow in healing. Cyanide is one of the few toxic materials for which an antidote exists; it functions as follows: First, amyl nitrite (inhalation) and sodium nitrite (intravenously) are administered to form methemoglobin, which binds firmly with free cyanide ions. This traps any circulating cyanide ions. The formation of 10 to 20% methemoglobin usually does not involve appreciable risk, yet provides a large amount of cyanide-binding substance. Second, sodium thiosulfate is administered intravenously to increase the rate of conversion of cyanide to the less toxic thiocyanate. Methylene blue should not be administered, because it is a poor methemoglobin former and, moreover, promotes the conversion of methemoglobin back to hemoglobin.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Potassium cyanide**

1. Molecular weight: 65.1
2. Boiling point (760 mm Hg): Data not available
3. Specific gravity (water = 1): 1.55
4. Vapor density (air = 1 at boiling point of potassium cyanide): Not applicable
5. Melting point: 635 C (1175 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 71.6
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Sodium cyanide**

1. Molecular weight: 49
2. Boiling point (760 mm Hg): 1500 C (2732 F) (extrapolated)
3. Specific gravity (water = 1): 1.6
4. Vapor density (air = 1 at boiling point of sodium cyanide): Not applicable
5. Melting point: 560 C (1040 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 58
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None. Hazardous if kept in closed containers. It may form toxic concentrations of hydrogen cyanide gas when in prolonged contact with air in a closed area.
2. Incompatibilities: Contact with strong oxidizers such as nitrates and chlorates may cause fires and

explosions. Contact with acids and acid salts causes immediate formation of toxic and flammable hydrogen cyanide gas.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen cyanide and carbon monoxide) may be released when cyanide decomposes.

4. Special precautions: Cyanide may react with carbon dioxide in ordinary air to form toxic hydrogen cyanide gas.

- Flammability

1. Not combustible

- Warning properties

1. Odor Threshold: No quantitative information is available concerning the odor threshold of sodium or potassium cyanide. HCN, however, is evolved from these substances in the presence of moisture. The Manufacturing Chemists Association states that "although HCN has a characteristic odor, its toxic action at hazardous concentrations is so rapid that it is of no value as a warning property."

2. Eye Irritation Level: Cyanide (as CN) is not known to be an eye irritant. However, according to Grant, HCN can produce eye irritation after chronic exposures.

3. Evaluation of Warning Properties: Although cyanide (as CN) has a negligible vapor pressure, in the presence of moisture HCN can be given off. HCN does not have adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of cyanide. Each measurement should consist of a ten (10) minute sample or series of consecutive samples totalling ten (10) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of cyanide with a cellulose membrane filter and an impinger containing sodium hydroxide, followed by analysis by direct potentiometry. An analytical method for cyanide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with cyanide or liquids containing cyanide.
- If employees' clothing has had any possibility of being contaminated with cyanide, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing which has had any possibility of being contaminated with cyanide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of cyanide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the cyanide, the person performing the operation should be informed of cyanide's hazardous properties.
- Where there is any possibility of exposure of an employee's body to cyanide or liquids containing cyanide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with cyanide should be removed immediately and not reworn until the cyanide is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of cyanide or liquids containing cyanide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to cyanide or liquids containing cyanide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with cyanide should be immediately washed or showered with soap or mild detergent and water to remove any cyanide.
• Workers subject to skin contact with cyanide should wash with soap or mild detergent and water any areas of the body which may have contacted cyanide at the end of each work day.
• Eating and smoking should not be permitted in areas where cyanide or liquids containing cyanide are handled, processed, or stored.
• Employees who handle cyanide or liquids containing cyanide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cyanide may occur and control methods which may be effective in each case:

Operation	Controls
Use as fumigants and pesticides in greenhouses, ships, mills, and warehouses; use of cyanogen chloride as a warning agent in fumigant gases	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in metal treatment in nitriding, tempering, and case hardening steel; coloring of metals by chemical or electrolytic process; cleaning and coating metals; welding and cutting of heat-resistant metals; liberation during ore extraction and metal purification	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use of calcium cyanamid in fertilizer on soil; during chemical synthesis for manufacture of intermediates in pharmaceuticals, dyes, vitamins, plastics, and sequestering agents; preparation of nitriles, carbylamines, cyano fatty acids, and inorganic cyanides	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in cellulose technology; paper manufacture; in dyeing; as cement stabilizers; use in photography as fixatives, and in blueprinting and process engraving; liberation in blast furance gases or in handling of illuminating gas	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If cyanide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with cyanides.
• **Skin Exposure**
If cyanide gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If cyanide penetrates through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.
• **Breathing**
If a person breathes in large amounts of cyanide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When cyanide has been swallowed and the person is conscious, give the person large quantities of w :r immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If cyanide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation, or for treatment in a cyanide disposal system.

• Waste disposal method:

After treatment as in above, cyanide may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Cyanide (as CN)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hydrogen Cyanide," *Hygienic Guide Series*, Detroit, Michigan, 1970.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Chen, K. K., and Rose, C. L.: "Nitrite and Thiosulfate Therapy in Cyanide Poisoning," *Journal of the American Medical Association*, 149:113-119, 1952.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-30, Cyanide*, Washington, D.C., 1967.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Hydrogen Cyanide and Cyanide Salts*, HEW Publication No. (NIOSH) 77-108, GPO No. 017-033-00163-4, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

• Wolfsie, J. H.: "Treatment of Cyanide Poisoning in Industry," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 4:417-425, 1951.

RESPIRATORY PROTECTION FOR CYANIDE

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
50 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 50 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against hydrogen cyanide and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Cyclohexane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_6H_{12}
- Synonyms: Hexahydrobenzene; hexamethylene; benzene hexahydride
- Appearance and odor: Colorless liquid with mild, sweet odor resembling chloroform or benzene.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cyclohexane is 300 parts of cyclohexane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1050 milligrams of cyclohexane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cyclohexane can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to cyclohexane may cause dizziness and nausea. At higher levels of exposure, a person may become unconscious. Liquid splashes of cyclohexane may iritate the eyes.

2. Long-term Exposure: Prolonged or repeated exposures can cause skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cyclohexane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to cyclohexane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from cyclohexane exposure.

—Skin disease: Cyclohexane is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although cyclohexane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of cyclohexane might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Liver disease: Although cyclohexane is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Cyclohexane is primarily a local irritant and central nervous system depressant. The depressant effect is from exposure to conconcentrations above 12,000 ppm, while prolonged or repeated exposure to concentrations above 300 ppm produces a mild irritation of the eyes and upper respiratory tract. Aspiration causes a chemical pneumonitis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- Physical data
  1. Molecular weight: 84
  2. Boiling point (760 mm Hg): 80 C (177 F)
  3. Specific gravity (water = 1): 0.78
  4. Vapor density (air = 1 at boiling point of cyclohexane): 2.98
  5. Melting point: 6.5 C (44 F)
  6. Vapor pressure at 20 C (68 F): 95 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Less than 0.01
  8. Evaporation rate (butyl acetate = 1): Data not available
- Reactivity
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving cyclohexane.
  4. Special precautions: None
- Flammability
  1. Flash point: −20 C (−4 F) (closed cup)
  2. Autoignition temperature: 245 C (473 F)
  3. Flammable limits in air, % by volume: Lower: 1.31; Upper: 8.35
  4. Extinguishant: Dry chemical, foam, or carbon dioxide
- Warning properties
  1. Odor Threshold: May reports that the odor threshold of cyclohexane is 0.41 ppm. The Manufacturing Chemists Association (MCA) reports that "the sweetish odor of cyclohexane, which resembles that of chloroform, is not adequate warning against exposure to hazardous concentrations." The AIHA *Hygienic Guide* reports similar information.
  2. Eye Irritation Level: The *Documentation of TLV's* reports that, according to Gerarde, a concentration of 300 ppm is somewhat irritating to the eyes. The MCA, however, states that even in high concentrations the vapor is not irritating to the eyes.
  3. Evaluation of Warning Properties: Since the MCA and the *Hygienic Guide* both state that the odor of cyclohexane is not sufficient warning against exposure to hazardous concentrations, and since MCA states that even high concentrations of cyclohexane do not cause eye irritation, for the purposes of this guideline, cyclohexane is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- Method

Sampling and analyses may be performed by collection of cyclohexane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure cyclohexane may be used.

An analytical method for cyclohexane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 1, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00267-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid cyclohexane.
- Clothing wet with liquid cyclohexane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of cyclohexane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the cyclohexane, the person performing the operation should be informed of cyclohexane's hazardous properties.
- Any clothing which becomes wet with liquid cyclohexane should be removed immediately and not reworn until the cyclohexane is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid cyclohexane may contact the eyes.

SANITATION

• Skin that becomes wet with cyclohexane should be promptly washed or showered with soap or mild detergent and water to remove any cyclohexane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cyclohexane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent to dissolve cellulose ethers, resins, fats, waxes, oils, bitumin, and crude rubber; use in perfume manufacture; use during surface coating operations (lacquers)	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of adipic acid for production of Nylon 66 and engineering plastics	Process enclosure; local exhaust ventilation; personal protective equipment
Use during synthesis of caprolactam in Nylon 6 production	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If cyclohexane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If cyclohexane gets on the skin, promptly flush the contaminated skin with water. If cyclohexane soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of cyclohexane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If cyclohexane has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If cyclohexane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Combustion may be improved by mixing with a more flammable liquid. Cyclohexane liquid should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Cyclohexane may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber. Combustion may be improved by mixing with a more flammable liquid.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Cyclohexane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Cyclohexane," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• American Petroleum Institute: "Cyclohexane," *API Toxicological Reviews*, New York.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products*

(3rd ed.), Williams and Wilkins, Baltimore, 1969.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-68, Cyclohexane*. Washington, D.C.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*. U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• Treon, H. F., et al.: "The Physiological Response of Rabbits to Cyclohexane, Methylcyclohexane, and Certain Derivatives of These Compounds," *Journal of Industrial Hygiene and Toxicology*, 25:6, pp. 199-214, 1943.

RESPIRATORY PROTECTION FOR CYCLOHEXANE

Condition	Minimum Respiratory Protection* Required Above 300 ppm
Vapor Concentration	
3000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
10,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Cyclohexanol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_{11}OH$
- Synonyms: Hexalin; hydroxycyclohexane; hydralin; anol; hexahydrophenol; cyclohexyl alcohol
- Appearance and odor: Colorless, viscous liquid or sticky solid with a faint, camphor-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cyclohexanol is 50 parts of cyclohexanol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 200 milligrams of cyclohexanol per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cyclohexanol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to cyclohexanol may cause headache and irritation of the eyes, nose, and throat.

2. Long-term Exposure: Repeated exposure to cyclohexanol may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cyclohexanol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to cyclohexanol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from cyclohexanol exposure.

—Skin disease: Cyclohexanol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although cyclohexanol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although cyclohexanol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of cyclohexanol might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Cyclohexanol vapor has a narcotic effect at high concentrations and causes irritation of the eyes, nose, and throat. Prolonged exposure at 145 ppm resulted in minimal changes in the liver and kidneys of rabbits. Lethargy occurs in the monkey at 700 ppm, and narcosis in rabbits at 1000 ppm. The liquid defats the skin and may produce dermatitis upon prolonged or frequent contact. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 100
  2. Boiling point (760 mm Hg): 161 C (322 F)
  3. Specific gravity (water = 1): 0.96
  4. Vapor density (air = 1 at boiling point of cyclohexanol): 3.5
  5. Melting point: 23.6 C (75 F)
  6. Vapor pressure at 20 C (68 F): 1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 3.6
  8. Evaporation rate (butyl acetate = 1): 0.08
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving cyclohexanol.
  4. Special precautions: Cyclohexanol will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 67.8 C (154 F (closed cup)
  2. Autoignition temperature: 300 C (572 F)
  3. Flammable limits in air, % by volume: Lower: 2.4 (calculated at flash point)
  4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: No quantitative information is available.
  2. Irritation Levels: The *Documentation of TLV's* states that "Nelson and his associates found 100 ppm of cyclohexanol to be objectionable to the ten persons subjected to this concentration in a study of sensory response to a number of solvent vapors. In this study the individuals classified the effect of the vapor on the eyes, nose, and throat after 3 to 5 minutes' exposure as objectionable. The limit of 50 ppm was ch[illegible]n to reduce objectionable irritation."
  3. Evaluation of Warning Properties: Since cyclohexanol is known to produce eye, nose, and throat irritation at a concentration only twice the permissible exposure limit, it is treated as a substance with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of cyclohexanol vapors using an adsorption tube with subsequent desorption with 2-propanol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure cyclohexanol may be used. An analytical method for cyclohexanol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid or liquid cyclohexanol.
- Clothing wet with liquid cyclohexanol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of cyclohexanol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the cyclohexanol, the person performing the operation should be informed of cyclohexanol's hazardous properties.
- Non-impervious clothing which becomes contaminated with solid or liquid cyclohexanol should be removed promptly and not reworn until the cyclohexanol is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where liquid or solid cyclohexanol may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid or solid cyclohexanol should be promptly washed or showered with soap or mild detergent and water to remove any cyclohexanol.

• Employees who handle liquid or solid cyclohexanol should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cyclohexanol may occur and control methods which may be effective in each case:

Operation	Controls
Use during synthesis of adipic acid, primarily in production of Nylon 66	General dilution ventilation; personal protective equipment
Liberation during synthesis of caprolactam	General dilution ventilation
Use during application of surface coatings of natural and synthetic textile dyes, cotton mercerizers, paints, varnishes, lacquers, and shellacs	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in cleaning and degreasing operations	Local exhaust ventilation; personal protective equipment
Use in production of dicyclohexyl phthalate, other cyclohexyl esters, soaps, synthetic detergents, and rubber cement	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If cyclohexanol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If cyclohexanol gets on the skin, promptly wash the contaminated skin with water. If cyclohexanol soaks through the clothing, remove the clothing promptly and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of cyclohexanol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When cyclohexanol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If cyclohexanol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected, mixed with ethyl alcohol, and atomized in a suitable combustion chamber.

• Waste disposal methods:

Cyclohexanol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By mixing with ethyl alcohol and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Cyclohexanol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR CYCLOHEXANOL

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
3500 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 3500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Cyclohexene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_6H_{10}
- Synonyms: Benzene tetrahydride
- Appearance and odor: Colorless liquid with a sweetish odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cyclohexene is 300 parts of cyclohexene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1015 milligrams of cyclohexene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cyclohexene can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to cyclohexene may cause irritation of the eyes, nose, and throat.
2. Long-term Exposure: Prolonged or repeated contact of this chemical with the skin may cause skin irritation.
3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cyclohexene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to cyclohexene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from cyclohexene exposure.

—Skin disease: Cyclohexene can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although cyclohexene is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although cyclohexene is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of cyclohexene might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

While no significant toxicologic studies on cyclohexene have been reported, it is regarded as a mild respiratory irritant and central nervous system depressant, chiefly by analogy to the observed effect of chemically similar substances. No acute or chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 82
2. Boiling point (760 mm Hg): 82.8 C (181 F)
3. Specific gravity (water = 1): 0.8
4. Vapor density (air = 1 at boiling point of cyclo-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

hexene): 2.8

5. Melting point: −103.7 C (−155 F)

6. Vapor pressure at 20 C (68 F): 67 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): Very low

8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving cyclohexene.

4. Special precautions: Cyclohexene will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: −12 C (10 F) (closed cup)

2. Autoignition temperature: 310 C (590 F)

3. Flammable limits in air, % by volume: Lower: 1.2; Upper: 4.8 at 100 C (212 F)

4. Extinguishant: Dry chemical, carbon dioxide, foam

• **Warning properties**

1. Odor Threshold: By analogy to cyclohexane, which has an odor threshold of 0.41 ppm according to May, the odor of cyclohexene is assumed to be below the permissible exposure limit of 300 ppm.

2. Eye Irritation Level: The *Documentation of TLV's* states that "Cook suggested 400 ppm as a TLV (for cyclohexene) on the basis of analogy to cyclohexane. This limit has subsequently been reduced to 300 ppm to provide a wider margin of safety from systemic effects and to reduce irritation."

3. Evaluation of Warning Properties: By analogy to cyclohexane, the odor threshold of cyclohexene is assumed to be below the permissible exposure limit. Cyclohexene, therefore, is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analysis may be performed by collection of cyclohexene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure cyclohexene may be used. An analytical method for cyclohexene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid cyclohexene.

• Clothing wet with liquid cyclohexene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of cyclohexene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the cyclohexene, the person performing the operation should be informed of cyclohexene's hazardous properties.

• Any clothing which becomes wet with liquid cyclohexene should be removed immediately and not reworn until the cyclohexene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid cyclohexene may contact the eyes.

SANITATION

• Skin that becomes wet with liquid cyclohexene should be promptly washed or showered with soap or mild detergent and water to remove any cyclohexene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cyclohexene may occur and control methods which may be effective in each case:

Operation	Controls
Use in organic synthesis as a starting material or chemical intermediate	Process enclosure; local exhaust ventilation; personal protective equipment; general dilution ventilation
Use as a constituent to study catalytic reactions, mechanisms of oxidation of hydrocarbons, and reaction kinetics	Process enclosure; local exhaust ventilation; general dilution ventilation
Use in synthesis of polymers; as a polymer modifier to control molecular weight; use as a stabilizing agent	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during catalytic hydrogenation of aromatic compounds	Process enclosure; local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If cyclohexene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If cyclohexene gets on the skin, promptly wash the contaminated skin using soap or mild detergent. If cyclohexene soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of cyclohexene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If cyclohexene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If cyclohexene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Cyclohexene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Cyclohexene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Cyclohexene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Cyclohexane," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Gafafer, W. M. (ed.): "Occupational Diseases: A Guide to Their Recognition," U.S. Public Health Service Publication No. 1097, 1964.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 19[illegible].

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck & Co., Inc., Rahway, New Jersey, 1968.
• Treon, J. F., et al.: "The Physiological Response of Rabbits to Cyclohexanol, Methylcyclohexane, and Certain Derivatives of These Compounds," *Journal of Industrial Hygiene and Toxicology*, 25:6, p. 199, June 1943.

RESPIRATORY PROTECTION FOR CYCLOHEXENE

Condition	Minimum Respiratory Protection* Required Above 300 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
10,000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Cyclopentadiene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_5H_6
- Synonyms: 1,3-Cyclopentadiene
- Appearance and odor: Colorless liquid with a sweet odor like turpentine; dimer is a crystalline material with a camphor-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for cyclopentadiene is 75 parts of cyclopentadiene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 200 milligrams of cyclopentadiene per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Cyclopentadiene might possibly affect the body if it is inhaled, is swallowed, or allowed to come in contact with the eyes or skin.

- **Effects of overexposure**

Overexposure to cyclopentadiene may cause irritation of the eyes and nose.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to cyclopentadiene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to cyclopentadiene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from cyclopentadiene exposure.

—Liver disease: Although cyclopentadiene is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although cyclopentadiene is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of cyclopentadiene might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Cyclopentadiene vapor is irritating to the eyes and nose and has an objectionable odor. Repeated daily exposure of rats at 500 ppm produced mild toxic effects in the liver and kidneys, whereas repeated daily exposures in several species of animals at 250 ppm for 135 times produced no manifest effects. Dogs exposed to repeated daily exposures of up to 800 ppm had no ill effects; liver function and hematologic findings remained negative. Chronic systemic effects have not been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 66
  2. Boiling point (760 mm Hg): 41.5 C (107 F)
  3. Specific gravity (water = 1): 0.8
  4. Vapor density (air = 1 at boiling point of cyclo-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

pentadiene): 2.3

5. Melting point: −85 C (−121 F)

6. Vapor pressure at 20 C (68 F): Data not available

7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble

8. Evaporation rate (butyl acetate = 1): Data not available

• Reactivity

1. Conditions contributing to instability: Heat. Cyclopentadiene is converted to the higher boiling dicyclopentadiene on storage even at 0 C (32 F). The reaction may become violent at higher temperatures.

2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving cyclopentadiene.

4. Special precautions: Cyclopentadiene should be stored at −20 to 0 C (−4 F to 32 F). When stored in bulk, the conversion to dicyclopentadiene may become violent if the temperature is allowed to rise above 0 C (32 F).

• Flammability

1. Flash point: Less than 32 C (90 F) (open cup) (flash point of dimer)

2. Autoignition temperature: 640 C (1184 F)

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Dry chemical, carbon dioxide, foam

• Warning properties

1. Odor Threshold: According to the *Documentation of TLV's*, cyclopentadiene has "an irritating, terpene-like odor," but no quantitative information is available concerning its odor threshold.

The *Documentation of TLV's* states that "human sensory response was distinctly unfavorable at both 500 ppm and 250 ppm. Thus, although systemic injury is not to be expected from exposure concentrations averaging 250 ppm, a concentration significantly below 250 ppm is required from the standpoint of comfort. A TLV of 75 ppm is recommended."

2. Eye Irritation Level: Cyclopentadiene vapor is not specifically known to cause eye irritation. Grant states that "a less reactive cyclopentadiene-dimer formed by spontaneous polymerization has been tested on rabbit eyes and found to be only slightly injurious . . . ."

3. Evaluation of Warning Properties: Through its sensory effects, cyclopentadiene can be detected at a concentration of about 3 times the permissible exposure limit. For the purposes of this guideline, therefore, cyclopentadiene is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Method

An analytical method for cyclopentadiene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid cyclopentadiene.

• Clothing wet with liquid cyclopentadiene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of cyclopentadiene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the cyclopentadiene, the person performing the operation should be informed of cyclopentadiene's hazardous properties.

• Any clothing which becomes wet with liquid cyclopentadiene should be removed immediately and not reworn until the cyclopentadiene is removed from the

clothing.
• Employees should be provided with and required to use splash-proof safety goggles where liquid cyclopentadiene may contact the eyes.

SANITATION

• Skin that becomes wet with liquid cyclopentadiene should be promptly washed or showered with soap or mild detergent and water to remove any cyclopentadiene.
• Employees who handle liquid cyclopentadiene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to cyclopentadiene may occur and control methods which may be effective in each case:

Operation	Controls
Use in thermal cracking of dicyclopentadiene; use in chemical synthesis	General dilution ventilation; personal protective equipment
Use in production of modified oil similar to tung oil from linseed or soybean oil	General dilution ventilation; personal protective equipment
Use in preparation of epoxy resins; preparation of ladder polymers; preparation of varnishes; use as a drying oil for varnishes	General dilution ventilation; personal protective equipment
Use in production of fire-resistant polyurethane foams; production of heat-stable, fire-resistant laminating agents and surface coatings; production of sanitary can coatings	General dilution ventilation; personal protective equipment
Use in production of foundry-core bindings; production of epoxidized olefins	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If cyclopentadiene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If cyclopentadiene gets on the skin, promptly wash the contaminated skin using soap or mild detergent. If cyclopentadiene soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent.
• **Breathing**
If a person breathes in large amounts of cyclopentadiene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
If cyclopentadiene has been swallowed, do not induce vomiting. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If cyclopentadiene is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, allow the material to dimerize, collect on paper or other material. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities may be reclaimed or dissolved in an appropriate solvent and atomized in a suitable combustion chamber. Cyclopentadiene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.
• Waste disposal method:
Cyclopentadiene may disposed of by dissolving in an appropriate solvent and atomizing in a suitable combustion chamber.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Cyclopentadiene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR CYCLOPENTADIENE

Condition	Minimum Respiratory Protection* Required Above 75 ppm
Vapor Concentration	
750 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
2000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 2,4-D *

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $Cl_2C_6H_3OCH_2COOH$
- Synonyms: 2,4-Dichlorophenoxyacetic acid
- Appearance and odor: Colorless, odorless solid

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 2,4-D is 10 milligrams of 2,4-D per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

2,4-D can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Massive exposure to 2,4-D may cause weakness, stupor, muscle twitching, and convulsions. Contact of the material with the skin may cause a rash. It has caused minor liver and kidney damage in animals.

2. Long-term Exposure: Not known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 2,4-D.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 2,4-D at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 2,4-D exposure.

—Liver disease: 2,4-D causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: 2,4-D causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Cardiovascular disease: 2,4-D causes ventricular fibrillation in animals. In persons with impaired cardiovascular function, the inhalation of 2,4-D might cause exacerbation of pre-existing disorder.

—Skin disease: 2,4-D can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Convulsive disorder or neuropathy: 2,4-D may cause convulsions in humans. Persons with a history of such disorders may be more susceptible to the effects of this agent. 2,4-D may also produce neuropathy by analogy to effects observed in experimental animals.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

2,4-D dust causes signs of both hypo- and hyperexcitation of the central nervous system in animals. In several species of animals given massive oral doses, sudden death has been ascribed to ventricular fibrillation. If death is delayed, myotonia, stiffness of the extremities, ataxia, paralysis, and coma are seen; autopsy findings have included minor liver and kidney injury. The myotonia characteristic of intoxication by 2,4-D in animals has not been reported in humans. Possibly the only recognized fatal case of poisoning involved a suicidal person who ingested not less than 6500 mg; the

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

person apparently experienced violent convulsions, although they were not actually observed; there were no significant findings at autopsy. A single dose of 3.6 g of 2,4-D administered intravenously to a patient for treatment of disseminated coccidiomycosis caused stupor, hyporeflexia, fibrillary twitching of some muscles, and urinary incontinence; 24 hours after the dose, the patient still complained of profound muscular weakness, which subsided after an additional 24 hours. Contact of the material with the skin may cause dermatitis; skin absorption is slight.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 221
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): 1.1 (estimated)
  4. Vapor density (air = 1 at boiling point of 2,4-D): 7.63
  5. Melting point: 140 C (284 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, at 20 C (68 F): 0.07 ppm
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving 2,4-D.
  4. Special precautions: None
- **Flammability**
  1. Flash point: Data not available
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Carbon dioxide, dry chemical, foam, water
- **Warning properties**

Since 2,4-D has a negligible vapor pressure, warning properties are not considered.

Grant states that "2,4-dichlorophenoxyacetic acid (2,4-D) is a herbicide for weed control, often used in the form of its salts or esters. Parenteral administration to dogs has caused sneezing, lacrimation, and rubbing of the eyes, along with gastrointestinal disturbances. In three human beings, absorption of an unspecified ester of dichlorophenoxyacetic acid through the skin caused polyneuritis, but with no disturbance of the eyes or vision." The above do not appear to be local effects on the eye. However, Stolman and Stecher note that this substance can cause irritation of the eyes.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for 2,4-D is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with 2,4-D or liquids containing 2,4-D.
- If employees' clothing may have become contaminated with 2,4-D, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with 2,4-D should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 2,4-D from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 2,4-D, the person performing the operation should be informed of 2,4-D's hazardous properties.
- Non-impervious clothing which becomes contami-

nated with 2,4-D should be removed promptly and not reworn until the 2,4-D is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where 2,4-D or liquids containing 2,4-D may contact the eyes.

SANITATION

• Skin that becomes contaminated with 2,4-D should be promptly washed or showered with soap or mild detergent and water to remove any 2,4-D.

• Eating and smoking should not be permitted in areas where solid 2,4-D is handled, processed, or stored.

• Employees who handle 2,4-D or liquids containing 2,4-D should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 2,4-D may occur and contr ·l methods which may be effective in each case:

Operation	Controls
Formulation of herbicides	Process enclosure; local exhaust ventilation; personal protective equipment; washing facilities
Manufacture of 2,4-D	Process enclosure; local exhaust ventilation; personal protective equipment; washing facilities
Application on cereal crops, corn, sorghum, milo, sugar cane, pastures, range land, and lawns for use as an herbicide; use as a plant hormone on agricultural crops	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 2,4-D or liquids containing 2,4-D get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 2,4-D or liquids containing 2,4-D get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 2,4-D or liquids containing 2,4-D penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 2,4-D, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 2,4-D has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If 2,4-D is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dispose of by burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device, as in below or deposit in a secured sanitary landfill.

• Waste disposal methods:

2,4-D may be disposed of:

1. By making packages of 2,4-D in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving 2,4-D in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. By disposal in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "2,4-D (2,4-Dichlorophenoxyacetic Acid)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Seabury, J. H.: "Toxicity of 2,4-Dichlorophenoxyacetic Acid for Man and Dog," *Archives of Environmental Health*, 7:202-209, 1963.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck & Co., Inc., Rahway, New Jersey, 1968.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 15, 1977.

RESPIRATORY PROTECTION FOR 2,4-D

Condition	Minimum Respiratory Protection* Required Above 10 mg/m³
Particulate Concentration	
100 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
500 mg/m³ or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s), and dust filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Decaborane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $B_{10}H_{14}$
- Synonyms: None
- Appearance and odor: Colorless solid with a pungent odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for decaborane is 0.05 part of decaborane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.3 milligram of decaborane per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Decaborane can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: The onset of symptoms from exposure to decaborane may be delayed until one or two days after exposure has occurred. Headache, nausea, lightheadedness, drowsiness, nervousness, lack of coordination, and tremors may occur. In more severe cases muscle spasms and convulsions may be produced. In animals impairment of liver and kidney function has occurred.

2. Long-term Exposure: Prolonged exposure to low concentrations of decaborane may cause headache, fatigue, drowsiness, inability to concentrate, and lack of coordination.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to decaborane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to decaborane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of convulsive disorders would be expected to be at increased risk from exposure. Examination of the nervous system, liver, and kidneys should be stressed.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Decaborane dust or vapor affects the nervous system and causes signs of both hyperexcitability and narcosis. Exposure of rabbits to 56 ppm for 6 hours was fatal; effects included dyspnea, coarse movements of the head, weakness, rigid hindquarters, absence of eye reflexes, and convulsive seizures. In dogs repeatedly given oral doses of 3 mg/kg, the effects on the central nervous system were not pronounced, but there was damage to the liver and kidneys. In humans the onset of symptoms is frequently delayed for 24 to 48 hours after exposure; dizziness, headache and nausea are common; other symptoms of mild intoxication include light-headedness, drowsiness, incoordination, and fatigue; more severe intoxication results in tremor, localized muscle spasms and convulsive seizures. Muscle spasms usually subside after 24 hours, while light-headedness and fatigue may remain for up to 3 days. Effects on the

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

eyes or skin of humans have not been reported; mice exposed to 26 ppm for 4 hours exhibited corneal opacity. Decaborane may impair the sense of smell.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 122.3
2. Boiling point (760 mm Hg): 213 C (416 F) (extrapolated)
3. Specific gravity (water = 1): 0.94
4. Vapor density (air = 1 at boiling point of decaborane): 4.2
5. Melting point: 99.7 C (211.5 F)
6. Vapor pressure at 25 C (77 F): 0.05 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble; reacts slowly to form hydrogen gas
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Heat above 170 C (338 F) causes decomposition and pressure.
2. Incompatibilities: Contact with oxidizers may cause fires and explosions. Mixtures of decaborane and halogenated compounds will explode when subject to shock. Contact with water causes slow formation of flammable hydrogen gas that may collect in enclosed areas.
3. Hazardous decomposition products: Toxic gases and vapors (such as boron oxide smoke) may be released in a fire involving decaborane.
4. Special precautions: Decaborane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 80 C (176 F) (closed cup)
2. Autoignition temperature: 149 C (300 F)
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Carbon dioxide, dry chemical

- **Warning properties**

1. Odor Threshold: According to Browning, decaborane has "an intense, bitter chocolate-like odor." Baskin, however, states that "odor cannot be relied upon for detection."
2. Eye Irritation Level: The ILO states that decaborane produces "marked irritation of the skin and mucous membranes, causing necrotic changes, serious conjunctivitis with ulceration, and corneal opacification." Deichmann and Gerarde report that "vapor concentration (of boranes) below the levels harmful on inhalation are not irritating to the eyes." Information is not available concerning the threshold of eye irritation.
3. Evaluation of Warning Properties: No quantitative data are available relating warning properties to air concentrations of decaborane. For the purposes of this guideline, decaborane is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for decaborane had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid decaborane or liquids containing decaborane, where skin contact may occur.
- If employees' clothing may have become contaminated with decaborane, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with decaborane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of decaborane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the decaborane, the person performing the operation should be informed of decaborane's hazardous properties.

• Where exposure of an employee's body to decaborane or liquids containing decaborane may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
• Non-impervious clothing which becomes contaminated with decaborane should be removed immediately and not reworn until the decaborane is removed from the clothing.
• Employees should be provided with and required to use dust- and splash-proof safety goggles where decaborane or liquids containing decaborane may contact the eyes.

SANITATION

• Skin that becomes contaminated with decaborane should be immediately washed or showered with soap or mild detergent and water to remove any decaborane.
• Workers subject to skin contact with decaborane or liquids containing decaborane should wash with soap or mild detergent and water any areas of the body which may have contacted decaborane at the end of each work day.
• Eating and smoking should not be permitted in areas where decaborane or liquids containing decaborane are handled, processed, or stored.
• Employees who handle decaborane or liquids containing decaborane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to decaborane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a reducing agent in chemical synthesis; use as a component or additive for high-energy fuel and rocket propellants; use in manufacture of polymers; an olefin polymerization catalyst	Process enclosure; personal protective equipment
Use as a vulcanizing agent in the rubber industry in manufacture of synthetic rubber	Process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If decaborane or liquids containing decaborane get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If decaborane or liquids containing decaborane get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If decaborane or liquids containing decaborane penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention promptly.
• **Breathing**
If a person breathes in large amounts of decaborane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When decaborane or liquids containing decaborane have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If decaborane is spilled, the following steps should be taken:
1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
• Waste disposal methods:
Decaborane may be disposed of:
1. By making packages of decaborane . paper or other flammable material and burning in a suitable combustion chamber equipped with an ap, opriate effluent gas cleaning device.
2. By dissolving decaborane in a flammable solvent (such as alcohol) and atomizing in a suitable combustion

chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Decaborane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Holzmann, R. T. (ed.): *Production of the Boranes and Related Research*, Academic Press, New York, 1967.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Krackow, E. H.: "Toxicity and Health Hazards of Boron Hydrides," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 8:335-339, 1953.

• Lowe, H. J., and Freeman, G.: "Boron Hydride (Borane) Intoxication in Man," *A.M.A. Archives of Industrial Health*, 16:523-533, 1957.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-84, Boron Hydrides*, Washington, D.C., 1967.

• Roush, G., Jr.: "The Toxicology of the Boranes," *Journal of Occupational Medicine*, 1:46-52, January 195

• Rozendaal, H. M.: "Clinical Observations on the Toxicology of Boron Hydrides," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 4:257-260, 1951.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• Weir, F. W., and Meyers, F. H.: "The Similar Pharmacologic Effects of Pentaborane, Decaborane, and Reserpine," *Industrial Medicine and Surgery*, 35:696-701, 1966.

RESPIRATORY PROTECTION FOR DECABORANE

Condition	Minimum Respiratory Protection* Required Above 0.3 mg/m³
Vapor or Particulate Concentration	
0.5 ppm (3 mg/m³) or less	Any supplied-air respirator. Any self-contained breathing apparatus.
2.5 ppm (15 mg/m³) or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
20 ppm (120 mg/m³) or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 20 ppm (120 mg/m³)** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of decaborane; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 20 ppm (120 mg/m³), an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Demeton

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_2H_5O)_2PSOC_2H_4SC_2H_5$
- Synonyms: Systox(R); O-O-diethyl O-(2-ethylthio)-ethyl phosphorothioate (2 parts) Demeton-O; O-O-diethyl S-(2-ethylthio)ethyl phosphorothioate (1 part) Demeton-S
- Appearance and odor: Light brown liquid with the odor of sulfur compounds

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Demeton is 0.1 milligram of Demeton per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for Demeton a Threshold Limit Value of 0.01 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Demeton can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: After inhalation of Demeton, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of vision, tearing, runny nose, headache, and watering of the mouth. After swallowing Demeton, loss of appetite, nausea, vomiting, abdominal cramps and diarrhea may appear within two hours. After skin absorption, sweating and twitching in the area of absorption may occur usually within 15 minutes to four hours. With severe intoxication by all routes, in addition to all the above symptoms, weakness, generalized twitching, and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, irregular or slow heart beat, convulsions, and coma may occur.

2. Long-term Exposure: Repeated exposure to Demeton may make a person more susceptible to the effects of this and related chemicals. Repeated exposures to concentrations which are too small to produce symptoms after a single exposure may result in the onset of symptoms.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Demeton.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Demeton at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system and attention to the cholinesterase levels in the blood should be stressed. The skin should be examined for evidence of chronic disorder.

—Cholinesterase determination: Demeton (Systox) causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

in the serum and erythrocytes should be determined by using medically acceptable biochemical tests prior to any new period of exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determination which should be performed quarterly or at any time overexposure is suspected or signs or symptoms of toxicity occur.

- **Summary of toxicology**

Demeton (Systox) is an anticholinesterase agent; absorption may occur from inhalation of the vapor, by skin absorption, or by ingestion of the liquid. At least four fatal, several severe nonfatal, and a number of mild cases of Demeton intoxication have been reported. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nervous system, skeletal and smooth muscle, and secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms may occur promptly or may be delayed for up to 12 hours. After inhalation, respiratory and ocular effects are the first to appear, often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects, such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption, localized sweating and muscular fasciculations in the immediate area occur, usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures and is increased by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels, and cardiac irregularities including complete heart block may occur; these effects may sometimes be reversed by establishing adequate pulmonary ventilation. Complete symptomatic recovery usually occurs within 1 week; increased susceptibility to the effects of anticholinesterase agents persists for weeks after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 258
  2. Boiling point (2 mm Hg): 134 C (273 F)
  3. Specific gravity (water = 1): 1.18
  4. Vapor density (air = 1 at boiling point of Demeton): Not applicable
  5. Melting point: Higher than −25 C (−13 F)
  6. Vapor pressure at 20 C (68 F): Very low
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.2
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide, phosphoric acid mist, and carbon monoxide) may be released when Demeton decomposes.
  4. Special precautions: Demeton will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: Data not available
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Carbon dioxide, dry chemical, foam
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold of Demeton.
  2. Eye Irritation Level: Demeton is not known to be an eye irritant.
  3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of Demeton, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for Demeton is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with Demeton.

• Clothing which has had any possibility of being contaminated with Demeton should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of Demeton from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the Demeton, the person performing the operation should be informed of Demeton's hazardous properties.

• Where there is any possibility of exposure of an employee's body to Demeton, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with Demeton should be removed immediately and not reworn until the Demeton is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of Demeton contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to Demeton, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with Demeton should be immediately washed or showered with soap or mild detergent and water to remove any Demeton.

• Workers subject to skin contact with Demeton should wash any areas of the body which may have contacted Demeton at the end of each work day.

• Eating and smoking should not be permitted in areas where Demeton is handled, processed, or stored.

• Employees who handle Demeton should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Demeton may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of acaricides and insecticides	Personal protective equipment
Application as a pesticide on agricultural crops, fruits/nuts, vegetables, and ornamentals	Material substitution; personal protective equipment
Manufacture of Demeton	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If Demeton or Demeton mists get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If Demeton or Demeton mists get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If Demeton or Demeton mists penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of Demeton, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When Demeton has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If Demeton is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.

2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Demeton may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Demeton (Systox)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Parathion," *Hygienic Guide Series*, Detroit, Michigan, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• *Hygienic Information Guide No. 67 - Demeton (Systox)*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1972.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koelle, G. B. (ed.): "Cholinesterases and Anticholinesterase Agents," Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR DEMETON (R)

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Vapor Concentration	
1 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
20 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 20 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of Demeton; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 20 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Diazomethane*.

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_2N_2
- Synonyms: Azimethylene; diazirine
- Appearance: Yellow gas. When stored under pressure, diazomethane can be in the liquid form.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for diazomethane is 0.2 part of diazomethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.4 milligram of diazomethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Diazomethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to diazomethane vapor may cause severe irritation of the eyes, nose, throat, skin, and lungs. Symptoms include headache, weakness, cough, fever, chest pains, shortness of breath, and wheezing. The onset of symptoms after exposure may be delayed. Skin and mucous membrane exposure to liquids containing diazomethane may cause burns with the loss of the skin or mucous membrane. If any of these symptoms appear, get medical attention immediately.

2. Long-term Exposure: Prolonged or repeated exposure to diazomethane may lead to sensitization. Should sensitization occur, a person may experience asthma-like symptoms or fever from exposure to concentrations of diazomethane which had previously caused no symptoms. Diazomethane has been reported to cause cancer of the lungs in animals.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to diazomethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to diazomethane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of respiratory system should be stressed.

—14" x 17" chest roentgenogram: Diazomethane may cause acute lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Diazomethane is reported to cause temporary pulmonary function impairment. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

Diazomethane gas is a severe respiratory irritant and sensitizer. It is one of the most dangerous products of the chemical laboratory, causing irritation of the eyes, chest pain, cough, fever, and severe asthmatic attacks. Exposure of cats to 175 ppm for 10 minutes resulted in pulmonary edema and hemorrhage, with death occurring in 3 days. A chemist briefly exposed to an unknown concentration in a laboratory developed a violent cough and shortness of breath leading to severe pul-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

monary edema; symptoms completely subsided within 2 weeks. In a fatal incident, another chemist exposed to an unknown concentration of diazomethane, as well as other irritant gases, experienced immediate respiratory distress leading to pneumonitis and death on the fourth day after exposure. A physician exposed to diazomethane from a laboratory spill noted only a faint odor, but immediately experienced severe headache, cough, mild anterior chest pain, generalized aching of muscles, and a sensation of overwhelming tiredness. Within 5 minutes he was stuporous, and on early admission to hospital was markedly flushed and feverish; he recovered in approximately 48 hours. Subsequent exposure to trace amounts of the gas produced wheezing, cough, and malaise, leading to the suspicion that this substance may have a sensitizing, as well as an irritating, effect upon the respiratory system. Skin irritation and sensitization occurs. Also mutagenic and carcinogenic effects have been reported in animals.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 42
2. Boiling point (760 mm Hg): −23 C (−9 F)
3. Specific gravity (water = 1): Data not available
4. Vapor density (air = 1 at boiling point of diazomethane): 1.4
5. Melting point: −145 C (-229 F)
6. Vapor pressure at 20 C (68 F): Not pertinent
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts
8. Evaporation rate (butyl acetate = 1): Not pertinent

- **Reactivity**

1. Conditions contributing to instability: Diazomethane may explode when not diluted with other inert gases such as nitrogen. Exposure of diazomethane gas or solutions in solvents to sunlight or other bright illumination may cause explosions. Contact with rough edges such as ground glass may cause explosions.
2. Incompatibilities: Contact of diazomethane gas with alkali metals or drying agents such as calcium sulfate will cause explosions.
3. Hazardous decomposition products: Data not available
4. Special precautions: Barriers or shields should be utilized to protect employees from accidental explosions.

- **Flammability**

1. Flash point: Not pertinent
2. Autoignition temperature: Pure material explodes above 150 C (302 F). Impure material explodes at lower temperature.
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Stop flow of gas.

- **Warning properties**

1. Odor Threshold: Patty reports that diazomethane has a musty odor. No quantitative data are available, however, relating the odor to air concentrations.
2. Eye Irritation Level: Grant reports that "irritation of the eye from exposure to the gas has developed occasionally among those working with this substance." The concentrations causing eye irritation are not given.
3. Other Information: Patty reports that diazomethane is a severe respiratory tract irritant, but the concentrations producing this irritation are not given.
4. Evaluation of Warning Properties: Patty reports that "the warning properties of diazomethane are not adequate to prevent serious intoxication or fatalities." Based upon this report and upon the lack of quantitative data relating warning properties to air concentrations of diazomethane, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube containing XAD-2 resin coated with octanoic acid, followed by desorption with carbon disulfide and gas chromatographic analysis. An analytical method for diazomethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming contaminated with liquid diazomethane or solutions containing diazomethane or from becoming frozen from contact with vessels containing liquid diazomethane.

• Clothing wet with flammable solutions containing diazomethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of diazomethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the diazomethane, the person performing the operation should be informed of diazomethane's hazardous properties.

• Any clothing which becomes wet with liquid diazomethane or flammable solutions containing diazomethane should be removed immediately and not reworn until the flammable liquids are removed from the clothing.

• Non-impervious clothing which becomes contaminated with solutions containing diazomethane should be removed promptly and not reworn until the diazomethane is removed from the clothing.

• Employees should be provided with and required to use safety goggles where there is any possibility of liquid diazomethane or solutions containing diazomethane contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid diazomethane or solutions containing diazomethane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with solutions containing diazomethane should be promptly washed or showered with soap or mild detergent and water to remove any solutions.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to diazomethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as methylating agent in chemical analysis and laboratory organic synthesis	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid diazomethane or solutions containing diazomethane get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid diazomethane or solutions containing diazomethane get on the skin, immediately flush the contaminated skin with water. If liquid diazomethane or solutions containing diazomethane soak through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of diazomethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If diazomethane has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If diazomethane is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
4. If in the liquid form, allow to vaporize.

• Waste disposal method:

Diazomethane may be disposed of by burning at a safe location or in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Diazomethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Lewis, C. E.: "Diazomethane Poisoning, Report of a Case Suggesting Sensitization Reaction," *Journal of Occupational Medicine*, 6:91-93, 1964.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Schoental, R.: "Carcinogenic Action of Diazomethane and of Nitroso-N-methyl Urethane," *Nature*, 188:420-421, 1960.

• Schoental, R., and Magee, P.N.: "Induction of Squamous Carcinoma of the Lung and of the Stomach and Oesophagus by Diazomethane and N-Methyl-N-Nitroso-Urethane, Respectively," *British Journal of Cancer*, 16:92, 1962.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 7, 1974.

RESPIRATORY PROTECTION FOR DIAZOMETHANE

Condition	Minimum Respiratory Protection* Required Above 0.2 ppm
Gas Concentration	
2 ppm or less**	Any supplied-air respirator. Any self-contained breathing apparatus.
10 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Diborane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: B_2H_6
- Synonyms: Boroethane
- Appearance and odor: Colorless gas with a repulsive, sweet odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for diborane is 0.1 part of diborane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.1 milligram of diborane per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Diborane can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Diborane may cause tightness in the chest, cough, inability to take a deep breath, and chest pain. Severe breathing difficulties may occur. These difficulties may be delayed in onset. High concentrations of diborane may irritate the eyes.

2. Long-term Exposure: Prolonged exposure to low concentrations of diborane may cause headache, lightheadedness, fatigue, muscular weakness, and tremors. It has caused liver and kidney damage in animals.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to diborane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to diborane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the lungs, nervous system, liver, and kidneys should be stressed.

—14" x 17" chest roentgenogram: Diborane causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Diborane is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when signs and symptoms of respiratory disease occur.

- **Summary of toxicology**

Diborane gas is a pulmonary irritant. The LC50 for rats was 50 ppm for 4 hours; in other animal experiments, acute exposure caused pulmonary edema and hemorrhage and temporary damage to the liver and kidneys. In humans, overexposure results in a sensation of tightness in the chest leading to precordial pain, shortness of breath, nonproductive cough, and sometimes nausea. Prolonged exposure to low concentrations causes headache, light-headedness, vertigo, chills and, less frequently, fever; fatigue or weakness occurs and may persist for several hours; tremor or muscular fasciculations occur infrequently and are usually localized and of short duration. Diborane gas has not been found to have significant effects upon contact with skin or mucous

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

membranes, although high concentrations may cause eye irritation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 27.7
2. Boiling point (760 mm Hg): −92 C (−134 F)
3. Specific gravity (water = 1): 0.47 (liquid)
4. Vapor density (air = 1 at boiling point of diborane): 0.96
5. Melting point: −165 C (−265 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts rapidly to form hydrogen gas
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Temperatures above −18 C (0 F). Containers are usually stored in "dry ice." Ignites spontaneously in moist air at room temperature.
2. Incompatibilities: Contact with air or halogenated compounds will cause fires and explosions. Contact with aluminum, lithium, and other active metals forms hydrides which may ignite spontaneously. Diborane reacts with many oxidized surfaces as a strong reducing agent.
3. Hazardous decomposition products: Toxic gases and vapors (such as boron oxide smoke) may be released in a fire involving diborane.
4. Special precautions: Diborane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Data not available
2. Autoignition temperature: 38 − 52 C (100 − 125 F)
3. Flammable limits in air, % by volume: Lower: 0.8; Upper: 98
4. Extinguishant: Stop flow of gas, or let fire burn.

- **Warning properties**

1. Odor Threshold: According to the AIHA *Hygienic Guide*, the nauseating odor of diborane is "not a reliable warning of toxic exposure." No quantitative information is available concerning the threshold of odor, however.
2. Eye Irritation Level: Diborane is not known to be an eye irritant.
3. Evaluation of Warning Properties: Since there is no quantitative information relating warning properties to air concentrations of diborane, it is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for diborane had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to diborane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a reducing agent in the synthesis of organic chemical intermediates; use as a component or additive for high-energy fuels; use as a catalyst in olefin polymerization	Process enclosure; personal protective equipment
Use in electronics industry to improve crystal growth or to impart electrical properties in pure crystals	Process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If strong concentrations of diborane gas get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Breathing**

If a person breathes in large amounts of diborane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If diborane is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Diborane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Diborane," *Hygienic Guide Series*, Detroit, Michigan, 1958.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Cordasco, E. M., et al.: "Pulmonary Aspects of Some Toxic Experimental Space Fuels," *Diseases of the Chest*, 41:68-74, 1962.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Holzmann, R. T. (ed.): *Production of the Boranes and Related Research*, Academic Press, New York, 1967.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Krackow, E. H.: "Toxicity and Health Hazards of Boron Hydrides," *A.M.A. Archives of Industrial Hygiene anOccupational Medicine*, 8:335-339, 1953.

• Kunkel, A. M., et al.: "Some Pharmacological Effects of Diborane," *A.M.A. Archives of Industrial Health*3:346-351, 1956.

• Lowe, H. J., and Freeman, G.: "Boron Hydride (Borane) Intoxication in Man," *A.M.A. Archives of IndustrialHealth*, 16:523-533, 1957.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-84, Boron Hydrides*, Washington, D.C., 1967.

• Roush, G., Jr.: "The Toxicology of the Boranes," *Journal of Occupational Medicine*, 1:46-52, January 195

• Rozendaal, H. M.: "Clinical Observations on the Toxicology of Boron Hydrides," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 4:257-260, 1951.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stumpe, A. R.: "Toxicity of Diborane in High Concentrations," *A.M.A. Archives of Industrial Health*, 21:519-524, 1960.

RESPIRATORY PROTECTION FOR DIBORANE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Gas Concentration	
1 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
40 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 40 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against diborane. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dibutyl Phosphate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_4H_9O)_2(OH)PO$
- Synonyms: Dibutyl acid o-phosphate; di-n-butyl hydrogen phosphate; dibutyl phosphoric acid
- Appearance and odor: Colorless to brown odorless liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dibutyl phosphate is 1 part of dibutyl phosphate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 5 milligrams of dibutyl phosphate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dibutyl phosphate can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Dibutyl phosphate may cause irritation of the eyes, nose, throat, and lungs. It may also cause headaches.

2. Long-term Exposure: Repeated or prolonged exposure to dibutyl phosphate may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dibutyl phosphate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dibutyl phosphate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from dibutyl phosphate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of dibutyl phosphate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Dibutyl phosphate can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Dibutyl phosphate vapor is a respiratory irritant. In rats the oral LD50 is 3.2 g/kg. Data on effects in humans are sparse; workers exposed to unspecified concentrations of vapor complained of respiratory irritation and headache. It is a moderately strong acid and could be expected to be irritating on contact.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 210
2. Boiling point (760 mm Hg): Higher than 100 C (212 F) (decomposes)
3. Specific gravity (water = 1): 1.06
4. Vapor density (air = 1 at boiling point of dibutyl phosphate): Not applicable
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Much less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F):

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Insoluble

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None hazardous

2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as phosphoric acid fume and carbon monoxide) may be released in a fire involving dibutyl phosphate.

4. Special precautions: Liquid dibutyl phosphate will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: Data not available

2. Autoignition temperature: Data not available

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Carbon dioxide, dry chemical, foam

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of dibutyl phosphate.

2. Eye Irritation Level: Dibutyl phosphate vapor is not known to be an eye irritant.

3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of dibutyl phosphate, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for dibutyl phosphate is in the *NIOSH Manual of Analytical Methods*. 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid dibutyl phosphate, where skin contact may occur.

• Clothing wet with liquid dibutyl phosphate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dibutyl phosphate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dibutyl phosphate, the person performing the operation should be informed of dibutyl phosphate's hazardous properties.

• Where exposure of an employee's body to liquid dibutyl phosphate may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with dibutyl phosphate should be removed promptly and not reworn until the dibutyl phosphate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid dibutyl phosphate may contact the eyes.

SANITATION

• Skin that becomes contaminated with dibutyl phosphate should be promptly washed or showered with soap or mild detergent and water to remove any dibutyl phosphate.

• Employees who handle liquid dibutyl phosphate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dibutyl phosphate may occur and

control methods which may be effective in each case:

Operation	Controls
Use as a catalyst in manufacture of phenolic and urea resins	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in metal separation and extraction	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid dibutyl phosphate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid dibutyl phosphate gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid dibutyl phosphate soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of dibutyl phosphate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid dibutyl phosphate has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid dibutyl phosphate is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Dibutyl phosphate may be disposed of by absorbing in vermiculite, dry sand, earth, or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dibutyl Phosphate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hawley, G. G. (ed.): *The Condensed Chemical Dictionary* (8th ed. rev.), Van Nostrand Reinhold, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR DIBUTYL PHOSPHATE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
10 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
125 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 125 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dibutylphthalate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_4(CO_2C_4H_9)_2$
- Synonyms: DBP; dibutyl 1,2-benzenedicarboxylate
- Appearance and odor: Colorless, oily liquid with a very weak, aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dibutylphthalate is 5 milligrams of dibutylphthalate per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dibutylphthalate can affect the body if it is swallowed, comes in contact with the eyes or skin, or is inhaled as a mist or spray.

- **Effects of overexposure**

Swallowing dibutylphthalate may cause nausea, dizziness, light sensitivity, and watering and redness of the eyes. Overexposure to hot vapors or mists of dibutylphthalate may cause nose and throat irritation.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dibutylphthalate.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to dibutylphthalate at potentially hazardous levels.

- **Summary of toxicology**

Extensive experience with dibutylphthalate as an insect repellant has shown that it is relatively non-irritating to the skin, eyes, and mucous membranes. Aerosols from heated dibutylphthalate may cause irritation of the eyes and upper respiratory tract. In one report of a human case, accidental ingestion of ten grams of this compound by a chemical operator produced nausea and dizziness with lacrimation, photophobia, and conjunctivitis, but recovery was prompt and uneventful. Animal experiments to determine dermal and oral toxicity of dibutylphthalate showed that extremely high doses were considered necessary to produce toxic effects. Dibutylphthalate was found to be teratogenic by intraperitoneal injection of doses representing 1/10, 1/8, and 1/5 of the LD50 value into female rats at the 5th, 10th, and 15th day of gestation. This probably is of no significance in industrial exposures.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 278
  2. Boiling point (760 mm Hg): 335 C (635 F)
  3. Specific gravity (water = 1): 1.05
  4. Vapor density (air = 1 at boiling point of dibutylphthalate): 9.6
  5. Melting point: −37 C (−35 F)
  6. Vapor pressure at 20 C (68 F): Less than 0.01 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.45
  8. Evaporation rate (butyl acetate = 1): Almost zero
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving dibutylphthalate.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

4. Special precautions: None

- **Flammability**

1. Flash point: 157 C (315 F) (closed cup)
2. Autoignition temperature: 403 C (757 F)
3. Flammable limits in air, % by volume: Lower: 0.5 (calculated at flash point)
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

According to Grant, "contact with the surface of human eyes has occurred by accidental droplet splash as well as by experimental application, and this has caused immediate, severe, stinging pain. The pain stimulated profuse tearing, which washed the oily liquid away, and the eyes were not appreciably damaged."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of dibutylphthalate on a filter, followed by extraction with carbon disulfide, and gas chromatographic analysis. An analytical method for dibutylphthalate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when the fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use splash-proof safety goggles where liquid dibutylphthalate may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dibutylphthalate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during spray application of polyvinyl acetate surface coatings by spraying, dipping, or crushing	Local exhaust ventilation; personal protective equipment
Liberation during spray application of polyester and epoxy resins	Local exhaust ventilation; personal protective equipment
Liberation during hand and dip applications of polyvinyl acetate, and polyester and epoxy resins	General dilution ventilation
Liberation during molding and forming of cellulose acetate butyrate, acetate, propionate, and polyvinyl acetate	Local exhaust ventilation; personal protective equipment
Liberation during application of polyvinyl acetate adhesives, both solvent and hot-melt types	Local exhaust ventilation; personal protective equipment
Liberation during manufacture of nitrile rubber; during molding of polyester and epoxy articles	General dilution ventilation
Liberation during manufacture of polyvinyl acetate surface coatings	General dilution ventilation
Use during spray application of nitrocellulose lacquer surface coatings, including paper coatings	Local exhaust ventilation

Operation	Controls
Liberation during forming of ethyl cellulose articles; during production of polyvinyl acetate; during production of cellulose acetate butyrate, cellulose acetate propionate, and polyvinyl acetate adhesives	General dilution ventilation
Liberation during brush application of nitrocellulose surface coatings; during manufacture of polyester and epoxy resins; during manufacture of nitrocellulose surface coatings	General dilution ventilation
Liberation during manufacture of explosives and propellants	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If dibutylphthalate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention if any discomfort continues. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If dibutylphthalate saturates the clothing, remove and clean the clothing before wearing it again. Wash any dibutylphthalate from the skin regularly, particularly when there has been much skin contact. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of dibutylphthalate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dibutylphthalate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing respiratory protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dibutylphthalate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber.

• Waste disposal methods:

Dibutylphthalate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dibutylphthalate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Karel, L., et al.: "The Intraperitoneal Toxicity of Some Glycols, Glycol Ethers, Glycol Esters, and Phthalates in Mice," *Journal of Pharmacology and Experimental Therapeutics*, 90:338-347, 1947.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Singh, A. R., et al.: "Teratogenicity of Phthalate Esters in Rats," *Journal of Pharmaceutical Sciences*, 61:51-55, 1972.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Dibutylphthalate*, New York, 1971.

RESPIRATORY PROTECTION FOR DIBUTYLPHTHALATE

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
250 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
9300 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 9300 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for o-Dichlorobenzene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: 1,2-$C_6H_4Cl_2$
- Synonyms: 1,2-Dichlorobenzene; o-dichlorobenzol
- Appearance and odor: Colorless to pale yellow liquid with a pleasant aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for o-dichlorobenzene is a ceiling of 50 parts of o-dichlorobenzene per million parts of air (ppm). This may also be expressed as 300 milligrams of o-dichlorobenzene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

o-Dichlorobenzene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may also be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: o-Dichlorobenzene vapor may cause irritation of the upper respiratory tract and eyes. Higher concentrations may cause drowsiness, unconsciousness, and death. The liquid may cause burning of the skin. The liquid may also cause burning of the eyes with tissue damage.

2. Long-term Exposure: Prolonged or repeated contact with o-dichlorobenzene may cause skin irritation. Prolonged or repeated inhalation of high concentrations of vapor might cause liver or kidney injury.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to o-dichlorobenzene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to o-dichlorobenzene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from o-dichlorobenzene exposure.

—Liver disease: o-Dichlorobenzene is known as a liver toxin in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: o-Dichlorobenzene is known as a kidney toxin in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: o-Dichlorobenzene may cause sensitization dermatitis and blistering of the skin . Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

o-Dichlorobenzene vapor at high concentrations is toxic to the liver and kidneys in animals. Rats died from exposure to 977 ppm for 7 hours, but survived when exposed for only 2 hours; animals survived exposure to 539 ppm for 3 hours and at necropsy showed marked centrolobular necrosis of the liver, as well as cloudy swelling of the tubular epithelium of the kidneys. Several species of animals exposed repeatedly to 93 ppm for 7 hours daily showed no adverse effects. The liquid instilled in the rabbit eye produced apparent distress and slight conjunctival irritation. Eye irritation is not

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

usually evident below 20 ppm but becomes noticeable at 25 to 30 ppm and painful to some at 60 to 100 ppm if exposures are for more than a few minutes duration. Some acclimatization may occur, but its extent is not great. Workers exposed daily to an average of 15 ppm showed no indication of injury. The liquid left on the skin may produce blistering. Sensitization dermatitis has been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 147
  2. Boiling point (760 mm Hg): 180 C (356 F)
  3. Specific gravity (water = 1): 1.3
  4. Vapor density (air = 1 at boiling point of o-dichlorobenzene): 5.1
  5. Melting point: −17.6 C (0.5 F)
  6. Vapor pressure at 20 C (68 F): 1.2 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.015
  8. Evaporation rate (butyl acetate = 1): Less than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat.
  2. Incompatibilities: Contact with strong oxidizers or with hot aluminum or aluminum alloys may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, chlorine, and carbon monoxide) may be released in a fire involving o-dichlorobenzene.
  4. Special precautions: Liquid o-dichlorobenzene will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 66 C (151 F) (closed cup)
  2. Autoignition temperature: 648 C (1198 F)
  3. Flammable limits in air, % by volume: Lower: 2.2; Upper: 9.2
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: 2 to 4 ppm, according to the AIHA *Hygienic Guide*; 50 ppm, according to May and Patty.
  2. Eye Irritation Level: 20 to 30 ppm according to the AIHA *Hygienic Guide*.
  3. Evaluation of Warning Properties: Since the odor threshold of o-dichlorobenzene and the concentration causing eye irritation are at or below the permissible exposure, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of o-dichlorobenzene. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure o-dichlorobenzene may be used. An analytical method for o-dichlorobenzene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6). ical Methods for Set J" (order number PB 263 959).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid o-dichlorobenzene.
- Clothing wet with liquid o-dichlorobenzene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of o-dichlorobenzene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the o-dichlorobenzene, the person performing the operation should be informed of o-dichlorobenzene's hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid o-dichlorobenzene should be removed promptly and not reworn until the o-dichlorobenzene is removed from the clothing.
• Employees should be provided with and required to use splash-proof safety goggles where liquid o-dichlorobenzene may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid o-dichlorobenzene should be promptly washed or showered with soap or mild detergent and water to remove any o-dichlorobenzene.
• Employees who handle liquid o-dichlorobenzene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to o-dichlorobenzene may occur and control methods which may be effective in each case:

Operation	Controls
Use in cleaning and degreasing of metal, leather, wool, paper, dry cleaning, brick, and upholstery	General dilution ventilation; personal protective equipment
Use as fumigant for poultry houses and stockyards for termites, moths, and beetles	Personal protective equipment
Use in application or removal of surface coatings	General dilution ventilation; personal protective equipment
Use in maintenance of equipment containing heat-transfer agents	Personal protective equipment
Use in organic synthesis in pesticides, herbicides, dyestuffs, and pharmaceuticals; chemical intermediate in manufacture of toluene-diisocyanate and extractive distillation of ethyl benzene from xylene; use as a deodorizing agent	General dilution ventilation
Use in textile dyeing operations	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If liquid o-dichlorobenzene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid o-dichlorobenzene gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid o-dichlorobenzene soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of o-dichlorobenzene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When o-dichlorobenzene has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If o-dichlorobenzene is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.

2. Ventilate area of spill or leak.

3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

o-Dichlorobenzene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "o-Dichlorobenzene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "o-Dichlorobenzene," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-54, o-Dichlorobenzene*, Washington, D.C., 1953.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• von Oettingen, W.F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., pp. 290-294, 1955.

RESPIRATORY PROTECTION FOR o-DICHLOROBENZENE

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
1700 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1700 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for p-Dichlorobenzene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: 1,4-$C_6H_4Cl_2$
- Synonyms: 1,4-Dichlorobenzene; dichlorocide; PDCB
- Appearance and odor: Colorless solid with a mothball-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for p-dichlorobenzene is 75 parts of p-dichlorobenzene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 450 milligrams of p-dichlorobenzene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

p-Dichlorobenzene can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to p-dichlorobenzene may cause irritation of the eyes, nose, and throat. It may also cause headache, swelling around the eyes, and runny nose. In addition, it may cause loss of appetite, nausea, vomiting, weight loss, and liver damage with yellow jaundice and death. Particles of solid p-dichlorobenzene in contact with the eyes may cause pain. The solid material also produces a burning sensation when held in contact with the skin with slight irritation. Warm fumes or strong solutions of p-dichlorobenzene may irritate the skin slightly on prolonged or repeated contact. Red blotching of the skin due to allergy to p-dichlorobenzene may occur.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to p-dichlorobenzene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to p-dichlorobenzene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver, respiratory tract, eyes, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Since liver damage has been observed in humans exposed to p-dichlorobenzene, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

—Urinalysis: Measurement of 2,5-dichlorophenol may serve as an index of exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

p-Dichlorobenzene vapor irritates the eyes and upper respiratory tract and is toxic to the liver. A group of animals repeatedly exposed to 798 ppm developed eye irritation, marked tremors, weakness, and loss of weight; some died. Reversible, nonspecific changes in the eye grounds were noted in rabbits, but there were no lens changes; other effects were centrolobular necrosis of the liver and mild damage to the lungs and kidneys. In five cases of intoxication from exposure to p-dichlorobenzene used as a mothproofing agent, one person with only moderate exposure complained of severe headache, periorbital swelling, and profuse rhinitis, which subsided 24 hours after cessation of exposure.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

The other four persons who had more prolonged exposure developed anorexia, nausea, vomiting, weight loss, and hepatic necrosis with jaundice; two died, and another developed cirrhosis. In 58 workers exposed for an average of 4.8 years (range, 8 months to 25 years) to p-dichlorobenzene at levels of 10 to 725 ppm, there was no evidence of hematologic effects; painful irritation of the eyes and nose was recorded at levels between 50 and 80 ppm, and it was severe at 160 ppm. Solid particles of p-dichlorobenzene in the human eye cause pain. The solid material produces a burning sensation when held in contact with the skin, but the resulting irritation is slight; warm fumes or strong solutions may irritate the intact skin slightly on prolonged or repeated contact. A case of allergic purpura induced by p-dichlorobenzene has been reported. In a study of workers engaged in synthesizing or otherwise handling p-dichlorobenzene, it was concluded that urinary excretion of 2,5-dichlorophenol (a metabolite of paradichlorobenzene) can serve as an index of exposure. Published studies of tests for carcinogenicity are considered to have been too short in duration and involved too few animals to have any significance.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 147
  2. Boiling point (760 mm Hg): 174 C (345 F)
  3. Specific gravity (water = 1): 1.46
  4. Vapor density (air = 1 at boiling point of p-dichlorobenzene): 5.1
  5. Melting point: 53 C (127 F)
  6. Vapor pressure at 20 C (68 F): 0.4 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.008
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving p-dichlorobenzene.
  4. Special precautions: Liquid p-dichlorobenzene will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 65.6 C (150 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Lower: 2.5 (calculated at flash point)
  4. Extinguishant: Foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: Patty states that "p-dichlorobenzene has a very distinctive aromatic odor. The threshold of detection will vary from 15 to 30 ppm in air. The odor becomes very strong at concentrations between 30 and 60 ppm .... It should be recognized, however, that a person may become sufficiently accustomed to the odor to tolerate high concentrations."
  2. Irritation Levels: Patty states that p-dichlorobenzene "is painful to the eyes and nose at concentrations of 80 to 160 ppm. Above 160 ppm, it is intolerable to any person who has not worked in it long enough to have had some adaptation."
  3. Evaluation of Warning Properties: Through its odor and irritant effects, p-dichlorobenzene can be detected within three times the permissible exposure limit. For the purposes of this guideline, therefore, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure p-dichlorobenzene may be used. An analytical method for p-dichlorobenzene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which

includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid particles or vapors from the surface of hot p-dichlorobenzene.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where p-dichlorobenzene or liquids containing p-dichlorobenzene may contact the eyes.

SANITATION

• Workers subject to skin contact with p-dichlorobenzene should wash any areas of the body which may have contacted p-dichlorobenzene at the end of each work day.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to p-dichlorobenzene may occur and control methods which may be effective in each case:

Operation	Controls
Formulation for use in moth control; as a deordorant for garbage and rest rooms; as an insecticide for control of fruit borers and ants; use in organic synthesis for preparation of dye intermediates	General dilution ventilation; local exhaust ventilation; personal protective equipment
Manufacture of p-dichlorobenzene	General dilution ventilation; local exhaust ventilation; personal protective equipment
Application as an insecticide, air deordorant, moth and mildew preventive, and household fumigant	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If p-dichlorobenzene or liquids containing p-dichlorobenzene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If p-dichlorobenzene or liquids containing p-dichlorobenzene get on the skin, wash the contaminated skin using soap or mild detergent and water. If p-dichlorobenzene or liquids containing p-dichlorobenzene penetrate through the clothing, remove the clothing and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of p-dichlorobenzene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When p-dichlorobenzene has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If p-dichlorobenzene is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dispose in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device as in below or deposit in a secured sanitary landfill.

• Waste disposal methods:

p-Dichlorobenzene may be disposed of:

1. By making packages of p-dichlorobenzene in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving p-dichlorobenzene in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

3. By disposal in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "p-Dichlorobenzene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "p-Dichlorobenzene," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• *American National Standard Acceptable Concentrations - p-Dichlorobenzene*: ANSI-Z37.27-1970, American National Standards Institute, Inc., New York, 1970.

• Cotter, L. H.: "Paradichlorobenzene Poisoning from Insecticides," *New York State Journal of Medicine*, 53:1690-1692, 1953.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hollingsworth, R. L., et al.: "Toxicity of Paradichlorobenzene - Determinations on Experimental Animals and Human Subjects," *A.M.A. Archives of Industrial Health*, 14:138-147, 1956.

• International Agency for Research on Cancer: *Some Anti-Thyroid and Related Substances, Nitrofurans and Industrial Chemicals*, Vol. 7 of *IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man*, Lyon, France, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Nalbandian, R. M., and Pearce, J. F.: "Allergic Purpura Induced by Exposure to p-Dichlorobenzene," *Journal of the American Medical Association*, 194:238-239, 1965.

• Pagnotto, L. D., and Walkley, J. E.: "Urinary Dichlorophenol as an Index of Para-Dichlorobenzene Exposure," *American Industrial Hygiene Association Journal*, 26:137-142, 1965.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR p-DICHLOROBENZENE

Condition	Minimum Respiratory Protection* Required Above 75 ppm
Vapor Concentration	
1,000 ppm or less	A chemical cartridge respirator with a full facepiece, an organic vapor cartridge(s), and dust filter. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1,3-Dichloro-5,5-Dimethylhydantoin

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_5H_6Cl_2N_2O_2$
- Synonyms: Halane; dactin
- Appearance and odor: White solid with a chlorine-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,3-dichloro-5,5-dimethylhydantoin is 0.2 milligram of 1,3-dichloro-5,5-dimethylhydantoin per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,3-Dichloro-5,5-dimethylhydantoin can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: This chemical is a chlorine bleach which is activated by moisture and may irritate the eyes, nose, throat, lungs, and skin.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,3-dichloro-5,5-dimethylhydantoin.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,3-dichloro-5,5-dimethylhydantoin at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,3-dichloro-5,5-dimethylhydantoin exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1,3-dichloro-5,5-dimethylhydantoin might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,3-Dichloro-5,5-dimethylhydantoin powder in contact with water yields hypochlorous acid, which is an eye and mucous membrane irritant. The LD50 for rats, when administered orally as a 10% aqueous suspension, was 542 mg/kg; at necropsy, gastrointestinal hemorrhages were found. There is a single report of workmen exposed to an average concentration of 1.97 mg/m^3 experiencing marked respiratory irritation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 197
2. Boiling point (760 mm Hg): Not available
3. Specific gravity (water = 1): 1.5
4. Vapor density (air = 1 at boiling point of 1,3-dichloro-5,5-dimethylhydantoin): 6.8
5. Melting point: 130 C (266 F)
6. Vapor pressure at 20 C (68 F): Not available
7. Solubility in water, g/100 g water at 20 C (68 F): 0.20
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Dry 1,3-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

dichloro-5,5-dimethylhydantoin decomposes with formation of toxic gases at 202 – 210 C (395 – 410 F). If material is wet, it will decompose at lower temperatures.

2. Incompatibilities: Contact with water, strong acids, and easily oxidized materials such as ammonium salts, sulfides, etc., may cause fires and explosions and formation of toxic fumes of chlorine and nitrogen trichloride.

3. Hazardous decomposition products: Toxic gases and vapors (such as chlorine, hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving 1,3-dichloro-5,5-dimethylhydantoin.

4. Special precautions: 1,3-Dichloro-5,5-dimethylhydantoin will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 174 C (346 F)
2. Autoignition temperature: Not available
3. Flammable limits in air, % by volume: Not available
4. Extinguishant: Carbon dioxide, dry chemical

• **Warning properties**

1,3-Dichloro-5,5-dimethylhydantoin is a powder, but in the presence of moisture chlorine gas is released. May states that the odor threshold of chlorine is .01 ppm, which is well below the permissible exposure of 1 ppm. Chlorine has adequate warning properties.

Stecher reports that the chlorine liberated upon the decomposition of 1,3-dichloro-5,5-dimethylhydantoin may produce irritation of the eyes and mucous membranes. Patty reports that men can work without interruption in an environment containing 3 to 6 mg/m³ of chlorine, but exposures to concentrations of 10 to 20 mg/m³ causes "a stinging or burning sensation in the eyes . . . ." Eye protection is recommended for any possibility of contact in the personal protection section.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for 1,3-dichloro-5,5-dimethylhydantoin had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid or liquids containing 1,3-dichloro-5,5-dimethylhydantoin.

• If employees' clothing may have become contaminated with solid 1,3-dichloro-5,5-dimethylhydantoin, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with solid or liquids containing 1,3-dichloro-5,5-dimethylhydantoin should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1,3-dichloro-5,5-dimethylhydantoin from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1,3-dichloro-5,5-dimethylhydantoin, the person performing the operation should be informed of 1,3-dichloro-5,5-dimethylhydantoin's hazardous properties.

• Non-impervious clothing which becomes contaminated with solid or liquids containing 1,3-dichloro-5,5-dimethylhydantoin should be removed promptly and not reworn until the 1,3-dichloro-5,5-dimethylhydantoin is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquids containing 1,3-dichloro-5,5-dimethylhydantoin contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solid or liquids containing 1,3-dichloro-5,5-dimethylhydantoin, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with solid or liquids containing 1,3-dichloro-5,5-dimethylhydantoin should be promptly washed or showered with soap or mild detergent and water to remove any 1,3-dichloro-5,5-dimethylhydantoin.

• Employees who handle solid or liquids containing 1,3-dichloro-5,5-dimethylhydantoin should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,3-dichloro-5,5-dimethylhydantoin may occur and control methods which may be effective in each case:

Operation	Controls
Use as a bactericide, sporicide, or sanitizer in swimming pools, dairies, laundries, restaurants, cutting oils, and pharmaceutical industry; as a general cleaner	General dilution ventilation; personal protective equipment
Use as a mild chlorinating agent in organic synthesis	Process enclosure; local exhaust ventilation; general dilution ventilation
Liberation during use as a rubber retarder	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as a bleaching agent in commercial laundries	General dilution ventilation; personal protective equipment
Use as stabilizer, discoloration preventer, and catalyst in polymer industry; use to emboss or texturize resinous sheet preparations	Process enclosure; local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 1,3-dichloro-5,5-dimethylhydantoin gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid or liquids containing 1,3-dichloro-5,5-dimethylhydantoin get on the skin, promptly flush the contaminated skin using soap or mild detergent and water. If liquids containing 1,3-dichloro-5,5-dimethylhydantoin soak through the clothing, remove the clothing promptly and flush the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1,3-dichloro-5,5-dimethylhydantoin, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 1,3-dichloro-5,5-dimethylhydantoin has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If 1,3-dichloro-5,5-dimethylhydantoin is spilled, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill.
3. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood.) Small quantities may also be slowly added to large amounts of water and flushed into a sewer. Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

1,3-Dichloro-5,5-dimethylhydantoin may be disposed of:

1. By making packages of 1,3-dichloro-5,5-dimethylhydantoin in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving 1,3-dichloro-5,5-dimethylhydantoin in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. Small quantities may be slowly added to large amounts of water and flushed into a sewer.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1,3-Dichloro-5,5-Dimethylhydantoin," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• BASF Wyandotte Corporation: *Material Safety Data Sheet - Halane (1,3-Dichloro-5,5-Dimethylhydantoin)*, Technical Inquiry Section, Wyandotte, Michigan.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR 1,3-DICHLORO-5,5-DIMETHYLHYDANTOIN

Condition	Minimum Respiratory Protection* Required Above 0.2 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any chemical cartridge respirator with a full facepiece, chlorine cartridge(s), and dust filter(s). A gas mask with a chin-style or a front- or back-mounted chlorine canister and dust filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against chlorine and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1,1-Dichloro-1-Nitroethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CCl_2NO_2$
- Synonyms: None
- Appearance and odor: Colorless liquid with an unpleasant odor that causes tears.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,1-dichloro-1-nitroethane is a ceiling of 10 parts of 1,1-dichloro-1-nitroethane per million parts of air (ppm). This may also be expressed as 60 milligrams of 1,1-dichloro-1-nitroethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,1-Dichloro-1-nitroethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure of animals has produced severe irritation of the lungs with severe breathing difficulties. These breathing difficulties may be delayed in onset. Liver, heart, kidney, and blood vessel damage were also reported in animals. In addition, eye and skin irritation have been reported in animals.

- **Reporting Signs and Symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,1-dichloro-1-nitroethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,1-dichloro-1-nitroethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,1-dichloro-1-nitroethane exposure.

—Chronic respiratory disease: 1,1-Dichloro-1-nitroethane causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1,1-dichloro-1-nitroethane might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: 1,1-Dichloro-1-nitroethane causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: 1,1-Dichloro-1-nitroethane causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Cardiovascular disease: 1,1-Dichloro-1-nitroethane causes heart damage in animals. In persons with impaired cardiovascular function, the inhalation of 1,1-dichloro-1-nitroethane might cause exacerbation of pre-existing disorders.

—Skin disease: 1,1-Dichloro-1-nitroethane can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,1-Dichloro-1-nitroethane vapor is a pulmonary, skin, and eye irritant in animals. It also causes liver, kidney, and heart damage in animals. At high concentrations animals showed lacrimation, increased nasal secretion,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

sneezing, coughing, pulmonary rales, and weakness. Exposure of rabbits to levels as low as 52 ppm for 18-½ hours was fatal. Autopsies on animals exposed to more than 170 ppm for over 30 minutes revealed pulmonary edema and hemorrhage, with damage to the heart, liver, and kidneys. Application of the liquid to the skin of rabbits caused irritation and edema. No human experience has been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 144
2. Boiling point (760 mm Hg): 125 C (257 F)
3. Specific gravity (water = 1): 1.42
4. Vapor density (air = 1 at boiling point of 1,1-dichloro-1-nitroethane): 5.0
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): 15 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.25
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Overheating in closed containers may cause explosions.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen, hydrogen chloride, and carbon monoxide) may be released in a fire involving 1,1-dichloro-1-nitroethane.
4. Special precautions: Liquid 1,1-dichloro-1-nitroethane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 58 C (136 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of 1,1-dichloro-1-nitroethane.
2. Eye Irritation Level: The *Handbook of Organic Industrial Solvents* states that this substance "may cause irritation of eyes and nose at twice threshold limit and, at higher concentrations, lung injury." Grant points out that it "has an irritant, lacrimogenic effect which gives adequate warning to prevent dangerous exposure."
3. Evaluation of Warning Properties: Although 1,1-dichloro-1-nitroethane produces irritant effects at only twice the permissible exposure limit, it is treated as a substance with poor warning properties, since the permissible exposure limit is a ceiling concentration which was set "to prevent serious injury in man."

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of 1,1-dichloro-1-nitroethane. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,1-dichloro-1-nitroethane may be used. An analytical method for 1,1-dichloro-1-nitroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 1,1-dichloro-1-nitroethane.

• Clothing wet with liquid 1,1-dichloro-1-nitroethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1,1-dichloro-1-nitroethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1,1-dichloro-1-nitroethane, the person performing the operation should be informed of 1,1-dichloro-1-nitroethane's hazardous properties.
• Non-impervious clothing which becomes contaminated with 1,1-dichloro-1-nitroethane should be removed promptly and not reworn until the 1,1-dichloro-1-nitroethane is removed from the clothing.
• Employees should be provided with and required to use splash-proof safety goggles where liquid 1,1-dichloro-1-nitroethane may contact the eyes.

SANITATION

• Skin that becomes contaminated with 1,1-dichloro-1-nitroethane should be promptly washed or showered with soap or mild detergent and water to remove any 1,1-dichloro-1-nitroethane.
• Employees who handle liquid 1,1-dichloro-1-nitroethane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,1-dichloro-1-nitroethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as an insecticidal fumigant for grain (this product is not in common use at this time)	Material substitution

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If liquid 1,1-dichloro-1-nitroethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid 1,1-dichloro-1-nitroethane gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid 1,1-dichloro-1-nitroethane soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of 1,1-dichloro-1-nitroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When liquid 1,1-dichloro-1-nitroethane has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If liquid 1,1-dichloro-1-nitroethane is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. 1,1-Dichloro-1-nitroethane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.
• Waste disposal method:
1,1-Dichloro-1-nitroethane may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1,1-Dichloro-1-Nitroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents, Technical Guide No. 6* (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Machle, W., et al.: "The Physiological Response of Animals to Certain Chlorinated Mononitroparaffins," *Journal of Industrial Hygiene and Toxicology*, 27:95-102, 1945.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

RESPIRATORY PROTECTION FOR 1,1-DICHLORO-1-NITROETHANE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
150 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 150 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dichlorodifluoromethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CCl_2F_2
- Synonyms: Refrigerant 12; Freon 12; propellant 12; Halon 122
- Appearance and odor: Colorless gas with a characteristic ether-like odor that is detectable only in concentrations well above the permissible exposure (above 20% by volume).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dichlorodifluoromethane is 1000 parts of dichlorodifluoromethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 4950 milligrams of dichlorodifluoromethane per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dichlorodifluoromethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to dichlorodifluoromethane may cause dizziness, involuntary trembling, unconsciousness, and death. It may also cause irregular heartbeat. If the liquid gets on the skin or in the eyes, it may cause frostbite.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dichlorodifluoromethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dichlorodifluoromethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from dichlorodifluoromethane exposure.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrhythmias, the inhalation of dichlorodifluoromethane might cause exacerbation of disorders of the conduction mechanism due to its sensitizing effects on the myocardium.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Dichlorodifluoromethane vapor is a narcotic and can cause asphyxia at very high concentrations. At 800,000 ppm rats were deeply anesthetized, but 4 to 6 hours' exposure produced no permanent effects. At 200,000 ppm dogs and monkeys showed only tremors, salivation, and lacrimation. Inhalation by man at 150,000 ppm produces unconsciousness, while dizziness occurs at 50,000 ppm. Sniffing aerosols of fluorochlorinated hydrocarbons has caused sudden death by cardiac arrest, probably due to sensitization of the myocardium. In liquid form this substance may cause frostbite.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 120.9
2. Boiling point (760 mm Hg): −29.8 C (−21.6 F)
3. Specific gravity (water = 1): 1.49 (at boiling

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

point)

4. Vapor density (air = 1 at boiling point of dichlorodifluoromethane): 4.2

5. Melting point: −157.7 C (−252 F)

6. Vapor pressure at 20 C (68 F): 5.7 atm.

7. Solubility in water, g/100 g water at 20 C (68 F): 0.008

8. Evaporation rate (butyl acetate = 1): 380

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Dichlorodifluoromethane reacts with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, and magnesium.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and hydrogen fluoride) may be released when dichlorodifluoromethane decomposes.

4. Special precautions: Liquid dichlorodifluoromethane will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Since dichlorodifluoromethane is practically odorless and is not an irritant, it is treated as a material with poor warning properties.

Grant states that "in ordinary occupational or domestic exposure to the gas, there is neither ocular nor respiratory irritation. Dogs, monkeys, and guinea pigs exposed to 20% of the gas in air for several hours a day for several days showed temporary intoxication with tremors, ataxia, and associated tendency to stare, salivate, and lacrimate, but no cumulative toxic effect and no specific ocular disturbance. The speed of reflex closure of the eyes is such that it seems extremely unlikely that any seriuos injury would result from an accidental spray of this substance in the eyes of human beings."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for dichlorodifluoromethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming wet with liquid dichlorodifluoromethane or from becoming frozen from contact with vessels containing dichlorodifluoromethane.

• Any clothing which becomes wet with liquid dichlorodifluoromethane should be removed immediately and not reworn until the dichlorodifluoromethane has evaporated from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid dichlorodifluoromethane may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dichlorodifluoromethane may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of aerosols for cosmetics,	General dilution ventilation; personal

pharmaceuticals, insecticides, paints, adhesives, and cleaners; use in manufacture and extensive use as a refrigerant in home and commercial applications	protective equipment
Use as a blowing agent for cellular polymers; use as a solvent or diluent in fumigants for food sterilization; in paints and varnish removers, and in polymerization processes	General dilution ventilation; personal protective equipment
Use as a foaming agent in fire extinguishing, aerosols, for surfactants; use in Immersion Quick Freezing of food products	General dilution ventilation; personal protective equipment
Use in water purification; copper and aluminum purification, petroleum recovery, and in manufacture of glass bottles	General dilution ventilation; personal protective equipment
Use in regulating devices for leak detection; in thermal expansion valves; use in manufacture of materials for electrical applications as insulators and generator windings	General dilution ventilation; personal protective equipment
Use in organic synthesis of Freons, and a polymerization catalysts; use as a working fluid for heat pumps and in hydraulic fluids	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid dichlorodifluoromethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid dichlorodifluoromethane gets on the skin, immediately flush the skin with water if the dichlorodifluoromethane has not already evaporated. If liquid dichlorodifluoromethane soaks through the clothing, remove the clothing immediately and flush the skin with water. Do not use hot water for flushing. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of dichlorodifluoromethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If dichlorodifluoromethane is leaked, the following steps should be taken:

1. Ventilate area of spill or leak to disperse gas.
2. Stop flow of gas.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dichlorodifluoromethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Dichlorodifluoromethane," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• E. I. DuPont de Nemours and Company: "Freon Compounds and Safety," *Freon Product Information.*

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products5(3rd ed.), Williams and Wilkins, Baltimore, 1969.*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Reinhardt, C. F., et al.: "Cardiac Arrhythmias and Aerosol 'Sniffing'," *Archives of Environmental Health*, 22:265-279, 1971.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Material Safety Data Sheet - Dichlorodifluoromethane*, New York, 1972.

RESPIRATORY PROTECTION FOR DICHLORODIFLUOROMETHANE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Gas Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a half facepiece operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 50,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1,1-Dichloroethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3CHCl_2
- Synonyms: Asymmetrical dichloroethane; ethylidene chloride; 1,1-ethylidene dichloride
- Appearance and odor: Colorless liquid with a chloroform-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,1-dichloroethane is 100 parts of 1,1-dichloroethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 400 milligrams of 1,1-dichloroethane per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has recommended for 1,1-dichloroethane a Threshold Limit Value of 200 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,1-Dichloroethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Breathing 1,1-dichloroethane vapor may cause drowsiness and unconsciousness. It might also cause damage to the liver, kidneys, and lungs. Splashing the liquid in the eyes may cause irritation.

2. Long-term Exposure: Prolonged, confined, or repeated skin contact with 1,1-dichloroethane can produce a slight burn.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,1-dichloroethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,1-dichloroethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,1-dichloroethane exposure.

—Skin disease: 1,1-Dichloroethane can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although 1,1-dichloroethane is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although 1,1-dichloroethane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1,1-dichloroethane might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,1-Dichloroethane vapor is a narcotic. Rats exposed to 32,000 ppm for 30 minutes did not survive. The most consistent findings in animals exposed to concentrations

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

of above 8,000 ppm for up to 7 hours were pathologic changes in the kidney and liver, and at much higher concentrations, near 64,000 ppm, damage to the lungs as well. Repeated daily exposure of several species of animals to 1,000 ppm resulted in no pathologic or hematologic changes. The liquid applied to the intact or abraded skin of rabbits produced slight edema and very slight necrosis after six daily applications. Instilled in the eyes of rabbits there was immediate, moderate conjunctival irritation and swelling which subsided within a week. There have been no reported cases of human overexposure by inhalation; prolonged, confined, or repeated skin contact can produce a slight burn.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 99
  2. Boiling point (760 mm Hg): 57.3 C (135 F)
  3. Specific gravity (water = 1): 1.2
  4. Vapor density (air = 1 at boiling point of 1,1-dichloroethane): 3.4
  5. Melting point: −96.7 C (−142 F)
  6. Vapor pressure at 20 C (68 F): 182 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Less than 0.1
  8. Evaporation rate (butyl acetate = 1): 11.6
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong caustics will cause formation of flammable and toxic acetaldehyde gas.
  3. Hazardous decomposition products: Toxic gases and vapors (such as vinyl chloride, hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving 1,1-dichloroethane.
  4. Special precautions: 1,1-Dichloroethane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −8.5 C (17 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Lower: 5.9; Upper: 15.9
  4. Extinguishant: Foam, dry chemical, carbon dioxide
- **Warning properties**

The AIHA *Hygienic Guide* reports that 1,1-dichloroethane has a distinctive, easily recognizable odor at the TLV.

1,1-Dichloroethane is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,1-dichloroethane may be used. An analytical method for 1,1-dichloroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 1,1-dichloroethane.
- Clothing wet with liquid 1,1-dichloroethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1,1-dichloroethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1,1-dichloroethane, the person performing the operation should be informed of 1,1-dichloroethane's hazardous properties.
- Any clothing which becomes wet with liquid 1,1-dichloroethane should be removed immediately and not

reworn until the 1,1-dichloroethane is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid 1,1-dichloroethane may contact the eyes.

SANITATION

• Skin that becomes wet with liquid 1,1-dichloroethane should be immediately washed or showered with soap or mild detergent and water to remove any 1,1-dichloroethane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,1-dichloroethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as dewaxer of mineral oils; extractant for heat-sensitive substances	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a fumigant	General dilution ventilation of work area; personal protective equipment
Use in manufacture of vinyl chloride by vapor phase cracking; use in manufacture of high vacuum rubber and silicon grease; use as a chemical intermediate	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 1,1-dichloroethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 1,1-dichloroethane gets on the skin, promptly flush the contaminated skin using soap or mild detergent and water. If 1,1-dichloroethane soaks through the clothing, remove the clothing immediately and flush the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1,1-dichloroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 1,1-dichloroethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 1,1-dichloroethane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. 1,1-Dichloroethane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of 1,1-dichloroethane vapors are permitted.

• Waste disposal method:

1,1-Dichloroethane may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1,1-Dichloroethane (Ethylidene Chloride)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "1,1-Dichloroethane (Ethylidene Chloride)," *Hygienic Guide Series*, Detroit, Michigan, 1971.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR 1,1-DICHLOROETHANE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
4000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contair breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1,2-Dichloroethylene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: ClCH = CHCl
- Synonyms: Acetylene dichloride; dioform; trans-acetylene dichloride; sym-dichloroethylene
- Appearance and odor: Colorless liquid with an ether-like, slightly acrid odor, like chloroform.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,2-dichloroethylene is 200 parts of 1,2-dichloroethylene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 790 milligrams of 1,2-dichloroethylene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,2-Dichloroethylene can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to 1,2-dichloroethylene may cause dizziness, drowsiness, and unconsciousness.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,2-dichloroethylene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,2-dichloroethylene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,2-dichloroethylene exposure.

—Liver disease: Although 1,2-dichloroethylene is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1,2-dichloroethylene might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,2-Dichloroethylene vapor is a narcotic and a mucous-membrane irritant. Variations in toxicity of the cis- as compared with the trans-form have been reported. A concentration of 39,000 ppm was lethal to guinea pigs, and narcosis was produced at 18,000 ppm. Dogs exposed to high concentrations of vapor developed superficial corneal turbidity which was reversible. No effects were observed in several species with repeated exposure for up to 6 months at 1000 ppm. It has been used as a general anesthetic in man; one industrial fatality was due to very high vapor inhalation in a small enclosure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 96.9
2. Boiling point (760 mm Hg): 45 to 60 C (113 to 140 F)
3. Specific gravity (water = 1): 1.27
4. Vapor density (air = 1 at boiling point of 1,2-dichloroethylene): 3.34
5. Melting point: −49 to −81.5 C (−56 to −115 F)
6. Vapor pressure at 20 C (68 F): 180 to 265 mm Hg

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

7. Solubility in water, g/100 g water at 20 C (68 F): 0.35 to 0.63

8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving 1,2-dichloroethylene.

4. Special precautions: 1,2-Dichloroethylene will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 2.2 to 3.9 C (36 to 39 F) (closed cup)

2. Autoignition temperature: 460 C (860 F) for trans-1,2-dichloroethylene

3. Flammable limits in air, % by volume: Lower: 9.7; Upper: 12.8

4. Extinguishant: Dry chemical, foam, carbon dioxide

• **Warning properties**

May reports an odor threshold of 0.085 ppm for dichloroethylene. For the purposes of this guideline, 1,2-dichloroethylene is treated as a material with adequate warning properties.

1,2-Dichloroethylene is an eye irritant, according to Grant, but the concentrations at which irritation occurs are not mentioned.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of 1,2-dichloroethylene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,2-dichloroethylene may be used. An analytical method for 1,2-dichloroethylene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 1,2-dichloroethylene.

• Clothing wet with liquid 1,2-dichloroethylene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1,2-dichloroethylene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1,2-dichloroethylene, the person performing the operation should be informed of 1,2-dichloroethylene's hazardous properties.

• Any clothing which becomes wet with liquid 1,2-dichloroethylene should be removed immediately and not reworn until the 1,2-dichloroethylene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid 1,2-dichloroethylene may contact the eyes.

SANITATION

• Skin that becomes wet with liquid 1,2-dichloroethylene should be promptly washed or showered with soap or mild detergent and water to remove any 1,2-dichloroethylene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,2-dichloroethylene may occur and control methods which may be effective in each case:

Operation	Controls
Use as a low-temperature solvent for heat-sensitive substances in extraction of caffeine, perfume oils, and fats from flesh of animals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in rubber and dye industries in extraction and application	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a direct solvent in gums, waxes, oils, camphor, and phenol; use in solvent mixtures for esters and ether derivatives, lacquers, resins, thermoplastics, and artificial fibers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis for polymers and telomers	Process enclosure; local exhaust ventilation; personal protective equipment
Use in miscellaneous applications as liquid dry cleaning agent, cleaning solution for printed circuit boards, food packaging adhesives, and germicidal fumigants	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 1,2-dichloroethylene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 1,2-dichloroethylene gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 1,2-dichloroethylene soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1,2-dichloroethylene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 1,2-dichloroethylene has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 1,2-dichloroethylene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. 1,2-Dichloroethylene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of 1,2-dichloroethylene vapors are permitted.

• Waste disposal method:

1,2-Dichloroethylene may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1.2-Dichloroethylene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., Jr.: "Improved Communication—Hygienic Standards for Daily Inhalation," *American Industrial Hygiene Association Quarterly*, 17:154, 1956.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck & Co., Inc., Rahway, New Jersey, 1968.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR 1,2-DICHLOROETHYLENE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
4000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dichloroethyl Ether

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(ClCH_2CH_2)_2O$
- Synonyms: Bis(2-chloroethyl)ether;2,2'-dichlorodiethyl ether
- Appearance and odor: Colorless liquid with a chlorinated solvent-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dichloroethyl ether is a ceiling level of 15 parts of dichloroethyl ether per million parts of air (ppm). This may also be expressed as 90 milligrams of dichloroethyl ether per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has recommended for dichloroethyl ether a Threshold Limit Value of 5 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dichloroethyl ether can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to dichloroethyl ether vapor may cause severe irritation of the eyes and nose with coughing, retching, and nausea. In animal experiments, dichloroethyl ether has caused severe irritation of the respiratory tract with severe breathing difficulties which can be delayed in onset. Animal experiments have also shown dichloroethyl ether vapor to be capable of causing drowsiness, dizziness, and unconsciousness at high concentrations. Liquid dichloroethyl ether placed in animal eyes has produced damage. Feeding this chemical to mice has been associated with an increased amount of liver tumors.

2. Long-term Exposure: Repeated exposure to dichloroethyl ether may cause bronchitis.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dichloroethyl ether.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dichloroethyl ether at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory tract, liver, and the central nervous system should be stressed.

—14" x 17" chest roentgenogram: Dichloroethyl ether causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Dichloroethyl ether is a severe pulmonary irritant in animals. Periodic surveillance is indicated.

2. Periodic Medical Examination: The above medical examinations are to be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or signs and symptoms of respiratory disease.

- **Summary of toxicology**

Dichloroethyl ether vapor is a severe respiratory irritant; high levels cause narcosis in animals. It is tumorigenic in animals. Repeated oral administration of 100 mg/kg daily to both sexes of two strains of mice for 80 weeks induced a significantly elevated incidence of tumors, mostly hepatomas. In guinea pigs, concentrations of 500 to 1000 ppm were fatal after 5 to 8 hours of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

exposure; there were immediate lacrimation and nasal irritation, followed by unsteadiness and coma; autopsy findings were pulmonary edema, hemorrhage and occasional complete consolidation. In experimental human exposure, 500 ppm caused intolerable irritation to the eyes and nose with cough, nausea and vomiting; at 100 ppm there was some irritation, while at 35 ppm there were no effects. Except for accidental inhalation of high concentrations, the chief hazard in industrial practice is mild bronchitis, which may be caused by repeated exposures to low concentrations. Both the liquid and a 10% solution dropped in the eye of a rabbit caused moderate discomfort, conjunctival irritation, and corneal injury which generally healed within 24 hours. On the skin of rabbits, the pure liquid had no local effect, but a sufficient amount penetrated the skin to cause death within a day.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 143
2. Boiling point (760 mm Hg): 178.2 C (353 F)
3. Specific gravity (water = 1): 1.2
4. Vapor density (air = 1 at boiling point of dichloroethyl ether): 4.9
5. Melting point: −52 C (−62 F)
6. Vapor pressure at 20 C (68 F): 0.4 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 1.1
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: At elevated temperatures containers may burst.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving dichloroethyl ether.
4. Special precautions: Dichloroethyl ether will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 55 C (131 F) (closed cup)
2. Autoignition temperature: 369 C (696 F)
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

1. Odor Threshold: According to Patty, "most people can detect the chemical at its threshold limit (15 ppm) by its odor."
2. Irritation Levels: Patty states that "Schrenk, Patty, and Yant exposed human volunteers to dichloroethyl ether. Brief exposure to concentrations above 550 ppm were very irritating to the eyes and nasal passages and were considered intolerable. They also caused coughing, retching, and nausea. At 260 and 100 ppm the irritating effects were still present to some extent but were not considered intolerable."
3. Evaluation of Warning Properties: Through its odor dichloroethyl ether can be detected at the permissible exposure limit. For the purposes of this guideline, therefore, dichloroethyl ether is treated as a substance with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of dichloroethyl ether. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure dichloroethyl ether may be used. An analytical method for dichloroethyl ether is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safe and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid dichloroethyl ether, where skin contact may occur.

• Clothing contaminated with dichloroethyl ether should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dichloroethyl ether from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dichloroethyl ether, the person performing the operation should be informed of dichloroethyl ether's hazardous properties.

• Where exposure of an employee's body to liquid dichloroethyl ether may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with dichloroethyl ether should be removed immediately and not reworn until the dichloroethyl ether is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid dichloroethyl ether may contact the eyes.

SANITATION

• Skin that becomes contaminated with dichloroethyl ether should be immediately washed or showered with soap or mild detergent and water to remove any dichloroethyl ether.

• Employees who handle dichloroethyl ether should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dichloroethyl ether may occur and control methods which may be effective in each case:

Operation	Controls
Use as solvent, dewaxing agent in petroleum industry and manufacture of oils, fats, waxes, gums, tars, resins, soaps, ethyl cellulose, paints, varnish, and lacquers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as scouring and penetrating agent in textile industry	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as fumigant in agricultural insecticide industry	Personal protective equipment
Use as chemical intermediate in synthesis during manufacture of pharmaceuticals, rubber chemicals, resins, plasticizers, and chemicals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as lead scavenger during production of gasoline engine anti-knock compounds	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid dichloroethyl ether gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid dichloroethyl ether gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid dichloroethyl ether soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of dichloroethyl ether, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid dichloroethyl ether has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dichloroethyl ether is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Dichloroethyl ether should not be allowed to enter a confined space, such as sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of dichloroethyl ether vapors are permitted.

• Waste disposal methods:

Dichloroethyl ether may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

ADDITIONAL INFORMATION

To find additional information on dichloroethyl ether, look up dichloroethyl ether in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dichloroethyl Ether," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Innes, J. R. M., et al.: "Bioassay of Pesticides and Industrial Chemicals for Tumorigenicity in Mice: A Preliminary Note," *Journal of the National Cancer Institute*, 42:1101-1114, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Dichloroethyl Ether*, New York, 1971.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 9, 1975.

RESPIRATORY PROTECTION FOR DICHLOROETHYL ETHER

Condition	Minimum Respiratory Protection* Required Above 15 ppm
Vapor Concentration	
150 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).**
	Any supplied-air respirator.**
	Any self-contained breathing apparatus.**
250 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 250 ppm*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of dichloroethyl ether; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 250 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Dichloromonofluoromethane (Refrigerant 21)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CHCl_2F$
- Synonyms: Refrigerant 21; Freon 21; Halon 112; dichlorofluoromethane
- Appearance and odor: Colorless liquid or gas with a slight ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Refrigerant 21 is 1000 parts of Refrigerant 21 per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 4200 milligrams of Refrigerant 21 per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Refrigerant 21 can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to Refrigerant 21 may cause drowsiness, unconsciousness, and death. Exposure to Refrigerant 21 may cause the heart to beat irregularly. If the liquid is spilled on the skin, it may cause frostbite.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Refrigerant 21.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Refrigerant 21 at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from Refrigerant 21 exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of Refrigerant 21 might cause exacerbation of symptoms due to its irritant properties.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrhythmias, the inhalation of Refrigerant 21 might cause exacerbation of disorders of the conduction mechanism due to its sensitizing effects on the myocardium.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Refrigerant 21 vapor is a respiratory irritant and causes asphyxia at extre . y high concentrations. Exposure to 400,000 ppm with 18% oxygen was fatal to guinea pigs; death was preceded by dyspnea, tremors, and convulsive movements but not narcosis. Animals died at 102,000 ppm with congested lungs, kidneys, and liver, but survived 52,000 ppm showing tremors, incoordination, and irregular breathing. In liquid form this substance may cause frostbite. Sniffing aerosols of fluorochlorinated hydrocarbons has caused sudden death by cardiac arrest, probably due to sensitization of the myocardium. Acute or chronic effects from human exposure have not been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 102.9

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

2. Boiling point (760 mm Hg): 8.9 C (48.1 F)
3. Specific gravity (water = 1): 1.37
4. Vapor density (air = 1 at boiling point of Refrigerant 21): 3.82
5. Melting point: −135 C (−211 F)
6. Vapor pressure at 20 C (68 F): Data not available
7. Solubility in water, g/100 g water at 20 C (68 F): 1
8. Evaporation rate (butyl acetate = 1): Much higher than 1

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Refrigerant 21 reacts with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, and magnesium.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and hydrogen fluoride) may be released when Refrigerant 21 decomposes.
4. Special precautions: Liquid Refrigerant 21 will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Since there is no available quantitative information relating warning properties to air concentrations of Refrigerant 21, this substance is treated as a material with poor warning properties.

Refrigerant 21 is not a known eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for Refrigerant 21 is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming wet with liquid Refrigerant 21.

• Any clothing which becomes wet with liquid Refrigerant 21 should be removed immediately and not reworn until the Refrigerant 21 has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid Refrigerant 21 may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Refrigerant 21 may occur and control methods which may be effective in each case:

Operation	Controls
Manufacture and use as an aerosol propellant in pharmaceuticals; use as a refrigerating agent; use as an industrial solvent in separation of fatty acids, of polymers	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a blowing agent for rigid foams and insulating foams	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a working fluid in Rankine cycle turbogenerators; use in water purification; use in organic synthesis in preparation of other Freons	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**
If liquid Refrigerant 21 gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid Refrigerant 21 gets on the skin, immediately flush the contaminated skin with water if the Refrigerant 21 has not already evaporated. If liquid Refrigerant 21 soaks through the clothing, remove the clothing immediately and flush the skin with water. Do not use hot water for skin flushing. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of Refrigerant 21, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When Refrigerant 21 has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If Refrigerant 21 is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If the gas is leaking, stop the flow.
3. If the liquid is spilled or leaked, allow to vaporize.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dichloromonofluoromethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Aviado, D. M. and Belej, M. A.: "Toxicity of Aerosol Propellants on the Respiratory and Circulatory Systems — I. Cardiac Arrhythmia in the Mouse," *Toxicology*, 2:31-42, 1974.
• E. I. DuPont de Nemours and Company: "Freon Compounds and Safety," *Freon Product Information*, Wilmington, Delaware, 1969.
• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Smyth, H. F., Jr.: "Improved Communication—Hygienic Standards for Daily Inhalation," *American Industrial Hygiene Association Quarterly*, 17:155, 1956.
• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*. U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR REFRIGERANT 21

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Gas Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 50,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dichlorotetrafluoroethane (Refrigerant 114)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $F_2ClCCClF_2$
- Synonyms: 1,2-Dichlorotetrafluoroethane; Freon 114; Refrigerant 114; Halon 242
- Appearance and odor: Colorless liquid or gas with a very slight ethereal odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Refrigerant 114 is 1000 parts of Refrigerant 114 per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 7000 milligrams of Refrigerant 114 per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Refrigerant 114 can affect the body if it is inhaled or if the liquid comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Breathing in very high concentrations may cause drowsiness and unconsciousness and may also cause the heart to beat irregularly or to stop suddenly. If the liquid gets on the skin or in the eyes, it may cause frostbite.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Refrigerant 114.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Refrigerant 114 at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from Refrigerant 114 exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of Refrigerant 114 might cause exacerbation of symptoms due to its irritant properties.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrhythmias, the inhalation of Refrigerant 114 might cause exacerbation of disorders of the conduction mechanism due to its sensitizing effects on the myocardium.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Refrigerant 114 vapor is a respiratory irritant and causes asphyxia at extremely high concentrations. Exposure to 200,000 ppm for 16 hours was fatal to dogs, while single 8-hour exposures produced tremors and convulsions but no fatalities; repeated exposures at 140,000 to 160,000 ppm for 8 hours caused incoordination, tremors, and occasionally convulsions, but all dogs survived. At 47,000 ppm guinea pigs developed respiratory irritation. Sniffing aerosols of fluorochlorinated hydrocarbons has caused sudden death by cardiac arrest, probably due to sensitization of the myocardium. The liquid spilled on the skin may produce frostbite.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 170.9
  2. Boiling point (760 mm Hg): 3.5 C (38.4 F)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

3. Specific gravity (water = 1): 1.44

4. Vapor density (air = 1 at boiling point of Refrigerant 114): 5.9

5. Melting point: −94 C (−137 F)

6. Vapor pressure at 20 C (68 F): 1444 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): 0.01

8. Evaporation rate (butyl acetate = 1). Higher than 1

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Refrigerant 114 reacts with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, and magnesium.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and hydrogen fluoride) may be released when Refrigerant 114 decomposes.

4. Special precautions: Liquid Refrigerant 114 will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Although Refrigerant 114 has a chloroform-like odor, no quantitative data are available relating warning properties to air concentrations. It is treated, therefore, as a material with poor warning properties.

Refrigerant 114 is not a known eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for Refrigerant 114 is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming wet with liquid Refrigerant 114.

• Any clothing which becomes wet with liquid Refrigerant 114 should be removed immediately and not reworn until the Refrigerant 114 has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid Refrigerant 114 may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Refrigerant 114 may occur and control methods which may be effective in each case:

Operation	Controls
Manufacture and use in aerosols with other Freons to lower vapor pressure and produce non-flammable aerosol propellants; use as a refrigerant in industrial cooling and airconditioning systems	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a blowing agent for cellular polymers; use as a solvent and diluent in polymerization of fluoro-olefins, cleaning and degreasing printed circuit boards, preparation of explosives, and extraction of volatile substances	General dilution ventilation; local exhaust ventilation; personal protective equipment

Use as a foaming agent in fire extinguishing and aerosols; in organic synthesis in preparation of uranium tetrafluoride, Freons, and polymer intermediates	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in inhibiting of metal erosion in hydraulic fluids; in strengthening glass bottles; in magnesium refining; and as a reflux liquid to assist heat removal	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid Refrigerant 114 gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid Refrigerant 114 gets on the skin, immediately flush the contaminated skin with water if the Refrigerant 114 has not already evaporated. If liquid Refrigerant 114 soaks through the clothing, remove the clothing immediately and flush the skin with water. Do not use hot water for skin flushing. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of Refrigerant 114, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When Refrigerant 114 has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If Refrigerant 114 is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If the gas is leaking, stop the flow.
3. If the liquid is spilled or leaked, allow to vaporize.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dichlorotetrafluoroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• E. I. DuPont de Nemours and Company: "Freon Compounds and Safety," *Freon Product Information*, Wilmington, Delaware, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Reinhardt, C. F., et al: "Cardiac Arrhythmias and Aerosol 'Sniffing'," *Archives of Environmental Health*, 22:265-279, 1971.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR REFRIGERANT 114

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Gas Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a half facepiece operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 50,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dichlorvos

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3O)_2POOCH=CCl_2$ or $C_4H_7Cl_2O_4P$
- Synonyms: DDVP; 2,2-dichlorovinyl dimethyl phosphate
- Appearance and odor: Colorless to amber liquid with a mild chemical odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dichlorvos is 1 milligram of dichlorvos per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dichlorvos can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: After inhalation of dichlorvos, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of vision, tearing, runny nose, headache, and watering of the mouth. After swallowing dichlorvos, loss of appetite, nausea, vomiting, abdominal cramps and diarrhea may appear within two hours. After skin absorption, sweating and twitching in the area of absorption may occur usually within 15 minutes to four hours. With severe intoxication by all routes, in addition to all the above symptoms, weakness, generalized twitching, and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, irregular or slow heart beat, convulsions, and coma may occur.

2. Long-term Exposure: Repeated exposure to dichlorvos may make a person more susceptible to the effects of this and related chemicals. Repeated exposure to concentrations which are too small to produce symptoms after a single exposure may result in the onset of symptoms.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dichlorvos.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dichlorvos at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system, and attention to the cholinesterase levels in the blood should be stressed. The skin should be examined for evidence of chronic disorders.

—Cholinesterase determination: Dichlorvos (DDVP) causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the serum and erythrocytes should be determined by using medically acceptable biochemical tests prior to any new period of exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determi-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

428

nation which should be performed quarterly or at any time overexposure is suspected or signs and symptoms of toxicity occur.

• **Summary of toxicology**

Dichlorvos (DDVP) is an anticholinesterase agent; absorption may occur from inhalation of the vapor or mist, from skin absorption of the liquid, or from ingestion. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nervous system, skeletal and smooth muscle, and secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms may occur promptly or may be delayed for up to 12 hours. After inhalation, respiratory and ocular effects are the first to appear, often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects, such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption, localized sweating and muscular fasciculations in the immediate area occur usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures and is increased by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels, and cardiac irregularities including complete heart block may occur; these effects may sometimes be reversed by establishing adequate pulmonary ventilation. Complete symptomatic recovery usually occurs within 1 week; increased susceptibility to the effects of anticholinesterase agents persists for weeks after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects. In a study of 13 workers exposed for 12 months to an average concentration of 0.7 mg/m^3, the erythrocyte cholinesterase activity was reduced by approximately 35%, and the serum cholinesterase activity was reduced by 60%; the results of other tests and of thorough medical examinations conducted at regular intervals were entirely normal.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 221
2. Boiling point (1 mm Hg): 77 C (170 F)
3. Specific gravity (water = 1): 1.44
4. Vapor density (air = 1 at boiling point of dichlorvos): Not applicable
5. Melting point: Data not available
6. Vapor pressure at 32 C (90 F): 0.032 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 1 (approx).
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: None
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride gas, phosphoric acid mist, and carbon monoxide) may be released in a fire involving dichlorvos.
4. Special precautions: Dichlorvos will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of dichlorvos.
2. Eye Irritation Level: Dichlorvos is not known to be an eye irritant.
3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of dichlorvos, it is treated as a material with poor warning properties. The concentration in saturated air at 20 C could result in a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for dichlorvos is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00249-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental

concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with dichlorvos.

• Clothing contaminated with dichlorvos should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dichlorvos from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dichlorvos, the person performing the operation should be informed of dichlorvos's hazardous properties.

• Non-impervious clothing which becomes contaminated with dichlorvos should be removed immediately and not reworn until the dichlorvos is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid dichlorvos may contact the eyes.

SANITATION

• Skin that becomes contaminated with dichlorvos should be immediately washed or showered with soap or mild detergent and water to remove any dichlorvos.

• Employees who handle dichlorvos should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dichlorvos may occur and control methods which may be effective in each case:

Operation	Controls
Formulation and mixing for insecticidal application	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Application on vegetables, animals, agriculutral premises, and for outdoor fogging; insecticidal use of tablets, rubbing devices, resin strips, animal collars, dust on animals, animal buildings, restaurants, hospitals, and aircraft	Personal protective equipment
Manufacture of dichlorvos	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If dichlorvos or dichlorvos mists get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If dichlorvos or dichlorvos mists get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If dichlorvos or dichlorvos mists soak through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of dichlorvos, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dichlorvos has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Under-

stand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dichlorvos is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Dichlorvos may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dichlorvos," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• *Hygienic Information Guide No. 97 – Dichlorvos*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koelle, G. B. (ed.): "Cholinesterases and Anticholinesterase Agents," Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• Menz, M., et al.: "Long-Term Exposure of Factory Workers to Dichlorvos (DDVP) Insecticide," *Archives of Environmental Health*, 28:72-76, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

RESPIRATORY PROTECTION FOR DICHLORVOS

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate or Vapor Concentration	
10 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 200 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of dichlorvos; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 200 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Diethylamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_2H_5)_2NH$
- Synonyms: None
- Appearance and odor: Colorless liquid with a fishy odor, like ammonia.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for diethylamine is 25 parts of diethylamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 75 milligrams of diethylamine per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has recommended for diethylamine a Threshold Limit Value of 3 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Diethylamine can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Diethylamine vapors may cause irritation of the respiratory tract, causing coughing, chest pain, or immediate or delayed breathing difficulties. High vapor concentrations may also cause severe irritation of the eyes. Contact of the liquid with bare skin may cause irritation. Covered contact as with clothing wet with diethylamine may cause skin burns. Contact of the liquid with the eyes is an emergency and may result in serious eye injury.

2. Long-term Exposure: Prolonged or repeated skin contact with liquid diethylamine may cause chronic irritation. Prolonged or repeated contact of the eyes with vapors of diethylamine at levels near the irritant level often results in swelling of the eye, causing foggy vision and the appearance of halos around lights.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to diethylamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to diethylamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from diethylamine exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of diethylamine might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Diethylamine is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Diethylamine is a severe eye irritant and may cause tissue damage. Persons with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Diethylamine vapor is a severe irritant to mucous membranes, eyes, and skin. Rabbits repeatedly exposed to 50 ppm for 7 hours daily showed corneal damage and pulmonary irritation. In one reported human case, liquid splashed into the eye caused immediate intense pain. In spite of emergency irrigation and treatment the cornea became swollen and cloudy. Some permanent

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

visual impairment resulted. Contact with the liquid causes vesiculation and necrosis of the skin.

CHEMICAL AND PHYSICAL PROPERTIES

1. Molecular weight: 73.14
2. Boiling point (760 mm Hg): 55.5 C (132 F)
3. Specific gravity (water = 1): 0.71
4. Vapor density (air = 1 at boiling point of diethylamine): 2.5
5. Melting point: −50 C (−58 F)
6. Vapor pressure at 20 C (68 F): 195 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): 16.9

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids will cause spattering.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving diethylamine.
4. Special precautions: Liquid diethylamine will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: Less than −18 C (less than 0 F) (closed cup)
2. Autoignition temperature: 312 C (594 F)
3. Flammable limits in air, % by volume: Lower: 1.8; Upper: 10.1
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: The MCA's *Material Safety Data Sheet* states that "diethylamine has a strong ammoniacal odor which gives good warning of its presence." The Department of Transportation's CHRIS manual for the Coast Guard gives an odor threshold of 0.14 ppm.
2. Eye Irritation Level: Grant reports that "chronic exposure to the vapors at concentrations as low as 50 ppm in air causes conjunctival and pulmonary irritation in rabbits; corneal erosion develops after 2 weeks of exposure." Patty notes that both edema of the cornea and eye irritation have been observed during industrial exposures to diethylamine. The concentrations producing these effects are not given. Permanent eye injury is reported to occur after repeated exposure to 50 ppm, according to Brieger and Hodes.
3. Other Information: The MCA's *Material Safety Data Sheet* states that diethylamine is a respiratory tract irritant, and the AIHA *Hygienic Guide* reports that this compound irritates mucous membranes. No quantitative information is given.
4. Evaluation of Warning Properties: Since the odor threshold of diethylamine (0.14 ppm) is well below the permissible exposure limit, this substance is considered to have good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of vapors in a silica gel tube, followed by desorption with sulfuric acid in methanol, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure diethylamine may be used. An analytical method for diethylamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid diethylamine, where skin contact may occur.

• Clothing wet with liquid diethylamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of diethylamine from the clothing. If the clothing is to be

laundered or otherwise cleaned to remove the diethylamine, the person performing the operation should be informed of diethylamine's hazardous properties.

- Where exposure of an employee's body to liquid diethylamine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes wet with or non-impervious clothing which becomes contaminated with liquid diethylamine should be removed immediately and not reworn until the diethylamine is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid diethylamine or solutions containing more than 0.5 percent by weight of diethylamine contacting the eyes.
- Employees should be provided with and required to use splash-proof safety goggles where solutions containing 0.5 percent or less of diethylamine by weight may contact the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid diethylamine or solutions containing more than 0.5 percent by weight of diethylamine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with liquid diethylamine should be immediately washed or showered to remove any diethylamine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to diethylamine may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of textile finishing agents, surfactants, rubber processing chemicals, agricultural chemicals, and pharmaceuticals	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as a corrosion inhibitor in iron, steel, and metal industries	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as polymerization inhibitor and catalyst in polymer industry; intermediate in dye industry	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as depilatory of animal skins; and in electroplating solutions	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If diethylamine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If diethylamine gets on the skin, immediately flush the contaminated skin with water. If diethylamine soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of diethylamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When diethylamine has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If diethylamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely

clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Diethylamine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of diethylamine vapors are permitted.

• Waste disposal method:

Diethylamine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Diethylamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Diethylamine," *Hygienic Guide Series*, Detroit, Michigan, 1960.

• Brieger, H., and Hodea, W. A.: "Toxic Effects of Exposure to Vapors of Aliphatic Amines," *Archives of Industrial Hygiene and Occupational Medicine*, 3:287-291, 1951.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-97, Diethylamine*, Washington, D.C., 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• U.S. Department of Transportation: *CHRIS Hazardous Chemical Data*, CG-446-2, U.S. Government Printing Office, Washington, January 1974.

RESPIRATORY PROTECTION FOR DIETHYLAMINE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
1250 ppm or less	A chemical cartridge respirator with a full facepiece and an cartridge(s) which provide protection against diethylamine. A gas mask with a chin-style or a front- or back-mounted canister which provides protection against diethylamine. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against diethylamine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Diethylamino Ethanol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_2H_5)_2NC_2H_4OH$
- Synonyms: 2-Diethylaminoethyl alcohol; N,N-diethylethanolamine; diethyl (2-hydroxytriethyl) amine; 2-diethylamino ethanol; 2-hydroxy-triethylamine
- Appearance and odor: Colorless liquid with a weak ammonia odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for diethylamino ethanol is 10 parts of diethylamino ethanol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 50 milligrams of diethylamino ethanol per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Diethylamino ethanol can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Liquid diethylamino ethanol splashes will cause skin irritation. Liquid splashes in the eye will cause irritation and damage. Diethylamino ethanol vapor may cause nausea and vomiting. It may also cause cough and shortness of breath. Splashes may cause eye and skin irritation.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to diethylamino ethanol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to diethylamino ethanol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from diethylamino ethanol exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of diethylamino ethanol might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Diethylamino ethanol is a primary skin irritant and a probable skin sensitizer. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Diethylamino ethanol is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Diethylamino ethanol vapor is a skin, eye, and respiratory irritant. Rats exposed to 500 ppm 6 hours daily for 5 days exhibited marked eye and nasal irritation, and a number of animals had corneal opacity by the end of the third day; the mortality rate was 20%, and at autopsy there was acute purulent bronchiolitis and bronchopneumonia. Daily exposure at 200 ppm for up to 6 months was fatal in some rats, with death occurring during the first 30 days. An attempt by a laboratory worker to remove animals from an inhalation chamber containing approximately 100 ppm resulted in nausea and vomiting within 5 minutes after a brief exposure; no irritation of the eyes or throat was noted during this

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

4°S

September 1978

brief exposure. Other persons in the same room also complained of a nauseating odor but showed no ill effects. The liquid is a severe skin irritant; in the guinea pig it is a skin sensitizer. It is also a severe eye irritant and may produce permanent eye injury. No systemic effects from human exposure have been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 117.2
  2. Boiling point (760 mm Hg): 162 C (324 F)
  3. Specific gravity (water = 1): 0.89
  4. Vapor density (air = 1 at boiling point of diethylamino ethanol): 4.0
  5. Melting point: Data not available
  6. Vapor pressure at 20 C (68 F): 1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 0.17
- **Reactivity**
  1. Conditions contributing to instability: Heat.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids will cause spattering.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving diethylamino ethanol.
  4. Special precautions: Liquid diethylamino ethanol will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 52 C (126 F) (closed cup)
  2. Autoignition temperature: 320 C (608 F)
  3. Flammable limits in air, % by volume: Lower: 6.7; Upper: 11.7
  4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: Diethylamino ethanol has a weak ammoniacal odor, but no information is available concerning its odor threshold.
  2. Eye Irritation Level: The Pennwalt Corporation *Material Safety Data Sheet* states that diethylamino ethanol is irritating to the eyes. Deichmann and Gerarde (in *Toxicology of Drugs and Chemicals*, p. 216) state that 2-diethylamino ethanol as the "undiluted" compound is a severe eye irritant capable of producing permanent eye injury. No information is available, however, concerning air concentrations producing eye irritation.
  3. Other Information: Deichmann and Gerarde report that the vapors of diethylamino ethanol irritate the respiratory tract, but the concentrations producing this irritation are not given.
  4. Evaluation of Warning Properties: Since no quantitative information is available relating the warning properties of diethylamino ethanol to air concentrations, it is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for diethylamino ethanol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid diethylamino ethanol, where skin contact may occur.
- Clothing contaminated with liquid diethylamino ethanol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of diethylamino ethanol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the diethylamino ethanol, the person performing the operation should be informed of diethylamino ethanol's hazardous properties.
- Where exposure of an employee's body to liquid diethylamino ethanol may occur, facilities for quick

drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with liquid diethylamino ethanol should be removed immediately and not reworn until the diethylamino ethanol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of solutions containing 5 percent or more of diethylamino ethanol by weight contacting the eyes and where solutions containing less than 5 percent diethylamino ethanol by weight may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to solutions containing 5 percent or more of diethylamino ethanol by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid diethylamino ethanol should be immediately washed or showered to remove any diethylamino ethanol.

• Employees who handle liquid diethylamino ethanol should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to diethylamino ethanol may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of medicinals and pharmaceuticals, pesticides, protective surface coatings for metals, emulsifying agents for polishes, resinous materials for treating fiber surfaces, fluorescent brightening agents, and in polymer production	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in organic synthesis to prepare compounds for surfactants, detergents, wetting agents, and yarn-treating	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in synthetic fiber dyeing and vat dyes; use as photographic stabilizing solutions	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If diethylamino ethanol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If diethylamino ethanol gets on the skin, immediately flush the contaminated skin with water. If diethylamino ethanol soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of diethylamino ethanol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When diethylamino ethanol has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If diethylamino ethanol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning de[illegible]. Diethylamino ethanol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explo-

sion. Sewers designed to preclude the formation of explosive concentrations of diethylamino ethanol vapors are permitted.

• Waste disposal methods:

Diethylamino ethanol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Diethylamino Ethanol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Cornish, H. H.: "Oral and Inhalation Toxicity of 2-Diethylaminoethanol," *American Industrial Hygiene Association Journal*, 26:479-484, 1965.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974

• Miller, F. A., et al.: "Determination of Microgram Quantities of Diethanolamine, 2-Methylaminoethanol, and 2-Diethylaminoethanol in Air," *American Industrial Hygiene Association Journal*, 28:330-334, 1967.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Pennwalt Corporation: *Material Safety Data Sheet - Diethylamino Ethanol*, Philadelphia, Pennsylvania, 1967

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Diethylamino Ethanol*, New York, 1974.

RESPIRATORY PROTECTION FOR DIETHYLAMINO ETHANOL

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 500 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of diethylamino ethanol; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 500 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Difluorodibromomethane (Freon 12B2)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CBr_2F_2
- Synonyms: Dibromodifluoromethane; Freon 12B2
- Appearance and odor: Colorless liquid or gas with a characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Freon 12B2 is 100 parts of Freon 12B2 per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 860 milligrams of Freon 12B2 per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Freon 12B2 can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to Freon 12B2 may cause irritation of the nose and throat, drowsiness, unconsciousness, and death. Exposure may also cause liver damage. If the liquid gets on the skin or in the eyes, it may cause frostbite.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Freon 12B2.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Freon 12B2 at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from Freon 12B2 exposure.

—Liver disease: Although Freon 12B2 is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of Freon 12B2 might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Freon 12B2 vapor is a respiratory irritant and a narcotic. Rats exposed to 4000 ppm for 15 minutes showed pulmonary edema, while 2300 ppm daily for 6 weeks resulted in the death of more than half the animals. At 2300 ppm dogs showed rapid and progressive signs of intoxication, with weakness and loss of balance after a few days' exposure, followed by convulsions. These dogs at autopsy had pulmonary congestion, centrolobular necrosis of the liver, and some evidence of central nervous system damage. However, other dogs tolerated daily exposures of 350 ppm for 7 months without signs of intoxication. No systemic effects have been reported from industrial exposures. In liquid form, this substance may cause frostbite.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 209.8

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

2. Boiling point (760 mm Hg): 24.5 C (76.1 F)
3. Specific gravity (water = 1): 2.46
4. Vapor density (air = 1 at boiling point of Freon 12B2): 7.2
5. Melting point: −141.6 C (−223 F)
6. Vapor pressure at 20 C (68 F): 620 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Higher than 1

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Freon 12B2 reacts with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, and magnesium.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen bromide and hydrogen fluoride) may be released when Freon 12B2 decomposes.
4. Special precautions: Liquid Freon 12B2 will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Freon 12B2 does not have adequate warning properties. Freon 12B2 is not a known eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of Freon 12B2 vapors using an adsorption tube with subsequent desorption with isopropyl alcohol and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure Freon 12B2 may be used. An analytical method for Freon 12B2 is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid Freon 12B2.

• Non-impervious clothing which becomes wet with liquid Freon 12B2 should be removed promptly and not reworn until the Freon 12B2 has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid Freon 12B2 may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Freon 12B2 may occur and control methods which may be effective in each case:

Operation	Controls
Use as a fire extinguishing agent; use in organic synthesis	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in processing cutting tools as razor blades, hypodermic needles, scalpels, culinary knives, and garden tools	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a special solvent for preparation of explosive mixtures	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid Freon 12B2 gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid Freon 12B2 gets on the skin, immediately flush the contaminated skin with water if the liquid Freon 12B2 has not already evaporated. If liquid Freon 12B2 soaks through the clothing, remove the clothing immediately and flush the skin with water. Do not use hot water for skin flushing. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of Freon 12B2, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When Freon 12B2 has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If Freon 12B2 is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If the gas is leaking, stop the flow.
3. If the liquid is spilled or leaked, allow to vaporize.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Difluorodibromomethane," *Documentation of the Threshold Limit Values for Substances in Workroon, Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Dichlorodifluoromethane," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• E. I. DuPont de Nemours and Company: "Freon Compounds and Safety," *Freon Product Information*, Wilmington, Delaware, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR FREON 1232

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
2500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Diisopropylamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_2CH\text{-}NH\text{-}CH(CH_3)_2$
- Synonyms: None
- Appearance and odor: Colorless liquid with an odor like ammonia.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for diisopropylamine is 5 parts of diisopropylamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 20 milligrams of diisopropylamine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Diisopropylamine can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Diisopropylamine may cause headache, visual problems and nausea. It may also cause irritation of the respiratory tract.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to diisopropylamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to diisopropylamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from diisopropylamine exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of diisopropylamine might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Diisopropylamine is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Diisopropylamine is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Diisopropylamine vapor is a respiratory irritant and a severe eye irritant. Exposure of experimental animals to 260 to 2200 ppm for several hours resulted in fatalities at the higher concentrations as a result of severe pulmonary damage; exposure at these concentrations for several hours caused clouding of the cornea which was reversible. Workers exposed to concentrations between 25 and 50 ppm complained of nausea, headache, and disturbances in vision. Diisopropylamine has been reported to cause skin irritation in animals.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 101.2
  2. Boiling point (760 mm Hg): 84 C (183 F)
  3. Specific gravity (water = 1): 0.72

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

4. Vapor density (air = 1 at boiling point of diisopropylamine): 3.5

5. Melting point: −96 C (−141 F)

6. Vapor pressure at 20 C (68 F): 60 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions below 27 C (81 F). Above this temperature, the maximum solubility is 30%.

8. Evaporation rate (butyl acetate = 1): 5.8

• **Reactivity**

1. Conditions contributing to instability: Heat.

2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids will cause spattering.

3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving diisopropylamine.

4. Special precautions: Liquid diisopropylamine will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: −6.7 C (20 F) (closed cup)

2. Autoignition temperature: 316 C (600 F)

3. Flammable limits in air, % by volume: Lower: 0.8; Upper: 7.1

4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: Diisopropylamine has an odor like ammonia, but no quantitative information is available concerning its odor threshold.

2. Eye Irritation Level: Grant reports that visual disturbances have been observed in men who have been exposed to concentrations of 25 to 50 ppm diisopropylamine. "Experimental exposures of rabbits, guinea pigs, rats, and cats have established that the vapor is injurious to the corneal epithelium." According to Grant, "this is presumably the cause of the visual disturbances observed in men." A several-hour exposure to concentrations of 260 to 2200 ppm has caused corneal injury to experimental animals.

3. Other Information: The *Documentation of TLV's* reports that Treon et al. observed irritation of the respiratory mucous membranes in animals exposed repeatedly to 260 ppm.

4. Evaluation of Warning Properties: Since there is no quantitative information relating warning properties to air concentrations of diisopropylamine, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for diisopropylamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid diisopropylamine.

• Clothing wet with liquid diisopropylamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of diisopropylamine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the diisopropylamine, the person performing the operation should be informed of diisopropylamine's hazardous properties.

• Any clothing which becomes wet with liquid diisopropylamine should be removed immediately and not reworn until the diisopropylamine is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of solutions containing 5 percent or more of diisopropylamine by weight contacting the eyes and where solutions containing less than 5 percent of diisopropylamine by weight may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to solutions containing 5 percent or more of diisopropylamine by weight, an eye-wash foun-

tain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes wet with liquid diisopropylamine should be promptly washed or showered to remove any diisopropylamine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to diisopropylamine may occur and control methods which may be effective in each case:

Operation	Controls
Use in synthesis of corrosion inhibitors in iron and steel	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in synthesis of herbicides, delayed action vulcanization accelerator for sulfur-cured rubbers; as a catalyst for chemical synthesis of alkylene cyanohydrin	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as component in gels for cosmetic and medical applications as deodorants and aftershave solutions	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If diisopropylamine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If diisopropylamine gets on the skin, immediately wash the contaminated skin with water. If diisopropylamine soaks through the clothing, remove the clothing immediately and wash the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of diisopropylamine, move the exposed person to fresh air at once. breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When diisopropylamine has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If diisopropylamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Diisopropylamine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of diisopropylamine vapors are permitted.

• Waste disposal method:

Diisopropylamine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Diisopropylamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Diisopropylamine*, New York, 1971.

RESPIRATORY PROTECTION FOR DIISOPROPYLAMINE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
250 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dimethyl Acetamide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CON(CH_3)_2$
- Synonyms: N,N-dimethyl acetamide; DMAC
- Appearance and odor: Colorless liquid with a faint, ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dimethyl acetamide is 10 parts of dimethyl acetamide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 35 milligrams of dimethyl acetamide per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dimethyl acetamide can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Repeated or prolonged exposure to dimethyl acetamide may cause liver damage with yellow jaundice. Repeated exposure at high concentrations may cause depression, drowsiness, confusion, and hallucinations.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dimethyl acetamide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dimethyl acetamide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver should be stressed.

—Liver function tests: Since liver damage has been observed in humans exposed to dimethyl acetamide, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Inhalation of the vapor or skin absorption of the liquid causes liver damage. Repeated dermal application of the liquid to dogs at a dosage level of 4.0 ml/kg for 6 weeks caused severe fatty infiltration of the liver. Repeated exposure of rats to a concentration of 195 ppm for 6 months resulted in focal necrosis of the liver; exposure to 40 ppm for the same period of time caused no adverse effects. Workers repeatedly exposed to 20 to 25 ppm developed jaundice; appreciable skin absorption was thought to have occurred. Dimethyl acetamide has a significant antitumor effect in animals. Nine patients with neoplastic disease were given daily doses of 400 mg/kg by an unspecified route for 3 or more days as a therapeutic trial; they experienced depression, lethargy, confusion, and disorientation; on the last (4th or 5th) day of therapy or within 24 hours thereafter, the patients had visual and auditory hallucinations, perceptual distortions, and at times delusions; after 24 hours these gradually subsided.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 87.1
  2. Boiling point (760 mm Hg): 166 C (331 F)
  3. Specific gravity (water = 1). 0.94
  4. Vapor density (air = 1 at boiling point of dimethyl acetamide): 3.0
  5. Melting point: −20 C (−4 F)
  6. Vapor pressure at 20 C (68 F): 1.5 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): Less than 0.17
- **Reactivity**
  1. Conditions contributing to instability: Temperatures above 350 C (662 F) cause decomposition and development of pressure in closed containers.
  2. Incompatibilities: Contact with carbon tetrachloride and other halogenated compounds, particularly when in contact with iron, may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as dimethylamine and carbon monoxide) may be released in a fire involving dimethyl acetamide.
  4. Special precautions: Dimethyl acetamide will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 70 C (158 F) (open cup)
  2. Autoignition temperature: 490 C (914 F)
  3. Flammable limits in air, % by volume: Lower: 1.8 (at 212 F); Upper: 11.5 (at 320 F)
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide. Do not use halogenated extinguishing media.
- **Warning properties**
  1. Odor Threshold: No quantitative information is available.
  2. Eye Irritation Level: Grant states that "on decomposition, it is said to emit fumes which are highly irritating to the eyes and mucous membranes." He reports that it causes mild, reversible injury graded 3 on a scale of 10 when tested on rabbit eyes.
  3. Evaluation of Warning Properties: Since no quantitative information is available relating its warning properties to air concentrations, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of dimethyl acetamide vapors using a silica gel tube, followed by desorption with methanol, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure dimethyl acetamide may be used. An analytical method for dimethyl acetamide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid dimethyl acetamide.
- Clothing contaminated with dimethyl acetamide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dimethyl acetamide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dimethyl acetamide, the person performing the operation should be informed of dimethyl acetamide's hazardous properties.
- Where exposure of an employee's body to dimethyl acetamide may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with dimethyl acetamide should be removed immediately and not reworn until the dimethyl acetamide is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid dimethyl acetamide may contact the eyes.

SANITATION

• Skin that becomes contaminated with dimethyl acetamide should be immediately washed or showered to remove any dimethyl acetamide.

• Eating and smoking should not be permitted in areas where liquid dimethyl acetamide is handled, processed, or stored.

• Employees who handle liquid dimethyl acetamide should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dimethyl acetamide may occur and control methods which may be effective in each case:

Operation	Controls
Use as a spinning solvent for synthetic fibers; as a solvent for film casting and top coating resins	Local exhaust ventilation; personal protective equipment
Use as a reaction medium and catalyst; as an extraction solvent for recovery and purification of butadiene; use as a crystallization and purification solvent; as a paint stripping solvent; during recovery and purification from top coating, film casting, spinning, and chemical processes	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If dimethyl acetamide gets into the eyes, wash eyes immediately, with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid dimethyl acetamide gets on the skin, immediately flush the contaminated skin with water. If liquid dimethyl acetamide soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of dimethyl acetamide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid dimethyl acetamide has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dimethyl acetamide is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Dimethyl acetamide may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in sealed containers in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dimethyl Acetamide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Davis, K. J., and Jenner, P. M.: "Toxicity of Three Drug Solvents," *Toxicology and Applied Pharmacology*,:576-578, 1959.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• Horn, H. J.: "Toxicology of Dimethylacetamide," *Toxicology and Applied Pharmacology*, 3:12-24, 1961.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Weiss, A. J., et al.: "Dimethylacetamide: A Hitherto Unrecognized Hallucinogenic Agent," *Science*, 136:151-152, 1962.

RESPIRATORY PROTECTION FOR DIMETHYL ACETAMIDE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
100 ppm or less	Any supplied-air respirator.**
	Any self-contained breathing apparatus.**
400 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 400 ppm*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of dimethyl acetamide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 400 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Dimethyl Formamide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $HCON(CH_3)_2$
- Synonyms: N,N-dimethyl formamide; DMF
- Appearance and odor: Colorless liquid with a faint, ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dimethyl formamide is 10 parts of dimethyl formamide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 30 milligrams of dimethyl formamide per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dimethyl formamide can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation of dimethyl formamide or skin contact with dimethyl formamide may cause abdominal distress, colicky abdominal pain, loss of appetite, nausea, vomiting, constipation, diarrhea, facial flushing (especially after drinking alcohol), liver injury, agitation, and increased blood pressure. Skin contact may cause skin irritation.

2. Long-term Exposure: Repeated or prolonged skin contact with dimethyl formamide may cause a rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dimethyl formamide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dimethyl formamide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver, kidneys, and cardiovascular system should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Since liver damage has been observed in humans exposed to dimethyl formamide, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Dimethyl formamide vapor is toxic to the liver. Repeated exposure of rats to concentrations of 100 to 450 ppm for 4 months resulted in necrosis of the liver and mild kidney damage. Animal studies have shown toxic effects at high levels on multiple organ systems. Thirteen workers exposed to concentrations below 20 ppm and occasionally to higher levels for up to 32 weeks complained of nausea, vomiting, and colic; some cases of hepatomegaly were detected. A worker who was splashed with the liquid over 20% of his body surface initially suffered only dermal irritation and hyperemia; abdominal pain began 62 hours after the exposure and became progressively more severe, with vomiting; the blood pressure was elevated to 190/100; the effects gradually subsided and were entirely abated by the 7th day after the exposure. Some workers have noted flushing of the face after inhalation of the vapor, especially with coincident ingestion of alcoholic bever-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

ages. Effects resemble those of porphyria. Prolonged or repeated skin contact with the liquid may cause dermatitis as a result of a defatting action.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 73.1
2. Boiling point (760 mm Hg): 153 C (307 F)
3. Specific gravity (water = 1): 0.94
4. Vapor density (air = 1 at boiling point of dimethyl formamide): 2.5
5. Melting point: −61 C (−78 F)
6. Vapor pressure at 20 C (68 F): 2.7 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): 0.17

- **Reactivity**

1. Conditions contributing to instability: Temperatures above 350 C (662 F) may cause decomposition and development of pressure in closed containers.
2. Incompatibilities: Contact with carbon tetrachloride and other halogenated compounds, particularly when in contact with iron, or contact with strong oxidizers may cause fires and explosions. Dimethyl formamide may react vigorously with alkylaluminums when the latter are used as polymerization catalysts.
3. Hazardous decomposition products: Toxic gases and vapors (such as dimethylamine and carbon monoxide) may be released in a fire involving dimethyl formamide.
4. Special precautions: Dimethyl formamide will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 58 C (136 F) (closed cup)
2. Autoignition temperature: 445 C (833 F)
3. Flammable limits in air, % by volume: Lower: 2.2; Upper: 15.2 (at 100 C (212 F))
4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide. Do not use halogenated extinguishing media.

- **Warning properties**

1. Odor Threshold: According to the Department of Transportation's *Hazardous Chemical Data*, the odor threshold of dimethyl formamide is 100 ppm.
2. Eye Irritation Level: According to Deichmann and Gerarde, dimethyl formamide "is highly irritating to skin, eyes, and mucous membranes." No quantitative information is available concerning the threshold levels of irritation.
3. Evaluation of Warning Properties: Since the odor threshold of dimethyl formamide is 10 times higher than the permissible exposure limit, and since no other quantitative information is available relating to warning properties to air concentrations, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of dimethyl formamide vapors using a silica gel tube, followed by desorption with methanol, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure dimethyl formamide may be used. An analytical method for dimethyl formamide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid dimethyl formamide.
- Non-impervious clothing which becomes contaminated with dimethyl formamide should be removed

promptly and not reworn until the dimethyl formamide is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid dimethyl formamide may contact the eyes.

SANITATION

• Skin that becomes contaminated with dimethyl formamide should be promptly washed or showered to remove any dimethyl formamide.

• Employees who handle liquid dimethyl formamide should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dimethyl formamide may occur and control methods which may be effective in each case:

Operation	Controls
Use as resin and polymer solvent as spinning solvent for acrylic fibers; booster solvent in coating, printing, and adhesive formulations	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a chemical intermediate, catalyst and reaction medium in chemical manufacturing industry	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a selective absorption and extraction solvent for recovery, purification absorption, separation and desulfurization of non-paraffinics from paraffin hydrocarbons	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of paint stripper component for removal of vinyl films, epoxy coatings, and varnish finishes	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in pigment and dye industry to improve dyeing properties; use as solvent of dyes and pigments for use with textiles, wood, leather, films, paper, and plastics; use as a crystallization solvent in pharmaceutical industry; use as a solvent for carbonaceous deposit cleaning	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in miscellaneous applications for high-voltage capacitors, oil sludge dispersing agent, antistall gasoline additive, quench for tinned parts and wood pulping	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid dimethyl formamide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid dimethyl formamide gets on the skin, promptly flush the contaminated skin with water. If liquid dimethyl formamide soaks through the clothing, remove the clothing promptly and flush the skin with water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of dimethyl formamide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid dimethyl formamide has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify some-

one else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid dimethyl formamide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Dimethyl formamide should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of dimethyl formamide vapors are permitted.

• Waste disposal methods:

Dimethyl formamide may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dimethylformamide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Dimethylformamide," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Clayton, J. W., Jr., et al.: "The Inhalation Toxicity of Dimethylformamide (DMF)," *American Industrial Hygiene Association Journal*, 24:144-154, 1963.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Department of Transportation: *CHRIS Hazardous Chemical Data*, CG-446-2, U.S. Government Printing Office, Washington, D.C., January 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Massmann, W.: "Toxicological Investigations on Dimethylformamide," *British Journal of Industrial Medicine*, 13:51-54, 1956.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Potter, H. P.: "Dimethylformamide-Induced Abdominal Pain and Liver Injury," *Archives of Environmental Health*, 27:340-341, 1973.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR DIMETHYL FORMAMIDE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
100 ppm or less	Any supplied-air respirator.**
	Any self-contained breathing apparatus.**
500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
3500 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 3500 ppm*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of dimethyl formamide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 3500 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Dimethyl-1,2-Dibromo-2,2-Dichloroethyl Phosphate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3O)_2P(O)OCHBrCBrCl_2$ or $C_4H_7Br_2Cl_2O_4P$
- Synonyms: Naled; 1,2-dibromo-2,2-dichloroethyl dimethyl phosphate; Dibrom
- Appearance and odor: Colorless solid or straw-colored liquid with a slightly pungent odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate is 3 milligrams of dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: If vapors of dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate are inhaled, effects on the respiratory system and the eyes are the first to appear. These include tightness of the chest, wheezing, cough, excessive salivation, nasal discharge, aching in and behind the eyes, blurred vision, tearing, and headache. After swallowing the liquid, intestinal effects include loss of appetite, nausea, vomiting, cramps, and diarrhea. If spilled on the skin, it may cause itching, redness, and irritation. On being absorbed through the skin, this chemical may cause twitching and sweating at the site of absorption. If splashed in the eye, it may cause irritation. Severe intoxication, which may occur from breathing this chemical, swallowing it, or absorbing it through the skin or eye, may cause lightheadedness, slurred speech, muscle twitching, irregular heart beat, convulsions, paralysis, coma, and death.

2. Long-term Exposure: Repeated exposure to levels of dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate may make a person more susceptible to the effects of this and related chemicals.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of skin sensitization to dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate, reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system, and attention to the cholinesterase levels in the blood should be stressed. The skin should be examined for evidence of chronic disorders.

—Cholinesterase determination: Dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the serum

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

and erythrocytes should be determined by using medically acceptable biochemical assays prior to any exposure.

2. *Periodic Medical Examination:* The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determination which should be performed semiannually or at any time overexposure is suspected or signs or symptoms of toxicity occur.

• **Summary of toxicology**

This substance is an anticholinesterase agent; absorption may occur from inhalation of the vapor, by skin absorption, or ingestion of the liquid. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine in the nervous system, skeletal and smooth muscles, and secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms occurs promptly, and almost always within 12 hours. After inhalation of the vapor, respiratory and ocular effects are the first to appear, often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion of the liquid, gastrointestinal effects such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption of the liquid, localized sweating and muscular fasciculations in the immediate area occur, usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures and is enhanced by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels and cardiac irregularities including complete heart block may occur, but these are often reversed by the establishment of adequate pulmonary ventilation. In nonfatal cases, complete symptomatic recovery usually occurs within 1 week; increased susceptibility to the effects of anticholinesterase agents persists for long periods after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects. Dermatitis occurred on the arms, face, neck, and abdomen of 9 of 12 persons working in a field of flowers which had been freshly sprayed with a solution of Dibrom; three of four workers patch-tested were positive to a 60% solution of Dibrom in xylene and negative to xylene alone. The liquid in the eye is expected to cause injury.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 381
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.97
4. Vapor density (air = 1 at boiling point of dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate): Not
5. Melting point: 27 C (81 F)
6. Vapor pressure at 20 C (68 F): 0.0002 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble, decomposes about 10% per day in water
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen bromide, hydrogen chloride, phosphoric acid, and carbon monoxide) may be released when dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate decomposes.
4. Special precautions: Liquid dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Dibrom is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate had been published by NIOSH.

RESPIRATORS

Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may

be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate, where skin contact may occur.
- If employees' clothing may have become contaminated with dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liqcontaining dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing which may have become contaminated with dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate, the person performing the operation should be informed of dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate's hazardous properties.
- Non-impervious clothing which becomes contaminated with dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate should be removed immediately and not reworn until the dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate should be immediately washed or showered with soap or mild detergent and water to remove any dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate.
- Workers subject to skin contact with dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate should wash any areas of the body which may have contacted dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate at the end of each work day.
- Eating and smoking should not be permitted in areas where dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate are handled, processed, or stored.
- Employees who handle dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate may occur and control methods which may be effective in each case:

Operation	Controls
Use as an agricultural insecticide and acaricide applied to fruit, vegetables, and agronomic crops; use in domestic, commercial, and agricultural premises	Personal protective equipment
Use in compounding water-base paints and floor polishes for insecticidal properties	Process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immedi-

ately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. If in the solid form, collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquid dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate or liquids containing dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal methods:

Dimethyl-1,2-dibromo-2,2-dichloroethyl phosphate may be disposed of:

1. If in the solid form, by disposing in a secured sanitary landfill.
2. If in the liquid form, by absorbing in vermiculite, dry sand, earth, or a similar material, and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dimethyl-1,2-Dibromo-2,2-Dichloroethyl Phosphate,7*Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Chevron Environmental Health Center: *Material Information Bulletin No. 441-1975, Chevron Naled Technical*, San Francisco, 1975.

• Edmundson, W. F., and Davies, J. E.: "Occupational Dermatitis from Naled — A Clinical Report," *Archives of Environmental Health*, 15:89-91, 1967.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koelle, G. B. (ed.): *Cholinesterases and Anticholinesterase Agents*, Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

RESPIRATORY PROTECTION FOR DIMETHYL-1,2-DIBROMO-2,2-DICHLOROETHYL PHOSPHATE

Condition	Minimum Respiratory Protection* Required Above 3 mg/m³
Particulate Concentration	
15 mg/m³ or less	Any dust and mist respirator, except single-use, including pesticide respirators which meet the requirements of this class.
30 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator, including pesticide respirators which meet the requirements of this class. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
150 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1800 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure mode.
Greater than 1800 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dimethylamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_2NH$
- Synonyms: Dimethylamine, anhydrous
- Appearance and odor: Colorless liquid or gas with a pungent, fishy, or ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dimethylamine is 10 parts of dimethylamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 18 milligrams of dimethylamine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dimethylamine can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Dimethylamine vapor may cause irritation of the lungs, nose, throat, and eyes. It may cause coughing and sneezing. Contact with the liquid may cause skin and eye burns.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dimethylamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dimethylamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from dimethylamine exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of dimethylamine might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Dimethylamine is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Dimethylamine is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-...sted conditions should be referred for further medical examination.

- **Summary of toxicology**

Dimethylamine gas is a severe respiratory, eye, and mucous membrane irritant in animals. Animals repeatedly exposed to concentrations of approximately 100 to 200 ppm for 18-20 weeks showed marked irritation of the respiratory tract with pulmonary edema as well as hepatic injury, including centrolobular necrosis; corneal injury was observed in guinea pigs and rabbits after 9 days of exposure. Various species survived 5 ppm of continuous exposure for 90 days without signs of toxicity, but at autopsy some showed mild inflammatory changes in the lungs. A drop of undiluted dimethylamine placed on a rabbit's cornea caused the cornea to become as white as the sclera in 1 minute. Both the liquid and the vapor are highly irritating to the eyes and may result in loss of visual acuity. Dermatitis and conjunctivitis are occasionally observed in chemical workers after prolonged exposure to the gas. No sys-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

501

temic effects from industrial exposure have been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 45.1
  2. Boiling point (760 mm Hg): 6.9 C (44.4 F)
  3. Specific gravity (water = 1): 0.68 (liquid at 0 C)
  4. Vapor density (air = 1 at boiling point of dimethylamine): 1.6
  5. Melting point: −92 C (−134 F)
  6. Vapor pressure at 20 C (68 F): 1.72 atm.
  7. Solubility in water, g/100 g water at 20 C (68 F): Very soluble
  8. Evaporation rate (butyl acetate = 1): Greater than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers, chlorine, and mercury may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving dimethylamine.
  4. Special precautions: Liquid dimethylamine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: Not pertinent (gas)
  2. Autoignition temperature: 402 C (755 F)
  3. Flammable limits in air, % by volume: Lower: 2.8; Upper: 14.4
  4. Extinguishant: Stop flow of gas.
- **Warning properties**
  1. Odor Threshold: Summer reports that the odor threshold of dimethylamine is 6 ppm, and May reports two odor thresholds, .021 and 23 ppm.
  2. Eye Irritation Level: The *Documentation of TLV's* reports that dimethylamine irritates mucous membranes. Repeated exposures of guinea pigs and rabbits to concentrations of 183 to 97 ppm dimethylamine have resulted in corneal injury. There is no available information on the threshold of eye irritation.
  3. Other Information: The *Documentation of TLV's* states that dimethylamine is a mucous membrane irritant and a respiratory tract irritant. The thresholds of irritation are not given.
  4. Evaluation of Warning Properties: Since the odor threshold ranges between one-five hundredth of the permissible exposure limit and approximately twice the permissible exposure limit, dimethylamine is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors in a silica gel tube, followed by desorption with sulfuric acid in methanol, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure dimethylamine may be used. An analytical method for dimethylamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid dimethylamine.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solutions containing dimethylamine.
- Clothing wet with solutions containing dimethylamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dimethylamine from the clothing. If the clothing is to be laundered or otherwise cleaned to

remove the dimethylamine, the person performing the operation should be informed of dimethylamine's hazardous properties.

- Where there is any possibility of exposure of an employee's body to liquid dimethylamine, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with liquid solutions of dimethylamine should be removed promptly and not reworn until the dimethylamine is removed from the clothing.
- Any clothing which becomes wet with liquid dimethylamine or liquid solutions of dimethylamine should be removed immediately and not reworn until the dimethylamine is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid dimethylamine or solutions containing dimethylamine contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid dimethylamine or solutions containing dimethylamine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with liquid dimethylamine should be immediately washed or showered to remove any dimethylamine.
- Skin that becomes contaminated with solutions containing dimethylamine should be promptly washed or showered to remove any dimethylamine.
- Employees who handle dimethylamine or solutions containing dimethylamine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dimethylamine may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of spinning solvents for acrylic and polymeric fibers	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as raw material in synthesis of agricultural chemicals; vulcanization accelerators for sulfur-cured rubber; softeners, lubricants; textile waterproofing agents; cationic surfactants; pharmaceuticals; detergents and soaps; as an antioxidant	Process enclosure; general dilution ventilation; personal protective equipment
Use as a general solvent; acid gas absorbent and flotation agent in manufacture of dyes and in electroplating	Process enclosure; general dilution ventilation; personal protective equipment
Use as photographic chemical, plasticizer, and ion exchange agent	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a stabilizer in natural rubber latex	Process enclosure; general dilution ventilation; local exhaust ventilation
Use as a stabilizer for certain types of resins (polymerization inhibitor)	General dilution ventilation; local exhaust ventilation
Use as a retarder in spinning bath of rayon (for tire cord)	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a component of rocket propellants; as an antiknock agent in other fuels	General dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If dimethylamine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If dimethylamine gets on the skin, immediately flush the contaminated skin with water. If dimethylamine soaks through the clothing, remove the clothing immediately

and wash the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of dimethylamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dimethylamine has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dimethylamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
4. If in the liquid form, allow to vaporize.

• Waste disposal method:

Dimethylamine may be disposed of by burning at a safe location or in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dimethylamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-57, Methylamines*, Washington, D.C., 1955.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

RESPIRATORY PROTECTION FOR DIMETHYLAMINE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Gas Concentration	
500 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) which provides protection against dimethylamine. A gas mask with a chin-style or a front- or back-mounted canister which provides protection against dimethylamine. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against dimethylamine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dimethylaniline

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5N(CH_3)_2$
- Synonyms: N,N-dimethylaniline
- Appearance and odor: Straw to brown-colored liquid with a characteristic amine-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dimethylaniline is 5 parts of dimethylaniline per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 25 milligrams of dimethylaniline per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dimethylaniline can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to dimethylaniline may affect the ability of the blood to carry oxygen. The earliest effect may be a bluish color of the skin, especially the lips. If the lack of oxygen becomes severe, a person may have drowsiness, headache, nausea, and vomiting. If oxygen lack is very severe, it may cause unconsciousness and even death.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dimethylaniline.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dimethylaniline at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, kidneys, liver, and cardiovascular system should be stressed.

—A complete blood count: Dimethylaniline has been shown to cause methemoglobinemia. A complete blood count should be performed, including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Dimethylaniline absorption, whether from inhalation of the vapor or by skin absorption of the liquid, causes anoxia due to the formation of methemoglobin. In dogs, the repeated subcutaneous injection of 1.5 g caused vomiting, weakness, cyanosis, methemoglobinemia, and hyperglobulinemia. It is said to be less toxic than aniline as regards methemoglobin formation but more of a central nervous system depressant. The liquid caused moderate injury in the eye of a rabbit.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 121
2. Boiling point (760 mm Hg): 192.8 C (379 F)
3. Specific gravity (water = 1): 0.96
4. Vapor density (air = 1 at boiling point of dimethylaniline): 4.2
5. Melting point: 2.5 C (36 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F):

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1.6

8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids may cause violent spattering.

3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving dimethylaniline.

4. Special precautions: Liquid dimethylaniline will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 62.8 C (145 F) (closed cup)

2. Autoignition temperature: 371 C (700 F)

3. Flammable limits in air, % by volume: Lower: 1.0 (calculated at flash point)

4. Extinguishant: Foam, dry chemical, carbon dioxide

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of dimethylaniline.

2. Eye Irritation Level: Dimethylaniline vapor is not known to be an eye irritant. Grant reports that "in only one instance has it been involved in an ocular disturbance," and in this instance, it is not known if the disturbance should be attributed to the inhalation of phenol, which was also present, or dimethylaniline.

3. Evaluation of Warning Properties: Since no quantitative information is available relating the warning properties of dimethylaniline to air concentrations, it is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of dimethylaniline vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure dimethylaniline may be used. An analytical method for dimethylaniline is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid dimethylaniline, where skin contact may occur.

• Clothing contaminated with dimethylaniline should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dimethylaniline from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dimethylaniline, the person performing the operation should be informed of dimethylaniline's hazardous properties.

• Where exposure of an employee's body to liquid dimethylaniline may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with dimethylaniline should be removed immediately and not reworn until the dimethylaniline is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid dimethylaniline may contact the eyes.

SANITATION

• Skin that becomes contaminated with dimethylaniline should be immediately washed or showered with soap or mild detergent and water to remove any dimethylaniline.

• Eating and smoking should not be permitted in areas where liquid dimethylaniline is handled, processed, or stored.

• Employees who handle liquid dimethylaniline should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dimethylaniline may occur and control methods which may be effective in each case:

Operation	Controls
Use in synthesis of dye and dye intermediates; synthesis of explosives; pharmaceuticals; polyester resin systems; and intermediates for vanillin	Process enclosure; local exhaust ventilation; personal protective equipment
Use in absorption of sulfur dioxide	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid dimethylaniline gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid dimethylaniline gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid dimethylaniline soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of dimethylaniline, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid dimethylaniline has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid dimethylaniline is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Dimethylaniline may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

ADDITIONAL INFORMATION

To find additional information on dimethylaniline, look up dimethylaniline in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dimethylaniline," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.). Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• H. M. Factory Inspectorate, Department of Employment and Productivity: *Technical Data Note – Dimethylaniline*, London.
• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-151956.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.
• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List III," *Archives of Industrial Hygiene*, 31:1, pp. 60-62, 1949.
• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List IV," *American Industrial Hygiene Association Journal*, 23:12, pp. 91-107, 1962.
• von Oettingen, W. F.: *The Aromatic Amino and Nitro Compounds, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 271, U.S. Government Printing Office, Washington, D.C., 1941.

RESPIRATORY PROTECTION FOR DIMETHYLANILINE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
50 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
100 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dimethylphthalate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_{10}O_4$
- Synonyms: DMP
- Appearance and odor: Colorless, oily liquid with a slight ester odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dimethylphthalate is 5 milligrams of dimethylphthalate per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dimethylphthalate can affect the body if it is swallowed, is inhaled, or comes in contact with the eyes.

- **Effects of overexposure**

Overexposure to hot vapors or mists of dimethylphthalate may cause irritation of the nasal passages and the mouth and throat. Eye contact with liquid dimethylphthalate causes pain. If swallowed, dimethylphthalate may cause irritation of the stomach, dizziness, and unconsciousness.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dimethylphthalate.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to dimethylphthalate at potentially hazardous levels.

- **Summary of toxicology**

Extensive experience with dimethylphthalate as an insect repellent has shown that it is relatively non-irritating to the skin, eyes, and mucous membranes. Aerosols from heated dimethylphthalate may cause irritation of the eyes and upper respiratory tract. In one fatal case of suicidal ingestion of a mixture containing dimethylphthalate and ketone peroxides, the principal toxic symptoms were marked esophagitis and gastritis with hemorrhage. Animal experiments to determine dermal and oral toxicity of dimethylphthalate showed that extremely high doses were considered necessary to produce toxic effects. Dimethylphthalate was found to be teratogenic by intraperitoneal injection of doses representing 1/10, 1/5, and 1/3 of the LD50 value into female rats at the 5th, 10th, and 15th day of gestation. This probably is of no significance in industrial exposures.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 194
2. Boiling point (760 mm Hg): 285 C (545 F)
3. Specific gravity (water = 1): 1.2
4. Vapor density (air = 1 at boiling point of dimethylphthalate): 6.7
5. Melting point: 0 to 2 C (32 to 36 F)
6. Vapor pressure at 100.3 C (212 F): 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.04
8. Evaporation rate (methyl acetate = 1): Almost zero

- **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving dimethylphthalate.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

4. Special precautions: None

- **Flammability**

1. Flash point: 146 C (295 F) (closed cup)
2. Autoignition temperature: 556 C (1032 F)
3. Flammable limits in air, % by volume: Lower: 1.2 (calculated at flash point)
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

According to Grant, contact of dimethylphthalate with the eye "produces considerable pain, but causes either no damage or only slight reversible disturbance of the epithelium." Air concentrations which would produce this effect are not given.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for dimethylphthalate had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use splash-proof safety goggles where liquid dimethylphthalate may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dimethylphthalate may occur and control methods which may be effective in each case:

Operation	Controls
Use as a plasticizer in compounding of plastics, primarily cellulose acetate, nitrocellulose, ethylcellulose, cellulose acetate butyrate, polystyrene, polyvinyl acetate, polyvinyl butyral, and polyvinyl chloride	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during manufacture of surface coatings containing plasticized resins and polymers, including furniture lacquers, printing inks, textile and paper coatings, and moisture-proof coatings for cellophane	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during molding, casting, extrusion, or other processing of heated, plasticized resins and polymers in manufacture of plastic articles	Local exhaust ventilation; general dilution ventilation
Use in spray (or dip applications or any method involving heat) of surface coatings containing plasticized resins and polymers, including furniture lacquers, printing inks, textiles and paper coatings, and moisture-proof coatings on cellophane	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a plasticizer in compounding of nitrile and neoprene rubber and chlorinated rubber	Local exhaust ventilation; general dilution ventilation; personal protective equipment

Operation	Controls
Use in spray or other applications of adhesives containing plasticizer, including polyvinyl acetate adhesives for cellulose acetate films, covering cut-out windows in cartons, or laminating cellulose acetate film to paper	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during processing of heated plasticized nitrile, neoprene, and chlorinated rubber into manufactured articles	Local exhaust ventilation; general dilution ventilation
Use during preparation of adhesives containing plasticizer, including polyvinyl acetate adhesives for cellulose film	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during manufacture of insect repellant formulations	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If dimethylphthalate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention if any discomfort continues. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If dimethylphthalate saturates the clothing, remove and clean the clothing before wearing it again. Wash any dimethylphthalate from the skin regularly, particularly when there has been much skin contact. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of dimethylphthalate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dimethylphthalate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing respiratory protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dimethylphthalate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber.

• Waste disposal methods:

Dimethylphthalate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dimethylphthalate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Burger, L. M., and Chandor, S. B.: "Fatal Ingestion of Plastic Resin Catalyst," *Archives of Environmental Health*, 23:402-404, 1971.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Lehman, A. J.: "Insect Repellents," *The Medical Bulletin*, 16:243-256, 1955.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Singh, A. R., et al.: "Teratogenicity of Phthalate Esters in Rats," *Journal of Pharmaceutical Science*, 61:51-55, 1972.
• Smyth, H. F., and Carpenter, C. P.: "Chemical Burn of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

RESPIRATORY PROTECTION FOR DIMETHYLPHTHALATE

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
250 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
9300 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 9300 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dimethylsulfate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_2SO_4$
- Synonyms: Methyl sulfate
- Appearance and odor: Colorless, oily liquid with a faint onion odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dimethylsulfate is 1 part of dimethylsulfate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 5 milligrams of dimethylsulfate per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has recommended for dimethylsulfate a Threshold Limit Value of 0.1 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dimethylsulfate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may readily enter the body through the skin.

- **Effects of overexposure**

Dimethylsulfate vapor is an extremely severe irritant of the eyes, respiratory tract, and skin. While exposure often produces no immediate effects other than slight eye and nose irritation, after a period of up to 10 hours or more, headache and giddiness with intense pain on exposure to light may occur. This is usually followed by inflammation of the throat and voice box, difficulty in speaking, difficulty in swallowing, cough, tightness of the chest, shortness of breath, a blue coloration of the skin, vomiting, diarrhea, and painful urination. Other effects are delirium, fever, yellow jaundice, and bloody urine. Liver and kidney damage may occur. If the liquid is swallowed, in addition to causing burns of the throat and stomach, the above effects may occur. Contact of the liquid with the eyes and skin will cause severe burns. Animal experiments have shown that this chemical may cause cancer in animals and their offspring.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dimethylsulfate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dimethylsulfate at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory tract, liver, kidneys, and central nervous system should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney damage has been observed in humans exposed to dimethylsulfate, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Since liver damage has been observed in humans exposed to dimethylsulfate, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

—14" x 17" chest roentgenogram: Dimethylsulfate causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Dimethylsulfate is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

2. *Periodic Medical Examination:* The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

• **Summary of toxicology**

Dimethylsulfate vapor is an extremely severe irritant of the eyes, mucous membranes, and skin; it is carcinogenic in rats. It has a strong vesicant action and rapidly hydrolyzes in the presence of water to produce sulfuric acid and methanol. It caused malignant tumors in rats in various organs by inhalation, subcutaneous injection, and following prenatal exposure. A single intravenous dose of 20 mg/kg given to 8 pregnant rats on day 15 of gestation induced malignant tumors, including 3 tumors of the nervous system, in 7 of 59 offspring which were observed for over 1 year. The LC50 in rats was 75 ppm for 18 minutes; autopsy findings were marked pulmonary edema, pulmonary emphysema, peribronchitis, and focal necrosis of the liver. Several human deaths have occurred from occupational exposure. While exposure of humans often produces no immediate effects other than occasional slight eye and nose irritation, after a latent period of up to 10 hours or more, there is onset of headache and giddiness with intense conjunctival irritation, photophobia, and periorbital edema; this is usually followed by inflammation of the pharyngo-laryngeal mucosa, dysphonia, aphonia, dysphagia, productive cough, oppression in the chest, dyspnea and cyanosis; vomiting and diarrhea may intervene. Dysuria may occur for 3 to 4 days; there may be persistence of laryngeal edema for up to 2 weeks and of photophobia for several months. Other effects are delirium, fever, icterus, albuminuria, and hematuria. Contact of the liquid with the eyes or skin will cause very severe burns due to its powerful vesicant action. In one incident of moderate skin contact with the liquid, generalized intoxication occurred even though there was prompt treatment of the skin; the vapor was inhaled for no more than a few minutes.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 126.1
2. Boiling point (760 mm Hg): 188.8 C (372 F)
3. Specific gravity (water = 1): 1.3
4. Vapor density (air = 1 at boiling point of dimethylsulfate): 4.35
5. Melting point: −31.8 C (−25 F)
6. Vapor pressure at 20 C (68 F): 0.5 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 2.8 (reacts slowly)
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Contact with water may allow formation of flammable concentrations of methyl alcohol.
2. Incompatibilities: Contact with strong oxidizers or with strong ammonia solutions may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as sulfuric acid mist, methyl alcohol, and carbon monoxide) may be released in a fire involving dimethylsulfate.
4. Special precautions: Dimethylsulfate will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 83.3 C (182 F) (closed cup)
2. Autoignition temperature: 187.8 C (370 F)
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: Patty states that "dimethylsulfate is a colorless, oily liquid, which is nearly odorless or which may have a faint onion-like odor."
2. Irritation Levels: Grant states that "injury of the eye by vapor of dimethylsulfate is a much more common industrial accident than injury by a splash of liquid, which is more easily prevented by goggles. Numerous instances of burns and poisoning from the vapor have been described. Also, in animal eyes the effects of the vapor have several times been studied and reproduced. Characteristically, during exposure to vapor of dimethylsulfate the patient or experimental animal is not aware of irritation or unpleasant sensation but begins to develop discomfort several hours later.

'Moeschlin in his book on poisonings particularly has placed great emphasis on the latent period that is characteristic of the action of dimethylsulfate vapors on the eyes, giving description of specific cases in which there were latent periods as long as six hours before severe inflammation of the eyes and respiratory tract developed. Browning in her book on toxicology has reviewed several of the reports in the literature of eye involvement from vapor exposure.

'Typical industrial exposure occurs when workmen pour dimethylsulfate from one container to another, with no irritation of eyes or nose, or no unpleasant odor to warn of danger. After several hours the eyes begin to feel irritated and have a sandy sensation. Photophobia and lacrimation develop; the lids become edematous and the conjunctiva hyperemic. The skin of the face and other exposed parts is reddened. The symptoms increase in intensity for several hours, and then superficial clouding and irregularity of the corneal epithelium may be seen. Associated with the ocular symptoms are temporary loss of smell and taste, with hoarseness and irritation of the respiratory passages which may become severe, and in the worst cases may develop into fatal pneumonia.

'The course of the eye injuries in the mildest cases may be spontaneous return to normal in a few days, or, in severe cases, gray necrosis of the epithelium, edema and infiltration of the corneal stroma, and permanent

partial opacification may result."

No quantitative information is available concerning the levels of dimethylsulfate which produce eye irritation. The effects on the eyes are delayed.

3. Evaluation of Warning Properties: Since dimethylsulfate is "almost odorless," and since the irritant effects produced by this compound are delayed, dimethylsulfate is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for dimethylsulfate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid dimethylsulfate.

• Clothing contaminated with dimethylsulfate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dimethylsulfate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dimethylsulfate, the person performing the operation should be informed of dimethylsulfate's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid dimethylsulfate, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with dimethylsulfate should be removed immediately and not reworn until the dimethylsulfate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid dimethylsulfate contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid dimethylsulfate, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with dimethylsulfate should be immediately washed or showered with soap or mild detergent and water to remove any dimethylsulfate.

• Employees who handle liquid dimethylsulfate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dimethylsulfate may occur and control methods which may be effective in each case:

Operation	Controls
Use as a methylating agent in organic chemical industry for manufacture of esters, ethers, and amines	Enclosed system/ segregation; general dilution ventilation; personal protective equipment
Use in manufacture of dyes, dyestuffs, coloring agents, and perfumes; use in pharmaceutical industry as a solvent for separation/preparation of mineral oils	Enclosed system/ segregation; general dilution ventilation; personal protective equipment
Use during analysis of automobile fluids	Enclosed system/ segregation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid dimethylsulfate or strong concentrations of dimethylsulfate vapors get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid dimethylsulfate or strong concentrations of dimethylsulfate vapors get on the skin, immediately flush the contaminated skin with large amounts of water. If liquid dimethylsulfate or strong concentrations of dimethylsulfate vapors penetrate through the clothing, remove the clothing immediately and flush the skin with large amounts of water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of dimethylsulfate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If dimethylsulfate has been swallowed and the person is conscious, give him large quantities of water immediately to dilute the dimethylsulfate. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dimethylsulfate is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.

3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Dimethylsulfate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dimethylsulfate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents, Technical Guide No. 6* (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• International Agency for Research on Cancer: *Some Aromatic Amines, Hydrazine and Related Substances, N-Nitroso Compounds and Miscellaneous Alkylating Agents*, Vol. 4 of *IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man*, Lyon, France, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-19, Dimethylsulfate*, Washington, D.C., 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadel-

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 4, 1974.

RESPIRATORY PROTECTION FOR DIMETHYLSULFATE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
10 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a full facepiece providing protection against dimethylsulfate. Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of dimethylsulfate; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 10 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Dinitrobenzene (All Isomers)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Ortho: 1,2-$C_6H_4(NO_2)_2$; Meta: 1,3-$C_6H_4(NO_2)_2$; Para: 1,4-$C_6H_4(NO_2)_2$
- Synonyms: O-dinitrobenzene; 1,2-dinitrobenzene; m-dinitrobenzene; 1,3-dinitrobenzene; p-dinitrobenzene; 1,4-dinitrobenzene
- Appearance: Pale yellow solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dinitrobenzene is 1 milligram of dinitrobenzene per cubic meter of air (mg/m³) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for dinitrobenzene a Threshold Limit Value of 0.15 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dinitrobenzene can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It is readily absorbed through the skin, either as solid, liquid, or vapor. Even a small amount absorbed from clothes or shoes may cause toxic symptoms.

- **Effects of overexposure**

Dinitrobenzene may affect the ability of blood to carry oxygen. A bluish discoloration of the skin may occur with headache, irritability, dizziness, weakness, nausea, vomiting, shortness of breath, drowsiness, and unconsciousness. If treatment is not given promptly, death may occur. The onset of symptoms may be delayed. Consuming alcohol may make symptoms worse. Dinitrobenzene may also cause an unpleasant taste or burning sensation in the mouth, dry, throat, and thirst. The eyes, hair, and skin may become yellowish. Dinitrobenzene may cause reduced vision. In addition, liver damage may occur. Repeated or prolonged exposure to dinitrobenzene may cause anemia.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dinitrobenzene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dinitrobenzene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, liver, cardiovascular system, and eyes should be stressed.

—A complete blood count: Dinitrobenzene has been shown to cause methemoglobinemia. Those with blood disorders may be at increased risk. A complete blood count should be performed, including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit. Observe for Heinz bodies.

—Liver function tests: Since liver damage has been observed in humans exposed to dinitrobenzene, a profile of liver function should be performed by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determinations should be performed at any time overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

Absorption of any isomer of dinitrobenzene, whether from inhalation of the vapor or dust or skin absorption

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

of the solid, causes anoxia due to the formation of methemoglobin; chronic exposure produces anemia. Exposed workers have complained of an unpleasant taste, burning sensation in the mouth, dry throat, and thirst. Signs and symptoms of overexposure are due to the loss of oxygen-carrying capacity of the blood. Rapid absorption through the intact skin is frequently the main route of entry. The onset of symptoms of methemoglobinemia is insidious and may be delayed for up to 4 hours; headache is commonly the first symptom and may become quite intense as the severity of methemoglobinemia progresses. Cyanosis develops early in the course of intoxication, first in the lips, the nose, and the ear lobes, and is often recognized by fellow workers. Cyanosis occurs when the methemoglobin concentration is 15% or more. Until the methemoglobin concentration approaches approximately 40%, the individual may feel well, have no complaints, and may insist nothing is wrong. At methemoglobin concentrations of over 40%, there usually is weakness and dizziness; up to 70% concentration there may be ataxia, dyspnea on mild exertion, tachycardia, nausea, vomiting, and drowsiness. The ingestion of alcohol has been reported to aggravate the toxic effects of dinitrobenzene. Chronic exposure of workers causes anemia; there are scattered reports of liver injury. Visual impairment has been reported in the form of reduced visual acuity and central scotomas, particularly for red and green colors; yellow discoloration of the conjunctiva and sclera is common. Yellow-brown discoloration of the hair and exposed skin of workers has been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 168.1
2. Boiling point (760 mm Hg): Ortho: 318 C (604 F); Meta: 300 C (572 F); Para: 297 C (566 F)
3. Specific gravity (water = 1): Ortho: 1.59; Meta: 1.57; Para: 1.63
4. Vapor density (air = 1 at boiling point of dinitrobenzene): 5.8
5. Melting point: Ortho: 117 C (243 F); Meta: 90 C (194 F); Para: 173 C (343 F)
6. Vapor pressure at 20 C (68 F): All isomers: Much less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Ortho: 0.01; Meta: 0.05; Para· 0.01
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Dinitrobenzene may detonate when subject to shock or when heated under confinement.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with caustics and metals such as tin and zinc may cause evolution of heat and increase in pressure.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving dinitrobenzene.
4. Special precautions: Liquid dinitrobenzene will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Explodes
2. Impact sensitivity (minimum fall of a 2 kg weight to cause at least one explosion in ten trials): Greater than 100 centimeters
2. Autoignition temperature: Data not available
4. Flammable limits in air, % by volume: Data not available
5. Extinguishant: None

- **Warning properties**

Grant states that "surface contact (with dinitrobenzene) may cause yellowing of the skin, and purportedly of the conjunctiva and cornea, but no original observations on corneal changes were found in the literature." According to Grant, "2,4-dinitrobenzene caused no inflammatory response when this substance was brought into contact with the uveal tract, retina, or conjunctiva" of guinea pigs.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for dinitrobenzene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situatio: If the use of respirators is necessary, the only respirators permitted

are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with dinitrobenzene or liquids containing dinitrobenzene, where skin contact may occur.

• If employees' clothing may have become contaminated with solid dinitrobenzene, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with dinitrobenzene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dinitrobenzene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dinitrobenzene, the person performing the operation should be informed of dinitrobenzene's hazardous properties.

• Where exposure of an employee's body to liquids containing dinitrobenzene may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes wet with liquids containing dinitrobenzene should be removed immediately and non-impervious clothing which becomes contaminated with dinitrobenzene should be removed promptly and such clothing should not be reworn until the dinitrobenzene is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where dinitrobenzene or liquids containing dinitrobenzene may contact the eyes.

SANITATION

• Skin that becomes wet with liquids containing dinitrobenzene should be immediately washed or showered with soap or mild detergent and water to remove any dinitrobenzene.

• Skin that becomes contaminated with dinitrobenzene should be promptly washed or showered with soap or mild detergent and water to remove any dinitrobenzene.

• Workers subject to skin contact with dinitrobenzene should wash with soap or mild detergent and water any areas of the body which may have contacted dinitrobenzene at the end of each work day.

• Eating and smoking should not be permitted in areas where dinitrobenzene or liquids containing dinitrobenzene are handled, processed, or stored.

• Employees who handle dinitrobenzene or liquids containing dinitrobenzene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dinitrobenzene may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of dyes and dye intermediates; use in organic synthesis in chemical industry as photographic developers, and as explosives	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in plastics industry as a substitute for camphor in production of celluloid; as a polymerization inhibitor	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as an explosive by substituting for TNT; use in explosive shells	Material substitution

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If dinitrobenzene or liquids containing dinitrobenzene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If dinitrobenzene or liquids containing dinitrobenzene get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If dinitrobenzene or liquids containing dinitrobenzene penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of dinitrobenzene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dinitrobenzene or liquids containing dinitroben-

zene have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If dinitrobenzene is spilled, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill.
3. For small quantities, sweep onto paper or other suitable material and burn in a suitable combustion chamber which allows burning in an unconfined condition and is equipped with an appropriate effluent gas cleaning device. Large quantities may be reclaimed; however, if this is not practical, dissolve in fuel oil and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Dinitrobenzene may be disposed of:

1. By making packages of dinitrobenzene in paper or other flammable material and burning in a suitable combustion chamber which allows burning in an unconfined condition and is equipped with an appropriate effluent gas cleaning device.
2. By dissolving dinitrobenzene in fuel oil and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dinitrobenzene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Linch, A. L.: "Biological Monitoring for Industrial Exposure to Cyanogenic Aromatic Nitro and Amino Compounds," *American Industrial Hygiene Association Journal*, 35:426-432, 1974.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• National Fire Protection Association: *Combustible Solids, Dusts, and Explosives*, Vol. 3 of *National Fire Codes*, National Fire Protection Association, Boston, 1973.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

• von Oettingen, W. F.: *The Aromatic Amino and Nitro Compounds, Their Toxicity and Potential Dangers*, U.S. Public Health Service Bulletin No. 271, U.S. Government Printing Office, Washington, D.C., 1941.

RESPIRATORY PROTECTION FOR DINITROBENZENE (ALL ISOMERS)

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any dust and mist respirator, except single-use.
10 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dinitrotoluene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $2,4\text{-}(NO_2)_2C_6H_3CH_3$
- Synonyms: 2,4-Dinitrotoluene; DNT
- Appearance and odor: Orange-yellow solid (sometimes shipped molten in tank cars) with a characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dinitrotoluene is 1.5 milligrams of dinitrotoluene per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dinitrotoluene can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed; It is readily absorbed through the skin. Even a small amount absorbed from clothes or shoes may cause toxic symptoms.

- **Effects of overexposure**

1. Short-term Exposure: Dinitrotoluene affects the ability of blood to carry oxygen normally. A bluish discoloration of the skin may occur with headache, irritability, dizziness, weakness, nausea, vomiting, shortness of breath, drowsiness, and unconsciousness. If treatment is not given promptly, death may occur. The onset of symptoms may be delayed. The ingestion of alcohol may cause increased susceptibility to the effects of dinitrotoluene.

2. Long-term Exposure: Repeated or prolonged exposure to dinitrotoluene may cause anemia and jaundice.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dinitrotoluene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dinitrotoluene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, liver, and cardiovascular system should be stressed.

—A complete blood count: Dinitrotoluene has been shown to cause methemoglobinemia. Those with blood disorders may be at increased risk. A complete blood count should be performed, including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit. Observe for Heinz bodies.

—Liver function tests: Since liver damage has been observed in humans exposed to dinitrotoluene, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determinations should be performed at any time overexposure is suspected or signs and symptoms of toxicity occur. The level of dinitrotoluene in the urine should be determined; excretion of dinitrotoluene in excess of 25 mg/liter indicates significant absorption.

- **Summary of toxicology**

Dinitrotoluene absorption, whether from inhalation of the vapor or absorption of the solid through skin, causes anoxia due to the formation of methemoglobin; jaundice and anemia have been reported. Signs and symptoms of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

overexposure are due to the loss of oxygen-carrying capacity of the blood. Rapid absorption through the intact skin is frequently the main route of entry. The onset of symptoms of methemoglobinemia is often insidious, and may be delayed for up to 4 hours; headache is commonly the first symptom and may become quite intense as the severity of methemoglobinemia progresses. Cyanosis develops early in the course of intoxication, first in the lips, the nose, and the ear lobes, and is often recognized by fellow workers. Cyanosis occurs when the methemoglobin concentration is 15% or more. The individual may feel well, have no complaints, and may insist that nothing is wrong until the methemoglobin concentrations approaches approximately 40%. At methemoglobin concentrations of over 40% there usually is weakness and dizziness; at up to 70% concentration there may be ataxia, dyspnea on mild exertion, tachycardia, nausea, vomiting, and drowsiness. Ingestion of alcohol is reported to aggravate the toxic effects of dinitrotoluene.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 182.1
2. Boiling point (760 mm Hg): Slow decompostion at 250 C (482 F); self-sustained decomposition at 270 C (518 F)
3. Specific gravity (water = 1): Solid: 1.52; Liquid: 1.32
4. Vapor density (air = 1 at boiling point of dinitrotoluene): Not applicable (too high boiling)
5. Melting point: 70 C (158 F)
6. Vapor pressure at 20 C (68 F): 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.03
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Temperatures above 250 C (482 F)
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with caustics and chemically active metals such as tin or zinc may cause evolution of heat and increase in pressure.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving dinitrotoluene.
4. Special precautions: Liquid dinitrotoluene will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 206.7 C (404 F) (closed cup)
2. Autoignition temperature: Data not available
3. Impact sensitivity (minimum fall of a 2 kg weight to cause at least one explosion in ten trials): Greater than 100 centimeters
4. Flammable limits in air, % by volume: Not available
4. Extinguishant: Water, dry chemical, carbon dioxide

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of dinitrotoluene.
2. Eye Irritation Level: Grant states that "a severe burn of the skin, eyelids, and cornea of one eye, with permanent scarring, has been attributed in one instance to hot fumes of dinitrotoluene." There is no quantitative information available concerning the concentrations which would produce these effects.
3. Evaluation of Warning Properties: Since no quantitative information is available relating the warning properties of dinitrotoluene to air concentration, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for dinitrotoluene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with molten dinitrotoluene.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with dinitrotoluene or liquids containing dinitrotoluene, where skin contact may occur.
- If employees' clothing may have become contaminated with solid dinitrotoluene, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with dinitrotoluene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dinitrotoluene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dinitrotoluene, the person performing the operation should be informed of dinitrotoluene's hazardous properties.
- Where exposure of an employee's body to dinitrotoluene or liquids containing dinitrotoluene may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes wet with molten dinitrotoluene or liquids containing dinitrotoluene should be removed immediately and non-impervious clothing which becomes contaminated with solid dinitrotoluene should be removed promptly and such clothing should not be reworn until the dinitrotoluene is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of molten dinitrotoluene contacting the eyes.

SANITATION

- Skin that becomes wet with molten dinitrotoluene or liquids containing dinitrotoluene should be immediately washed or showered with soap or mild detergent and water to remove any dinitrotoluene.
- Workers subject to skin contact with dinitrotoluene or liquids containing dinitrotoluene should wash with soap or mild detergent and water any areas of the body which may have contacted dinitrotoluene at the end of each work day.
- Skin that becomes contaminated with dinitrotoluene should be promptly washed or showered with soap or mild detergent and water to remove any dinitrotoluene.
- Eating and smoking should not be permitted in areas where dinitrotoluene or liquids containing dinitrotoluene are handled, processed, or stored.
- Employees who handle dinitrotoluene or liquids containing dinitrotoluene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dinitrotoluene may occur and control methods which may be effective in each case:

Operation	Controls
Use in the manufacture of toluene diisocyanate for production of polyurethane plastics	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in production of military and some commercial explosives; use to plasticize cellulose nitrate in explosives; use to moderate burning rate of propellants and explosives; use in manufacture of gelatin explosives (less sensitive to shock or friction); use as a waterproofing coating for some smokeless powders; use as an intermediate in TNT manufacture	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of azo dye intermediates; use in organic synthesis in preparation of toluidines, dyes, and explosives	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If dinitrotoluene or liquids containing dinitrotoluene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. If molten dinitrotoluene gets into the eyes, flush the eyes immediately with large amounts of water to remove heat. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If dinitrotoluene or liquids containing dinitrotoluene get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If dinitroto-

luene or liquids containing dinitrotoluene penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately. If molten dinitrotoluene gets on the skin, immediately flush the skin with water to remove heat. Wash the skin with soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of dinitrotoluene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dinitrotoluene has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If dinitrotoluene is spilled, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill.
3. For small quantities, sweep onto paper or other suitable material and burn in a suitable combustion chamber which allows burning in an unconfined condition and is equipped with an appropriate effluent gas cleaning device. Large quantities may be reclaimed; however, if this is not practical, dissolve in fuel oil and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
4. If in the molten form, allow to cool and solidify and treat as in (3) above.

• Waste disposal methods:

Dinitrotoluene may be disposed of:

1. By making packages of dinitrotoluene in paper or other flammable material and burning in a suitable combustion chamber which allows burning in an unconfined condition and is equipped with an appropriate effluent gas cleaning device.
2. By dissolving dinitrotoluene in fuel oil and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES*

• American Conference of Governmental Industrial Hygienists: "Dinitrotoluene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Linch, A. L.: "Biological Monitoring for Industrial Exposure to Cyanogenic Aromatic Nitro and Amino Compounds," *American Industrial Hygiene Association Journal*, 35:426-432, 1974.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-93, Dinitrotoluene*, Washington, D.C., 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• von Oettingen, W. F.: *The Aromatic Amino and Nitro Compounds, Their Toxicity and Potential Dangers*, U.S. Public Health Service Bulletin No. 271, U.S. Government Printing Office, Washington, D.C., 1941.

RESPIRATORY PROTECTION FOR DINITROTOLUENE

Condition	Minimum Respiratory Protection* Required Above 1.5 mg/m³
Particulate or Vapor Concentration	
15 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
75 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dioxane*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $OCH_2CH_2OCH_2CH_2$
- Synonyms: Diethylene dioxide; diethylene ether; dioxan; p-dioxane; 1,4-dioxane
- Appearance and odor: Colorless liquid with a mild ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dioxane is 100 parts of dioxane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 360 milligrams of dioxane per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to a ceiling level of 1 ppm averaged over a 30-minute period, and that dioxane be regulated as an occupational carcinogen. The NIOSH Criteria Document for Dioxane should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dioxane can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Overexposure to dioxane may cause irritation of the eyes, nose, and throat. It may also cause drowsiness, dizziness, loss of appetite, headache, nausea, vomiting, stomach pain, and liver and kidney damage. Prolonged skin exposure to the liquid may cause drying and cracking. Dioxane has been shown to induce tumor formation in experimental animals.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dioxane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dioxane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the upper respiratory system, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Dioxane may cause liver damage. A profile of liver function should be performed by using a medically acceptable array of biochemical tests.

—Urinalysis: Since kidney damage has also been observed from exposure, a urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Skin disease: Dioxane is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—14" x 17" chest roentgenogram: Dioxane causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Dioxane is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

• **Summary of toxicology**

Dioxane vapor is a mucous membrane irritant, and on prolonged exposure is toxic to the liver and kidneys. Repeated exposure of several animal species to 1000 ppm produced damage to kidneys and liver, and the repeated inhalation of 800 ppm over 30 days resulted in fatal kidney injury in some rabbits. Human volunteers exposed for 15 minutes to 300 ppm reported mild transient irritation of the eyes, nose, and throat. There is significant absorption of the liquid through the skin, adding to the inhalation hazard. Prolonged or repeated skin contact may also result in drying and cracking due to defatting action. Fatal intoxication due to liver necrosis and severe kidney damage has been reported in workers after two months of heavy exposure to dioxane vapor; the onset of poisoning was marked by drowsiness and headache, nausea, vomiting, and irritation of the eyes and respiratory passages. In one fatal case there was significant damage to the brain as well as to liver and kidney. Due to its mild odor, serious or fatal exposures have been experienced without forewarning. Tumors of the nose, liver, and lungs have been reported in animals following ingestion of high concentrations of dioxane. Immersion of chick embryoes in dioxane has been reported to cause possible mutagenic effects. The significance of these findings in humans in unknown.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 88
2. Boiling point (760 mm Hg): 101 C (214 F)
3. Specific gravity (water = 1): 1.03
4. Vapor density (air = 1 at boiling point of dioxane): 3.0
5. Melting point: 11.8 C (53 F)
6. Vapor pressure at 20 C (68 F): 29 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): 2.7

• **Reactivity**

1. Conditions contributing to instability: Heat, long exposure to moisture.
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products. Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving dioxane.
4. Special precautions: Dioxane is hydroscopic and will produce peroxides in the presence of moisture. Dioxane containing peroxides should not be distilled to dryness because of the potential explosion of nonvolatile peroxides.

• **Flammability**

1. Flash point: 12 C (54 F) (closed cup)
2. Autoignition temperature: 180 C (356 F)
3. Flammable limits in air, % by volume: Lower: 2.0; Upper: 22.0
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: Summer reports an odor threshold of 170 ppm; May reports 2.7 and 170 ppm.
2. Eye Irritation Level: Grant states that "in human beings, irritation of the eye is noted only at concentrations greater than 220 ppm of vapor in air." Patty states that at 300 ppm, dioxane "caused irritation of the eyes, nose, and throat; and at 500 ppm, it was objectionable. Even at higher concentrations, the initial irritation to eyes and respiratory passages is transitory . . . ."
3. Evaluation of Warning Properties: Patty states that the initial irritation produced by exposure to dioxane is transitory and that the "warning properties of dioxane are completely inadequate to prevent exposure to toxic amounts." The AIHA *Hygienic Guide* also notes that "the vapor has poor warning properties and can be inhaled in amounts which may cause serious intoxication or death with injury of the liver and kidneys."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of dioxane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure dioxane may be used. An analytical method for dioxane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted

are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid dioxane.
- Any clothing which becomes wet with liquid dioxane should be removed immediately and non-impervious clothing which becomes contaminated with dioxane should be removed promptly and such clothing should not be reworn until the dioxane is removed from the clothing.
- Clothing wet with liquid dioxane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dioxane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dioxane, the person performing the operation should be informed of dioxane's hazardous properties.
- Employees should be provided with and required to use splash-proof safety goggles where liquid dioxane may contact the eyes.

SANITATION

- Skin that becomes contaminated with dioxane should be promptly washed or showered to remove any dioxane.
- Eating and smoking should not be permitted in areas where liquid dioxane is handled, processed, or stored.
- Employees who handle liquid dioxane should wash their hands thoroughly before eating, smoking, or using toilet facilities.
- Areas in which exposure to dioxane may occur should be identified by signs or other appropriate means, and access to these areas should be limited to authorized persons.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dioxane may occur and control methods which may be effective in each case:

Operation	Controls
Use in spray application of natural and synthetic resin-based varnishes, lacquers, and paints	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in dipping, roller coating, tumbling, knifing, and brushing of natural and synthetic resin-based varnishes, lacquers, and paints	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent for fats, oils, waxes, greases, and natural and synthetic resins	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a wetting agent in textile processing, dye baths, and stain and printing compositions	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a degreaser	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a dehydrating agent in preparation of histological slides	Local exhaust ventilation
Use in manufacture of detergents and cleaning preparations; manufacture of polishing compounds	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a stabilizer for chlorinated solvents; use in preparation of cosmetics and deodorants; use in purification of drugs	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a working fluid for scintillation counter samples	General dilution ventilation; personal protective equipment
Use as a solvent in pulping of wood; polishing compounds	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If dioxane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If dioxane gets on the skin, promptly wash the contaminated skin with water. If dioxane soaks through the clothing, remove the clothing promptly and wash the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of dioxane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dioxane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dioxane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Dioxane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Dioxane may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Dioxane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Dioxane," *Hygienic Guide Series*, Detroit, Michigan, 1960.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Dioxane*, HEW Publication No. (NIOSH) 77-226, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Dioxane*, New York, 1971.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 11, 1976.

RESPIRATORY PROTECTION FOR DIOXANE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
200 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 200 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Diphenyl*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5C_6H_5$ or $C_{12}H_{10}$
- Synonyms: Biphenyl; phenylbenzene
- Appearance and odor: Colorless to pale yellow solid with a very characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for diphenyl is 0.2 part of diphenyl per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1 milligram of diphenyl per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Diphenyl can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin. (It may be absorbed through the skin).

- **Effects of overexposure**

1. Short-term Exposure: Exposure to diphenyl may cause irritation of the eyes and throat.

2. Long-term Exposure: Repeated exposure to diphenyl may cause headache, nausea, indigestion, abdominal pain, fatigue, numbness, and aching of the limbs (nervous system damage), and liver damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to diphenyl.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to diphenyl at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from diphenyl exposure.

—Liver disease: Exposure to high concentrations of vapor may incur damage to the liver, to which individuals with pre-existing liver disease may be more susceptible.

—Skin disease: Diphenyl can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Central nervous system disorders: Exposure to high concentrations of vapor may cause damage to the central nervous system, to which individuals with pre-existing conditions may be more susceptible.

—Kidney disease: Although diphenyl is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

At concentrations of 5 mg/m³ or higher, irritation of the eyes and throat has been reported. Employees with repeated exposure to higher concentrations had gastrointestinal symptoms as well as polyneuritic complaints, with abnormalities of both the electroencephalogram and the electromyogram. Some showed hepatic damage detected by liver function tests and biopsy, and one fatal case of liver necrosis with some areas of cirrhosis occurred in an individual who had been exposed regularly to concentrations of vapor in air of approximately 100 mg/m³. At higher concentrations, mice and rats

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

showed damage to the liver and kidney, as well as broncho-pulmonary effects.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 154
  2. Boiling point (760 mm Hg): 254 C (489 F)
  3. Specific gravity (water = 1): 1.04
  4. Vapor density (air = 1 at boiling point of diphenyl): Not applicable
  5. Melting point: 69 C (156 F)
  6. Vapor pressure at 20 C (68 F): Very low
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving diphenyl.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 113 C (235 F) (closed cup)
  2. Autoignition temperature: 538 C (1004 F)
  3. Flammable limits in air, % by volume: Lower: 0.6 at 111 C (212 F); Upper: 5.8 at 155 C (311 F)
  4. Extinguishant: Water. dry chemical, carbon dioxide, and foam.
- **Warning properties**
  1. Odor Threshold: The AIHA *Hygienic Guide* states that diphenyl has a "distinctive aromatic odor" which is detectable at 0.06 to 0.29 mg/m^3.
  2. Eye Irritation Level: Concerning eye irritation, the *Hygienic Guide* reports that "mild to moderate irritation is reported by humans exposed to the vapor." Grant reports that when concentrations of 3 to 4 ppm of Dowtherm A (a mixture of diphenyloxide (75%) and diphenyl (25%)) are reached, there is irritation of the eyes, nose, and throat."
  3. Evaluation of Warning Properties: Since the odor threshold of diphenyl is well below the permissible exposure limit, diphenyl is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for diphenyl is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid diphenyl or liquids containing diphenyl.
- If employees' clothing may have become contaminated with solid diphenyl, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with diphenyl should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of diphenyl from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the diphenyl, the person performing the operation should be informed of diphenyl's hazardous properties.
- Non-impervious clothing which becomes contaminated with diphenyl should be removed promptly and not reworn until the diphenyl is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of molten diphenyl contacting the eyes.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where solid diphenyl or liquids containing diphenyl may contact the eyes.

SANITATION

- Skin that becomes contaminated with solid diphenyl or liquids containing diphenyl should be promptly washed or showered with soap or mild detergent and water to remove any diphenyl.
- Eating and smoking should not be permitted in areas where solid diphenyl or liquids containing diphenyl are handled, processed, or stored.
- Employees who handle solid diphenyl or liquids containing diphenyl should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to diphenyl may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during mixing for paper impregnation process	Local exhaust ventilation; personal protective equipment
Liberation during impregnation process for producing wrapping papers	Local exhaust ventilation
Liberation during wrapping and packaging of citrus with diphenyl-impregnated paper	Local exhaust ventilation; personal protective equipment
Liberation during use as a dye carrier for plastics and synthetic resin dyeing; during production of derivatives as diphenyl oxide	General dilution ventilation
Use as a heat-transfer medium	General dilution ventilation; personal protective equipment
Liberation during solvent applications in producing allyl alcohol from propylene oxide or phenol	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If diphenyl gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If diphenyl gets on the skin, immediately flush the contaminated skin with water. If diphenyl soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of diphenyl, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

If diphenyl has been swallowed, do not induce vomiting. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If diphenyl is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill.
3. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, use a procedure similar to that for small quantities.

- Waste disposal methods:

Diphenyl may be disposed of:

1. By making packages of diphenyl in paper or other flammable material and burning in a suitable combustion chamber.
2. By dissolving diphenyl in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Diphenyl," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Diphenyl," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hakkinen, I., et al.: "Diphenyl Poisoning in Fruit Paper Production," *Archives of Environmental Health*, 26:70-74, 1973.

• Henderson, J. S., and Weeks, J. L.: "A Study of the Carcinogenicity for Skin of a Polyphenyl Coolant," *Industrial Medicine*, 42:2, pp. 10-21, February 1973.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Paget, G. E. (ed.): *Methods in Toxicology*, F. A. Davis, Philadelphia, 1970.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

* SPECIAL NOTE

Diphenyl appears on the Environmental Protection Agency's (EPA) Chemical Assessment Group "List of Chemicals" having substantial evidence of carcinogenicity (Environmental Protection Agency, Washington, D.C., 22 April 1980).

RESPIRATORY PROTECTION FOR DIPHENYL

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³ (0.2 ppm)
Particulate or Vapor Concentration	
10 mg/m³ (2 ppm) or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s). Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ (10 ppm) or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
300 mg/m³ (60 ppm) or less	A powered air-purifying chemical cartridge respirator with a full facepiece, organic vapor cartridge, and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 300 mg/m³ (60 ppm) or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Dipropylene Glycol Methyl Ether

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CH(OCH_3)CH_2OCH_2CH(OH)CH_3$
- Synonyms: Dipropylene glycol monomethyl ether; Dowanol 50B
- Appearance and odor: Colorless liquid with a weak odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for dipropylene glycol methyl ether is 100 parts of dipropylene glycol methyl ether per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 600 milligrams of dipropylene glycol methyl ether per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Dipropylene glycol methyl ether can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

Overexposure to high airborne levels or liquid splashes of dipropylene glycol methyl ether may cause irritation of the eyes and nose. Swallowing, breathing, or absorbing this chemical through the skin may cause nausea and sleepiness.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to dipropylene glycol methyl ether.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to dipropylene glycol methyl ether at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from dipropylene glycol methyl ether exposure.

—Liver disease: Although dipropylene glycol methyl ether is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although dipropylene glycol methyl ether is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of dipropylene glycol methyl ether might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Dipropylene glycol methyl ether is primarily a narcotic with mild irritating properties. Single 7-hour exposures of rats to 500-ppm vapor resulted in only mild narcosis with rapid recovery. Repeated daily inhalation exposures to four animal species at 300 to 400 ppm also produced mild narcosis but no other significant effects. These levels are disagreeable to humans, causing some eye and nasal irritation. High vapor concentrations or liquid splashes cause transient irritation of the eyes. There is no skin irritation from even prolonged or

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

repeated contact. Chronic systemic effects have not been observed in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 148
  2. Boiling point (760 mm Hg): 190 C (374 F)
  3. Specific gravity (water = 1): 0.95
  4. Vapor density (air = 1 at boiling point of dipropylene glycol methyl ether): 5.11
  5. Melting point: −83 C (−117 F)
  6. Vapor pressure at 20 C (68 F): 0.3 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 0.02
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving dipropylene glycol methyl ether.
  4. Special precautions: Dipropylene glycol methyl ether will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 85 C (185 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Browning states that dipropylene glycol monomethyl ether has "a mild ether odor in moderate concentrations but a strong objectionable odor at 1000 ppm."
  2. Eye Irritation Level: Dipropylene glycol methyl ether vapor is not known to be an eye irritant, but, according to Patty, the undiluted liquid when placed in a rabbit's eye "on each of five consecutive days (causes) a mild transitory irritation of the conjunctival membranes."
  3. Other Information: According to Browning, "high concentrations of the vapor cause marked irritation of the nasal mucuous membrane, which is difficult for humans to tolerate."
  4. Evaluation of Warning Properties: Browning reports that nasal irritation is a warning property which "is a valuable protection against concentrations which might have toxic effects, and an inhalation hazard is not likely since, as Rowe remarks, 'levels that may be toxic on repeated exposure probably will not be tolerated voluntarily.'" The *Documentation of TLVs* notes that concentrations of 300 to 400 ppm "were very disagreeable to man; levels of 100 ppm, which might be voluntarily tolerated without complaints, were considered to be safe with respect to organic injury."

For the purposes of this guideline, dipropylene glycol methyl ether is treated as a material with good warning properties.

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of dipropylene glycol methyl ether vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure dipropylene glycol methyl ether may be used. An analytical method for dipropylene glycol methyl ether is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Clothing wet with liquid dipropylene glycol methyl ether should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of dipropylene glycol methyl ether from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the dipropylene glycol

methyl ether, the person performing the operation should be informed of dipropylene glycol methyl ether's hazardous properties.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to dipropylene glycol methyl ether may occur and control methods which may be effective in each case:

Operation	Controls
Use as a general solvent for oils and greases; use in application of coating materials	General dilution ventilation
Use as a coupling and dispersing agent in manufacture and application of printing pastes, dyes, and inks	General dilution ventilation
Use in manufacture of cosmetics	General dilution ventilation
Use in manufacture of latex paints, lacquers, and leather protective coatings	General dilution ventilation
Use as a slimicide in food packaging and adhesives in food industry	General dilution ventilation
Use as a heat-transfer agent in hydraulic brake fluid	General dilution ventilation
Use in glass cleaning, metal cleaning, and antifogging compositions	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If dipropylene glycol methyl ether gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If dipropylene glycol methyl ether saturates the clothing, promptly remove the clothing and wash or shower. Wash any dipropylene glycol methyl ether from the skin regularly. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of dipropylene glycol methyl ether, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When dipropylene glycol methyl ether has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If dipropylene glycol methyl ether is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber or absorbed in vermiculite, dry sand, earth, or a similar material and disposed of in a sanitary landfill.

• Waste disposal methods:

Dipropylene glycol methyl ether may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a sanitary landfill.
2. By atomizing in a suitable combustion chamber.

• American Conference of Governmental Industrial Hygienists: "Dipropylene Glycol Methyl Ether," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Dow Chemical Company: *Material Safety Data Sheet - Dipropylene Glycol Methyl Ether.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Rowe, V. K., et al.: "Toxicology of Mono-, Di-, and Tri- Propylene Glycol Methyl Ethers," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 9:509-525, 1954.

RESPIRATORY PROTECTION FOR DIPROPYLENE GLYCOL METHYL ETHER

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Endrin

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{12}H_8Cl_6O$
- Synonyms: 1,2,3,4,10,10-Hexachloro-6,7-epoxy-1,4,4a,5,6,7,8,8a-octahydro-1,4-endo-endo-5,8-dimethanonaphthalene
- Appearance and odor: Colorless to tan solid with a mild chemical odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for endrin is 0.1 milligram of endrin per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Endrin can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to endrin may cause sudden convulsions which may occur from 30 minutes to 10 hours after exposure. Headache, dizziness, sleepiness, weakness, and loss of appetite may be present for two to four weeks following this exposure. A number of deaths have occurred from swallowing endrin. In less severe cases of endrin poisoning, the complaints include headache, dizziness, abdominal discomfort, nausea, vomiting, insomnia, agitation, and mental confusion. Experimental feeding of endrin to animals has produced abnormalities in their offspring.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to endrin.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to endrin at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of convulsive disorders would be expected to be at increased risk from exposure. Examination of the nervous system and liver should be stressed. The concentration of endrin in the blood is helpful in determining the extent of absorption.

2. Periodic Medical Examination: The aforementioned medical examination should be repeated on an annual basis.

- **Summary of toxicology**

Endrin as the dust or in solution is a convulsant. Single doses of 2.5 mg/kg of endrin administered orally to pregnant golden hamsters during the period of fetal organogenesis caused a high incidence of fetal deaths, congenital anomalies, and growth retardation. Rats fed a diet of 50 or 100 ppm endrin for 2 years developed degenerative changes in the liver. In humans, the first effect of endrin intoxication is frequently a sudden epileptiform convulsion, which may occur from 30 minutes to up to 10 hours after overexposure; it lasts for several minutes and is usually followed by a stuporous state for 15 minutes to 1 hour. The electroencephalogram may show dysrhythmic changes which frequently precede convulsions; withdrawal from exposure usually results in a normal electroencephalogram within 1 to 6 months. In most cases recovery is rapid, but headache, dizziness, lethargy, weakness, and anorexia may persist

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

for 2 to 4 weeks. In less severe cases of endrin intoxication, the complaints are headache, dizziness, abdominal discomfort, nausea, vomiting, insomnia, agitation and, occasionally, slight mental confusion. There are numerous reports of fatalities from ingestion of endrin. In one nonfatal incident, ingestion of bread made with endrin-contaminated flour resulted in sudden convulsions in three people; in one person the serum endrin level was 0.053 ppm 30 minutes after the convulsion and 0.038 ppm after 20 hours; in the other two cases no endrin was detected in the blood at 8.5 or 19 hours, respectively, after convulsions.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 380.9
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.7
4. Vapor density (air = 1 at boiling point of endrin): Not applicable
5. Melting point: 200 C (392 F) decomposes
6. Vapor pressure at 20 C (68 F): 0.0000002 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 160 ppb
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Temperatures above 200 C (392 F) cause a chemical change that gives off heat and may cause containers to burst. If a solvent is present, flammable vapors may be formed from it.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids may cause evolution of heat and formation of explosive solvent vapors.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, other volatile chlorinated compounds, and carbon monoxide) may be released when endrin decomposes.
4. Special precautions: None

- **Flammability**

1. Solid not combustible; may be dissolved in flammable solvent

- **Warning properties**

Since the vapor pressure of endrin is negligible, warning properties are not considered.
Endrin is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for endrin is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with endrin or liquids containing endrin.
- If employees' clothing has had any possibility of being contaminated with endrin or liquids containing endrin, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing which has had any possibility of being contaminated with endrin should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of endrin from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the endrin, the person performing the operation should be informed of endrin's hazardous properties.
- Where there is any possibility of exposure of an employee's body to endrin or liquids containing endrin, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with endrin should be removed immediately and not reworn until the endrin is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is

any possibility of endrin or liquids containing endrin contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to endrin, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with endrin should be immediately washed or showered with soap or mild detergent and water to remove any endrin.

• Workers subject to skin contact with endrin or liquids containing endrin should wash with soap or mild detergent and water any areas of the body which may have contacted endrin at the end of each work day.

• Eating and smoking should not be permitted in areas where endrin or liquids containing endrin are handled, processed, or stored.

• Employees who handle endrin or liquids containing endrin should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to endrin may occur and control methods which may be effective in each case:

Operation	Controls
Application as an insecticide on cotton fields and vegetable crops, and as a rodenticide against mice and chipmunks in orchards	Personal protective equipment
Formulation for use as an insecticide and rodenticide	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Manufacture of endrin	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If endrin or liquids containing endrin get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If endrin or liquids containing endrin get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If endrin or liquids containing endrin penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of endrin, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When endrin or liquids containing endrin have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If endrin is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquid containing endrin should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Endrin may be disposed of in sealed containers in a secured sanitary landfill.

ADDITIONAL INFORMATION

To find additional information on endrin, look up endrin in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Endrin," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Coble, Y., et al.: "Acute Endrin Poisoning," *Journal of the American Medical Association*, 202:153-157, 1967.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• Jager, K. W.: *Aldrin, Dieldrin, Endrin and Telodrin - An Epidemiological and Toxicological Study of Long-Term Occupational Exposure*, Elsevier, Amsterdam, 1970.

• Ottolenghi, A. D., et al.: "Teratogenic Effects of Aldrin, Dieldrin, and Endrin in Hamsters and Mice," *Teratology*, 9:11-16, 1974.

• Shell Chemical Company: *Material Safety Data Sheet - Endrin.*

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

RESPIRATORY PROTECTION FOR ENDRIN

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
1 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ or less	A powered air-purifying respirator with an organic vapor cartridge and high efficiency particulate filter, including pesticide respirators which meet the requirements of this class. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of endrin; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 200 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Epichlorohydrin*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_3H_5OCl
- Synonyms: 1-Chloro-2,3-epoxypropane; 2-chloropropylene oxide; gamma-chloropropylene oxide
- Appearance and odor: Colorless liquid with an irritating chloroform-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for epichlorohydrin is 5 parts of epichlorohydrin per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 19 milligrams of epichlorohydrin per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be reduced to 2 mg/m³ (0.5 ppm) averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 19 mg/m³ averaged over a 15-minute period. The NIOSH Criteria Document for Epichlorohydrin should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Epichlorohydrin can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Epichlorohydrin may cause irritation of the eyes, respiratory tract, and skin. Nausea and vomiting may also occur. Coughing, difficult breathing, and a blue coloration of the skin may be present. Liquid epichlorohydrin may produce blistering and deep-seated pain on contact with the skin. The liquid is highly irritating to the eyes. Breathing difficulty may occur several hours after exposure. A person may become sensitized to this chemical so that even very small amounts cannot be tolerated.

2. Long-term Exposure: Repeated or prolonged skin contact with epichlorohydrin may cause skin burns. Repeated or prolonged contact with this chemical might also cause liver, lung, and kidney injury. Antifertility effects, including persistent sterility, have been induced in animals exposed to epichlorohydrin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to epichlorohydrin.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to epichlorohydrin at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, hematopoetic and respiratory systems, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Epichlorohydrin may cause human lung damage. Surveillance of the lungs is indicated.

—Pulmonary function testing of FVC and FEV (1 sec): Epichlorohydrin is a severe pulmonary irritant in animals.

—Urinalysis: Since kidney damage has also been observed from exposure, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Eye disease: Epichlorohydrin is a severe eye irritant and may cause tissue damage. Those with pre-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety a Health Administration

551

September 1978

existing eye problems may be at increased risk from exposure.

—Liver function tests: Epichlorohydrin may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Skin disease: Epichlorohydrin is a defatting agent and can cause dermatitis on prolonged exposure. It can also cause burning, itching, blisters, skin erosion, redness, and residual erythema which may occur from a few minutes to several hours after exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Medical warning: Employees should be informed that large doses of epichlorohydrin have caused antifertility effects in animals; however, no effects have been found on potency.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

Epichlorohydrin vapor is a potent eye and respiratory irritant. The LC50 for rats was 500 ppm for 4 hours; the animals showed gradual development of cyanosis followed by muscular relaxation of the extremities, but not narcosis. Rats exposed repeatedly to 120 ppm for 6-hour periods showed lung, liver, and kidney injury; some respiratory distress was observed at 56 ppm, while 9 ppm produced no effects. The liquid is markedly irritating when instilled in the eye and intensely irritating to the depilated skin of laboratory animals, leading to widespread necrosis. Subcutaneous injection of epichlorohydrin in animals has been reported to cause sarcoma at the site of injection. In man, contact of the liquid with the skin at first produces a slight transient burning sensation which may be followed several hours later by blistering and pain in the region of contact; it is also highly irritating to the eyes. An occasional case of sensitization with resulting intolerance to very small quantities of the substance has been reported. At 25 ppm the odor is recognized by the majority of persons; one report indicated eye and nose irritation only at levels exceeding 100 ppm while another stated that 40 ppm at the site of a spill caused immediate eye, nose, and throat irritation. The earliest symptoms of intoxication may be referable to the gastrointestinal tract (nausea, vomiting, abdominal discomfort) or pain in the region of the liver; labored breathing, cough, and cyanosis may be evident; the onset of chemical pneumonitis may occur several hours after exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 92.5
2. Boiling point (760 mm Hg): 115 C (239 F)
3. Specific gravity (water = 1): 1.18
4. Vapor density (air = 1 at boiling point of epichlorohydrin): 3.19
5. Melting point: −58 C (−72 F)
6. Vapor pressure at 20 C (68 F): 13 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 6.4
8. Evaporation rate (butyl acetate = 1): 1.35

- **Reactivity**

1. Conditions contributing to instability: Temperatures above 325 C (617 F) will cause epichlorohydrin to polymerize.
2. Incompatibilities: Contact with strong acids, caustics, zinc, aluminum, chlorides of iron and aluminum and strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as phosgene, hydrogen chloride, and carbon monoxide) may be released in a fire involving epichlorohydrin.
4. Special precautions: Epichlorohydrin will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 37.8 C (100 F) (closed cup)
2. Autoignition temperature: 415.6 C (780 F)
3. Flammable limits in air, % by volume: Lower: 3.8; Upper: 21.0
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

- **Warning properties**

The AIHA *Hygienic Guide* states that 5 ppm of epichlorohydrin, the permissible exposure limit, cannot be detected by odor. At 16 ppm, four humans "detected the presence of epichlorohydrin, but only two could identify it;" at 64 ppm, all four could recognize the odor. In another investigation, half of a group of people detected 10-12 ppm, and within 5 minutes all of the subjects detected 25 ppm. According to the *Hygienic Guide*, "the threshold for nose and eye irritation is reported to be greater than 100 ppm." Since the warning properties of epichlorohydrin do not become evident until concentrations are several times the permissible exposure limit, epichlorohydrin is treated as a material with poor warning properties.

Epichlorohydrin is an eye irritant. The NIOSH Criteria Document cites data indicating that exposure to 20 ppm for one hour causes temporary burning of the eye and nasal passages.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of epichlorohydrin. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure epichlorohydrin may be used. An analytical method for epichlorohydrin is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid epichlorohydrin.

• Clothing contaminated with liquid epichlorohydrin should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of epichlorohydrin from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the epichlorohydrin, the person performing the operation should be informed of epichlorohydrin's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid epichlorohydrin, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with liquid epichlorohydrin should be removed immediately and not reworn until the epichlorohydrin is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid epichlorohydrin contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid epichlorohydrin, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid epichlorohydrin should be immediately washed or showered with soap or mild detergent and water to remove any epichlorohydrin.

• Eating and smoking should not be permitted in areas where liquid epichlorohydrin is handled, processed, or stored.

• Employees who handle liquid epichlorohydrin should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to epichlorohydrin may occur and control methods which may be effective in each case:

Operation	Controls
Use as intermediate in manufacture of DGEBA resins, epoxy novolac resins, phenoxy resins, and wet-strength resins for paper	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of glycerol and glycidol derivatives for use as as plasticizer, stabilizer solvent, intermediate, dyestuff surfactants, pharmaceuticals, and intermediates for further synthesis	Process enclosure; local exhaust ventilation; personal protective equipment

Operation	Controls
Use as stabilizer in manufacture of chlorinated rubber and chlorinated insecticides	Process enclosure; local exhaust ventilation; personal protective equipment
Use in coating fibers and textile surface coatings	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If epichlorohydrin gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If epichlorohydrin gets on the skin, immediately flush the contaminated skin using soap or mild detergent and water. If epichlorohydrin soaks through the clothing, remove the clothing immediately and flush the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of epichlorohydrin, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When epichlorohydrin has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If epichlorohydrin is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Epichlorohydrin should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of epichlorohydrin vapors are permitted.

• Waste disposal method:

Epichlorohydrin may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Epichlorohydrin," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Epichlorohydrin," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Dow Chemical Company: *Material Safety Data Sheet – Epichlorohydrin*, Midland, Michigan, 1971.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Epichlorohydrin.* HEW Publication No. (NIOSH) 76-206, GPO No. 017-033-00197-9, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Van Duuren, B. L., et al.: "Carcinogenicity of Halo-Ethers. II. Structure-Activity Relationships of Analogs of Bis (Chloromethyl) Ether," *Journal of National Cancer Institute*, 48:1431-1439, 1972.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 11, 1976, and Volume 18, 1978.

RESPIRATORY PROTECTION FOR EPICHLOROHYDRIN

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
50 ppm or less	Any supplied-air respirator.**
	Any self-contained breathing apparatus.**
250 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 250 ppm*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and acid gases.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of epichlorohydrin; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 250 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for EPN

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(4\text{-}NO_2C_6H_4O)(C_2H_5O)C_6H_5PS$ $C_{14}H_{14}NO_4PS$
- Synonyms: O-ethyl O-p-nitrophenyl thionobenzenephosphonate; O-ethyl O-p-nitrophenyl benzenephosphonothioate
- Appearance: Yellow solid or brown liquid

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for EPN is 0.5 milligram of EPN per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

EPN can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: After inhalation of EPN, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of vision, tearing, runny nose, headache, and watering of the mouth. After swallowing EPN, loss of appetite, nausea, vomiting, abdominal cramps and diarrhea may appear within two hours. After skin absorption, sweating and twitching in the area of absorption may occur, usually within 15 minutes to four hours. With severe intoxication by all routes, in addition to all the above symptoms, weakness, generalized twitching, and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, slow heartbeat, convulsions and coma may occur.

2. *Long-term Exposure:* Repeated exposure to EPN may make a person more susceptible to the effects of this and related chemicals. Repeated exposure to concentrations which are too small to produce symptoms after a single exposure may result in the onset of symptoms.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to EPN.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to EPN at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system, and attention to the cholinesterase levels in the blood should be stressed. The skin should be examined for evidence of chronic disorders.

—Cholinesterase determination: EPN causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the serum and erythrocytes should be determined by using medically acceptable biochemical tests prior to any new period of exposure.

2. *Periodic Medical Examination:* The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determination which should be performed quarterly or at any

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

556

September 1978

time overexposure is suspected or signs and symptoms of toxicity occur.

• **Summary of toxicology**

EPN is an anticholinesterase agent; absorption may occur from inhalation of the dust or mist, from skin absorption of solutions, or from ingestion. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nervous system, skeletal and smooth muscle, and secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms may occur promptly or may be delayed for up to 12 hours. After inhalation, respiratory and ocular effects are the first to appear, , often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects, such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption, localized sweating and muscular fasciculations in the immediate area occur, usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures and is increased by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels, and cardiac irregularities including complete heart block may occur; these effects may sometimes be reversed by establishing adequate pulmonary ventilation. Complete symptomatic recovery usually occurs within 1 week; increased susceptibility to the effects of anticholinesterase agents persists for weeks after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects. In animals, EPN has produced a demyelination syndrome.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 323.3
2. Boiling point (760 mm Hg): Data not available
3. Specific gravity (water = 1): 1.27
4. Vapor density (air = 1 at boiling point of EPN): Not applicable
5. Melting point: 36 C (97 F)
6. Vapor pressure at 20 C (68 F): 0.0003 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of sulfur and nitrogen, phosphoric acid mist, and carbon monoxide) may be released when EPN decomposes.
4. Special precautions: Liquid EPN will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of EPN.
2. Eye Irritation Level: EPN is not known to be an eye irritant.
3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of EPN, it is treated as a material with poor warning properties. The Pennsylvania *Hygienic Information Guide* for EPN states that the "lack of odor and warning signs, as well as the delayed onset of symptoms, make EPN a dangerous material to work with."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of EPN using a filter with subsequent recovery with iso-octane and gas chromatrographic analysis. A detailed analytical method for EPN may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22161, under the title "NIOSH Analytical Methods for Set T" (order number PB 262 404).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental

concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with EPN or liquids containing EPN.

• If employees' clothing has had any possibility of being contaminated with EPN or liquids containing EPN, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with EPN should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of EPN from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the EPN, the person performing the operation should be informed of EPN's hazardous properties.

• Where there is any possibility of exposure of an employee's body to EPN or liquids containing EPN, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with EPN should be removed immediately and not reworn until the EPN is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of EPN or liquids containing EPN contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to EPN or liquids containing EPN, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with EPN should be immediately washed or showered with soap or mild detergent and water to remove any EPN.

• Workers subject to skin contact with EPN or liquids containing EPN should wash with soap or mild detergent and water any areas of the body which may have contacted EPN at the end of each work day.

• Eating and smoking should not be permitted in areas where EPN or liquids containing EPN are handled, processed, or stored.

• Employees who handle EPN or liquids containing EPN should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to EPN may occur and control methods which may be effective in each case:

Operation	Controls
Formulation for use as an insecticide and acaricide	Process enclosure; dust collection; personal protective equipment; general dilution ventilation
Application as an insecticide and acaricide on agricultural crops, vegetables, fruit trees, and ornamentals	Material substitution; personal protective equipment
Manufacture of EPN	Process enclosure; general dilution ventilation; personal protective equipment; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If EPN or liquids or mists containing EPN get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If EPN or liquids or mists containing EPN get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If EPN or liquids or mists containing EPN penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**
If a person breathes in large amounts of EPN, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When EPN or liquids containing EPN have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If EPN is spilled, the following steps should be taken:
1. Ventilate area of spill.
2. Cover with soda ash, mix and spray with water. Place in a container of water and allow to stand for two days, then neutralize with 6 molar HCl.
• Waste disposal method:
EPN may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "EPN (O-Ethyl-O-p-Nitrophenyl Thionobenzene PhosphoDocumentation of the Threshold Limit Values for Substances in Workroom Air (3rd ed., 2nd printing), Cincinnati, 1974.
• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.
• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.
• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons. Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.
• *Hygienic Information Guide No. 68 - EPN*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1970.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Koelle, G. B. (ed.): "Cholinesterases and Anticholinesterase Agents," Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.
• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR EPN

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate or Vapor Concentration	
5 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
50 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 50 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of EPN; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 50 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Ethanolamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $HOCH_2CH_2NH_2$
- Synonyms: Ethylolamine; monoethanolamine; beta-aminoethyl alcohol; 2-aminoethanol; 2-hydroxyethylamine
- Appearance and odor: Colorless liquid with a mild ammonia-like odor. It can be a solid below 10.3 C (51 F).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethanolamine is 3 parts of ethanolamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 6 milligrams of ethanolamine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethanolamine can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Ethanolamine may cause nose, eye, and skin irritation.

2. Long-term Exposure: Prolonged or repeated skin contact with liquid ethanolamine may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethanolamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethanolamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethanolamine exposure.

—Skin disease: Ethanolamine may cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Ethanolamine causes liver damage in animals and this justifies consideration before exposing persons with impaired liver function.

—Kidney disease: Ethanolamine causes kidney damage in animals and this justifies special consideration before exposing those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethanolamine might cause exacerbation of symptoms.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethanolamine vapor is a skin, eye, and respiratory irritant, and has significant narcotic properties. In animals exposed repeatedly to 66 to 100 ppm, some animals died during 24 to 30 days of exposure, and all animals were lethargic. Dogs and cats exposed to 2.47 mg/l (990 ppm) for 4 days survived but four of six guinea pigs died from exposure to 0.58 mg/l (233 ppm) for 1 hour; pathologic changes were chiefly those of pulmonary irritation, with some non-specific changes in the liver and kidneys. No mortality or pathology resulted from 90 days of continuous exposure of dogs to 26 ppm, of rats to 12 ppm, or of guinea pigs to 15 ppm. The liquid produced moderate irritation of the skin of rabbits and

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

561

September 1978

severe irritation in the eyes of rabbits. When applied to human skin for 1-½ hours, marked redness of the skin occurred. No systemic effects from industrial exposure have been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 61.1
2. Boiling point (760 mm Hg): 170 C (338 F)
3. Specific gravity (water = 1): 1.0
4. Vapor density (air = 1 at boiling point of ethanolamine): 2.1
5. Melting point: 10.3 C (51 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Less than 1

- **Reactivity**

1. Conditions contributing to instability: Heat.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids may cause spattering.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving ethanolamine.
4. Special precautions: Liquid ethanolamine will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 85 C (185 F) (closed cup)
2. Autoignition temperature: 780 C (1436 F)
3. Flammable limits in air, % by volume: Lower: 5.5 (calculated); Upper: 17 (estimated)
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

- **Warning properties**

1. Odor Threshold: Ethanolamine has a mild ammonia-like odor, which the AIHA *Hygienic Guide* reports is noticeable at 2 to 3 ppm.
2. Eye Irritation Level: The *Hygienic Guide* states that ethanolamine is an eye irritant, but do not specify whether both liquid and vapor have this effect. Grant reports that "a drop of ethanolamine applied to rabbit eyes causes injury similar to that caused by ammonia, but slightly less severe." The available literature does not specifically report that the vapor of ethanolamine produces eye irritation. By analogy with ammonia, ethanolamine is treated as an eye irritant for the purposes of this guideline.
3. Other Information: The *Hygienic Guide* reports that ethanolamine is a respiratory tract irritant. The concentrations producing this irritation are not given.
4. Evaluation of Warning Properties: Since ethanolamine has an odor threshold which is at or below the permissible exposure limit, it is treated as a substance with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- Method

An analytical method for ethanolamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid or solid ethanolamine.
- If employees' clothing may have become contaminated with solid ethanolamine, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with liquid or solid ethanolamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethanolamine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethanolamine, the person performing the operation should be informed of ethanolamine's hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid or solid ethanolamine should be removed promptly and not reworn until the ethanolamine is removed from the clothing.
• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid or solid ethanolamine contacting the eyes.
• Where there is any possibility that employees' eyes may be exposed to liquid or solid ethanolamine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid or solid ethanolamine should be promptly washed or showered to remove any ethanolamine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethanolamine may occur and control methods which may be effective in each case:

Operation	Controls
Use in production of monoalkanolamides for nonionic detergents, emulsifiers, and soaps; fuel oil additives; water-in-oil emulsifiers; pharmaceuticals; agricultural chemicals; cosmetics; emulsion paints; polishers, and cleansers	Process enclosure; local exhaust ventilation
Use during synthesis of acetethanolamine in manufacture of inks, paper, glues, textiles, and polishes; syntheses of phenylethanolamine for acetate rayon dyes, dyestuffs; synthesis of tolyethanolamine in emulsifiers and dyestuffs	Process enclosure; local exhaust ventilation
Use during synthesis of 2-mercaptothiazole in rubber vulcanization acceleration	Process enclosure; local exhaust ventilation; personal protective equipment
Use in recovery and removal of acid gases from natural, fuel, and process gas in synthesis of ammonia; use in dry ice manufacture	Process enclsoure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If ethanolamine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If ethanolamine gets on the skin, promptly flush the contaminated skin with water. If ethanolamine soaks through the clothing, remove the clothing promptly and flush the skin with water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of ethanolamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When ethanolamine has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If ethanolamine is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.
2. Ventilate area of spill or leak.

3. If in liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

4. If in solid form, allow to melt and follow (3) above.

• Waste disposal methods:

Ethanolamine may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethanolamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethanolamine," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Weeks, M. H., et al.: "The Effects of Continuous Exposure of Animals to Ethanolamine Vapor," *Journal of Industrial Hygiene Association*, 21:374-381, 1960.

RESPIRATORY PROTECTION FOR ETHANOLAMINE

Condition	Minimum Respiratory Protection* Required Above 3 ppm
Vapor Concentration	
30 ppm or less	A chemical cartridge respirator which provides protection against ethanolamine.**
	Any supplied-air respirator.**
	Any self-contained breathing apparatus.**
150 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) which provides protection against ethanolamine.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
	A gas mask with a chin-style or a front- or back-mounted canister which provides protection against ethanolamine.
1000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against ethanolamine.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for 2-Ethoxyethanol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_2H_5OCH_2CH_2OH$
- Synonyms: Ethyleneglycol monoethyl ether; Cellosolve (R) solvent
- Appearance and odor: Colorless liquid with a sweetish odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 2-ethoxyethanol is 200 parts of 2-ethoxyethanol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 740 milligrams of 2-ethoxyethanol per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for 2-ethoxyethanol from 100 ppm to 50 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

2-Ethoxyethanol can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

In animal experiments 2-ethoxyethanol has caused liver, kidney, and lung damage and anemia due to the destruction of red blood cells. It has also caused irritation of the eyes.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 2-ethoxyethanol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 2-ethoxyethanol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 2-ethoxyethanol exposure.

—Chronic respiratory disease: 2-Ethoxyethanol causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 2-ethoxyethanol might cause exacerbation of symptoms due to its irritant properties.

—Blood disease: 2-Ethoxyethanol causes in animals an increase in red cell fragility, decreased levels of red cells and hemoglobin, and an increase in immature white cells. Persons with anemia may be at increased risk from exposure.

—Kidney disease: 2-Ethoxyethanol causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: 2-Ethoxyethanol is absorbed through the skin. Persons with chronic skin disorders characterized by eczema or fissures may be at added risk of absorption of toxic amounts.

—Liver disease: Although 2-ethoxyethanol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

566

• **Summary of toxicology**

2-Ethoxyethanol vapor is toxic to the lungs, kidneys, and hematopoietic system in animals. In mice the LC50 for 7 hours was 1820 ppm; death was attributed to lung and kidney injury. In rabbits, repeated daily doses of 1 ml/kg given orally caused albuminuria and hematuria on the 7th day with death on the 8th day due to kidney injury. Dogs repeatedly exposed to 840 ppm for 12 weeks developed a slight decrease in red cells and hemoglobin and an increase in immature white cells. In female rats exposed to 125 ppm for 4 hours, there was an increase in erythrocyte fragility. Of two workers employed for 3 years in factories using 2-ethoxyethanol as a solvent, one had a slight yellowish discoloration of the sclera and the other had trace albuminuria and a slightly increased level of bilirubin in the blood. The liquid instilled in the eyes of animals caused immediate discomfort, some conjunctival irritation, and a slight transitory irritation of the cornea which was readily reversible. Repeated and prolonged contact of the liquid with the skin of rabbits caused only a mild irritation, but toxic amounts were readily absorbed through the skin.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 90.1
2. Boiling point (760 mm Hg): 135 C (275 F)
3. Specific gravity (water = 1): 0.93
4. Vapor density (air = 1 at boiling point of 2-ethoxyethanol): 3.0
5. Melting point: −70 C (−94 F) (pour point)
6. Vapor pressure at 20 C (68 F): 4 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Less than 1

• **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause containers to burst.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving 2-ethoxyethanol.
4. Special precautions: 2-Ethoxyethanol will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 49 C (120 F) (closed cup)
2. Autoignition temperature: 235 C (455 F)
3. Flammable limits in air, % by volume: Lower: 1.8; Upper: 14
4. Extinguishant: "Alcohol" foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that 2-ethoxyethanol has "a slight odor at low concentrations and a disagreeable odor at high concentrations." Grant states that this substance "is a practically odorless liquid."
2. Eye Irritation Level: Grant states that "exposure of rabbits to high vapor concentrations causes symptoms of ocular and respiratory irritation, but even at concentrations which are probably lethal, causes no significant ocular injury."
3. Other Information: The *Hygienic Guide* states that "high vapor concentrations can cause irritation of the nose and throat." No quantitative information is available, however, concerning the thresholds of irritation.
4. Evaluation of Warning Properties: Since eye, nose and throat irritation occur only at high levels, and since Grant points out that this substance is almost odorless, 2-ethoxyethanol is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for 2-ethoxyethanol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 2-ethoxyethanol.

• Clothing wet with 2-ethoxyethanol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 2-ethoxyethanol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 2-ethoxyethanol, the person performing the operation should be informed of 2-ethoxyethanol's hazardous properties.

• Non-impervious clothing which becomes contaminated with 2-ethoxyethanol should be removed promptly and not reworn until the 2-ethoxyethanol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid 2-ethoxyethanol may contact the eyes.

SANITATION

• Skin that becomes contaminated with 2-ethoxyethanol should be promptly washed or showered to remove any 2-ethoxyethanol.

• Employees who handle liquid 2-ethoxyethanol should wash their hands thoroughly before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 2-ethoxyethanol may occur and control methods which may be effective in each case:

Operation	Controls
Use as solvent in manufacture of lacquers, lacquer thinners, nitrocellulose lacquers, alkyd resins, printing ink solvents, varnish removers, cleaning compounds, soaps, cosmetics, pesticides, pharmaceuticals, adhesives, and detergents; during use in textile dyeing and printing and manufacture of leather finishes	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as anti-icing additive in manufacture of brake fluids, aviation fuels, and automotive anti-stall additives	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid 2-ethoxyethanol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid 2-ethoxyethanol gets on the skin, promptly flush the contaminated skin with water. If liquid 2-ethoxyethanol soaks through the clothing, promptly flush the skin with water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 2-ethoxyethanol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 2-ethoxyethanol has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 2-ethoxyethanol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. 2-Ethoxyethanol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers

designed to preclude the formation of explosive concentrations of 2-ethoxyethanol vapors are permitted.

• Waste disposal methods:

2-Ethoxyethanol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "2-Ethoxyethanol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethylene Glycol Monomethyl Ether," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Carpenter, C. P., et al.: "The Toxicity of Butyl Cellosolve Solvent," *A.M.A. Archives of Industrial Health*, 14:114-131, 1956.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

RESPIRATORY PROTECTION FOR 2-ETHOXYETHANOL

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
2000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
6000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure mode or continuous-flow mode.
Greater than 6000 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of 2-ethoxyethanol; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 6000 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for 2-Ethoxyethylacetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_2H_5OCH_2CH_2OCOCH_3$
- Synonyms: Cellosolve acetate; glycol monoethyl ether acetate; ethylene glycol monoethyl ether acetate
- Appearance and odor: Colorless liquid with a mild, non-residual odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 2-ethoxyethylacetate is 100 parts of 2-ethoxyethylacetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 540 milligrams of 2-ethoxyethylacetate per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for 2-ethoxyethylacetate from 100 ppm to 50 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

2-Ethoxyethylacetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

High air concentrations of 2-ethoxyethylacetate may cause irritation of the eyes and nose. The material is not very toxic when swallowed, but if a large enough dose is swallowed, death may result. It is not very toxic when inhaled in amounts likely to be encountered under ordinary conditions, but inhaling large amounts might cause vomiting, kidney damage, paralysis, and death. The material may be absorbed through the skin and, if a large amount of it is absorbed in this way, death may result.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 2-ethoxyethylacetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 2-ethoxyethylacetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 2-ethoxyethylacetate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 2-ethoxyethylacetate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: 2-Ethoxyethylacetate is absorbed through the skin. It also is a defatting agent and may cause dryness and cracking. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although 2-ethoxyethylacetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Liver disease: Although 2-ethoxyethylacetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

High concentrations of 2-ethoxyethylacetate vapor are

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

irritating to the eyes and mucous membranes. Guinea pigs and rabbits survived exposure to saturated vapor-air mixtures (4000 ppm) for 1 hour, but two such exposures for 4 to 6 hours caused delayed death to cats.

There was narcosis before death in these animals, and damage to the kidneys was found at autopsy. This agent is absorbed through the skin. Lethal doses have been administered through the skin to rabbits. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 132
  2. Boiling point (760 mm Hg): 156 C (313 F)
  3. Specific gravity (water = 1): 0.98
  4. Vapor density (air = 1 at boiling point of 2-ethoxyethylacetate): 4.6
  5. Melting point: −62 C (−80 F)
  6. Vapor pressure at 20 C (68 F): 2 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 23
  8. Evaporation rate (butyl acetate = 1): 0.2
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving 2-ethoxyethylacetate.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 47 C (117 F) (closed cup)
  2. Autoignition temperature: 380 C (716 F)
  3. Flammable limits in air, % by volume: Lower: 1.7
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: According to the *Handbook of Organic Industrial Solvents*, the odor of 2-ethoxyethylacetate is detectable at the threshold limit.
  2. Eye Irritation Level: According to the *Documentation of TLV's*, dogs exposed to "120 seven-hour inhalations of 600 ppm" experienced eye and nose irritation. No quantitative information is available, however, concerning the threshold of eye irritation. Patty reports that "high concentrations of vapor . . . are irritating to the eyes and nose."
  3. Evaluation of Warning Properties: Since the odor of 2-ethoxyethylacetate can be detected at the TLV, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of 2-ethoxyethylacetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 2-ethoxyethylacetate may be used. An analytical method for 2-ethoxyethylacetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 2-ethoxyethylacetate.
- Clothing wet with liquid 2-ethoxyethylacetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 2-ethoxyethylacetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 2-ethoxyethylacetate, the person performing the operation should be informed of 2-ethoxyethylacetate's hazardous properties.

• Non-impervious clothing which becomes wet with 2-ethoxyethylacetate should be removed promptly and not reworn until the 2-ethoxyethylacetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid 2-ethoxyethylacetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid 2-ethoxyethylacetate should be promptly washed or showered to remove any 2-ethoxyethylacetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 2-ethoxyethylacetate may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent vehicle during hot and cold spray applications of lacquers and wood stains, including automobiles, airplanes, and metal and wood finishing	Local exhaust ventilation; personal protective equipment
Use in manufacture of varnishes, thinners, lacquers, wood stains, adhesives, varnish removers, fabric coatings, paper coatings, and textile sizing	General dilution ventilation; personal protective equipment
Liberation during manufacture of cellulose acetate films, including transparent wrapping material, safety film, packaging film, and photographic film	General dilution ventilation
Liberation during coating process of fabrics, leather, and paper for water-proofing, sizing, and laminating	General dilution ventilation
Use during dipping application of lacquers and enamels of small articles having rounded or cylindrical shapes, wire flash bulbs, etc.	General dilution ventilation; personal protective equipment
Use during brushing or other hand applications of lacquers, adhesives, enamels, household cement, specialized lacquers, etc.	General dilution ventilation; personal protective equipment
Use during solvent recovery during equipment maintenance, pouring solvent, and refilling containers	General dilution ventilation; personal protective equipment
Use as a solvent for many oils and gums	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 2-ethoxyethylacetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 2-ethoxyethylacetate gets on the skin, promptly flush the contaminated skin with water. If 2-ethoxyethylacetate soaks through the clothing, remove the clothing promptly and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of 2-ethoxyethylacetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 2-ethoxyethylacetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 2-ethoxyethylacetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. 2-Ethoxyethylacetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

2-Ethoxyethylacetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "2-Ethoxyethylacetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethylene Glycol Monoethyl Ether Acetate," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR 2-ETHOXYETHYLACETATE (CELLOSOLVE ACETATE)

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOC_2H_5$
- Synonyms: Acetic ester; acetic ether; ethyl ethanoate
- Appearance and odor: Colorless liquid with a pleasant, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl acetate is 400 parts of ethyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1400 milligrams of ethyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to ethyl acetate may cause irritation of the eyes, nose, and throat. Severe overexposure may cause weakness, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl acetate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Ethyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although ethyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although ethyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethyl acetate vapor is irritating to the eyes and respiratory passages of man at concentrations above 400 ppm. In animals it has a narcotic effect at concentrations of over 5000 ppm. Due to its irritating properties, employees will not voluntarily remain in such high concentrations. Repeated exposures of rabbits to 4450 ppm for 1 hour daily for 40 days resulted in anemia with leukocytosis, and damage to liver and kidneys. Animals exposed to lethal concentrations died with pulmonary edema

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

and hemorrhage. This substance is a defatting agent, and prolonged exposure may cause irritation of the skin. Painful conjunctival irritation may occur from splashes in the eye. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 88
  2. Boiling point (760 mm Hg): 77 C (171 F)
  3. Specific gravity (water = 1): 0.9
  4. Vapor density (air = 1 at boiling point of ethyl acetate): 3.0
  5. Melting point: −83 C (−117 F)
  6. Vapor pressure at 20 C (68 F): 76 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 8.7
  8. Evaporation rate (butyl acetate = 1): 6
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, or strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ethyl acetate.
  4. Special precautions: Ethyl acetate will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −4.4 C (24 F) (closed cup)
  2. Autoignition temperature: 427 C (800 F)
  3. Flammable limits in air, % by volume: Lower: 2.2; Upper: 11
  4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: May and Summer report odor thresholds for ethyl acetate of 0.0056 ppm and 50 ppm, respectively.
  2. Eye Irritation Level: Grant states that "a concentration of 400 ppm in air causes a sensation of irritation in human eyes." Animals exposed to much higher concentrations developed no corneal damage, only conjunctival irritation.
  3. Evaluation of Warning Properties: Through its odor and irritant effects, ethyl acetate can be detected below or at the permissible exposure limit. For the purposes of this guideline, ethyl acetate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethyl acetate may be used. An analytical method for ethyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl acetate.
- Clothing wet with liquid ethyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethyl acetate, the person performing the operation should be informed of ethyl acetate's hazardous properties.
- Any clothing which becomes wet with liquid ethyl acetate should be removed immediately and not reworn until the ethyl acetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid ethyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid ethyl acetate should be promptly washed or showered to remove any ethyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during use of shellacs, lacquers, dopes, varnishes, and stains	Local exhaust ventilation; general dilution ventilation
Liberation during manufacture of smokeless powder; during manufacture of artificial leather; during preparation of photographic films	Process enclosure; general dilution ventilation
Liberation and use as a solvent during application of coatings containing nitrocellulose, cellulose acetate, shellac, synthetic rubber, vinyl resins, and inks	Process enclosure; general dilution ventilation
Use as a cleaning agent in textile industry	Process enclosure; general dilution ventilation
Liberation during manufacture of photographic film	Process enclosure; general dilution ventilation
Liberation during manufacture of linoleum and plastic wood; during manufacture of dyes, drug intermediates, ethyl acetoacetate, etc.; during use of duplicator fluid	Process enclosure; general dilution ventilation.
Liberation during use of varnish removers	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ethyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ethyl acetate gets on the skin, promptly flush the contaminated skin with water. If ethyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Ethyl acetate should not be allowed

to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Ethyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethyl Acetate," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Gafafer, W. M. (ed.): "Occupational Diseases: A Guide to Their Recognition," U.S. Public Health Service Publication No. 1097, 1964.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-51, Ethyl Acetate*, Washington, D.C., 1972.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Ethyl Acetate*, New York, 1968.

• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters: Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 21:28-65, 1960.

RESPIRATORY PROTECTION FOR ETHYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 400 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
10,000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethyl Acrylate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2=CHCOOC_2H_5$
- Synonyms: Ethyl propenoate
- Appearance and odor: Colorless liquid with a sharp, acrid odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl acrylate is 25 parts of ethyl acrylate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 100 milligrams of ethyl acrylate per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for ethyl acrylate from 25 ppm to 5 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl acrylate can affect the body if it is inhaled, comes in contact with the eyes or skin., or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to ethyl acrylate may cause irritation of the eyes, nose, throat, and lungs. Death may be caused by lung damage from breathing high air levels or from swallowing it.

2. Long-term Exposure: Prolonged contact with the skin or eyes may result in severe damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl acrylate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl acrylate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl acrylate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl acrylate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Ethyl acrylate is absorbed through the skin. It also is a defatting agent and may cause dryness or cracking. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although ethyl acrylate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although ethyl acrylate is not known as a kidney toxin in humans, the importance of this organ in the excretion of certain chemicals and their metabolites should be considered before exposing persons with impaired kidney function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The vapor of ethyl acrylate is irritating to the conjunctiva and upper respiratory tract. In moderate concentrations there are characteristic lacrimatory effects in man. Animals exposed to high concentrations show marked

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

irritation of the eyes and of the respiratory tract, leading to pulmonary edema. The lowest concentration of vapor producing no significant effect in rodents is 75 ppm. A concentration of 2000 ppm vapor killed rats in 4 hours, with death attributable to severe pulmonary irritation, although 1000 ppm for 4 hours allowed survival. Prolonged contact with the skin in animals causes moderate damage, and skin sensitization may occur. Fatal doses are absorbed through the skin of animals exposed for 24 hours. While there are no reports of injury to man from long-term exposure to concentrations ordinarily encountered in the work situation, common practice suggests that most workmen do not tolerate exposure to 25 ppm for more than a few minutes.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 100
2. Boiling point (760 mm Hg): 99 C (211 F)
3. Specific gravity (water = 1): 0.92
4. Vapor density (air = 1 at boiling point of ethyl acrylate): 3.45
5. Melting point: −75 C (−103 F)
6. Vapor pressure at 20 C (68 F): 29.5 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 1.5
8. Evaporation rate (butyl acetate = 1): 3.3

- **Reactivity**

1. Conditions contributing to instability: Heat and/or lack of appropriate inhibitor concentration can cause ethyl acrylate to polymerize violently and burst container.
2. Incompatibilities: Contact with oxidizing materials, including peroxides and other initiators of polymerization, strong alkalies, and atmospheric moisture may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ethyl acrylate.
4. Special precautions: Inhibitors do not function in absence of air, so inert gas blankets should not be used.

- **Flammability**

1. Flash point: 9 C (48 F) (closed cup)
2. Autoignition temperature: 383 C (721 F)
3. Flammable limits in air, % by volume: Lower: 1.8
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that "the odor of ethyl acrylate vapor is readily detectable at 1 ppm and was described as fairly strong and moderately irritating at 4 ppm." The Manufacturing Chemists Association reports that an odor of ethyl acrylate can be detected by most persons at 8 ppm.
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "a concentration of 272 ppm ethyl acrylate vapor caused irritation of the conjunctiva of rabbit eyes, but 75 ppm did not elicit any observable reaction." According to the MCA, however, irritation of the eyes occurs at about 75 ppm.
3. Other Information: The MCA states that irritation of the mucous membranes occurs at 75 ppm.

The AIHA *Hygienic Guide* states that the TLV (25 ppm) "is considered to be too high to prevent irritating effects in humans."

4. Evaluation of Warning Properties: Through its odor ethyl acrylate can be detected below the permissible exposure limit, and through its irritant effects it can be detected at or just several times above the TLV. Therefore, the substance is considered to have good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethyl acrylate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethyl acrylate may be used. An analytical method for ethyl acrylate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which

includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl acrylate.
- Clothing wet with liquid ethyl acrylate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethyl acrylate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethyl acrylate, the person performing the operation should be informed of ethyl acrylate's hazardous properties.
- Where exposure of an employee's body to liquid ethyl acrylate may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes wet with liquid ethyl acrylate or non-impervious clothing which becomes contaminated with liquid ethyl acrylate should be removed immediately and not reworn until the ethyl acrylate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid ethyl acrylate may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid ethyl acrylate should be promptly washed or showered with soap or mild detergent and water to remove any ethyl acrylate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl acrylate may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of acrylic resins for use in paint formulations, industrial coatings, and latexes; use in manufacture of plastics such as ethylene ethyl acrylate	Local exhaust ventilation; personal protective equipment
Use in manufacture of polyacrylate elastomers and acrylic rubber	Local exhaust ventilation; personal protective equipment
Use in forming of denture materials	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If ethyl acrylate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If ethyl acrylate gets on the skin, immediately flush the contaminated skin with water. If ethyl acrylate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of ethyl acrylate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When ethyl acrylate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If ethyl acrylate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Ethyl acrylate should not be allowed

to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Ethyl acrylate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill in an area where the odor will not be objectionable.

2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl Acrylate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethyl Acrylate," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-79, Methyl Acrylate and Ethyl Acryla Washington, D.C., 1960.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Ethyl Acrylate*, New York, 1971.

RESPIRATORY PROTECTION FOR ETHYL ACRYLATE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of ethyl acrylate; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 2000 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Ethyl Benzene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_2H_5C_6H_5$
- Synonyms: Phenylethane; ethylbenzol
- Appearance and odor: Colorless liquid with an aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl benzene is 100 parts of ethyl benzene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 435 milligrams of ethyl benzene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl benzene can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Ethyl benzene causes irritation of the eyes, nose, throat, and skin. With exposure to high concentrations, irritating effects are more pronounced, and a person may begin to feel weak, dizzy, drowsy, and become unconscious.

2. Long-term Exposure: Prolonged or repeated ethyl benzene exposure of the skin may casue skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl benzene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl benzene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl benzene exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl benzene might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Kidney disease: Although ethyl benzene is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although ethyl benzene is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Skin disease: Ethyl benzene is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethyl benzene is primarily an irritant of skin and, to some degree, of eyes and upper respiratory tract. Systemic absorption causes depression of the central nervous system with narcosis at very high concentrations. Aspiration of small amounts causes extensive edema and hemorrhage of lung tissue. It is readily metabolized and excreted chiefly as mandelic acid in the urine.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 106
  2. Boiling point (760 mm Hg): 136 C (277 F)
  3. Specific gravity (water = 1): 0.865
  4. Vapor density (air = 1 at boiling point of ethyl benzene): 3.66
  5. Melting point: −95 C (−139 F)
  6. Vapor pressure at 20 C (68 F): 7.1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.015
  8. Evaporation rate (butyl acetate = 1): Less than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ethyl benzene.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 15 C (59 F) (closed cup)
  2. Autoignition temperature: 432 C (810 F)
  3. Flammable limits in air, % by volume: Lower: 1.0; Upper: 6.7
  4. Extinguishant: Dry chemical, foam, or carbon dioxide
- **Warning properties**
  1. Odor Threshold: According to the Department of Transportation's *CHRIS Hazardous Chemical Data*, ethyl benzene has an odor threshold of 140 ppm.
  2. Eye Irritation Level: According to the AIHA *Hygienic Guide*, "the vapor caused a noticeable eye irritation in humans at concentrations of 200 ppm."
  3. Evaluation of Warning Properties: Through its odor and irritant effects, ethyl benzene can be detected at a concentration less than twice the permissible exposure limit. Therefore, for the purposes of this guideline, ethyl benzene is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethyl benzene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethyl benzene may be used. An analytical method for ethyl benzene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977 available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl benzene.
- Clothing wet with liquid ethyl benzene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethyl benzene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethyl benzene, the person performing the operation should be informed of ethyl benzene's hazardous properties.
- Non-impervious clothing which becomes contaminated with liquid ethyl benzene should be removed promptly and not reworn until the ethyl benzene is removed from the clothing.
- Any clothing which becomes wet with liquid ethyl benzene should be removed immediately and not reworn until the ethyl benzene is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid ethyl benzene may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid ethyl benzene should be promptly washed or showered with soap or mild detergent and water to remove any ethyl benzene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl benzene may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during manufacture of styrene monomer	Local exhaust ventilation
Use during spray application of vinyl resin surface coating	Local exhaust ventilation; personal protective equipment
Liberation during manufacture of paints, varnishes, and other surface coatings	Local exhaust ventilation; general dilution ventilation
Use in manufacture and application of rubber adhesives	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use during electroplating of aluminum on copper or steel	Local exhaust ventilation for open-surface tanks
Liberation during oven baking and drying of surface coatings	Local exhaust ventilation for ovens
Liberation during application of surface coatings by dipping, flow coatings, and roller coating	Local exhaust ventilation
Liberation during use as an intermediate in dye manufacture	General dilution ventilation
Use as a heat-transfer medium; use as a dielectric	General dilution ventilation; personal protective equipment
Liberation during production of acetophenone by oxidation of ethyl benzene	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ethyl benzene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ethyl benzene gets on the skin, promptly flush the contaminated skin with water. If ethyl benzene soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethyl benzene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If ethyl benzene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethyl benzene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Combustion may be improved by mixing with a more flammable liquid. Ethyl benzene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Ethyl benzene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber. Combustion may be improved by mixing with a more flammable liquid.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl Benzene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethyl Benzene," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Department of Transportation: *CHRIS Hazardous Chemical Data*, CG-446-2, U.S. Government Printing Office, Washington, January 1974.

• Dutkiewicz, T., and Tyras, H.: "A Study of Skin Absorption of Ethylbenzene in Man," *British Journal of Industrial Medicine*, 24:330-332, 1967.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Ethyl Benzene*, New York, 1967.

• Wolf, M. A., et al.: "Toxicological Studies of Certain Aklylated Benzenes and Benzene," *AMA Archives of Industrial Health*, 14:4, pp. 387-399, 1956.

RESPIRATORY PROTECTION FOR ETHYL BENZENE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethyl Bromide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_2H_5Br
- Synonyms: Bromoethane
- Appearance and odor: Colorless to yellow liquid with an ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl bromide is 200 parts of ethyl bromide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 890 milligrams of ethyl bromide per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl bromide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to ethyl bromide may cause irritation of the lungs, eyes, and skin. It may cause dizziness, loss of balance, slurred speech, unconsciousness, and death. Overexposure to this agent may also cause damage to the liver, kidneys, and heart. After-effects from severe exposure may occur up to 30 hours after the exposure has ceased.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl bromide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl bromide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl bromide exposure.

—Skin disease: Ethyl bromide can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Ethyl bromide has produced liver damage in animals and man, which should be considered before exposing persons with impaired liver function.

—Kidney disease: Since ethyl bromide has produced kidney damage in animals and man, special consideration in those with impaired renal function is justified.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl bromide might cause exacerbation of symptoms due to its irritant properties.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrhythmias, the inhalation of ethyl bromide might cause exacerbation of disorders of the conduction mechanism due to its sensitizing effects on the myocardium.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethyl bromide vapor is a respiratory irritant, a narcotic, and a hepato- and renal toxin. Exposure of guinea pigs for 30 minutes to 2.4% by volume (24,000 ppm) was fatal within 3 days due to pulmonary congestion, centrolobular necrosis of the liver, and diffuse nephritis; exposure to 3200 ppm for 9 hours produced lung irritation and nephritis; death occurred after 1 to 5 days.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

590

September 1978

The former use of ethyl bromide as a human anesthetic produced respiratory irritation and caused some fatalities, either immediately, due to respiratory or cardiac arrest, or delayed, from effects on the liver, kidney, or heart. Relatively little experience with this substance in industry has been reported, but exposure of volunteers to 6500 ppm for 5 minutes produced vertigo, slight headache, and mild eye irritation. Irritation of the skin occurs from repeated contact with ethyl bromide liquid.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 109
2. Boiling point (760 mm Hg): 38.8 C (100 F)
3. Specific gravity (water = 1): 1.45
4. Vapor density (air = 1 at boiling point of ethyl bromide): 3.8
5. Melting point: −119 C (−182 F)
6. Vapor pressure at 20 C (68 F): 375 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.9
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, and magnesium may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ethyl bromide. Ethyl bromide readily decomposes into hydrogen bromide and bromine particularly in the presence of hot surfaces.
4. Special precautions: Liquid ethyl bromide will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Less than −20 C (less than −4F) (closed cup)
2. Autoignition temperature: 511 C (952 F)
3. Flammable limits in air, % by volume: Lower: 6.7; Upper: 11.3
4. Extinguishant: Foam, carbon dioxide, dry chemical

- **Warning properties**

Since the AIHA *Hygienic Guide* states that the odor of ethyl bromide is detectable only at concentrations well above the permissible exposure, it has been treated as a substance with poor warning properties. In addition, the *Hygienic Guide* reports a situation in which only mild eye irritation was produced in a human subject after a 5-minute exposure to 6500 ppm, a concentration many times greater than the permissible exposure. Information on the eye irritation threshold is not available.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethyl bromide vapors using an adsorption tube with subsequent desorption with isopropyl alcohol and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethyl bromide may be used. An analytical method for ethyl bromide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl bromide.

• Clothing contaminated with liquid ethyl bromide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethyl bromide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethyl bromide, the person performing the operation should be informed of ethyl bromide's hazardous properties.

• Any clothing which becomes wet with liquid ethyl bromide should be removed immediately and not reworn until the ethyl bromide is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid ethyl bromide may contact the eyes.

SANITATION

• Skin that becomes wet with liquid ethyl bromide should be promptly washed or showered with soap or mild detergent and water to remove any ethyl bromide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl bromide may occur and control methods which may be effective in each case:

Operation	Controls
Use as an alkylating or ethylating agent in manufacture of pharmaceuticals, and to a lesser extent, chemicals, dyes, and perfumes	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent for fats, waxes, and resins	Process enclosure; if possible, local exhaust ventilation; personal protective equipment
Use as a local surface anesthetic for minor surgery and neuralgic pain	General dilution ventilation
Use as a liquid fumigant for grain and fruit	General dilution ventilation; personal protective equipment
Liberation during use as a refrigerant	Process enclosure; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ethyl bromide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ethyl bromide gets on the skin, promptly flush the contaminated skin using soap or mild detergent and water. If ethyl bromide soaks through the clothing, remove the clothing promptly and flush the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethyl bromide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethyl bromide has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethyl bromide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Ethyl bromide should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

Sewers designed to preclude the formation of explosive concentrations of ethyl bromide vapors are permitted.

• Waste disposal method:

Ethyl bromide may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl Bromide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethyl Bromide," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Dow Chemical Company: *Material Safety Data Sheet – Ethyl Bromide*, Midland, Michigan.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR ETHYL BROMIDE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
2000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
3500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a half facepiece operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 3500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethyl Butyl Ketone

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_2H_5COC_4H_9$
- Synonyms: Butyl ethyl ketone; 3-heptanone
- Appearance and odor: Colorless liquid with a mild, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl butyl ketone is 50 parts of ethyl butyl ketone per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 230 milligrams of ethyl butyl ketone per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl butyl ketone can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Ethyl butyl ketone may cause irritation of the eyes, nose, throat, and lungs. Exposure to high concentrations may cause headaches, dizziness, or unconsciousness.

2. Long-term Exposure: Prolonged or repeated skin contact may cause dryness and irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl butyl ketone.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl butyl ketone at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl butyl ketone exposure.

—Kidney disease: Although ethyl butyl ketone is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl butyl ketone might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Liver disease: Although ethyl butyl ketone is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Skin disease: Ethyl butyl ketone is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

There is some local irritation of the skin and respiratory tract by solvent effect of ethyl butyl ketone on lipids. Central nervous depression occurs on exposure to high concentration, producing narcosis. Effects may be more pronounced in unacclimated individuals. No chronic systemic effects have been reported.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 114
  2. Boiling point (760 mm Hg): 147 C (297 F)
  3. Specific gravity (water = 1): 0.82
  4. Vapor density (air = 1 at boiling point of ethyl butyl ketone): 3.93
  5. Melting point: −39 C (−38 F)
  6. Vapor pressure at 20 C (68 F): 4 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.43
  8. Evaporation rate (butyl acetate = 1): 0.45
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ethyl butyl ketone.
  4. Special precautions: Ethyl butyl ketone will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 46 C (115 F) (open cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Lower: 1.4; Upper: 8.8
  4. Extinguishant: Carbon dioxide, dry chemical, or foam
- **Warning properties**
  1. Odor Threshold: According to Patty, ethyl butyl ketone has a "typical ketone-type odor."
  2. Eye Irritation Level: According to the *Documentation of TLV's*, "when in contact with skin and eyes, it (ethyl butyl ketone) produces, at most, irritation of mild degree."
  3. Evaluation of Warning Properties: For the purposes of this guideline, ethyl butyl ketone is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethyl butyl ketone vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethyl butyl ketone may be used. An analytical method for ethyl butyl ketone is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl butyl ketone.
- Clothing wet with liquid ethyl butyl ketone should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethyl butyl ketone from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethyl butyl ketone, the person performing the operation should be informed of ethyl butyl ketone's hazardous properties.
- Non-impervious clothing which becomes contaminated with liquid ethyl butyl ketone should be removed promptly and not reworn until the ethyl butyl ketone is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid ethyl butyl ketone may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid ethyl butyl ketone should be promptly washed or showered to remove any ethyl butyl ketone.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl butyl ketone may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during application of lacquers, varnishes, epoxies, vinyl coatings, finishes, and adhesives	Local exhaust ventilation; personal protective equipment
Liberation during application of lacquer, varnishes, epoxies, vinyl coatings, finishes, and adhesives by dipping, roller coating, tumbling, knifing, or brushing	Local exhaust ventilation; general dilution ventilation
Liberation during oven or air drying of coatings and adhesives	General dilution ventilation
Use during manual application of cellulosic, acetate, and rubber adhesives in shoe manufacturing, book binding, and packaging	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during use of cellulosic household cements	General dilution ventilation
Liberation during application of mastics or other natural gum/ based adhesives for floor and wall tiles, other floor coverings, automobile silencer, and lining pads	General dilution ventilation; local exhaust ventilation
Liberation during cleaning and maintenance of ketone-processing equipment, such as distillation columns, reactors, mixers, and storage vessels	Personal protective equipment
Liberation during blending of coating and adhesive raw materials in open mixers	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ethyl butyl ketone gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ethyl butyl ketone gets on the skin, promptly flush the contaminated skin with water. If ethyl butyl ketone soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is evidence of skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethyl butyl ketone, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethyl butyl ketone has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethyl butyl ketone is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Ethyl butyl ketone should not be

allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of ethyl butyl ketone vapors are permitted.

• Waste disposal methods:

Ethyl butyl ketone may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl Butyl Ketone," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Carpenter, C. P., Smith, H. F., and Pozzani, V. C.: "The Assay of Acute Vapor Toxicity in, and the Grading, and Investigation of Results on Ninety-Six Chemical Compounds," *Journal of Industrial Hygiene and Toxicology*, 31:343-349, 1949.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List III," *Journal of Industrial Hygiene*, 31:1, pp. 60-62, 1949.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – 3-Heptanone*, New York, 1969.

RESPIRATORY PROTECTION FOR ETHYL BUTYL KETONE

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
500 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).**
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
3000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 3000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, a full-facepiece respirator should be worn.

Occupational Health Guideline for Ethyl Chloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_2H_5Cl
- Synonyms: Chloroethane; monochloroethane; hydrochloric ether; muriatic ether
- Appearance and odor: Colorless liquid or gas with a pungent, ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl chloride is 1000 parts of ethyl chloride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2600 milligrams of ethyl chloride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl chloride can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. In the liquid form, it may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Ethyl chloride may cause drowsiness, unconsciousness, irregular heart beat, and death. It may also cause irritation of the eyes and abdominal cramps. Spilled on the skin, it may cause frostbite.

2. Long-term Exposure: Ethyl chloride may cause liver and kidney damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl chloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl chloride at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl chloride exposure.

—Liver disease: Ethyl chloride is known as a liver toxin in animals and justifies consideration before exposing persons with impaired liver function.

—Kidney disease: Ethyl chloride is known as a kidney toxin in animals and justifies special consideration before exposing persons with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl chloride might cause exacerbation of symptoms due to its irritant properties.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrhythmias, the inhalation of ethyl chloride might cause exacerbation of disorders of the conduction mechanism due to its sensitizing effects on the myocardium.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethyl chloride vapor is a narcotic. Guinea pigs died from a 9-hour exposure to 40,000 ppm but survived 4-½ hour exposure; histopathological changes in the lungs, liver, and kidneys were observed in animals in the latter group. Inhalation of 40,000 ppm by human subjects caused dizziness, eye irritation, and abdominal cramps, while inhalation of 3.36% by volume (33,600 ppm) caused a toxic effect after 30 seconds, increasing within 5 minutes to noisy talkativeness followed by incoordina-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

tion. At 2.5% by volume (25,000 ppm) there was incoordination; 1.9% (19,000 ppm) caused weak analgesia after 12 minutes, and 1.3% (13,000 ppm) caused slight symptoms of inebriation. Sudden and unforeseen fatalities from ethyl chloride anesthesia have been reported, probably due to respiratory or cardiac arrest. Chronic effects from industrial exposure have not been reported, although skin absorption is said to occur. In liquid form this substance may cause frostbite.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 64.5
  2. Boiling point (760 mm Hg): 12.2 C (54 F)
  3. Specific gravity (water = 1): 0.92
  4. Vapor density (air = 1 at boiling point of ethyl chloride): 2.2
  5. Melting point: −139 C (−218 F)
  6. Vapor pressure at 20 C (68 F): 1064 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.57
  8. Evaporation rate (butyl acetate = 1): Much higher than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, and magnesium may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving ethyl chloride.
  4. Special precautions: Liquid ethyl chloride will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −50 C (−58 F) (closed cup)
  2. Autoignition temperature: 519 C (966 F)
  3. Flammable limits in air, % by volume: Lower: 3.8; Upper: 15.4
  4. Extinguishant: Stop flow of gas. Use carbon dioxide, dry chemical, or foam for small fires.
- **Warning properties**

Ethyl chloride has a somewhat pungent, ether-like odor, but no quantitative data are available on the odor threshold. For the purposes of this guideline, therefore, ethyl chloride has been treated as a material with poor warning properties.

Ethyl chloride is a mild eye irritant. Grant reports that at 4% the gas has been noted to cause slight irritation of the eyes of human beings.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for ethyl chloride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl chloride.
- Clothing wet with liquid ethyl chloride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethyl chloride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethyl chloride, the person performing the operation should be informed of ethyl chloride's hazardous properties.
- Any clothing which becomes wet with liquid ethyl chloride should be removed immediately and not reworn until the ethyl chloride has evaporated.
- Employees should be provided with and required to use splash-proof safety goggles where liquid ethyl chloride may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl chloride may occur and control methods which may be effective in each case:

Operation	Controls
Use in production of tetraethyl lead and ethyl cellulose	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as a local or general anesthetic; use as a refrigeration compound; use as a solvent for fats, oils, waxes, phosphorus, acetylene, and many resins	General dilution ventilation; personal protective equipment
Use in organic synthesis of perchloroethane, esters, and Grignard reagents	General dilution ventilation; process enclosure; personal protective equipment
Use in manufacture of dyes and drugs; use as a propellant in aerosols	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of perfumes	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid ethyl chloride gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid ethyl chloride gets on the skin, promptly wash the contaminated skin with water if the ethyl chloride has not already evaporated. If liquid ethyl chloride soaks through the clothing, remove the clothing immediately and flush the skin with water. Do not use hot water for skin flushing. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethyl chloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethyl chloride has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethyl chloride is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. If in the liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Ethyl chloride should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.
4. If in the gaseous form, stop flow of gas.

• Waste disposal methods:

Ethyl chloride may be disposed of:

1. If in the liquid form, by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. If in the gaseous form, by burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl Chloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethyl Chloride," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-50, Ethyl Chloride*, Washington, D.C., 1953.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR ETHYL CHLORIDE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
20,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a half facepiece operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 20,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethyl Ether

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_2H_5OC_2H_5$
- Synonyms: Diethyl ether; ethyl oxide; ether; diethyl oxide; sulfuric ether
- Appearance and odor: Colorless liquid with a characteristic, sweet ether odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl ether is 400 parts of ethyl ether per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1200 milligrams of ethyl ether per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl ether can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to ethyl ether may cause irritation of the eyes, nose, and throat. It may also cause dizziness, drowsiness, unconsciousness, and death.

2. Long-term Exposure: Prolonged overexposure may cause loss of appetite, dizziness, drowsiness, headache, exhaustion, excitation, and mental disturbances. It may also increase the severity of the effects of drinking alcoholic beverages. Repeated exposure may be habit forming.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl ether.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl ether at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl ether exposure.

—Skin disease: Ethyl ether can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although ethyl ether is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although ethyl ether is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl ether might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethyl ether has predominantly narcotic properties leading to anesthesia; it is also an eye and respiratory irritant. Continued inhalation of 2000 ppm in human subjects may produce dizziness. Higher concentrations produce vomiting, pallor, and irregular respiration. Temporary aftereffects are salivation, vomiting, respi-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

ratory tract irritation, headache, and either depression or excitation. Chronic exposure results in some persons in anorexia, exhaustion, headache, drowsiness, dizziness, excitation, and psychic disturbances. Albuminuria has been reported. Tolerance may be acquired through repeated exposures. Ethyl ether is a mild skin irritant; repeated exposure causes drying and cracking. The vapor is irritating to the eye, and the undiluted liquid causes painful inflammation of a transitory nature. Human subjects found 200 ppm irritating to the nose, but not to the eyes or throat. Permanent aftereffects are rare.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 74.1
  2. Boiling point (760 mm Hg): 35 C (95 F)
  3. Specific gravity (water = 1): 0.7
  4. Vapor density (air = 1 at boiling point of ethyl ether): 2.6
  5. Melting point: −123 C (−190 F)
  6. Vapor pressure at 20 C (68 F): 442 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 7.5
  8. Evaporation rate (butyl acetate = 1): 37.5
- **Reactivity**
  1. Conditions contributing to instability: Heat; sunlight
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ethyl ether.
  4. Special precautions: Ethyl ether will attack some forms of plastics, rubber, and coatings. Ethers, which have been in contact with air or exposed to light for a long time, may contain peroxides. Ethers which contain peroxides may explode when the caps or stoppers of their containers are removed. Ethyl ether, being a nonconductor, may accumulate static electric charges that may result in ignition of its vapors.
- **Flammability**
  1. Flash point: −45 C (−49 F) (closed cup)
  2. Autoignition temperature: 160 C (320 F)
  3. Flammable limits in air, % by volume: Lower: 1.9; Upper: 36.0
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold for ethyl ether of 0.33 ppm. Patty notes that the odor is pungent.
  2. Eye Irritation Level: Grant states that ethyl ether "causes a transitory smarting sensation if splashed in the eye or if a high vapor concentration contacts the eye, but momentary exposure generally does not cause injury. Prolonged exposure of the cornea to high concentration of ether vapor, such as employed in general anesthesia, does cause superficial epithelial injury, from which recovery is usually prompt." Patty also reports that in high concentrations ethyl ether causes eye irritation.
  3. Other Information: Patty reports that "Nelson et al. reported that human subjects found ethyl ether irritating to the nose, but not to the eyes or throat, at a vapor concentration of 200 ppm."
  4. Evaluation of Warning Properties: Through its odor and nasal irritation, ethyl ether can be detected below the permissible exposure limit. For the purposes of this guideline, therefore, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethyl ether vapors using an adsorption tube with subsequent desorption with ethyl acetate and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethyl ether may be used. An analytical method for ethyl ether is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which

includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl ether.
- Clothing wet with liquid ethyl ether should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethyl ether from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethyl ether, the person performing the operation should be informed of ethyl ether's hazardous properties.
- Any clothing which becomes wet with liquid ethyl ether should be removed immediately and not reworn until the ethyl ether is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid ethyl ether may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl ether may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in manufacture of smokeless powder	Local exhaust ventilation; general dilution ventilation
Use as a laboratory solvent and chemical extractant	General dilution ventilation; personal protective equipment
Use as a solvent cleaning agent in shoe and textile industries	General dilution ventilation; personal protective equipment
Use as an anesthetic	General dilution ventilation
Liberation from manufacture of alkali or sodium ethylxanthotes by heated processes; from manufacture of warm-process pharmaceuticals; from manufacture of chemicals from cold processes – Grignard reactions and acetic acid recovery	Process enclosure; general dilution ventilation; local exhaust ventilation
Use as a solvent in manufacture of textiles, cellulose acetate, plastics, and dyes	Process enclosure; local exhaust ventilation; general dilution ventilation
Liberation during manufacture of cold-process pharmaceuticals	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as an additive in motor fuels, perfumes, and denatured alcohol	Process enclosure; local exhaust ventilation; general dilution ventilation
Use in the priming of gasoline engines in cold climates	General dilution ventilation
Liberation during refueling of diesel engines in cold climates	General dilution ventilation
Use as an anesthetic by animal handlers	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If ethyl ether gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If ethyl ether gets on the skin, promptly wash the contaminated skin with water if the ethyl ether has not already evaporated. If ethyl ether soaks through the clothing, remove the clothing promptly and flush the skin with water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of ethyl ether, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When ethyl ether has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethyl ether is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected, dissolved in alcohol of greater molecular weight than butyl alcohol, and atomized in a suitable combustion chamber. Ethyl ether should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Ethyl ether may be disposed of by dissolving in alcohol of greater molecular weight than butyl alcohol, and by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl Ether," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethyl Ether," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 44 - Ethyl Ether*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1973.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-29, Ethyl Ether*, Washington, D.C.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Ethyl Ether*, New York, 1973.

RESPIRATORY PROTECTION FOR ETHYL ETHER

Condition	Minimum Respiratory Protection* Required Above 400 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).
4000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
19,000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 19,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethyl Formate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $HCOOC_2H_6$
- Synonyms: Ethyl methanoate; formic acid ethyl ester
- Appearance and odor: Colorless liquid with a fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl formate is 100 parts of ethyl formate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 300 milligrams of ethyl formate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl formate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to ethyl formate may cause irritation of the eyes, nose, throat and skin. At high concentrations it may cause drowsiness and unconsciousness.

2. Long-term Exposure: Long-term overexposure to ethyl formate may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl formate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl formate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl formate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl formate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: This substance is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although ethyl formate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although ethyl formate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethyl formate is irritating to the eyes and nose at concentrations of 330 ppm. Narcosis occurs in animals, but only at exposure levels near the lethal concentration of 10,000 ppm. Dogs exposed to this very high concentration died of pulmonary edema. Rats survived at 4000 ppm. Application to the skin caused only slight irritation; when dropped into the eye, it caused moderate injury to the cornea. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEP. .TMENT OF LABOR
Occupational Safety and Health Administration

608

September 1978

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 74
2. Boiling point (760 mm Hg): 54.5 C (130 F)
3. Specific gravity (water = 1): 0.92
4. Vapor density (air = 1 at boiling point of ethyl formate): 2.6
5. Melting point: −79 C (−110 F)
6. Vapor pressure at 20 C (68 F): 194 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 13.6
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ethyl formate.
4. Special precautions: None

- **Flammability**

1. Flash point: −20 C (−4 F) (closed cup)
2. Autoignition temperature: 455 C (851 F)
3. Flammable limits in air, % by volume: Lower: 2.8; Upper: 16
4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide

- **Warning properties**

1. Odor Threshold: No information is available concerning the odor threshold of ethyl formate.
2. Eye Irritation Level: According to the *Documentation of TLV's*, "in man, a concentration of 330 ppm produced a slight irritation of the eyes and a rapidly increasing nasal irritation . . . . A threshold limit of 100 ppm is recommended to prevent eye and nasal irritation."
3. Evaluation of Warning Properties: Since eye and nasal irritation occur at a concentration which is approximately only three times the permissible exposure limit, ethyl formate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethyl formate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethyl formate may be used. An analytical method for ethyl formate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl formate.
- Any clothing which becomes wet with liquid ethyl formate should be removed immediately and not reworn until the ethyl formate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid ethyl formate may contact the eyes.

SANITATION

- Skin that becomes wet with liquid ethyl formate should be promptly washed or showered to remove any ethyl formate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl formate may occur and control methods which may be effective in each case:

Operation	Controls
Use during spray, brush, or dip applications of lacquers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent for cellulose acetate in artificial silk manufacture	General dilution ventilation; personal protective equipment
Use in shoe industry to dissolve celluloid heel coverings; use as a solvent in manufacture of artificial leather	General dilution ventilation; personal protective equipment
Use in manufacture of safety glass	General dilution ventilation
Use as a fumigant and larvacide for tobacco, cereals, and dried fruits	Personal protective equipment
Liberation during use as an intermediate in organic synthesis	General dilution ventilation
Liberation during formulation of synthetic flavors	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ethyl formate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ethyl formate gets on the skin, immediately flush the contaminated skin with water. If ethyl formate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethyl formate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethyl formate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethyl formate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Ethyl formate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Ethyl formate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Ethyl Formate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
- Smyth, H. F., et al.: "Range-Finding Toxicity Data, List V," *Archives of Industrial Hygiene and Occupational Medicine*, 10:61, July 1954.
- Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Ethyl Formate*, New York, 1968.

RESPIRATORY PROTECTION FOR ETHYL FORMATE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
8000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethyl Silicate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_2H_5O)_4Si$ or $(C_2H_5)_4SiO_4$
- Synonyms: Ethyl silicate, condensed; tetraethyl orthosilicate; tetraethyl silicate; ethyl orthosilicate tetraethoxysilane
- Appearance and odor: Colorless liquid with a mild, sweet, alcohol-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethyl silicate is 100 parts of ethyl silicate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 850 milligrams of ethyl silicate per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for ethyl silicate a Threshold Limit Value of 10 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethyl silicate can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to ethyl silicate may irritate the eyes and nose. In animals, exposure to ethyl silicate has caused severe breathing difficulties, liver damage, kidney damage, and anemia. Repeated applications of ethyl silicate to animal skin has caused the skin to become dry.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethyl silicate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethyl silicate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethyl silicate exposure.

—Chronic respiratory disease: Ethyl silicate causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethyl silicate might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Ethyl silicate causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Ethyl silicate causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Blood disease: Ethyl silicate causes anemia in animals. Persons with pre-existing blood disorders may be more susceptible to the effects of this agent.

—Skin disease: Ethyl silicate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethyl silicate vapor irritates the eyes and nose and in animals causes lung, liver, and kidney damage. Exposure of guinea pigs to 2530 ppm for 4 hours was lethal to more than half of the animals; usually death was delayed and a result of pulmonary edema; effects were

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

612

irritation of eyes and nose, lacrimation, tremor, dyspnea, and narcosis; some surviving animals later developed a delayed profound anemia. Exposure of rats to 1000 ppm for up to three 7-hour periods was fatal; autopsy findings were marked tubular degeneration and necrosis of the kidneys, mild liver damage, and slight pulmonary edema and hemorrhage. In rats exposed to 125 ppm for 15 to 20 7-hour periods, slight to moderate kidney damage was observed, but no pathologic changes were detected in the liver or lungs. In humans, the eyes and nose are affected by brief exposures as follows: 3000 ppm, extremely irritating and intolerable; 1200 ppm, lacrimation and stinging; 700 ppm, mild stinging; 250 ppm, slight tingling; Instillation of the liquid into the rabbit eye caused immediate marked irritation which was reversible. Repeated or prolonged skin contact with the liquid may cause dermatitis due to its solvent effect.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 208.3
2. Boiling point (760 mm Hg): 169 C (336 F)
3. Specific gravity (water = 1): 0.94
4. Vapor density (air = 1 at boiling point of ethyl silicate): 7.2
5. Melting point: Less than −85 C (−121 F)
6. Vapor pressure at 20 C (68 F): 2 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts slowly to form ethyl alcohol and silica gel
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: High temperatures may cause containers to explode.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with water causes formation of volatile and flammable ethyl alcohol.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ethyl silicate.
4. Special precautions: Ethyl silicate will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 37.2 C (99 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Lower: 1.3; Upper: 23
4. Extinguishant: Carbon dioxide, dry chemical, foam

- **Warning properties**

1. Odor Threshold: According to Grant, ethyl silicate can be detected by odor at 85 ppm.
2. Irritation levels: Grant states that "observations were made of the effect of various concentrations on the human experimenters: 3000 ppm was found to be extremely irritating to the eyes and nose; 1200 ppm stings eyes and nose and produces tears; 700 ppm mildly stings eyes and nose; 250 ppm makes the eyes and nose tingle slightly . . . ."
3. Evaluation of Warning Properties: Since the threshold of odor is below the permissible exposure limit, and since the thresholds of eye and nasal irritation are within three times the permissible exposure limit, ethyl silicate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube packed with XAD-2 resin, followed by desorption with carbon disulfide and gas chromatographic analysis. Detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethyl silicate may be used. An analytical method for ethyl silicate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethyl silicate.

- Clothing wet with liquid ethyl silicate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethyl silicate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethyl silicate, the person performing the operation should be informed of ethyl silicate's hazardous properties.
- Any clothing which becomes wet with liquid ethyl silicate should be removed immediately and not reworn until the ethyl silicate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid ethyl silicate contacting the eyes.

SANITATION

- Skin that becomes wet with liquid ethyl silicate should be promptly washed or showered with soap or mild detergent and water to remove any ethyl silicate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethyl silicate may occur and control methods which may be effective in each case:

Operation	Controls
Use as a bonding agent for investment castings, ceramic shells, crucibles, and types of refractory shapes	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a protective coating for paints, lacquers, and films	General dilution ventilation; personal protective equipment
Use in manufacture of protective and preservative coatings for protection from corrosion, chemicals, heat, scratches, and fire	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in impregnation of porous materials to increase strength, hardness, stiffness, and abrasion	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a waterproofing and weatherproofing agent in porous rock	General dilution ventilation; personal protective equipment
Use as a chemical intermediate; use as a gelling agent in organic liquids; use as a coating agent inside electric lamp bulbs, and in the synthesis of fused quartz	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in textile industry in aqueous emulsions, deluster and fireproofing, and to increase strength; use as a component of lubricants as mold release agent	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid ethyl silicate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid ethyl silicate gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid ethyl silicate soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of ethyl silicate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When liquid ethyl silicate has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethyl silicate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. Ethyl silicate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of ethyl silicate vapors are permitted.

• Waste disposal methods:

Ethyl silicate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl Silicate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethyl Silicate," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Pozzani, U. C., and Carpenter, C. P.: "Response of Rodents to Repeated Inhalation of Vapors of Tetraethyl Orthosilicate," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 4:465-468, 1951.

• Rowe, V. K., et al.: "Toxicological Studies on Certain Commercial Silicones and Hydrolyzable Silane Intermediates," *Journal of Industrial Hygiene and Toxicology*, 30:332-352, 1948.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth H. F., Jr., and Seaton, J.: "Acute Response of Guinea Pigs and Rats to Inhalation of the Vapors of TetraOrthosilicate (Ethyl Silicate)," *Journal of Industrial Hygiene and Toxicology*, 23:288-296, 1940.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

RESPIRATORY PROTECTION FOR ETHYL SILICATE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethylamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_2H_5NH_2$
- Synonyms: Ethylamine, anhydrous; aminoethane; monoethylamine
- Appearance and odor: Colorless liquid or gas with a strong, ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethylamine is 10 parts of ethylamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 18 milligrams of ethylamine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethylamine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Ethylamine causes severe irritation of the eyes and skin. It may also cause irritation of the nose, throat, and lungs.

2. Long-term Exposure: Repeated or prolonged exposure to ethylamine may also cause irritation of the lungs and kidney damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethylamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethylamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ethylamine exposure.

—Chronic respiratory disease: Ethylamine causes lung irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ethylamine might cause exacerbation of symptoms due to its irritant properties.

—Eye disease: Ethylamine is an eye irritant and has caused corneal edema in workers. Persons with pre-existing eye disorders may be more susceptible to the effects of this agent.

—Skin disease: Ethylamine is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although ethylamine is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although ethylamine is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Cardiovascular disease: Ethylamine causes myocardial degeneration in animals. Persons with cardiac disease may be at increased risk.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ethylamine vapor is a primary irritant to mucous membranes, eyes, and skin. Exposure to 8000 ppm for 4 hours was lethal to rats. Rabbits survived exposures to

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

50 ppm daily for 6 weeks but showed pulmonary irritation and some myocardial degeneration; corneal damage was observed after 2 weeks of exposure. In the rabbit eye, 1 drop of a 70% solution of ethylamine caused immediate, severe irritation. Eye irritation and corneal edema in humans have been reported from industrial exposure. A 70% solution of the base dropped on the skin of guinea pigs caused prompt skin burns leading to necrosis; when held in contact with guinea pig skin for 24 hours there was severe skin irritation with extensive necrosis and deep scarring.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 45.1
  2. Boiling point (760 mm Hg): 16.7 C (62 F)
  3. Specific gravity (water = 1): 0.7
  4. Vapor density (air = 1 at boiling point of ethylamine): 1.6
  5. Melting point: −81 C (−114 F)
  6. Vapor pressure at 20 C (68 F): 1.18 atmospheres
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): Greater than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact of liquid ethylamine with strong acids will cause violent spattering. Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving ethylamine.
  4. Special precautions: Liquid ethylamine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: Less than −18 C (less than 0 F) (closed cup)
  2. Autoignition temperature: 385 C (725 F)
  3. Flammable limits in air, % by volume: Lower: 3.5; Upper: 14.0
  4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: No quantitative data are available concerning the odor threshold of ethylamine.
  2. Eye Irritation Level: Patty and the *Documentation of TLV's* report that in repeated exposure experiments, "100 ppm ethylamine produced irritation of the cornea" in rabbits. In addition, corneal injury, which did not appear for 2 weeks, was produced in rabbits exposed repeatedly to 50 ppm ethylamine. This concentration (50 ppm) is not specifically stated to be the lowest concentration producing eye injury.
  3. Other Information: Patty and the *Documentation of TLV's* report that rabbits exposed to both 100 ppm and 50 ppm ethylamine for 7 hours per day, 5 days per week for 6 weeks, experienced lung irritation.
  4. Evaluation of Warning Properties: Since no information is available concerning the odor threshold of ethylamine, and since the irritant effects produced by this substance are not stated to occur immediately upon exposure, ethylamine is treated as a substance with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethylamine in an adsorption tube containing silica gel, followed by desorption with sulfuric acid and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethylamine may be used. An analytical method for ethylamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid ethylamine, where skin contact may occur.

- Clothing wet with liquid ethylamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethylamine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethylamine, the person performing the operation should be informed of ethylamine's hazardous properties.
- Where exposure of an employee's body to liquid ethylamine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with ethylamine should be removed immediately and not reworn until the ethylamine is removed from the clothing.
- Any clothing which becomes wet with liquid ethylamine should be removed immediately and not reworn until the ethylamine is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid ethylamine or solutions containing ethylamine contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid ethylamine or solutions containing 0.75% or more of ethylamine by weight, an eyewash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with ethylamine should be immediately washed or showered to remove any ethylamine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethylamine may occur and control methods which may be effective in each case:

Operation	Controls
Use in synthesis of agricultural chemicals for herbicides; use as a dyestuff intermediate; use as a solvent for dyes, resins, and oils; use as a catalyst for polyurethane foams; use in pharmaceuticals, emulsifying agents, and as a vulcanization accelerator for sulfur-cured rubbers	General dilution ventilation; local exhaust ventilation
Use as a stabilizer for rubber latex; use as a catalyst for curing epoxy resins	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in synthesis of dimethylolethyltriazone, a wash and wear agent for cotton fabrics; synthesis of 1,3-diethylthiourea, a corrosion inhibitor	General dilution ventilation; local exhaust ventilation
Use in synthesis of chemical intermediates and solvents; use as plasticizers and in refining of lubricating oils	General dilution ventilation; local exhaust ventilation
Use as a selective solvent in refining of petroleum and vegetable oils	General dilution ventilation
Use in synthesis of alkyl isocyanates for intermediates in manufacture of organic products such as pharmaceuticals and resins	General dilution ventilation; local exhaust ventilation
Use in synthesis of rhodamine dyes	General dilution ventilation; local exhaust ventilation
Use as a deflocculating agent in ceramics industry; use in manufacture of detergents	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If ethylamine or solutions containing ethylamine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If ethylamine gets on the skin, immediately flush the contaminated skin with water. If ethylamine soaks through the clothing, remove the clothing immediately

and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethylamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethylamine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethylamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Allow ethylamine to evaporate. Ethylamine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethylamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Brieger, H., and Hodes, W. A.: "Toxic Effects of Exposure to Vapors of Aliphatic Amines," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 3:287-291, 1951.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List IV," *American Industrial Hygiene Association Journal*, 23:12, pp. 95-107, 1962.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Ethylamine*, New York, 1958.

• U.S. Coast Guard: "Ethylamine," *Characteristics of Liquid Chemicals Proposed for Bulk Water Movement.*

RESPIRATORY PROTECTION FOR ETHYLAMINE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Gas Concentration	
500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
4000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against ethylamine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ethylene Chlorohydrin

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_2ClCH_2OH
- Synonyms: 2-Chloroethanol; 2-chloroethyl alcohol
- Appearance and odor: Colorless liquid with an ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethylene chlorohydrin is 5 parts of ethylene chlorohydrin per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 16 milligrams of ethylene chlorohydrin per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for ethylene chlorohydrin a Threshold Limit Value of 1 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethylene chlorohydrin can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It may be absorbed through the skin without causing irritation.

- **Effects of overexposure**

Exposure to ethylene chlorohydrin vapor may cause irritation of the eyes, nose, throat, and lungs, nausea, vomiting, dizziness, poor coordination, numbness, visual disturbance, liver or kidney damage (lower concentrations may cause serious effects without causing irritation). Breathing in higher concentrations produces headache, thirst, delirium, low blood pressure, collapse, and unconsciousness. The urine may contain blood. Death may occur from lung or brain damage. Absorption through the skin can cause the above symptoms without skin irritation. Prolonged overexposure to ethylene chlorohydrin may cause the skin to become yellow and a change in frequency of urination or the amount of urine.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethylene chlorohydrin.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethylene chlorohydrin at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, liver, kidneys, and central nervous system should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Ethylene chlorohydrin may cause liver damage. A profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

—Urinalysis: Since kidney damage has been observed from exposure, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on a semi-annual basis for the first two years and annually thereafter.

- **Summary of toxicology**

Ethylene chlorohydrin vapor is highly toxic to the liver, kidneys, brain, and other organs. It is rapidly absorbed through the skin. A concentration of 250 ppm was fatal to rats in 4 hours; 125 ppm was not. A human fatality was reported following exposure to an estimat-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Center for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

622

ed 300 ppm for 2-¼ hours. In another fatal case, autopsy showed severe damage to the liver and brain. Several employees survived exposures averaging 18 ppm but showed signs of circulatory shock with incoordination and repeated vomiting. There is little margin of safety between early reversible symptoms and fatal intoxication. Absorption by any route, including the skin, may lead to severe illness or death. Contact with vapor causes irritation of mucous membranes, nausea, vomiting, vertigo, incoordination, numbness, and visual disturbance. With higher concentrations, headache, severe thirst, delirium, low blood pressure, collapse, shock, and coma may result. Urine may contain albumin, casts, and red blood cells. Death results from pulmonary edema or from congestion and edema of the brain. The cause of the toxic effect is probably the result of oxidation of the alcohol to chloracetic acid. The liquid instilled in rabbit eyes caused moderately severe injury, but in human eyes corneal burns have been observed to recover within 48 hours. Skin contact is particularly hazardous, because there are no signs of immediate irritation to warn the victim of exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 80.5
  2. Boiling point (760 mm Hg): 130 C (266 F)
  3. Specific gravity (water = 1): 1.2
  4. Vapor density (air = 1 at boiling point of ethylene chlorohydrin): 2.8
  5. Melting point: −62.6 C (−81 F)
  6. Vapor pressure at 20 C (68 F): 5 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong caustics may cause formation of flammable ethylene gas.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving ethylene chlorohydrin.
  4. Special precautions: Ethylene chlorohydrin will attack some forms of plastics, rubber, and coatings. Special attention to the care and maintenance of personal protective equipment should be maintained.
- **Flammability**
  1. Flash point: 60 C (140 F) (closed cup)
  2. Autoignition temperature: 425 C (797 F)
  3. Flammable limits in air, % by volume: Lower: 4.9; Upper: 15.9
  4. Extinguishant: Dry chemical, carbon dioxide, alcohol foam
- **Warning properties**

According to the AIHA *Hygienic Guide*, the warning properties of ethylene chlorohydrin are "poor and inadequate to prevent injury."

Ethylene chlorohydrin is an eye irritant, according to the *Hygienic Guide*.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of ethylene chlorohydrin vapors using an adsorption tube with subsequent desorption with isopropyl alcohol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethylene chlorohydrin may be used. An analytical method for ethylene chlorohydrin is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with ethylene chlorohydrin.

• Clothing contaminated with liquid ethylene chlorohydrin should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethylene chlorohydrin from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethylene chlorohydrin, the person performing the operation should be informed of ethylene chlorohydrin's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid ethylene chlorohydrin, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with liquid ethylene chlorohydrin should be removed immediately and not reworn until the ethylene chlorohydrin is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid ethylene chlorohydrin contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid ethylene chlorohydrin, an eyewash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid ethylene chlorohydrin should be immediately washed or showered to remove any ethylene chlorohydrin.

• Eating and smoking should not be permitted in areas where liquid ethylene chlorohydrin is handled, processed, or stored.

• Employees who handle liquid ethylene chlorohydrin should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethylene chlorohydrin may occur and control methods which may be effective in each case:

Operation	Controls
Use as a fumigant in treatment of seed potatoes	General dilution ventilation; personal protective equipment
Use in dyeing operations during color printing of textiles	Process enclosure; local exhaust ventilation
Use during cleaning, degreasing, and dewaxing operations	Material substitution; process enclosure; local exhaust ventilation
Use in organic synthesis and synthesis of dyes, pharmaceuticals, and resin processing; use in extraction of pine lignin and oil of rose	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ethylene chlorohydrin gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ethylene chlorohydrin gets on the skin, immediately flush the contaminated skin with water. If ethylene chlorohydrin soaks through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of ethylene chlorohydrin, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethylene chlorohydrin has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethylene chlorohydrin is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Ethylene chlorohydrin should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Ethylene chlorohydrin may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethylene Chlorohydrin," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethylene Chlorohydrin," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Ethylene Chlorohydrin*, New York, 1971.

RESPIRATORY PROTECTION FOR ETHYLENE CHLOROHYDRIN

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
10 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of ethylene chlorohydrin; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 10 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Ethylene Dibromide*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_2BrCH_2Br
- Synonyms: 1,2-Dibromoethane; ethylene bromide
- Appearance and odor: Colorless liquid or solid with a mild, sweet odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethylene dibromide is 20 parts of ethylene dibromide per million parts of air (ppm) averaged over an eight-hour work shift, with a ceiling level of 30 ppm and a maximum peak of 50 ppm for 5 minutes during an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be changed to a ceiling level of 1 mg/m³ (0.13 ppm) averaged over a 15-minute period. The NIOSH Criteria Document for Ethylene Dibromide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethylene dibromide can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Ethylene dibromide may cause vomiting, irritation of the eyes, nose, throat, and skin. It may also cause drowsiness. In addition, overexposure may cause damage to the lungs, liver, and kidneys.

2. Long-term Exposure: Prolonged or repeated exposure to ethylene dibromide may cause injury to the lungs, liver, or kidneys. Adverse effects, including abnormalities in offspring, mutations, and stomach cancer, have been found in animals following exposure to ethylene dibromide. The relevance to humans of these findings has not yet been established.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethylene dibromide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethylene dibromide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the nervous and respiratory systems, heart, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Ethylene dibromide causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Ethylene dibromide is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Liver function tests: Ethylene dibromide may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Kidney disease: Although ethylene dibromide is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Cardiovascular disease: Persons with cardiac disease may be at increased risk. An electrocardiogram should be performed on workers over 40 years of age and where indicated.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

627

—Skin disease: Ethylene dibromide is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Medical warning: Workers should be informed that adverse effects have been found in animals following exposure to ethylene dibromide. These effects have included abnormalities in offspring, mutations, and stomach cancer.

2. *Periodic Medical Examination:* The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Ethylene dibromide vapor is a narcotic, a severe mucous membrane irritant, and a hepatic toxin. Rats did not survive when exposed to the vapor for longer than 6 minutes at 3000 ppm; minimum lethal concentration for an 8-hour exposure was 200 ppm; these exposures caused hepatic necrosis, pulmonary edema, and cloudy swelling of renal tubules. Four species of animals tolerated daily inhalation of 25 ppm for 6 months without adverse effects but did not tolerate similar exposure to 50 ppm. Accidental use as a human anesthetic resulted in severe irritation of the conjunctiva and respiratory tract, followed by protracted vomiting and death. Excessive exposure may be expected to cause irritation of the eyes and respiratory tract. The liquid is highly irritating to human skin, causing marked erythema and vesiculation. Serious skin injury has been reported from contact with clothing and especially shoes wet with ethylene dibromide. In a bioassay conducted by the National Cancer Institute (NCI), ethylene dibromide was found carcinogenic to rats and mice when fed by gavage. The compound induced squamous cell carcinomas of the fore stomach in rats of both sexes, hepatocellular carcinomas in female rats, and hemangiosarcomas in male rats. In mice of both sexes, the compound induced squamous cell carcinomas of the fore stomach and alveolar/bronchiolar adenomas. In NIOSH-sponsored research, laboratory rats exposed to 20 ppm ethylene dibromide by inhalation and also receiving a diet containing 0.05% disulfiram experienced exceedingly high mortality levels as well as a high incidence of tumors (including hemangiosarcomas of the liver, spleen, and kidney).

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 187.9
2. Boiling point (760 mm Hg): 131 C (268 F)
3. Specific gravity (water = 1): 2.18
4. Vapor density (air = 1 at boiling point of ethylene dibromide): 6.5
5. Melting point: 10 C (50 F)
6. Vapor pressure at 20 C (68 F): 11 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.4
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat; ethylene dibromide slowly decomposes in the presence of light.
2. Incompatibilities: Ethylene dibromide reacts with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, magnesium, liquid ammonia, and strong oxidizers.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen bromide, bromine, and carbon monoxide) may be released when ethylene dibromide decomposes.
4. Special precautions: Liquid ethylene dibromide will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

According to the International Labour Office (ILO), the odor of ethylene dibromide is detectable at 10 ppm, well above the NIOSH recommended permissible exposure concentration. Therefore, it is treated as a material with poor warning properties.

Ethylene dibromide is an eye irritant, according to Stecher.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of ethylene dibromide. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Peak Level Evaluation**

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of ethylene dibromide. Each measurement should consist of a 5-minute sample or a series of consecutive samples totalling 5 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift

and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of ethylene dibromide vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ethylene dibromide may be used. An analytical method for ethylene dibromide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid ethylene dibromide.

• Non-impervious clothing which becomes contaminated with liquid ethylene dibromide should be removed immediately and not reworn until the ethylene dibromide is removed from the clothing.

• Clothing contaminated with liquid ethylene dibromide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethylene dibromide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ethylene dibromide, the person performing the operation should be informed of ethylene dibromide's hazardous properties.

• Where exposure of an employee's body to liquid ethylene dibromide may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Employees should be provided with and required to use splash-proof safety goggles where liquid ethylene dibromide may contact the eyes.

SANITATION

• Skin that becomes contaminated with ethylene dibromide should be immediately washed or showered with soap or mild detergent and water to remove any ethylene dibromide.

• Employees who handle ethylene dibromide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

• Eating and smoking should not be permitted in areas where ethylene dibromide is handled, processed, or stored.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ethylene dibromide may occur and control methods which may be effective in each case:

Operation	Controls
Use in fumigation operations in preplanting and on grains, fruits, and vegetables	Local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use in production of antiknock fluids and fuels	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in production of water-proofing agents fire extinguishing agents, and gauge fluids during manufacture of measuring intruments	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis in production of dyes, pharmaceuticals, and ethylene oxide; use as a specialty solvent for resins, gums, and waxes	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

Operation	Controls
Liberation during production and handling of fumigant preparations	Local exhaust ventilation; general mechanical ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ethylene dibromide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ethylene dibromide gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If ethylene dibromide soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethylene dibromide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethylene dibromide has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethylene dibromide is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If in the liquid form, collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.
3. If in the solid form, collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquids containing ethylene dibromide should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal methods:

Ethylene dibromide may be disposed of:

1. If in the liquid form, by absorbing it in vermiculite, dry sand, earth, or a similar material and disposing in a secured sanitary landfill.
2. If in the solid form, by disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1,2-Dibromomethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethylene Dibromide," *Hygienic Guide Series*, Detroit, Michigan, 1958.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 69 – Ethylene Dibromide*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1968.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Ethylene Dibromide*, HEW Publication No. (NIOSH) 77-221, U.S. Government Printing Office, Washington, D.C., 1977.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Current Intelligence Bulletin 23 - Ethylene Dibromide and Disulfiram Toxic Interaction*, HEW Publication No. (NIOSH) 78-145, U.S. Government Printing Office, Washington, D.C., 11 April 1978.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Powers, M. B., et al.: "Carcinogenicity of Ethylene Dibromide (EDB) and 1,2-Dibromo-3-Chloropropane (DBCP) After Oral Administration in Rats and Mice," paper presented at 14th annual meeting of Society of Toxicology, Williamsburg, Virginia, March 9-13, 1975.

• Rowe, V. K., et al.: "Toxicity of Ethylene Dibromide

Determined in Experimental Animals," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 6:158-173, 1952.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck & Co., Inc., Rahway, New Jersey, 1968.

• U.S. Department of Health, Education, and Welfare: *Bioassay of 1,2-Dibromoethane for Possible Carcinogenicity*, HEW Publication No. (NIH) 78-1336, Public Health Service, National Institutes of Health, National Cancer Institute, Bethesda, pp. 63, 1978.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

• SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 15, 1977.

RESPIRATORY PROTECTION FOR ETHYLENE DIBROMIDE

Condition	Minimum Respiratory Protection* Required Above 20 ppm
Vapor Concentration	
400 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 400 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of ethylene dibromide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 400 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Ethylenediamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $NH_2CH_2CH_2NH_2$
- Synonyms: 1,2-Diaminoethane; ethylenediamine, anhydrous; 1,2-ethanediamine
- Appearance and odor: Colorless liquid or solid with an ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ethylenediamine is 10 parts of ethylenediamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 25 milligrams of ethylenediamine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ethylenediamine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Ethylenediamine vapors may cause irritation of the eyes, nose, and throat. If splashed on the skin, it may cause severe irritation, skin damage, and blistering. If splashed in the eyes, it may cause damage. It may cause tingling of the face.

2. Long-term Exposure: Repeated or prolonged overexposure to ethylenediamine may cause dermatitis. A person may become allergic to ethylenediamine (skin rash and asthma). Liver, kidney, and lung damage may occur from repeated exposure to this chemical.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ethylenediamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ethylenediamine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to ethylenediamine would be expected to be at increased risk from exposure. Examination of the respiratory system, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Ethylenediamine vapor is a sensitizer and primary irritant to the skin, mucous membranes, and respiratory tract. Exposure of rats to 4000 ppm for 8 hours was uniformly fatal as a result of kidney injury, although some lung injury also occurred; 2000 ppm was not lethal. Rats exposed daily for 30 days to 484 ppm did not survive; injury to lungs, liver, and kidneys was observed; at 132 ppm there was no mortality. In human subjects, inhalation of 400 ppm for 5 to 10 seconds caused intolerable nasal irritation; 200 ppm caused tingling of the face and slight nasal irritation; 100 ppm was not irritating. In the eye of a rabbit the liquid caused extreme irritation and corneal damage; partial corneal opacity was produced by a 5% solution. The undiluted liquid applied to the shaved skin of rabbits and left uncovered produced severe irritation and ne-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

633

September 1978

crosis. Cutaneous sensitization in man has been observed.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 60.1
  2. Boiling point (760 mm Hg): 117 C (242 F)
  3. Specific gravity (water = 1): 0.91
  4. Vapor density (air = 1 at boiling point of ethylenediamine): 2.1
  5. Melting point: 11 C (52 F)
  6. Vapor pressure at 20 C (68 F): 10 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 0.91
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact of liquid ethylenediamine with strong acids will cause violent spattering. Contact with strong oxidizers and chlorinated organic compounds may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving ethylenediamine.
  4. Special precautions: Liquid ethylenediamine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 34 C (93 F) (closed cup)
  2. Autoignition temperature: 379.4 C (715 F)
  3. Flammable limits in air, % by volume: Lower: 5.8; Upper: 11.1
  4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: The AIHA *Hygienic Guide* states that the ammonia-like odor of ethylenediamine is detectable at 10 ppm.
  2. Eye Irritation Level: Grant notes that "workmen exposed to ethylenediamine are said occasionally to see haloes around objects and to have some blurring of vision, presumably attributable to an effect on the corneal epithelium." Grant does not give any quantitative information, however.

The *Hygienic Guide* reports that ethylenediamine vapor causes eye irritation, but the exact concentrations producing the irritation are not given. They also state that "a chemical cartridge respirator with a cartridge designed for amine vapors may be used for protection against concentrations of ethylenediamine that do not cause eye irritation."

3. Other Information: The *Documentation of TLV's* states that "human subjects found 100 ppm for a few seconds to be inoffensive, but higher concentrations, 200 and 400 ppm, produced noticeable irritation of the nasal mucosa."

4. Evaluation of Warning Properties: Since the odor of ethylenediamine is noticeable at the permissible exposure, this material is treated as a substance with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for ethylenediamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solid or liquid ethylenediamine.
- If employees' clothing has had any possibility of being contaminated with solid ethylenediamine, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing which has had any possibility of being contaminated with solid or liquid ethylenediamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ethylenediamine from the clothing. If the

clothing is to be laundered or otherwise cleaned to remove the ethylenediamine, the person performing the operation should be informed of ethylenediamine's hazardous properties.

- Where there is any possibility of exposure of an employee's body to solid or liquid ethylenediamine, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes wet with liquid ethylenediamine or non-impervious clothing which becomes contaminated with ethylenediamine should be removed immediately and not reworn until the ethylenediamine is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid ethylenediamine or solutions containing ethylenediamine contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid or solid ethylenediamine or solutions containing more than 5% ethylenediamine by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with ethylenediamine should be immediately washed or showered to remove any ethylenediamine.
- Workers subject to skin contact with solid or liquid ethylenediamine should wash any areas of the body which may have contacted ethylenediamine at the end of each work day.
- Eating and smoking should not be permitted in areas where solid or liquid ethylenediamine are handled, processed, or stored.
- Employees who handle solid or liquid ethylenediamine should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some com non operations in which exposure to ethylenediamine may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of carbamate fungicides, pesticides, and weed killers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of chelating agents in dyes, soaps, and cleaning compounds, water treatment, in agriculture, in rubber processing, in pulp and paper processing, and in metal cleaning and electroplating	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of urea resins for use in textile and paper finishing; use in production of textile finishing compounds, resins, rubber products, insecticides, and medicinals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an activator for epoxy resin menders; in preparation of Spandex, adhesives, inks, surface coatings, cross-linking agents, plasticizers, resins curing compounds, and as a dye assist	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of surfactants, emulsifying agents, wetting agents, dispersants, corrosion inhibitors, detergents, and textile surface treatments	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis for preparation of dye intermediates, heterocyclic compounds, pharmaceuticals, corrosion inhibitors, adhesives, and salts	Local exhaust ventilation; general dilution ventilation; personal protective equipment

Miscellaneous uses in brightening agent for electroplating, anti-tarnish agent in detergents, lubricant stabilizer, soldering fluxes, processing chemicals for rubber, solvent for casein, albumin, shellac, and sulfur	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solid or liquid ethylenediamine or solutions containing ethylenediamine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid or liquid ethylenediamine gets on the skin, immediately flush the contaminated skin with water. If solid or liquid ethylenediamine penetrates through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of ethylenediamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When ethylenediamine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If ethylenediamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. If in the liquid form, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Ethylenediamine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.
4. If in the solid form, collect, allow to melt, and dispose of the liquid as above.

• Waste disposal method:

Ethylenediamine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethylenediamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethylenediamine," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Baer, R. L., et al.: "The Most Common Contact Allergens," *Archives of Dermatology*, 108:74-78, 1973.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Pozzani, U. C., and Carpenter, C. P.: "Response of Rats to Repeated Inhalation of Ethylenediamine Vapor," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 9:223-226, 1954.

• Smyth, H. F., Jr., et al.: "Range-Finding Toxicity Data: List IV," *A.M.A. Archives of Industrial Hygieneand Occupational Medicine*, 4:119-122, 1951.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List VI," *American Industrial Hygiene Association Journal*, 23:2, pp. 95-107, 1962.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Ethylenediamine*, New York, 1971.

RESPIRATORY PROTECTION FOR ETHYLENEDIAMINE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
500 ppm or less	A chemical cartridge respirator with a full facepiece and a cartridge(s) providing protection against ethylenediamine. A gas mask with a chin-style or a front- or back-mounted canister providing protection against ethylenediamine. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
12000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against ethylenediamine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of ethylenediamine; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 2000 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for n-Ethylmorpholine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_{13}ON$
- Synonyms: 4-Ethylmorpholine
- Appearance and odor: Colorless liquid with an ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for N-ethylmorpholine is 20 parts of N-ethylmorpholine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 94 milligrams of N-ethylmorpholine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

n-Ethylmorpholine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: n-Ethylmorpholine may cause irritation of the eyes, nose, and throat. Eye exposure may result in foggy vision and seeing halos around lights.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to N-ethylmorpholine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to n-ethylmorpholine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from n-ethylmorpholine exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of N-ethylmorpholine might cause exacerbation of symptoms due to its irritant properties.

—Eye disease: n-Ethylmorpholine is an eye irritant and has caused corneal edema in workers. Persons with pre-existing eye disorders may be more susceptible to the effects of this agent.

—Liver disease: Although N-ethylmorpholine is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although N-ethylmorpholine is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

n-Ethylmorpholine vapor causes visual disturbances and irritates mucous membranes. Some rats died after exposure to 2000 ppm for 4 hours. In an experimental study, humans exposed to 100 ppm for 2-½ minutes experienced irritation of eyes, nose, and throat, while 50 ppm produced lesser irritation. Workers exposed to low vapor concentrations for several hours reported temporarily fogged vision with rings around lights; corneal edema was observed; this effect is thought to occur

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

638

when air concentrations of substituted morpholines are 40 ppm or higher; the symptoms usually appear at the end of the work day and clear within 3 to 4 hours after cessation of exposure. The liquid when placed into the eye of a rabbit caused corneal haziness, sloughing, and irregularities of the surface, characteristic of severe desiccation. On the skin of a rabbit, the undiluted liquid produced no reaction, unlike unsubstituted morpholine, which is a severe skin irritant.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 115.2
  2. Boiling point (760 mm Hg): 138.6 C (281 F)
  3. Specific gravity (water = 1): 0.91
  4. Vapor density (air = 1 at boiling point of N-ethylmorpholine): 4.0
  5. Melting point: −63 C (−81 F)
  6. Vapor pressure at 20 C (68 F): 5 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 0.8
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact of liquid N-ethylmorpholine with strong acids will cause violent spattering. Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as ammonia, oxides of nitrogen, and carbon monoxide) may be released in a fire involving N-ethylmorpholine.
  4. Special precautions: Liquid N-ethylmorpholine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 32.2 C (90 F) (closed cup)
  2. Autoignition temperature: 185 C (365 F)
  3. Flammable limits in air, % by volume: Lower: 1.0; Upper: 9.8
  4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: According to the *Documentation of TLV's*, in a study with human volunteers, the ammonia odor of N-ethylmorpholine is noticeable at 25 ppm. The odor becomes stronger at higher concentrations, but olfactory fatigue occurs.
  2. Eye Irritation Level: Grant reports the occurrence of "transient edema of the corneal epithelium in workers exposed to 40 ppm or more in air during the work day."

  The *Documentation of TLV's* reports that eye irritation was noted in human volunteers exposed to 100 ppm N-ethylmorpholine for 2-½ minutes. "Slight if any irritation" occurred at 50 ppm.
  3. Other Information: The *Documentation of TLV's* reports that nose and throat irritation also occurred among human volunteers exposed to 100 ppm N-ethylmorpholine for 2-½ minutes. "Slight if any irritation" occurred at 50 ppm.
  4. Evaluation of Warning Properties: Since olfactory fatigue occurs during exposure to N-ethylmorpholine, odor is not considered to be a good warning property. In addition, since irritation does not definitely occur until a concentration several times greater than the permissible exposure limit, N-ethylmorpholine is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of N-ethylmorpholine in an adsorption tube containing silica gel, followed by desorption with sulfuric acid, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure N-ethylmorpholine may be used. An analytical method for N-ethylmorpholine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid N-ethylmorpholine.

• Clothing contaminated with N-ethylmorpholine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of N-ethylmorpholine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the N-ethylmorpholine, the person performing the operation should be informed of N-ethylmorpholine's hazardous properties.

• Where exposure of an employee's body to liquid N-ethylmorpholine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with N-ethylmorpholine should be removed promptly and not reworn until the N-ethylmorpholine is removed from the clothing.

• Any clothing which becomes wet with liquid N-ethylmorpholine should be removed immediately and not reworn until the N-ethylmorpholine is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid N-ethylmorpholine or solutions containing N-ethylmorpholine contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to N-ethylmorpholine or solutions containing more than 15% N-ethylmorpholine by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with N-ethylmorpholine should be promptly washed or showered to remove any N-ethylmorpholine.

• Employees who handle liquid N-ethylmorpholine should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to N-ethylmorpholine may occur and control methods which may be effective in each case:

Operation	Controls
Use as a catalyst for flexible, semi-flexible, and rigid polyurethane foam production	Local exhaust ventilation; personal protective equipment
Use in polymer technology as a promoter for resin surface curing, and as a stabilizer for fiber spinning solutions	Local exhaust ventilation; personal protective equipment
Use in manufacture of vat dyes; use in manufacture of pharmaceuticals in purification of Penicillin G	Local exhaust ventilation; personal protective equipment
Use in organic synthesis as a special solvent, pH regulator, and for preparation of chemical intermediates	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If N-ethylmorpholine or solutions containing N-ethylmorpholine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If N-ethylmorpholine gets on the skin, promptly flush the contaminated skin with water. If N-ethylmorpholine soaks through the clothing, remove the clothing immediately and flush the skin with water.

• **Breathing**

If a person breathes in large amounts of N-ethylmorpholine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When N-ethylmorpholine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Under-

stand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If N-ethylmorpholine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. n-Ethylmorpholine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

n-Ethylmorpholine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

ADDITIONAL INFORMATION

To find additional information on N-ethylmorpholine, look up N-ethylmorpholine in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "n-Ethylmorpholine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Dernehl, C. U.: "Health Hazards Associated with Polyurethane Foams," *Journal of Occupational Medicine*, 8:59-62, 1966.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Jefferson Chemical Company: *n-Ethylmorpholine* Houston, Texas, 1972.

• Mellerio, J., and Weale, R. A.: "Miscellanea: Hazy Vision in Amine Plant Operatives," *British Journal of Industrial Medicine*, 23:153-154, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data," *Journal of Industrial Hygiene and Toxicology*, 31:60, 1949.

RESPIRATORY PROTECTION FOR N-ETHYLMORPHOLINE

Condition	Minimum Respiratory Protection* Required Above 20 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ferbam

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $((CH_3)_2NCS_2)_3Fe$
- Synonyms: Ferric dimethyldithiocarbamate; tris(dimethyldithiocarbamato)iron
- Appearance and odor: Odorless black solid

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ferbam is 15 milligrams of ferbam per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for ferbam a Threshold Limit Value of 10 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ferbam can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It may also affect the body if it is swallowed.

- **Effects of overexposure**

Ferbam dust may cause irritation of the eyes and respiratory tract. Swallowing large amounts of ferbam or liquids containing ferbam may cause gastrointestinal disturbances. Ferbam may also cause a skin rash in people who are allergic to sulfur.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ferbam.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ferbam at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ferbam exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ferbam might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Ferbam can cause dermatitis. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ferbam dust irritates the eyes and respiratory tract. In guinea pigs given ferbam by stomach tube, the lethal range was 450 to 2000 mg/kg; the animals became stuporous and died in coma. Ten of 20 rats died from a diet containing 0.5% ferbam for 30 days; there was a slight and ill-defined tendency toward anemia; at autopsy there was no evidence of a regularly appearing tissue injury; minor abnormalities of the lung, liver, kidney and bone marrow were observed in a few animals. In humans, the dust is irritating to the eyes and respiratory tract; it causes dermatitis in individuals sensitized to sulfur. Large oral doses cause gastrointestinal disturbances. Because of chemical similarity to Antabuse, absorption of ferbam may potentiate action of ethyl alcohol.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 416.5
  2. Boiling point (760 mm Hg): Decomposes

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of ferbam): Not applicable
5. Melting point: 180 C (356 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.012
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Temperatures above 180 C (356 F) cause decomposition with formation of toxic gases.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of sulfur and nitrogen and carbon monoxide) may be released in a fire involving ferbam.
4. Special precautions: None.

• **Flammability**

1. Flash point: Not applicable
2. Minimum ignition temperatures: 280 C (536 F) (cloud); 150 C (302 F) (layer)
3. Minimum explosive dust concentration: 0.055 g/l
4. Extinguishant: Water, dry powder

• **Warning properties**

Grant states that ferbam "is a fungicide, the dust of which is irritating to the eye, nose, throat, and skin."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for ferbam had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with ferbam or liquids containing ferbam.

• If employees' clothing may have become contaminated with ferbam or liquids containing ferbam, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with ferbam should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ferbam from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ferbam, the person performing the operation should be informed of ferbam's hazardous properties.

• Non-impervious clothing which becomes contaminated with ferbam should be removed promptly and not reworn until the ferbam is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where ferbam or liquids containing ferbam may contact the eyes.

SANITATION

• Skin that becomes contaminated with ferbam should be promptly washed or showered with soap or mild detergent and water to remove any ferbam.

• Eating and smoking should not be permitted in areas where solid ferbam is handled, processed, or stored.

• Employees who handle ferbam or liquids containing ferbam should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ferbam may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of fungicides	Process enclosure; local exhaust ventilation; personal protective equipment
Application as a foliage fungicide for control of scab and rust diseases	Personal protective equipment
Manufacture of ferbam	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If ferbam or liquids containing ferbam get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If ferbam or liquids containing ferbam get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If ferbam or liquids containing ferbam penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of ferbam, move the exposed person to fresh air at once.

• **Swallowing**

When ferbam or liquids containing ferbam have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If ferbam is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquid containing ferbam should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Ferbam may be disposed of in a secured sanitary landfill.

ADDITIONAL INFORMATION

To find additional information on ferbam, look up ferbam in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• A.M.A. Council on Pharmacy and Chemistry: "Outlines of Information on Pesticides," *Journal of the AmericanMedical Association*, 157:237-241, 1955.

• American Conference of Governmental Industrial Hygienists: "Ferbam," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Signs, Symptoms and Treatment of Certain Acute Intoxications*, C. C. Thomas, Illinois, 1958.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hodge, H. C., et al.: "Acute and Short-Term Oral Toxicity Tests of Ferric Dimethyldithiocarbamate (Ferbam) and Zinc Dimethyldithiocarbamate (Ziram)," *Journal of the American Pharmaceutical Association*, 41:662-665, 1952.

• Plunkett, E. R.: *Handbook of Industrial Toxicology*, Chemical Publishing Company, New York, 1966.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR FERBAM

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Particulate Concentration	
75 mg/m³ or less**	Any dust respirator, except single-use.
150 mg/m³ or less**	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
7500 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 7500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Ferrovanadium Dust

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Ferrovanadium contains varying amounts of iron and vanadium and several other minor constituents (e.g., silicon, manganese, chromium, and nickel). Ferrovanadium has been produced with as little as 35% vanadium and as much as 85% vanadium.
- Synonyms: None
- Appearance: Dark, odorless solid particles.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ferrovanadium dust is 1 milligram of ferrovanadium dust (as vanadium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be changed to 1 mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week. The NIOSH Criteria Document for Vanadium should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ferrovanadium dust can affect the body if it is inhaled or if it comes in contact with the eyes.

- **Effects of overexposure**

Ferrovanadium dust causes irritation of the eyes, nose, and throat.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ferrovanadium dust.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ferrovanadium dust at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed. The skin and eyes should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Ferrovanadium dust may cause respiratory impairment. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Ferrovanadium dust is reported to cause asthmatic-like symptoms. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

Ferrovanadium dust is a mild irritant of the eyes and respiratory tract. Animals exposed for 1 hour on alternate days for 2 months to very high concentrations (1000 to 2000 mg/m^3) developed chronic bronchitis and pneumonitis. Workers exposed to unspecified concentrations developed a slight irritation of the eyes and respiratory tract. Systemic effects have not been reported from industrial exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: Not applicable
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of ferrovanadium dust): Not applicable

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

5. Melting point: Not applicable
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**
1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: None
4. Special precautions: None

• **Flammability**
1. Flash point: Not applicable
2. Minimum ignition temperature: 400 C (752 F) (layer); 440 C (824 F) (cloud)
3. Minimum explosive concentration: 1.3 grams per cubic meter
4. Extinguishant: Dry sand, dry dolomite, dry graphite powder

• **Warning properties**
Ferrovanadium dust may cause eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

• **General**
Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**
Sampling and analyses may be performed by collection of ferrovanadium dust, followed by chemical treatment and atomic absorption spectrophotometry. An analytical method for ferrovanadium dust is in the *NIOSH Manual of Analytical Methods*. 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

SANITATION

• Eating and smoking should not be permitted in areas where ferrovanadium dust is generated in handling, processing, or storing of ferrovanadium.

• Employees who handle ferrovanadium dust should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ferrovanadium dust may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during manufacture and processing of ferrovanadium alloy	General dilution ventilation; personal protective equipment
Use in the production of steel as an additive to produce grain refinement and hardenability	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**
If ferrovanadium dust gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention . Contact lenses should not be worn when working with this chemical.

• **Breathing**
If a person breathes in large amounts of ferrovanadium dust, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of release until cleanup has been completed.

• If potentially hazardous amounts of ferrovanadium dust are inadvertently released, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of release to disperse the dust.
3. Collect released material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Ferrovanadium dust may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ferrovanadium," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kirk, R , and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Vanadium*, HEW Publication No. (NIOSH) 77-222, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Roberts, W. C.: "The Ferroalloy Industry - Hazards of the Alloys and Semimetallics: Part II," *Journal of Occupational Medicine*, 7:71, 76-77, 1965.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR FERROVANADIUM DUST

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any dust and mist respirator, except single-use respirator.
10 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Fluoride Dust (as Fluoride)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all fluoride. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Sodium fluoride

- Formula: NaF
- Synonyms: None
- Appearance and odor: Colorless or blue, odorless solid.

Cryolite (sodium hexafluoroaluminate)

- Formula: Na_3AlF_6
- Synonyms: Sodium hexafluoroaluminate
- Appearance and odor: Colorless to dark, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for fluoride is 2.5 milligrams of fluoride per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be changed to 2.5 mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week. The NIOSH Criteria Document for Inorganic Fluorides should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Fluoride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Fluoride containing dust may cause irritation of the eyes and respiratory tract. Swallowing fluoride may cause a salty or soapy taste, vomiting, abdominal pain, diarrhea, shortness of breath, difficulty in speaking, thirst, weakness of the pulse, disturbed color vision, muscular weakness, convulsions, loss of consciousness, and death. Kidney injury and bleeding from the stomach may occur.

2. Long-term Exposure: Repeated exposure to fluoride containing dust may cause excessive calcification of the bone and calcification of ligaments of the ribs, pelvis, and spinal column. Stiffness and limitation of motion may result. Repeated or prolonged exposure of the skin to fluoride containing dust may cause a skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to fluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to fluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory tract, central nervous system, skeletal system, and the kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney disease interferes with excretion of fluoride, thus increasing the risk from exposure to excessive fluoride, a urinalysis should be

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

651

obtained to include, at a minimum, specific gravity, albumin, glucose, and a microscopic examination on centrifuged sediment. An analysis for fluoride should be performed.

—Pelvic roentgenogram: Fluoride causes skeletal abnormalities. A radiologic examination of the male pelvis with proper gonadal shielding should be conducted at the time of the preplacement examination and when indicated by analysis of the results of the urinary fluoride tests.

—Eye disease: Fluoride is an eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

—14" x 17" chest roentgenogram: Fluoride may cause respiratory system effects, such as fibrosis and asthma. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Fluoride is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Skin disease: Fluoride can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that the radiologic examination of the pelvis should be conducted only when clinically indicated.

- **Summary of toxicology**

Fluoride causes irritation of the eyes and respiratory tract; absorption of excessive amounts of fluoride over a long period of time results in increased radiographic density of bone. The lethal oral dose of sodium fluoride for humans is approximately 5 g; effects are diffuse abdominal pain, diarrhea, and vomiting; excessive salivation, thirst, and perspiration; painful spasms of the limbs; and sometimes albuminuria. Workers exposed to an airborne fluoride concentration of 5 mg/m³ complained of eye and respiratory tract irritation and nausea. A portion of absorbed fluoride is stored in bone and part is excreted promptly in the urine; with continued exposure and increasing amounts of fluoride already present in the bone, the fraction appearing in the urine increases. Some storage of fluoride occurs from the ingestion of as little as 3 mg/day. Repeated exposure to excessive concentrations of fluorides over a period of years results in increased radiographic density of bone and eventually may cause crippling fluorosis (osteosclerosis due to deposition of fluoride). The gross changes in the skeleton are quite distinctive and characteristic; as the amount of fluoride in the bone increases, exostoses may develop, especially on the long bones; the spinal and pelvic ligaments begin to calcify, occasionally vertebrae fuse together, and a typical stiffness of the spinal column develops. The absorption of 20 to 80 mg of fluoride daily may be expected to lead to crippling fluorosis in 10 to 20 years; this condition has not been reported in the United States from industrial exposure. Evidence from several sources indicates that urinary fluoride concentrations not exceeding 5 mg/l in preshift samples taken after 2 days off work are not associated with detectable osteosclerosis and that such changes are unlikely at urinary levels of 5 to 8 mg/l. Repeated or prolonged exposure of the skin to fluoride-bearing dusts and fumes may cause dermatitis. Mottled appearance and altered form of teeth are most pronounced when excessive amounts of fluoride are ingested during the period of formation and calcification of teeth, which occurs during the first 8 years of life in humans; after the teeth erupt and calcification has been completed, fluoride does not have an adverse effect on the teeth.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data—Sodium fluoride**
  1. Molecular weight: 42
  2. Boiling point (760 mm Hg): 1702 C (3095 F)
  3. Specific gravity (water = 1): 2.8
  4. Vapor density (air = 1 at boiling point of sodium fluoride): Not applicable
  5. Melting point: 992 C (1818 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 4.2
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Physical data—Cryolite (sodium hexafluoroaluminate)**
  1. Molecular weight: 209.9
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): 2.8
  4. Vapor density (air = 1 at boiling point of cryolite): Not applicable
  5. Melting point: 1009 C (1848 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.04
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with strong acids may cause formation of toxic and irritating hydrogen fluoride gas.
  3. Hazardous decomposition products: None
  4. Special precautions. None
- **Flammability**
  1. Not combustible
- **Warning properties**

Concerning fluorides, Grant states that "industrially, fluorides may contact the eyes in the form of fumes from fluxes in soldering, in welding, and in magnesium foundries. Irritation of the eyes and nose has been reported when fluoride concentration has reached 5 mg/m³ of air."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of fluoride in an impinger containing sodium hydroxide, followed by dilution with a buffer, and analysis with an ion-specific electrode. An analytical method for fluoride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 1, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00267-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with fluoride.

• If employees' clothing has had any possibility of being contaminated with fluoride, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with fluoride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of fluoride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the fluoride, the person performing the operation should be informed of fluoride's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of sodium fluoride or liquids containing sodium fluoride contacting the eyes.

• Non-impervious clothing which becomes contaminated with fluoride should be removed promptly and not reworn until the fluoride is removed from the clothing.

SANITATION

• Skin that becomes contaminated with fluoride should be promptly washed or showered to remove any fluoride.

• Eating and smoking should not be permitted in areas where fluoride is handled, processed, or stored.

• Employees who handle fluoride should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to fluoride dust may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from mining, beneficiation, packaging, and distribution of fluorspar	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation from fluorides from phosphate rock treatment	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation from use of fluorspars as a fluxing additive for steel production	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation from manufacture of cryolite from phosphate rock processing; use of fluorspar and cryolite in the production of metallic aluminum by electrolysis	Local exhaust ventilation; general dilution ventilation; personal protective equipment

Operation	Controls
Use in formulations of insecticides for agricultural crops, fruits, vegetables, ornamentals, and trees	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in chemical industry as a source of fluorine compounds; use of fluorspar and cryolite in ceramics and glass industry in manufacture of fiberglass, optical glass, lenses, and pottery; use of fluorspar in manufacture of welding rods and welding fluxes; use in electroplating	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in treatment of water	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If fluoride or liquids containing fluoride get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If fluoride or liquids containing fluoride get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If fluoride or liquids containing fluoride soak through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of fluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquids containing fluoride have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or releases until cleanup has been completed.

• If fluoride is spilled or released in hazardous concentrations, the following steps should be taken:

1. Ventilate area of spill or release.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing fluoride should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Fluoride may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Fluoride Dust," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Fluoride-Bearing Dusts and Fumes (Inorganic)," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Biological Monitoring Guides: "Fluorides," *American Industrial Hygiene Association Journal*, 32:274-279, 1971.

• Committee on Biologic Effects of Atmospheric Pollutants, Division of Medical Sciences, National Research Council: *Fluorides*, Washington, D.C., 1971.

• Dinman, B. D., et al.: "Prevention of Bony Fluorosis in Aluminum Smelter Workers," *Journal of Occupational Medicine*, 18:7-25, 1976.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hodge, H. C., and Smith, F. A.: "Air Quality Criteria for the Effects of Fluorides on Man," *Journal of theAir Pollution Control Association*, 20:226-232, 1970.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Largent, E. J.: "Rates of Elimination of Fluoride Stored in the Tissues of Man," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 6:37-42, 1952.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Inorganic Fluorides*, HEW Publication No. (NIOSH) 76-103, GPO No. 017-033-00118-9, U.S. Government Printing Office, Washington, D C., 1975.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

• World Health Organization: *Fluorides and Human Health*, Geneva, 1970.

RESPIRATORY PROTECTION FOR FLUORIDE DUST (AS FLUORIDE)

Condition	Minimum Respiratory Protection* Required Above 2.5 mg/m³
Particulate Concentration	
12.5 mg/m³ or less**	A single-use dust respirator.
25 mg/m³ or less**	Any dust respirator, except single-use or quarter-mask respirator.*** Any supplied-air respirator. Any self-contained breathing apparatus.
125 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece.*** Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
250 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter, and a full facepiece.*** A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 250 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	An escape gas mask with an acid gas canister. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

***If acid gases are present, air-purifying elements providing protection against acid gases and including the indicated filters should be used.

Occupational Health Guideline for Fluorine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: F_2
- Synonyms: None
- Appearance and odor: Pale yellow gas.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for fluorine is 0.1 part of fluorine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.2 milligram of fluorine per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for fluorine a Threshold Limit Value of 1 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Fluorine can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

Exposure to fluorine gas may cause irritation of the eyes, nose, throat, lungs, and skin. It may cause severe breathing difficulties which may be delayed in onset. At high concentrations, as when coming directly from a gas cylinder, fluorine may cause severe burns of the eyes and skin. In animal experiments, exposure to fluorine has produced kidney and liver damage.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to fluorine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to fluorine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory tract, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Fluorine causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEC (1 sec): Fluorine is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Fluorine gas is a severe irritant of the eyes, mucous membranes, and skin. It reacts with water to produce ozone and hydrofluoric acid. The LC50 in mice for 60 minutes was 150 ppm; effects were irritation of the eyes and nose and the delayed onset of dyspnea and lethargy; autopsy findings included marked pulmonary congestion and hemorrhage. Mice exposed to sublethal concentrations had pulmonary irritation and delayed development of focal necrosis in the liver and kidneys. In humans the inhalation of high concentrations causes laryngeal spasm and bronchospasm, followed by the delayed onset of pulmonary edema; there may also be

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

gastrointestinal disturbances. Two human subjects found momentary exposure to 50 ppm intolerable; 25 ppm was tolerated briefly, but both subjects developed sore throat and chest pain which persisted for 6 hours. A blast of fluorine gas on the shaved skin of a rabbit caused a second-degree burn; lower concentrations cause severe burns of insidious onset resulting in ulceration, similar to those produced by hydrogen fluoride.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 38
2. Boiling point (760 mm Hg): −188 C (−307 F)
3. Specific gravity (water = 1): (Liquid) 1.5 at boiling point
4. Vapor density (air = 1 at boiling point of fluorine): 1.3
5. Melting point: −219 C (−363 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause cylinders to burst.
2. Incompatibilities: Fluorine is a dangerously reactive gas. Contact with water causes formation of toxic hydrogen fluoride gas. It reacts vigorously with most oxidizable materials at room temperature, frequently with ignition. It reacts with nitric acid to form fluorine nitrate, which is an explosive gas.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen fluoride) may be released when fluorine decomposes.
4. Special precautions: Fluorine will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible, but strong oxidizer.
2. Compressed gas cylinders containing fluorine should be stored in accordance with 29 CFR 1910.101.

- **Warning properties**

1. Odor Threshold: The *Hygienic Information Guide* for fluorine of the Commonwealth of Pennsylvania Division of Occupational Health states that fluorine "can be detected by odor in concentrations of only a few parts per million." Deichmann and Gerarde note that the odor is "sharp, penetrating, and characteristic."
2. Eye Irritation Level: Grant states that "exposure of human volunteers to fluorine in air showed that, although it caused very little irritation up to 25 ppm, it caused much irritation of the eyes and nose at 100 ppm. However, there were no aftereffects from exposure of the eyes to 100 ppm for one-half minute. Contact with high concentrations of fluorine gas or liquefied fluorine would presumably be extremely destructive."
3. Evaluation of Warning Properties: Since the odor and irritation thresholds are not within three times the permissible exposure limit, fluorine is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for fluorine had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid fluorine, and to prevent skin from becoming frozen from contact with vessels containing liquid fluorine.
- Where there is any possibility of exposure of an employee's body to liquid fluorine, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with liquid fluorine should be removed immedi-

ately and not reworn until the fluorine is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid fluorine contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid fluorine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid fluorine should be immediately washed or showered to remove any fluorine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to fluorine may occur and control methods which may be effective in each case:

Operation	Controls
Use during organic and inorganic synthesis in the production of fluorine compounds, refrigerants, plastics, incendiary devices, and electrolytic solvents	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a rocket fuel oxidizer for ammonia, hydrazine, hydrogen, JP-4, and diborane fuels at laboratories and test sites	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid fluorine or high concentrations of fluorine gas get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid fluorine or high concentrations of fluorine gas get on the skin, immediately flush the contaminated skin with water. If liquid fluorine or high concentrations of fluorine gas penetrate through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of fluorine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If fluorine is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Fluorine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Fluorine," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dibbell, D. G., et al.: "Hydrofluoric Acid Burns of the Hand," *Journal of Bone and Joint Surgery*, 52A:931-936, 1970.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• *Hygienic Information Guide No. 38 - Fluorine*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Keplinger, M. L., and Suissa, L. W.: "Toxicity of Fluorine Short-Term Inhalation," *American Industrial Hygiene Association Journal*, 29:10-18, 1968.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Ricca, P. M.: "A Survey of the Acute Toxicity of Elemental Fluorine," *American Industrial Hygiene Association Journal*, 31:22-29, 1970.

RESPIRATORY PROTECTION FOR FLUORINE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Gas Concentration	
1ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
25 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 25 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-oxidizable sorbents and providing protection against fluorine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of fluorine; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 25 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Fluorotrichloromethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CCl_3F
- Synonyms: Refrigerant 11; Freon 11; monofluorotrichloromethane; trichlorofluoromethane; trichloromonofluoromethane
- Appearance and odor: Colorless liquid or gas with a chlorinated-solvent odor that is detectable only at concentrations well above the permissible exposure (above 20% by volume).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for fluorotrichloromethane is 1000 parts of fluorotrichloromethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 5600 milligrams of fluorotrichloromethane per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for fluorotrichloromethane from 1000 ppm as a time-weighted average value to 1000 ppm as a ceiling value.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Fluorotrichloromethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Fluorotrichloromethane may cause drowsiness, unconsciousness, and death. Breathing high concentrations of this material may also cause the heart to beat irregularly or to stop suddenly.

2. Long-term Exposure: Prolonged overexposure to fluorotrichloromethane may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to fluorotrichloromethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to fluorotrichloromethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from fluorotrichloromethane exposure.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrhythmias, the inhalation of fluorotrichloromethane might cause exacerbation of disorders of the conduction mechanism due to its sensitizing effects on the myocardium.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Fluorotrichloromethane vapor is a narcotic and may cause asphyxia at high concentrations. The approximate lethal concentration for rats exposed for 4 hours was 66,000 ppm; guinea pigs exhibited stupor and incoordination after exposure to 50,000 ppm for 2 hours, while animals breathing concentrations of 22,000 ppm showed only occasional tremors. Repeated exposure of several species to 4,000 ppm for 7 hours daily resulted in no toxic effects. Sniffing aerosols of fluorochlorinated hydrocarbons has caused sudden death by cardiac arrest,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

probably due to sensitization of the myocardium. No instances of toxic effects from industrial exposure have been reported, but since the substance can dissolve the natural oils of the skin, dermatitis may be expected to result from repeated contact.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 137.4
  2. Boiling point (760 mm Hg): 23.8 C (74.8 F)
  3. Specific gravity (water = 1): 1.49
  4. Vapor density (air = 1 at boiling point of fluorotrichloromethane): 4.7
  5. Melting point: −111 C (−168 F)
  6. Vapor pressure at 20 C (68 F): 690 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.11
  8. Evaporation rate (butyl acetate = 1): 63
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Fluorotrichloromethane reacts with chemically active metals such as sodium, potassium, calcium, powdered aluminum, zinc, and magnesium.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and hydrogen fluoride) may be released when fluorotrichloromethane decomposes.
  4. Special precautions: Liquid fluorotrichloromethane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**

According to Patty, fluorotrichloromethane is odorless; therefore, for the purposes of this guideline, it is treated as a material with poor warning properties.

Fluorotrichloromethane is not a known eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for fluorotrichloromethane had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid fluorotrichloromethane.
- Non-impervious clothing which becomes wet with liquid fluorotrichloromethane should be removed promptly and not reworn until the fluorotrichloromethane has evaporated.
- Employees should be provided with and required to use splash-proof safety goggles where liquid fluorotrichloromethane may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to fluorotrichloromethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a propellant in aerosols for insecticides, floor waxes, paint, cosmetics, and perfumes	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a refrigerant; as a blowing agent in foam plastics; as a solvent and degreaser; in production of polymeric	General dilution ventilation; local exhaust ventilation; personal protective equipment

resins; as a dielectric fluid in bubble chambers, and in wind tunnels; use as a sulfonation solvent in chemical synthesis

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid fluorotrichloromethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid fluorotrichloromethane gets on the skin, immediately flush the contaminated skin with water if the liquid fluorotrichloromethane has already evaporated. If liquid fluorotrichloromethane soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of fluorotrichloromethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention immediately.

• **Swallowing**

When fluorotrichloromethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If fluorotrichloromethane is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If the gas is leaking, stop the flow of gas.
3. If in the liquid form, allow to vaporize.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Fluorotrichloromethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Fluorotrichloromethane," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• E. I. DuPont de Nemours and Company: "Freon Compounds and Safety," *Freon Product Information*.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Reinhardt, C., et al.: "Cardiac Arrhythmias and Aerosol 'Sniffing'," *Archives of Environmental Health*, 22:265-279, 1971.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck & Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR FLUOROTRICHLOROMETHANE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Formic Acid

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: HCOOH
- Synonyms: Formic acid 85%; formic acid 90%; formic acid 95%; hydrogen carboxylic acid; methanoic acid
- Appearance and odor: Colorless liquid that may fume with a pungent, penetrating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for formic acid is 5 parts of formic acid per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 9 milligrams of formic acid per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- Routes of exposure

Formic acid can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- Effects of overexposure

1. Short-term Exposure: Formic acid may cause irritation of the eyes, nose, throat, upper respiratory tract, and skin. These are often accompanied by watering of the eyes, nasal discharge, and coughing. Skin contact with concentrated solutions causes severe irritation and blistering. Swallowing formic acid has caused a number of cases of severe poisoning and death. The symptoms found in this type of poisoning include salivation, vomiting, burning sensation of the mouth, bloody vomiting, diarrhea, and pain. In severe poisoning, the person may go into shock. Later, the person may have trouble breathing and may die. The person may also have kidney damage. One death has been reported in a worker who had hot formic acid splashed in his face. This worker could not speak, had trouble breathing, and died six hours later.

2. Long-term Exposure: Prolonged or repeated exposure to formic acid may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to formic acid.

- Recommended medical surveillance

The following medical procedures should be made available to each employee who is exposed to formic acid at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from formic acid exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of formic acid might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Formic acid is a primary skin irritant and has caused skin sensitization. Persons with preexisting skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although formic acid is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Liver disease: Although formic acid is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

—Eye disease: Formic acid is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure. *2. Periodic Medical Examination:* Any employee developing the above-listed conditions should be referred for further medical examination.

• **Summary of toxicology**

Formic acid vapor is a severe irritant of the eyes, mucous membranes, and skin. Exposure causes eye irritation with lacrimation, nasal discharge, throat irritation, and cough. A worker splashed in the face with hot formic acid developed marked dyspnea with dysphagia, and died within 6 hours. Workers exposed to a mixture of formic and acetic acids at an average concentration of 15 ppm of each complained of nausea. The liquid on the skin causes burns with vesiculation; keloid formation at the site of the burn often results. Skin sensitization may occur in persons previously exposed to formaldehyde. While ingestion of the liquid is unlikely in ordinary industrial use, the highly corrosive nature of the substance may be expected to produce serious burns of the mouth and esophagus.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 46.03
2. Boiling point (760 mm Hg): 85%: 107 C (224.6 F); 90%: 106.5 C (223.7 F); 95%: 102 C (215.6 F)
3. Specific gravity (water = 1): 1.2
4. Vapor density (air = 1 at boiling point of formic acid): 1.6
5. Melting point: 85%: −15.3 C (4.5 F); 90%: −6.5 C (20.3 F); 95%: 1.4 C (34.5 F)
6. Vapor pressure at 20 C (68 F): 23− 33 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): 2.1

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers or strong caustics may cause fires and explosions. Contact with concentrated sulfuric acid causes formation of toxic and flammable carbon monoxide gas.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving formic acid.
4. Special precautions: Liquid formic acid will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point (90% solution): 50 C (122 F) (closed cup)
2. Autoignition temperature (90% solution): 435 C (813 F)
3. Flammable limits in air, % by volume: Lower: 18; Upper: 57
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: May reports an odor threshold of 21 ppm. Patty states that formic acid has a "pungent, penetrating" odor.
2. Eye Irritation Level: Grant notes,"It has been said that the vapors of formic acid are irritating to the eyes . . ., but there appears to be little in the literature on this subject." According to Patty, "the principal hazard is that of severe primary damage to the skin, eye, or mucosal surfaces." Deichmann and Gerarde also state that formic acid is irritating to the eyes.
3. Other Information: Grant, Patty, and Deichmann and Gerarde report that formic acid is a mucous membrane irritant, capable of irritating the upper respiratory tract and the eyes. The *Documentation of TLV's* states that "workers exposed to formic and acetic acids in a textile plant . . . at concentrations of each acid averaging 15 ppm" experienced irritation at these levels.
4. Evaluation of Warning Properties: Through its odor and irritant effects, formic acid is detectable at concentrations only several times the permissible exposure limit. For the purposes of this guideline, therefore, formic acid is judged to have adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of formic acid on chromosorb 103, desorption with deionized water, and analysis by ion chromatography. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure formic acid may be used. An analytical method for formic acid is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the

process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid formic acid.

• Clothing contaminated with formic acid should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of formic acid from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the formic acid, the person performing the operation should be informed of formic acid's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid formic acid, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with formic acid should be removed immediately and not reworn until the formic acid is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid formic acid or solutions containing formic acid contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid formic acid or solutions containing 1% or more of formic acid by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with formic acid should be immediately washed or showered to remove any formic acid.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to formic acid may occur and control methods which may be effective in each case:

Operation	Controls
Use in textile dyeing and finishing industry as a dye exhausting agent; chrome dyeing; to impart finishes to cotton; an acidifying agent; and shrink- and wrinkle-proofing compound	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a chemical intermediate as a strong reducing agent for acids, salts, dyes, fumigants, refrigerants, pharmaceuticals, and solvents	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in leather processing industry as a deliming agent and neutralizer; as a preservative and levelling agent	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in rubber industry as a coagulant for natural rubber latex and form making; as a preservative of latex	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a catalyst in hydrocarbon-formaldehyde resins and phenolic resins, and plasticizer for vinyl resins	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in electroplating industry to control particle size and plating thickness	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an antiseptic in wine and beer brewing, preservative in animal feed additives and cleaning solution compounds	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in miscellaneous operations as a wire stripping compound and preparing bare wires for soldering; laundry sour; and as an oil well acidifying agent	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If formic acid or solutions containing formic acid get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If formic acid gets on the skin, immediately flush the contaminated skin with water. If formic acid soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of formic acid, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If formic acid has been swallowed and the person is conscious, give him large quantities of water immediately to dilute the formic acid. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If formic acid is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Formic acid should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Formic acid may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Formic Acid," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Formaldehye," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Henson, E. V.: "Toxicology of the Fatty Acids," *Journal of Occupational Medicine*, 1:339-345, 1959.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saunders, Philadelphia, 1960.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Formic Acid*, New York, 1968.

• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters - Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 20:517-522, 530-531, 1959.

RESPIRATORY PROTECTION FOR FORMIC ACID

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor of Particulate Concentration	
100 ppm or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Furfural

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_4H_3OCHO
- Synonyms: 2-Furaldehyde; furfuraldehyde; fural; 2-furancarboxaldehyde
- Appearance and odor: Colorless to light brown liquid that darkens on standing in light and air. Odor is like almonds.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for furfural is 5 parts of furfural per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 20 milligrams of furfural per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes to their recommended Threshold Limit Value for furfural from 5 ppm to 2 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Furfural can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Furfural may cause irritation of the skin, eyes, and respiratory tract. It may also cause a person to become unconscious.

2. Long-term Exposure: Furfural may cause sensitization of the skin, loss of sense of taste, and numbness of the tongue.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to furfural.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to furfural at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from furfural exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of furfural might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Skin disease: Furfural can cause dermatitis on excessive exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although furfural is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although furfural is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Furfural vapor is irritating to the eyes, respiratory tract, and skin. It has been reported to be a central nervous system poison in large doses in some animals, causing hyper-reflexia and convulsions.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

670

September 1978

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 96
  2. Boiling point (760 mm Hg): 162 C (323 F)
  3. Specific gravity (water = 1): 1.16
  4. Vapor density (air = 1 at boiling point of furfural): 3.3
  5. Melting point: −36.5 C (−33.7 F)
  6. Vapor pressure at 20 C (68 F): 2 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 8.3
  8. Evaporation rate (butyl acetate = 1): Very low
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong acids and oxidizing materials may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving furfural.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 60 C (140 F) (closed cup)
  2. Autoignition temperature: 316 C (600 F)
  3. Flammable limits in air, % by volume: Lower: 2.1; Upper: 19.3
  4. Extinguishant: Carbon dioxide, dry chemical, or alcohol foam
- **Warning properties**
  1. Odor Threshold: The AIHA *Hygienic Guide* states that "although the odor threshold of furfural vapor has been reported to be 0.25 to 0.38 ppm, some industrial hygienists maintain that the odor becomes readily noticeable only near the TLV concentration of 5 ppm."
  2. Eye Irritation Level: Grant states that "chronic exposure to the vapor at concentrations of 13.5 ppm or less in air is reported to cause reddening of the eyes, tearing, and irritation of the throat in workers." The *Hygienic Guide* states that the "irritating properties of furfural, which become uncomfortable at 20 to 50 ppm, probably preclude voluntary exposures which might lead to significant injury."
  3. Nasal Irritation Level: The *Hygienic Guide* states that "nasal irritation would indicate that the TLV was being exceeded."
  4. Evaluation of Warning Properties: Through its odor and irritant effects, furfural can be detected near the permissible exposure limit. For the purposes of this guideline, therefore, furfural is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for furfural is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid furfural.
- Clothing contaminated with furfural should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of furfural from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the furfural, the person performing the operation should be informed of furfural's hazardous properties.
- Non-impervious clothing which becomes contaminated with furfural should be removed promptly and not reworn until the furfural is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid furfural may contact the eyes.

SANITATION

- Skin that becomes contaminated with furfural should be promptly washed or showered to remove any furfural.
- Employees who handle liquid furfural should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to furfural may occur and control methods which may be effective in each case:

Operation	Controls
Use during removal of industrial coatings in open-surface tanks	Local exhaust ventilation; personal protective equipment
Liberation during cold molding of abrasive grinding wheels	General dilution ventilation
Use in rubber of phenolic cement adhesives	General dilution ventilation; personal protective equipment
Liberation during molding of miscellaneous phenolic resin products	Local exahaust ventilation; general dilution ventilation
Use during molding of friction materials as brake linings, clutch facings, brake blocks, etc.	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during manufacture of reinforced plastic products	General dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during coating of products with resins/varnishes as wire coating, food containers, paper, canvas, etc.	General dilution ventilation; process enclosure; local exhaust ventilation
Liberaiton during vulcanization of rubber in processes using furfural as an accelerator	General dilution ventilation; process enclosure; local exhaust ventilation
Liberation during manufacture of furfuryl alcohol	Process enclosure; general dilution ventilation
Liberation during use as a chemical intermediate in manufacture of furor, tetrahydrofuran, tetrahydrofuryl alcohol, hexamethylene diamens, and pyromucic acid	General dilution ventilation
Liberation during manufacture of phenolic-furfural resins; during dewaxing of oils, primarily lubricating oils; during decolorization of wood resins	Process enclosure; general dilution ventilation
Use during manufacture of surface coatings	General dilution ventilation; process enclosure; local exhaust ventilation
Liberation during separation of butadiene, benzene, and miscellaneous compounds from C_4 hydrocarbons; during manufacture of some polyurethane elastomers	Process enclosure; general dilution ventilation
Use during in situ desludging and decarbonizing of internal combustion engines	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If furfural gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If furfural gets on the skin, promptly flush the contaminated skin with water. If furfural soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of furfural, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When furfural has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If furfural is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. For large quantities, cover with sodium bisulfite ($NaHSO_3$), add a small amount of water and mix. Then, after one hour, flush with large amounts of water and wash site with soap solution.

• Waste disposal methods:

Furfural may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. For small quantities, by absorbing it in vermiculite, dry sand, earth, or a similar material and disposing it in a suitable combustion chamber.
3. For large quantities, by mixing with a flammable liquid (such as acetone) and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Furfural," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Furfural," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Ill., 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

RESPIRATORY PROTECTION FOR FURFURAL

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
250 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 250 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Glycidol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_3H_6O_2$
- Synonyms: 2-Hydroxymethyloxiran; hydroxymethyl ethylene oxide; epoxypropyl alcohol; glycide; 3-hydroxypropylene oxide; 2,3-epoxy-1-propanol
- Appearance: Colorless liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for glycidol is 50 parts of glycidol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 150 milligrams of glycidol per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Glycidol can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to glycidol may cause irritation of the eyes, nose, and throat.

2. Long-term Exposure: Prolonged overexposure might produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to glycidol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to glycidol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from glycidol exposure.

—Skin disease: Glycidol is a primary skin irritant and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of glycidol might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Glycidol vapor is an irritant to the eyes and upper respiratory tract, a skin irritant, and a central nervous system depressant. The LC50 for mice (4 hr) was 450 ppm, and for rats (8 hr), 580 ppm, resulting in pneumonitis; rats exposed at 400 ppm daily showed only slight eye irritation and mild respiratory distress, with no evidence of systemic toxicity. Lethal doses of 0.45 to 0.85 g/kg of the liquid administered by gastric tube resulted initially in nervous system depression, but surviving animals showed a reversal of the depressant effect, manifested by excitation and tremors. Direct application of the liquid to the skin of animals classifies glycidol as a moderate skin irritant; instilled into the eye, it is classified as a severe eye irritant. Exposure to near-saturated vapor for 8 hours resulted in corneal opacity. Repeated intramuscular injections do not affect hematopoiesis in rats. The only report of toxic effects in humans is that of irritation of the eyes, nose, and respiratory tract of experimenters working with the compound at room temperature.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 74
2. Boiling point (760 mm Hg): 166 C (331 F) (decomposes)
3. Specific gravity (water = 1): 1.1
4. Vapor density (air = 1 at boiling point of glycidol): 2.6
5. Melting point: −45 C (−49 F)
6. Vapor pressure at 20 C (68 F): 0.9 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents (especially nitrates) may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving glycidol.
4. Special precautions: Glycidol will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 72 C (162 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, carbon dioxide, alcohol foam

• **Warning properties**

1. Odor Threshold: No information is available concerning the odor threshold of glycidol.
2. Eye Irritation Level: Grant states, "In vapor form, glycidol has proven damaging to the corneas of rats, but for human beings the vapor has been found to have adequate warning properties, consisting of eye and respiratory irritation, to preclude excessive industrial exposure." The *Documentation of TLV's* states that following the first few exposures, "rats exposed at 400 ppm glycidol 7 hours a day for 50 days . . . (experienced) very slight irritation of the eyes, with slight lacrimation and encrustation of the eyelids . . . ." No quantitative information is available concerning the threshold of eye irritation.
3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of glycidol, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of glycidol vapors using an adsorption tube with subsequent desorption with tetrahydrofuran and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure glycidol may be used. An analytical method for glycidol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid glycidol.

• Clothing contaminated with liquid glycidol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of glycidol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the glycidol, the person performing the operation should be informed of glycidol's hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid glycidol should be removed promptly and not reworn until the glycidol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid glycidol may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid glycidol should be promptly washed or showered to remove any glycidol.
• Employees who handle liquid glycidol should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to glycidol may occur and control methods which may be effective in each case:

Operation	Controls
Use in surface coatings; use in chemical synthesis; use as a stabilizer for natural oils and vinyl polymers	General dilution ventilation; personal protective equipment
Use as a demulsifying agent; use as a dye leveling (retarding) agent	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If glycidol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If glycidol gets on the skin, promptly wash the contaminated skin with water. If glycidol soaks through the clothing, remove the clothing immediately and wash the skin with water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of glycidol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When glycidol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If glycidol is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber, or absorbed in vermiculite, dry sand, earth, or a similar material and disposed in a sanitary landfill.
• Waste disposal method:
Glycidol may be disposed of by dissolving in petroleum and atomizing in a suitable combustion chamber, or absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Glycidol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Biesele, J. J., et al.: "Chromosome Alteration and Tumour Inhibition by Nitrogen Mustards: The Hypothesis of Cross-Linking Alkylation," *Nature*, 166:4235, pp. 1112-1113, December 1950.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Ill., 1974.
• Hine, C. H., et al.: "Toxicology of Glycidol and Some Glycidyl Ethers," *A.M.A. Archives of Industrial Health*, 14:250-264, 1956.
• Kodama, J. K., et al.: "Some Effects of Epoxy Compounds on the Blood," *Archives of Environmental Health*, 2:1, pp. 50-61, January 1961.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR GLYCIDOL

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Natural Graphite

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C
- Synonyms: Plumbago; potelot; carbo mineralis; black lead; carburet of iron; silver lead; crayon noir
- Appearance and odor: Black, greasy, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for natural graphite is 15 million particles of natural graphite per cubic foot of air (mppcf) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Natural graphite can affect the body if it is inhaled or if it comes in contact with the eyes.

- **Effects of overexposure**

Repeated inhalation of natural graphite over a number of years may cause scarring of the lungs with such symptoms as chest tightness, shortness of breath, cough, black sputum, and pain.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to natural graphite.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to natural graphite at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system and the cardiovascular system should be stressed.

—14" x 17" chest roentgenogram: Natural graphite may cause human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Natural graphite is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Natural graphite dust causes graphite pneumoconiosis. The earliest roentgenologic changes may be the disappearance of normal vascular markings, with the appearance later of pinpoint and macronodular densities in all lung fields. Massive lesions, when present, are caused by large cysts filled with black fluid. The pleura is often involved: hydrothorax, pneumothorax, and pleural thickening may occur. At autopsy, the lungs are gray-black to black; histologically there are widely scattered particles, spicules, and plates of graphite, often within intra-alveolar phagocytes amidst diffuse interstitial fibrosis and occasionally pneumonitis. There are also interwoven bands of collagen, similar to those found in silicosis, which frequently are the most prominent feature of the fibrotic lesions occupying the lung and the bronchial lymph nodes. Symptoms include expectoration of black sputum, dyspnea, and cough. It has been generally believed that the capacity of inhaled natural graphite dust to cause disease is largely the result of its crystalline silica component. However, there is a recent report of a worker who, after exposure to "nearly pure" carbon for 17 years as a grinder of synthetic graphite bars, developed cough, dyspnea, and reduced pulmonary function, and died. At autopsy, both ventricles of

---

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

the heart were hypertrophied, and the lungs revealed the typical findings of graphite pneumoconiosis including fibrous tissue; the ashed material from the lung showed little or no birefringent particles, indicating the absence of silicious material.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 12
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): 2.25
  4. Vapor density (air = 1 at boiling point of natural graphite): Not applicable
  5. Melting point: 3350 C (6040 F) (sublimes)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with very strong oxidizers such as fluorine, chlorine trifluoride, and potassium peroxide may cause fires and explosions.
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Flash point: Not applicable
  2. Minimum ignition temperature: 730 C (1346 F) (cloud); 580 C (1076 F) (layer)
  3. Minimum explosive concentration: Data not available
  4. Extinguishant: Water
- **Warning properties**

Grant states that "carbon, when pure, has no toxic effect on the eye. As superficial foreign bodies, carbon black and graphite may be slightly irritating mechanically and may cause discoloration of lids and conjunctivae, but they are chemically inert."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for graphite had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to natural graphite may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during mining, purification, packaging, blasting, and drilling	Local exhaust ventilation; personal protective equipment
Use in foundry facings; steelmaking as carbon raiser; manufacture of refractories in crucibles and retorts; use in manufacture of lubricants and adhesives in bearings, slides, gears, engines, and mold release agents	Process enclosure; local exhaust ventilation; personal protective equipment
Manufacture of writing and drafting agents; manufacture of industrial paints, inks, and polishes; manufacture of motor and generator brushes, batteries, carbon resistors, and electrodes	Process enclosure; local exhaust ventilation; personal protective equipment

Use in manufacture of tungsten carbide cutting tools, friction materials and clutch facings; use in electroplating; use in manufacture of ammunition; miscellaneous uses in hard rubber, engine packing, cord, rope, twine, floor coverings, and coatings for fertilizer	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If natural graphite gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Breathing**

If a person breathes in large amounts of natural graphite, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If natural graphite is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation, burning in a suitable combustion chamber or for disposal in a secured sanitary landfill.

• Waste disposal methods:

Natural graphite may be disposed of:

1. In a sanitary landfill.
2. By burning in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Graphite (Natural)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Gaensler, E. A., et al.: "Graphite Pneumoconiosis of Electrotypers," *American Journal of Medicine*, 41:864-869, 871, 873-882, 1966.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Lister, W. B., and Wimborne, D.: "Carbon Pneumoconiosis in a Synthetic Graphite Worker," *British Journal of Industrial Medicine*, 29:108-110, 1972.

• Pendergrass, E. P., et al.: "Observations on Workers in the Graphite Industry - Part One," *Medical Radiography and Photography*, 43:70-99, 1967.

• Pendergrass, E. P., et al.: "Observations on Workers in the Graphite Industry - Part Two," *Medical Radiography and Photography*, 44:2-17, 1968.

• Ranasinha, K. W., and Uragoda, C. G.: "Graphite Pneumoconiosis," *British Journal of Industrial Medicine*, 29:178-183, 1972.

• Zenz, C.: *Occupational Medicine - Principles and Practical Applications*, Year Book Medical Publishers, Inc., Chicago, 1975.

RESPIRATORY PROTECTION FOR NATURAL GRAPHITE

Condition	Minimum Respiratory Protection* Required Above 15 mppcf
Particulate Concentration	
75 mppcf or less	Any dust respirator.
150 mppcf or less	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mppcf or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
7500 mppcf or less	A powered air-purifying respirator with a high efficiency filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 7500 mppcf or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Hafnium and Compounds (as Hafnium)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all hafnium and compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Hafnium

- Formula: Hf
- Synonyms: Hafnium, metallic; hafnium, elemental
- Appearance: Gray solid

Hafnium tetrachloride

- Formula: $HfCl_4$
- Synonyms: None
- Appearance and odor: White solid with an acrid odor in moist air.

Hafnium oxychloride

- Formula: $HfOCl_2 \cdot 8H_2O$
- Synonyms: Hafnium oxychloride octahydrate
- Appearance and odor: White, odorless solid

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hafnium and compounds (as hafnium) is 0.5 milligram of hafnium and compounds (as hafnium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hafnium, hafnium tetrachloride, or hafnium oxychloride can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

Exposure to hafnium salts has caused irritation of the eyes and skin in animals. Hafnium chloride has caused liver damage in animals on prolonged feeding.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hafnium and compounds (as hafnium).

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to hafnium and compounds at potentially hazardous levels. The employer should screen employees for history of liver disease. Hafnium compounds have been reported to cause liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function. Only those giving a postive history of these conditions should be referred for further medical examinations.

- **Summary of toxicology**

Hafnium and its compounds have been reported to cause liver damage in animals. The LD50 of hafnium, chiefly as the oxychloride, was 76 mg Hf/kg for mice. A 90-day hafnium chloride feeding study in rats at 1.0% and 0.1% resulted in unspecified liver effects. Studies with radioactive Hf mandelate indicate slow elimination from the body. Some compounds may cause irritation of eyes, skin, and mucous membranes.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Hafnium**

1. Molecular weight: 178.5
2. Boiling point (760 mm Hg): 3100 C (5612 F) approximately
3. Specific gravity (water = 1): 13.3
4. Vapor density (air = 1 at boiling point of hafnium): Not applicable
5. Melting point: 2227 C (4040 F)
6. Vapor pressure at 20 C (68 F): Very low
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Hafnium tetrachloride**

1. Molecular weight: 320.3
2. Boiling point (760 mm Hg): 317 C (603 F)
3. Specific gravity (water = 1): Data not available
4. Vapor density (air = 1 at boiling point of hafnium tetrachloride): Not applicable
5. Melting point: 432 C (809 F)
6. Vapor pressure at 20 C (68 F): Very low
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Hafnium oxychloride**

1. Molecular weight: 409.5
2. Boiling point (760 mm Hg): Decomposes (data not available)
3. Specific gravity (water = 1): Data not available
4. Vapor density (air = 1 at boiling point of hafnium oxychloride): Not applicable
5. Melting point: Less than 50 C (less than 122 F)
6. Vapor pressure at 20 C (68 F): Very low
7. Solubility in water, g/100 g water at 20 C (68 F): Very soluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact of hafnium metal with chlorine and strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving hafnium, hafnium tetrachloride, or hafnium oxychloride.
4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: Hafnium: Data not applicable; hafnium tetrachloride and hafnium oxychloride: Not applicable
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Hafnium: Water; hafnium tetrachloride and hafnium oxychloride: Not applicable

• **Warning properties**

Hafnium is not known to be an eye irritant; however, Haley reports that hafnium compounds may prove irritating to the mucosal surfaces.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for hafnium and compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with wet or dry hafnium powder. The clothing should be flame-resistant and should be treated or should be of a type so as to minimize the static electricity hazard of ignition.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing

necessary to prevent skin contact with hafnium tetrachloride, hafnium oxychloride, or liquids containing these compounds, where skin contact may occur.

- If employees' clothing has had any possibility of being contaminated with wet or dry hafnium powder, employees should change into uncontaminated clothing before leaving the work premises.
- If employees' clothing may have become contaminated with hafnium tetrachloride, hafnium oxychloride, or liquids containing these compounds, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing which has had any possibility of being contaminated with wet or dry hafnium powder should be placed in fireproof closed containers for storage until it can be discarded or until provision is made for the removal of hafnium from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the hafnium, the person performing the operation should be informed of hafnium's hazardous properties.
- Clothing contaminated with hafnium tetrachloride or hafnium oxychloride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of contaminant from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the contaminant, the person performing the operation should be informed of contaminant's hazardous properties.
- Where there is any possibility of exposure of an employee's body to wet or dry hafnium powder, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Where exposure of an employee's body to hafnium tetrachloride, hafnium oxychloride, or liquids containing these compounds may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes contaminated with wet or dry hafnium powder should be removed promptly but in a careful and cautious manner so as to reduce the probability of ignition by friction, static electricity, or other causes. Such clothing should not be reworn until the hafnium is removed from the clothing.
- Non-impervious clothing which becomes wet with hafnium tetrachloride, hafnium oxychloride, or liquids containing these compounds should be removed promptly and not reworn until the contaminant is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of wet or dry hafnium powder, hafnium tetrachloride, hafnium oxychloride, or liquids containing these compounds contacting the eye.
- Where there is any possibility that employees' eyes may be exposed to wet or dry hafnium powder, hafnium tetrachloride, hafnium oxychloride, or liquids containing these compounds, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Workers subject to skin contact with wet or dry hafnium powder should wash any areas of the body which may have contacted hafnium powder at the end of each work day.
- Skin that becomes wet with wet or dry hafnium powder should be promptly washed or showered with soap or mild detergent and water to remove any contaminant.
- Skin that becomes contaminated with hafnium tetrachloride, hafnium oxychloride, or liquids these compounds should be promptly washed or showered to remove any contaminant.
- Eating and smoking should not be permitted in areas where wet or dry hafnium powder, hafnium tetrachloride, or solid hafnium oxychloride or liquids containing these compounds are handled, processed, or stored.
- Employees who handle hafnium or its compounds or liquids containing hafnium or its compounds should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hafnium and compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from mining and purification of hafnium (separation from zirconium); manufacture and fabrication of special alloys	Local exhaust ventilation; personal protective equipment
Use as control rods in water-cooled nuclear reactors; use in gas-filled tubes and incandescent lamps as scavenger for oxygen and nitrogen; use in the manufacture of photographic flash bulbs, light bulb filaments, and in electronic equipment as cathodes and capacitors	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid proce-

dures and send for first aid or medical assistance.

• **Eye Exposure**

If hafnium, hafnium tetrachloride, or hafnium oxychloride get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If hafnium gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If hafnium tetrachloride or hafnium oxychloride get on the skin, promptly flush the contaminated skin with water. If hafnium or its compounds soak through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of hafnium, hafnium tetrachloride, or hafnium oxychloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When hafnium, hafnium tetrachloride, or hafnium oxychloride have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If hafnium, hafnium tetrachloride, or hafnium oxychloride are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquid containing hafnium, hafnium tetrachloride, or hafnium oxychloride should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Hafnium, hafnium tetrachloride, or hafnium oxychloride may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hafnium," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Haley, T., et al.: "The Toxicologic and Pharmacologic Effects of Hafnium Salts," *Toxicology and Applied Pharmacology*, 4:238-246, 1962.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-92, Hafnium*, Washington, D.C., 1966.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

RESPIRATORY PROTECTION FOR HAFNIUM AND COMPOUNDS (AS HAFNIUM)

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate Concentration	
2.5 mg/m³ or less	Any dust and mist respirator, except single-use.
5 mg/m³ or less	Any dust and mist respirator, except single-use respirator or quarter mask. Any fume respirator or high efficiency particulate respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
250 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode. A powered air-purifying respirator with a high efficiency particulate filter.
Greater than 250 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Heptachlor *

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_5Cl_7$ (principal ingredient)
- Synonyms: 1,4,5,6,7,8,8a-Heptachloro-3a,4,7,7a-tetra-hydro-4, 7-methanoindene (principal ingredient)
- Appearance and odor: Light tan, waxy solid with an odor like camphor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for heptachlor is 0.5 milligram of heptachlor per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Heptachlor can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

In animals, exposure to heptachlor has produced tremors, convulsions, and liver damage. Heptachlor is very similar to chlordane. Exposure to chlordane has caused convulsions and kidney damage in humans.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to heptachlor.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to heptachlor at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of convulsive disorders would be expected to be at increased risk from exposure. Examination of the eyes, nervous system, liver, and kidneys should be stressed.

2. Periodic Medical Examination: The aforementioned medical examination should be repeated on an annual basis.

- **Summary of toxicology**

Heptachlor dust is a convulsant in animals. In rats the oral LD50 was 90 mg/kg; within 30 to 60 minutes after administration there were tremors and convulsions; liver damage occurred. Multiple applications of a solution to the skin of rats of 20 mg/kg were toxic, indicating a marked cumulative action. The carcinogenicity of heptachlor was tested in rats by oral administration; one of five experiments suggested hepatocarcinogenicity, but this was not reproduced in the other experiments within the same dose range. Rats given heptachlor in the diet at 6 mg/kg body weight developed cataracts after 4.5 to 9.5 months of feeding. In animals, heptachlor is more potent than chlordane, to which it is closely related chemically; ingestion of chlordane has caused convulsions and kidney damage in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 373.5 (principal ingredient)
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.65
4. Vapor density (air = 1 at boiling point of heptachlor): Not applicable
5. Melting point: 46 – 74 C (114 – 165 F)
6. Vapor pressure at 20 C (68 F): 0.0003 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F):

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

688

September 1978

Insoluble

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Solid: None. Liquid (above 74 C (165 F): Can react with iron and rust to form toxic hydrogen chloride gas.

2. Incompatibilities: Contact of melted heptachlor with iron and rust may form hydrogen chloride gas.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released when heptachlor decomposes.

4. Special precautions: None.

• **Flammability**

1. Not combustible, but may be dissolved in flammable liquid

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of heptachlor.

2. Eye Irritation Level: Heptachlor is not known to be an eye irritant.

3. Evaluation of Warning Properties: Since there is no quantitative information available relating warning properties to air concentrations of heptachlor, it has been treated as a material with poor warning properties. Its concentration in saturated air at 20 C could result in a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for heptachlor is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with heptachlor or liquids containing heptachlor where skin contact may occur.

• If employees' clothing has had any possibility of being contaminated with heptachlor or liquids containing heptachlor, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with heptachlor should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of heptachlor from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the heptachlor, the person performing the operation should be informed of heptachlor's hazardous properties.

• Where exposure of an employee's body to heptachlor or liquids containing heptachlor may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with heptachlor should be removed immediately and not reworn until the heptachlor is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where heptachlor or liquids containing heptachlor may contact the eyes.

SANITATION

• Skin that becomes contaminated with heptachlor should be immediately washed or showered with soap or mild detergent and water to remove any heptachlor.

• Workers subject to skin contact with heptachlor or liquids containing heptachlor should wash with soap or mild detergent and water any areas of the body which may have contacted heptachlor at the end of each work day.

• Eating and smoking should not be permitted in areas where heptachlor or liquids containing heptachlor are handled, processed, or stored.

• Employees who handle heptachlor or liquids contain-

ing heptachlor should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to heptachlor may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of pesticides supplied as an emulsifiable concentrate, wettable powder, dust or granular material	Local exhaust ventilation; personal protective equipment; general dilution ventilation
Use as an insecticide in seed treatment, preplanting soil application, dipping tops of plants and roots for control of insects, flies and mosquitoes; use on household plots and on agricultural crops and fruits; use in termite control (dispensed in caulking guns)	Personal protective equipment
Manufacture of heptachlor	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• Eye Exposure

If heptachlor or liquids containing heptachlor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• Skin Exposure

If heptachlor or liquids containing heptachlor get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If heptachlor or liquids containing heptachlor soak through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• Breathing

If a person breathes in large amounts of heptachlor, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• Swallowing

When heptachlor or liquids containing heptachlor have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If heptachlor is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquid containing heptachlor should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Heptachlor may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Heptachlor," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Council on Pharmacy and Chemistry, American Medical Association: "The Present Status of Chlordane," *Journal of the American Medical Association*, 158:1364-1367, 1955.

• Derbes, V. J., et al.: "Fatal Chlordane Poisoning," *Journal of the American Medical Association*, 158:1367-1369, 1955.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Agency for Research on Cancer: *Some Organochlorine Pesticides*, Vol. 5 of *IARC Evaluation of the Carcinogenic Risk of Chemicals to Man*, Lyon, France, 1974.

• Mestitzova, M.: "On Reproduction Studies and the

Occurrence of Cataracts in Rats after Long-Term Feeding of the Insecticide Heptachlor," *Experientia*, 23:42-43, 1967.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 5, 1974.

RESPIRATORY PROTECTION FOR HEPTACHLOR

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate or Vapor Concentration	
5mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
700 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 700 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of heptachlor; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 700 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Heptane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3(CH_2)_5CH_3$
- Synonyms: Normal heptane
- Appearance and odor: Colorless liquid with a mild, gasoline-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for heptane is 500 parts of heptane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2000 milligrams of heptane per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be reduced to 85 ppm averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 440 ppm averaged over a 15-minute period. The NIOSH Criteria Document for Alkanes should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Heptane can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to heptane may cause a slight irritation of the eyes, nose, and throat, lightheadedness, hilarity, semi-consciousness, and dizziness. It may also cause loss of appetite and nausea. Higher concentrations may cause unconsciousness.

2. Long-term Exposure: Prolonged overexposure to the liquid may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to heptane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to heptane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central and peripheral nervous systems and the skin should be stressed.

—Skin disease: Heptane is a skin defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of heptane might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although heptane is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although heptane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: The aforementioned examinations should be performed on an annual basis.

- **Summary of toxicology**

Heptane vapor is a narcotic. Concentrations of 10,000 to 15,000 ppm produced narcosis in mice within 30 to 60 minutes, while 15,000 to 20,000 ppm caused convulsions

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

and death. At 48,000 ppm respiratory arrest was produced in mice in 3 to 4 minutes from the start of exposure. Human subjects exposed to 1000 ppm for 6 minutes, or to 2000 ppm for 4 minutes, reported slight vertigo. At 5000 ppm for 4 minutes, there was marked vertigo, inability to walk a straight line, hilarity, and incoordination, but no complaints of eye and upper respiratory tract or mucous membrane irritation. A 15-minute exposure at 5000 ppm produced in some subjects a state of stupor lasting for 30 minutes after exposure. These subjects also reported loss of appetite, slight nausea, and a taste resembling gasoline for several hours after exposure. The liquid is a defatting agent, and prolonged exposure may cause irritation of the skin. Aspiration may cause a chemical pneumonia. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 100
  2. Boiling point (760 mm Hg): 98.4 C (209 F)
  3. Specific gravity (water = 1): 0.7
  4. Vapor density (air = 1 at boiling point of heptane): 3.5
  5. Melting point: −90.6 C (−132 F)
  6. Vapor pressure at 20 C (68 F): 40 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.005
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving heptane.
  4. Special precautions: Heptane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −3.9 C (25 F) (closed cup)
  2. Autoignition temperature: 215 C (419 F)
  3. Flammable limits in air, % by volume: Lower: 1.05; Upper: 6.7
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Summer reports an odor threshold of 220 ppm; May reports 50 and 220 ppm.
  2. Eye Irritation Level: Heptane is not known to be an eye irritant.
  3. Evaluation of Warning Properties: Since the odor threshold of heptane is well below the permissible exposure limit, heptane is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of heptane. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of heptane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure heptane may be used. A analytical method for heptane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid heptane.
- Any clothing which becomes wet with liquid heptane should be removed immediately and not reworn until the heptane is removed from the clothing.
- Clothing wet with liquid heptane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of heptane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the heptane, the person performing the operation should be informed of heptane's hazardous properties.
- Employees should be provided with and required to use splash-proof safety goggles where liquid heptane may contact the eyes.
- Where there is any possibility that employees' eyes may be exposed to heptane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes wet with liquid heptane should be promptly washed or showered with soap or mild detergent and water to remove any heptane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to heptane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a carrier and penetrant solvent for adhesives, use in azeotrophic distillations, and in rubber tire manufacture; as a solvent in rubber cements	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an ink solvent in gravure printing	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent in polymer industry as a swelling and blowing agent for plastic foams	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a reference fuel for testing gasoline engine knock and pollution and combustion studies	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a diluent solvent for lacquers during preparation and application	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic chemical synthesis in preparations of toluene and alkylbenzenes	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an extraction solvent for tallow from meat, rosin from wood, and oils from seeds	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in cleaning surfaces before application of adhesives	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a laboratory solvent for scientific testing	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If heptane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If heptane gets on the skin, promptly wash the contaminated skin using soap or mild detergent. If heptane soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of heptane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If heptane has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If heptane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Heptane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Heptane may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Heptane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Heptane," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Exxon Corporation: *Material Safety Data Sheet - Heptane.*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Alkanes*, HEW Publication No. (NIOSH) 77-151, GPO No. 017-033-00213-4, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Swann, H. E., Jr., et al.: "Acute Inhalation Toxicology of Volatile Hydrocarbons," *American Industrial Hygiene Association Journal*, 35:511-518, 1974.

RESPIRATORY PROTECTION FOR HEPTANE

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
850 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
4250 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 4250 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Hexachloroethane*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CCl_3CCl_3
- Synonyms: Perchloroethane
- Appearance and odor: Colorless solid with a camphor-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hexachloroethane is 1 part of hexachloroethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 10 milligrams of hexachloroethane per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of their recommended Threshold Limit Value for hexachloroethane from 1 ppm to 10 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hexachloroethane can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

Exposure to the hot fumes of hexachloroethane may cause irritation of the eyes.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hexachloroethane. employee who is exposed to hexachloroethane at potentially hazardous levels.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to hexachloroethane at potentially hazardous levels.

- **Summary of toxicology**

Hexachloroethane is an eye irritant. High oral doses in animals cause hepatic, renal, and central nervous system effects. Dogs given oral doses of 1 to 1.4 g/kg showed depression of the central nervous system characterized by weakness, staggering, and muscle twitching. When administered orally to domestic animals as a parasiticide, it caused chronic lesions in the liver and acute, diffuse nephrosis in cattle at high doses, but it had no noticeable toxic effect in horses at levels of 0.2 g/kg. Exposure of workmen to fumes from hot hexachloroethane resulted in blepharospasm, photophobia, lacrimation, and reddening of the conjunctiva, but no corneal injury or permanent damage. No chronic effects have been reported from industrial exposure, although significant absorption through the skin is said to occur.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 236.7
2. Boiling point (760 mm Hg): 189 C (372 F) (sublimes)
3. Specific gravity (water = 1): 2.1
4. Vapor density (air = 1 at boiling point of hexachloroethane): 8.2
5. Melting point: 189 C (372 F) (sealed tube)
6. Vapor pressure at 20 C (68 F): 0.22 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.005
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

608

1. Conditions contributing to instability: Heat

2. Incompatibilities: Hexachloroethane reacts with hot iron, zinc, and aluminum. Dehalogenation by reaction with alkalies will produce spontaneously explosive chloroacetylene.

3. Hazardous decomposition products: Toxic gases and vapors (such as phosgene, chlorine, carbon tetrachloride, and tetrachloroethylene) may be released when hexachloroethane decomposes.

4. Special precautions: Liquid hexachloroethane will attack some forms of plastics, rubber, and coatings.

• Flammability

1. Not combustible

• Warning properties

Although hexachloroethane has a camphor-like odor, no quantitative data are available relating air concentrations of this substance to warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Method

Sampling and analyses may be performed by collection of hexachloroethane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure hexachloroethane may be used. An analytical method for hexachloroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid hexachloroethane or liquids containing hexachloroethane.

• If employees' clothing may have become contaminated with solid hexachloroethane or liquids containing hexachloroethane, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with solid hexachloroethane or liquids containing hexachloroethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of hexachloroethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the hexachloroethane, the person performing the operation should be informed of hexachloroethane's hazardous properties.

• Non-impervious clothing which becomes contaminated with solid hexachloroethane or liquids containing hexachloroethane should be removed promptly and not reworn until the hexachloroethane is removed from the clothing.

SANITATION

• Workers subject to skin contact with solid hexachloroethane or liquids containing hexachloroethane should wash with soap or mild detergent and water any areas of the body which may have contacted hexachloroethane at the end of each work day.

• Skin that becomes contaminated with solid hexachloroethane or liquids containing hexachloroethane should be promptly washed or showered with soap or mild detergent and water to remove hexachloroethane.

• Employees who handle hexachloroethane or liquids containing hexachloroethane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, and using toilet facilities.

• Eating and smoking should be permitted in areas where solid hexachloroethane or liquids containing hexachloroethane are handled, processed, or stored.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hexachloroethane may occur and

control methods which may be effective in each case:

Operation	Controls
Use in manufacture of pyrotechnics	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in lubricants in foundries for mold treatment; extreme-pressure lubricants; use in preparation of nitrocellulose esters camphor substitutes; use as a fumigant, insecticide, fungicide, and animal antihelmintics; use as a modifier in manufacture of synthetic rubber	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a chemical additive; use to reduce ignitability of combustibles, and as submarine paint to prevent corrosion; as an additive to fire extinguishers	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If hexachloroethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If hexachloroethane gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquids containing hexachloroethane soak through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of hexachloroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention immediately.

• **Swallowing**

When hexachloroethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If hexachloroethane is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquid containing hexachloroethane should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Hexachloroethane may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hexachloroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 20, 1979.

RESPIRATORY PROTECTION FOR HEXACHLOROETHANE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
10 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
300 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 300 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any pesticide respirator providing protection against pesticides. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Hexachloronaphthalene (Halowax 1014)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_2Cl_6$
- Synonyms: Halowax 1014
- Appearance and odor: Light yellow solid with an aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Halowax 1014 is 0.2 milligram of Halowax 1014 per cubic meter of air (mg/m³) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Halowax 1014 can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. Every effort should be made to prevent skin, eye, oral, or inhalation contact with this material.

- **Effects of overexposure**

Overexposure to Halowax 1014 may cause an acne-like skin rash. It may also injure the liver, resulting in such effects as fatigue, dark urine, yellow jaundice, and possibly death.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Halowax 1014.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Halowax 1014 at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Since this substance is a known liver toxin, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Halowax 1014 vapor and dust are toxic to the liver and the skin. Repeated exposure to an average concentration of 8.9 mg/m³ of a mixture of penta- and Halowax 1014 produced jaundice and was fatal to rats; the liver showed marked fatty degeneration and centrolobular necrosis. At concentrations of mixed penta- and Halowax 1014 averaging 1 to 2 mg/m³, there were human fatalities due to acute yellow atrophy of the liver. Such exposures produced jaundice associated with nausea, indigestion, and weight loss. The acute late stage progresses from restlessness to confusion, fever, and coma. Exposure of workers by inhalation of vapor or dust, or by skin absorption, has caused a severe acneform dermatitis termed chloracne, as well as serious liver injury.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 335
2. Boiling point (760 mm Hg): 343 to 388 C (650 to 730 F) (approximately)
3. Specific gravity (water = 1): 1.78
4. Vapor density (air = 1 at boiling point of Halowax 1014): 11.6
5. Melting point: 137 C (279 F)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

702

6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble

8. Evaporation rate (butyl acetate = 1): Much less than 1

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Halowax 1014 reacts with strong oxidizing agents.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released when Halowax 1014 decomposes.

4. Special precautions: None

• **Flammability**

1. Not combustible

• **Warning properties**

No quantitative data are available on the relationship between air concentrations of the chloronaphthalenes and warning properties. Vapor pressure at 20 C is less than 1 mm Hg, creating a concentration of less than 1500 ppm at 20 C.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of Halowax 1014 on a filter, followed by extraction with hexane, and gas chromatographic analysis. An analytical method for Halowax is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with molten Halowax 1014.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid Halowax 1014 or with liquids containing Halowax 1014.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with Halowax 1014 fumes from the heated material.

• Non-impervious clothing which becomes contaminated with molten Halowax 1014 should be removed immediately and not reworn until the Halowax 1014 is removed from the clothing.

• Non-impervious clothing which becomes contaminated with solid Halowax 1014 or liquids containing Halowax 1014 should be removed promptly and not reworn until the Halowax 1014 is removed from the clothing.

• If employees' clothing may have become contaminated with solid Halowax 1014, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with Halowax 1014 should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of Halowax 1014 from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the Halowax 1014, the person performing the operation should be informed of Halowax 1014's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of molten Halowax 1014 contacting the eyes.

• Employees should be provided with and required to use splash-proof safety goggles where solid Halowax 1014 or liquids containing Halowax 1014 may contact the eyes.

SANITATION

• Eating and smoking should not be permitted in areas where Halowax 1014 is handled, processed, or stored.

• Workers subject to skin contact with Halowax 1014 should wash with soap or mild detergent and water any areas of the body which may have contacted Halowax 1014 at the end of each work day.
• Skin that becomes contaminated with solid Halowax 1014 or liquids containing Halowax 1014 should be promptly washed or showered with soap or mild detergent and water to remove any Halowax 1014.
• Employees who handle Halowax 1014 should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Halowax 1014 may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture (pouring, dipping, and peeling) of electric equipment as insulating material	Local exhaust ventilation; personal protective equipment; general dilution ventilation with intake and exhaust fans
Use as an inert component of resins or polymers for coating or impregnating textiles, wood, paper for flame- and water-proofing, and fungicidal and insecticidal properties	Process enclosure; local exhaust ventilation with intake and exhaust fans; general dilution ventilation
Use as an additive to special lubricants	General dilution ventilation
Use as an additive to cutting oils and special lubricants	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during use of electrical equipment when substance used as insulating material	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in polymer manufacture as fillers; use during manufacture of special lubricants	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**
If solid Halowax 1014 or liquids containing Halowax 1014 get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. If molten Halowax 1014 gets into the eyes, immediately flush the eyes with large amounts of water to remove the heat. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If non-impervious clothing becomes soiled with Halowax 1014, remove and clean the clothing before wearing again. If non-impervious clothing becomes heavily contaminated, it should be destroyed. If solid Halowax 1014 or liquids containing Halowax 1014 get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If skin irritation persists after washing, get medical attention. If molten Halowax 1014 gets on the skin or non-impervious clothing, immediately flush the affected area with large amounts of water to remove heat. Get medical attention immediately.
• **Breathing**
If a person breathes in large amounts of Halowax 1014, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention immediately.
• **Swallowing**
When Halowax 1014 has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If Halowax 1014 is spilled, the following steps should be taken:
1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquids containing Halowax 1014

should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:
Halowax 1014 may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hexachloronaphthalene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hexachloronaphthalene," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kleinfeld, M., et al.: "Clinical Effects of Chlorinated Naphthalene Exposure," *Journal of Occupational Medicine*, 14:377-379, 1972.

• Koppers Corporation: *Material Safety Data Sheet – Hexachloronapthalene.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR HALOWAX 1014

Condition	Minimum Respiratory Protection* Required Above 0.2 mg/m³
Particulate or Vapor Concentration	
2 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against pesticides. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Hexane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3(CH_2)_4CH_3$
- Synonyms: Hexyl hydride; normal hexane
- Appearance and odor: Colorless liquid with a mild, gasoline-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hexane is 500 parts of hexane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1800 milligrams of hexane per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be reduced to 100 ppm (350 mg/m³) averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 510 ppm (1,800 mg/m³) averaged over a 15-minute period. The NIOSH Criteria Document for Alkanes should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hexane can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to hexane may cause lightheadedness, giddiness, nausea, and headache. It may also cause irritation of the eyes and nose. Greater exposure may cause unconsciousness and death.

2. Long-term Exposure: Prolonged overexposure to the liquid may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hexane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to hexane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central and peripheral nervous systems and the skin should be stressed.

—Skin disease: Hexane is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of hexane might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although hexane is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although hexane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: The aforementioned examinations should be performed on an annual basis.

- **Summary of toxicology**

Hexane vapor is a narcotic; it also is a mild upper respiratory irritant. Polyneuropathy has been reported to occur in Japanese workers exposed to hexane vapors. Effects appeared to be reversible. Concentrations of 30,000 ppm produced narcosis in mice within 30 to 60

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

minutes; convulsions and death occurred at 35,000 to 40,000 ppm; at 64,000 ppm respiratory arrest was produced in 2.5 to 4.5 minutes from the start of exposure. Concentrations up to 8000 ppm produced no anesthesia. In human subjects, 2000 ppm for 10 minutes produced no effects, but 5000 ppm resulted in dizziness and a sensation of giddiness. Other investigators reported slight nausea, headache, and irritation of the eyes and throat at 1400 to 1500 ppm. In industrial practice, mild narcotic symptoms such as dizziness have been observed when concentrations exceeded 1000 ppm, but not below 500 ppm. Chronic effects have rarely been reported. The liquid is a defatting agent, and prolonged exposure may cause irritation of the skin. Aspiration may cause a chemical pneumonia.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 86
  2. Boiling point (760 mm Hg): 68.9 C (156 F)
  3. Specific gravity (water = 1): 0.7
  4. Vapor density (air = 1 at boiling point of hexane): 3.0
  5. Melting point: −95 C (−139 F)
  6. Vapor pressure at 20 C (68 F): 124 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.014
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving hexane.
  4. Special precautions: Hexane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −21.7 C (−7 F) (closed cup)
  2. Autoignition temperature: 225 C (437 F)
  3. Flammable limits in air, % by volume: Lower: 1.1; Upper: 7.5
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: No quantitative information is available.
  2. Irritation Levels: The *Documentation of TLV's* notes that "Drinker, Yaglou, and Warren found slight nausea, headache, and eye and throat irritation at 1400 to 1500 ppm. Nelson found no irritation at 500 ppm in unacclimated subjects."
  3. Evaluation of Warning Properties: Since hexane can be detected at a concentration approximately 3 times the permissible exposure limit, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of hexane. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of hexane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure hexane may be used. An analytical method for hexane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

707

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid hexane.
- Any clothing which becomes wet with liquid hexane should be removed immediately and not reworn until the hexane is removed from the clothing.
- Clothing wet with liquid hexane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of hexane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the hexane, the person performing the operation should be informed of hexane's hazardous properties.
- Employees should be provided with and required to use splash-proof safety goggles where liquid hexane may contact the eyes.
- Where there is any possibility that employees' eyes may be exposed to hexane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes wet with liquid hexane should be promptly washed or showered with soap or mild detergent and water to remove any hexane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hexane may occur and control methods which may be effective in each case:

Operation	Controls
Use as an extractant of agricultural products	Process enclosure; general dilution ventilation
Use in manufacture of polyolefins and certain elastomers as a catalyst carrier and assist in controlling molecular weight by dropping polymer out of solution when a certain molecular weight is reached	Process enclosure; general dilution ventilation; personal protective equipment
Use as an extractant of animal fat	Process enclosure; general dilution ventilation; personal protective equipment
Use as a solvent in adhesives to control viscosity and reduce drying time	General dilution ventilation; personal protective equipment
Use in pharmaceutical industry as a reaction medium, immiscible solvent, and extraction ergot	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during compounding of adhesives as a diluent or vehicle solvent; use in compounding printing inks, lacquers, or stains; use as a laboratory reagent and general solvent; use in manufacture of low-temperature thermometers	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If hexane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If hexane gets on the skin, promptly wash the contaminated skin using soap or mild detergent. If hexane soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of hexane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

If hexane has been swallowed, do not induce vomiting. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If hexane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Hexane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Hexane may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hexane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hexane," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Charter Chemical Company: *Product Bulletin - Hexane.*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Inoue, T., et al.: "Polyneuritis Caused by n-Hexane and the Maximum Allowable Concentration," presentation at XVI Congress on Occupational Health, Tokyo, Japan, September 22-27, 1969.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Alkanes*, HEW Publication No. (NIOSH) 77-151, GPO No. 017-033-00213-4, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Swann, H. E., Jr., et al.: "Acute Inhalation Toxicology of Volatile Hydrocarbons," *American Industrial Hygiene Association Journal*, 35:511-518, 1974.

RESPIRATORY PROTECTION FOR HEXANE

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for sec-Hexyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOCH(CH_3)CH_2CH(CH_3)_2$
- Synonyms: 1,3-Dimethylbutyl acetate; methylamyl acetate; methylisoamyl acetate; methylisobutyl carbinol acetate; hexyl acetate
- Appearance and odor: Colorless liquid with a mild, pleasant, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sec-hexyl acetate is 50 parts of sec-hexyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 300 milligrams of sec-hexyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

sec-Hexyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to sec-hexyl acetate may cause eye and throat irritation. It may also cause headache, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged exposure to sec-hexyl acetate may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sec-hexyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sec-hexyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from sec-hexyl acetate exposure.

—Kidney disease: Although sec-hexyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of sec-hexyl acetate might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Liver disease: Although sec-hexyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Skin disease: sec-Hexyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

High concentrations of sec-hexyl acetate vapor may be mildly irritating to the eyes and upper respiratory tract. The lethal dose for animals by inhalation is approximately 4000 ppm, although rats survived 8 hour exposures to concentrated vapors. This agent is poorly absorbed through the skin. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 144
  2. Boiling point (760 mm Hg): 141 C (285 F)
  3. Specific gravity (water = 1): 0.86
  4. Vapor density (air = 1 at boiling point of sec-hexyl acetate): 5.0
  5. Melting point: −64 C (−83 F)
  6. Vapor pressure at 20 C (68 F): 4 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.13
  8. Evaporation rate (butyl acetate = 1): 0.47
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving sec-hexyl acetate.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 45 C (113 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Lower: 0.9 (calculated at flash point)
  4. Extinguishant: Dry chemical, foam, or carbon dioxide
- **Warning properties**
  1. Odor Threshold: The *Documentation of TLV's* reports that human subjects noted an unpleasant odor at 100 ppm.
  2. Eye Irritation Level: The *Documentation of TLV's* also reports that eye irritation was experienced by human subjects exposed to 100 ppm. The TLV was recommended "to prevent significant eye irritation."
  3. Other Information: According to the *Documentation of TLV's*, the human subject noted an unpleasant taste at 100 ppm.
  4. Evaluation of Warning Properties: At a concentration of only twice the permissible exposure limit, human subjects can detect sec-hexyl acetate through odor, eye irritation, and taste. For the purposes of this guideline, therefore, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of sec-hexyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure sec-hexyl acetate may be used. An analytical method for sec-hexyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid sec-hexyl acetate.
- Clothing wet with liquid sec-hexyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of sec-hexyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the sec-hexyl acetate, the person performing the operation should be informed of sec-hexyl acetate's hazardous properties.
- Non-impervious clothing which becomes wet with sec-hexyl acetate should be removed promptly and not reworn until the sec-hexyl acetate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid sec-hexyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid sec-hexyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any sec-hexyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sec-hexyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Use during application of nitrocellulose lacquers and other lacquers	General dilution ventilation; local exhaust ventilation
Liberation during manufacture of nitrocellulose and other lacquers	General dilution ventilation
Liberation during use as an inhibitor in handling of diacyl peroxide solutions	Process enclosure; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If sec-hexyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If sec-hexyl acetate gets on the skin, promptly flush the contaminated skin with water. If sec-hexyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of sec-hexyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When sec-hexyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If sec-hexyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Liquid sec-hexyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

sec-Hexyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "sec-Hexyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR SEC-HEXYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
4000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Hydrogen Bromide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: HBr
- Synonyms: Anhydrous hydrobromic acid
- Appearance and odor: Colorless gas with an irritating, sharp odor. It also can be a liquid when stored under pressure.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hydrogen bromide is 3 parts of hydrogen bromide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 10 milligrams of hydrogen bromide per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hydrogen bromide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Hydrogen bromide may cause irritation of the eyes, nose, and throat. If a solution is splashed on the skin or in the eyes, it will cause a burn.

2. Long-term Exposure: Repeated or prolonged exposure to hydrogen bromide may cause irritation of the nose and throat with mucous production and indigestion.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hydrogen bromide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to hydrogen bromide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from hydrogen bromide exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of hydrogen bromide might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Hydrogen bromide is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Hydrogen bromide is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Hydrogen bromide gas irritates the eyes, mucous membranes, and skin. Experimental exposure of humans to 5 ppm for several minutes caused nose and throat irritation in most individuals, and a few were affected at concentrations of 3 to 4 ppm. Solutions and the vapor irritate the upper respiratory tract. Contact with the eyes, skin, or mucous membranes may cause burns.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 80.92
2. Boiling point (760 mm Hg): −66.8 C (−88.2 F)
3. Specific gravity (water = 1): 2.16
4. Vapor density (air = 1 at boiling point of hydro-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

gen bromide): 2.8

5. Melting point: −86.9 C (−124 F)

6. Vapor pressure at 16.8 C (62 F): 20 atm.

7. Solubility in water, g/100 g water at 20 C (68 F): 194

8. Evaporation rate (butyl acetate = 1): Not pertinent

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact of liquid hydrogen bromide with strong oxidizers, strong caustics, metals, and moisture may cause violent spattering and fire.

3. Hazardous decomposition products: None

4. Special precautions: In the presence of moisture, hydrogen bromide liquid or gas will attack most metals with the formation of flammable hydrogen gas.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: According to the *Documentation of TLV's*, the odor of hydrogen bromide is detectable at 2 ppm.

2. Eye Irritation Level: According to the *Documentation of TLV's*, no eye irritation was observed in human subjects exposed to concentrations up to 6 ppm. Kirk and Othmer state that hydrogen bromide is an eye irritant, but do not specify the necessary concentration.

3. Other Information: The *Documentation of TLV's* reports that 1 out of 6 human subjects experienced nose and throat irritation at 3 ppm hydrogen bromide. At 4 ppm, 3 out of 6 experienced nose irritation. All exposed subjects experienced nose irritation at 5 and 6 ppm. Only 1 out of 6 subjects experienced throat irritation at concentrations of 4 ppm, 5 ppm, and 6 ppm.

4. Evaluation of Warning Properties: Through its odor and irritant effects, hydrogen bromide can be detected at the permissible exposure limit or slightly above it. Therefore, hydrogen bromide is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of hydrogen bromide in a bubbler containing sodium hydroxide, followed by analysis with an ion-specific electrode. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure hydrogen bromide may be used. An analytical method for hydrogen bromide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid hydrogen bromide or solutions containing hydrogen bromide.

• Clothing contaminated with hydrogen bromide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of hydrogen bromide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the hydrogen bromide, the person performing the operation should be informed of hydrogen bromide's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid hydrogen bromide or solutions containing hydrogen bromide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with hydrogen bromide should be removed immediately and not reworn until the hydrogen bromide is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety [illegible]gles where there is any possibility of liquid hydrogen bromide or solutions containing hydrogen bromide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid hydrogen bromide or solutions containing hydrogen bromide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with hydrogen bromide should be immediately washed or showered to remove any hydrogen bromide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hydrogen bromide may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of inorganic bromides for use in photography, pharmaceuticals, industrial drying, textile finishing, engraving and lithography, chemical synthesis, and fire retardants	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of brominated fluorocarbons for fire extinguishing, refrigeration, and aerosols	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in organic synthesis as intermediates for barbituate manufacture, manufacture of synthetic hormones, catalyst for alkylations, controlled oxidations, isomerizations, and polymerizations	General dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during decomposition of brominated fluorocarbon fire-extinguishing agents or flame-retardant chemicals	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a reagent in analytical chemistry; use in etching of germanium crystals, silicon discs, and metal alloys	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a solvent for ore minerals	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid hydrogen bromide or solutions containing hydrogen bromide get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid hydrogen bromide or solutions containing hydrogen bromide get on the skin, immediately flush the contaminated skin with water. If liquid hydrogen bromide or solutions containing hydrogen bromide penetrate through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of hydrogen bromide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If a solution of hydrogen bromide has been swallowed and the person is conscious, give him large quantities of water immediately to dilute the hydrogen bromide. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If hydrogen bromide is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. If in the gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the

open air, and repair the leak or allow the cylinder to empty.

3. If in the liquid form, allow to vaporize and disperse the gas.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Hydrogen Bromide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- American Industrial Hygiene Association: "Bromine," *Hygienic Guide Series*, Detroit, Michigan, 1958.
- Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.
- Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
- Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
- Dow Chemical Company: *Material Safety Data Sheet - Hydrogen Bromide*, Midland, Michigan, 1972.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.
- Lanza, A. J., and Goldberg, J. A. (eds.): *Industrial Hygiene*, Oxford University, London, 1939.
- National Institute for Occupational Safety and Health: "Hazard Entry No. 91 — Hydrogen Bromide," *Hazard Pr*
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR HYDROGEN BROMIDE

Condition	Minimum Respiratory Protection* Required Above 3 ppm
Gas or Vapor Concentration	
50 ppm or less	Any chemical cartridge respirator with a full facepiece and an acid gas cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted acid gas canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 50 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against acid gases.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Hydrogen Chloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: HCl
- Synonyms: Anhydrous hydrogen chloride; hydrochloric acid, anhydrous
- Appearance and odor: Colorless gas with an irritating, pungent odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hydrogen chloride is a ceiling of 5 parts of hydrogen chloride per million parts of air (ppm). This may also be expressed as 7 milligrams of hydrogen chloride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hydrogen chloride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: When hydrogen chloride gas is inhaled, it may cause irritation of the respiratory tract with burning, choking, and coughing. Severe breathing difficulties may occur which may be delayed in onset. At times ulceration of the nose and throat may occur. Hydrogen chloride gas and solutions of hydrogen chloride (hydrochloric acid) may cause eye irritation, severe burns, and permanent damage with loss of sight. Solutions of hydrogen chloride may cause severe burns of the skin unless the acid is washed off immediately. Exposure of the skin to hydrogen chloride gas may cause skin inflammation or burns. Swallowing hydrogen chloride solution may cause burns of the mouth, throat, and stomach.

2. Long-term Exposure: Repeated or prolonged exposure to hydrogen chloride may cause erosion of the teeth. Repeated exposure of the skin to dilute solutions of hydrogen chloride may cause skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hydrogen chloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to hydrogen chloride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, skin, and eyes should be stressed.

—14" x 17" chest roentgenogram: Hydrogen chloride causes lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Hydrogen chloride is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Hydrogen chloride gas irritates the eyes, mucous membranes, and skin. Exposure of rabbits and guinea pigs to 6400 mg/m^3 (approximately 4290 ppm) for 30 minutes caused death, in many instances from laryngeal spasm, laryngeal edema, or pulmonary edema. Exposure of three species of animals to 300 ppm for 6 hours caused

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

corneal and upper respiratory irritation. In humans, exposure to the gas immediately causes severe irritation of the upper respiratory tract resulting in cough, burning of the throat, and a choking sensation; effects are usually limited to inflammation and occasionally ulceration of the nose, throat, and larynx; if inhaled deeply, pulmonary edema may occur. In workers, exposure to 50 to 100 ppm for 1 hour was barely tolerable; short exposure to 35 ppm caused irritation of the throat, and 10 ppm was considered the maximal concentration allowable for prolonged exposure. High concentrations of the gas caused eye irritation and may cause prolonged or permanent visual impairment, including total loss of vision. Exposure of the skin to a high concentration of the gas or to a concentrated solution of the gas (hydrochloric acid) will cause burns; repeated or prolonged exposure to dilute solutions may cause dermatitis. Erosion of the teeth may occur from repeated or prolonged exposure. Although unlikely to occur, ingestion of hydrochloric acid causes severe burns of the mucous membranes of the mouth, esophagus, and stomach; pain; nausea and vomiting.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 36.5
2. Boiling point (760 mm Hg): −85 C (−121 F)
3. Specific gravity (water = 1): 1.194 (liquid)
4. Vapor density (air = 1 at boiling point of hydrogen chloride): 1.27
5. Melting point: −114 C (−173 F) (triple point)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): 62
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: High temperatures may cause cylinders to burst.
2. Incompatibilities: Contact with most metals corrodes them severely and forms flammable hydrogen gas. Contact of hydrogen chloride gas or liquid with any alkali or active metal may develop enough heat to cause fire in adjacent combustible material.
3. Hazardous decomposition products: None
4. Special precautions: Hydrogen chloride will attack most metals and some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible

- **Warning properties**

1. Odor Threshold: Patty notes that according to Hirt, a concentration of 35 ppm "cannot be detected by taste or odor. (Editor's note: Most people can detect 1 to 5 ppm; 5 to 10 ppm is disagreeable)." The editor does not specify how most people can detect 1 to 5 ppm, however.
2. Eye Irritation Level: Grant states that an exposure of animals to "100 ppm for 6 hours daily for 50 days caused only slight unrest and irritation of the eyes, but no injury."
3. Other Information: The *Documentation of TLV's* states that hydrogen chloride is a strong irritant. Thirty-five ppm "caused irritation of the throat on short exposure . . . . Elkins states, however, that hydrogen chloride was immediately irritating when inhaled at concentrations of 5 ppm or more."
4. Evaluation of Warning Properties: Through its irritant effects, hydrogen chloride can be detected at or slightly above the permissible exposure limit. For the purposes of this guideline, therefore, hydrogen chloride is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of hydrogen chloride. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of hydrogen chloride in a bubbler containing sodium acetate solution, followed by dilution with water, and analysis with an ion-specific electrode. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure hydrogen chloride may be used. An analytical method for hydrogen chloride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted

are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with mists or solutions of hydrogen chloride which have a pH less than 3.0.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with mists or solutions of hydrogen chloride which have a pH equal to or greater than 3.0.
- Where there is any possibility of exposure of an employee's body to solutions of hydrogen chloride which have a pH less than 3.0, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with solutions of hydrogen chloride which have a pH less than 3.0 should be removed immediately and not reworn until the hydrogen chloride is removed from the clothing.
- Non-impervious clothing which becomes wet with solutions of hydrogen chloride with a pH equal to or greater than 3.0 should be removed promptly and not reworn until the hydrogen chloride is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of mists of solutions of hydrogen chloride contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to solutions of hydrogen chloride which have a pH less than 3.0, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with solutions of hydrogen chloride which have a pH less than 3.0 should be immediately washed or showered to remove any hydrogen chloride.
- Skin that becomes wet with solutions of hydrogen chloride which have a pH equal to or greater than 3.0 should be promptly washed or showered to remove any hydrogen chloride.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hydrogen chloride may occur and control methods which may be effective in each case:

Operation	Controls
Use during pickling of metals including stainless steel, iron, nickel, and monel	Local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use as a catalyst or chlorinating agent in chemical synthesis; use during metal treatment and fabricating operations in electroplating, acid dipping, stripping, electropolishing, etching, welding, and flame-cutting of metal primed with paint or cleaned with chlorinated hydrocarbons, and used as a gaseous flux in babbitting	Local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use in oxyhydrochlorination processing in production of chlorinated hydrocarbons	Local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use in food processing and manufacture including sugar cane refining, glucose, and corn sugar, and brewing operations	Local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use in industrial chemical cleaning operations; use in production of plastics and resins	Local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use in rubber manufacture including synthesis of chloroprene; use as a chlorinating agent and in coagulation of latex	Local exhaust ventilation; general mechanical ventilation; personal protective equipment

Operation	Controls
Liberation during synthesis of other organic chemicals; use in extraction and reduction processing of metal ores	Local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use as a deliner of hides in leather manufacture	Local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use in activation of petroleum wells; use in waste treatment operations for neutralization of alkaline waste streams; use in production of chlorine	Local exhaust ventilation; general mechanical ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solutions of hydrogen chloride or strong concentrations of hydrogen chloride gas get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solutions of hydrogen chloride or strong concentrations of hydrogen chloride gas get on the skin, immediately flush the contaminated skin with water. If solutions of hydrogen chloride or strong concentrations of hydrogen chloride gas penetrate through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of hydrogen chloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If solutions of hydrogen chloride have been swallowed and the person is conscious, give him large amounts of water to dilute the hydrogen chloride. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If hydrogen chloride gas is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

• If solutions of hydrogen chloride are spilled, the following steps should be taken:

1. Collect or confine spilled material in the most convenient and safe manner.
2. If possible, reclaim the spilled material. If this is not possible;
3. dilute and/or neutralize and dispose in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hydrogen Chloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hydrogen Chloride," *Hygienic Guide Series*, Detroit, Michigan, 1958.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-39, Hydrogen Chloride*, Washington, D.C., 1970.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Poteshman, N. L.: "Corrosive Gastritis Due to Hydrochloric Acid Ingestion," *American Journal of Roentgenology, Radium Therapy and Nuclear Medicine*, 99:182-185, 1967.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadel-

phia, 1958.

RESPIRATORY PROTECTION FOR HYDROGEN CHLORIDE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Gas Concentration	
50 ppm or less	Any chemical cartridge respirator with an acid gas cartridge(s).
	Any supplied-air respirator.
	Any self-contained breathing apparatus.
100 ppm or less	Any chemical cartridge respirator with a full facepiece and an acid gas cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted acid gas canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 100 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against acid gases.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of hydrogen chloride; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 100 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Hydrogen Cyanide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: HCN
- Synonyms: Hydrocyanic acid; prussic acid; formonitrile
- Appearance and odor: Colorless or pale blue liquid or gas with a bitter almond odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hydrogen cyanide is 10 parts of hydrogen cyanide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 11 milligrams of hydrogen cyanide per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be reduced to 5 mg cyanide/m³ averaged over a 10-minute period. The NIOSH Criteria Document for Hydrogen Cyanide and Cyanide Salts should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hydrogen cyanide can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation, ingestion, or skin absorption of hydrogen cyanide may be rapidly fatal. Larger doses may cause the person to rapidly lose consciousness, stop breathing, and die. At lower levels of exposure, a person may experience weakness, headache, confusion, nausea, and vomiting. These symptoms may be followed by unconsciousness and death. Hydrogen cyanide liquid may irritate the eyes.

2. Long-term Exposure: Effects from chronic exposure to hydrogen cyanide are non-specific and rare.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hydrogen cyanide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to hydrogen cyanide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of fainting spells, such as occur in various types of cardiovascular and nervous disorders, and and those who are unusually susceptible to effects of anoxia or with anemia would be expected to be at increased risk from exposure. Examination of the cardiovascular, nervous, and upper respiratory systems, and thyroid should be stressed.

—Cardiovascular disease: Persons with cardiac disease may be at increased risk. An electrocardiogram should be performed on workers over 40 years of age and where indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

3. First Aid Kits: First aid kits should be immediately available in workplaces where there is a potential for the release of hydrogen cyanide. These kits should contain a minimum of 48 ampules, each of 0.3 ml amyl nitrate, and complete instructions for use. In addition, 2 physician's kits should be immediately available to trained medical personnel. These kits should contain the above quantity of amyl nitrate as well as sterile sodium

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

721

nitrite solution (3%) and sterile sodium thiosulfate solution (25%). All of the above drugs should be replaced at least biannually to ensure their potency.

• **Summary of toxicology**

Hydrogen cyanide (HCN) vapor, a source of cyanide ion, is an asphyxiant due to an inhibitory action on metabolic enzyme systems and can be rapidly fatal. Cyanide exerts this effect because it inactivates certain enzymes by forming very stable complexes with the metal in them. Cytochrome oxidase is probably the most important of these since it occupies a fundamental position in the respiratory process and is involved in the ultimate electron transfer to molecular oxygen. Since cytochrome oxidase is present in practically all cells that function under aerobic conditions, and since the cyanide ion diffuses easily to all parts of the body, it is capable of suddenly bringing to a halt practically all cellular respiration. A few inhalations of high concentrations of HCN may be followed by almost instantaneous collapse and cessation of respiration; 270 ppm HCN is immediately fatal to humans, 181 ppm is fatal after 10 minutes, 135 ppm after 30 minutes, and 110 ppm may be fatal in 1 hour. At lower levels of exposure to HCN, the earliest symptoms of intoxication may include weakness, headache, confusion, and occasionally nausea and vomiting; respiratory rate and depth usually increase initially and at later stages become slow and gasping; if cyanosis is present, it usually indicates that respiration has either ceased or has been very inadequate for a few minutes. Humans tolerate 45 to 54 ppm for ½ to 1 hour without immediate or delayed effects, while 18 to 36 ppm may result in some symptoms after an exposure of several hours. The ingestion by humans of 50 to 100 mg of HCN may also be fatal. Eye contact with liquid HCN may cause irritation. Cyanide is one of the few toxic substances for which an antidote exists, and it functions as follows. First, amyl nitrite (inhalation) and sodium nitrite (intravenously) are administered to form methemoglobin, which binds firmly with free cyanide ions. This traps any circulating cyanide ions. The formation of 10 to 20% methemoglobin usually does not involve appreciable risk, yet provides a large amount of cyanide-binding substance. Second, sodium thiosulfate is administered intravenously to increase the rate of conversion of cyanide to the less toxic thiocyanate. Methylene blue should not be administered, because it is a poor methemoglobin former and, moreover, promotes the conversion of methemoglobin back to hemoglobin.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 27
2. Boiling point (760 mm Hg): 26 C (79 F)
3. Specific gravity (water = 1): 0.7
4. Vapor density (air = 1 at boiling point of hydrogen cyanide): 0.93
5. Melting point: −14.4 to −16.8 C (7 to 2 F)
6. Vapor pressure at 20 C (68 F): 620 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Older samples may polymerize and explode unless acid stabilizer is maintained at proper concentration. Samples containing more than 2 – 5% of water are less stable than dry material. Samples stored more than 90 days are hazardous.
2. Incompatibilities: Contact with bases such as caustics and amines may cause violent polymerization and explosion.
3. Hazardous decomposition products: None more toxic than hydrogen cyanide.
4. Special precautions: Liquid hydrogen cyanide will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: −17.8 C (0 F) (closed cup)
2. Autoignition temperature: 538 C (1000 F)
3. Flammable limits in air, % by volume: Lower: 5.6; Upper: 40
4. Extinguishant: Dry chemical, carbon dioxide, alcohol foam

• **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that "the odor of HCN is usually described as 'sweet'; trained persons describe the odor as that of bitter almonds and can detect it at about one ppm." The Manufacturing Chemists Association (MCA) states that "although hydrocyanic acid has a characteristic odor, its toxic action at hazardous concentrations is so rapid that it is of no value as a warning."
2. Eye Irritation Level: Grant states that "only occasionally has reference been made to an irritation of the eye, conjunctivitis, or superficial keratitis developing after chronic exposure to hydrogen cyanide gas."
3. Evaluation of Warning Properties: For the purposes of this guideline, hydrogen cyanide has been treated as a material with poor warning properties. Although the odor threshold appears to be below the permissible exposure limit, Patty states that "the sense of smell is . . . easily fatigued; and there is wide individual variation in the minimum odor threshold."

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of hydrogen cyanide. Each measurement should consist of a ten (10) minute sample or series of consecutive samples totalling ten (10) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Hydrogen cyanide may be monitored by collection in midget impingers containing sodium hydroxide, followed by analysis with an ion specific electrode. An analytical method for hydrogen cyanide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid hydrogen cyanide.

• Where there is any possibility of exposure of an employee's body to liquid hydrogen cyanide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Any clothing which becomes wet with, or non-impervious clothing which becomes contaminated with, liquid hydrogen cyanide should be removed immediately and not reworn until the hydrogen cyanide is removed from the clothing.

• Clothing wet with hydrogen cyanide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of hydrogen cyanide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the hydrogen cyanide, the person performing the operation should be informed of hydrogen cyanide's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid hydrogen cyanide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to hydrogen cyanide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with hydrogen cyanide should be immediately washed or showered to remove any hydrogen cyanide.

• Employees who handle hydrogen cyanide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hydrogen cyanide may occur and control methods which may be effective in each case:

Operation	Controls
Use in fumigation of structures and agricultural crops	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during use of cyanide salts or solutions in metal treatment operations, blast furnace and coke oven operations, metal ore processing, and photoengraving operations	Process enclosure; local exhaust ventilation; personal protective equipment
Use in production of intermediates in synthesis of acrylic plastics, nylon 66, chelating agents, dyes, pharmaceuticals, and specialty chemicals	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid hydrogen cyanide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid hydrogen cyanide gets on the skin, immediately flush the contaminated skin with water. If liquid hydrogen cyanide soaks through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of hydrogen cyanide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When hydrogen cyanide has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If hydrogen cyanide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. If in the gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
4. If in liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to com pletely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. Hydrogen cyanide should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of hydrogen cyanide vapors are permitted.

• Waste disposal method:

Liquid hydrogen cyanide may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hydrogen Cyanide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hydrogen Cyanide," *Hygienic Guide Series*, Detroit, Michigan, 1970.

• Chen, K. K., and Rose, C. L.: "Nitrite and Thiosulfate Therapy in Cyanide Poisoning," *Journal of the American Medical Association*, 149:113-119, 1952.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hirsch, F.G.: "Cyanide Poisoning," Archives of Environmental Health, 8:622-624, 1964.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saunders, Philadelphia, 1960.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-67, Hydrogen Cyanide*, Washington, D.C., 1961.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Hydrogen Cyanide and Cyanide Salts*, HEW Publication No. (NIOSH) 77-108, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

727

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

• Wolfsie, J.H.: "Treatment of Cyanide Poisoning in Industry," A.M.A. Archives of Industrial Hygiene and Occupational Medicine, 4:417-425, 1951.

RESPIRATORY PROTECTION FOR HYDROGEN CYANIDE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
50 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 50 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against hydrogen cyanide. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of hydrogen cyanide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 50 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Hydrogen Fluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: HF
- Synonyms: Anhydrous hydrofluoric acid; HF-A
- Appearance and odor: Colorless, fuming liquid or gas with a strong irritating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hydrogen fluoride is 3 parts of hydrogen fluoride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2 milligrams of hydrogen fluoride per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be changed to 2.5 mg fluoride/m³ averaged over a work shift of not more than 10 hours per day, 40 hours per week, with a ceiling level of 5 mg fluoride/m³ averaged over a 15-minute period. The NIOSH Criteria Document for Hydrogen Fluoride should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hydrogen fluoride can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Hydrogen fluoride liquid or vapor causes severe irritation and deep-seated burns of the eye and eye lids if it comes in contact with the eyes. If the chemical is not removed immediately, permanent visual defects or blindness may result. When lower concentrations (20% or less) come into contact with the skin, the resulting burns do not usually become apparent for several hours. Skin contact with higher concentrations is usually apparent in a much shorter period, if not immediately. The skin burns may be very severe and painful. Hydrofluoric acid is a severe irritant to the nose, throat, and lungs. Severe exposure causes rapid inflammation and congestion of the lungs. Breathing difficulties may not occur until some hours after exposure has ceased. Death may occur from breathing this chemical. If swallowed, hydrofluoric acid will immediately cause severe damage to the throat and stomach.

2. Long-term Exposure: Prolonged or repeated exposure to lower concentrations of hydrogen fluoride vapor may cause changes in the bones. Exposure to low concentrations of vapors of hydrogen fluoride may also cause chronic irritation and congestion of the nose, throat, and bronchial tubes.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hydrogen fluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to hydrogen fluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory tract, central nervous system, skeletal system, and the kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney damage has been observed in acute overexposures to hydrogen fluoride, a urinalysis should be obtained to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centri-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

fuged sediment. An analysis for fluoride should be performed.

—Pelvic roentgenogram: Hydrogen fluoride may cause skeletal abnormalities. A radiologic examination of the male pelvis with proper gonadal shielding should be conducted at the time of the preplacement examination and when indicated by analysis of the results of the urinary hydrogen fluoride tests.

—Eye disease: Hydrogen fluoride is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

—14" x 17" chest roentgenogram: Hydrogen fluoride may cause human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Hydrogen fluoride is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Skin disease: Hydrogen fluoride can cause dermatitis on prolong exposure to concentrations from 1.8 to 8.1 mg/m³. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that the radiologic examination of the pelvis should be conducted only when clinically indicated.

• **Summary of toxicology**

Hydrogen fluoride as a gas is a severe respiratory irritant, and in solution causes severe and painful burns of the skin. Animals repeatedly exposed to 17 ppm showed damage to the lungs, liver, and kidneys, but at 8.6 ppm there was only occasional lung injury. Fatalities occurred in 3 of 6 workers exposed to spills of 70% solutions on the skin and inhalation of the vapor; despite prompt showering with water for skin burns, death from pulmonary edema occurred 2 hours after exposure. A chemist, splashed on the face and upper extremities with hydrogen fluoride, developed pulmonary edema 3 hours after exposure and died 10 hours later. In human subjects, 120 ppm was the highest concentration that could be tolerated for 1 minute, because of the onset of conjunctival and respiratory irritation with stinging of the skin. Repeated experimental human exposures to concentrations of 2 ppm for 6 hours daily caused a slight stinging of the eyes and skin of the face, with nasal irritation. Repeated exposures to low concentrations at work may produce chronic irritation of the nose, throat, and bronchi. Hydrogen fluoride solutions in contact with skin, if untreated, result in marked tissue destruction; the fluoride ion readily penetrates skin and deep tissue, causing necrosis of soft tissues and decalcification of bone. When skin contact is with solutions of less than 50% hydrogen fluoride, the burns do not become manifest immediately; burns from solutions stronger than 50% and anhydrous HF are felt in a matter of minutes, and because fluoride ions penetrate the skin readily, necrosis of deep tissue and damage to the bone may occur. Severe eye injuries from splashes may occur. In one case of eye burns from a fine spray of hydrofluoric acid in the face, considerable loss of corneal epithelium occurred despite immediate and copious flushing with water and irrigation for 3 hours with a 0.5% solution of benzethonium chloride; within 19 days there was recovery of normal vision.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 20
2. Boiling point (760 mm Hg): 19.5 C (67.1 F)
3. Specific gravity (water = 1): 1.0
4. Vapor density (air = 1 at boiling point of hydrogen fluoride): 0.7
5. Melting point: −83.4 C (−118 F)
6. Vapor pressure at 20 C (68 F): 760 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact of hydrogen fluoride (liquid or gas) with metals, concrete, glass, and ceramics causes severe corrosion. Contact with metals may form flammable hydrogen gas.
3. Hazardous decomposition products: None
4. Special precautions: Liquid or gaseous hydrogen fluoride will attack some forms of plastics, rubber, and coatings. It will also attack glass and other ceramic materials.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: The Manufacturing Chemists Association reports that the vapor has a sharp and penetrating odor, but no quantitative information is available concerning the odor threshold.
2. Eye Irritation Level: Grant states that "air containing as little as 5 ppm (hydrogen fluoride) causes irritation of the eyes."
3. Other Information: According to Grant, irritation of the nose occurs at a concentration as low as 5 ppm.
4. Evaluation of Warning Properties: Since hydrogen fluoride can be detected through its irritant effects at a concentration slightly above the permissible exposure limit, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30

minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Ceiling Evaluation

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of hydrogen fluoride. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Method

Sampling and analyses may be performed by collection of hydrogen fluoride in a bubbler, followed by dilution with a buffer, and analysis with an ion-specific electrode. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure hydrogen fluoride may be used. An analytical method for hydrogen fluoride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid hydrogen fluoride or solutions containing hydrogen fluoride.

• Clothing contaminated with hydrogen fluoride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of hydrogen fluoride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the hydrogen fluoride, the person performing the operation should be informed of hydrogen fluoride's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid hydrogen fluoride or solutions containing hydrogen fluoride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with hydrogen fluoride should be removed immediately and not reworn until the hydrogen fluoride is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid hydrogen fluoride or solutions containing hydrogen fluoride contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid hydrogen fluoride or solutions containing hydrogen fluoride, an eye-wash fountain should be provided within the immediate work area for emergency use.

• Whenever hydrogen fluoride is accidentally released into the workplace air, employees should be required to immediately evacuate the area.

SANITATION

• Skin that becomes contaminated with hydrogen fluoride should be immediately washed or showered to remove any hydrogen fluoride.

• Eating and smoking should not be permitted in areas where liquid hydrogen fluoride or solutions containing hydrogen fluoride are handled, processed, or stored.

• Employees who handle liquid hydrogen fluoride or solutions containing hydrogen fluoride should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hydrogen fluoride may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of chlorofluorohydrocarbons for application as refrigerant fluids, aerosol propellants, specialty solvents, high-performance plastics, and foaming agents	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of aqueous acid in cleaning sandstone and marble; use as a pickling agent for stainless steel and other metals; use as a cleaner in meat packing industry	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of anhydrous acid in manufacture of aluminum fluoride and synthetic cryolite for reduction of aluminum oxide to aluminum	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of aqueous acid in electroplating operations	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberation from fertilizer manufacture	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of anhydrous acid as a catalyst in alkylation of petroleum fractions to produce high-octane fuels	Process enclosure; local exhaust ventilation; personal protective equipment
Use of aqueous acid in etching, frosting, and polishing glassware and ceramics	Process enclosure; local exhaust ventilation; personal protective equipment
Use as an acidizing agent during injection of acid into oil wells	Process enclosure; local exhaust ventilation; personal protective equipment
Use of aqueous acid in removal of sand and scale from foundry castings	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of anhydrous acid in separation and purification of uranium isotopes	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of insecticides; use of aqueous acid in treating textiles to remove trace metals	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of anhydrous acid in production of fluorosilicone products	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of aqueous acid in preparation of microelectronic circuits and quartz crystals for radio oscillators	Process enclosure; local exhaust ventilation; personal protective equipment
Use of aqueous acid in manufacture of laundry sours and stain removers	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of aqueous acid in extraction and purification of minerals	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of anhydrous acid in manufacture of pharmaceuticals and special dyes	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid hydrogen fluoride or solutions containing hydrogen fluoride get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid hydrogen fluoride or solutions containing hydrogen fluoride get on the skin, immediately flush the contaminated skin with water for a considerable time. If liquid hydrogen fluoride or solutions containing hydrogen fluoride penetrate through the clothing, remove the clothing immediately and flush the skin with water for a considerable time. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of hydrogen fluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If liquid hydrogen fluoride or solutions containing hydrogen fluoride have been swallowed and the person is conscious, give him large quantities of water immediately to dilute the hydrogen fluoride. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If hydrogen fluoride is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak to disperse gas.
2. If in the gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
3. If in the liquid form, allow to vaporize and disperse the gas.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hydrogen Fluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hydrogen Fluoride," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Burke, W. J., et al.: "Systemic Fluoride Poisoning Resulting from a Fluoride Skin Burn," *Journal of Occupational Medicine*, 15:39-41, 1973.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dibbell, D. G., et al.: "Hydrofluoric Acid Burns of the Hand," *Journal of Bone and Joint Surgery*, 52A:931-936, 1970.

• Fleming, A. J., et al.: *Modern Occupational Medicine* (2d ed. rev.), Lea and Febiger, Philadelphia, 1960.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saunders, Philadelphia, 1960.

• Kleinfeld, M.: "Acute Pulmonary Edema of Chemical Origin," *Archives of Environmental Health*, 10:942-946, 1965.

• Largent, E. J.: "The Metabolism of Fluorides in Man," *A.M.A. Archives of Industrial Health*, 21:318-323, 1960.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-25, Hydrogen Fluoride*, Washington, D.C., 1970.

• Mayer, L., and Guelich, J.: "Hydrogen Fluoride (HF) Inhalation and Burns," *Archives of Environmental Health*, 7:445-447, 1963.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Hydrogen Fluoride*, HEW Publication No. (NIOSH) 76-143, GPO No. 017-033-00171-5, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Reinhardt, C. F., et al.: "Hydrofluoric Acid Burn Treatment," *American Industrial Hygiene Association Journal*, 27:166-171, 1966.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR HYDROGEN FLUORIDE

Condition	Minimum Respiratory Protection* Required Above 3 ppm
Gas or Vapor Concentration	
20 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) providing protection against hydrogen fluoride. A gas mask with a chin-style or a front- or back-mounted canister and filter providing protection against hydrogen fluoride. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 20 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against hydrogen fluoride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of hydrogen fluoride; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 20 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Hydrogen Peroxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: H_2O_2
- Synonyms: High-strength hydrogen peroxide; peroxide; hydrogen dioxide
- Appearance and odor: Colorless liquid with a slightly sharp odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hydrogen peroxide is 1 part of hydrogen peroxide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1.4 milligrams of hydrogen peroxide per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hydrogen peroxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to vapor from hydrogen peroxide may cause extreme irritation of the eyes, nose, and throat. Splashes of hydrogen peroxide in the eyes may cause severe damage and possible blindness. Eye damage may appear a week or more after exposure. If the liquid is splashed on the skin, it may cause tingling and temporary whitening. If the skin is washed promptly, the skin will return to normal in 2 or 3 hours. If the hydrogen peroxide is not removed, redness and blister formation may result. If swallowed, hydrogen peroxide may cause injury to the mouth and throat with possible bleeding from the esophagus and stomach. The swallowed hydrogen peroxide may produce large quantities of oxygen gas which may distend the esophagus and stomach and cause severe damage.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hydrogen peroxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to hydrogen peroxide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from hydrogen peroxide exposure.

—Eye disease: Hydrogen peroxide, 90 percent, is an eye irritant. Persons with pre-existing eye disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: Hydrogen peroxide, 90 percent, causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of hydrogen peroxide, 90 percent, might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Hydrogen peroxide, 90 percent, is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ninety percent hydrogen peroxide vapor, mist, or liquid irritates the eyes, mucous membranes, and skin. Repeated exposure of dogs to 7 ppm for 6 months caused sneezing, lacrimation, and bleaching of hair; at autopsy there was local atelectasis. In humans, inhalation of high concentrations of vapor or mist may cause extreme irritation and inflammation of the nose and

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

throat. Exposure for a short period to mist or diffused spray may cause stinging of the eyes and lacrimation. Splashes of the liquid in the eyes may cause severe damage, including ulceration of the cornea; there may be a delayed appearance of damage to the eyes, and corneal ulceration has, on rare occasions, appeared even a week or more after exposure. Skin contact with the liquid for a short time will cause a temporary whitening or bleaching of the skin; if splashes on the skin are not removed, erythema and formation of vesicles may occur. Ingestion may cause irritation of the upper gastrointestinal tract; decomposition of the hydrogen peroxide will result in the rapid liberation of oxygen, which may distend and damage the esophagus or stomach.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 34
2. Boiling point (760 mm Hg): 141 C (286 F) (calculated)
3. Specific gravity (water = 1): 1.38
4. Vapor density (air = 1 at boiling point of hydrogen peroxide): Not applicable (decomposes)
5. Melting point: −11 C (12 F)
6. Vapor pressure at 30 C (86 F): 5 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Hydrogen peroxide decomposes slowly at ordinary temperatures and builds up pressure if the container is closed. The rate of decomposition doubles for each 10 C rise (1.5 times 10 C rise) in temperature and becomes self-sustaining at 141 C (285 F). Contaminated hydrogen peroxide can decompose at a rate that will exceed the capacity of the vent in the container. Hydrogen peroxide in concentrations up to about 90% does not readily detonate. Higher concentrations or elevated temperatures may facilitate detonation.
2. Incompatibilities: Contact with most organic or readily oxidizable materials and combustibles causes fires and explosions. Contact with iron, copper, brass, bronze, chromium, zinc, lead, manganese, silver, and other catalytic metals (or their salts) causes rapid decomposition with evolution of oxygen gas and heat which may increase container pressure.
3. Hazardous decomposition products: None
4. Special precautions: Liquid hydrogen peroxide will attack some forms of plastics, rubber, and coatings; many will ignite. The adiabatic decomposition temperature is 740 C (1364 F), so that most combustible materials in contact with the decomposition products will readily burst into flames.

• **Flammability**

1. Not combustible, but a powerful oxidizing agent

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of hydrogen peroxide.
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "the eyes do not appear to be damaged from exposure to the vapor." Grant reports, "Injuries of human eyes have been rare. Workers exposed to vapors from 90% hydrogen peroxide have noted primarily respiratory irritation, but a splash of such high concentration is generally feared as a potential cause of severe corneal damage . . . .

'Experimental exposure of dogs to 7 ppm hydrogen peroxide in air 6 hours a day caused no adverse effect during 23 weeks but then began to cause sneezing and lacrimation. Rabbits similarly exposed for 10 weeks suffered no corneal damage."

Deichmann and Gerarde, however, note that "vapors are irritating to the eyes, nose and throat."

According to the *Hygienic Guide*, hydrogen peroxide can be "recognized only by irritant effects, especially in nasal passages." They give an irritation threshold of approximately 100 ppm.

3. Evaluation of Warning Properties: Hydrogen peroxide has poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for hydrogen peroxide had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforce-

ment and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid hydrogen peroxide.

• Clothing contaminated with hydrogen peroxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of hydrogen peroxide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the hydrogen peroxide, the person performing the operation should be informed of hydrogen peroxide's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid hydrogen peroxide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with hydrogen peroxide should be removed immediately and not reworn until the hydrogen peroxide is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid hydrogen peroxide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid hydrogen peroxide, an eyewash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with hydrogen peroxide should be promptly washed or showered to remove any hydrogen peroxide.

• Employees who handle liquid hydrogen peroxide should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hydrogen peroxide may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of propellants for military and space programs; use as a component of explosives	Process enclosure; general dilution ventilation; personal protective equipment; vented containers; ample available water supply
Use in chemical synthesis as an oxidant in organic and inorganic synthesis	Process enclosure; general dilution ventilation; personal protective equipment vented containers; ample available water supply
Use as a polymerization promoter; use as a bleaching agent for oils, waxes, fats, and discolored concentrated acids	Process enclosure; general dilution ventilation; personal protective equipment vented containers; ample available water supply

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid hydrogen peroxide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid hydrogen peroxide gets on the skin, immediately flush the contaminated skin with water. If liquid hydrogen peroxide soaks through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of hydrogen peroxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When hydrogen peroxide has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency

rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If hydrogen peroxide is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Dilute with copious quantities of water.

- Waste disposal method:

After dilution with copious quantities of water, hydrogen peroxide may be flushed into a sewer.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Hydrogen Peroxide (90%)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- American Industrial Hygiene Association: "Hydrogen Peroxide (90%)," *Hygienic Guide Series*, Detroit, Michigan, 1957.
- Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-53, Hydrogen Peroxide*, Washington, D.C., 1969.
- Oberst, F. W., et al.: "Inhalation Toxicity of Ninety Per Cent Hydrogen Peroxide Vapor - Acute, Subacute, and Chronic Exposures of Laboratory Animals," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 10:319-327, 1954.
- Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

RESPIRATORY PROTECTION FOR HYDROGEN PEROXIDE (90%)

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
10 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
75 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 75 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-oxidizable sorbents and providing protection against hydrogen peroxide. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of hydrogen peroxide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 75 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Hydrogen Selenide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: H_2Se
- Synonyms: Selenium hydride
- Appearance and odor: Colorless gas with a very offensive odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hydrogen selenide is 0.05 part of hydrogen selenide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.2 milligram of hydrogen selenide per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hydrogen selenide can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

Exposure to hydrogen selenide may cause irritation of the eyes, nose, throat, and lungs, nausea, vomiting, and diarrhea. Subsequently, there may be a metallic taste in the mouth, garlic odor of the breath, dizziness, and extreme tiredness. Hydrogen selenide has been known to cause pneumonia and liver damage in animals.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hydrogen selenide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to hydrogen selenide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from hydrogen selenide exposure.

—Chronic respiratory disease: Hydrogen selenide causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of hydrogen selenide might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Hydrogen selenide causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Hydrogen selenide gas irritates the eyes, nose, and throat and causes pulmonary irritation in animals. Guinea pigs exposed to 10 ppm for 2 hours exhibited immediate irritation of the eyes and nose; a high percentage of the animals died, apparently from pneumonitis. Exposure of guinea pigs to 1 mg/m^3 (0.3 ppm) for 8 hours produced death in half of the animals; pulmonary irritation and liver damage were observed. In humans, a concentration of 1.5 ppm is said to produce intolerable irritation of the eyes and nose. Five workers exposed to concentrations of less than 0.2 ppm of hydrogen selenide and possibly other selenium compounds for 1 month developed nausea, vomiting, diarrhea, metallic taste in the mouth, garlic odor of the breath, dizziness, lassitude, and fatigability; following cessation of exposure, there was a gradual regression of symptoms during the succeeding months. Urinary selenium levels of the workers

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

ranged from 0 to 13.1 mg Se/100 cc urine; there was no correlation between symptoms and levels of urinary excretion.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 81
2. Boiling point (760 mm Hg): −41.3 C (−42 F)
3. Specific gravity (water = 1): Liquid = 2.1 at boiling point
4. Vapor density (air = 1 at boiling point of hydrogen selenide): 2.8
5. Melting point: −65.7 C (−86.5 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): 0.73
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with oxidizers, acids, water, and halogenated hydrocarbons may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as selenium dioxide fume) may be released in a fire involving hydrogen selenide.
4. Special precautions: None

- **Flammability**

1. Flash point: Not applicable (gas)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Shut off flow of gas; carbon dioxide

- **Warning properties**

1. Odor Threshold: May and Summer report odor thresholds for hydrogen selenide of 0.3 ppm and 3 ppm, respectively.
2. Irritation Level: Grant states that "a concentration of 1.5 ppm in air is said to produce intolerable irritation of the eyes and nose which tends to limit exposure and safeguard against injury. However, below 1 ppm the ocular and respiratory warning properties are insufficient to prevent exposure which may cause systemic intoxication." Dudley and Miller state that at 0.001 mg/l (0.3 ppm) "no eye or nasal irritation is produced in man."
3. Evaluation of Warning Properties: Since the odor and irritation thresholds of hydrogen selenide are not within three times the permissible exposure limit, hydrogen selenide is treated as a material with poor warning properties. In addition, the AIHA *Hygienic Guide* states that "the odor perception of it (hydrogen selenide) is soon lost."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for hydrogen selenide had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hydrogen selenide may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of semi-conductor materials; use in chemical synthesis for metal selenides and organoselenium, lasers, and emulsions	Process enclosure; local exhaust ventilation; personal protective equipment

Liberation from roasting of metal ores and pyrites, production of glass and ceramics, vulcanization of rubber, and etching with inks	Local exhaust ventilation; personal protective equipment
Liberation from overloaded selenium rectifiers	Local exhaust ventilation; personal protective equipment
Liberation from bacterial action of selenium-contaminated clothing	Good personal hygiene practice

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of hydrogen selenide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If hydrogen selenide is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak to disperse gas.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

• Waste disposal method:

Hydrogen selenide may be disposed of by burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hydrogen Selenide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hydrogen Selenide," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Buchan, R. F.: "Industrial Selenosis," *Occupational Medicine*, 3:439-456, 1947.

• Dudley, H. C., and Miller, J. W.: "Toxicology of Selenium: VI. Effects of Subacute Exposure to Hydrogen Selenide," *Journal of Industrial Hygiene and Toxicology*, 23:470-477, December 1941.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

RESPIRATORY PROTECTION FOR HYDROGEN SELENIDE

Condition	Minimum Respiratory Protection* Required Above 0.05 ppm
Gas Concentration	
0.5 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
2 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against hydrogen selenide. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Hydrogen Sulfide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: H_2S
- Synonyms: Sulfuretted hydrogen; hydrosulfuric acid; hepatic gas
- Appearance and odor: Colorless gas with a strong odor of rotten eggs. The odor of this gas should not be used as a warning, since its presence may deaden the sense of smell. Hydrogen sulfide can also exist as a liquid at low temperature and high pressure.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for hydrogen sulfide is a ceiling level of 20 parts of hydrogen sulfide per million parts of air (ppm) or a maximum allowable peak of 50 ppm for 10 minutes once, if no other measurable exposure occurs. NIOSH has recommended that the permissible exposure limit be reduced to 15 mg/m³ (10 ppm) averaged over a 10-minute period, and that work areas in which the concentration of hydrogen sulfide exceeds 70 mg/m³ be evacuated. The NIOSH Criteria Document for Hydrogen Sulfide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Hydrogen sulfide can affect the body if it is inhaled or if it comes in contact with the eyes, skin, nose or throat. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation of high concentrations of hydrogen sulfide vapor may cause loss of consciousness and death. Inhalation of lower concentrations may cause headache, dizziness, and upset stomach. Exposure to hydrogen sulfide can cause temporary loss of the sense of smell, and irritation of the eyes, nose, or throat.

2. Long-term Exposure: Not known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to hydrogen sulfide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to hydrogen sulfide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes and lungs should be stressed.

—Eye disease: Hydrogen sulfide is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

—14" x 17" chest roentgenogram: Hydrogen sulfide may cause human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Hydrogen sulfide is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

7:1

• **Summary of toxicology**

Hydrogen sulfide gas is a rapidly acting systemic poison which causes respiratory paralysis with consequent asphyxia at high concentrations. It irritates the eyes and respiratory tract at low concentrations. Inhalation of high concentrations of hydrogen sulfide, 1000 to 2000 ppm, may cause coma after a single breath and may be rapidly fatal; convulsions may also occur. Exposure to concentrations of hydrogen sulfide above 50 ppm for one hour may produce acute conjunctivitis with pain, lacrimation, and photophobia; in severe form this may progress to keratoconjunctivitis and vesiculation of the corneal epithelium. In low concentrations, hydrogen sulfide may cause headache, fatigue, irritability, insomnia, and gastrointestinal disturbances; in somewhat higher concentrations it affects the central nervous system, causing excitement and dizziness. Prolonged exposure to 250 ppm of hydrogen sulfide may cause pulmonary edema. Prolonged exposure to concentrations of hydrogen sulfide as low as 50 ppm may cause rhinitis, pharyngitis, bronchitis, and pneumonitis. Repeated exposure to hydrogen sulfide results in increased susceptibility, so that eye irritation, cough, and systemic effects may result from concentrations previously tolerated without any effect. Rapid olfactory fatigue can occur at high concentrations.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 34.08
2. Boiling point (760 mm Hg): −60 C (−76 F)
3. Specific gravity (water = 1): Liquid = 1.54
4. Vapor density (air = 1 at 15 C (59 F)): 1.189
5. Melting point: −82.4 C (−116 F)
6. Vapor pressure at 25 C (77 F): 20 atm
7. Solubility in water, g/100 g water at 20 C (68 F): 2.9 (slight)
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause containers to burst.
2. Incompatibilities: Contact with strong oxidizers and oxidizing materials may cause fires and explosions. Hydrogen sulfide attacks many metals, which results in the formation of sulfides.
3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur oxides) may be released in a fire involving hydrogen sulfide.
4. Special precautions: Liquid hydrogen sulfide will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Hydrogen sulfide is a flammable gas.
2. Autoignition temperature: 260 C (500 F)
3. Flammable limits in air, % by volume: Lower: 4.3; Upper: 46
4. Extinguishant: Alcohol foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: According to the AIHA *Hygienic Guide*, hydrogen sulfide can be recognized by the "sense of smell at low concentrations. Odor not reliable at high concentrations, and olfactory fatigue occurs quickly . . . . Threshold is 0.13 ppm. Faint but readily perceptible at 0.77 ppm. Easily noticeable at 4.6 ppm. Strong, unpleasant, but not intolerable at 27 ppm." The *Hygienic Guide* also states that "olfactory fatigue can occur with(in) 2 to 15 minutes at 100 ppm."

2. Eye Irritation Level: Grant states that "effects of hydrogen sulfide on the eyes are notable only at sublethal concentrations, most commonly at concentrations so low that they have no discernible systemic effect . . . . Typically, workmen exposed to low concentrations of hydrogen sulfide gas . . . have no sensation of irritation or discomfort for at least several hours, or sometimes for several days while working in the presence of low concentrations. Ocular symptoms generally start after several hours of exposure and may not appear until the patient has finished his work for the day. There is then gradual onset of a scratchy, irritated sensation in the eyes, with tearing and burning . . . . Experimentally it is demonstrable that at a concentration of 100 ppm in air an immediate irritation of the eyes and respiratory tract is produced, but conditions responsible for the vast majority of cases of hydrogen sulfide keratoconjunctivitis are those in which the concentration is too low to cause immediate irritation and has toxic effect only after several hours or days of exposure. However, in industries where the concentration is regularly kept below 10 ppm in air, it is rare to have any irritation of the eyes."

The *Hygienic Guide* states that "50 to 100 ppm causes slight conjunctivitis and respiratory tract irritation after 1 hour."

3. Evaluation of Warning Properties: Since olfactory fatigue occurs at high concentrations, and since the irritant effects are delayed, hydrogen sulfide is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of hydrogen sulfide. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15)

minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Peak Above Ceiling Evaluation

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of hydrogen sulfide. Each measurement should consist of a 10-minute sample or a series of consecutive samples totalling 10 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Method

Sampling and analyses may be performed by collection of hydrogen sulfide in an impinger containing an alkaline suspension of cadmium hydroxide, followed by chemical treatment, and spectrophotometric analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure hydrogen sulfide may be used. An analytical method for hydrogen sulfide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid hydrogen sulfide or from contact with vessels containing liquid hydrogen sulfide.

• Any clothing which becomes wet with liquid hydrogen sulfide should be removed immediately and not reworn until the hydrogen sulfide has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid hydrogen sulfide may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to hydrogen sulfide may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from pockets during underground mining operations near sulfide ores	Local exhaust ventilation; respiratory protective devices
Liberation during refining of high-sulfur petroleum	Concentration and recovery of H_2SO_4
Liberation from accumulations of decaying organic matter in sewers and waste waters of tanneries, glue factories, fat-rendering plants, and fertilizer plants	Provide continuous water discharge to sewer and cover and vent waste drains
Liberation as a by-product of dehairing and tanning process	Provide separate sewage lines and cover and vent waste drains; add neutralizing agents ($CaCl_2$) as appropriate; local exhaust ventilation
Liberation during manufacture of viscose rayon	Local exhaust ventilation
Liberation during production of sulfur dyes, carbon disulfide, sulfur, oleum, and thioprene	Local exhaust ventilation or process enclosure
Liberation during vulcanization of rubber; during manufacture of coke from coal having high gypsum content	Local exhaust ventilation or process enclosure
Liberation during excavation projects	Respiratory protective equipment

Liberation in closed containers containing organic matter	Respiratory protective equipment; life-support line

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid hydrogen sulfide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid hydrogen sulfide gets on the skin, immediately flush the contaminated skin with water. If liquid hydrogen sulfide penetrates through the clothing, remove the clothing immediately and flush the skin with water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of hydrogen sulfide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If hydrogen sulfide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak to disperse gas.
3. If in the gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
4. If in the liquid form, allow to vaporize.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Hydrogen Sulfide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hydrogen Sulfide," *Hygienic Guide Series*, Detroit, Michigan, 1962.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• *Hygienic Information Guide No. 20 – Hydrogen Sulfide*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-36, Hydrogen Sulfide*, Washington, D.C., 1968.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-71, Phosphorus Pentasulfide*, Washington, D.C., 1958.

• Milby, T. H.: "Hydrogen Sulfide Intoxication – Review of the Literature and Report of Unusual Accident Resulting in Two Cases of Nonfatal Poisoning," *Journal of Occupational Medicine*, 4:431-437, 1962.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Hydrogen Sulfide*, HEW Publication No. (NIOSH) 77-158, GPO No. 017-033-00217-7, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR HYDROGEN SULFIDE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Gas Concentration	
300 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 300 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against acid gases or hydrogen sulfide. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Iodine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: I_2
- Synonyms: None
- Appearance and odor: Violet solid with a sharp, characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for iodine is a ceiling level of 0.1 part of iodine per million parts of air (ppm). This may also be expressed as 1 milligram of iodine per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Iodine can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Iodine vapor is a severe irritant of the eyes, respiratory tract, and to a lesser extent, the skin. It may cause severe breathing difficulties which may be delayed in onset. Swallowing iodine may cause burning in the mouth, vomiting, abdominal pain, and diarrhea. Death may result. Crystalline iodine or strong solutions of iodine may cause severe irritation of the skin. It is not easily removed from the skin and may cause burns. An allergic skin rash may occur. It may cause irritation, brown staining, and burning of the eyes.

2. Long-term Exposure: Chronic absorption of iodine may cause insomnia, inflammation of the eyes and nose, bronchitis, tremor, rapid heart beat, diarrhea, and weight loss.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to iodine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to iodine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of thyroid disorders, asthma, allergies, or known sensitization to iodine would be expected to be at increased risk from exposure. Examination of the respiratory tract, eyes, nervous system, and cardiovascular system should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Iodine causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Iodine is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when signs and symptoms of respiratory disease occur.

- **Summary of toxicology**

Iodine vapor is a severe irritant of the eyes, respiratory tract, and, to a lesser extent, the skin. Intratracheal administration to dogs of the vapor from 36 mg iodine/kg body weight was fatal after about 3 hours; the animals developed cough, dyspnea, and rales; autopsy findings were pulmonary edema, subpleural hemorrhage, and an increased iodine content of the thyroid

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

and urine. Workers exposed to an unspecified concentration experienced a burning sensation in the eyes, lacrimation, blepharitis, rhinitis, stomatitis, and chronic pharyngitis; after accidental exposure in a laboratory, technicians reported headache and a feeling of tightness in the chest. Iodine absorbed by the lungs is changed to iodide and eliminated mainly in the urine; iodine is an essential element in nutrition and is required by the thyroid. Accidental ingestion of 2 to 3 g may be fatal; chronic absorption of iodine causes "iodism," a disease characterized by insomnia, conjunctivitis, rhinitis, bronchitis, tremor, tachycardia, parotitis, diarrhea, and weight loss. In an experimental investigation, four human subjects tolerated 0.57 ppm iodine vapor for 5 minutes without eye irritation, but all experienced eye irritation in 2 minutes at 1.63 ppm. In patients exposed to air saturated with iodine vapor for 3 to 4 minutes for therapeutic purposes, there was brown staining of the corneal epithelium and subsequent spontaneous loss of the layer of tissue; recovery occurred within 2 to 3 days. Iodine in crystalline form or in strong solutions is a severe skin irritant; it is not easily removed from the skin, and the lesions resemble thermal burns. Hypersensitivity to iodine characterized by a skin rash has been reported. Iodine is absorbed through the skin in small amounts from a tincture or from vapor applied to the skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 253.8
  2. Boiling point (760 mm Hg): 184 C (363 F)
  3. Specific gravity (water = 1): 4.9
  4. Vapor density (air = 1 at boiling point of iodine): 9
  5. Melting point: 113.6 C (237 F)
  6. Vapor pressure at 20 C (68 F): 0.3 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.03
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None hazardous
  2. Incompatibilities: Contact of iodine with gaseous or aqueous ammonia forms a water-insoluble solid that is very sensitive to shock when dry and which will explode, causing fires. Contact with acetylene, acetaldehyde, powdered aluminum, or other active metals may cause fires and explosions.
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible by itself, but can react vigorously with reducing materials
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold of iodine.
  2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "irritation rather than systemic action limits the concentrations of iodine vapor which can be tolerated. An earlier report states that 0.1 ppm is tolerable, whereas 0.3 ppm is not, but no time limits were furnished in the citation. In a recent investigation, four human subjects tolerated 0.57 ppm iodine vapor for 5 minutes without eye irritation, but all experienced eye irritation in 2 minutes at 1.63 ppm." The eye irritation threshold data reported are not consistent.
  3. Evaluation of Warning Properties: Since the *Hygienic Guide* states that "the warning properties of iodine vapor are not adequate to prevent excessive inhalation exposure," iodine has been treated as a material with poor warning properties. The ILO also notes that the warning properties of iodine vapor cannot be depended upon to prevent excessive exposure. In addition, a recent investigation has shown that a 5-minute exposure to 0.57 ppm iodine vapor did not produce eye irritation in human subjects.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of iodine. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

At the time of publication of this guideline, no measurement method for iodine had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which

includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solid iodine or liquids containing more than 7% iodine by weight.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquids containing 7% or less of iodine by weight.
- If employees' clothing has had any possibility of being contaminated with solid iodine, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with iodine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of iodine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the iodine, the person performing the operation should be informed of iodine's hazardous properties.
- Where there is any possibility of exposure of an employee's body to solid iodine or liquids containing more than 7% iodine by weight, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with iodine should be removed immediately and not reworn until the iodine is removed from the clothing.
- Non-impervious clothing which becomes wet with liquids containing 7% or less of iodine by weight should be removed promptly and not reworn until the iodine is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid iodine or liquids containing more than 7% iodine by weight contacting the eyes.
- Employees should be provided with and required to use splash-proof safety goggles where liquids containing 7% or less of iodine by weight may contact the eyes.
- Where there is any possibility that employees' eyes may be exposed to solid iodine or liquids containing more than 7% iodine by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with solid iodine or liquids containing more than 7% iodine by weight should be immediately washed or showered with soap or mild detergent and water to remove any iodine.
- Skin that becomes wet with solutions containing 7% or less of iodine by weight should be promptly washed or showered with soap or mild detergent and water to remove any iodine.
- Eating and smoking should not be permitted in areas where solid iodine is handled, processed, or stored.
- Employees who handle solid iodine or liquids containing iodine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to iodine may occur and control methods which may be effective in each case:

Operation	Controls
Use in synthesis of chemical intermediates, pharmaceuticals, photographic chemicals, antiseptics, disinfectants, detergent sanitizers, and organic and inorganic compounds	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a reagent in analytical chemistry; as catalytst in organic synthesis; synthesis of dyes, food additives, and coloring agents	Process enclosure; local exhaust ventilation; personal protective equipment
Use in production of intermediates in purification of metals; use as a catalyst in the modification of selenium during manufacture of photoelectric cells and rectifiers	Process enclosure; local exhaust ventilation; personal protective equipment
Use during manufacture of specialty lubricants and in production of steriospecific polymers	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If iodine, liquids containing iodine, or strong concentrations of iodine vapor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If iodine or liquids containing iodine get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If iodine or liquids containing iodine penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation or burns are present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of iodine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When iodine or liquids containing iodine have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately. (If milk is immediately available, give the person milk instead of water).

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If iodine is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing iodine should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Iodine may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Iodine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Iodine," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Dow Chemical Company: *Material Safety Data Sheet - Iodine*, Midland, Michigan, 1972.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 55 - Iodine*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Luckhardt, A. B., et al.: "The Physiological Action of the Fumes of Iodine," *Journal of Pharmacology and Experimental Therapeutics*, 15:1-21, 1920.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Seymour, W. B., Jr.: "Poisoning from Cutaneous Application of Iodine, A Rare Aspect of Its Toxicologic Properties," *Archives of Internal Medicine*, 59:952-966, 1937.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR IODINE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Vapor or Particulate Concentration	
1 ppm or 10 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5 ppm or 50 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 ppm or 100 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10 ppm or 100 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors, acid gases, and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Iron Oxide Fume

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Fe_2O_3
- Synonyms: Ferric oxide fume
- Appearance: Red-brown fume with a metallic taste

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for iron oxide fume is 10 milligrams of iron oxide fume per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for iron oxide fume a Threshold Limit Value of 5 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Iron oxide fume can affect the body if it is inhaled.

- **Effects of overexposure**

Repeated exposure to iron oxide fume over a period of years may cause x-ray changes of the lungs, but does not cause the exposed person to become ill.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to iron oxide fume.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to iron oxide fume at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed.

—14" x 17" chest roentgenogram: Iron oxide fume causes an apparently benign pneumoconiosis. However, since exposure may be associated with other more toxic dust exposures, surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Iron oxide fume causes an apparently benign pneumoconiosis. However, since exposure may be associated with other more toxic dust exposures, periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

Inhalation of iron oxide fume or dust causes an apparently benign pneumoconiosis termed siderosis. Iron oxide alone does not cause fibrosis in the lungs of animals, and the same probably applies to humans. Exposures of 6 to 10 years are usually considered necessary before changes recognizable by x-ray can occur; the retained dust gives x-ray shadows that may be indistinguishable from fibrotic pneumoconiosis. Eight of 25 welders exposed chiefly to iron oxide for an average of 18.7 (range 3 to 32) years had reticulonodular shadows on chest x-rays consistent with siderosis but no reduction in pulmonary function; exposure levels ranged from 0.65 to 47 mg/m^3. In another study, 16 welders with an average exposure of 17.1 (range 7 to 30) years also had x-rays suggesting siderosis and spirograms which were normal; however, the static and functional compliance of the lungs was reduced; some of the welders were smokers. The welders with the lowest compliance complained of dyspnea.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 159.7
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): Solid = 5.24
  4. Vapor density (air = 1 at boiling point of iron oxide fume): Not applicable
  5. Melting point: 1566 C (2850 F) (decomposes)
  6. Vapor pressure at 20 C (68 F): Zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact of iron oxide fume with calcium hypochlorite may cause explosions.
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Iron oxide fume is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of iron oxide fume on a filter, followed by atomic absorption spectrophotometric analysis. An analytical method for iron oxide fume is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to iron oxide fume may occur and control methods which may be effective in each case:

Operation	Controls
Liberation in production of steel ingots; processing of iron ore to pig iron; heating and pouring of molten metal in foundry operations; hot rolling sheet and strip steel; fettling of castings in foundry operations; during forging of metal items containing iron/steel; pressing of metal items, grinding and polishing of glass, precious metals, stones, and gem stones	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Breathing**

If a person breathes in large amounts of iron oxide fume, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.
- If potentially hazardous amounts of iron oxide fume are inadvertantly released, ventilate the area of the release to disperse the fume.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Iron Oxide Fume," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Harding, H. E., et al.: "Clinical, Radiographic, and Pathological Studies of the Lungs of Electric-Arc and Oxyacetylene Welders," *Lancet*, 2:394-398, 1958.
- Jones, J. G., and Warner, C. G.: "Chronic Exposure to Iron Oxide, Chromium Oxide, and Nickel Oxide Fumes of Metal Dressers in a Steelworks," *British Journal of Industrial Medicine*, 29:169-177, 1972.
- Kleinfeld, M., et al.: "Welders' Siderosis," *Archives of Environmental Health*, 19:70-73, 1969.
- Levy, S. A., and Margolis, I.: "Siderosilicosis and Atypical Epithelial Hyperplasia," *Journal of Occupational Medicine*, 16:796-799, 1974.
- McLaughlin, A. I. G.: "Siderosis," *British Journal of Tuberculosis and Diseases of the Chest*, 45:105-114, 1951.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sentz, F. C., Jr., and Rakow, A. B.: "Exposure to Iron Oxide Fume at Arcair and Powder-Burning Operations," *American Industrial Hygiene Association Journal*, 30:143-146, 1969.
- Stanescu, D. C., et al.: "Aspects of Pulmonary Mechanics in Arc Welders' Siderosis," *British Journal of Industrial Medicine*, 24:143-147, 1967.

RESPIRATORY PROTECTION FOR IRON OXIDE FUME

Condition	Minimum Respiratory Protection* Required Above 10 mg/m³
Particulate Concentration	
100 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
500 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5,000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5,000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Isoamyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOCH_2CH_2CH(CH_3)_2$
- Synonyms: Banana oil; 3-methyl-1-butanol acetate; 2-methylbutyl ethanoate
- Appearance and odor: Clear, colorless liquid with a banana-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for isoamyl acetate is 100 parts of isoamyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 525 milligrams of isoamyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Isoamyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- ***Effects of overexposure***

1. Short-term Exposure: Overexposure to isoamyl acetate may cause irritation of the eyes, nose, and throat. Overexposure may also cause headache, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to isoamyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to isoamyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from isoamyl acetate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isoamyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Isoamyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although isoamyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although isoamyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The toxicologic effects of isoamyl acetate are probably similar to those of amyl acetate: chiefly irritation of the conjunctiva and upper respiratory tract, followed by gradual onset of narcosis, with slow recovery after exposure ceases. Men exposed to 950 ppm for 30 minutes reported only irritation of the nose and throat, headache, and weakness; cats exposed to 1900 ppm for 2 to 3 hours per day for a week showed only irritation, weakness, and loss of weight; dogs exposed to 5000 ppm

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

757

for 1 hour had nasal irritation and drowsiness. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 130.2
  2. Boiling point (760 mm Hg): 145.6 C (294 F)
  3. Specific gravity (water = 1): 0.87
  4. Vapor density (air = 1 at boiling point of isoamyl acetate): 4.5
  5. Melting point: −100 C (−148 F)
  6. Vapor pressure at 20 C (68 F): 4 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.2
  8. Evaporation rate (butyl acetate = 1): 0.42
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving isoamyl acetate.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 25 C (77 F) (closed cup)
  2. Autoignition temperature: 360 C (680 F)
  3. Flammable limits in air, % by volume: Lower: 1.0 (at 100 C (212 F)); Upper: 7.5
  4. Extinguishant: Dry chemical, carbon dioxide, foam
- **Warning properties**
  1. Odor Threshold: By analogy to amyl acetate, which has an odor threshold of 7 ppm (*Handbook of Industrial Organic Solvents*), the odor of isoamyl acetate is assumed to be detectable below the permissible exposure limit (100 ppm).
  2. Eye Irritation Level: The *Handbook of Industrial Organic Solvents* indicates that significant eye and nose irritation does not occur below the threshold limit.
  3. Other Information: According to the *Documentation of TLV's*, the "threshold limit of 100 ppm is recommended to prevent significant irritation of the respiratory passages."
  4. Evaluation of Warning Properties: For the purposes of this guideline, isoamyl acetate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of isoamyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure isoamyl acetate may be used. An analytical method for isoamyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid isoamyl acetate.
- Clothing wet with liquid isoamyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of isoamyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the isoamyl acetate, the person performing the operation should be informed of isoamyl acetate's hazardous properties.
- Any clothing which becomes wet with liquid isoamyl acetate should be removed immediately and not reworn until the isoamyl acetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid isoamyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid isoamyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any isoamyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to isoamyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during spray application of varnishes and nitrocellulose lacquers as protective and finish coatings for wood, especially in furniture industry, and on plastic, metal, leather, and other surfaces	Local exhaust ventilation; personal protective equipment
Liberation during application of varnishes and nitrocellulose lacquers as protective and finish coatings for wood, paper, metal, leather, and other surfaces by dipping, roller coating, tumbling, knifing, or brushing	General dilution ventilation; local exhaust ventilation
Liberation during air or oven-drying of varnishes and lacquers	General dilution ventilation
Liberation during application of cellulosic adhesives by machine spraying, dipping, roller coating, tumbling, knifing, or brushing in shoe manufacturing, book binding, packaging, leather processing, paper processing, and textile	General dilution ventilation; local exhaust ventilation
Liberation during manual application of cellulosic adhesives, including household cements	General dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during manufacture of shoe polish and furniture polish; during fermentation of whiskey grains	General dilution ventilation
Liberation during manufacture of cellulosic photographic film by formation from solvent solutions	General dilution ventilation; local exhaust ventilation
Liberation during preparation of perfumes, foods, and other materials for use as flavoring or odorant	General dilution ventilation
Liberation during use as an extractant in purification of pharmaceuticals, including penicillin	General dilution ventilation; local exhaust ventilation
Liberation during cleaning and maintenance of acetate-processing equipment, such as kettles, distillation columns, and storage vessels	Personal protective equipment
Liberation during manufacture of bath sponges	General dilution ventilation
Liberation during manufacture of artificial leathers	General dilution ventilation; local exhaust ventilation
Liberation during manufacture of artificial silk, rayon, and pearls; during manufacture and use of bronzing fluids	General dilution ventilation; local exhaust ventilation
Liberation during use in dry cleaning preparations	General dilution ventilation
Use in treating of natural leathers by tanning	General dilution ventilation; local exhaust ventilation; personal protective equipment

Liberation during drying, dry printing, and other finishing processes for textiles; during application of phosphorus in manufacture of fluorescent lamps	General dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If isoamyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If isoamyl acetate gets on the skin, promptly flush the contaminated skin with water. If isoamyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of isoamyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When isoamyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If isoamyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Isoamyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Isoamyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Isoamyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Amyl Acetate," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters: Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 21:28-65, 1960.

RESPIRATORY PROTECTION FOR ISOAMYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
3000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 3000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Isoamyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_2CHCH_2CH_2OH$
- Synonyms: 3-Methyl-1-butanol; isobutylcarbinol; isopentyl alcohol; fermentation amyl alcohol; fusel oil
- Appearance and odor: Colorless liquid with an alcoholic odor that causes coughing.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for isoamyl alcohol is 100 parts of isoamyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 360 milligrams of isoamyl alcohol per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Isoamyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to isoamyl alcohol may cause irritation of the eyes and respiratory tract, headache, dizziness, shortness of breath, cough, nausea, vomiting, and diarrhea. Double vision, deafness, delerium, and death may occur. Coma, sugar in the urine, and blood changes have also been reported.

2. Long-term Exposure: Drying and cracking of the skin may result from prolonged or repeated skin exposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to isoamyl alcohol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to isoamyl alcohol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from isoamyl alcohol exposure.

—Skin disease: Isoamyl alcohol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although isoamyl alcohol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although isoamyl alcohol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isoamyl alcohol might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Isoamyl alcohol vapor is a mild irritant. Among the few reports of experience with the amyl alcohols, exposure of rats to vapor at 8000 ppm was not lethal. Chemically related alcohols are considered to have predominantly narcotic properties at high concentrations. Slight throat irritation has been observed in unacclimated subjects at 100 ppm and objectionable irritation of the eyes, nose, and throat at higher concentrations. No chronic system-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

702

ic effects from isoamyl alcohol have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- Physical data
  1. Molecular weight: 88
  2. Boiling point (760 mm Hg): 132 C (270 F)
  3. Specific gravity (water = 1): 0.8
  4. Vapor density (air = 1 at boiling point of isoamyl alcohol): 3.0
  5. Melting point: −117 C (−179 F)
  6. Vapor pressure at 20 C (68 F): 2 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 2.4
  8. Evaporation rate (butyl acetate = 1): 0.2
- Reactivity
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving isoamyl alcohol.
  4. Special precautions: Isoamyl alcohol will attack some forms of plastics, rubber, and coatings.
- Flammability
  1. Flash point: 42.8 C (109 F) (closed cup)
  2. Autoignition temperature: 350 C (662 F)
  3. Flammable limits in air, % by volume (at 212 F): Lower: 1.2; Upper: 9.0
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide
- Warning properties
  1. Odor Threshold: Quantitative information concerning the odor threshold is not available. The *Handbook of Industrial Solvents*, however, states that the odor of n-amyl alcohol is "apparent at approximately 60 ppm." May reports an odor threshold for amyl alcohol of 35 ppm, and Summer reports 10 ppm. By analogy, it is assumed that the odor of isoamyl alcohol is also below the TLV.
  2. Irritation Levels: Patty states that "according to Nelson et al., the following concentrations of 3-methyl-1-butanol (isoamyl alcohol) caused irritation of the respective mucous membranes of the majority of persons subjected to exposure for a few minutes: eyes, 150 ppm (0.54 mg/l); nose, 150 ppm; and throat, 100 ppm (0.36 mg/l)."
  3. Evaluation of Warning Properties: Because of its irritant effects and its odor, isoamyl alcohol is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- Method

Sampling and analyses may be performed by collection of isoamyl alcohol vapors using an adsorption tube with subsequent desorption with 2-propanol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure isoamyl alcohol may be used. An analytical method for isoamyl alcohol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid isoamyl alcohol.
- Clothing wet with liquid isoamyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of isoamyl alcohol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the isoamyl alcohol, the person performing the operation should be informed of isoamyl alcohol's hazardous properties.
- Non-impervious clothing which becomes wet with liquid isoamyl alcohol should be removed promptly and

not reworn until the isoamyl alcohol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid isoamyl alcohol may contact the eyes.

SANITATION

• Skin that becomes wet with liquid isoamyl alcohol should be promptly washed or showered with soap or mild detergent and water to remove any isoamyl alcohol.

• Employees who handle liquid isoamyl alcohol should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to isoamyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Use as a vehicle, latent, or diluent solvent during application of paints, lacquers, varnishes, thinners, and paint removers	Local exhaust ventilation; general dilution ventilation
Use in synthesis of drugs and medicinals, as a solvent for alkaloids, and as an extractant of antibiotics in pharmaceutical industry	Local exhaust ventilation; general dilution ventilation
Use in manufacture of lacquers, paints, varnishes, thinners, and paint removers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a chemical intermediate in organic synthesis of photographic chemicals, isoamyl acetate, and other esters	Local exhaust ventilation; general dilution ventilation; enclosed process; personal protective equipment
Liberation during manufacture and use of printing inks	Local exhaust ventilation; general dilution ventilation
Use as a solvent for resins, gums, waxes, and oils — perfumes, explosives, shoe cement, analytical determination for fat in milk, and artificial rubber	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during manufacture and use in antifoaming agents and carburing fluids	Local exhaust ventilation; general dilution ventilation
Use in mining industry as a frothing agent for flotation of non-ferrous ores	Local exhaust ventilation; general dilution ventilation
Use as a vehicle solvent for celloidin solutions in microscopy	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If isoamyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If isoamyl alcohol gets on the skin, promptly flush the contaminated skin with water. If isoamyl alcohol soaks through the clothing, remove the clothing promptly and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of isoamyl alcohol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When isoamyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency

rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If isoamyl alcohol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Isoamyl alcohol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Isoamyl alcohol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Isoamyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., Jr.: "Improved Communication — Hygienic Standards for Daily Inhalation," *Industrial Hygiene Quarterly*, 17:145-146, June 1956.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Material Safety Data Sheet - Isoamyl Alcohol*, New York, 1972.

RESPIRATORY PROTECTION FOR ISOAMYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
8000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Isobutyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOCH_2CH(CH_3)_2$
- Synonyms: 2-Methylpropyl acetate; beta-methylpropyl ethanoate; acetic acid isobutyl ester
- Appearance and odor: Clear, colorless liquid with a pleasant, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for isobutyl acetate is 150 parts of isobutyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 700 milligrams of isobutyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Isobutyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to isobutyl acetate may cause irritation of the eyes, nose, and throat. Severe overexposure may cause weakness, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to isobutyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to isobutyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from isobutyl acetate exposure.

—Skin disease: Isobutyl acetate is a mild defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although isobutyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isobutyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although isobutyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The principal effects of overexposure to isobutyl acetate are irritation of the eyes and nose. Narcosis occurs at high concentrations. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 116
  2. Boiling point (760 mm Hg): 117 C (243 F)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

3. Specific gravity (water = 1): 0.87
4. Vapor density (air = 1 at boiling point of isobutyl acetate): 4.0
5. Melting point: −97 C (−143 F)
6. Vapor pressure at 20 C (68 F): 13 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.67
8. Evaporation rate (butyl acetate = 1): 1.5

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving isobutyl acetate.
4. Special precautions: Isobutyl acetate will dissolve a wide variety of resins and plastics.

• **Flammability**

1. Flash point: 18 C (64 F) (closed cup)
2. Autoignition temperature: 421 C (790 F)
3. Flammable limits in air, % by volume: Lower: 2.4; Upper: 10.5
4. Extinguishant: Dry chemical, carbon dioxide, foam

• **Warning properties**

1. Odor Threshold: Summer and May both report an odor threshold for isobutyl acetate of 4 ppm.
2. Eye Irritation Level: According to the *Documentation of TLV's*, the TLV of 150 ppm "is recommended primarily to prevent irritation of eyes and respiratory passages."
3. Evaluation of Warning Properties: Since the odor threshold of isobutyl acetate is below the permissible exposure limit, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of isobutyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure isobutyl acetate may be used. An analytical method for isobutyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid isobutyl acetate.

• Clothing wet with liquid isobutyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of isobutyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the isobutyl acetate, the person performing the operation should be informed of isobutyl acetate's hazardous properties.

• Any clothing which becomes wet with liquid isobutyl acetate should be removed immediately and not reworn until the isobutyl acetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid isobutyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid isobutyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any isobutyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to isobutyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during spray application of varnishes and nitrocellulose lacquers as protective and finish coatings for wood, plastic, metal, leather, and other surfaces	Local exhaust ventilation; personal protective equipment
Liberation during application of varnishes and nitrocellulose lacquers as protective and finish coatings for wood, paper, metal, leather, and other surfaces by dipping, roller coating, tumbling, knifing, or brushing	Local exhaust ventilation; general dilution ventilation
Liberation during oven backing of phenolic and epoxy coatings	General dilution ventilation
Liberation during application of nitrocellulose, cellulose acetate, cellulose acetate butyrate, and cyclized rubber adhesives by machine spraying, dipping, roller coating, tumbling, knifing, or brushing in shoe manufacturing, book binding, packaging, leather processing, photographic film manufacturing, and paper processing	Local exhaust ventilation; general dilution ventilation
Use and liberation during manual application of nitrocellulose, cellulose acetate, cellulose acetate butyrate, and cyclized rubber adhesives	General dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during cleaning and maintenance of acetate-processing equipment, including kettles, distillation columns, and storage vessels	Personal protective equipment
Liberation during manufacture of some perfumes, cosmetics, and flavoring agents	General dilution ventilation
Liberation during spray application of vinyl-based primers, maintenance paints, and other industrial coatings	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If isobutyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If isobutyl acetate gets on the skin, promptly flush the contaminated skin with water. If isobutyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of isobutyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When isobutyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If isobutyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Isobutyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Isobutyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Isobutyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Isobutyl Acetate*, New York, 1971.

• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters: Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 21:28-65, 1960.

RESPIRATORY PROTECTION FOR ISOBUTYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 150 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
7500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 7500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Isobutyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_2CHCH_2OH$
- Synonyms: Isobutanol; IBA; 2-methyl-1-propanol; isopropylcarbinol
- Appearance and odor: Colorless liquid with a mild, non-residual odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for isobutyl alcohol is 100 parts of isobutyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 300 milligrams of isobutyl alcohol per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for isobutyl alcohol a Threshold Limit Value of 50 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Isobutyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to isobutyl alcohol may cause irritation of the eyes, nose, and throat, headache, dizziness, and drowsiness.

2. Long-term Exposure: Drying and cracking of the skin may result from prolonged skin exposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to isobutyl alcohol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to isobutyl alcohol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from isobutyl alcohol exposure.

—Skin disease: Isobutyl alcohol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although isobutyl alcohol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although isobutyl alcohol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isobutyl alcohol might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Isobutyl alcohol vapor had a narcotic effect in high concentrations (6400 ppm) for mice, and was lethal at 10,000 to 15,000 ppm. In employees, repeated exposures at 100 ppm had no significant effect, although irritation of the eyes and throat were observed in other studies where the vapor concentrations were higher. Isobutyl alcohol is a mild skin irritant. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- Physical data
  1. Molecular weight: 74
  2. Boiling point (760 mm Hg): 103 C (226 F)
  3. Specific gravity (water = 1): 0.8
  4. Vapor density (air = 1 at boiling point of isobutyl alcohol): 2.6
  5. Melting point: −108 C (−162 F)
  6. Vapor pressure at 20 C (68 F): 8.8 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 8.7
  8. Evaporation rate (butyl acetate = 1): 0.82
- Reactivity
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving isobutyl alcohol.
  4. Special precautions: Isobutyl alcohol will attack some forms of plastics, rubber, and coatings. It may react with metallic aluminum at high temperatures.
- Flammability
  1. Flash point: 27.8 C (82 F) (closed cup)
  2. Autoignition temperature: 427 C (800 F)
  3. Flammable limits in air, % by volume (at 212 F): Lower: 1.2; Upper: 10.9
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide
- Warning properties
  1. Odor Threshold: Both Summer and May report an odor threshold of 40 ppm.
  2. Eye Irritation Level: Patty states, "Fassett has studied isobutyl alcohol under the same conditions of exposure as for n-butyl alcohol. No evidence of eye irritation was noted with repeated 8-hour exposures to levels on the order of 100 ppm. Animal data showed that it was very similar to n-butyl alcohol in its effects." n-Butyl alcohol is known to be an eye irritant.
  3. Evaluation of Warning Properties: Since the odor threshold of isobutyl alcohol is below the permissible exposure limit, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- Method

Sampling and analyses may be performed by collection of isobutyl alcohol vapors using an adsorption tube with subsequent desorption with 2-propanol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure isobutyl alcohol may be used. An analytical method for isobutyl alcohol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid isobutyl alcohol.
- Clothing wet with liquid isobutyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of isobutyl alcohol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the isobutyl alcohol, the person performing the operation should be informed of isobutyl alcohol's hazardous properties.
- Any clothing which becomes wet with liquid isobutyl alcohol should be removed immediately and not reworn until the isobutyl alcohol is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid isobutyl alcohol may contact the eyes.

SANITATION

• Skin that becomes wet with liquid isobutyl alcohol should be promptly washed or showered to remove any isobutyl alcohol.
• Employees who handle liquid isobutyl alcohol should wash their hands thoroughly before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to isobutyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during spray applications of nitrocellulose lacquers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during use of industrial cleaners; during use of paint removers	General dilution ventilation; personal protective equipment
Liberation during hand application of nitrocellulose lacquers; during manufacture of lubricating oil and hydraulic fluids; during manufacture of amino resins and plasticizers	General dilution ventilation
Use during manufacture of nitrocellulose lacquers, paint removers, and industrial cleaners	General dilution ventilation; personal protective equipment
Liberation during manufacture of acetaldehyde; during distillation of whiskey	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• Eye Exposure
If isobutyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.
• Skin Exposure
If isobutyl alcohol gets on the skin, promptly flush the contaminated skin with water. If isobutyl alcohol soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.
• Breathing
If a person breathes in large amounts of isobutyl alcohol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• Swallowing
When isobutyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.
• Rescue
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If isobutyl alcohol is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Isobutyl alcohol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.
• Waste disposal methods:
Isobutyl alcohol may be disposed of:
1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Isobutyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Standen, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Isobutyl Alcohol*, New York, 1966.

RESPIRATORY PROTECTION FOR ISOBUTYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
8000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Isopropyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOCH(CH_3)_2$
- Synonyms: Isopropyl ester of acetic acid, sec-propyl acetate
- Appearance and odor: Colorless liquid with a fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for isopropyl acetate is 250 parts of isopropyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 950 milligrams of isopropyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- Routes of exposure

Isopropyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- Effects of overexposure

1. Short-term Exposure: Overexposure to isopropyl acetate may cause irritation of the eyes, nose, and throat. Severe overexposure may cause weakness, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to isopropyl acetate.

- Recommended medical surveillance

The following medical procedures should be made available to each employee who is exposed to isopropyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from isopropyl acetate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isopropyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Isopropyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although isopropyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although isopropyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- Summary of toxicology

Isopropyl acetate irritates the eyes and upper respiratory tract. It may produce narcosis at high concentrations approaching the lethal level in animals. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- Physical data
  1. Molecular weight: 102
  2. Boiling point (760 mm Hg): 90 C (194 F)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

777

3. Specific gravity (water = 1): 0.87

4. Vapor density (air = 1 at boiling point of isopropyl acetate): 3.5

5. Melting point: −69 C (−92 F)

6. Vapor pressure at 20 C (68 F): 43 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): 2.9

8. Evaporation rate (butyl acetate = 1): 5

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, or strong acids may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving isopropyl acetate.

4. Special precautions: Isopropyl acetate will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 4.4 C (40 F) (closed cup)

2. Autoignition temperature: 460 C (860 F)

3. Flammable limits in air, % by volume: Lower: 1.8; Upper: 8.0

4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide

• **Warning properties**

1. Odor Threshold: May reports two odor thresholds for isopropyl acetate: 30 ppm and 400 ppm.

2. Eye Irritation Level: Patty reports that 200 ppm causes eye irritation in man.

3. Evaluation of Warning Properties: Because of its low thresholds of odor and eye irritation, isopropyl acetate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of isopropyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure isopropyl acetate may be used. An analytical method for isopropyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid isopropyl acetate.

• Clothing wet with liquid isopropyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of isopropyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the isopropyl acetate, the person performing the operation should be informed of isopropyl acetate's hazardous properties.

• Any clothing which becomes wet with liquid isopropyl acetate should be removed immediately and not reworn until the isopropyl acetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid isopropyl acetate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid isopropyl acetate should be promptly washed or showered with soap or mild detergent and water to remove any isopropyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to isopropyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during coating application to artificial silk, leather, and vinyl resin fabrics	Local exhaust ventilation; general dilution ventilation
Liberation during use as a vehicle solvent during spray application of cellulose nitrate and ethyl cellulose lacquers	Local exhaust ventilation; spray booths; personal protective equipment
Liberation during manufacture of cellulose nitrate and ethyl cellulose lacquers and thinners	Local exhaust ventilation; general dilution ventilation
Use as a solvent of synthetic resins in plastics industry	Local exhaust ventilation; general dilution ventilation
Liberation during manufacture and use of printing and litho inks; during manufacture of perfumes and flavoring agents	Local exhaust ventilation; general dilution ventilation
Use as a general solvent for waxes, gums, and oils	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If isopropyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If isopropyl acetate gets on the skin, promptly flush the contaminated skin with water. If isopropyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of isopropyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When isopropyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If isopropyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Isopropyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Isopropyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Isopropyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
• Enjay Corporation: *Product Bulletin – Isopropyl Acetate.*
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• International Lsbour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Chemical Company Guide-Isopropyl Acetate*, New York.
• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters: Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 21: 28-65, 1960.

RESPIRATORY PROTECTION FOR ISOPROPYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 250 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
12,500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
16,000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 16,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Isopropyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CHOHCH_3$
- Synonyms: Isopropanol; IPA; 2-propanol; sec-propyl alcohol
- Appearance and odor: Colorless liquid with an odor of rubbing alcohol.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for isopropyl alcohol is 400 parts of isopropyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 980 milligrams of isopropyl alcohol per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be changed to 400 ppm averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling of 800 ppm averaged over a 15-minute period. The NIOSH Criteria Document for Isopropyl Alcohol should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Isopropyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to high air concentrations of isopropyl alcohol may cause mild irritation of the eyes, nose, and throat. Drowsiness, headache, and incoordination may also occur. Swallowing isopropyl alcohol may cause drowsiness, unconsciousness, and death. Gastrointestinal pain, cramps, nausea, vomiting, and diarrhea may also result from swallowing this alcohol.

2. Long-term Exposure: Drying and cracking of the skin may result from prolonged skin exposure. Epidemiological investigations have established that a carcinogenic substance is present in isopropyl alcohol manufacturing areas, but have not confirmed isopropyl alcohol as a causative agent of cancer.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to isopropyl alcohol.

- Recommended medical surveillance

The following medical procedures should be made available to each employee who is exposed to isopropyl alcohol at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the skin, liver, kidneys, and respiratory system should be stressed.

—Skin disease: Isopropyl alcohol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although isopropyl alcohol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although isopropyl alcohol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isopropyl

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

731

alcohol might cause exacerbation of symptoms due to its irritant properties.

2. *Periodic Medical Examination:* The aforementioned medical examinations should be repeated on an annual basis.

• Summary of toxicology

The most important toxic effect of isopropyl alcohol is narcosis, which occurs in mice at vapor concentrations of 3000 ppm, the effects increasing with the duration of exposure. Exposure to higher concentrations results in ataxia, followed by deep narcosis and death. Reversible changes occurred in the liver fat of mice repeatedly exposed to high concentrations of vapor. Isopropyl alcohol is metabolized fairly rapidly, and acetone may be detected in the urine following heavy exposures. Human volunteers reported mild irritation of the eyes, nose, and throat after 3 to 5 minutes exposure to vapor at 400 ppm; at 800 ppm the results were not severe, but most subjects found the atmosphere to be objectionable. Accidental, extensive wetting of the skin could occur in industrial situations and as isopropyl alcohol is absorbed readily through the skin, the additive effect of inhalation and skin absorption could have serious results. Similarly, there is a risk of deliberate ingestion of isopropyl alcohol as a substitute for ethyl alcohol, which would add to the effects of inhalation. The defatting action of isopropyl alcohol can cause mild skin irritation, but a small percentage of workers may develop contact dermatitis of a more serious nature. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

• Physical data

1. Molecular weight: 60
2. Boiling point (760 mm Hg): 82 C (180 F)
3. Specific gravity (water = 1): 0.78
4. Vapor density (air = 1 at boiling point of isopropyl alcohol): 2.1
5. Melting point: −89 C (−128 F)
6. Vapor pressure at 20 C (68 F): 33 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): 2.83

• Reactivity

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving isopropyl alcohol.
4. Special precautions: Isopropyl alcohol will attack some forms of plastics, rubber, and coatings. It may also react with metallic aluminum at high temperatures.

• Flammability

1. Flash point: 12 C (53 F) (closed cup)
2. Autoignition temperature: 399 C (750 F)
3. Flammable limits in air, % by volume: Lower: 2.0; Upper: 12.0
4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide

• Warning properties

1. Odor Threshold: Patty reports, "Scherberger et al. stated that the concentration with identifiable odor of isopropyl alcohol is 200 ppm." May reports an odor threshold of 45 ppm.
2. Irritation Level: According to Patty, "mild irritation of the eyes, nose, and throat was induced in human subjects exposed by Nelson and associates for 3 to 5 minutes to 400 ppm of isopropyl alcohol."
3. Evaluation of Warning Properties: Through its odor and irritant effects, isopropyl alcohol can be detected below or at the permissible exposure limit. For the purposes of this guideline, therefore, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• Eight-Hour Exposure Evaluation

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Ceiling Evaluation

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of isopropyl alcohol. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Method

Sampling and analyses may be performed by collection of isopropyl alcohol vapors using an adsorption tube with subsequent desorption with 2-butanol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure isopropyl alcohol may be used. An analytical method for isopropyl alcohol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental

concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid isopropyl alcohol.
- Any clothing which becomes wet with liquid isopropyl alcohol should be removed immediately and not reworn until the isopropyl alcohol is removed from the clothing.
- Clothing wet with liquid isopropyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of isopropyl alcohol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the isopropyl alcohol, the person performing the operation should be informed of isopropyl alcohol's hazardous properties.
- Employees should be provided with and required to use splash-proof safety goggles where liquid isopropyl alcohol may contact the eyes.

SANITATION

- Skin that becomes wet with liquid isopropyl alcohol should be promptly washed or showered to remove any isopropyl alcohol.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to isopropyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in spray and heat applications of surface coatings, including stain, varnish, nitrocellulose lacquers, and quick-drying inks and paints	General dilution ventilation; personal protective equipment
Use as a solvent in application other than spray or heat of surface coatings, including stain, varnish, nitrocellulose lacquers, quick-drying inks and paints, textile coatings and dyes, dopes, and polishes	General dilution ventilation; personal protective equipment
Use in manufacture and liberation during packing of acetone	General dilution ventilation; personal protective equipment
Use as a solvent in manufacture of surface coatings and thinners	General dilution ventilation; personal protective equipment
Use in organic synthesis for isopropyl derivatives, including phenols, acetates, xanthates, ether, amines, myristate, palmitate, nitrite, and glycerin	General dilution ventilation; personal protective equipment
Use in manufacture of cosmetics, including liniments, skin lotions, permanent wave lotions, and color hair rinses	General dilution ventilation; personal protective equipment
Liberation during use as a disinfectant and sanitizer; use during cleaning and degreasing operations	General dilution ventilation; personal protective equipment
Use in preparation, manufacture, and packaging of disinfectants and sanitizers, including rubbing alcohol, other antiseptic solutions, skin astringents, mouth washes, and medicated sprays	General dilution ventilation; personal protective equipment

Operation	Controls
Use in manufacture of cleaning and degreasing agents, including stain and spot removers, glass cleaners, rug and upholstery cleaning, tar remover, liquid soap, and windshield cleaner fluid; use in manufacture of de-icing, de-fogging, and anti-freeze products	General dilution ventilation; personal protective equipment
Use in extraction and purification of alkaloids, proteins, chlorophyll, perfumes, sulfuric acid, vitamins, kelp, pectin, resins, gums, and waxes	General dilution ventilation; personal protective equipment
Use in manufacture of rubber products; use as an additive in anti-stalling gasoline, lubricants, denatured ethyl alcohol, hydraulic brake fluids, and rocket fuel	General dilution ventilation; personal protective equipment
Use in manufacture of adhesives, including nitrocellulose film and microfilm cement; use in manufacture of safety glass	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If isopropyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If isopropyl alcohol gets on the skin, flush the contaminated skin with water. If isopropyl alcohol soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of isopropyl alcohol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When isopropyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If isopropyl alcohol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Isopropyl alcohol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Isopropyl alcohol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Isopropyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Propanol," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Henson, E. V.: "Toxicology of Some Aliphatic Alcohols – Part II," *Journal of Occupational Medicine*, 2:497-502, 1960.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-98, Isopropyl Alcohol*, Washington, D.C., 1972.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Isopropyl Alcohol*, HEW Publication No. (NIOSH) 76-142, GPO No. 017-033-00165-1, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Isopropyl Alcohol*, New York, 1970.

RESPIRATORY PROTECTION FOR ISOPROPYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 400 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
20,000 ppm or less	A gas mask with a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 20,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Isopropylamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_2CHNH_2$
- Synonyms: Monoisopropylamine; 2-aminopropane
- Appearance and odor: Colorless liquid with a pungent, ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for isopropylamine is 5 parts of isopropylamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 12 milligrams of isopropylamine per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Isopropylamine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Isopropylamine vapor may cause irritation of the nose, throat, and lungs. Both isopropylamine liquid and vapor may cause irritation or burning of the eyes and skin. Permanent eye damage may occur if proper care is not given immediately. Breathing difficulties may occur either immediately or may be delayed.

2. Long-term Exposure: Repeated or prolonged exposure to isopropylamine causes an irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to isopropylamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to isopropylamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from isopropylamine exposure.

—Chronic respiratory disease: Isopropylamine causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isopropylamine might cause exacerbation of symptoms due to its irritant properties.

—Eye disease: Isopropylamine is an eye irritant and has caused corneal edema in workers. Persons with pre-existing eye disorders may be more susceptible to the effects of this agent.

—Skin disease: Isopropylamine is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Isopropylamine vapor is a respiratory and eye irritant. Rats exposed to 8000 ppm for 4 hours died as a result of pulmonary edema. Human subjects experienced irritation of the nose and throat after brief exposures to 10 to 20 ppm. Workers complained of transient visual disturbances after exposure to the vapor for 8 hours, probably due to mild corneal edema that usually cleared within 3 or 4 hours. The liquid is capable of causing very severe eye burns, which may cause permanent visual impairment. Isopropylamine in both liquid and vapor forms is irritating to the skin and may cause skin burns; repeated lesser exposures may result in dermatitis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

766

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 59.1
  2. Boiling point (760 mm Hg): 32.4 C (90 F)
  3. Specific gravity (water = 1): 0.68
  4. Vapor density (air = 1 at boiling point of isopropylamine): 2.03
  5. Melting point: −95 C (−139 F)
  6. Vapor pressure at 20 C (68 F): 478 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): Greater than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact of liquid isopropylamine with strong acids will cause explosive spattering. Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving isopropylamine.
  4. Special precautions: Liquid isopropylamine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −37 C (−35 F) (closed cup)
  2. Autoignition temperature: 402 C (756 F)
  3. Flammable limits in air, % by volume: Lower: 2.0; Upper: 10.4
  4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: Patty reports that at a concentration of 5 to 10 ppm, the ammoniacal odor is definite, and at 10 to 20 ppm, the odor is strong.
  2. Eye Irritation Level: The MCA Chemical Safety Data Sheet notes that the vapors of isopropylamine are highly irritating to the eyes, but no quantitative information is available concerning the threshold of eye irritation.
  3. Other Information: Patty reports that nose and throat irritation results from short exposures to 10 to 20 ppm isopropylamine. No eye irritation is cited.
  4. Evaluation of Warning Properties: Since the odor of isopropylamine is definite at a concentration which is only twice the permissible exposure, and since nose and throat irritation occurs at a concentration which is only 2 to 4 times the permissible exposure, isopropylamine is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of isopropylamine in a bubbler containing sulfuric acid, followed by treatment with sodium hydroxide, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure isopropylamine may be used. An analytical method for isopropylamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid isopropylamine, where skin contact may occur.
- Clothing wet with liquid isopropylamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of isopropylamine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the isopropylamine, the person performing the operation should be informed of isopropylamine's hazardous properties.
- Where exposure of an employee's body to liquid isopropylamine may occur, facilities for quick drench-

ing of the body should be provided within the immediate work area for emergency use.

• Any clothing which becomes wet with isopropylamine or non-impervious clothing which becomes contaminated with isopropylamine should be removed immediately and not reworn until the isopropylamine is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid isopropylamine contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid isopropylamine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes wet with liquid isopropylamine should be immediately washed or showered to remove any isopropylamine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to isopropylamine may occur and control methods which may be effective in each case:

Operation	Controls
Use as an intermediate in synthesis of agricultural chemicals	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a solubilizer for 2,4-D and 2,4,5-T herbicides in hard water	Local exhaust ventilation; personal protective equipment
Use as an intermediate in synthesis of insecticides and bactericides	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use with surface-active sulfonate to form oil-soluble emulsifier and detergent for use in dry cleaning operations	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as an intermediate in synthesis of vulcanization accelerators for sulfur-cured rubbers	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of ore flotation agents; use as a depilatory on skins and hides in leather manufacture; use in manufacture of emulsion-type floor polish	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a general solvent; use as a stabilizer against oxidation and polymerization	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of medicinals in purification of penicillin and streptomycin; use as an intermediate in synthesis of some dyes	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If isopropylamine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If isopropylamine gets on the skin, immediately flush the contaminated skin with water. If isopropylamine soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of isopropylamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When isopropylamine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If isopropylamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Isopropylamine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

- Waste disposal method:

Isopropylamine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Isopropylamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-72, Isopropylamine,* Washington, D.C., 1959.
- Patty, F. A. (ed.): *Toxicology,* Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Isopropylamine,* New York, 1971.

RESPIRATORY PROTECTION FOR ISOPROPYLAMINE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
250 ppm or less	A chemical cartridge respirator with a full facepiece and a cartridge(s) providing protection against isopropylamine. A gas mask with a chin-style or a front- or back-mounted canister which provides protection against isopropylamine. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
4000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against isopropylamine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Isopropylether

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $((CH_3)_2CH)_2O$
- Synonyms: Diisopropyl ether; 2-isopropoxypropane
- Appearance and odor: Colorless liquid with a sharp, sweet, ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for isopropylether is 500 parts of isopropylether per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2100 milligrams of isopropylether per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for isopropylether a Threshold Limit Value of 250 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Isopropylether can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Strong concentrations of isopropylether vapors may cause irritation of the eyes and nose. Animal experiments suggest that exposure to high concentrations of this chemical may cause drowsiness, dizziness, and unconsciousness.

2. Long-term Exposure: Repeated or prolonged exposure to liquid isopropylether may cause dryness and irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to isopropylether.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to isopropylether at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from isopropylether exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isopropylether might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Isopropylether is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Isopropylether vapor is a mild irritant of the eyes and mucous membranes; high levels cause narcosis in animals. Animals exposed to 30,000 ppm for 1 hour showed signs of narcosis. Exposure of human subjects to 800 ppm for 5 minutes caused irritation of the eyes and nose and some reported respiratory discomfort; exposure to 500 ppm for 15 minutes was not irritating, but at 300 ppm one third of the subjects objected to the unpleasant odor. The liquid dropped in the eye of a rabbit caused minor injury. In rabbits, repeated skin exposure to the liquid for 10 days caused dermatitis, possibly due to defatting action.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

701

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 102.2
2. Boiling point (760 mm Hg): 68.9 C (156 F)
3. Specific gravity (water = 1): 0.7
4. Vapor density (air = 1 at boiling point of isopropylether): 3.5
5. Melting point: −85 C (−121 F)
6. Vapor pressure at 20 C (68 F): 119 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.2
8. Evaporation rate (butyl acetate = 1): 8

- **Reactivity**

1. Conditions contributing to instability: Contact with air causes formation of explosive peroxides that may detonate when heated or subjected to shock.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving isopropylether.
4. Special precautions: Isopropylether will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: −27.8 C (−18 F) (closed cup)
2. Autoignition temperature: 443 C (830 F)
3. Flammable limits in air, % by volume: Lower: 1.4; Upper: 7.9
4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide

- **Warning properties**

1. Odor Threshold: Patty states that 35% of human subjects exposed experimentally to isopropylether "objected to the unpleasant odor of this solvent at a vapor concentration of 30 ppm."
2. Irritation Level: Patty states that "Silverman et al. reported that humans exposed to a vapor concentration of 500 ppm isopropyl ether for 15 minutes while watching a movie noted no irritating properties . . . . At 800 ppm for 5 minutes most subjects reported irritation of the eyes and nose, and the most sensitive reported respiratory discomfort."
3. Evaluation of Warning Properties: Through its odor and irritant effects, isopropylether can be detected at or slightly above the permissible exposure limit. For the purposes of this guideline, therefore, isopropylether is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure isopropylether may be used. An analytical method for isopropylether is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid isopropylether.

• Clothing wet with isopropylether should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of isopropylether from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the isopropylether, the person performing the operation should be informed of isopropylether's hazardous properties.

• Any clothing which becomes wet with liquid isopropylether should be removed immediately and not reworn until the isopropylether is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid isopropylether may contact the eyes.

SANITATION

• Skin that becomes wet with liquid isopropylether should be promptly washed or showered with soap or mild detergent and water to remove any isopropylether.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to isopropylether may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in extraction processes, rubber adhesives, lacquers, resins, oils, cellulose, pharmaceutical manufacture, smokeless gunpowder, and textile spot cleaning	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis as an alkylation agent; emulsion breaker in petroleum industry; and as blending agent for gasoline	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid isopropylether gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid isopropylether gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid isopropylether soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of isopropylether, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When isopropylether has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If isopropylether is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. Isopropylether should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of isopropylether vapors are permitted.

• Waste disposal method:

Isopropylether may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Isopropylether," *Documentation of the Threshold Limit Values for Substances in Workroom Air*

(3rd ed., 2nd printing), Cincinnati, 1974.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Isopropylether*, New York, 1968.

RESPIRATORY PROTECTION FOR ISOPROPYLETHER

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
10,000 ppm or less	A gas mask with a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ketene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_2CO
- Synonyms: None
- Appearance and odor: Colorless gas with a sharp odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ketene is 0.5 parts of ketene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.9 milligrams of ketene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ketene can affect the body if it is inhaled or if it comes in contact with the eyes.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to ketene may cause irritation of the eyes, nose, throat, and lungs. It may also cause cough, chest pain, and severe breathing difficulty. This may occur several hours after exposure and may be severe enough to cause death.

2. Long-term Exposure: Chronic overexposure to ketene may cause permanent lung damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ketene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ketene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Ketene causes lung damage in animals.

—FVC and FEV (1 sec): Ketene is a severe pulmonary irritant in animals.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

Ketene is a severe respiratory irritant. Concentrations over 100 ppm were invariably fatal to mice, rats, and guinea pigs; death occurred rapidly with symptoms of marked eye, nose, throat, and pulmonary irritation; autopsies showed major damage to alveolar walls with pulmonary edema. The LC50 for mice was established at 17 ppm for 10 minutes, but 1 ppm was tolerated without apparent chronic injury by several animal species exposed for 6 hours daily for 6 months. Although it has not been reported in humans, animal data indicate that chronic pulmonary changes (emphysema and fibrosis) may result from repeated acute exposures.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 42
2. Boiling point (760 mm Hg): −56 C (−69 F)
3. Specific gravity (water = 1): Not applicable

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

4. Vapor density (air = 1 at boiling point of ketene): 1.45

5. Melting point: −151 C (−239 F)

6. Vapor pressure at 20 C (68 F): Not pertinent

7. Solubility in water, g/100 g water at 20 C (68 F): Reacts with water to form acetic acid

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Ketene reacts vigorously with water and with a wide variety of organic compounds.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving ketene.

4. Special precautions: Dimerization of ketene to diketene occurs even at low temperatures.

• **Flammability**

1. Flash point: Not applicable (gas)

2. Autoignition temperature: Data not available

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Stop flow of gas

• **Warning properties**

1. Odor Threshold: No quantitative information is available.

2. Eye Irritation Level: Grant states that "exposure of monkeys to 23 ppm in air for 4 hours caused the animals to rub their eyes, cough, and become lethargic. . . . The dimer, diketene, is said to be lacrimatory and to cause marked irritation of the conjunctiva."

3. Evaluation of Warning Properties: Since there is no quantitative information relating its warning properties to air concentrations, ketene is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of ketene in a bubbler containing alkaline hydroxlammonium chloride, followed by treatment with ferric chloride, and colorimetric analysis. An analytical method for ketene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ketene may occur and control methods which may be effective in each case:

Operation	Controls
Use as an intermediate in production of acetic anhydride, cellulose and vinyl acetate resins and plastics, acrylic resins, dyes, pigments, and pharmaceuticals	Process enclosure; local exhaust ventilation; personal protective equipment
Use in industrial organic synthesis in manufacture of acetyl chloride, acid anhydrides, esters, nitriles, and diketene	Process enclosure; local exhaust ventilation; personal protective equipment
Use during laboratory operations as an acetylating agent	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of ketene, move the exposed person to fresh air at once. If breathing is difficult, properly trained personnel may assist the affected person by administering oxygen. If breathing has stopped, perform artificial respiration. Keep the

affected person warm and at rest. Get medical attention as soon as possible.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If ketene is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak.
3. Stop flow of gas.

• Waste disposal method:

Ketene may be disposed of by burning at a safe location or in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ketene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Phosgene," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

RESPIRATORY PROTECTION FOR KETENE

Condition	Minimum Respiratory Protection* Required Above 0.5 ppm
Vapor Concentration	
25 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 25 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Lindane*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_6Cl_6$
- Synonyms: 1,2,3,4,5,6-Hexachlorocyclohexane; gamma-hexachlorocyclohexane; benzene hexachloride
- Appearance and odor: Colorless solid with a musty odor (pure material is odorless).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for lindane is 0.5 milligram of lindane per cubic meter of air (mg/m³) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Lindane can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to lindane may cause vomiting, restlessness, muscle spasms, convulsions, and respiratory failure. It may also cause severe breathing difficulties which may be delayed in onset. Exposure to lindane vapors may cause headache, vomiting, and irritation of the eyes, nose, and throat. Repeated exposure to lindane may cause severe blood disorders which may be fatal. Skin rash may also occur from exposure to this chemical.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to lindane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to lindane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of convulsive disorders would be expected to be at increased risk from exposure. Examination of the eyes, central nervous system, blood, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Lindane may cause aplastic anemia. A complete blood count should be performed, including a red cell count, a white cell count, and a differential count of a stained smear, as well as hemoglobin and hematocrit. The concentration of lindane in the blood is an indication of the extent of absorption.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Lindane (the gamma isomer of hexachlorocyclohexane) dust or vapor is a convulsant and causes cancer in mice. Repeated feeding to rats of 800 ppm in the diet resulted in mild liver damage; kidney damage occurred at higher levels. Mice fed 400 ppm in the diet developed liver tumors and, in some cases, lung metastases. In humans, accidental ingestion has caused fatalities; effects were repeated, violent, clonic convulsions, sometimes superimposed on a continuous tonic spasm; respiratory difficulty and cyanosis secondary to the convulsions were common. Exposure to the vapor causes irritation of the eyes, nose, and throat, severe headache, and nausea. Lindane levels in the blood do not appear to increase with increased duration of exposure but primarily reflect recent lindane absorption; production workers

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

738

exposed to air levels of 31 to 1800 ug/m³ had blood levels of 1.9 to 8.3 ppb. Lindane has been suspected as a cause of aplastic anemia in a number of cases reported from various countries; this condition may have been caused either by a contaminant, or a thermal breakdown product of lindane, because many of the cases were associated with a space vaporizer as the source of exposure. The dry material applied to the skin of rabbits caused moderate skin irritation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 290.8
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): 1.89
  4. Vapor density (air = 1 at boiling point of lindane): Not applicable
  5. Melting point: 112 C (234 F)
  6. Vapor pressure at 20 C (68 F): 0.0000094 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.001
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: Above 177 C (350 F) lindane decomposes to form toxic and irritating hydrogen chloride gas.
  2. Incompatibilities: None
  3. Hazardous decomposition products: Toxic gases and vapors (such as phosgene, hydrogen chloride, and carbon monoxide) may be released in a fire involving lindane.
  4. Special precautions: None
- **Flammability**
  1. Not combustible, but may be dissolved in a combustible solvent
- **Warning properties**

Since the vapor pressure is so low, warning properties are not considered.

Grant states that "as a dust, lindane is said to have caused irritation of the eyes and respiratory passages in particularly sensitive individuals. However, test applications of a 3% dust mixture with talc on the eyes and nasal mucosa of rabbits produced no irritation."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of lindane using a filter with subsequent recovery with iso-octane and gas chromatographic analysis. An analytical method for lindane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with lindane or liquids containing lindane where skin contact may occur.
- If employees' clothing may have become contaminated with lindane or liquids containing lindane, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with lindane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of lindane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the lindane, the person performing the operation should be informed of lindane's hazardous properties.
- Where exposure of an employee's body to lindane or liquids containing lindane may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with solid lindane should be removed promptly and non-impervious clothing which becomes contaminated with liquids containing lindane should be re-

moved immediately and not reworn until the lindane is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where lindane or liquids containing lindane may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquids containing lindane should be immediately washed or showered with soap or mild detergent and water to remove any lindane.

• Skin that becomes contaminated with solid lindane should be promptly washed or showered with soap or mild detergent and water to remove any lindane.

• Eating and smoking should not be permitted in areas where solid lindane is handled, processed, or stored.

• Employees who handle lindane or liquids containing lindane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to lindane may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of insecticides, scabicides, pediculicides, and vermifuges	Process enclosure; general dilution ventilation; personal protective equipment
Application as a pesticide on plant, animal, household, and agricultural premises and equipment	Personal protective equipment
Manufacture of lindane	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• Eye Exposure

If lindane or liquids containing lindane get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• Skin Exposure

If lindane or liquids containing lindane get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If lindane or liquids containing lindane soak through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• Breathing

If a person breathes in large amounts of lindane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• Swallowing

When lindane or liquids containing lindane have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If lindane is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing lindane should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Lindane may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Lindane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hexachlorocyclohexane, Gamma Isomer - Lindane," *Hygienic Guide Series*, Detroit, Michigan, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Agency for Research on Cancer: "Some Organochlorine Pesticides," Vol. 5 in *IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man*, Lyon, France, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• West, I.: "Lindane and Hematologic Reactions," *Archives of Environmental Health*, 15:97-101, 1967.

* SPECIAL NOTE

Lindane appears on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding its carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980).

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 5, 1974.

RESPIRATORY PROTECTION FOR LINDANE

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 mg/m³ or less	A powered air-purifying respirator with an organic vapor cartridge and high efficiency particulate filter, including pesticide respirators which meet the requirements of this class. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
1000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of lindane; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 1000 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Lithium Hydride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: LiH
- Synonyms: None
- Appearance and odor: Off-white, translucent solid which is odorless.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for lithium hydride is 0.025 milligram of lithium hydride per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Lithium hydride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Lithium hydride causes sneezing, coughing, and severe irritation of the nose and throat. Lithium hydride can cause severe eye and skin burns. If swallowed, the mouth, trachea, and esophagus may be burned. Inadvertent ingestion of lithium hydride may cause nausea, muscle twitches, mental confusion, blurring of vision, coma, and death.

2. Long-term Exposure: None reported. Nervous system damage has been reported from high short-term exposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to lithium hydride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to lithium hydride at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from lithium hydride exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of lithium hydride might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Lithium hydride is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Eye disease: Lithium hydride is a severe eye irritant and may cause tissue damage. Persons with pre-existing eye conditions may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Lithium hydride dust is a severe irritant of the eyes, respiratory tract, and skin due to the formation of lithium hydroxide and its caustic action on moist surfaces. The inherent toxicity of the lithium ion is high; a few milliequivalents in the plasma give rise to signs and symptoms of serious nervous system effects: anorexia, nausea, tremor, muscle twitches, apathy, mental confusion, blurring of vision, coma and death. Exposure of animals to concentrations of 5 to 55 mg/m^3 of lithium hydride caused sneezing and coughing; levels of 10 mg/m^3 corroded the body fur and skin of the legs, and there was occasionally severe inflammation of the eyes and nasal septum. Lesions of the nose and paws were similar to thermal burns and were attributed to the alkalinity of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

8C3

the hydrolysis product of lithium hydride. The explosion of a cylinder of lithium hydride led to eye contact and swallowing of a small amount of the dust by a technician. The resulting burns caused scarring of both corneas, with strictures of the larynx, trachea, bronchi and esophagus; delayed death occurred. Exposure of humans to 0.5 mg/m³ caused eye and skin irritation; 0.025 mg/m³ caused sneezing, to which some degree of tolerance was acquired. Although unlikely to occur from industrial exposures, ingestion will cause severe burns of the mouth and esophagus. Restricted sodium intakes are reported to increase the toxicity of lithium.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 7.95
2. Boiling point (760 mm Hg): Decomposes at very high temperatures
3. Specific gravity (water = 1): 0.78
4. Vapor density (air = 1 at boiling point of lithium hydride): Not applicable
5. Melting point: 686 C (1267 F)
6. Vapor pressure at 20 C (68 F): 0 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts to form hydrogen gas and lithium caustic
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Moisture and carbon dioxide, even in concentrations normally in air; heat
2. Incompatibilities: Contact with oxidizers, halogenated hydrocarbons, and acids will cause fires and explosions. Contact with water will cause formation of flammable and explosive hydrogen gas. The heat of the reaction may be sufficient to cause ignition.
3. Hazardous decomposition products: Toxic gases and vapors (such as lithium hydride oxide) may be released in a fire involving lithium hydride.
4. Special precautions: Solid lithium hydride will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: 200 C (392 F) (may ignite spontaneously in moist air even at ambient temperatures)
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Smother with nitrogen or other inert gas, or by covering containers, or cover with dry graphite or dry dolomite.

- **Warning properties**

According to Grant, "in rats, rabbits, and guinea pigs, it (lithium hydride dust) has been observed to cause irritation and inflammation in the eyes at concentrations which were very irritating to the respiratory tract." Grant states that even very low concentrations can produce respiratory irritation. According to the AIHA *Hygienic Guide*, "well-fitted respirators of the half mask type, when used with dust filters, protect adequately to 0.1 mg/m³," because "persons with some degree of adaptation complain of eye and nose irritation at concentrations above 0.1 mg/m³ . . . ."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for lithium hydride had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with lithium hydride or liquids containing lithium hydride.

Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with lithium hydride at or above an airborne concentration of 0.1 mg/m³.

• If employees' clothing has had any possibility of being contaminated with lithium hydride or liquids containing lithium hydride, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with lithium hydride or liquids containing lithium hydride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of lithium hydride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the lithium hydride, the person performing the operation should be informed of lithium hydride's hazardous properties.

• Where there is any possibility of exposure of an employee's body to lithium hydride, liquids containing lithium or airborne concentrations of lithium hydride exceeding 0.5 mg/m³, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with lithium hydride should be removed immediately and not reworn until the lithium hydride is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of lithium hydride or liquids containing lithium hydride contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to lithium hydride or liquids containing lithium hydride, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with lithium hydride should be immediately brushed to remove any solid lithium hydride from the skin and washed or showered with copious quantities of water to remove any lithium hydride.

• Workers subject to skin contact with lithium hydride or liquids containing lithium hydride should wash any areas of the body which may have contacted lithium hydride at the end of each work day.

• Eating and smoking should not be permitted in areas where lithium hydride or liquids containing lithium hydride are handled, processed, or stored.

• Employees who handle lithium hydride or liquids containing lithium hydride should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to lithium hydride may occur and control methods which may be effective in each case:

Operation	Controls
Use in powder metallurgy; use in manufacture of buoyancy devices, fuel cells, and portable field generators; use in manufacture of reducing agent and propellant	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as a shielding material for thermal neutrons in nuclear industry; use as a desiccant; use as a condensing agent in organic synthesis; use in a condensation polymerization; use in manufacture of electronic tubes and in ceramics	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as an intermediate in manufacture of lithium aluminum hydride and lithium amide	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If lithium hydride or liquids containing lithium hydride get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If lithium hydride or liquids containing lithium hydride get on the skin, immediately flush the contaminated skin with large amounts of water. If lithium hydride or liquids containing lithium hydride penetrate through the clothing, remove the clothing immediately and flush the skin with large amounts of water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of lithium hydride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If lithium hydride or liquids containing lithium hydride have been swallowed and the person is conscious, give him large quantities of water immediately to dilute the

lithium hydride. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If lithium hydride is spilled, the following steps should be taken:

1. Remove all igntion sources.
2. Ventilate area of spill.
3. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Avoid contact with water.

• Waste disposal method:

Lithium hydride may be disposed of in dry sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Lithium Hydride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Lithium Hydride," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Cracovaner, A. J.: "Stenosis After Explosion of Lithium Hydride," *Archives of Otolaryngology*, 80:87-92, 1964.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spiegl, C. J., et al.: "Acute Inhalation Toxicity of Lithium Hydride," *A.M.A. Archives of Industrial Health*, 14:468-470, 1956.

RESPIRATORY PROTECTION FOR LITHIUM HYDRIDE

Condition	Minimum Respiratory Protection* Required Above 0.025 mg/m³
Particulate Concentration	
0.1 mg/m³ or less	Any high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
1.25 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
25 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter.
50 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 50 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator with a full facepiece. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of lithium hydride; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 50 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for LPG

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_3H_6 - C_3H_8 - C_4H_8 - C_4H_{10}$ mixture
- Synonyms: Liquefied petroleum gas; bottled gas
- Appearance and odor: Colorless, odorless gas (a foul-smelling odorant is usually added).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for LPG is 1000 parts of LPG per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1800 milligrams of LPG per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

LPG can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

Overexposure to LPG can cause lightheadedness and drowsiness. Greater exposure may also cause unconsciousness and death. Contact with the liquid may also cause frostbite and irritation.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to LPG.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to LPG at potentially hazardous levels.

- **Summary of toxicology**

LPG in gaseous form acts as a simple asphyxiant and a central nervous system depressant. In liquid form it may cause frostbite, as well as skin irritation. Toxicologic data are meager, and no chronic systemic effects have been reported from industrial exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 42 – 58 depending on relative amounts of ingredients
2. Boiling point (760 mm Hg): −40 to −0.5 C (−40 to 31 F)
3. Specific gravity (water = 1): 0.5 to 0.58
4. Vapor density (air = 1 at boiling point of LPG): 1.6 to 2.0
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Propane: 8.6 atm.; Butane: 2.1 atm.
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Much greater than 1

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving LPG.
4. Special precautions: LPG will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Not applicable (gas)
2. Autoignition temperature: 405 to 450 C (761 to 842 F)
3. Flammable limits in air, % by volume: Lower: 1.9; Upper: 9.5 (estimated)
4. Extinguishant: Stop flow of gas

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

• **Warning properties**

1. Odor Threshold: Propane is the main constituent of LPG, according to the *Documentation of TLV's*. The odor threshold of propane (20,000 ppm) is 20 times the permissible exposure limit (1000 ppm).

2. Eye Irritation Level: Since propane is the main constituent of LPG, and since the eye irritation threshold of propane is above its lower flammable limit, eye irritation does not restrict respirator selection either for propane or for LPG

3. Evaluation of Warning Properties: The odor threshold of propane is 20 times higher than its permissible exposure limit. On the basis of the judgment that propane does not have adequate warning properties, for the purposes of this guideline, LPG is also assumed not to have adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by utilizing a combustible gas meter. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure LPG may be used. An analytical method for LPG is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid LPG or from contact with vessels containing liquid LPG.

• Any clothing which becomes wet with liquid LPG should be removed immediately and not reworn until the LPG has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid LPG may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to LPG may occur and control methods which may be effective in each case:

Operation	Controls
Use in chemical industry as feedstock in catalytic cracking in manufacture of petrochemicals and polymers	Process enclosure; general dilution ventilation
Use as an internal combustion engine fuel	General dilution ventilation
Use in manufacture of synthetic rubber	Process enclosure; general dilution ventilation
Use as a fuel for industrial space and wall heating, air conditioning, and water heating	General dilution ventilation
Use as a fuel for drying agricultural products; use as a low sulfur fuel for cutting, soldering, and brazing	General dilution ventilation
Use as a fuel to augment public supply; to increase BTU content of manufactured gas	General dilution ventilation

809

Use as an aerosol propellant for shaving lather, window cleaners, starch sprays, room deodorants, insecticides, and pharmaceuticals	General dilution ventilation
Use as an agricultural tool in flame cultivation, non-selective cultivation, and weed control	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid LPG gets into the eyes, flush the eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Do not use hot water for eye flushing. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid LPG gets on the skin, immediately flush the contaminated skin with water. If liquid LPG soaks through the clothing, remove the clothing immediately and flush the skin with water. Do not use hot water for skin flushing. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of LPG, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.
- If LPG is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

- Waste disposal method:

LPG may be disposed of by burning at a safe location or in a suitable combustion chamber.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "LPG," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Underwriters' Laboratories: *LPG*.

RESPIRATORY PROTECTION FOR LPG

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
19,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 19,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Magnesium Oxide Fume

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: MgO
- Synonyms: Magnesia fume
- Appearance: White fume.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for magnesium oxide fume is 15 milligrams of magnesium oxide fume per cubic meter of air (mg/m³) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for magnesium oxide fume a Threshold Limit Value of 10 mg/m³.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Magnesium oxide fume can affect the body if it is inhaled or if it comes in contact with the eyes.

- **Effects of overexposure**

1. Short-term Exposure: Magnesium oxide fume may cause irritation of the eyes and nose. It may also cause a metal fume fever. Symptoms of metal fume fever include chills, fever, headache, tightness of chest, cough, weakness, tiredness, dryness of the nose and mouth, muscular pain, nausea, and vomiting.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to magnesium oxide fume.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to magnesium oxide fume at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from magnesium oxide fume exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of magnesium oxide fume might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Magnesium oxide fume mildly irritates the eyes and nose. Examination of 95 workers exposed to an unspecified concentration of magnesium oxide dust revealed slight irritation of the eyes and nose; the magnesium level in the serum of 60% of those examined was above the normal upper limit of 3.5 mg%. Experimental subjects exposed to fresh magnesium oxide fume developed metal fume fever, an illness similar to influenza; their symptoms included fever, cough, oppression in the chest, and a leukocytosis. There are no reports of metal fume fever resulting from industrial exposure. Metal magnesium slivers produce a gaseous reaction and cause a slow-healing burn with ulceration, but this has not been reported for magnesium oxide.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 40.3
2. Boiling point (760 mm Hg): 3582 C (6480 F) (solid)
3. Specific gravity (water = 1): Solid = 3.58
4. Vapor density (air = 1 at boiling point of magnesium oxide fume): Not applicable
5. Melting point: 2800 C (5072 F) (solid)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

812

6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Magnesium oxide fume reacts violently with chlorine trifluoride.
3. Hazardous decomposition products: None
4. Special precautions: None

• **Flammability**

1. Not combustible

• **Warning properties**

Magnesium oxide fume may cause mild eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of magnesium oxide fume on a cellulose membrane filter, followed by treatment with nitric acid, and atomic absorption spectrophotometric analysis. An analytical method for magnesium oxide fume is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to magnesium oxide fume may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from fabrication of alloys for aircraft, ships, automobiles, boats, tools, machinery, and military equipment	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation from casting of metal and alloys	Local exhaust ventilation; general dilution ventilation
Liberation from fabrication of metal	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of magnesium oxide fume, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.

• If potentially hazardous amounts of magnesium oxide fume are inadvertently released, ventilate the area of release to disperse the fume.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Magnesium Oxide Fume," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Magnesium," *Hygienic Guide Series*, Detroit, Michigan, 1960.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR MAGNESIUM OXIDE FUME

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Particulate Concentration	
150 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
7,500 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 7,500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Malathion

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_{19}O_6PS_2$
- Synonyms: O,O-Dimethyl dithiophosphate of diethyl mercaptosuccinate; O,O-dimethyl S-(1,2-dicarbethoxyethyl) phosphorodithiocite
- Appearance and odor: Colorless to brown liquid with a mild skunk-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for malathion is 15 milligrams of malathion per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended a permissible exposure limit of 15 mg/m^3 averaged over a work shift of up to ten hours per day, forty hours per week. The NIOSH Criteria Document for Malathion should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Malathion can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Malathion is one the least toxic of the organophosphate insecticides. Very large exposures are required to cause symptoms. After inhalation of malathion, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of the vision, tearing, runny nose, headache, and watering of the mouth. After swallowing malathion, loss of appetite, nausea, vomiting, abdominal cramps and diarrhea may appear within two hours. After skin absorption, sweating and twitching in the area of absorption may occur, usually within 15 minutes to four hours. With severe intoxication by all routes, in addition to the above symptoms, weakness, generalized twitching and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, irregular or slow heartbeat, convulsions, and coma may occur.

2. Long-term Exposure: Repeated exposure to malathion may make a person more susceptible to the effects of this and related chemicals.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to malathion.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to malathion at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, liver, and attention to the cholinesterase levels in the blood should be stressed.

—Cholinesterase determination: Malathion can cause depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the erythrocytes should be measured by using medically acceptable biochemical tests before employment (or exposure) in order to establish an individual baseline

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

value, which should be the mean of two ChE activity measurements, taken at least one day apart.

—14" x 17" chest roentgenogram: Malathion causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Malathion is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Liver function tests: Malathion may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determination which should be performed quarterly or at any time overexposure is suspected or signs and symptoms of toxicity occur.

• **Summary of toxicology**

Malathion is a mild anticholinesterase agent; absorption may occur from inhalation of the mist, from skin absorption of solutions, or from ingestion. Malathion is less toxic to humans than most anticholinesterase agents because it is metabolized in the liver to an inactive form. However, ingestion of 50 to 90 cc of a 50% solution of malathion in a petroleum hydrocarbon base caused severe intoxication; the human LD50 is estimated to be about 1 g/kg. Signs and symptoms of intoxication by anticholinesterase agents are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nueromuscular system, and secretory glands. After inhalation of extremely high concentrations, respiratory and ocular effects may appear simultaneously. Respiratory effects include tightness in the chest, wheezing, laryngeal spasms, and excessive salivation. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear. Effects on the central nervous system may include giddiness, confusion, ataxia, and slurred speech. In a group of workers with maximum exposure of 56 mg/m^3 for 5 hours and an average of 3.3 mg/m^3, the cholinesterase levels in the blood were not significantly lowered and no one exhibited signs of cholinesterase inhibition. In a human experiment in which 4 men were exposed 1 hour daily for 42 days to 84.8 mg/m^3, there was moderate irritation of nose and conjunctiva but there were no cholinergic signs or symptoms.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 330
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.23
4. Vapor density (air = 1 at boiling point of malathion): Not applicable
5. Melting point: 2.8 C (37 F)
6. Vapor pressure at 20 C (68 F): 0.00004 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0145
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Starts to decompose at 49 C (140 F) but is not hazardous.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide, phosphoric acid mist, and carbon monoxide) may be released in a fire involving malathion.
4. Special precautions: Malathion will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible.

• **Warning properties**

Since malathion has a negligible vapor pressure, warning properties are not considered.

Grant states that "undiluted technical liquid malathion dropped on a rabbits's eye caused slight immediate irritation with conjunctival hyperemia and edema of the lids, but the eye returned to normal in twenty-four hours."

The *Documentation of TLV's* notes that workers exposed to 84.8 mg/m^3 experienced moderate eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for malathion is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not

technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with malathion.

• Non-impervious clothing which becomes contaminated with malathion should be removed promptly and not reworn until the malathion is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid malathion may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to malathion, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with malathion should be promptly washed or showered with soap or mild detergent and water to remove any malathion.

• Employees who handle malathion should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

• Eating and smoking should not be permitted in areas where malathion is handled, processed, or stored.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to malathion may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of pesticide products	Process enclosure; local exhaust ventilation; personal protective equipment
Application as an insecticide for treatment of grain, nut, fruit, and fiber crops; grasses, seeds, and tobacco; animals; agricultural premises	Personal protective equipment
Manufacture of malathion	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If malathion or formulations containing malathion get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If malathion or formulations containing malathion get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If malathion or formulations containing malathion penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of malathion, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When malathion or formulations containing malathion have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If malathion is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Malathion may be disposed of by absorbing in vermiculite, dry sand, earth, or a similar material and disposing in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Malathion," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Crowley, W. J., Jr., and Johns, T. R.: "Accidental Malathion Poisoning," *Archives of Neurology*, 14:611-616, 1966.

• Culver, D., et al.: "Studies of Human Exposure During Aerosol Application of Malathion and Chlorthion," *A.M.A. Archives of Industrial Health*, 13:37-50, 1956.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Bulletin of Supplementary Material for Clinical Toxicology of Commercial Products*, University of Rochester, 1969-1975.

• Golz, H. H.: "Controlled Human Exposures to Malathion Aerosols," *A.M.A. Archives of Industrial Health*, 19:516-523, 1959.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koelle, G. B. (ed.): *Cholinesterases and Anticholinesterase Agents*, Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Malathion*, HEW Publication No. (NIOSH) 76-205, NTIS No. PB267070, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

RESPIRATORY PROTECTION FOR MALATHION

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Particulate or Vapor Concentration	
150 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class.** Any supplied-air respirator.** Any self-contained breathing apparatus.**
750 mg/m³ or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s) and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered chemical cartridge respirator with a full facepiece, helmet, or hood, an organic vapor cartridge, and high efficiency particulate filter, including pesticide respirators which meet the requirements of this class. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 5000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If an employee informs his employer that he is experiencing eye irritation from malathion while wearing a half- or quarter-mask respirator, the employer should provide an equivalent respirator with a full facepiece, helmet, or hood.

Occupational Health Guideline for Maleic Anhydride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CHCO)_2O$
- Synonyms: 2,5-Furanedione; cis-butenedioic anhydride; toxilic anhydride
- Appearance and odor: Colorless or white solid with a penetrating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for maleic anhydride is 0.25 part of maleic anhydride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1 milligram of maleic anhydride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Maleic anhydride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Maleic anhydride dust and vapor may cause irritation of the eyes, nose, throat, and skin. On contact with the skin, maleic anhydride may not cause an immediate burning sensation, especially if the skin is dry. If the solid form is allowed to remain in contact with moist tissues, burn may occur. Upon inhalation of dust or vapors, a person may experience coughing, sneezing, and burning of the throat. If the dust or vapors get into a person's eyes, irritation, sensitivity to light, and double vision may occur.

2. Long-term Exposure: Repeated or prolonged exposure to maleic anhydride may cause chronic skin or eye irritation. An allergic type of skin rash and asthma may also occur.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to maleic anhydride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to maleic anhydride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to maleic anhydride would be expected to be at increased risk from exposure. Examination of the eyes and respiratory tract should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Maleic anhydride in the form of a vapor, fume, or dust is a severe irritant of the eyes; it is both an irritant and sensitizer of both the skin and respiratory tract, and may produce asthma on repeated exposures. In a carcinogenesis experiment with a few rats injected subcutaneously with 1 mg maleic anhydride in oil twice weekly for 61 weeks, 2 of 3 surviving animals developed fibrosarcomas which appeared 80 weeks after the start of the experiment. Workers exposed to vapors from heated maleic anhydride developed an intense burning sensation in the eyes and throat, with cough and vomiting; exposure to high fume concentrations caused photophobia, double vision, and a sensation of seeing rings around lights. Exposure of humans to a concentration of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

820

September 1978

6 to 8 mg/m³ of air resulted in nasal irritation within 1 minute and eye irritation after 15 to 20 minutes. Among workers repeatedly exposed to 5 to 10 mg/m³ there was ulceration of nasal mucous membranes, chronic bronchitis, and some asthma. The dust on dry skin may result in a delayed burning sensation, but on moist skin the sensation is almost immediate, producing erythema which may progress to vesiculation. Prolonged or repeated exposure also may cause dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 98.1
2. Boiling point (760 mm Hg): 202 C (396 F)
3. Specific gravity (water = 1): 1.43 (solid); 1.3 (melt)
4. Vapor density (air = 1 at boiling point of maleic anhydride): 3.38
5. Melting point: 53 C (127 F)
6. Vapor pressure at 20 C (68 F): 0.16 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble but reacts slowly and dissolves
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Maleic anhydride is decomposed by water at temperatures above 66 C (150 F).
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with alkali metals, caustics, and amines may cause polymerization if temperature is greater than 66 C (150 F).
3. Hazardous decomposition products: Toxic gases and vapors (such as irritating fume of unburned material and carbon monoxide) may be released in a fire involving maleic anhydride.
4. Special precautions: None

- **Flammability**

1. Flash point: 102 C (215 F) (closed cup)
2. Autoignition temperature: 477 C (890 F)
3. Flammable limits in air, % by volume: Lower: 3.4 (calculated); Upper: 7.1
4. Extinguishant: Alcohol foam, carbon dioxide. Dry chemical, multi-purpose dry chemical, or loaded stream fire extinguishing media should not be used because of the possibility of an explosion due to the probable reaction of basic compounds in these extinguishing media with maleic anhydride.

- **Warning properties**

1. Odor Threshold: According to the AIHA *Hygienic Guide*, "at a concentration of 2 mg/m³ a faint odor is noticed."
2. Eye Irritation Level: Exposure to a concentration of 6 to 8 mg/m³ maleic anhydride results in eye irritation within 15 to 20 minutes, according to the *Hygienic Guide*, which also states that "a tendency for eye irritation at levels of approximately 1 mg/m³ has been observed."

Grant reports that maleic anhydride is a "crystalline material which powders and sublimes readily, producing fumes which are powerfully irritating to the eyes and respiratory tract." Grant gives no quantitative information, however.

3. Other Information: The *Hygienic Guide* notes that at a concentration of 6 to 8 mg/m³ "persons not accustomed to handling maleic anhydride report definite nasal irritation within 1 minute."
4. Evaluation of Warning Properties: Through its odor maleic anhydride can be detected at a concentration of only twice the TLV. In addition, the *Hygienic Guide* states that eye irritation can occur at the TLV.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for maleic anhydride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid or liquid maleic anhydride or liquids containing maleic anhydride.

- Clothing contaminated with maleic anhydride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of maleic anhydride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the maleic anhydride, the person performing the operation should be informed of maleic anhydride's hazardous properties.
- Non-impervious clothing which becomes contaminated with maleic anhydride should be removed promptly and not reworn until the maleic anhydride is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid maleic anhydride or liquids containing maleic anhydride contacting the eyes.
- Where there is any possibility of exposure of an employee's body to solid or liquid maleic anhydride or liquids containing maleic anhydride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Where there is any possibility that employees' eyes may be exposed to solid or liquid maleic anhydride or liquids containing maleic anhydride, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with maleic anhydride should be promptly washed or showered with soap or mild detergent and water to remove any maleic anhydride.
- Employees who handle solid or liquid maleic anhydride or liquids containing maleic anhydride should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to maleic anhydride may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of polyester resins for automobile bodies, structural building panels, molded boats, and chemical storage tanks	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during manufacture of fumaric acid (as food acidulant) and polyester; use in manufacture of alkyld resins as enamels, interior flat finishes, automotive finishes, printing inks, reactive plasticizers, and marine paints and varnishes	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of detergents and lubricating additives as dispersant and wetting agent; use in manufacture of drying oils	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of tall oil resins as general coating and industrial dip cotaing; use in manufacture of terpene resins as shellac substitutes, in aniline inks, as protective coatings on paper, in metal foil, cellulose films, and natural and synthetic fiber	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of chlorendic anhydride for fire-retardant polyester resins, as expoxy hardener, component of military paints, manufacture of extreme pressure lubricants; and use in organic synthesis and in production of chemical intermediates	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If maleic anhydride gets into the eyes, wash eyes immediately with copious amounts of water, lifting the lower and upper lids occasionally. If irritation or other eye problems are present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If maleic anhydride gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If maleic anhydride or liquids containing maleic anhydride penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of maleic anhydride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When maleic anhydride has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If maleic anhydride is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. Large quantities should be collected in the most convenient and safe manner for reclamation or disposal in a secured sanitary landfill.

• Waste disposal methods:

Maleic anhydride may be disposed of:

1. By making packages of maleic anhydride in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving maleic anhydride in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. By placing maleic anhydride in closed containers and depositing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Maleic Anhydride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Maleic Anhydride," *Hygienic Guide Series*, Detroit, Michigan, 1970.

• Dickens, F., and Jones, H. E. H.: "Further Studies on the Carcinogenic and Growth-Inhibitory Activity of Lactones and Related Substances," *British Journal of Cancer*, 17:100-108, 1963.

• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-88, Maleic Anhydride*, Washington, D.C., 1962.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

RESPIRATORY PROTECTION FOR MALEIC ANHYDRIDE

Condition	Minimum Respiratory Protection* Required Above 0.25 ppm
Particulate or Vapor Concentration	
12.5 ppm or 50 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
250 ppm or 1000 mg/m³ or less	A powered air-purifying respirator with an organic vapor cartridge and a high efficiency particulate filter and a full facepiece, helmet, or hood.
500 ppm or 2000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 500 ppm or 2000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a full facepiece providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

824

Occupational Health Guideline for Manganese

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Mn
- Synonyms: None
- Appearance: Gray solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for manganese is a ceiling level of 5 milligrams of manganese per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Manganese can affect the body if it is inhaled. Manganese can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation of fumes with high concentrations of manganese and its oxides may bring about "metal fume fever." Symptoms of metal fume fever are chills and fever, upset stomach, vomiting, dryness of the throat, cough, weakness, and aching of the head and body. Symptoms often occur several hours after exposure to fumes and usually last for only a day.

2. Long-term Exposure: Prolonged or repeated exposure to manganese may affect the nervous system with difficulty in walking and balancing, weakness or cramps in the legs, hoarseness of the voice, trouble with memory and judgment, unstable emotions or unusual irritability. If high exposure continues, a person may have poor coordination, difficulty in speaking clearly, or shaking or tremor of the arms or legs. A person may also have hallucinations or uncontrollable laughter or crying. The respiratory system may be affected by a condition known as "manganese pneumonia," which may result in symptoms and signs of coughing, fever, chills, general aching of the body, chest pain, and other common signs of pneumonia.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to manganese.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to manganese at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of alcoholism, psychiatric, neurologic, or pulmonary diseases or liver dysfunction would be expected to be at increased risk from exposure. Examination of the respiratory tract, hemopoietic system, and kidneys should be stressed.

—14" x 17" chest roentgenogram: Manganese causes pneumonitis or metal fume fever. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Manganese is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

—A complete blood count: Manganese has been reported to cause blood changes. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Urinalysis: Since kidney damage has been observed in humans exposed to manganese, a urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

805

sediment. Determination of manganese level in urine may be helpful in assessing exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

• **Summary of toxicology**

Inhalation of manganese dust or fume primarily affects the central nervous system; high concentrations cause the influenza-like illness termed manganese pneumonitis. Manganese acts either as a direct neurotoxin, or it adversely affects certain neuroenzymes. Manganese fume causes a disease quite similar to Parkinsonism after 6 months to 2 years of exposure. Initially there is headache; asthenia; restless sleep or somnolence; change in personality with psychomotor instability associated with restlessness, irritability, and a tendency to either cry or laugh inappropriately. This is followed by an intermediate phase with visual hallucinations, double vision; impaired hearing; uncontrollable impulses; mental confusion; euphoria; and normal reaction to painful stimuli. In the advanced phase, the subject exhibits possible anemia; excessive salivation; disorders of the basal ganglia of Parkinsonian type, such as mask-like facies, muscle weakness, muscle rigidity, tremor of the uppper extremities and head, and impaired gait. High concentrations of manganese dust produce fever and chills similiar to mental fume fever. During human exposure to manganese fume there is dryness and irritation of the throat, a sweet or metallic taste followed by substernal tightness, constriction in the chest, and a dry cough. Several hours following exposure the subject develops chills, lassitude, malaise, fatigue, frontal headache, low back pain, muscle cramps, and occasionally blurred vision, nausea, and vomiting. Physical examination reveals fever, perspiration, dyspnea, rales throughout the chest, and tachycardia; in some instances there has been a reversible reduction in pulmonary vital capacity. Leukopenia has been reported in 4 out of 16 cases of manganese poisoning, although there is no convincing evidence that any changes in the blood should be regarded as specific or diagnostic of manganism.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 54.94
2. Boiling point (760 mm Hg): 2097 C (3806 F)
3. Specific gravity (water = 1): 7.2
4. Vapor density (air = 1 at boiling point of manganese): Data not available
5. Melting point: 1245 C (2273 F)
6. Vapor pressure at 1227 C (2240 F): 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Not pertinent
8. Evaporation rate (butyl acetate = 1): Not pertinent
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Data not available

• **Warning properties**

Grant states that "local contact of manganese with the cornea does not appear to be a problem industrially."

MONITORING AND MEASUREMENT PROCEDURES

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of manganese. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of manganese in a filter, followed by atomic absorption spectrophotometric analysis. An analytical method for manganese is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to manganese may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during welding operations	Local exhaust ventilation; respiratory protective devices; dilution ventilation
Liberation during casting of molten ferro-manganese	Local exhaust ventilation
Liberating during bagging of manganese ore	Local exhaust ventilation; respiratory protective devices and dust suppression with water
Liberation during mixing and pressing of dry battery depolarization	Local exhaust ventilation
Liberation during grinding of ore containing manganese	Local exhaust ventilation; respiratory protective devices and dust suppression with water
Liberation during arc burning of manganese-hardened steel in repair and manufacture programs	Local exhaust ventilation; respiratory protective devices; dilution ventilation
Liberation from top of submerged arc electric furnace	General dilution ventilation and process enclosure, if possible
Liberation of dust during ore extraction	General dilution ventilation; respiratory protective devices
Liberation during metal finishing operations of high manganese steel	Local exhaust ventilation; respiratory protective equipment
Liberation of dust during crushing of ferro-manganese metal prior to shipment; during dumping, weighing, and mixing operations in ceramics and glass manufacture for pigmentation and coloration purposes	Local exhaust ventilation; respiratory protective equipment
Liberation from formulation of proprietary mixtures for paint and varnish manufacture	Local exhaust ventilation; respiratory protective equipment
Liberation of dioxide and sulfate during manufacture and application of fertilizers	Local exhaust ventilation
Liberation of dust during manufacture of manganese soap and wood preservatives; manufacture of safety matches, signal flares, fire-works, and strikers; during mixing and kiln operations of brick manufacture	Local exhaust ventilation
Liberation of dusts during manufacture and utilization of oxidation catalysts, such as hopcalite, manganese acetate, and naphthenate	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Breathing**

If a person breathes in large amounts of manganese, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When manganese has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If manganese is spilled, the following steps should be taken:

1. Remove all ignition sources.

807

2. Ventilate area of spill.

2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Manganese may be disposed of:

1. By making packages of manganese in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving manganese in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

ADDITIONAL INFORMATION

To find additional information on manganese, look up manganese in the following documents:

• Medical Surveillance for Chemical Hazards

• Respiratory Protection for Chemical Hazards

• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Manganese," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Manganese," *Hygienic Guide Series*, Detroit, Michigan, 1962.

• *American National Standard Acceptable Concentrations – Manganese*: ANSI-Z37.6-1948, American National Standards Institute, Inc., New York, 1948.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Dow Chemical Company: *Material Safety Data Sheet – Manganese*, Midland, Michigan, 1975.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 29 – Manganese*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1973.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Penalver, R.: "Manganese Poisoning," *Industrial Medicine and Surgery*, 24:1-7, 1955.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, L. T., et al.: "Clinical Manganism and Exposure to Manganese in the Production and Processing of Ferromanganese Alloy," *Journal of Occupational Medicine*, 15:101-109, 1973.

RESPIRATORY PROTECTION FOR MANGANESE

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Dust or Mist Concentration	
25 mg/m³ or less	Any dust and mist respirator, except single-use respirators.
50 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator.
Dust, Mist, or Fume Concentration	
50 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
250 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
10,000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Inorganic Mercury

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Hg
- Synonyms: Quicksilver
- Appearance and odor: Silvery, mobile, odorless liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for mercury is a ceiling level of 0.1 milligram of mercury per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be changed to 0.05 mg/m^3 averaged over an eight-hour work shift. The NIOSH Criteria Document for Inorganic Mercury should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Mercury can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Inhaled mercury vapor may cause headaches, cough, chest pains, chest tightness, and difficulty in breathing. It may also cause chemical pneumanitis. In addition, it may cause soreness of the mouth, loss of teeth, nausea, and diarrhea. Liquid mercury may irritate the skin.

2. Long-term Exposure: Repeated or prolonged exposure to mercury liquid or vapor causes effects which develop gradually. The first effects to occur are often fine shaking of the hands, eyelids, lips, tongue, or jaw. Other effects are allergic skin rash, headache, sores in the mouth, sore and swollen gums, loose teeth, insomnia, excess salivation, personality change, irritability, indecision, loss of memory, and intellectual deterioration.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to mercury.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to mercury at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of allergies or known sensitization to mercury, chronic respiratory disease, nervous system disorders, or kidney disease would be expected to be at increased risk from exposure. Examination for any signs or symptoms of unacceptable mercury absorption such as weight loss, insomnia, tremors, personality changes, or other evidence of central nervous system involvement, as well as evidence of kidney damage, should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney damage has been observed in humans exposed to mercury, a urinalysis should be obtained to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centrifuged sediment. Determination of mercury level in urine may be helpful in assessing extent of absorption.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

800

• **Summary of toxicology**

Acute exposure to mercury at high levels causes severe respiratory irritation, digestive disturbances, and marked renal damage; chronic mercurialism, the form of intoxication most frequently caused by occupational exposure, is characterized by neurologic and psychic disturbances, anorexia, weight loss, and stomatitis. Skin absorption of inorganic mercury probably adds to the toxic effects of vapor inhalation. Intraperitoneal injection of metallic mercury in rats has produced sarcomas. Exposure of humans to mercury vapor in concentrations of 1.2 to 8.5 mg/m³ causes cough, chest pain and dyspnea, leading to bronchitis and pneumonitis. Metallic mercury readily vaporizes at room temperature, and the vapor has no warning properties. At low levels, the onset of symptoms resulting from chronic exposure is insidious; fine tremors of the hands, eyelids, lips and tongue are often the presenting complaint. Coarse jerky movements and incoordination may interfere with the fine movements considered necessary for writing and eating. Psychic disturbances such as insomnia, irritability, and indecision occur; headache, excessive fatigue, anorexia, digestive disturbances, and weight loss are common; stomatitis with excessive salivation is sometimes severe; muscle weakness has been reported. Proteinuria may occur, but is relatively infrequent. Mercury has been reported to be capable of causing sensitization dermatitis. Examination of urine for mercury may be of value. There is no "critical" level of mercury in urine above or below which poisoning cannot be seen. Various observers have suggested from 0.1 to 0.5 mg of Hg/l of urine as having clinical significance. Mercury, particularly organic forms, is known to adversely affect the fetus if the mother is exposed during pregnancy.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 200.6
2. Boiling point (760 mm Hg): 357 C (674 F)
3. Specific gravity (water = 1): 13.5
4. Vapor density (air = 1 at boiling point of mercury): Not applicable
5. Melting point: −39 C (-38 F)
6. Vapor pressure at 20 C (68 F): 0.0012 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.002
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with acetylene, acetylene products, or ammonia gases may form solid products that are sensitive to shock and which can initiate fires of combustible materials.
3. Hazardous decomposition products: None
4. Special precautions: Mercury can attack copper and copper alloy materials.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: Mercury is odorless.
2. Eye Irritation Level: Grant states that "when mercury metal droplets are in the epithelium, rather than the corneal stroma or anterior chamber, they are extruded rapidly with little reaction, as was reported in a patient who was sprayed forcefully with metallic mercury and was observed to have many fine silvery globules beneath the epithelium of the cornea . . . .

"Mercury metal in contact with the conjunctiva has been shown in rabbits to be absorbed and ultimately to be detectable in the urine. While in contact with the conjunctiva, metallic mercury produced no clinical signs of conjunctivitis, but histologically an inflammatory reaction has been demonstrable. External contact with mercury vapor has repeatedly been observed to induce a characteristic discoloration of the crystalline lens (mercurialentis)." Mercurialentis also is caused by systemic poisoning "from absorption of mercury vapor through the respiratory tract, the skin, and the gastrointestinal tract."

For the purposes of this guideline, mercury is not treated as an eye irritant.

3. Evaluation of Warning Properties: Mercury has no warning properties, according to the *Hygienic Guide*.

MONITORING AND MEASUREMENT PROCEDURES

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of mercury. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of mercury with a three-section solid phase sampler, followed by analysis with an atomic absorption spectrophotometer. An analytical method for mercury is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may

be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid mercury.
- If employees' clothing may have become contaminated with mercury, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with mercury should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of mercury from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the mercury, the person performing the operation should be informed of mercury's hazardous properties.
- Non-impervious clothing which becomes contaminated with mercury should be removed promptly and not reworn until the mercury is removed from the clothing.

SANITATION

- Workers subject to skin contact with liquid mercury should wash with soap or mild detergent and water any areas of the body which may have contacted mercury at the end of each work day.
- Skin that becomes contaminated with mercury should be promptly washed or showered with soap or mild detergent and water to remove any mercury.
- Eating and smoking should not be permitted in areas where mercury is handled, processed, or stored.
- Employees who handle mercury should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to mercury may occur and control methods which may be effective in each case:

Operation	Controls
Use as a liquid cathode in electrolytic production of chlorine and caustic soda from brine	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment; meticulous housekeeping
Use during manufacture and repair of industrial and medical apparatus; use during manufacture of inorganic and organic compounds for use as pesticides, antiseptics, germicides, and skin preparations, and miscellaneous applications as chemical intermediates, preservatives, and pigments	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment; meticulous housekeeping
Use in preparation of amalgams for use in tooth restorations, chemical processing, and molding operations; use during manufacture of mildew-proof paints and marine antifouling agents	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of organic mercurials; use in manufacture of batteries, lamps, and power tubes; manufacture of tungsten-molybdenum wire and rods; use in manufacture of inorganic salts for use as catalysts in production of urethanes, vinyl chloride monomers, anthraquinone derivatives, and other miscellaneous chemicals	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment; meticulous housekeeping

Operation	Controls
Use as a chemical intermediate and in the manufacture of felt; as a flotation agent in manufacture of bowling balls; use as a laboratory reagent or as a working fluid in instruments	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment; meticulous housekeeping
Use as a conductor during construction and maintenance of military and nuclear power systems, in mercury-stem boilers, and in air-rectifiers	General dilution ventilation; personal protective equipment; meticulous housekeeping
Liberation during roasting and smelting operations	General dilution ventilation; local exhaust ventilation
Use in manufacture of explosives; in preparation of amalgams for use in artificial jewelry	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment; meticulous housekeeping
Use in manufacture of compounds for pulp and paper industry as controls for biological growths	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberation during mining and subsequent refining of ore containing cinnabar	General dilution ventilation; personal protective equipment; meticulous housekeeping

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid mercury gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid mercury gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid mercury penetrates through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of mercury, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When large quantities of mercury have been swallowed or mercury has been swallowed repeatedly and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If mercury is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material for reclamation using commercially available mercury vapor depressants or specialized vacuum cleaners.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Mercury as Hg," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- American Industrial Hygiene Association: "Mercury and Its Inorganic Compounds," *Hygienic Guide Series*, Detroit, Michigan, 1966.
- *American National Standard Acceptable Concentrations - Mercury*: ANSI-Z37.8-1972, American National Standards Institute, Inc., New York, 1972.
- Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.
- Danziger, S. J., and Possick, P. A.: "Metallic Mercury Exposure in Scientific Glassware Manufacturing Plants," *Journal of Occupational Medicine*, 15:1, pp. 15-20, 1973.
- Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and

Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• *Mercury Poisoning*, Occupational Health Technical Information Service, California State Department of Public Health, 1963.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Inorganic Mercury*, HEW Publication No. HSM 73-11024, GPO No. 017-033-00022, U.S. Government Printing Office, Washington, D.C., 1973.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Vostal, J. J., and Clarkson, T. W.: "Mercury as an Environmental Hazard," *Journal of Occupational Medicine*, 15:649-656, 1973.

• "Working with Mercury in Industry," *U.S. Department of Health, Education, and Welfare Pamphlet*, U.S. Government Printing Office, Washington, D.C., 1973.

RESPIRATORY PROTECTION FOR INORGANIC MERCURY

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate or Vapor Concentration	
1 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
28 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 28 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against mercury. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methoxychlor

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{16}H_{15}Cl_3O_2$
- Synonyms: 2,2-Bis(p-methoxyphenyl)-1,1,1-trichloroethane
- Appearance and odor: Colorless to tan solid with a slight fruity odor (or emulsifiable solution in heavy aromatic naphtha).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methoxychlor is 15 milligrams of methoxychlor per cubic meter of air (mg/m³) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for methoxychlor a Threshold Limit Value of 10 mg/m³.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methoxychlor can affect the body if it is inhaled. It can also affect the body if it is swallowed.

- **Effects of overexposure**

There are no reported effects in humans from exposure to methoxychlor. Animal experiments have shown that this chemical may produce trembling, convulsions, and mild kidney and liver damage. Women may be at increased risk.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methoxychlor.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methoxychlor at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methoxychlor exposure.

—Liver disease: Methoxychlor causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Methoxychlor causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Convulsive and other neurologic disorders: Methoxychlor causes convulsions and other neurologic disorders in animals. Persons with a history of such disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Methoxychlor affects the nervous system and causes convulsions in animals. The oral LD50 in rats is 6 g/kg; the fatal oral dose in humans is estimated to be 450 g. Although some liver tumors were observed in rats fed up to 2000 ppm in the diet, it is not possible to evaluate adequately the carcinogenicity of methoxychlor due to inadequate reporting of these data; three other feeding studies produced no evidence of carcinogenesis. Dogs fed a daily diet containing 4 g/kg body weight developed signs of chlorinated hydrocarbon intoxication, including fasciculations, tremor, hyperesthesia, tonic seizures, and tetanic convulsions after 5 to 8 weeks; most of the dogs died within 3 weeks after onset of effects. Rabbits given 200 mg/kg orally per day died

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

835

September 1978

after 4 to 5 doses; autopsy findings included mild liver damage and nephrosis. In mice given 5 mg orally over 3 days and in rats given 20 mg, there was a uterotrophic effect manifested as a marked increase in weight of the uterus. There are no reported effects in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 345.7
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): 1.41
  4. Vapor density (air = 1 at boiling point of methoxychlor): Not applicable
  5. Melting point: 78 or 86 C (172 or 187 F) (dimorphic)
  6. Vapor pressure at 20 C (68 F): Very low
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.01
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None hazardous
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released when methoxychlor decomposes.
  4. Special precautions: Methoxychlor will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: Not applicable
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Not applicable
  4. Extinguishant: For solids: Dry chemical, water, carbon dioxide, and foam
- **Warning properties**

Since the vapor pressure of this substance is very low, and since methoxychlor decomposes upon heating, warning properties are not considered.

Methoxychlor is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for methoxychlor is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with methoxychlor or liquids containing methoxychlor.
- Non-impervious clothing which becomes contaminated with methoxychlor should be removed promptly and not reworn until the methoxychlor is removed from the clothing.

SANITATION

- Skin that becomes contaminated with methoxychlor should be promptly washed or showered with soap or mild detergent and water to remove any methoxychlor.
- Employees who handle methoxychlor or liquids containing methoxychlor should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methoxychlor may occur and control methods which may be effective in each case:

Operation	Controls
Use as an agricultural insecticide on fruits, vegetables, foliage, crops, and ornamentals; agricultural premises; and animal treatment	Personal protective equipment
Liberation during formulation and manufacture for use as an agricultural insecticide	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Skin Exposure**

If methoxychlor or liquids containing methoxychlor get on the skin, wash the contaminated skin using soap or mild detergent and water. Be sure to wash the hands well before eating or smoking and at the end of work.

• **Breathing**

If a person breathes in large amounts of methoxychlor, move the exposed person to fresh air at once.

• **Swallowing**

When methoxychlor or liquids containing methoxychlor have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If methoxychlor is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquid containing methoxychlor should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Methoxychlor may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methoxychlor," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• International Agency for Research on Cancer: *Some Organochlorine Pesticides, Vol. 5 in IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man*, Lyon, France, 1974.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• Tegeris, A. S., et al.: "Methoxychlor Toxicity," *Archives of Environmental Health*, 13:776-787, 1966.

• Tullner, W. W.: "Uterotrophic Action of the Insecticide Methoxychlor," *Science*, 133:647-648, 1961.

RESPIRATORY PROTECTION FOR METHOXYCHLOR

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Particulate Concentration	
150 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust, mist, and fume filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust, mist, and fume filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust, mist, and fume filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
7500 mg/m³ or less	A powered chemical cartridge respirator with an organic vapor cartridge and a high efficiency particulate filter, including pesticide respirators which meet the requirements of this class. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 7500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for o-Methylcyclohexanone

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_7H_{12}O$
- Synonyms: 2-Methylcyclohexanone
- Appearance and odor: Colorless liquid with a weak peppermint odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for o-methylcyclohexanone is 100 parts of o-methylcyclohexanone per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 460 milligrams of o-methylcyclohexanone per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for o-methylcyclohexanone a Threshold Limit Value of 50 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

o-Methylcyclohexanone can affect the body if it is inhaled, comes in contact with the eyes or skin, or swallowed.

- **Effects of overexposure**

There are no reported effects of human exposure to o-methylcyclohexanone. In animal experiments o-methylcyclohexanone has caused drowsiness, unconsciousness, irritation of the eyes, nose, and throat, and skin rash.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to o-methylcyclohexanone.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to o-methylcyclohexanone at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from o-methylcyclohexanone exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of o-methylcyclohexanone might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Although o-methylcyclohexanone is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although o-methylcyclohexanone is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: o-Methylcyclohexanone is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Neurologic disorders: By analogy to effects observed in animals, the nervous system may be adversely affected by o-methylcyclohexanone.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

o-Methylcyclohexanone vapor irritates the eyes and mucous membranes in animals; at high concentrations it

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

causes narcosis. Several species of animals exposed to 3500 ppm suffered marked irritation of the mucous membranes, became incoordinated after 15 minutes of exposure, and prostrate after 30 minutes. Repeated daily application to the skin of rabbits of large doses of the liquid caused irritation of the skin, tremors, narcosis, and death. Exposure of mice to 450 ppm for an unspecified time period resulted in irritation of the eyes and respiratory tract. Repeated or prolonged contact of the liquid with the skin may cause dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 112.2
2. Boiling point (760 mm Hg): 165 C (329 F)
3. Specific gravity (water = 1): 0.93
4. Vapor density (air = 1 at boiling point of o-methylcyclohexanone): 3.9
5. Melting point: −14 C (6.8 F)
6. Vapor pressure at 20 C (68 F): 1 mm Hg (approximately)
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: None hazardous
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving o-methylcyclohexanone.
4. Special precautions: o-Methylcyclohexanone will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 47.8 C (118 F) (Closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Foam, dry chemical, carbon dioxide

- **Warning properties**

1. Odor Threshold. No quantitative information is available concerning the odor threshold of o-methylcyclohexanone.
2. Irritation Level: According to Patty, eye and respiratory irritation may occur below the permissible exposure limit.
3. Evaluation of Warning Properties: Through its irritant effects, o-methylcyclohexanone can be detected at the permissible exposure limit. For the purposes of this guideline, therefore, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for o-methylcyclohexanone is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid o-methylcyclohexanone.
- Clothing wet with o-methylcyclohexanone should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of o-methylcyclohexanone from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the o-methylcyclohexanone, the person performing the operation should be informed of o-methylcyclohexanone's hazardous properties.
- Non-impervious clothing which becomes contaminated with o-methylcyclohexanone should be removed

tration and Cutaneous Application," *Journal of Industrial Hygiene and Toxicology*, 25:199-214, 1943.
• Treon, J. F., et al.: "The Physiological Response of Rabbits to Cyclohexane, Methylcyclohexane, and Certain Derivatives of These Compounds. II. Inhalation," *Journal of Industrial Hygiene and Toxicology*, 25:323-347, 1943.

RESPIRATORY PROTECTION FOR o-METHYLCYCLOHEXANONE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2500 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

promptly and not reworn until the o-methylcyclohexanone is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid o-methylcyclohexanone may contact the eyes.

SANITATION

• Skin that becomes contaminated with o-methylcyclohexanone should be promptly washed or showered with soap or mild detergent and water to remove any o-methylcyclohexanone.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to o-methylcyclohexanone may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in plastic industry; manufacture of lacquers and varnishes; as a co-solvent with cyclohexanone	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in leather industry; use as a rust remover	Process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid o-methylcyclohexanone gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid o-methylcyclohexanone gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid o-methylcyclohexanone soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of o-methylcyclohexanone, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When o-methylcyclohexanone has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If o-methylcyclohexanone is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and reclaimed or atomized in a suitable combustion chamber. o-Methylcyclohexanone should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of o-methylcyclohexanone vapors are permitted.

• Waste disposal methods:

o-Methylcyclohexanone may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "o-Methylcyclohexanone," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Treon, J. F., et al.: "The Physiological Response of Rabbits to Cyclohexane, Methylcyclohexane, and Certain Derivatives of These Compounds. I. Oral Adminis-

Occupational Health Guideline for 5-Methyl-3-Heptanone

INTRODUCTION

This guideline is inte::ded as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_8H_{16}O$
- Synonyms: Ethyl sec-amyl ketone; ethyl amyl ketone; amyl ethyl ketone
- Appearance and odor: Colorless liquid with a mild, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 5-methyl-3-heptanone is 25 parts of 5-methyl-3-heptanone per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 130 milligrams of 5-methyl-3-heptanone per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

5-Methyl-3-heptanone can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: 5-Methyl-3-heptanone may irritate the eyes, nose, and throat, and may cause headache, and dizziness. At very high air concentrations, the vapor may cause unconsciousness in a short time.
2. Long-term Exposure: Prolonged or repeated skin contact may cause dryness and irritation of the skin.
3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 5-methyl-3-heptanone.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 5-methyl-3-heptanone at potentially hazardous levels:
1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 5-methyl-3-heptanone exposure.

—Kidney disease: Although 5-methyl-3-heptanone is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 5-methyl-3-heptanone might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Liver disease: Although 5-methyl-3-heptanone is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Skin disease: 5-Methyl-3-heptanone is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.
2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

There is local irritation of tissues by solvent effect of 5-methyl-3-heptanone on lipids. Central nervous system depression may occur on exposure to high concentrations, producing narcosis. No chronic effects are reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 128

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

8:13

2. Boiling point (760 mm Hg): 159 C (318 F)
3. Specific gravity (water = 1): 0.82
4. Vapor density (air = 1 at boiling point of 5-methyl-3-heptanone): 4.4
5. Melting point: −57 C (−70 F)
6. Vapor pressure at 20 C (68 F): 2 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.26
8. Evaporation rate (butyl acetate = 1): 0.26

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving 5-methyl-3-heptanone.
4. Special precautions: None

• **Flammability**

1. Flash point: 43.3 C (110 F) (Tag closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Carbon dioxide, dry chemical, or foam

• **Warning properties**

1. Odor Threshold: The *Documentation of TLV's* reports that Shell Chemical Corporation determined the odor threshold to be 6 ppm.
2. Irritation Levels: According to the *Documentation of TLV's*, "Shell Chemical Corporation presented the following observations in respect to sensory responses by unconditioned personnel during or following 5-minute exposures to the vapor: . . . 50% Threshold, eye irritation 50 ppm 50% Threshold, nose irritation 50 ppm"

The irritation of the nose and eyes is, according to the *Documentation of TLV's*, transient.

3. Evaluation of Warning Properties: Since 5-methyl-3-heptanone has an odor threshold which is lower than the permissible exposure limit, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of 5-methyl-3-heptanone vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 5-methyl-3-heptanone may be used. An analytical method for 5-methyl-3-heptanone is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).
number PB 245 851).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to protect any area of the body which may come in contact with liquid 5-methyl-3-heptanone.

• Clothing wet with 5-methyl-3-heptanone should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 5-methyl-3-heptanone from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 5-methyl-3-heptanone, the person performing the operation should be informed of 5-methyl-3-heptanone's hazardous properties.

• Non-impervious clothing which becomes wet with 5-methyl-3-heptanone should be removed promptly and not reworn until the 5-methyl-3-heptanone is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid 5-methyl-3-heptanone may contact the eyes.

SANITATION

• Skin that becomes wet with 5-methyl-3-heptanone should be promptly washed or showered to remove any 5-methyl-3-heptanone.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 5-methyl-3-heptanone may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during spray application of resinous and lacquer surface coatings	Local exhaust ventilation; personal protective equipment
Liberation during subdivision of large quantities of ethyl amyl ketone or compounds containing it	General dilution ventilation; personal protective equipment
Use in preparation of perfumes	Local exhaust ventilation; personal protective equipment
Use as a specialized solvent in cleaning operations	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 5-methyl-3-heptanone gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 5-methyl-3-heptanone gets on the skin, promptly flush the contaminated skin with water. If 5-methyl-3-heptanone soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is evidence of skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of 5-methyl-3-heptanone, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 5-methyl-3-heptanone has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the affected person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 5-methyl-3-heptanone is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. 5-Methyl-3-heptanone should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of 5-methyl-3-heptanone vapors are permitted.

• Waste disposal methods:

5-Methyl-3-heptanone may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Ethyl sec-Amyl Ketone," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Shell Chemical Company: *Material Safety Data Sheet - Ethyl Amyl Ketone.*

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR 5-METHYL-3-HEPTANONE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
3000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 3000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3COOCH_3
- Synonyms: Acetic acid methyl ester; methyl acetic ester; methyl ethanoate
- Appearance and odor: Colorless liquid with a fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl acetate is 200 parts of methyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 610 milligrams of methyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to methyl acetate may cause irritation of the nose, throat, and eyes. Headache, drowsiness, and unconsciousness are also possible. (Several cases of disturbance of vision have been reported from overexposure to this chemical).

2. Long-term Exposure: Prolonged overexposure may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methyl acetate exposure.

—Chronic respiratory disease. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Methyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although methyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although methyl acetate is not known as a kidney toxin in humans, the importance of this organ in the excretion of certain chemicals and their metabolites should be considered before exposing persons with impaired kidney function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The vapor of methyl acetate is mildly irritating to the upper respiratory tract and, in higher concentrations, to the eyes. Upon absorption, methyl acetate may be hydrolyzed with the liberation of methanol. The systemic effects, especially the chronic effects, may therefore be similar to those of methanol, and could include atrophy of the optic nerve. Animals exposed to concentrations of approximately 10,000 ppm showed narcosis leading to death in some. Chronic poisoning of animals

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

by inhalation resulted in pulmonary edema and changes in liver, kidney, and myocardium. Liquid methyl acetate in the eye causes inflammation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 74
  2. Boiling point (760 mm Hg): 57 C (135 F)
  3. Specific gravity (water = 1): 0.94
  4. Vapor density (air = 1 at boiling point of methyl acetate): 2.8
  5. Melting point: −98 C (−144 F)
  6. Vapor pressure at 20 C (68 F): 173 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 24.5
  8. Evaporation rate (butyl acetate = 1): 11.8
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methyl acetate.
  4. Special precautions: None
- **Flammability**
  1. Flash point: −10 C (14 F) (closed cup)
  2. Autoignition temperature: 502 C (935 F)
  3. Flammable limits in air, % by volume: Lower: 3.1; Upper: 16
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Summer and May report that the odor threshold of methyl acetate is 200 ppm.
  2. Eye Irritation Level: According to Grant, "the vapor at a concentration of 10,000 ppm in air causes irritation of the eyes, nose, and throat in human beings, also in cats." Sax also reports that "the irritant concentration is about 10,000 ppm."
  3. Evaluation of Warning Properties: Since the odor threshold of methyl acetate is at the TLV, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- Method

Sampling and analyses may be performed by collection of methyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl acetate may be used. An analytical method for methyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).
935).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methyl acetate.
- Clothing wet with liquid methyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl acetate, the person performing the operation should be informed of methyl acetate's hazardous properties.
- Any clothing whicb becomes wet with liquid methyl acetate should be removed immediately and not reworn until the methyl acetate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid methyl acetate may contact the eyes.

SANITATION

- Skin that becomes wet with liquid methyl acetate should be promptly washed or showered to remove any methyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Use during preparation of methyl acetone, including methylacetate, methanol, and acetone for use as solvents	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent for nitrocellulose and cellulose acetate	General dilution ventilation; personal protective equipment
Liberation during use as a chemical intermediate	General dilution ventilation
Use during spraying of lacquers, paint thinners, and vinyl resin coatings; use of paint removers	Local exhaust ventilation; personal protective equipment
Liberation during preparation of paint removers and lacquer solvents	Local exhaust ventilation; general dilution ventilation
Liberation during preparation of methylacetate or recovery as a by-product from wood carbonization	Local exhaust ventilation
Use during preparation of artificial leather	Local exhaust ventilation; personal protective equipment
Liberation during formulation of lacquers, paints, perfumes, and any vinyl resin coatings	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methyl acetate gets on the skin, promptly flush the contaminated skin with water. If methyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When methyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Methyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Methyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Methanol," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• American Industrial Hygiene Association: "Methyl Acetate," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters: Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 21:28-65, 1960.

RESPIRATORY PROTECTION FOR METHYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
10,000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. A powered air-purifying chemical cartridge respirator with an organic vapor cartridge. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Acetylene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_3H_4
- Synonyms: Propyne; allylene
- Appearance and odor: Colorless gas with a sweet odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl acetylene is 1000 parts of methyl acetylene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1650 milligrams of methyl acetylene per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl acetylene can affect the body if it is inhaled.

- **Effects of overexposure**

Overexposure to methyl acetylene may cause the overexposed person to become drowsy and unconscious.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl acetylene.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to methyl acetylene at potentially hazardous levels.

- **Summary of toxicology**

Methyl acetylene primarily affects the central nervous system. The gas has anesthetic properties at concentrations as high as 42,000 ppm, which is below the LC50 value. At 28,700 ppm for 6 hours daily, 5 days a week for 6 months, most animals survived; there was hyperexcitability, ataxia, tremors, and occasional convulsions, all of which subsided rapidly when the 6-hour exposure period ended. Animals that died or were killed on termination of the study showed pulmonary irritation. Neither acute nor chronic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 40.1
  2. Boiling point (760 mm Hg): −23 C (−10 F)
  3. Specific gravity (water = 1): Not applicable
  4. Vapor density (air = 1 at boiling point of methyl acetylene): 1.4
  5. Melting point: −103 C (-153 F)
  6. Vapor pressure at 20 C (68 F): 3800 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Almost insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable (gas)
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents and chlorine may cause fires and explosions. Methyl acetylene forms compounds with copper and copper alloys that are very sensitive to shock.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methyl acetylene.
  4. Special precautions: Copper or copper alloys containing more than 67% copper should not be used in equipment handling methyl acetylene.
- **Flammability**
  1. Flash point: Not applicable
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Lower: 1.7; Upper: 11.7

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

852

4. Extinguishant: Stop flow of gas

• **Warning properties**

1. Odor Threshold: No quantitative information is available.

2. Eye Irritation Level: Methyl acetylene is not known to be an eye irritant.

3. Evaluation of Warning Properties: Since no quantitative information is available relating its warning properties to air concentrations, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for methyl acetylene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid methyl acetylene or from contact with vessels containing methyl acetylene.

• Any clothing which becomes wet with liquid methyl acetylene should be removed immediately and not reworn until the methyl acetylene has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl acetylene may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl acetylene may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during synthesis of pharmaceuticals and aromatics	General dilution ventilation
Liberation during high-temperature, gas-welding operations using MAPP fuel; liberation from decomposition of magnesium carbide by hydrolysis	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of methyl acetylene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If methyl acetylene is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak to disperse gas.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, keep people

away, and repair the leak or allow the cylinder to empty.

• Waste disposal methods:

Methyl acetylene may be disposed of

1. If in small quantities, by allowing gas to escape into open air at a place where there are no ignition sources.
2. If in larger quantities, by allowing the gas to burn under the supervision of qualified personnel.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Acetylene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Horn, H. J., Weir, R. J., and Reese, W. H.: "Inhalation Toxicology of Methylacetylene," *A.M.A. Archives of Industrial Health*, 15:20-25, 1957.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR METHYL ACETYLENE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
11,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 11,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Acetylene-Propadiene Mixture

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_3H_4 isomers
- Synonyms: MAPP gas; methyl acetylene-allene mixture; propyne-allene mixture
- Appearance and odor: Colorless gas with a strong, characteristic, foul odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl acetylene-propadiene mixture is 1000 parts of methyl acetylene-propadiene mixture per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1800 milligrams of methyl acetylene-propadiene mixture per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl acetylene-propadiene mixture can affect the body if it is inhaled or if the liquid comes in contact with the skin or eyes

- **Effects of overexposure**

Overexposure to methyl acetylene-propadiene mixture may cause a person to become drowsy or unconscious. Spilled on the skin or in the eyes, it may also cause frostbite.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl acetylene-propadiene mixture.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to methyl acetylene-propadiene mixture at potentially hazardous levels.

- **Summary of toxicology**

Methyl acetylene-propadiene mixture (MAPP) is a gas with anesthetic properties at high concentrations. Animals exposed for 7 hours daily for 16 weeks to 1000 ppm showed no adverse effects; at 5000 ppm there was only slight decline in body and organ weights of some rats, but no pathological changes. In another study of the main component of the mixture, methyl acetylene, rats survived a single 6-hour exposure at 42,000 ppm, which resulted in anesthesia with rapid recovery; autopsy of the rats 9 days after exposure showed bronchiolitis and pneumonitis. Some human subjects indicated that they could detect 25 ppm, and most could detect 100 ppm. The musty odor was considered to be strong at 1000 ppm and quite objectionable at higher concentrations. No adverse effects have been reported from repeated exposures. The liquefied gas may cause frostbite.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 40
2. Boiling point (760 mm Hg): −37.8 to −20 C (−36 F to −4 F)
3. Specific gravity (water = 1): 0.576 (liquid)
4. Vapor density (air = 1 at boiling point of methyl acetylene-propadiene mixture): 1.48
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Not pertinent
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Much greater than 1

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions. Contact with

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

copper alloys containing more than 6% copper may form explosive copper compounds.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methyl acetylene-propadiene mixture.

4. Special precautions: Methyl acetylene-propadiene mixture will attack some forms of plastics, rubber, and coatings.

• Flammability

1. Flash point: Not applicable (gas)

2. Autoignition temperature: 454 C (850 F)

3. Flammable limits in air, % by volume: Lower: 3.4; Upper: 10.8

4. Extinguishant: Stop flow of gas

• Warning properties

1. Odor Threshold: According to the Biochemical Research Laboratory of the Dow Chemical Company, MAPP has a strong odor which is easily detectable at 100 ppm.

2. Eye Irritation Level: MAPP is not known to be an eye irritant.

3. Evaluation of Warning Properties: Since the odor threshold of MAPP is below the permissible exposure limit, MAPP is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Method

An analytical method for methyl acetylene-propadiene mixture is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid methyl acetylene-propadiene mixture or from contact with vessels containing liquid methyl acetylene-propadiene mixture.

• Any clothing which becomes wet with liquid methyl acetylene-propadiene mixture should be removed immediately and not reworn until the methyl acetylene-propadiene mixture has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl acetylene-propadiene mixture may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl acetylene-propadiene mixture may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from flame hardening, metallizing, brazing, welding and cutting	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• Eye Exposure

If liquid methyl acetylene-propadiene mixture gets into the eyes, flush eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Do not use hot water for eye flushing. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• Skin Exposure

If liquid methyl acetylene-propadiene mixture gets on the skin, immediately flush the contaminated skin with water. If liquid methyl acetylene-propadiene mixture soaks through the clothing, remove the clothing immediately and flush the skin with water. Do not use hc water for skin flushing. If irritation persists after washing, get medical attention.

856

• **Breathing**

If a person breathes in large amounts of methyl acetylene-propadiene mixture, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If methyl acetylene-propadiene mixture is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

• Waste disposal method:

Methyl acetylene-propadiene mixture may be disposed of by burning at a safe location or in a suitable combustion chamber.

• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methylene Acetylene-Propadiene Mixture," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Dow Chemical Company, Biochemical Research Laboratory: *Material Safety Data Sheet – Methyl Acetylene-Propadiene Mixture*, Midland, Michigan, 1964.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Torkelson, T. R., and Rowe, V. K.: "Results of Repeated Inhalation by Laboratory Animals and a Limited Human Sensory Study of a Mixture of Saturated and Unsaturated C_3 and C_4 Hydrocarbons (MAPP Industrial Gas)," *American Industrial Hygiene Association Journal*, 25:554-559, 1964.

• Underwriters' Laboratories: *Methyl Acetylene-Propadiene Mixture.*

RESPIRATORY PROTECTION FOR METHYL ACETYLENE-PROPADIENE MIXTURE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
5000 ppm or less	A gas mask with a chin-style canister providing protection against methyl acetylene-propadiene mixture.
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
20,000 ppm or less	A gas mask with a front- or back-mounted canister providing protection against methyl acetylene-propadiene mixture. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 20,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against methyl acetylene-propadiene mixture. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Acrylate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2=CHCOOCH_3$
- Synonyms: Methyl propenoate
- Appearance and odor: Clear, colorless liquid with a sharp, sweet, and fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl acrylate is 10 parts of methyl acrylate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 35 milligrams of methyl acrylate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl acrylate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to methyl acrylate may cause irritation of the eyes, nose, throat, and lungs. Death may be caused by lung damage from breathing high air levels or from swallowing it.

2. Long-term Exposure: Prolonged contact with the skin or eyes may result in severe damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl acrylate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl acrylate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methyl acrylate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methyl acrylate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Methyl acrylate is absorbed through the skin. It also is a defatting agent and can cause drying and cracking. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although methyl acrylate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although methyl acrylate is not known as a kidney toxin in humans, the importance of this organ in the excretion of certain chemicals and their metabolites should be considered before exposing persons with impaired kidney function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The vapor of methyl acrylate is irritating to the conjunctiva and upper respiratory tract. In moderate concentrations there are characteristic lacrimatory effects in man. Animals exposed to high concentrations show marked irritation of the eyes and of the respiratory tract, leading to pulmonary edema. The lowest concentration of vapor producing no significant effect in rodents is 30 ppm. Prolonged contact with the eye or the skin in animals causes severe damage. Skin sensitiza-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

tion probably occurs, and fatal doses of the liquid are absorbed through the skin of animals exposed for 24 hours. There are no reports of injury to man from long-term exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 86
  2. Boiling point (760 mm Hg): 80 C (176 F)
  3. Specific gravity (water = 1): 0.96
  4. Vapor density (air = 1 at boiling point of methyl acrylate): 2.95
  5. Melting point: −75 C (−103 F)
  6. Vapor pressure at 20 C (68 F): 68.2 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 5.5
  8 Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat and/or lack of appropriate inhibitor concentration can cause methyl acrylate to polymerize violently and burst container.
  2. Incompatibilities: Contact with nitrates and other oxidizing materials, including peroxides and other initiators of polymerization, strong alkalies, and atmospheric moisture may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methyl acrylate.
  4. Special precautions: Inhibitors do not function in absence of air, so inert gas blankets should not be used.
- **Flammability**
  1. Flash point: −7.8 C (18 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Lower: 2.8; Upper: 25
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: The Manufacturing Chemists Association states that most persons can detect the odor of methyl acrylate at 20 ppm. "Odor detection has little practical value in chronic repeated exposures, since most workers become less sensitive to the odor and will tolerate atmospheric concentrations greater than the threshold limits."
  2. Eye Irritation Level: The MCA states that "irritation of the eyes and mucous membranes is experienced beginning at about 75 ppm."
  3. Evaluation of Warning Properties: Methyl acrylate has poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of methyl acrylate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl acrylate may be used. An analytical method for methyl acrylate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid methyl acrylate.
- Clothing wet with liquid methyl acrylate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methyl acrylate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl acrylate, the person performing the operation should be informed of methyl acrylate's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid methyl acrylate, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Any clothing which becomes wet with liquid methyl acrylate should be removed immediately and not reworn until the methyl acrylate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl acrylate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid methyl acrylate should be immediately washed or showered to remove any methyl acrylate.

• Employees who handle liquid methyl acrylate should wash their hands thoroughly before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl acrylate may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of thermoplastic coatings; use in manufacture of acrylic fibers; use in synthesis of higher acrylates; during preparation of adhesives and sealants based on methyl acrylate	Local exhaust ventilation; personal protective equipment
Use during polymerization in aqueous emulsions to produce resins for surface coatings and adhesives; use during polymerization in solutions to produce resins for surface coatings and adhesives	Local exhaust ventilation; personal protective equipment
Use during preparation of amphoteric surfactants for use in hair shampoos	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, titute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methyl acrylate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methyl acrylate gets on the skin, immediately flush the contaminated skin with water. If methyl acrylate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl acrylate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible. Properly trained individuals may assist the affected person by administering 100% oxygen.

• **Swallowing**

When methyl acrylate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl acrylate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Methyl acrylate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Methyl acrylate may be disposed of:
1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill in an area where the odor will not be objectionable.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Acrylate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-79, Methyl Acrylate and Ethyl Acryla Washington, D.C., 1960.*
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Suvorov, A. P.: "Results of Examinations Carried Out on Workers Exposed to Methyl Acrylate," *Gigiena Truda I Professional Nye Zabolenvanioa*, 15:10, pp. 49-50, October 1971.

RESPIRATORY PROTECTION FOR METHYL ACRYLATE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
75 ppm or less	Any supplied-air respirator.** Any self-contained breathing apparatus.**
500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a full facepiece providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Methyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3OH
- Synonyms: Methanol; wood alcohol; Columbian spirits; carbinol
- Appearance and odor: Colorless liquid with a characteristic, pungent odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl alcohol is 200 parts of methyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 260 milligrams of methyl alcohol per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be changed to 200 ppm averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling of 800 ppm averaged over a 15-minute period. The NIOSH Criteria Document for Methyl Alcohol should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

1. Short-term Exposure: Swallowing methyl alcohol or breathing very high concentrations of methyl alcohol may produce headache, weakness, drowsiness, lightheadedness, nausea, vomiting, drunkenness, and irritation of the eyes, blurred vision, blindness, and death. A person may get better and then worse again up to 30 hours later.

2. Long-term Exposure: Prolonged exposure to higher concentrations of methyl alcohol may result in headaches, burning of the eyes, dizziness, sleep problems, digestive disturbances, and failure of vision. Repeated or prolonged skin exposure may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl alcohol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl alcohol at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the skin, liver, kidneys, and eyes should be stressed.

—Skin disease: Methyl alcohol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be susceptible to the effects of this agent.

—Liver function tests: Methyl alcohol may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Kidney disease: Although methyl alcohol has not been proven to be kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Eye disease: Because methyl alcohol may cause optic atrophy and blindness, those with pre-existing eye diseases may be at increased risk from exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. In addition, anyone developing the above-listed conditions or who has been splashed in the eyes with,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

has ingested, or otherwise has been exposed to methyl alcohol should be placed under medical surveillance.

• **Summary of toxicology**

Ingestion of methyl alcohol is a well-known cause of optic neuropathy and may be lethal. Severe acidosis may result from ingestion or high exposures. Animals exposed to vapor concentrations above 8000 to 10,000 ppm show narcotic effects progressing from lethargy, to ataxia, to prostration and death in a state of profound acidosis due in part to the metabolic formation of formaldehyde and formic acid. Occupational exposure to high concentrations of methyl alcohol vapor has been reported to cause death or blindness, usually from working in a confined space. A woman died after exposure for 12 hours to vapor concentrations calculated at 4000 to 13,000 ppm. Chronic poisoning manifested by marked diminution of vision and enlargement of the liver has been reported in a workman exposed at levels of 1200 to 8000 ppm for a period of 4 years. Direct skin contact with methy alcohol may cause dermatitis, erythema, and scaling.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 32
2. Boiling point (760 mm Hg): 64.5 C (148 F)
3. Specific gravity (water = 1): 0.8
4. Vapor density (air = 1 at boiling point of methyl alcohol): 1.1
5. Melting point: −98 C (-144 F)
6. Vapor pressure at 20 C (68 F): 97 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): 5.9

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide and formaldehyde) may be released in a fire involving methyl alcohol.
4. Special precautions: Methyl alcohol will attack some forms of plastics, rubber, and coatings. It may also react with metallic aluminum at high temperatures.

• **Flammability**

1. Flash point: 11 C (52 F) (closed cup)
2. Autoignition temperature: 385 C (725 F)
3. Flammable limits in air, % by volume: Lower: 6.7; Upper: 36
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: May and Summer report that the odor threshold of methyl alcohol (methanol) is 5900 ppm. The AIHA *Hygienic Guide* states that the odor is faint at 2000 ppm.
2. Eye Irritation Level: The *Hygienic Guide* states that irritation occurs only at high concentrations. Grant states that "external contact of methanol with the eye has been alleged to have caused corneal opacities, but this must be far from the rule . . . . By exposure of cats to methanol vapors an attempt has been made to induce vacuoles in the corneal epithelium similar to those produced by other solvents, but this has been unsuccessful."

Browning reports that concentrations ranging from 7500 ppm to 69,000 ppm irritate mucous membranes.

3. Evaluation of Warning Properties: Methyl alcohol (methanol) has poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of methyl alcohol. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of methyl alcohol in an adsorption tube containing silica gel, followed by desorption with water, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl alcohol may be used. An analytical method for methyl alcohol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the

process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methyl alcohol.

• Clothing wet with liquid methyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methyl alcohol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl alcohol, the person performing the operation should be informed of methyl alcohol's hazardous properties.

• Any clothing which becomes wet with liquid methyl alcohol should be removed immediately and not reworn until the methyl alcohol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl alcohol may contact the eyes.

SANITATION

• Skin that becomes wet with liquid methyl alcohol should be promptly washed or showered to remove any methyl alcohol.

• Eating and smoking should not be permitted in areas where liquid methyl alcohol is handled, processed, or stored.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during application of surface coatings such as shellac, wood dyes, nitrocellulose lacquers, water-proofing formulations, and phenolic resins	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent for rotogravure inks, aniline dyes, and duplicator fluids	General dilution ventilation
Liberation during manual application of methanol as a cleaner for coated surfaces, leather, gloves, and metal and resins surfaces prior to further treatment	General dilution ventilation; personal protective equipment
Liberation during manufacture of formaldehyde by oxidation or dehydrogenation	Local exhaust ventilation; general dilution ventilation
Use in plastics industry to produce plasticizers, softening agents, and acrylic resins	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during use as an intermediate in the preparation of methacrylates, methyl chlorides, methyl ethers, dimethyl sulfate, methyl formate, and methyl bromide	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during application as an extractant in industrial chemical processes such as refinery gasoline and oils and purifying pharmaceuticals such as steroids and hormones	Local exhaust ventilation; general dilution ventilation
Use as a solvent in rubber industry	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• Eye Exposure

If methyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• Skin Exposure

If methyl alcohol gets on the skin, promptly flush the contaminated skin with water. If methyl alcohol soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• Breathing

If a person breathes in large amounts of methyl alcohol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• Swallowing

When methyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl alcohol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Methyl alcohol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Methyl alcohol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Methyl Alcohol," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-22, Methyl Alcohol*, Washington, D.C., 1970.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Methyl Alcohol*, HEW Publication No. (NIOSH) 76-148, GPO No. 017-033-00191-0, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Methyl Alcohol*, New York, 1970.

RESPIRATORY PROTECTION FOR METHYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
2000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
10,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
25,000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 25,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Bromide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3Br
- Synonyms: Bromomethane
- Appearance and odor: Colorless liquid or or gas with a chloroform-like odor at high concentrations.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl bromide is a ceiling of 20 parts of methyl bromide per million parts of air (ppm). This may also be expressed as 80 milligrams of methyl bromide per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for methyl bromide from 15 ppm to 5 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl bromide can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Methyl bromide may cause headache, dizziness, nausea, vomiting, blurred vision, slurred speech, and convulsions. High concentrations may cause unconsciousness and death. High concentrations may also cause lung irritation resulting in congestion with coughing, chest pain, and shortness of breath. Lung effects may be delayed in onset. Exposure may also result in kidney damage. The liquid splashed on clothing, gloves, or shoes may be held in close contact with the skin and result in skin burns. Blisters commonly appear after several hours. If the exposure is less severe, an itching skin rash may appear after several days. Contact of liquid methyl bromide with the eyes may cause serious injury.

2. Long-term Exposure: Prolonged or repeated exposure to methyl bromide may cause a variety of symptoms and signs mostly due to injury of the central nervous system. These include visual disturbances, slurred speech, numbness of the arms and legs, confusion, shaking, and unconsciousness. The symptoms may stop within a few days after the termination of exposure or may last for several months. Usually recovery is complete.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl bromide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl bromide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. A careful history and examination of the nervous and respiratory systems should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Methyl bromide may cause human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Methyl bromide is reported to cause pulmonary impairment. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

8C8

basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing.

• **Summary of toxicology**

Methyl bromide gas is a severe pulmonary irritant and neurotoxin. It is also a narcotic at high concentrations. Rats did not survive when exposed to 12,850 ppm for 6 minutes, but did survive following exposure to 260 ppm for 8 hours; the no-effect level on repeated exposure was 16 ppm for all species. There are numerous reports of human intoxication from accidental exposure associated with its use in fire extinguishers and as a fumigant. Estimates of concentrations which have caused human fatalities range from 8000 ppm for a few hours to 60,000 ppm for a brief exposure. The onset of toxic symptoms is usually delayed, and the latent period may be from 30 minutes to several days. Early symptoms include headache, visual disturbances, nausea, vomiting, and malaise. In some cases eye irritation, vertigo, and tremors of the hands have occurred; the tremors may progress to twitchings and finally to convulsions. The onset of dyspnea may herald the development of pulmonary edema. Tubular damage in the kidneys has been observed in fatal cases. Some who recovered from severe intoxication have had persistent central nervous system effects including vertigo, depression, hallucinations, anxiety, and inability to concentrate. The determination of bromide in human blood has been proposed for the purpose of estimating the severity of exposure; in a few cases, levels of 40 mg/100 ml of blood have been associated with gross disability, while levels of 10 mg/100 ml and less have been followed by complete recovery. The procedure has not been sufficiently verified to recommend it for routine monitoring of occupational exposure. Local contact with the eye by the gas or liquid results in transient irritation and conjunctivitis. Repeated splashes of the liquid on the skin cause marked irritation with vesiculation; less severe exposures result in a dry, scaling, itching dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 94.9
2. Boiling point (760 mm Hg): 3.6 C (38.4 F)
3. Specific gravity (water = 1): 1.7
4. Vapor density (air = 1 at boiling point of methyl bromide): 3.3
5. Melting point: −94 C (−137 F)
6. Vapor pressure at 20 C (68 F): 1.83 atm.
7. Solubility in water, g/100 g water at 20 C (68 F): Less than 0.1
8. Evaporation rate (butyl acetate = 1): Greater than 1

• **Reactivity**

1. Conditions contributing to instability: Heat.
2. Incompatibilities: Contact with aluminum or strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen bromide and carbon monoxide) may be released in a fire involving methyl bromide.
4. Special precautions: Liquid methyl bromide will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: None in standard test method
2. Autoignition temperature: 537 C (999 F)
3. Flammable limits in air, % by volume: (Only in presence of high energy ignition source) Lower: 13.5; Upper: 14.5
4. Extinguishant: Stop flow of gas.

• **Warning properties**

1. Odor Threshold: Both Patty and the AIHA *Hygienic Guide* report that methyl bromide has practically no odor. Grant notes, however, that at extremely high concentrations, methyl bromide has a "sweetish, not unpleasant odor."
2. Eye Irritation Level: Grant reports that methyl bromide "causes no immediate irritation of the eyes, . . . even at severely poisonous concentrations." Following a period of several hours after exposure to the gas, however, the victim may "have lacrimation from irritation of the eyes." Grant states that "local contact of methyl bromide with the eye, either as concentrated vapor or as a splash of liquid, has resulted in no more than transient irritation and conjunctivitis in the few cases in which this accident has been observed." He also reports that exposing a rabbit's eye to pure methyl bromide gas for 1-1/2 minutes resulted in an "immediate loss of surface luster, followed in several hours by a loss of corneal epithelium and much edema of the conjunctivae and lids." The cornea became opaque but began clearing within 5 days. Grant notes that this exposure was far more severe than that which would happen by accident.
3. Other Information: Grant reports that methyl bromide causes no immediate irritation of the "nose or respiratory tract, even at severely poisonous concentrations."
4. Evaluation of Warning Properties: Since methyl bromide has virtually no odor and no immediately irritating effects, it has poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of methyl bromide. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Method

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl bromide may be used. An analytical method for methyl bromide is in the *NIOSH* obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22161, under the title "NIOSH Analytical Methods for Set J" (order number PB 263 959).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid methyl bromide.

• Clothing contaminated with liquid methyl bromide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methyl bromide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl bromide, the person performing the operation should be informed of methyl bromide's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid methyl bromide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with liquid methyl bromide should be removed immediately and not reworn until the methyl bromide is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl bromide may contact the eyes.

SANITATION

• Skin that becomes wet with liquid methyl bromide should be immediately washed or showered with soap or mild detergent and water to remove any methyl bromide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl bromide may occur and control methods which may be effective in each case:

Operation	Controls
Use as a space and soil fumigant in agriculture and industry	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in food sterilization for pest control in fruits, vegetables, dairy products, nuts, and grains	General dilution ventilation; local exhaust ventilation
Use in organic synthesis as methylating agent, for preparation of quarternary ammonium compounds and organo-tin derivatives; use as selective solvent in aniline dyes; laboratory procedures	General dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methyl bromide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methyl bromide gets on the skin, immediately flush the contaminated skin with water. If methyl bromide soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl bromide, move the exposed person to fresh air at once. If

breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When methyl bromide has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl bromide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
4. If in the liquid form, allow to vaporize.

• Waste disposal method:

Methyl bromide may be disposed of by burning at a safe location or in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Bromide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Methyl Bromide," *Hygienic Guide Series*, Detroit, Michigan, 1958.

• Butler, E. C. B., et al.: "Methyl Bromide Burns," *British Journal of Industrial Medicine*, 2:30-31, 1945.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hine, C. H.: "Methyl Bromide Poisoning," *Journal of Occupational Medicine*, 11:1-10, 1969.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-35, Methyl Bromide*, Washington, D.C., 1968.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Rathus, E. M., and Landy, P. J.: "Methyl Bromide Poisoning," *British Journal of Industrial Medicine*, 18:53-57, 1961.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955, pp. 15-30.

• Watrous, R. M.: "Methyl Bromide," *Industrial Medicine*, 11:12, pp.575-79, 1942.

RESPIRATORY PROTECTION FOR METHYL BROMIDE

Condition	Minimum Respiratory Protection* Required Above 20 ppm
Gas Concentration	
200 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
1000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Cellosolve

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3OCH_2CH_2OH$
- Synonyms: 2-Methoxyethanol; glycol monomethyl ether; ethylene glycol monomethyl ether; methyl oxitol; Ektasolve; Jeffersol EM
- Appearance and odor: Colorless liquid with a mild, non-residual odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl cellosolve is 25 parts of methyl cellosolve per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 80 milligrams of methyl cellosolve per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl cellosolve can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to methyl cellosolve may cause irritation of the eyes, nose, and throat, drowsiness, weakness, and shaking. Swallowing methyl cellosolve may be fatal.

2. Long-term Exposure: Prolonged or repeated exposure may cause headache, drowsiness, weakness, fatigue, staggering, personality change, and decreased mental ability. Anemia and other blood changes may result.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl cellosolve.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl cellosolve at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system should be stressed.

—A complete blood count: This compound has been shown to affect the hematopoietic system. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Urinalysis: This compound has caused acute kidney damage in animals and in humans after oral ingestion.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Methyl cellosolve exerts its effects primarily on the hematopoietic and central nervous systems, although the vapor is also a mild irritant. Cases of toxic encephalopathy and macrocytic anemia have been reported from industrial exposures that may have been as low as 25 to 75 ppm. Symptoms were headache, drowsiness, lethargy, and weakness. Manifestations of central nervous system instability included ataxia, dysarthria, tremor, and somnolence. These effects are usually reversible. In acute exposures the central nervous system effects were the more pronounced, while prolonged exposure to lower concentrations produced primarily evidence of depression of erythrocyte formation. Anemia may be pronounced. When exposure was re-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

8?3

September 1978

duced to 20 ppm, no further cases occurred. The LC50 for 7-hour exposures of rats was 1480 ppm; death was due to lung and kidney injury. Rabbits exposed to 800 ppm and 1600 ppm for 4 to 10 days showed irritation of the upper respiratory tract and lungs, severe glomerulonephritis, hematuria, and albuminuria. Instilled in rabbit eyes, it caused immediate pain, conjunctival irritation, and slight corneal cloudiness which cleared in 24 hours.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 76.1
  2. Boiling point (760 mm Hg): 124 C (256 F)
  3. Specific gravity (water = 1): 1.0
  4. Vapor density (air = 1 at boiling point of methyl cellosolve): 2.6
  5. Melting point: −85 C (−121 F)
  6. Vapor pressure at 20 C (68 F): 6 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): Approximately 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions. Contact with strong caustics may cause decomposition.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methyl cellosolve.
  4. Special precautions: Methyl cellosolve will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 42 C (107 F) (closed cup)
  2. Autoignition temperature: 285 C (545 F)
  3. Flammable limits in air, % by volume: Lower: 2.5; Upper: 19.8
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold for methyl cellosolve of 60 ppm.
  2. Eye Irritation Level: Grant states that methyl cellosolve, "tested by applying three drops to rabbit eyes, . . . was found to be only slightly irritating, causing only temporary, slight reddening of the conjunctiva." Browning states that the "vapor of methyl cellosolve is irritant to mucous membranes," but does not give concentrations producing this irritation.
  3. Evaluation of Warning Properties: Although the odor threshold of methyl cellosolve is within three times the permissible exposure limit, odor is not considered an adequate warning property. Browning reports that cases of toxic encephalopathy and macrocytic anemia have been reported among workers exposed to concentrations as low as 25 to 75 ppm methyl cellosolve. The latter was present in a solvent mixture including ethanol and cellulose acetate, however.

The AIHA *Hygienic Guide* states that "warning properties, both odor and irritation, are not sufficient to prevent exposure to concentrations which are physiologically significant."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of methyl cellosolve vapors using an adsorption tube with subsequent desorption with methanol in methylene chloride and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl cellosolve may be used. An analytical method for methyl cellosolve is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing

necessary to prevent repeated or prolonged skin contact with liquid methyl cellosolve.

- Clothing contaminated with liquid methyl cellosolve should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methyl cellosolve from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl cellosolve, the person performing the operation should be informed of methyl cellosolve's hazardous properties.
- Where exposure of an employee's body to liquid methyl cellosolve may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with liquid methyl cellosolve and any clothing which becomes wet with liquid methyl cellosolve should be removed immediately and such clothing should not be reworn until the methyl cellosolve is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid methyl cellosolve may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid methyl cellosolve should be immediately washed or showered to remove any methyl cellosolve.
- Employees who handle liquid methyl cellosolve should wash their hands thoroughly before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl cellosolve may occur and control methods which may be effective in each case:

Operation	Controls
Use during spray application or other method involving heat of surface coatings containing solvent, including wood- and wire-coating lacquers, metal coatings, alkyd baking enamels, phenolic varnishes, and epoxy resin coatings	Local exhaust ventilation; personal protective equipment
Use in printing on plastic materials, rotogravure printing, and cellulose acetate pigment printing on textiles	General dilution ventilation; personal protective equipment
Use during non-heat related application of surface coatings containing solvent, including varnishes and lacquers	Local exhaust ventilation; personal protective equipment
Use in manufacture of surface coatings and dyeing agents for stains, lacquers, dyes, and inks	Process enclosure; local exhaust ventilation
Liberation during sealing of moisture-proof cellophane wrappers and packaging	Process enclosure
Liberation during dyeing operations, including cellulose acetate fibers and fabric, rayon, leather dyeing, and wood staining	Process enclosure; general dilution ventilation
Use as an anti-icing agent in JP-4 military jet fuel and as an anti-stall additive in gasoline	General dilution ventilation
Liberation during synthesis of plasticizer and other compounds	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If methyl cellosolve gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If methyl cellosolve gets on the skin, promptly wash the contaminated skin with water. If methyl cellosolve soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of methyl cellosolve, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When methyl cellosolve has been swallowed, get medical attention immediately. If medical attention is not

immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl cellosolve is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Methyl cellosolve should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Methyl cellosolve may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Cellosolve," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Methyl Cellosolve," *Hygienic Guide Series*, Detroit, Michigan, 1970.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Methyl Cellosolve*, New York, 1969.

RESPIRATORY PROTECTION FOR METHYL CELLOSOLVE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
250 ppm or less	Any supplied-air respirator.** Any self-contained breathing apparatus.**
1250 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Methyl Cellosolve Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOCH_2CH_2OCH_3$
- Synonyms: 2-Methoxyethyl acetate; glycol monomethyl ether acetate; ethylene glycol monomethyl ether acetate
- Appearance and odor: Colorless liquid with a mild, ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl cellosolve acetate is 25 parts of methyl cellosolve acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 120 milligrams of methyl cellosolve acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl cellosolve acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

Swallowing a large single dose of methyl cellosolve acetate might be fatal. Swallowing repeated smaller doses of methyl cellosolve acetate or repeated breathing of high air levels of methyl cellosolve acetate might cause lung or kidney damage, brain damage, and death. It is unlikely that air levels of methyl cellosolve acetate will be dangerous unless the liquid is heated. Methyl cellosolve acetate might cause eye irritation if splashed in the eyes. Methyl cellosolve acetate can be absorbed through intact skin. If a large amount is absorbed, death may result.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl cellosolve acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl cellosolve acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methyl cellosolve acetate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methyl cellosolve acetate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Methyl cellosolve acetate is absorbed through the skin. It also is a defatting agent and may cause dryness and cracking. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Since methyl cellosolve acetate may cause kidney damage in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although methyl cellosolve acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Methyl cellosolve acetate is irritating to the upper respiratory tract and is only slightly narcotic. Guinea

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

pigs and cats exposed to nearly saturated vapor died after some delay; concentrations of 1500 ppm for 7 hours killed cats, while 7000 ppm for 4 hours was lethal to some rats. On repeated exposures, 500 ppm for 8 hours killed some cats. There was irritation of upper respiratory tract, disturbance of equilibrium, drowsiness, and apathy followed by death. These animals had damage to the lung and kidney. There was only slight irritation of the eyes. There was no irritation upon skin contact, but absorption did occur. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 118
2. Boiling point (760 mm Hg): 145 C (293 F)
3. Specific gravity (water = 1): 1.01
4. Vapor density (air = 1 at boiling point of methyl cellosolve acetate): 4.1
5. Melting point: −65 C (−85 F)
6. Vapor pressure at 20 C (68 F): 2 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Completely miscible
8. Evaporation rate (butyl acetate = 1): 0.3

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methyl cellosolve acetate.
4. Special precautions: None

- **Flammability**

1. Flash point: 44 C (111 F) (closed cup)
2. Autoignition temperature: 393 C (740 F)
3. Flammable limits in air, % by volume: Lower: 1.7; Upper: 8.2
4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

- **Warning properties**

1. Odor Threshold: According to the *Handbook of Organic Industrial Solvents*, the odor threshold of methyl cellosolve acetate is twice the permissible exposure level.
2. Eye Irritation Level: According to Browning, methyl cellosolve acetate is only slightly irritating to the eyes and mucous membranes. No quantitative information is available concerning what concentrations produce the irritation, however. Union Carbide reports that "five drops of undiluted chemical produced minor injury in rabbit eyes."
3. Evaluation of Warning Properties: Since the odor threshold of methyl cellosolve acetate is only twice the permissible exposure level, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of methyl cellosolve acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl cellosolve acetate may be used. An analytical method for methyl cellosolve acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methyl cellosolve acetate.
- Clothing wet with liquid methyl cellosolve acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the

removal of methyl cellosolve acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl cellosolve acetate, the person performing the operation should be informed of methyl cellosolve acetate's hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid methyl cellosolve acetate should be removed promptly and not reworn until the methyl cellosolve acetate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl cellosolve acetate may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid methyl cellosolve acetate should be promptly washed or showered to remove any methyl cellosolve acetate.

• Employees who handle liquid methyl cellosolve acetate should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl cellosolve acetate may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent during spray or heat applications of surface coatings, including varnishes, dopes, lacquers, metal lacquers, cellulose lacquers for paper coatings, textile printing, and leather finishes	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent during spray or heat applications of adhesives, including polyvinyl formal, polyvinyl butyral, and polyvinyl acetate adhesives	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of photographic film	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during dry cleaning operations	Local exhaust ventilation; personal protective equipment
Use as a solvent during manufacture of surface coatings, including lacquers, dopes, varnishes, nail polishes; use during manufacture of adhesives	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methyl cellosolve acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methyl cellosolve acetate gets on the skin, promptly flush the contaminated skin with water. If methyl cellosolve acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl cellosolve acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When methyl cellosolve acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl cellosolve acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.

2. Ventilate area of spill or leak.

3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Liquid methyl cellosolve acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Methyl cellosolve acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Cellosolve Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Methyl Cellosolve Acetate*, New York, 1973.

• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters: Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 21:28-65, 1960.

RESPIRATORY PROTECTION FOR METHYL CELLOSOLVE ACETATE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
250 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
4500 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 4500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Chloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3Cl
- Synonyms: Chloromethane
- Appearance and odor: Colorless gas with a faint, sweet odor that is not noticeable at dangerous concentrations.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl chloride is 100 parts of methyl chloride per million parts of air (ppm) averaged over an eight-hour work shift, with a ceiling level of 200 ppm and a maximum acceptable peak of 300 ppm for 5 minutes in any three-hour period. The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for methyl chloride from 100 ppm to 50 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl chloride can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Deaths have occurred following single severe or repeated prolonged moderate overexposure. Overexposure may cause dizziness, vomiting, abdominal pain, diarrhea, breathing difficulties, and unconsciousness. Convulsions and disturbances of vision may occur. It may also damage the kidneys, liver, or blood. The symptoms of methyl chloride overexposure are usually delayed in onset. Frostbite may occur from contact with liquefied methyl chloride.

2. Long-term Exposure: Repeated moderate or mild overexposure may cause delayed (24 to 48 hours) onset of dizziness, headache, mental confusion, slurred speech, double vision, and sleepiness. Recovery from the effects of exposure to this chemical may be slow.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl chloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl chloride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system, liver, and kidneys should be stressed.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Methyl chloride vapor is a narcotic and may cause a toxic encephalopathy. The LC50 for mice for 7-hour exposure was approximately 3000 ppm. At this concentration some species showed pulmonary edema with hemorrhage, moderate centrolobular necrosis of the liver, and tubular damage in the kidney. At 500 ppm repeated daily for 6 hours, there was response in some species, while 300 ppm daily for 64 weeks produced no detectable effects. Human fatalities have occurred from a single severe exposure or less severe prolonged exposures. Severe but nonfatal poisoning in man is characterized by a latent period of several hours, followed by dizziness, nausea, vomiting, double vision, weakness, paralysis, convulsions, and coma; renal or hepatic

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

damage and anemia also occur. Some workers exposed daily to concentrations averaging 195 to 475 ppm showed delayed signs, including weakness, drowsiness, staggering gait, slurred speech, lapses of memory, and cyanosis. The onset is often insidious and may be confused with mild viral illness; more severe intoxication has been mistaken for viral encephalitis or heavy-metal poisoning. Effects may last for a long period following exposure. No effects were seen in other workers exposed to 15 to 195 ppm. Frostbite may result from contact with the liquid.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 50.5
2. Boiling point (760 mm Hg): −24.2 C (−11.6 F)
3. Specific gravity (water = 1): 0.92 (liquid)
4. Vapor density (air = 1 at boiling point of methyl chloride): 1.8
5. Melting point: −97.6 C (−144 F)
6. Vapor pressure at 20 C (68 F): 4.8 atm.
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Heat, especially when in contact with water or metals such as aluminum, magnesium, and zinc.
2. Incompatibilities: Contact with chemically active metals such as potassium, powdered aluminum, magnesium, and zinc will cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released in a fire involving methyl chloride.
4. Special precautions: Methyl chloride will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Not pertinent (gas)
2. Autoignition temperature: 632 C (1170 F)
3. Flammable limits in air, % by volume: Lower: 7.6; Upper: 19
4. Extinguishant: Stop flow of gas.

- **Warning properties**

May reports an odor threshold of 10 ppm. However, Patty states that methyl chloride has no odor or other warning properties, and Jacobs states that methyl chloride does not have adequate warning properties at higher concentrations.

Methyl chloride is not an eye irritant, according to Grant, even in concentrations which are "dangerously toxic."

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of methyl chloride. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Peak Above Ceiling Evaluation**

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of methyl chloride. Each measurement should consist of a 5-minute sample or a series of consecutive samples totalling 5 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of methyl chloride on activated carbon, followed by desorption with methanol and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl chloride may be used. An analytical method for methyl chloride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted

are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming wet with liquid methyl chloride or from becoming frozen from contact with vessels containing methyl chloride.

• Any clothing which becomes wet with liquid methyl chloride should be removed immediately and not reworn until the methyl chloride has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl chloride may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl chloride may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of silicone resins, and tetramethyl lead; use as a methylating and chlorinating agent; use as a dewaxing agent in petroleum refining; use as a catalyst solvent in production of butyl rubber	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of a variety of other compounds; as an extractant for greases, oils, and resins	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during use as a foaming agent in production of plastics; in the manufacture and application of pesticides, pharmaceuticals, and perfumes; as a propellant in aerosols; and use as a refrigerant	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquefied methyl chloride gets into the eyes, wash eyes immediately with large amounts of water. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquefied methyl chloride gets on the skin, immediately flush the contaminated skin using soap or mild detergent and water if the methyl chloride has not already evaporated. If liquefied methyl chloride soaks through the clothing, remove the clothing immediately and flush the skin using soap or mild detergent and water. Do not use hot water for skin flushing. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl chloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If methyl chloride is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak.
3. Stop flow of gas.

• Waste disposal method:

Methyl chloride may be disposed of by burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Chloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Methyl Chloride," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Ansul Chemical Company: *Physical Effects of Methyl*

Chloride.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• MacDonald, J. D. C.: "Methyl Chloride Intoxication," *Journal of Occupational Medicine*, 6:81-84, 1964.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-40, Methyl Chloride*, Washington, D.C., 1970.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Scharnweber, H. C., et al.: "Chronic Methyl Chloride Intoxication in Six Industrial Workers," *Journal of Occupational Medicine*, 16:112-113, 1974.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR METHYL CHLORIDE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressu.e-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Chloroform

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3CCl_3
- Synonyms: 1,1,1-trichloroethane; 1,1,1-trichloroethane, stabilized
- Appearance and odor: Colorless liquid with a mild odor, like chloroform.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl chloroform is 350 parts of methyl chloroform per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1910 milligrams of methyl chloroform per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be changed to a ceiling of 350 ppm (1910 mg/m^3) averaged over a 15-minute period. The NIOSH Criteria Document for 1,1,1-Trichloroethane should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl chloroform can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to methyl chloroform vapor may cause headache, dizziness, drowsiness, unconsciousness, irregular heart beat, and death. Methyl chloroform liquid splashed in the eyes may cause irritation.

2. Long-term Exposure: Prolonged or repeated skin contact with liquid methyl chloroform may cause irritation of the skin. Reproductive abnormalities have been noted in studies of animals exposed to high concentrations of methyl chloroform.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl chloroform.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl chloroform at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the skin, liver, and cardiovascular system should be stressed. The physician should be made aware of any adverse reproductive effects in workers exposed to methyl chloroform.

—Skin disease: Methyl chloroform can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: At high concentrations, methyl chloroform causes liver changes in animals, which justifies consideration of the possible consequences before exposing persons with impaired liver function.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrhythmias, the inhalation of methyl chloroform might cause exacerbation of disorders of the conduction mechanism due to its sensitizing effects on the myocardium.

—Medical warning: Workers should be provided with information advising them of studies in which congenital abnormalities were found following exposure of animals to high concentrations of methyl chloro-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

807

form. The physician should be made aware of any reproductive abnormalities in workers.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Methyl chloroform vapor is a narcotic. Repeated exposure of animals to concentrations of 1000 to 10,000 ppm caused liver and lung changes in some species. In dogs, cardiac sensitization to epinephrine occurred at concentrations of 5000 to 10,000 ppm. A number of human fatalities related to industrial exposure in closed spaces have been reported. A 5-minute exposure to 5000 ppm can be expected to produce marked incoordination and anesthesia. Prolonged exposure at this concentration may cause coma and death. Exposure to concentrations in excess of 1000 ppm for 15 minutes, or 2000 ppm for 5 minutes, can be expected to produce a disturbance of equilibrium in the majority of adults. Above 1700 ppm, minor disturbances of equilibrium have been observed, with complaints of headache and lassitude. In controlled human exposures to 500 ppm no effects other than slight, transient eye irritation were noted; at 1000 ppm and above, mild eye irritation was experienced by all subjects, and some became dizzy. Following exposure, most of the compound is eliminated unchanged via the lungs within 48 hours. When placed into the rabbit eye, the liquid caused conjunctival irritation but no corneal damage. Dermatitis may result from repeated skin contact with the liquid.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 133.4
2. Boiling point (760 mm Hg): 74 C (165 F)
3. Specific gravity (water = 1): 1.33
4. Vapor density (air = 1 at boiling point of methyl chloroform): 4.55
5. Melting point: −38 C (−36 F)
6. Vapor pressure at 20 C (68 F): 100 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.07
8. Evaporation rate (butyl acetate = 1): 12.8

• **Reactivity**

1. Conditions contributing to instability: Heat.
2. Incompatibilities: Contact with strong caustics, strong oxidizers, and chemically active metals such as aluminum and magnesium powders, or sodium and potassium may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving methyl chloroform.
4. Special precautions: Liquid methyl chloroform will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: None in normal test method.
2. Autoignition temperature: 500 C (932 F)
3. Flammable limits in air, % by volume: (At elevated temperature and pressure) Lower: 7; Upper: 16
4. Extinguishant: Foam, dry chemical, carbon dioxide

• **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that the odor threshold of methyl chloroform may range from 20 to 100 ppm. Both May and Summer give 400 ppm as the odor threshold, however.
2. Eye Irritation Level: The *Hygienic Guide* states that "in controlled human exposures to 500 ppm no effects other than slight, transient eye irritation were noted, but at 1000 ppm and above, mild eye irritation was experienced by all subjects."
3. Evaluation of Warning Properties: Since the odor threshold of methyl chloroform is near or below the permissible exposure limit, and since eye irritation occurs at a concentration only twice the permissible exposure limit, methyl chloroform is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of methyl chloroform. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl chloroform may be used. An analytical method for methyl chloroform is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methyl chloroform.

• Non-impervious clothing which becomes wet with liquid methyl chloroform should be removed promptly and not reworn until the methyl chloroform is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl chloroform may contact the eyes.

SANITATION

• Skin that becomes wet with liquid methyl chloroform should be promptly washed or showered to remove any methyl chloroform.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl chloroform may occur and control methods which may be effective in each case:

Operation	Controls
Use as solvent in cold cleaning of metals, and plastics; in vapor degreasing; in ultrasonic cleaning; in dyeing and cleaning of fabrics and yarns	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in organic synthesis in polymer manufacture; as primary and carrier solvent in spot cleaners, adhesives, shoe polishes, stain repellants, hair sprays, Mace, insecticides, resins, inks, lubricants, protective coatings, asphalt extraction, and waste water treatment; use in aerosol manufacture as pressure depressant	Process enclosure; local exhaust ventilation
Use as coolant and lubricant in cutting oils on metals; use during printed circuit boards production; liquid Drano production and photographic film processing	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methyl chloroform gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methyl chloroform gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If methyl chloroform soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl chloroform, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When methyl chloroform has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl chloroform is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Methyl chloroform may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Chloroform," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "1,1,1-Trichloroethane (Methyl Chloroform)," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Ethyl Corporation: *Material Safety Data Sheet - Methyl Chloroform*, Baton Rouge, Louisiana.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-90, Methyl Chloroform*, WashingtonD.C., 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to 1,1,1-Trichloroethane*, HEW Publication No. (NIOSH) 76-184, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Reinhardt, C. F., et al.: "Epinephrine-Induced Cardiac Arrhythmia Potential of Some Common Industrial Solvents," *Journal of Occupational Medicine*, 15:953-955, 1973.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stewart, R. D.: "Methyl Chloroform Intoxication," *Journal of the American Medical Association*, 215:1789-1792, March 15, 1971.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• "1,1,1-Trichloroethane: Emergency Exposure Limits," *American Industrial Hygiene Association Journal*, 25:585-586, 1964.

RESPIRATORY PROTECTION FOR METHYL CHLOROFORM

Condition	Minimum Respiratory Protection* Required Above 350 ppm
Vapor Concentration	
500 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).
	Any supplied-air respirator.
	Any self-contained breathing apparatus.
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Formate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $HCOOCH_3$
- Synonyms: Methyl methanoate; formic acid, methyl ester
- Appearance and odor: Colorless liquid with a pleasant odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl formate is 100 parts of methyl formate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 250 milligrams of methyl formate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl formate can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to methyl formate may cause irritation of the eyes, nose, throat, and lungs. It may also cause drowsiness and, at high levels, unconsciousness and death.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl formate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl formate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methyl formate exposure.

—Eye disease: Methyl formate is an eye irritant. Persons with pre-existing eye disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methyl formate might cause exacerbation of symptoms due to its irritant properties.

—Neurological disorders: By analogy to effects observed in animals and by effects observed in humans, persons with pre-existing neurological disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Methyl formate vapor at high concentrations is an irritant of the eyes and respiratory tract; it also causes narcosis in animals. Exposure of guinea pigs to 10,000 ppm for 3 hours was fatal; effects were eye and nose irritation, incoordination, narcosis, and pulmonary edema. Workers exposed to the vapor of a solvent containing 30% methyl formate, in addition to ethyl formate, methyl acetate, and ethyl acetate, complained of irritation of mucous membranes, oppression in the chest, dyspnea, symptoms of central nervous system depression, and temporary visual disturbances; air concentrations were not determined. No short-term effects were noted from experimental human exposures to 1500 ppm for 1 minute.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

802

September 1976

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 60.1
  2. Boiling point (760 mm Hg): 31.7 C (89 F)
  3. Specific gravity (water = 1): 0.98
  4. Vapor density (air = 1 at boiling point of methyl formate): 2.1
  5. Melting point: −100 C (−148 F)
  6. Vapor pressure at 20 C (68 F): 476 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 30
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as formic acid and carbon monoxide) may be released in a fire involving methyl formate.
  4. Special precautions: Methyl formate will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −18.9 C (−2 F) (closed cup)
  2. Autoignition temperature: 465 C (869 F)
  3. Flammable limits in air, % by volume: Lower: 5.0; Upper: 23
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Both Summer and May report an odor threshold of 2000 ppm for methyl formate. Browning, however, states that "men exposed for 1 minute to 1500 ppm of the vapour in air noticed the odour of methyl formate . . . ." Browning states that olfactory fatigue occurs, and thus odor may not be an effective warning of exposure to dangerous concentrations.
  2. Eye Irritation Level: Grant states that the vapor of methyl formate "has been found to cause no eye irritation in experimental animals at a concentration of 1500 ppm in air, but does cause some irritation at 3500 ppm."
  3. Other Information: According to Grant, methyl formate in high concentrations causes nasal irritation also, but quantitative information is not given.
  4. Evaluation of Warning Properties: Since the thresholds of odor and of irritation are well above the permissible exposure limit, methyl formate is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for methyl formate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methyl formate.
- Clothing wet with liquid methyl formate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methyl formate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl formate, the person performing the operation should be informed of methyl formate's hazardous properties.
- Any clothing which becomes wet with liquid methyl formate should be removed immediately and not reworn until the methyl formate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid methyl formate may contact the eyes.

SANITATION

- Skin that becomes wet with liquid methyl formate should be promptly washed or showered to remove any methyl formate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl formate may occur and control methods which may be effective in each case:

Operation	Controls
Use as insecticide and larvicide for fumigating dried fruits, nuts, tobacco, cereals, and infected clothing	Personal protective equipment
Use as a general industrial solvent for greases, fatty acids, cellulose acetate, collodion, and celluloid	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis for production of sulfa drugs, perfumes, dyes, military poison gases, and embalming fluid	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Manufacture of methyl formate	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid methyl formate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid methyl formate gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid methyl formate soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl formate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When methyl formate has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl formate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. Methyl formate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of methyl formate vapors are permitted.

• Waste disposal method:

Methyl formate may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Formate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Schrenk, H. H., et al.: "Acute Response of Guinea Pigs to Vapors of Some New Commercial Organic Compounds. XIII. Methyl Formate," *Public Health Reports*, 51:1329-1337, 1936.
• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.
• von Oettingen, W.F.: "The Aliphatic Acids and Their Esters - Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 20:517-531, 1959.

RESPIRATORY PROTECTION FOR METHYL FORMATE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
3500 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.**
5000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Methyl Iodide*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3I
- Synonyms: Iodomethane
- Appearance: Colorless liquid which turns yellow, red, and brown on exposure to light and moisture.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl iodide is 5 parts of methyl iodide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 28 milligrams of methyl iodide per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for methyl iodide from 5 ppm to 2 ppm and has classified it as having a carcinogenic potential for man.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl iodide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Methyl iodide may cause nausea and vomiting, diarrhea, dizziness, slurred speech, visual disturbances, staggering, shaking, irritability, drowsiness, coma, and death. It may irritate the eyes and lungs. Contact with the liquid may cause irritation and blistering of the skin.

2. Long-term Exposure: Prolonged overexposure to methyl iodide may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl iodide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl iodide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Methyl iodide vapor is an acute neurotoxin and possible pulmonary irritant. In mice, the LC50 for 57 minutes' exposure was 900 ppm; the minimum fatal dose with 24-hour exposure was 75 ppm. A chemical worker accidentally exposed to the vapor developed giddiness, diarrhea, sleepiness, and irritability, with recovery in a week; when re-exposed 3 months later, he experienced drowsiness, vomiting, pallor, incoordination, slurred speech, muscular twitching, oliguria, coma, and death. At autopsy there was bronchopneumonia and pulmonary hemorrhages, with accumulation of combined iodine in the brain. Experimental application of the liquid to human skin produced a stinging sensation and slight reddening in 10 minutes; after 6 hours' contact there was spreading erythema with later formation of vesicles. One report mentions the production of sarcomas in 15 of 24 rats of BD strain arising from the subcutaneous injection of methyl iodide in an oil solution, but the report is fragmentary.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

808

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 142
  2. Boiling point (760 mm Hg): 42.5 C (108 F)
  3. Specific gravity (water = 1): 2.3
  4. Vapor density (air = 1 at boiling point of methyl iodide): 4.9
  5. Melting point: −66 C (−87 F)
  6. Vapor pressure at 20 C (68 F): 375 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 2
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat, light, and moisture
  2. Incompatibilities: Methyl iodide reacts with strong oxidizing agents.
  3. Hazardous decomposition products: Toxic gases and vapors (such as iodine and hydrogen iodide) may be released when methyl iodide decomposes.
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Although methyl iodide is known to have a sweet, ethereal odor, no quantitative data are available on the odor threshold. Methyl iodide is treated as a material with poor warning properties.

According to Grant, concentrations of methyl iodide of 4300 to 14,620 ppm caused immediate irritation of the eyes and lacrimation in mice, but 860 ppm for 10 minutes caused no irritation.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of methyl iodide vapors using an adsorption tube with subsequent desorption with toluene and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl iodide may be used. An analytical method for methyl iodide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methyl iodide.
- Non-impervious clothing which becomes contaminated with liquid methyl iodide should be removed immediately and not reworn until the methyl iodide is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid methyl iodide may contact the eyes.

SANITATION

- Skin that becomes wet with liquid methyl iodide should be immediately washed or showered with soap or mild detergent and water to remove any methyl iodide.
- Employees who handle liquid methyl iodide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.
- Eating and smoking should not be permitted in areas where liquid methyl iodide is handled, processed, or stored.

COMMON OPERATIONS AND CONTROLS

The following list includes ne common operations in which exposure to methyl iodide may occur and control methods which may be effective in each case:

Operation	Controls
Use as a methylating agent in organic synthesis; use as a laboratory reagent; use in academic laboratory courses in organic chemistry	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an insecticidal fumigant on scale insects and beetles	Process enclosure; general dilution ventilation; personal protective equipment
Use in analytical chemistry laboratories (test for pyridine, evaluating type of sulfur linkage in vulcanized rubber)	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methyl iodide gets into the eyes, wash eyes promptly with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methyl iodide gets on the skin, immediately flush the contaminated skin using soap or mild detergent and water. If methyl iodide soaks through the clothing, remove the clothing immediately and flush the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl iodide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When methyl iodide has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl iodide is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Iodide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Buckell, M.: "The Toxicity of Methyl Iodide: I. A Preliminary Survey," *British Journal of Industrial Medicine*, 7:122, 1950.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dixon, M.: "Reactions of Lachrymators with Enzymes and Proteins," *Biochemical Society Symposia*, 2:39-49, 1948.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Preussman, R.: "Direct Alkylating Agents as Carcinogens," *Food and Cosmetics Toxicology*, 6:576-577, 1968.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

* SPECIAL NOTE

Methyl iodide appears on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding its carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980). The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 15, 1977.

RESPIRATORY PROTECTION FOR METHYL IODIDE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
50 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
250 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
800 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 800 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Isobutyl Carbinol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_2CHCH_2CHOHCH_3$
- Synonyms: Methyl amyl alcohol; 4-methyl-2-pentanol; MIBC
- Appearance and odor: Colorless liquid with a mild odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl isobutyl carbinol is 25 parts of methyl isobutyl carbinol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 100 milligrams of methyl isobutyl carbinol per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl isobutyl carbinol can affect the body if it is swallowed, is inhaled, or comes in contact with the eyes or skin.

- **Effects of overexposure**

Overexposure to methyl isobutyl carbinol may cause eye and skin irritation. The overexposed person may also experience headache and drowsiness.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl isobutyl carbinol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl isobutyl carbinol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methyl isobutyl carbinol exposure.

—Skin disease: Methyl isobutyl carbinol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although methyl isobutyl carbinol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although methyl isobutyl carbinol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Only limited observations of the effects of methyl isobutyl carbinol have been reported, but exposure of rats to 2000 ppm for 8 hours is fatal, while 1000 ppm is not. The most important effects of methyl isobutyl carbinol are narcosis and eye irritation. Unacclimated volunteer subjects exposed to 50 ppm vapor had eye irritation. Chronic systemic effects have not been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 102
  2. Boiling point (760 mm Hg): 132 C (269 F)
  3. Specific gravity (water = 1): 0.8

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

4. Vapor density (air = 1 at boiling point of methyl isobutyl carbinol): 3.5
5. Melting point: −90 C (−130 F)
6. Vapor pressure at 20 C (68 F): 3.8 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 1.5
8. Evaporation rate (butyl acetate = 1): 0.27

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methyl isobutyl carbinol.
4. Special precautions: Methyl isobutyl carbinol will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 41 C (106 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Lower: 1.0; Upper: 5.5
4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide

• **Warning properties**

1. Odor Threshold: The *Documentation of TLV's* states that Silverman and associates observed that human subjects did not find the odor objectionable at 50 ppm.
2. Eye Irritation: According to the *Documentation of TLV's*, Silverman and associates found that human subjects experienced eye irritation at 50 ppm.
3. Evaluation of Warning Properties: Since eye irritation occurs at a level only twice the permissible exposure limit, this substance is considered to have good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of methyl isobutyl carbinol vapors using an adsorption tube with subsequent desorption with 2-propanol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl isobutyl carbinol may be used. An analytical method for methyl isobutyl carbinol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, field, Virginia 22161, under the title "NIOSH Analyt-

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methyl isobutyl carbinol.

• Clothing wet with liquid methyl isobutyl carbinol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methyl isobutyl carbinol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl isobutyl carbinol, the person performing the operation should be informed of methyl isobutyl carbinol's hazardous properties.

• Non-impervious clothing which becomes wet with liquid methyl isobutyl carbinol should be removed promptly and not reworn until the methyl isobutyl carbinol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methyl isobutyl carbinol may contact the eyes.

SANITATION

• Skin that becomes wet with liquid methyl isobutyl carbinol should be promptly with soap or mild detergent and water washed or showered to remove any methyl isobutyl carbinol.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl isobutyl carbinol may occur

and control methods which may be effective in each case:

Operation	Controls
Liberation during application of nitrocellulose lacquers and other coatings; application of hot-spray lacquers	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as an extractant in dewaxing of mineral oils; use as a frother in froth flotation of various minerals, especially copper; use as an extractant in manufacture of antibiotics	General dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during preparation of brake fluids; during preparation of lubricant additives	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in synthesis of surfactants; use in preparation of lubricating oil additives	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methyl isobutyl carbinol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methyl isobutyl carbinol gets on the skin, promptly wash the contaminated skin with water. If methyl isobutyl carbinol soaks through the clothing, remove the clothing promptly and flush the skin with water. If there is skin irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methyl isobutyl carbinol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When methyl isobutyl carbinol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl isobutyl carbinol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Methyl isobutyl carbinol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Methyl isobutyl carbinol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Isobutyl Carbinol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Methyl Isobutyl Carbinol," *Hygienic Guide Series*, Detroit, Michigan, 1956.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., Jr., Carpenter, C. P., and Weil, C. S.: "Range-Finding Toxicity Data: List IV," *A.M.A. Archives of Industrial Hygiene and Occupational Health*, 4:119-122, 1951.

RESPIRATORY PROTECTION FOR METHYL ISOBUTYL CARBINOL

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Isocyanate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3NCO
- Synonyms: None
- Appearance and odor: Colorless liquid with a sharp odor that causes tears.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl isocyanate is 0.02 part of methyl isocyanate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.05 milligram of methyl isocyanate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl isocyanate can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Inhalation of methyl isocyanate vapors may cause irritation of the eyes, nose, throat, and lungs. Cough, shortness of breath, increased phelgm and chest pain may be present. The liquid splashed in the eyes may cause permanent damage. The liquid splashed on the skin may cause irritation. Exposure to methyl isocyanate may cause a person to become allergic to it so that extremely low levels of exposure may cause an asthmatic attack.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl isocyanate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl isocyanate at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to methyl isocyanate would be expected to be at increased risk from exposure. Examination of the eyes and respiratory tract should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Methyl isocyanate causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Methyl isocyanate is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Methyl isocyanate vapor is an intense lacrimator and irritates the eyes, mucous membranes, and skin. It can cause pulmonary irritation and sensitization. In rats exposed for 4 hours, the LC50 was 5 ppm; effects were injury to the lungs and subsequent pulmonary edema. Exposure of humans to high concentrations can cause cough, dyspnea, increased secretions, and chest pain. Isocyanates cause pulmonary sensitization in susceptible individuals; should this occur, further exposure should be avoided, since extremely low levels of expo-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

sure may trigger an asthmatic episode; cross sensitization to unrelated materials probably does not occur. Experimental exposure of four human subjects for 1 to 5 minutes caused the following effects: 0.4 ppm, no effects; 2 ppm, lacrimation, irritation of the nose and throat; 4 ppm, symptoms of irritation more marked; 21 ppm, unbearable irritation of eyes, nose, and throat. A cotton plug saturated with the liquid was applied to the ear of a rabbit for 30 minutes and caused erythema, edema, necrosis, and perforation; a few drops of the liquid on the ear of a rabbit caused destruction of tissue. The liquid in contact with the eye may cause permanent damage.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 57.1
2. Boiling point (760 mm Hg): 39 C (102 F)
3. Specific gravity (water = 1): 0.96
4. Vapor density (air = 1 at boiling point of methyl isocyanate): 2.0
5. Melting point: −80 C (−112 F)
6. Vapor pressure at 20 C (68 F): 348 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 6.7 (reacts slowly)
8. Evaporation rate (butyl acetate = 1): 26.8

- **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause methyl isocyanate to polymerize and burst container.
2. Incompatibilities: Contact with water causes formation of carbon dioxide and methylamine gases. The reaction is much more rapid in the presence of acids, alkalies, and amines. Contact with iron, tin, copper (or salts of these elements) and with certain other catalysts (such as triphenylarsenic oxide, triethylphosphine, and tributyltin oxide) may cause violent polymerization.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen cyanide, oxides of nitrogen, and carbon monoxide) may be released in a fire involving methyl isocyanate.
4. Special precautions: Methyl isocyanate will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Less than −18 C (0 F) (open cup)
2. Autoignition temperature: 535 C (995 F)
3. Flammable limits in air, % by volume: Lower: 5.3; Upper: 26
4. Extinguishant: Carbon dioxide, dry chemical, foam

- **Warning properties**

1. Odor Threshold: The *Documentation of TLV's* states that humans exposed to 0.4 ppm methyl isocyanate for periods up to 5 minutes could not detect the odor. Even at a concentration of 2 ppm, the odor was not perceived.
2. Irritation Levels: At a concentration of 0.4 ppm, eye, nose, and throat irritation was not experienced by human subjects who were exposed for periods up to 5 minutes. The *Documentation of TLV's* states that "at 2 ppm no odor was detected, but the subjects experienced irritation and lacrimation. At 4 ppm the symptoms of irritation were more marked. Exposure was unbearable at 21 ppm."
3. Evaluation of Warning Properties: Since the odor and irritation thresholds of methyl isocyanate are not within 3 times the permissible exposure limit, for the purposes of this guideline, methyl isocyanate is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for methyl isocyanate had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid methyl isocyanate.

• Clothing wet with liquid methyl isocyanate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methyl isocyanate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl isocyanate, the person performing the operation should be informed of methyl isocyanate's hazardous properties.

• If employees' clothing has had any possibility of being contaminated with liquid methyl isocyanate, employees should change into uncontaminated clothing before leaving the work premises.

• Any clothing which becomes wet with and non-impervious clothing which becomes contaminated with liquid methyl isocyanate should be removed immediately and not reworn until the methyl isocyanate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid methyl isocyanate contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid methyl isocyanate, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid methyl isocyanate should be immediately washed or showered to remove any methyl isocyanate.

• Employees who handle liquid methyl isocyanate should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl isocyanate may occur and control methods which may be effective in each case:

Operation	Controls
Use as a cross-linking agent; additive to adhesives in polymer technology; use in organic synthesis	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid methyl isocyanate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid methyl isocyanate gets on the skin, immediately flush the contaminated skin with large amounts of water. If liquid methyl isocyanate soaks through the clothing, remove the clothing immediately and flush the skin with large amounts of water. If irritation persists after washing, get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of methyl isocyanate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid methyl isocyanate has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl isocyanate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Methyl isocyanate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of methyl isocyanate vapors are permitted.

• Waste disposal method:

Methyl isocyanate may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Isocyanate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Rye, W. A.: "Human Responses to Isocyanate Exposure," *Journal of Occupational Medicine*, 15:306-307, 1973.

RESPIRATORY PROTECTION FOR METHYL ISOCYANATE

Condition	Minimum Respiratory Protection* Required Above 0.02 ppm
Vapor Concentration	
0.2 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
1ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
20 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 20 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methyl Methacrylate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2=C(CH_3)COOCH_3$
- Synonyms: Methacrylic acid, methyl ester
- Appearance and odor: Colorless liquid with an acrid, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methyl methacrylate is 100 parts of methyl methacrylate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 410 milligrams of methyl methacrylate per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methyl methacrylate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to methyl methacrylate may cause irritation of the nose, throat, skin, and eyes. It may also cause drowsiness and, at very high levels, perhaps unconsciousness.

2. Long-term Exposure: Prolonged exposure may cause a skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methyl methacrylate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methyl methacrylate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methyl methacrylate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methyl methacrylate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Methyl methacrylate can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although methyl methacrylate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although methyl methacrylate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The main toxic effect of methyl methacrylate is irritation of the respiratory tract by exposure to the vapor of the monomer. Rabbits exposed to 13,500 ppm for 3 hours died. Dust generated from the solid polymer is also irritating. Application to the eyes of rabbits caused irritation requiring several days for recovery. Dental technicians molding the polymer by hand developed dermatitis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 100
2. Boiling point (760 mm Hg): 100 C (212 F)
3. Specific gravity (water = 1): 0.95
4. Vapor density (air = 1 at boiling point of methyl methacrylate): 3.6
5. Melting point: −48 C (−54 F)
6. Vapor pressure at 20 C (68 F): 35 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 1.5
8. Evaporation rate (butyl acetate = 1): 3.1

- **Reactivity**

1. Conditions contributing to instability: Heat/and or lack of appropriate inhibitor concentration can cause methyl methacrylate to polymerize violently and burst container.
2. Incompatibilities: Contact with nitrates, oxidizing materials, including peroxides and other initiators of polymerization, strong alkalies, and strong acids may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methyl methacrylate.
4. Special precautions: Inhibitors do not function in absence of air, so inert gas blankets should not be used.

- **Flammability**

1. Flash point: 10 C (50 F) (closed cup)
2. Autoignition temperature: 421 C (790 F)
3. Flammable limits in air, % by volume: Lower: 1.7; Upper: 8.2
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

1 Odor Threshold: May reports an odor threshold for methyl methacrylate of 0.21 ppm.

2. Eye Irritation Level: According to Grant, "on application to rabbit eyes it (methyl methacrylate) has caused irritation requiring several days for recovery. The TLV is recommended "to protect against discomfort from irritation."

3. Other Information: According to the *Documentation of TLV's*, some "investigators noted irritation at 170 to 250 ppm, but workers tolerated without complaint levels approximating 200 ppm . . . . It was the opinion of men in the field that 100 ppm could be tolerated continuously for 8 hours without discomfort."

4. Evaluation of Warning Properties: Since its odor threshold is below the permissible exposure limit, and since irritation occurs within 3 times the permissible exposure limit, methyl methacrylate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of methyl methacrylate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methyl methacrylate may be used. An analytical method for methyl methacrylate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methyl methacrylate.
- Clothing wet with liquid methyl methacrylate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of

methyl methacrylate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methyl methacrylate, the person performing the operation should be informed of methyl methacrylate's hazardous properties.

- Any clothing which becomes wet with liquid methyl methacrylate should be removed immediately and not reworn until the methyl methacrylate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid methyl methacrylate may contact the eyes.

SANITATION

- Skin that becomes wet with liquid methyl methacrylate should be promptly washed or showered with soap or mild detergent and water to remove any methyl methacrylate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methyl methacrylate may occur and control methods which may be effective in each case:

Operation	Controls
Use during casting of acrylic sheets	Local exhaust ventilation; personal protective equipment
Use during molding of acrylic sheets or polymethacrylate powders	Local exhaust ventilation; general dilution ventilation
Use during spray application of unsaturated polyester resins (surface coatings or structural components); use during brush or roller applications of unsaturated polyester resins (surface coatings or structural components)	Local exhaust ventilation; personal protective equipment
Liberation during manufacture of methyl methacrylate resins for surface coatings; during polymerization to produce molding and extruding powders	Process enclosure; general dilution ventilation
Liberation during production of synthetic fibers; during manufacture of unsaturated polyester resins	Process enclosure; local exhaust ventilation; general dilution ventilation
Liberation during dye molding of articles from polyester resins; during production of emulsion polymers for use in adhesives, sealants, fabrics, sizes, leather finishes, paper coatings, polishes, etc.; during machining of articles from resins (acrylic plastics)	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If methyl methacrylate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If methyl methacrylate gets on the skin, promptly flush the contaminated skin with water. If methyl methacrylate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of methyl methacrylate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When methyl methacrylate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methyl methacrylate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Methyl methacrylate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Methyl methacrylate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill in an area where the odor will not be objectionable.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methyl Methacrylate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• E. I. DuPont de Nemours and Company: *Storage and Handling of Methacrylate Esters*, Wilmington, Delaware.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Material Safety Data Sheet – Methyl Methacrylate*, New York, 1971.

RESPIRATORY PROTECTION FOR METHYL METHACRYLATE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
4000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for alpha-Methyl Styrene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5C(CH_3)=CH_2$ or C_9H_{10}
- Synonyms: 1-Methyl-1-phenylethylene; AMS
- Appearance and odor: Colorless liquid with a characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for alpha-methyl styrene is a ceiling level of 100 parts of alpha-methyl styrene per million parts of air (ppm). This may also be expressed as 480 milligrams of alpha-methyl styrene per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for alpha-methyl styrene from 100 ppm to 50 ppm as a ceiling value.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

alpha-Methyl styrene can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: alpha-Methyl styrene may cause irritation of the eyes, nose, and throat. The overexposed person may experience drowsiness.

2. Long-term Exposure: Prolonged exposure may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to alpha-methyl styrene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to alpha-methyl styrene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from alpha-methyl styrene exposure.

—Skin disease: alpha-Methyl styrene can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of alpha-methyl styrene might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Kidney disease: Although alpha-methyl styrene is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although alpha-methyl styrene is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Overexposure to alpha-methyl styrene causes slight irritation of the eyes, upper respiratory tract, and skin. With prolonged and repeated contact, there may be depression of the central nervous system.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 118
2. Boiling point (760 mm Hg): 165 C (329 F)
3. Specific gravity (water = 1): 0.92
4. Vapor density (air = 1 at boiling point of alpha-methyl styrene): 4.1
5. Melting point: −23 C (−9 F)
6. Vapor pressure at 20 C (68 F): 1.9 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Less than 1

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with oxidizing agents (including peroxides and halogens) may cause fires and explosions. Also, avoid contact with catalysts for vinyl polymerization and catalysts for ionic polymerization, such as aluminum or iron chloride.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving alpha-methyl styrene.
4. Special precautions: None

- **Flammability**

1. Flash point: 54 C (129 F) (closed cup)
2. Autoignition temperature: 574 C (1066 F)
3. Flammable limits in air, % by volume: Lower: 1.9; Upper: 6.1
4. Extinguishant: Carbon dioxide, dry chemical, or foam.

- **Warning properties**

1. Odor Threshold: According to the *Documentation of TLV's*, "four human subjects exposed to a concentration of 200 ppm of alpha-methyl styrene reported definite unpleasant odor . . . after two minutes." This concentration is not necessarily the odor threshold.
2. Eye Irritation Level: The *Documentation of TLV's* also notes that at 200 ppm human subjects experienced eye irritation. This concentration is not necessarily the threshold of eye irritation.
3. Evaluation of Warning Properties: alpha-Methyl styrene can be detected at a concentration less than twice the permissible exposure limit. Even though the permissible exposure limit is a ceiling concentration, alpha-methyl styrene is still treated as a material with adequate warning properties, since the ceiling appears to have been established to avoid irritant effects. The *Documentation of TLV's* gives the following quote of Dow Chemical Company: "We suggest, therefore, an Industrial Hygiene Standard of 200 ppm based on toxicity. For engineering purposes, we suggest that the vapor concentration be controlled to 100 ppm alpha-methyl styrene in order to minimize complaints of exposed persons."

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of alpha-methyl styrene. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of alpha-methyl styrene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure alpha-methyl styrene may be used. An analytical method for alpha-methyl styrene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid alpha-methyl styrene.
- Clothing wet with liquid alpha-methyl styrene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of

alpha-methyl styrene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the alpha-methyl styrene, the person performing the operation should be informed of alpha-methyl styrene's hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid alpha-methyl styrene should be removed promptly and not reworn until the alpha-methyl styrene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid alpha-methyl styrene may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid alpha-methyl styrene should be promptly washed or showered with soap or mild detergent and water to remove any alpha-methyl styrene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to alpha-methyl styrene may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during manufacture of styrene-butadiene rubber	General dilution ventilation
Liberation during spray application of specialized alpha-methyl-styrene-polyester surface coatings	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during manufacture of high-impact acrylonitrile-butadiene-styrene plastics; during manufacture of specialized alpha-methyl-styrene-polyester and alkyd surface coating resins; during manufacture of certain plasticizers in varnishes, adhesives, and plastics; during manufacture of carbolic acid with cumene peroxidation process	General dilution ventilation; local exhaust ventilation
Liberation during brush application of specialized surface coatings	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If alpha-methyl styrene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If alpha-methyl styrene gets on the skin, promptly flush the contaminated skin with water. If alpha-methyl styrene soaks through the clothing, remove the clothing immediately and flush the skin with water When there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of alpha-methyl styrene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If alpha-methyl styrene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If alpha-methyl styrene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Combustion may be improved by mixing with a flammable liquid. Liquid alpha-methyl styrene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

alpha-Methyl styrene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary

landfill.
2. By atomizing in a suitable combustion chamber. Combustion may be improved by mixing with a flammable liquid.

REFERENCES

- Allied Chemical Company: *Material Safety Data Sheet - alpha-Methyl Styrene.*
- American Conference of Governmental Industrial Hygienists: "alpha-Methyl Styrene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
- Wolf, M. A., et al.: "Toxicological Studies of Certain Alkylated Benzenes and Benzene," *Archives of Industrial Health*, 14:4, pp. 387-398, 1956.

RESPIRATORY PROTECTION FOR ALPHA-METHYL STYRENE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methylal

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3OCH_2OCH_3$
- Synonyms: Dimethoxymethane; methyl formal; formal; dimethylacetal formaldehyde
- Appearance and odor: Colorless liquid with a pungent odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methylal is 1000 parts of methylal per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 3100 milligrams of methylal per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methylal can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to methylal may cause irritation of the eyes, nose, and throat, lightheadedness, incoordination, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure to methylal may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methylal.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methylal at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methylal exposure.

—Skin disease: Methylal is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although methylal is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although methylal is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methylal might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Methylal vapor is a mild respiratory irritant with anesthetic properties. Mice exposed at 11,000 ppm showed mild irritation of the eyes and respiratory tract, as well as incoordination; recovery was rapid after single exposures. At 14,000 ppm, mice showed more respiratory irritation, occasional pulmonary edema, and a greater degree of anesthesia. At the LC50 level of approximately 18,000 ppm, animals died of bronchopneumonia with fatty changes in the liver, kidney, and heart. At 4000 ppm rats were unaffected by daily 6-hour exposures.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Skin irritation may be expected due to defatting action by the solvent, and eye irritation if splashing occurs. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 76
  2. Boiling point (760 mm Hg): 44 C (111 F)
  3. Specific gravity (water = 1): 0.86
  4. Vapor density (air = 1 at boiling point of methylal): 2.6
  5. Melting point: −105 C (−157 F)
  6. Vapor pressure at 20 C (68 F): 330 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 33
  8. Evaporation rate (butyl acetate = 1): 23.1
- **Reactivity**
  1. Conditions contributing to instability: Heat, presence of acids
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions. Contact with acids causes decomposition to methyl alcohol and formaldehyde.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide, formaldehyde, and methyl alcohol) may be released in a fire involving methylal.
  4. Special precautions: Methylal will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −18 C (−4 F) (closed cup)
  2. Autoignition temperature: 237 C (459 F)
  3. Flammable limits in air, % by volume: Lower: 1.6; Upper: 17.6
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold, but Browning notes that it has a slightly pungent odor.
  2. Eye Irritation Level: Grant states that "exposures of mice and guinea pigs to much higher concentrations of methylal vapor than would be encountered industrially were found to cause . . . occasional irritation of the eyes but no histologically demonstrable abnormality of the optic nerve or retina."

  Patty reports that mice which had received 15 7-hour exposures at 11,000 ppm experienced only mild irritation.

  No quantitative information is available, however, concerning the threshold of eye irritation.
  3. Evaluation of Warning Properties: Since there is no useful quantitative information relating warning properties to air concentrations of methylal, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of methylal vapors using an adsorption tube with subsequent desorption with hexane and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methylal may be used. An analytical method for methylal is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methylal.
- Clothing wet with liquid methylal should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methylal from the clothing. If the clothing is to be laundered or

otherwise cleaned to remove the methylal, the person performing the operation should be informed of methylal's hazardous properties.

- Any clothing which becomes wet with liquid methylal should be removed immediately and not reworn until the methylal is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid methylal may contact the eyes.

SANITATION

- Skin that becomes wet with liquid methylal should be promptly washed or showered to remove any methylal.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methylal may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent for adhesives, resins, gums, waxes, and protective coatings; use as a solvent for extraction of alkaloids, barbituates, organic acids, and hydroxy-acids	General dilution ventilation; process enclosure; personal protective equipment
Use in manufacture of artificial resins; use as a gasoline and diesel fuel additive; use as a special fuel for rocket and jet engines	General dilution ventilation; process enclosure; personal protective equipment
Use as a reaction solvent with acetylene or in Grignard and Reppe reaction; use as a source of formaldehyde and methanol	General dilution ventilation; process enclosure; personal protective equipment
Use as a methylating agent or chemical intermediate	General dilution ventilation; process enclosure; personal protective equipment
Use in manufacture of perfume	General dilution ventilation; process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If methylal gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If methylal gets on the skin, promptly wash the contaminated skin with water, if the methylal has not already evaporated. If methylal soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention. If there is skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of methylal, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When methylal has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If methylal is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected, dissolved in alcohol of greater molecular weight than butyl alcohol, and atomized in a suitable combustion chamber. Methylal should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:
Methylal may be disposed of by dissolving in alcohol of greater molecular weight than butyl alcohol and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methylal," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Celanese Corporation: *Product Bulletin - Methylal*, New York.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Weaver, F. L., et al.: "Toxicity of Methylal," *British Journal of Industrial Medicine*, 8:279-283, 1951.

RESPIRATORY PROTECTION FOR METHYLAL

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methylamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3NH_2
- Synonyms: Monomethylamine; anhydrous methylamine
- Appearance and odor: Colorless gas with an odor like ammonia, but more fishy, particularly at lower concentrations. It can be stored under pressure as a liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methylamine is 10 parts of methylamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 12 milligrams of methylamine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methylamine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Methylamine may cause irritation of the eyes, nose, throat, and lungs. It may also cause coughing and sneezing. Both the liquid and vapor of methylamine are highly irritating to the eyes. Eye injury may occur if proper care is not given immediately. Methylamine solutions may burn the skin.

2. Long-term Exposure: Repeated or prolonged exposure to methylamine may cause irritation of the skin or eyes.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methylamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methylamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methylamine exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methylamine might cause exacerbation of symptoms due to its irritant properties.

—Eye disease: Methylamine causes eye damage in animals and eye irritation in humans. Persons with pre-existing eye disorders may be more susceptible to the effects of this agent.

—Skin disease: Methylamine in solution is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Methylamine gas is a severe eye and respiratory irritant. The LD50 was 0.1 to 0.2 g/kg in rats exposed orally to a 40% aqueous solution of methylamine. One case of bronchitis in a chemical worker has been reported; concentrations measured in the workroom ranged from 2 to 60 ppm; the duration of the exposure was not given. Brief exposures to 20 to 100 ppm are said to produce transient irritation of the eyes, nose, and throat. No symptoms of irritation are produced from longer exposures at less than 10 ppm. One drop of 5% aqueous solution caused conjunctival hemorrhage, superficial corneal opacities, and edema in experimental animals; a

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

40% solution caused corneal damage in rabbits. A 40% solution caused necrosis when applied to the skin of a rabbit. Dermatitis and conjunctivitis are occasionally observed in workers after prolonged exposure to the vapor.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 31.1
  2. Boiling point (760 mm Hg): −6.32 C (20.6 F)
  3. Specific gravity (water = 1): 0.656
  4. Vapor density (air = 1 at boiling point of methylamine): 1.1
  5. Melting point: −93.5 C (-136.3 F)
  6. Vapor pressure at 20 C (68 F): Not pertinent
  7. Solubility in water, g/100 g water at 25 C (77 F): 959 cc/100 ml
  8. Evaporation rate (butyl acetate = 1): Greater than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact of gas or liquid methylamine with mercury or with strong oxidizers will cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving methylamine.
  4. Special precautions: Liquid methylamine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: Not applicable (gas)
  2. Autoignition temperature: 430 C (806 F)
  3. Flammable limits in air, % by volume: Lower: 5; Upper: 21
  4. Extinguishant: Stop flow of gas; use carbon dioxide, alcohol foam, or dry chemical for water solutions
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold of 3.3 ppm. Patty reports that "olfactory fatigue occurs readily" upon exposure to methylamine.
  2. Eye Irritation Level: Grant reports that methylamine is an eye irritant, but the concentrations producing irritation are not given. Patty, however, reports that "brief exposures to 20 to 100 ppm produce transient eye . . . irritation."
  3. Other Information: Patty reports that transitory nose and throat irritation is caused by short exposures to 20 to 100 ppm.
  4. Evaluation of Warning Properties: Although the odor threshold of methylamine (3.3 ppm) is well below the permissible exposure limit, methylamine is treated as a material with poor warning properties, since "olfactory fatigue occurs readily." In addition, the irritant effects produced by brief exposures to methylamine are not considered to give adequate warning, since these effects are only transient.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for methylamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming contaminated with liquid methylamine or solutions containing methylamine or from becoming frozen from contact with vessels containing methylamine.
- Clothing wet with liquid methylamine or solutions containing methylamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methylamine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methylamine, the person performing the operation should be informed of methylamine's hazardous properties.
- Where there is any possibility of exposure of an employee's body to liquid methylamine or solutions

containing methylamine, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

- Any clothing which becomes wet with methylamine or non-impervious clothing which becomes contaminated with methylamine should be removed immediately and not reworn until the methylamine is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid methylamine or solutions containing methylamine contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid methylamine or solutions containing methylamine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with methylamine should be immediately washed or showered to remove any methylamine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methylamine may occur and control methods which may be effective in each case:

Operation	Controls
Use as a chemical intermediate in production of insecticides, herbicides, and fungicides; use as a chemical intermediate in production of surfactants	Local exhaust ventilation; general dilution ventilation
Use in production of rocket fuels and explosives	Local exhaust ventilation; general dilution ventilation
Use in production of pharmaceuticals and photographic chemicals; intermediate for dyes, textiles, dye assists, rubber, and anti-corrosive chemicals	Local exhaust ventilation; general dilution ventilation
Use as a polymerization inhibitor of hydrocarbons during distillization; use to prevent coagulation and webbing in natural and synthetic latex; use to prevent polymerization in paint removers	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid methylamine or solutions containing methylamine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid methylamine or solutions containing methylamine get on the skin, immediately flush the contaminated skin with water. If liquid methylamine or solutions containing methylamine soak through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of methylamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When a solution of methylamine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If methylamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak to disperse gas.
3. If in the gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
4. If in the liquid form, allow to vaporize.

• Waste disposal method:

Methylamine may be disposed of by burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methylamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Commercial Solvents Corporation: "Methylamine," *Manufacturers Bulletin*, 1965.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-57, Methylamine*, Washington, D.C., 1955.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR METHYLAMINE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Gas Concentration	
100 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a full facepiece providing protection against methylamine. Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methylcyclohexane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3C_6H_{11}$
- Synonyms: Cyclohexylmethane; hexahydrotoluene
- Appearance and odor: Colorless liquid with a faint, benzene-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methylcyclohexane is 500 parts of methylcyclohexane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2000 milligrams of methylcyclohexane per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for methylcyclohexane a Threshold Limit Value of 400 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methylcyclohexane can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to methylcyclohexane may cause light-headedness and drowsiness. It may also cause a slight irritation of the eyes, nose, and throat. At high concentrations, it may cause unconsciousness and death.

2. Long-term Exposure: Prolonged exposure to the liquid may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methylcyclohexane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methylcyclohexane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methylcyclohexane exposure.

—Skin disease: Methylcyclohexane is a skin defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although methylcyclohexane is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although methylcyclohexane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methylcyclohexane might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Methylcyclohexane vapor is a mild narcotic. Concentrations of 10,000 to 12,500 ppm were fatal to mice. Rabbits exposed to 3330 ppm for 300 hours showed minor evidence of liver and kidney injury, while 1200 ppm was innocuous for rabbits, and prolonged exposure at 370 ppm was harmless to monkeys. No toxic effects from industrial exposure have been reported. Prolonged

---

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

or repeated skin contact may produce drying and irritation due to defatting action.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 98
  2. Boiling point (760 mm Hg): 101 C (214 F)
  3. Specific gravity (water = 1): 0.77
  4. Vapor density (air = 1 at boiling point of methylcyclohexane): 3.4
  5. Melting point: −126 C (−196 F)
  6. Vapor pressure at 20 C (68 F): 37 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methylcyclohexane.
  4. Special precautions: Methylcyclohexane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −3.9 C (25 F) (closed cup)
  2. Autoignition temperature: 250 C (482 F)
  3. Flammable limits in air, % by volume: Lower: 1.2; Upper: 6.7
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Sax states that at the level of 500 ppm, methylcyclohexane "exhibits only a very faint odor."
  2. Irritation Levels: Sax states that "this material does not cause irritation to the eyes and nose."
  3. Evaluation of Warning Properties: At concentrations within two or three times the permissible exposure limit, methylcyclohexane can be detected through its odor. Therefore, for the purposes of this guideline, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of methylcyclohexane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methylcyclohexane may be used. An analytical method for methylcyclohexane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methylcyclohexane.
- Clothing wet with liquid methylcyclohexane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methylcyclohexane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methylcyclohexane, the person performing the operation should be informed of methylcyclohexane's hazardous properties.
- Any clothing which becomes wet with liquid methylcyclohexane should be removed immediately and not reworn until the methylcyclohexane is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid methylcyclohexane may contact the eyes.

SANITATION

• Skin that becomes wet with liquid methylcyclohexane should be promptly washed or showered with soap or mild detergent and water to remove any methylcyclohexane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methylcyclohexane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a diluent solvent for cellulose during spray application of lacquers	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during wire- and textile-coating operations with resins and rubber	General dilution ventilation
Liberation during brush and hand application of synthetic varnishes, lacquers, and paints	General dilution ventilation; personal protective equipment
Use during manufacture of rotogravure inks	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a solvent for oils, fats, waxes, and rubber; use as a diluent in resin molding; use as a degreasing agent	General dilution ventilation; personal protective equipment
Use in industrial organic synthesis in hydroreforming process	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methylcyclohexane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methylcyclohexane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If methylcyclohexane soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methylcyclohexane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If methylcyclohexane has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methylcyclohexane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Methylcyclohexane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• **Waste disposal method:**

Methylcyclohexane may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methylcyclohexane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Phillips Petroleum Company: *Material Safety Data Sheet – Methylcyclohexane*, Bartlesville, Oklahoma.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Treon, J. F., Crutchfield, W. E., and Kitzmiller, K. V.: "The Physiological Response of Rabbits to Cyclohexane, Methylcyclohexane, and Certain Derivatives of These Compounds: I. Oral Administration and Cutaneous Application," *Journal of Industrial Hygiene and Toxicology*, 25:6, p. 323, 1943.

RESPIRATORY PROTECTION FOR METHYLCYCLOHEXANE

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister. Any supplied-air respirator. Any self-contained breathing apparatus.
10,000 ppm or less	A gas mask with a front- or back-mounted organic vapor canister. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methylcyclohexanol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_7H_{14}O$
- Synonyms: Hexahydrocresols; mixture of 2-, 3-, and 4-methylcyclohexanols
- Appearance and odor: Straw-colored liquid with a weak coconut oil odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methylcyclohexanol is 100 parts of methylcyclohexanol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 470 milligrams of methylcyclohexanol per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has recommended for methylcyclohexanol a Threshold Limit Value of 50 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methylcyclohexanol can affect the body if it is inhaled, comes in contact with the eyes or skin, or swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Headache and irritation of the eyes, nose, and throat may result from prolonged exposure to excessive concentrations of methylcyclohexanol. Prolonged or repeated contact of liquid methylcyclohexanol may cause a skin rash. In animal experiments methylcyclohexanol has caused drowsiness, unconsciousness, and mild liver and kidney damage.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methylcyclohexanol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methylcyclohexanol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from methylcyclohexanol exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of methylcyclohexanol might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Methylcyclohexanol causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Methylcyclohexanol causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: Methylcyclohexanol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Neurologic disorders: By analogy to effects observed in animals, methylcyclohexanol may adversely affect the nervous system.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Methylcyclohexanol vapor is a mild irritant of the eyes and mucous membranes in animals; high concentrations cause signs of narcosis. The oral LD50 in rats was approximately 2 g/kg; effects were signs of narcosis;

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

autopsy findings included congestive changes in several organs, including the liver and kidneys. Repeated daily application of large doses to the skin of rabbits caused skin irritation, weakness, tremor, narcosis, and death. Repeated daily exposure of rabbits to 503 ppm for 10 weeks caused conjunctivitis and lethargy; 230 ppm caused no effects; narcosis did not occur at the highest vapor concentration achievable at room temperature. In humans, headache and irritation of the eyes and upper respiratory tract may result from prolonged exposure to excessive concentrations. Prolonged or repeated contact of the liquid on the skin may cause dermatitis due to a defatting action.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 114.2
2. Boiling point (760 mm Hg): 155 – 180 C (311 – 356 F)
3. Specific gravity (water = 1): 0.92
4. Vapor density (air = 1 at boiling point of methylcyclohexanol): 3.9
5. Melting point: Less than −21 C (less than −6 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Slight
8. Evaporation rate (butyl acetate = 1): 0.02

- **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving methylcyclohexanol.
4. Special precautions: Methylcyclohexanol will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 65 C (149 F) (closed cup)
2. Autoignition temperature: 296 C (565 F)
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Foam, dry chemical, carbon dioxide

- **Warning properties**

1. Odor Threshold: Patty states that "methylcyclohexanol vapor in air can be detected and recognized by its odor when present to the extent of 500 ppm . . . ."
2. Eye Irritation Level: The *Handbook of Organic Industrial Solvents* states that eye irritation does not occur until concentrations reach 500 ppm.
3. Other Information: Patty states that 500 ppm is capable of causing upper respiratory tract irritation.
4. Evaluation of Warning Properties: Since the odor and irritation thresholds of methylcyclohexanol are not within three times the permissible exposure limit, methylcyclohexanol is treated like a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for methylcyclohexanol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methylcyclohexanol.
- Clothing wet with methylcyclohexanol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methylcyclohexanol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methylcyclohexanol, the person performing the operation should be informed of methylcyclohexanol's hazardous properties.
- Non-impervious clothing which becomes contaminated with methylcyclohexanol should be removed promptly and not reworn until the methylcyclohexanol is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methylcyclohexanol may contact the eyes.

SANITATION

• Skin that becomes contaminated with methylcyclohexanol should be promptly washed or showered with soap or mild detergent and water to remove any methylcyclohexanol.
• Employees who handle liquid methylcyclohexanol should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methylcyclohexanol may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in lacquers, oils, gums, waxes, and resins	Process enclosure; local exhaust ventilation; personal protective equipment
Use as an auxiliary solvent for dry cleaning soaps in soap manufacture	Process enclosure; local exhaust ventilation; personal protective equipment
Use in textile industry as a blending agent in textile soaps; use as a degreaser; as an anti-oxidant in lubricants	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If liquid methylcyclohexanol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid methylcyclohexanol gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid methylcyclohexanol soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of methylcyclohexanol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When methylcyclohexanol has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If methylcyclohexanol is spilled or leaked, the following steps should be taken:
1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and reclaimed or atomized in a suitable combustion chamber.
• Waste disposal methods:
Methylcyclohexanol may be disposed of:
1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methylcyclohexanol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• *Handbook of Organic Industrial Solvents, Technical Guide No. 6* (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Treon, J. F., et al.: "The Physiological Response of Rabbits to Cyclohexane, Methylcyclohexane, and Certain Derivatives of These Compounds. I. Oral Administration and Cutaneous Application," *Journal of Industrial Hygiene and Toxicology*, 25:199-214, 1943.

• Treon, J. F., et al.: "The Physiological Response of Animals to Cyclohexane, Methylcyclohexane, and Certain Derivatives of These Compounds. II. Inhalation," *Journal of Industrial Hygiene and Toxicology*, 25:323-347, 1943.

RESPIRATORY PROTECTION FOR METHYLCYCLOHEXANOL

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
500 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methylene Bisphenyl Isocyanate (MDI)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $NCOC_6H_4CH_2C_6H_4NCO$
- Synonyms: MDI; 4,4-diphenylmethane diisocyanate; methylene bis (4-phenyl isocyanate); 4,4-diisocyantodiphenylmethane
- Appearance and odor: White to light-yellow flakes with no odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methylene bisphenyl isocyanate is a ceiling level of 0.02 part of methylene bisphenyl isocyanate per million parts of air (ppm). This may also be expressed as 0.2 milligram of methylene bisphenyl isocyanate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methylene bisphenyl isocyanate can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to methylene bisphenyl isocyanate may make a person allergic to it and produce wheezing, shortness of breath, and coughing. It may also cause irritation of the eyes and lungs, upset stomach, vomiting, possibly fever, stuffiness of the nose, sore throat, a feeling of tightness in the chest, cough, shortness of breath and wheezing. Such symptoms may be delayed up to eight hours after the person has been exposed.

2. Long-term Exposure: A person may become increasingly sensitive or allergic to methylene bisphenyl isocyanate. Chronic exposure to it may lead to permanent breathing or chest problems. Repeated or prolonged exposure of the skin to methylene bisphenyl isocyanate may cause a skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methylene bisphenyl isocyanate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methylene bisphenyl isocyanate at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to methylene bisphenyl isocyanate would be expected to be at increased risk from exposure. Examination of the eyes and respiratory tract should be stressed.

—14" x 17" chest roentgenogram: Methylene bisphenyl isocyanate may cause lung damage in humans. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Methylene bisphenyl isocyanate is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Methylene bisphenyl isocyanate (MDI) vapor is a potent respiratory sensitizer. It also is a strong irritant of the eyes, mucous membranes, and skin and can cause

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

pulmonary edema. Exposure of humans to high concentrations causes cough, dyspnea, increased secretions, and chest pain. Isocyanates cause pulmonary sensitization in susceptible individuals; should this occur, further exposure should be avoided, since extremely low levels of exposure may trigger an asthmatic episode; cross sensitization to unrelated materials probably does not occur. The liquid in contact with the eye may cause an irritation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 250.25
2. Boiling point (760 mm Hg): 172 C (341.6 F)
3. Specific gravity (water = 1): 1.27
4. Vapor density (air = 1 at boiling point of methylene bisphenyl isocyanate): 8.6
5. Melting point: 37 C (98.6 F)
6. Vapor pressure at 20 C (68 F): 0.05 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.2
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Temperatures above 37.8 C (100 F)
2. Incompatibilities: Avoid contact with strong alkalies, acids, and alcohol.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving methylene bisphenyl isocyanate.
4. Special precautions: Liquid methylene bisphenyl isocyanate will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 202 C (395.6 F) (open cup)
2. Autoignition temperature: 240 C (464 F)
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Carbon dioxide, dry chemical, or inert gas. For large fires, water in the form of spray should be used.

- **Warning properties**

1; Odor Threshold: No quantitative information is available.

2; Irritation Levels: By analogy to TDI, which, according to Grant, causes irritation of the eyes and nose beginning at 0.05 ppm to 0.1 ppm, MDI is assumed to produce eye and nose irritation at the same levels.

3; Evaluation of Warning Properties: MDI is treated as a material with poor warning properties, for the purposes of this guideline. By analogy with TDI, MDI is assumed to produce eye and nose irritation within several times the permissible exposure limit, but the permissible exposure is a ceiling concentration.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of methylene bisphenyl isocyanate. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

At the time of publication of this guideline, no measurement method for methylene bisphenyl isocyanate had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with solid methylene bisphenyl isocyanate or liquids containing methylene bisphenyl isocyanate, where skin contact may occur.
- If employees' clothing may have become contaminated with methylene bisphenyl isocyanate, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with methylene bisphenyl isocyanate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of methylene bisphenyl isocyanate from

the clothing. If the clothing is to be laundered or otherwise cleaned to remove the methylene bisphenyl isocyanate, the person performing the operation should be informed of methylene bisphenyl isocyanate's hazardous properties.

- Non-impervious clothing which becomes contaminated with methylene bisphenyl isocyanate should be removed promptly and not reworn until the methylene bisphenyl isocyanate is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid methylene bisphenyl isocyanate or liquids containing methylene bisphenyl isocyanate contacting the eyes.

SANITATION

- Skin that becomes wet with methylene bisphenyl isocyanate should be promptly washed or showered with soap or mild detergent and water to remove any methylene bisphenyl isocyanate.
- Employees who handle solid methylene bisphenyl isocyanate or liquids containing methylene bisphenyl isocyanate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methylene bisphenyl isocyanate may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during in place spraying of urethane foams	Local exhaust ventilation; respiratory protective equipment
Liberation during in place molding of urethane foams	Local exhaust ventilation; dilution ventilation
Liberation during application of polyisocyanate lacquer sealant finishes	Local exhaust ventilation; respiratory protective equipment
Liberation during shake-out and core knock-out operations at foundries using MDI-oil-base-no-bake binding systems	Local exhaust ventilation; respiratory protective equipment
Liberation during manufacture of lacquer	Process enclosure; local exhaust ventilation
Liberation during production of component chemicals for foam systems	Local exhaust ventilation; process enclosure
Liberation during casting of high-density polyurethane elastomers	Process enclosure; local exhaust ventilation
Liberation following combustion of urethane foams in fires or thermal decomposition to salvage metal inserts	Air-supply respiratory protective equipment or local exhaust ventilation
Liberation of unreacted vapor during cutting and fabricating of polyurethane foams	Local exhaust ventilation; respiratory protective equipment
Liberation during curing process; during flame lamination of fabrics	Process enclosure; local ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If methylene bisphenyl isocyanate or liquids containing methylene bisphenyl isocyanate get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If methylene bisphenyl isocyanate or liquids containing methylene bisphenyl isocyanate get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If methylene bisphenyl isocyanate or liquids containing methylene bisphenyl isocyanate soak through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention promptly.

- **Breathing**

If a person breathes in large amounts of methylene bisphenyl isocyanate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When methylene bisphenyl isocyanate or liquids containing methylene bisphenyl isocyanate have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify some-

one else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methylene bisphenyl isocyanate is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.

2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Methylene bisphenyl isocyanate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methylene Bisphenyl Isocyanate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Toluene-2,4-Diisocyanate," *Hygienic Guide Series*, Detroit, Michigan, 1967.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Key, M. M.: "Occupational Dermatitis from Plastics," *Journal of Medicine of the Association of Georgia*,57:421-424, September 1968.

• Konzen, R. B., et al.: "Human Response to Low Concentrations of p, p-Diphenylmethane Diisocyanate (MDI)," *American Industrial Hygiene Association Journal*, 27:121-127, 1966.

• Lapp, N. L.: "Physical Changes in Diagnostic Aids in Isocyanate Exposure," *American Industrial Hygiene Association Journal*, 32:378-382, 1971.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Toluene Diisocyanate*, HSM 73-11022, U.S. Government Printing Office, Washington, D.C., 1973.

• Rye, W. A.: "Human Responses to Isocyanate Exposure," *Journal of Occupational Medicine*, 15:306-307, 197

• Woolrich, P. F., and Rye, W. A.: "Urethanes – Engineering, Medical Control and Toxicologic Considerations," *Journal of Occupational Medicine*, 11:184-190, 1969.

RESPIRATORY PROTECTION FOR METHYLENE BISPHENYL ISOCYANATE (MDI)

Condition	Minimum Respiratory Protection* Required Above 0.02 ppm
Vapor or Particulate Concentration	
1 ppm (10 mg/m³) or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 ppm (100 mg/m³) or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10 ppm (100 mg/m³) or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Methylene Chloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_2Cl_2
- Synonyms: Dichloromethane; methylene dichloride
- Appearance and odor: Colorless liquid with an odor like chloroform.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for methylene chloride is 500 parts of methylene chloride per million parts of air (ppm) averaged over an eight-hour work shift, with an acceptable ceiling level of 1000 ppm and a maximum peak concentration of 2000 ppm for 5 minutes in any two-hour period. NIOSH has recommended that the permissible exposure limit be reduced to 75 ppm averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 500 ppm averaged over a 15-minute period. NIOSH further recommends that permissible levels of methylene chloride be reduced where carbon monoxide is present. The NIOSH Criteria Document for Methylene Chloride should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Methylene chloride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Methylene chloride is an anesthetic. Inhaling the vapor may cause mental confusion, light-headedness, nausea, vomiting, and headache. Continued exposure may cause increased light-headedness, staggering, unconsciousness, and death. High vapor concentrations may also cause irritation of the eyes and respiratory tract. Exposure to this chemical may make the symptoms of angina worse. Skin exposure to the liquid may cause irritation. If the liquid is held in contact with the skin, it may cause skin burns. Splashes of the liquid into the eyes may cause irritation.

2. Long-term Exposure: Prolonged or repeated exposure to methylene chloride may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to methylene chloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to methylene chloride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the skin, liver, kidneys, cardiovascular system, and blood should be stressed. Clinical impressions of the autonomic nervous system and pulmonary function should be made, with additional tests conducted where indicated.

—Skin disease: Methylene chloride can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver function test: Methylene chloride causes liver damage in animals and this justifies consideration before exposing persons with impaired liver function. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Kidney disease: Methylene chloride causes kidney damage in animals and this justifies special considera-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

tion before exposing persons with impaired renal function.

—Cardiovascular disease: Because of reports of excessive carbon monoxide levels following exposure to methylene chloride, persons with cardiac disease may be at increased risk.

—A complete blood count: A complete blood count should be performed, including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit. Carboxyhemoglobin values should also be determined periodically, and any level above 5% should prompt an investigation of the worker and his workplace.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Methylene chloride vapor is a mild narcotic. Exposure of animals to 15,000 ppm for 7 hours was fatal. Animal experiments have shown that continuous exposure to 1,000 ppm can be lethal in 5 to 7 weeks for dogs and that fatty livers, icterus, pneumonia, and splenic atrophy developed in dogs. Cardiac arrhytmias attributed to sensitization of the myocardium have been observed following exposure to high concentrations of some chlorinated hydrocarbons, but dogs exposed to 10,000 and 20,000 ppm of methylene chloride did not show this phenomenon. In human experiments, inhalation of 500 to 1000 ppm for 1 to 2 hours resulted in lightheadedness; there was sustained elevation of carboxyhemoglobin level. High exposures have resulted in deaths in industrial situations. Lower but unknown concentrations have caused such symptoms as lightheadedness, weakness, nausea, and "drunken behavior," resulting in mistakes and accidental falls. Phosgene poisoning has been reported to occur in several cases where methylene chloride was used in the presence of an open fire. Liquid methylene chloride is irritating to the skin on repeated contact. Splashed in the eye, it is painfully irritating, but is not likely to cause serious injury.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 84.9
2. Boiling point (760 mm Hg): 39.8 C (104 F)
3. Specific gravity (water = 1): 1.3
4. Vapor density (air = 1 at boiling point of methylene chloride): 2.9
5. Melting point: −97 C (−142 F)
6. Vapor pressure at 20 C (68 F): 350 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 1.32
8. Evaporation rate (butyl acetate = 1): 27.5

• **Reactivity**

1. Conditions contributing to instability: Heat and moisture
2. Incompatibilities: Contact with strong oxidizers, strong caustics, and chemically active metals such as aluminum or magnesium powder, sodium and potassium may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving methylene chloride.
4. Special precautions: Liquid methylene chloride will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: None with normal test method
2. Autoignition temperature: 556 C (1033 F)
3. Flammable limits in air, % by volume: (at elevated temperatures) Lower: 12; Upper: 19
4. Extinguishant: Dry chemical, carbon dioxide, foam

• **Warning properties**

1. Odor Threshold: Different authors have reported varying odor thresholds for methylene chloride. Summer and May both report 150 ppm; Kirk-Othmer and Sax both report 25 to 50 ppm; Spector reports 320 ppm. Patty, however, states that since one can become adapted to the odor, it cannot be considered an adequate warning property.
2. Eye Irritation Level: Grant reports that methylene chloride "presents no particular hazard to the eyes." Kirk-Othmer, however, reports that "methylene chloride vapor is seriously damaging to the eyes." Sax agrees with Kirk-Othmer's statement.

The *Documentation of TLV's* states that irritation of the eyes has been observed in workers who had been exposed to concentrations up to 5000 ppm, but that neurasthenic disorders were found in 50% and digestive disturbances in 30% of the persons exposed.

3. Other Information: Gleason reports that methylene chloride may be "irritating to the respiratory tract and may produce pulmonary edema" but gives no quantitative information. The *Documentation of TLV's* reports that in one investigation, irritation of the respiratory passages was observed in workers who had been exposed to concentrations up to 5000 ppm.
4. Evaluation of Warning Properties: Since no detailed information is available relating the irritant effects of methylene chloride to air concentrations and since adaptation to the odor occurs, methylene chloride is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of methylene chloride. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Peak Above Ceiling Evaluation**

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of methylene chloride. Each measurement should consist of a 30-minute sample or a series of consecutive samples totalling 30 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure methylene chloride may be used. An analytical method for methylene chloride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid methylene chloride.

• Non-impervious clothing which becomes wet with liquid methylene chloride should be removed promptly and not reworn until the methylene chloride is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid methylene chloride may contact the eyes.

SANITATION

• Skin that becomes wet with liquid methylene chloride should be promptly washed or showered with soap or mild detergent and water to remove any methylene chloride.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to methylene chloride may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in paint and varnish removers; manufacture of aerosols; cold cleaning and ultrasonic cleaning; and as an extraction solvent for foods and furniture processing	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a cooling solvent in manufacture of cellulose acetate; in organic synthesis; and in plastics processing	Process enclosure; local exhaust ventilation
Use as a solvent in vapor degreasing of thermal switches and thermometers	Process enclosure; local exhaust ventilation
Use as a secondary refrigerant in air conditioning and scientific testing	General dilution ventilation; local exhaust ventilation; personal protective equipment

Operation	Controls
Use as an extraction solvent for edible fats, coca, butter, beer flavoring in hops, decaffeinated coffee, oleoresin manufacture, oils, waxes, perfumes, flavorings, and drugs	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a solvent for paints, lacquers, varnishes, enamels, adhesives, rubber cements, manufacture of printed circuit boards, as a carrier for pharmaceutical tablet coatings, shrink-fitting of synthetic rubber covers, and dyeing of synthetic fibers	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If methylene chloride gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If methylene chloride gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water if the methylene chloride has not already evaporated. If methylene chloride soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of methylene chloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When methylene chloride has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the packa This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If methylene chloride is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Methylene Chloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Dichloromethane," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hughes, J. P.: "Hazardous Exposure to Some So-Called Safe Solvents," *Journal of the American Medical Association*, 156:234-237, Sept. 18, 1954.

• *Hygienic Information Guide No. 98 - Methylene Chloride*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1963.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-86, Methylene Chloride*, Washington, D.C., 1962. D.C., 1962.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Fire Protection Association: *Fire Protection Handbook* (13th ed.), National Fire Protection Association, Boston, 1969.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Methylene Chloride* HEW Publication No. (NIOSH) 76-138, GPO No. 017-033-00194-4, U.S. Government Printing Office, Washing-

ton, D.C., 1976.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Reinhardt, C. F., et al.: "Epinephrine-Induced Cardiac Arrythmia Potential of Some Common Industrial Solvents," *Journal of Occupational Medicine*, 15:953-955, 1973.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
• Stewart, R. D., and Dodd, H. C.: "Absorption of Carbon Tetrachloride, Trichloroethylene, Tetrachloroethylene, Methylene Chloride, and 1,1,1-Trichloroethane through the Human Skin," *Industrial Hygiene Journal*, Sept. - Oct., 1964, p. 439.
• Stewart, R. D., et al.: "Experimental Human Exposure to Methylene Chloride," *Archives of Environmental Health*, 25:342-348, 1972.
• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.
• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR METHYLENE CHLORIDE

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
5000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Mica

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Muscovite (most important) is: $K_2Al_4(Al_2Si_6O_{20})(OH)_4$ (typical)
- Synonyms: Muscovite; amber mica; roscoelite; lepidolite; phlogopite; biotite; zinnwaldite; fluorophlogopite
- Appearance and odor: Colorless, odorless flakes or sheets containing less than 1% quartz (free crystalline silica).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for mica is 20 million particles of mica per cubic foot of air (mppcf) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Mica can affect the body if it is inhaled.

- **Effects of overexposure**

Exposure to mica dust over a period of years may cause scarring of the lungs. The symptoms which may occur with this condition are cough, shortness of breath, weakness, and weight loss.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to mica.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to mica at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed.

—14" x 17" chest roentgenogram: Mica causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Mica causes pneumoconiosis. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Mica dust causes pneumoconiosis. In a study of 57 workers exposed to mica dust, 5 of the 6 workers exposed more than 10 years to concentrations in excess of 25 mppcf had pneumoconiosis. The most characteristic finding by chest x-ray was fine granulation of uneven density; there was a tendency to a coalescence of shadows in some cases. The symptoms most frequently reported were chronic cough and dyspnea; complaints of weakness and weight loss were less frequent.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Formula weight (muscovite): 797
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 2.6 – 3.2
4. Vapor density (air = 1 at boiling point of mica): Not applicable
5. Melting point: Not applicable
6. Vapor pressure at 20 C (68 F): Essentially zero

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service ·nters for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble

8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Mica is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for mica had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to mica may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from open and underground mining operations	General dilution ventilation; local exhaust ventilation; dust collection; process enclosure; personal protective equipment; wet drilling
Use in manufacture of electrical insulation for low thermal conductivity and high dielectric strength	General dilution ventilation; local exhaust ventilation; dust collection; wet methods; personal protective equipment
Use in manufacture of asphalt shingles and roll roofing	General dilution ventilation; local exhaust ventilation; dust collection; process enclosure; personal protective equipment
Use in manufacture of paint, wall paper, and bituminized cardboard	General dilution ventilation; local exhaust ventilation; dust collection; wet methods; personal protective equipment
Use in manufacture of molded rubber products; plastics; special greases; absorbent of well drilling muds	General dilution ventilation; local exhaust ventilation; dust collection; personal protective equipment
Use in fabrication of windows and diaphragms	Process enclosure

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If mica gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Breathing**

If a person breathes in large amounts of mica, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency

rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or releases until cleanup has been completed.

• If mica is spilled or released in hazardous concentrations, the following steps should be taken:

1. Ventilate area of spill or release.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a sanitary landfill.

• Waste disposal method:

Mica may be disposed of in a sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Mica," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dreessen, W. C., et al.: "Pneumoconiosis among Mica and Pegmatite Workers," U.S. Public Health Service Bulletin No. 250, U.S. Government Printing Office, Washington, D.C., pp. 1-74, 1940.

• Heimann, H., et al.: "Note on Mica Dust Inhalation," *Industrial Hygiene and Occupational Medicine*, 8:531-532, 1953.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Morgan, W. K. C., and Seaton, A.: *Occupational Lung Diseases*, Saunders, Philadelphia, 1975.

• Plunkett, E. R.: *Handbook of Industrial Toxicology*, Chemical Publishing Company, Inc., New York, 1966.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Vestal, T. F., et al.: "Pneumoconiosis among Mica and Pegmatite Workers," *Industrial Medicine*, 12:11-14, 1943.

RESPIRATORY PROTECTION FOR MICA

Condition	Minimum Respiratory Protection* Required Above 20 mppcf
Particulate Concentration	
100 mppcf or less	Any dust respirator.
200 mppcf or less	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
1000 mppcf or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 mppcf or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 10,000 mppcf or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Molybdenum and Insoluble Molybdenum

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all molybdenum and insoluble molybdenum compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Metallic molybdenum

- Formula: Mo
- Synonyms: None
- Appearance: Silvery white metal or gray-black powder.

Molybdenum disulfide

- Formula: MoS_2
- Synonyms: Molybdenite
- Appearance and odor: Shiny gray, odorless plates.

Lead molybdate

- Formula: $PbMoO_4$
- Synonyms: Sulfenite
- Appearance and odor: Colorless to pale yellow, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for molybdenum and insoluble molybdenum compounds is 15 milligrams of molybdenum and insoluble molybdenum compounds per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for molybdenum and insoluble molybdenum compounds a Threshold Limit Value of 10 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Molybdenum and insoluble molybdenum compounds can affect the body if they are inhaled or if they come in contact with the eyes. They can also affect the body if they are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Molybdenum trioxide has caused irritation of the eyes, nose, and throat, weight loss, and digestive disturbances in animals.

2. Long-term Exposure: Not known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to molybdenum and insoluble molybdenum compounds.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to molybdenum and insoluble molybdenum compounds at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from molybdenum and insoluble molybdenum compounds exposure.

—Kidney disease: Fume from arcing molybdenum metal causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

[redacted]

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

—Chronic respiratory disease: Fume from arcing molybdenum metal causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of insoluble molybdenum compounds might cause exacerbation of symptoms due to their irritant properties.

—Liver disease: Fume from arcing molybdenum metal causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

• **Summary of toxicology**

Molybdenum and its insoluble compounds, which include molybdenum disulfide, calcium molybdate, and many of the oxides and halides, have a low toxicity; however, molybdenum trioxide irritates the eyes and mucous membranes. Guinea pigs repeatedly exposed to molybdenum trioxide dust at a concentration of 200 mg molybdenum/m³ for 1 hour daily developed nasal irritation, diarrhea, weight loss, and incoordination. In guinea pigs exposed to fume from arcing molybdenum metal, there were some deaths at 190 mg/m³ but minimal effects at 53 mg/m³; autopsy revealed bronchial and alveolar irritation with moderate fatty changes in the liver and kidneys. Animals receiving daily oral doses of up to 500 mg molybdenum per day in the form of molybdenum trioxide or calcium molybdate showed anorexia, listlessness, and weight loss. The metabolism of molybdenum is closely associated with that of copper; molybdenum toxicity to animals can be alleviated by the administration of copper. While molybdenum is essential to the action of certain enzymes, higher molybdenum levels may inhibit the action of these enzymes. High intake of molybdenum in rats resulted in a substantial reduction in activity of sulfide oxidase in the liver. The reduced activity of this enzyme leads to accumulation of sulfide in the tissues and subsequent formation of highly undissociated copper sulfide, thus removing copper from metabolic activity. This is a probable explanation for the induction of copper deficiency by molybdate. High dietary intake of molybdenum has been reported to be associated with a gout-like disease and high blood uric acid.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Metallic molybdenum**

1. Molecular weight: 95.94
2. Boiling point (760 mm Hg): 5,560 C (10,040 F)
3. Specific gravity (water = 1): 10.22
4. Vapor density (air = 1 at boiling point of metallic molybdenum): Not applicable
5. Melting point: 2,610 C (4,730 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Molybdenum disulfide**

1. Molecular weight: 160.1
2. Boiling point (760 mm Hg): Oxidizes above 315 C (599 F)
3. Specific gravity (water = 1): 4.7
4. Vapor density (air = 1 at boiling point of molybdenum disulfide): Not applicable
5. Melting point: 1370 C (2498 F) (oxidizes above 315 C (599 F))
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Lead Molybdate**

1. Molecular weight: 367.1
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 6.8
4. Vapor density (air = 1 at boiling point of lead molybdate): Not applicable
5. Melting point: 1066 C (1950 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.000012
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact of finely divided molybdenite with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as molybdenum oxide fume, sulfur dioxide gas, and carbon monoxide) may be released when insoluble molybdenum compounds decompose.
4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable
2. Minimum ignition temperature: Molybdenum: 360 C (680 F) (layer); 720 C (1328 F) (cloud); Molybdenite: 290 C (554 F) (layer); 570 C (1058 F) (cloud)
3. Minimum explosive concentration: Data not available
4. Extinguishant: Molybdenum and molybdenum disulfide: Dry sand, dry dolomite, dry graphite

• **Warning properties**

None of the insoluble compounds of molybdenum are known to be significant eye irritants.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour

samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of molybdenum and insoluble molybdenum compounds on a filter, followed by chemical treatment, and atomic absorption spectrophotometric analysis. An analytical method for molybdenum and insoluble molybdenum compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

SANITATION

• Eating and smoking should not be permitted in areas where solids containing molybdenum and insoluble molybdenum compounds are handled, processed, or stored.

• Employees who handle solids or liquids containing insoluble molybdenum compounds should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to molybdenum and insoluble molybdenum compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from mining and processing of ore; from grinding and other abrasive treatment of metal or alloys for use in electrical contacts, spark plugs, x-ray tubes, grids for radio tubes, missle and aircraft parts, and iron/steel alloys	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as lubricants in greases, oil dispersions, resin-bonded films, and dry powders; as catalysts in petroleum refining and chemical processing	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in pigment mixture for labelling glass bottles, for printing inks, for paints, and for plastics; as reagents in analytical chemistry laboratories	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in powder as chemical intermediates; use in molybdic acid; use as alloying agents in production of iron/steel	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as catalysts in organic synthesis in medicinals, in decorative and protective coatings for metal, and as feed additives	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during temperature application as protective coatings for electrical resistors and engine parts, and as catalysts	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as chemical intermediates and plating agents for mirrors; use in metal brazing and in manufacture of cutting tools	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment

Liberation during use as solid lubricants	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation as catalysts in manufacture of propylene oxide	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in chemical laboratory	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of molybdenum and insoluble molybdenum compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When molybdenum and insoluble molybdenum compounds have been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If molybdenum and insoluble molybdenum compounds are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation, or for disposal in a secured sanitary landfill. Liquid containing insoluble molybdenum compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Molybdenum and insoluble molybdenum compounds may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Molybdenum as Mo," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Molybdenum," *Hygienic Guide Series*, Detroit, Michigan, 1960.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Halverson, A. W., et al.: "A Mechanism for the Copper-Molybdenum Interrelationship," *Journal of Nutrition*, 71:95-100, 1960.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kovalsky, V. V., et al.: "Changes in Purine Metabolism in Man and Animals in Various Molybdenum-Rich Biogeochemical Provinces," *Z. Obsc. Biol.*, 22:179, 1961.

• Lauring, L., and Wergeland, F. L.: "Ocular Toxicity of New Industrial Metals," *Military Medicine*, 135:12, pp. 1171-1174, December 1970.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR MOLYBDENUM AND INSOLUBLE MOLYBDENUM COMPOUNDS (AS MOLYBDENUM)

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Dust or Mist Concentration	
75 mg/m³ or less	Any dust and mist respirator, except single-use.
150 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator.
Dust, Mist, or Fume Concentration	
150 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
7,500 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 7,500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Soluble Molybdenum Compounds (as Molybdenum)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all soluble molybdenum compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION— Molybdenum trioxide

- Formula: MoO_3
- Synonyms: Molybdenum anhydride; molybdic oxide
- Appearance and odor: Yellow to white, odorless solid.

SUBSTANCE IDENTIFICATION— Ammonium molybdate

- Formula: $(NH_4)_2MoO_4$
- Synonyms: 85% molybdic acid
- Appearance and odor: Yellow to white, odorless solid.

SUBSTANCE IDENTIFICATION— Ammonium paramolybdate

- Formula: $(NH_4)_6Mo_7O_{24}\cdot 4H_2O$
- Synonyms: None
- Appearance and odor: Yellow to white, odorless solid.

SUBSTANCE IDENTIFICATION— Calcium molybdate

- Formula: $CaMoO_4$
- Synonyms: None
- Appearance and odor: Yellow to white, odorless solid.

SUBSTANCE IDENTIFICATION— Sodium molybdate, dihydrate

- Formula: $Na_2MoO_4\cdot 2H_2O$
- Synonyms: Sodium molybdate
- Appearance: White crystalline powder.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for soluble molybdenum compounds is 5 milligrams of soluble molybdenum compounds (as molybdenum) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Soluble molybdenum compounds can affect the body if they are inhaled or if they come in contact with the eyes or skin. They might also affect the body if they are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Soluble molybdenum compounds have caused loss of appetite, incoordination, and irritation of eyes, nose, and throat, difficulty in breathing, anemia, and colic in animals.

2. Long-term Exposure: Animal data suggest that repeated exposure to soluble molybdenum compounds might be associated with gout.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to soluble molybdenum compounds.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

• **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to soluble molybdenum compounds at potentially hazardous levels:

1. Initial Medical Screening: Routine medical histories and physical examinations are not considered necessary. However, the employer should screen employees for history of certain medical conditions (listed below) which might place the employee at increased risk from soluble molybdenum compounds exposure. Only those giving a positive history of these conditions should be referred for further medical examinations.

—Kidney disease: Although soluble molybdenum compounds are not known as kidney toxins in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of soluble molybdenum compounds might cause exacerbation of symptoms due to their irritant properties.

—Blood disease: Soluble molybdenum compounds cause anemia in animals. Persons with pre-existing blood disorders may be more susceptible to the effects of these agents.

—Gout: Soluble molybdenum compounds may cause gout. Persons with pre-existing conditions may be more susceptible to the effects of these agents.

2. Periodic Medical Examination: Routine periodic examinations are not considered necessary. However, anyone developing the above listed conditions should be referred for further medical examination.

• **Summary of toxicology**

Soluble molybdenum compounds have a low toxicity but may cause anemia and deformities of the forelegs when fed to rabbits in high doses. In rats, the approximate oral LD50 for daily repeated doses of ammonium molybdate was 333 mg molybdenum/g/day; sodium molybdate was fatal to rabbits within a few weeks at a dietary level of 0.1%. In rats and guinea pigs, oral doses of 1.2 g/kg ammonium molybdate caused anorexia, colic, trembling, incoordination, and dyspnea; anemia and deformity of the forelegs occurred in rabbits. Exposure of mice for 1 hour to a high concentration of the dust of ammonium molybdate caused a transitory irritation of mucous membranes. While molybdenum is essential to the action of certain enzymes, higher molybdenum levels may inhibit the action of other enzymes. High intake of molybdenum in rats resulted in a substantial reduction in activity of sulfide oxidase in the liver. The reduced activity of this enzyme leads to accumulation of sulfide in the tissues and subsequent formation of highly undissociated copper sulfide, thus removing copper from metabolic activity. This is a probable explanation for the induction of copper deficiency by molybdate. There have been no reports of systemic effects from industrial exposure. A study from the Ankavan Province of Russia, where dietary molybdenum intake ranges from 10 to 15 mg per day due to high natural levels, has shown elevated blood xanthine oxidase activity and increased uric acid concentrations in blood of residents compared with controls living in an area with lower molybdenum exposure. A high percentage (31%) of the population examined from the Ankavan Province were diagnosed as having a gout-like disease.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Molybdic trioxide**

1. Molecular weight: 144
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 4.7
4. Vapor density (air = 1 at boiling point of soluble molybdenum compounds): Not applicable
5. Melting point: 795 C (1463 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.5
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Ammonium molybdate**

1. Molecular weight: 196
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 2.3
4. Vapor density (air = 1 at boiling point of soluble molybdenum compounds): Not applicable
5. Melting point: Decomposes
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Soluble, decomposes
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Ammonium paramolybdate**

1. Molecular weight: 1238
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 2.5
4. Vapor density (air = 1 at boiling point of soluble molybdenum compounds): Not applicable
5. Melting point: Decomposes
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 43
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Calcium molybdate**

1. Molecular weight: 200
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 4.35
4. Vapor density (air = 1 at boiling point of soluble molybdenum compounds): Not applicable
5. Melting point: 695 C (1283 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.01
8. Evaporation rate (butyl acetate = 1): Not applica-

ble

- **Physical data—Sodium molybdate, dihydrate**

1. Molecular weight: 241.95
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 3.28
4. Vapor density (air = 1 at boiling point of soluble molybdenum compounds): Not applicable
5. Melting point: Loses its water at 100 C (212 F)
6. Vapor pressure at 20 C (68 F): Data not available
7. Solubility in water, g/100 g water at 0 C (32 F): 56.2
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Ammonium molybdate and ammonium paramolybdate decompose above 360 C (680 F). Other are stable.
2. Incompatibilities: Contact with alkali metals such as sodium and potassium or with molten magnesium may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as ammonia and carbon monoxide) may be released when some soluble molybdenum compounds decompose.
4. Special precautions: None

- **Flammability**

1. Not combustible

- **Warning properties**

According to Patty, "exposure to molybdenum oxide is irritating to eyes . . .," but he gives no quantitative information concerning the concentrations necessary. Examples of molybdenum compounds which cause eye irritation are: compounds containing nitrate, acetate, chloride, trioxide, and molybdate.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of soluble molybdenum compounds on a filter, followed by leaching-off of analyte with hot water and atomic absorption spectrophotometric analysis. An analytical method for soluble molybdenum compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with soluble molybdenum compounds or liquids containing soluble molybdenum compounds.
- Non-impervious clothing which becomes contaminated with soluble molybdenum compounds should be removed promptly and not reworn until the soluble molybdenum compounds are removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where soluble molybdenum compounds or liquids containing soluble molybdenum compounds may contact the eyes.

SANITATION

- Skin that becomes contaminated with soluble molybdenum compounds should be promptly washed or showered with soap or mild detergent and water to remove any soluble molybdenum compounds.
- Eating and smoking should not be permitted in areas where soluble molybdenum compounds are handled, processed, or stored.
- Employees who handle soluble molybdenum compounds or liquids containing soluble molybdenum compounds should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to soluble molybdenum compounds

may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during rolling of hot billets in processing molybdenum steel; for use as electrodes; during welding operations	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as chemical reagent for laboratory analyses; in petroleum refining and chemical processing; as an intermediate in the manufacture of corrosion inhibitors; use as coloring agents for enamels and ceramic glazes; agricultural chemicals	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in electroplating process; use in formulation of corrosion inhibitors for aqueous systems; pigments for paints, lacquers, and coloring animal fibers and hair	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in enamel processes for adherence of vitreous coatings to ceramics and metal; use in leather and skin tanning	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as chlorination catalysts; in fire-retardant resins; as a brazing flux and as an intermediate for organo-metallic compounds; use in photography; ion exchange processes and formulation of plastics and adhesives; as a catalyst in desulfurization of gasoline; use as a reagent for determination of phosphorus and lead	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If soluble molybdenum compounds or liquids containing soluble molybdenum compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

- **Skin Exposure**

If soluble molybdenum compounds or liquids containing soluble molybdenum compounds get on the skin, flush the contaminated skin with water. If soluble molybdenum compounds or liquids containing soluble molybdenum compounds penetrate through the clothing, remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of soluble molybdenum compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When soluble molybdenum compounds or liquids containing soluble molybdenum compounds have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If soluble molybdenum compounds or liquids containing soluble molybdenum compounds are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquids containing soluble molybdenum compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:
Soluble molybdenum compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Molybdenum as Mo," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Molybdenum," *Hygienic Guide Series*, Detroit, Michigan, 1960.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Halverson, A. W., et al.: "A Mechanism for the Copper-Molybdenum Interrelationship," *Journal of Nutrition*, 71:95-100, 1960.

• Kovalsky, V. V., et al.: "Changes in Purine Metabolism in Man and Animals in Various Molybdenum-Rich Biogeochemical Provinces," *Z. Obsc. Biol.*, 22:179, 1961.

• Lauring, L., and Wergeland, F. L.: "Ocular Toxicity of New Industrial Metals," *Military Medicine*, 115:12, pp. 1171-1174, 1970.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR SOLUBLE MOLYBDENUM COMPOUNDS (AS MOLYBDENUM)

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
25 mg/m³ or less	Any dust or mist respirator**.
50 mg/m³ or less	Any dust and mist respirator, except single-use or quarter mask respirators**. Any high efficiency particulate filter respirator**.
250 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece**. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter and a full facepiece, helmet, or hood.
10,000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**In those cases where eye irritation occurs, full facepiece respirators are recommended. Examples of molybdenum compounds which cause eye irritation are: compounds containing nitrate, acetate, chloride, trioxide, and molybdate.

Occupational Health Guideline for Monomethyl Aniline

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5NH(CH_3)$
- Synonyms: N-Methyl aniline; MA; methyl aniline
- Appearance and odor: Yellow to light brown liquid with a weak, ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for monomethyl aniline is 2 parts of monomethyl aniline per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 9 milligrams of monomethyl aniline per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has recommended for monomethyl aniline a Threshold Limit Value of 0.5 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Monomethyl aniline can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Monomethyl aniline may cause a bluish discoloration of the skin. Headache, dizziness, weakness, drowsiness, and unconsciousness may also occur.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to monomethyl aniline.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to monomethyl aniline at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, liver, kidneys, and blood should be stressed.

—A complete blood count: Monomethyl aniline has been shown to cause methemoglobinemia and anemia in animals. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit and a methemoglobin determination.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Monomethyl aniline vapor causes anoxia due to the formation of methemoglobin. Animal fatalities occurred from daily exposures to 7.6 ppm; signs of intoxication included prostration, labored breathing, and cyanosis; methemoglobinemia developed promptly in rabbits and cats; the rabbits also exhibited mild anemia and bone marrow hyperplasia. Autopsy of animals that died revealed pulmonary involvement ranging from edema to interstitial pneumonia, as well as occasional centrilobular hepatic necrosis and moderate kidney damage. The liquid readily caused poisoning in animals by absorption through the skin. No effects from industrial exposure have been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 107.2

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

2. Boiling point (760 mm Hg): 195.6 C (384 F)
3. Specific gravity (water = 1): 0.99
4. Vapor density (air = 1 at boiling point of monomethyl aniline): 3.70
5. Melting point: −80 C (-112 F) (approximately)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Moderate
8. Evaporation rate (butyl acetate = 1): Less than 1

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact of liquid monomethyl aniline with strong acids will cause violent spattering. Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving monomethyl aniline.
4. Special precautions: Liquid monomethyl aniline will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 79.4 C (175 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, carbon dioxide, alcohol foam

• **Warning properties**

1. Odor Threshold: Cyanamid's *Chemical Safety Data Sheet* states that monomethyl aniline has a "moderate aniline-type odor," but no quantitative information is available concerning the odor threshold.
2. Eye Irritation Level: Monomethyl aniline vapor is not a known eye irritant.
3. Evaluation of Warning Properties: Since no information is available relating warning properties of monomethyl aniline to air concentrations, the substance is considered to have poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of monomethyl aniline in a bubbler filled with sulfuric acid, followed by treatment with sodium hydroxide, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure monomethyl aniline may be used. An analytical method for monomethyl aniline is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid monomethyl aniline, where skin contact may occur.

• Clothing contaminated with monomethyl aniline should be placed in closed containers for storage until it can be discarded or until provision is made for removal of monomethyl aniline from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the monomethyl aniline, the person performing the operation should be informed of monomethyl aniline's hazardous properties.

• Non-impervious clothing which becomes contaminated with monomethyl aniline should be removed immediately and not reworn until the monomethyl aniline is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid monomethyl aniline may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid monomethyl aniline should be immediately washed or showered with soap or mild detergent and water to remove any monomethyl aniline.

• Eating and smoking should not be permitted in areas where liquid monomethyl aniline is handled, processed, or stored.

• Employees who handle liquid monomethyl aniline should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to monomethyl aniline may occur and control methods which may be effective in each case:

Operation	Controls
Use during organic synthesis and in dye intermediates	Process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If monomethyl aniline gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If monomethyl aniline gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If monomethyl aniline soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention.

• **Breathing**

If a person breathes in large amounts of monomethyl aniline, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When monomethyl aniline has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If monomethyl aniline is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Monomethyl aniline may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Monomethyl Aniline," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Cyanamid Corporation: *Chemical Safety Data Sheet - Monomethyl Aniline.*

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969. *1969.*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Treon, J. F., et al.: "The Toxic Properties of Xylidine and Monomethylaniline," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 1:506-524, 1950.

RESPIRATORY PROTECTION FOR MONOMETHYL ANILINE

Condition	Minimum Respiratory Protection* Required Above 2 ppm
Vapor Concentration	
20 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
100 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a half facepiece operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against monomethyl aniline. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Morpholine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_4H_9ON
- Synonyms: Tetrahydro-1,4-oxazine; diethyleneimide oxide
- Appearance and odor: Colorless liquid with a weak, ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for morpholine is 20 parts of morpholine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 70 milligrams of morpholine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Morpholine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Morpholine may cause irritation of the eyes, nose, throat, lungs, and skin.

2. Long-term Exposure: Repeated or prolonged overexposure to morpholine may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to morpholine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to morpholine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from morpholine exposure.

—Chronic respiratory disease: Morpholine causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of morpholine might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Morpholine causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Morpholine causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Eye disease: Morpholine is an eye irritant and has caused corneal edema in workers. Persons with preexisting eye disorders may be more susceptible to the effects of this agent.

—Skin disease: Morpholine is a primary skin irritant and induces hypersensitive responses. Persons with preexisting skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Morpholine vapor is an irritant to the skin, eyes, mucous membranes, and the respiratory tract. Hypersensitivity is common. Repeated daily exposure of rats to 18,000 ppm was lethal to some animals; those dying during the third to fifth days of exposure revealed damage to lungs, liver, and kidneys. A human exposure

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

9/83

September 1978

to 12,000 ppm for 1-½ minutes in a laboratory produced nose irritation and cough; mouth pipetting of the liquid caused a severe sore throat and reddened mucous membranes. The liquid dropped in the eye of a rabbit caused moderate injury with ulceration of the conjunctiva and corneal clouding. Workers exposed for several hours to low vapor concentrations complained of foggy vision with rings around lights, the result of corneal edema which cleared within 3 to 4 hours after cessation of exposure. The liquid is a severe skin irritant and may produce contact dermatitis. In industry, some instances of skin and respiratory tract irritation have been observed.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 87.1
  2. Boiling point (760 mm Hg): 128 C (263 F)
  3. Specific gravity (water = 1): 1.0
  4. Vapor density (air = 1 at boiling point of morpholine): 3.0
  5. Melting point: −4.8 C (23 F)
  6. Vapor pressure at 20 C (68 F): 7 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): Less than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact of liquid morpholine with strong acids will cause violent spattering. Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving morpholine.
  4. Special precautions: Liquid morpholine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 35 C (95 F) (closed cup)
  2. Autoignition temperature: 310 C (590 F)
  3. Flammable limits in air, % by volume: Lower: 1.8 (calculated); Upper: 11 (estimated)
  4. Extinguishant: Carbon dioxide, dry chemical, alcohol foam
- **Warning properties**
  1. Odor Threshold: Grant states that morpholine has a characteristic amine odor. No quantitative information is available concerning the odor threshold, however.
  2. Eye Irritation Level: Grant reports that lacrimation has been observed among experimental animals and among industrial workers who have been exposed to high vapor concentrations. "At low concentrations in air, morpholine has been listed with its N-ethyl and N-methyl derivatives among the amines which have been observed to cause transient edema of the cornea and temporary foggy vision with haloes around lights in workers exposed to the vapors for many hours, the symptoms usually coming on after work and clearing spontaneously by the next day."

  Patty also reports that morpholine irritates the mucous membranes.

  No quantitative information is available, however, concerning the threshold of eye irritation.

  3. Other Information: Both Patty and Grant note that morpholine is a respiratory tract irritant, but no quantitative information is available concerning the threshold of this irritation.

  4. Evaluation of Warning Properties: Since no quantitative information relating warning properties to air concentrations is available, morpholine is treated as a substance with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of morpholine in an adsorption tube containing silica gel, followed by desorption with sulfuric acid, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure morpholine may be used. An analytical method for morpholine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situatic · If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid morpholine or solutions containing greater than 25% morpholine by weight and to prevent repeated or prolonged skin contact with solutions containing 25% or less of morpholine by weight.
• Clothing contaminated with morpholine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of morpholine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the morpholine, the person performing the operation should be informed of morpholine's hazardous properties.
• Where there is any possibility of exposure of an employee's body to liquid morpholine or solutions containing greater than 25% morpholine by weight, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
• Any clothing which becomes wet with liquid morpholine should be removed immediately and not reworn until the morpholine is removed from the clothing.
• Non-impervious clothing which becomes contaminated with morpholine should be removed promptly and not reworn until the morpholine is removed from the clothing.
• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid morpholine or solutions containing morpholine contacting the eyes.
• Where there is any possibility that employees' eyes may be exposed to liquid morpholine or solutions containing greater than 15% morpholine by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with morpholine should be promptly washed or showered to remove any morpholine.
• Employees who handle liquid morpholine or solutions containing morpholine should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to morpholine may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of rubber chemicals for rubber accelerators, catalysts, plasticizers, curing agents, stabilizers of halogenated butyl rubber, and emulsifying agents	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a corrosion inhibitor in steam boiler systems, petroleum refining, sterilization autoclaves, and in natural gas processing; use in manufacture of optical brightening agents in bleaches and detergents	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in compounding of waxes and polishes for commercial use as automobile waxes, rubless waxes and polishes, and water-resistant polishes	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a chemical intermediate for textile industry as lubricants, sizing emulsifiers, and softening agents; in pharmaceutical industry as bactericides, analgesics, anesthetics, anti-spasmotics, and anti-malarials; in chemical industry for alkyl morpholines, emulsifying agents, surface-active agents, cosmetics, and soap emulsifiers; in agriculture for protective coatings for fresh fruits and vegetables, pesticide emulsifiers, insecticides, fumigants, and herbicides	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent for dyes, waxes, resins, and casein	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid morpholine or solutions containing morpholine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid morpholine or solutions containing morpholine get on the skin, immediately flush the contaminated skin with water. If liquid morpholine or solutions containing morpholine soak through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of morpholine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When morpholine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If morpholine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Morpholine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Morpholine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

ADDITIONAL INFORMATION

To find additional information on morpholine, look up morpholine in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Morpholine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Jefferson Chemical Company: *Material Safety Data Sheet - Morpholine.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Shea, T. E.: "The Acute and Sub-Acute Toxicity of Morpholine," *Journal of Industrial Hygiene and Toxicology*, 21:7, September 1939.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List V," *Archives of Industrial Hygiene and Occupational Medicine*, 10:61, July 1954.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Morpholine*, New York, 1967.

RESPIRATORY PROTECTION FOR MORPHOLINE

Condition	Minimum Respiratory Protection* Required Above 20 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
8000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Naphthalene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_8$
- Synonyms: White tar; naphthalin
- Appearance and odor: Colorless to brown solid with the odor of mothballs.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for naphthalene is 10 parts of naphthalene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 50 milligrams of naphthalene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Naphthalene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation or ingestion of naphthalene may cause abdominal cramps, nausea, vomiting, diarrhea, headache, tiredness, confusion, painful urination, and bloody or dark urine. Swallowing large amounts may cause convulsions or coma. Inhalation, ingestion, and possibly skin absorption of naphthalene may cause destruction of red blood cells with anemia, fever, yellow jaundice, bloody urine, kidney and liver damage. Naphthalene, on contact with the eyes, has produced irritation. Naphthalene, on contact with the skin, has produced skin irritation.

2. Long-term Exposure: Repeated skin exposure to naphthalene may cause an allergic rash. Repeated exposure may cause cataracts.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to naphthalene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to naphthalene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a deficiency of glucose-6-phosphate dehydrogenase in erythrocytes may be at increased risk from exposure. Examination of the eyes, blood, liver and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Naphthalene has been shown to cause red blood cell hemolysis. A complete blood count should be performed, including a red cell count, a white cell count, and a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Urinalysis: Since kidney damage may also occur from exposure to naphthalene, a urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Naphthalene vapor causes hemolysis and eye irritation; it may cause cataracts. Severe intoxication from ingestion of the solid results in characteristic manifestations of marked intravascular hemolysis and its consequences, including potentially fatal hyperkalemia. Initial symptoms include eye irritation, headache, confu-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

907

sion, excitement, malaise, profuse sweating, nausea, vomiting, abdominal pain, and irritation of the bladder; there may be progression to jaundice, hematuria, hemoglobinuria, renal tubular blockage, and acute renal shutdown. Hematologic features include red cell fragmentation, icterus, severe anemia with nucleated red cells, leukocytosis, and dramatic decreases in hemoglobin, hematocrit, and red cell count; sometimes there is formation of Heinz bodies and methemoglobin. Individuals with a deficiency of glucose-6-phosphate dehydrogenase in erythrocytes may be more susceptible to hemolysis by naphthalene. Cataracts and ocular irritation have been produced experimentally in animals and have been described in humans; of 21 workers exposed to high concentrations of fume or vapor for 5 years, 8 had peripheral lens opacities; in other studies no abnormalities of the eyes have been detected in workers exposed to naphthalene for several years. The vapor causes eye irritation at 15 ppm; eye contact with the solid may result in conjunctivitis, superficial injury to the cornea, chorioretinitis, scotoma, and diminished visual acuity. Naphthalene on the skin may cause hypersensitivity dermatitis; chronic dermatitis is rare.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 128.2
  2. Boiling point (760 mm Hg): 218 C (424 F)
  3. Specific gravity (water = 1): 1.14
  4. Vapor density (air = 1 at boiling point of naphthalene): 4.4
  5. Melting point: 74– 80 C (165 – 176 F)
  6. Vapor pressure at 20 C (68 F): 0.05 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.003
  8. Evaporation rate (butyl acetate = 1): Much less than 1
- **Reactivity**
  1. Conditions contributing to instability: None.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as dense acrid smoke and carbon monoxide) may be released in a fire involving naphthalene.
  4. Special precautions: Melted naphthalene will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 79 C (174 F) (closed cup)
  2. Autoignition temperature: 526 C (979 F)
  3. Flammable limits in air, % by volume: Lower: 0.9; Upper: 5.9
  4. Extinguishant: Carbon dioxide, dry chemical, foam
- **Warning properties**
  1. Odor Threshold: The AIHA *Hygienic Guide* reports that the odor threshold of naphthalene is "at least as low as 0.3 ppm."
  2. Eye Irritation Level: The *Hygienic Guide* states that "naphthalene vapor is reported to cause eye irritation at 15 ppm or above in air."
  3. Evaluation of Warning Properties: Through its odor and irritant effects, naphthalene can be detected at or below the permissible exposure limit. Naphthalene, therefore, is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure naphthalene may be used. An analytical method for naphthalene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with naphthalene or liquids containing naphthalene.
- If employees' clothing may have become contaminated with solid naphthalene, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with naphthalene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of naphthalene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the naphthalene, the person performing the operation should be informed of naphthalene's hazardous properties.
- Non-impervious clothing which becomes contaminated with naphthalene should be removed promptly and not reworn until the naphthalene is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where solid naphthalene or liquids containing naphthalene may contact the eyes.

SANITATION

- Skin that becomes contaminated with naphthalene should be promptly washed or showered with soap or mild detergent and water to remove any naphthalene.
- Eating and smoking should not be permitted in areas where solid naphthalene is handled, processed, or stored.
- Employees who handle naphthalene or liquids containing naphthalene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to naphthalene may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of insecticide and moth repellant as flakes, powder, balls, or cakes	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a fumigant for moth repellant and insecticide	General dilution ventilation; personal protective equipment
Use in manufacture of chemical intermediates for production of pharmaceuticals, resins, dyes, plasticizers, solvents, coatings, insecticides, pigments, rubber chemicals, tanning agents, surfactants, waxes, cable coatings, textile spinning lubricants, rodenticides, and in storage batteries	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Manufacture of naphthalene	Local exhaust ventilation; process enclosure; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If naphthalene or liquids containing naphthalene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If molten naphthalene gets on the skin, immediately flush the skin with large amounts of water. Get medical attention immediately. If naphthalene or liquids containing naphthalene get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If naphthalene or liquids containing naphthalene penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of naphthalene, move the exposed person to fresh air at once.

- **Swallowing**

When naphthalene has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify some-

one else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If naphthalene is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber.

• Waste disposal methods:

Naphthalene may be disposed of:

1. By making packages of naphthalene in paper or other flammable material and burning in a suitable combustion chamber.
2. By dissolving naphthalene in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber.

ADDITIONAL INFORMATION

To find additional information on naphthalene, look up naphthalene in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Naphthalene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Naphthalene," *Hygienic Guide Series*, Detroit, Michigan, 1967.

• American Petroleum Institute: "Naphthalene," *API Toxicological Reviews*, New York, 1959.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products*(3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-58, Naphthalene*, Washington, D.C.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

• Union Carbide Corporation Industrial Medicine and Toxicology Department: *Toxicology Studies - Naphthalene*, New York, 1968.

• Zinkham, W. H., and Childs, B.: "A Defect of Glutathione Metabolism in Erythrocytes from Patients with a Naphthalene-Induced Hemolytic Anemia," *Pediatrics*, 22:461-471, 1958.

RESPIRATORY PROTECTION FOR NAPHTHALENE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Particulate and Vapor Concentration	
500 ppm or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust filter. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Naphtha (Coal Tar)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_7H_8 - C_8H_{10}$ (approximately)
- Synonyms: Naphtha, 49 degrees Be-coal tar type; crude solvent coal tar naphtha; high-solvent coal tar naphtha
- Appearance and odor: Reddish-brown, mobile liquid with an aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for coal tar naphtha is 100 parts of coal tar naphtha per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 400 milligrams of coal tar naphtha per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Coal tar naphtha can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to coal tar naphtha can cause lightheadedness, drowsiness, and unconsciousness. It also may cause mild irritation of the eyes, nose, and skin.

2. Long-term Exposure: Prolonged overexposure to coal tar naphtha may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to coal tar naphtha.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to coal tar naphtha at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from coal tar naphtha exposure.

—Skin disease: Coal tar naphtha is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although coal tar naphtha is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although coal tar naphtha is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of coal tar naphtha might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Coal tar naphtha vapor is narcotic. Rats survived continuous exposure at 3200 ppm for two months; at 1800 ppm some animals showed damage to the liver and kidneys; above 1000 ppm there was evidence of narcotic action. Rats exposed at 567 ppm and 312 ppm for 18 to 20 hours a day for 7 days had some reduction in blood leukocytes, possibly the result of the presence of benzene. There are few if any well documented reports of industrial injury resulting from the inhalation of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

9?:?

September 1978

naphtha. However, exposure to high concentrations might be expected to cause lightheadedness, drowsiness, and possibly irritation of the eyes, nose, and throat. Repeated or prolonged contact with the liquid may result in drying and cracking skin due to defatting action. Coal tar (naphtha) is a non-uniform mixture of aromatic hydrocarbons and may contain benzene.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 110 (approximately)
2. Boiling point (760 mm Hg): 110 to 190 C (230 to 374 F)
3. Specific gravity (water = 1): 0.97
4. Vapor density (air = 1 at boiling point of coal tar naphtha): 3 (approximately)
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Less than 5 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Greater than 1

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving coal tar naphtha.
4. Special precautions: Coal tar naphtha will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 38 to 43 C (100 to 109 F) (closed cup)
2. Autoignition temperature: 482 to 510 C (900 to 950 F)
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

1. Odor Threshold: Since the odor thresholds of the main constituents of coal tar naphtha are below their permissible exposure limits, the odor threshold of coal tar naphtha is assumed to be below the permissible exposure limit.
2. Eye Irritation Level: According to Grant, Gafafer states that the naphthas cause conjunctival irritation. Two of the main constituents of coal tar naphtha, xylene and toluene, cause noticeable eye irritation at concentrations of 200 and 300 ppm, respectively.
3. Evaluation of Warning Properties: Since the odor threshold of the main constituents of coal tar naphtha are well below their permissible exposure limits, coal tar naphtha is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of coal tar naphtha vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure coal tar naphtha may be used. An analytical method for coal tar naphtha is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).
026).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid coal tar naphtha.
- Clothing wet with liquid coal tar naphtha should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of

coal tar naphtha from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the coal tar naphtha, the person performing the operation should be informed of coal tar naphtha's hazardous properties.

- Non-impervious clothing which becomes wet with liquid coal tar naphtha should be removed promptly and not reworn until the coal tar naphtha is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid coal tar naphtha may contact the eyes.

SANITATION

- Skin that becomes wet with liquid coal tar naphtha should be promptly washed or showered with soap or mild detergent and water to remove any coal tar naphtha.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to coal tar naphtha may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of coal-tar paints	Process enclosure; general dilution ventilation; personal protective equipment
Use in preparation of coumarone and indene	General dilution ventilation; personal protective equipment
Use as a solvent in rubber industry in manufacture of water-proof cloth, shoe adhesives, and rubber tires	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a solvent, diluent, or thinner in paint, varnish, and lacquer industries	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in formulations of nitrocellulose and ethylcellulose	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a solvent for polymerized styrol, short-oil phenolic varnishes, urea, resins, melamine, and other synthetic resins; use as a solvent for pesticides as DDT and Gammexane	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If coal tar naphtha gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If coal tar naphtha gets on the skin, promptly wash the contaminated skin using soap or mild detergent. If coal tar naphtha soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of coal tar naphtha, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

If coal tar naphtha has been swallowed, do not induce vomiting. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If coal tar naphtha is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely

clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Coal tar naphtha should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Coal tar naphtha may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Naphtha (Coal Tar)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Benzene," *Hygienic Guide Series*, Detroit, Michigan, 1970.

• American Industrial Hygiene Association: "Ethyl Benzene," *Hygienic Guide Series*, Detroit, Michigan, 1969.

• American Industrial Hygiene Association: "Petroleum Naphtha," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• American Industrial Hygiene Association: "Toluene," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• American Industrial Hygiene Association: "Xylene," *Hygienic Guide Series*, Detroit, Michigan, 1971.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR NAPHTHA (COAL TAR)

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Nickel Carbonyl*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $Ni(CO)_4$
- Synonyms: None
- Appearance and odor: Colorless liquid with a musty odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nickel carbonyl is 0.001 part of nickel carbonyl per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.007 milligram of nickel carbonyl per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be retained, but has recommended that nickel carbonyl be regulated as an occupational carcinogen. The NIOSH Special Occupational Hazard Review for Nickel Carbonyl and the NIOSH Criteria Document for Inorganic Nickel should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nickel carbonyl can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Depending on the severity of inhalation exposure, both initial and delayed symptoms may develop. Initial symptoms include dizziness, headache, shortness of breath, and vomiting. These symptoms generally disappear when the individual is removed from exposure. The delayed symptoms may develop 12 to 36 hours after exposure. These symptoms include chest pain, cough, rapid breathing, shortness of breath, a bluish discoloration of the skin, and increased temperature. Delirium and other signs of nervous system problems usually appear at this time. In some cases the two stages may merge. In severe cases death may occur.

2. Long-term Exposure: Repeated or prolonged exposure to nickel carbonyl has been associated with an increased incidence of cancer of the lungs and sinuses.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nickel carbonyl.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nickel carbonyl at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the lungs and upper respiratory tract should be stressed.

—14" x 17" chest roentgenogram: Nickel carbonyl causes human lung damage and is a suspected lung carcinogen. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Nickel carbonyl is a severe pulmonary irritant. Persons with decreased pulmonary function may be at increased risk from exposure.

—Sputum cytology: Nickel carbonyl is associated with an increase of lung cancer in humans.

—Urinalysis: Since kidney damage has been observed from exposure, a urinalysis should be performed to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centrifuged sediment. Examination of the urine for nickel should be conducted on a monthly basis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, with the exception that a urinalysis should be conducted on a monthly basis.

• **Summary of toxicology**

Nickel carbonyl vapor is a severe pulmonary irritant and probably causes cancer of the paranasal sinuses and the lungs in animals and man. Initial symptoms of overexposure usually include frontal headache, vertigo, nausea, vomiting, and sometimes substernal and epigastric pain; generally these early effects disappear when the individual is removed to fresh air. There may be an asymptomatic interval between recovery from initial symptoms and the onset of delayed symptoms, which tend to develop 12 hours or more following exposure; constrictive pain in the chest is characteristic of the delayed onset of pulmonary effects, followed by cough, hyperpnea and cyanosis, leading to profound weakness; gastrointestinal symptoms may also occur. The temperature seldom rises above 101 F, and leukocytosis above 12,000 per mg/m³ is infrequent. Physical signs compatible with pneumonitis or bronchopneumonia are elicited in the chest. Except for the pronounced weakness and hyperpnea, the physical findings and symptoms resemble those of a viral or influenzal pneumonia. Terminally, delirium and convulsions frequently occur; death has occurred from 3 to 13 days after exposure to nickel carbonyl. In subjects who recover from nickel carbonyl intoxication, convalescence is usually protracted (2 to 3 months) and is characterized by excessive fatigue on slight exertion. Exposure of rats to nickel carbonyl has caused pulmonary carcinomata; multiple intravenous injection of nickel carbonyl in rats has caused carcinomata and sarcomata in diverse organs, including the liver and kidneys. Several epidemiologic studies have shown an increased incidence of cancer of the paranasal sinuses and lungs among workers in nickel refineries and factories; suspicion of carcinogenicity has been focused primarily on nickel carbonyl vapor, although there are usually concurrent exposures to respirable particles of nickel, nickel subsulfide, and nickel oxide.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 170.7
2. Boiling point (760 mm Hg): 43 C (109 F)
3. Specific gravity (water = 1): 1.32
4. Vapor density (air = 1 at boiling point of nickel carbonyl): 5.89
5. Melting point: −25 C (−13 F)
6. Vapor pressure at 20 C (68 F): 321 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.018
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Liquid nickel carbonyl may explode when heated above 60 C (140 F). In the presence of air, nickel carbonyl forms a deposit which becomes peroxidized. This tends to decompose and ignite.
2. Incompatibilities: Contact with nitric acid, chlorine, and other oxidizers may cause fires and explosions. The vapor of nickel carbonyl may promote the ignition of mixtures of combustible vapors (such as gasoline) and air.
3. Hazardous decomposition products: Toxic gases and vapors (such as nickel oxide fume and carbon monoxide) may be released in a fire involving nickel carbonyl.
4. Special precautions: Liquid nickel carbonyl will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: Lower than −20 C (−4 F) (closed cup)
2. Autoignition temperature: May ignite spontaneously
3. Flammable limits in air, % by volume: Lower: 2; Upper: Data not available
4. Extinguishant: Foam, carbon dioxide, dry chemical

• **Warning properties**

1. Odor Threshold: Patty states that the odor of nickel carbonyl is detectable at between 1 and 3 ppm.
2. Eye Irritation Level: According to the AIHA *Hygienic Guide*, the effect of eye contact with nickel carbonyl is unknown. This substance is not known to be an eye irritant, however.
3. Evaluation of Warning Properties: Since the odor threshold of nickel carbonyl is over 1000 times greater than the permissible exposure limit, nickel carbonyl is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Measurement of nickel carbonyl may be done by sampling with a bubbler containing alcoholic-iodine solution, followed by chemical treatment and colorimetric analysis. The NIOSH Special Occupational Hazard Review for Nickel Carbonyl suggests a detailed method which may be employed for sampling and analyzing nickel carbonyl.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid nickel carbonyl.

• Any clothing which becomes wet with liquid nickel carbonyl should be removed immediately and not reworn until the nickel carbonyl is removed from the clothing.

• Clothing wet with liquid nickel carbonyl should be placed in vapor-tight, sealed containers for storage until it can be discarded or until provision is made for the removal of nickel carbonyl from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the nickel carbonyl, the person performing the operation should be informed of nickel carbonyl's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid nickel carbonyl contacting the eyes.

SANITATION

• Skin that becomes wet with liquid nickel carbonyl should be immediately washed or showered to remove any nickel carbonyl.

• Eating and smoking should not be permitted in areas where nickel carbonyl is handled, processed, or stored.

• Employees who handle nickel carbonyl should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nickel carbonyl may occur and control methods which may be effective in each case:

Operation	Controls
Use in Mond process for nickel refining	Process enclosure; local exhaust ventilation; personal protective equipment
Use in plating operations on foundry patterns, steel, and electronics manufacture	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a reagent in synthesis of acrylic esters; use as a catalyst or reagent in organic synthesis	Process enclosure; local exhaust ventilation; personal protective equipment
Use in petroleum and petrochemical processing (including methanation of ammonia synthesis gas)	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid nickel carbonyl gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid nickel carbonyl gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid nickel carbonyl soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of nickel carbonyl, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid nickel carbonyl has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If nickel carbonyl is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Nickel carbonyl should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Nickel carbonyl may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nickel Carbonyl," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Nickel Carbonyl," *Hygienic Guide Series*, Detroit, Michigan, 1956.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Committee on Medical and Biologic Effects of Environmental Pollutants, Division of Medical Sciences, National Research Council: *Nickel*, National Academy of Sciences, Washington, D.C., 1975.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Jones, C. C.: "Nickel Carbonyl Poisoning," *Archives of Environmental Health*, 26:245-248, 1973.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Inorganic Nickel*, HEW Publication No. (NIOSH) 77-164, GPO No. 017-033-00219-3, U.S. Government Printing Office, Washington, D.C., 1977.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *NIOSH Special Occupational Hazard Review for Nickel Carbonyl*, HEW Publication No. (NIOSH) 77-184, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sunderman, F. W.: "The Treatment of Acute Nickel Carbonyl Poisoning with Sodium Diethyldithiocarbamate," *Annals of Clinical Research*, 3:182-185, 1971.

* SPECIAL NOTE

Nickel carbonyl appears on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding its carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980). The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 11, 1976.

RESPIRATORY PROTECTION FOR NICKEL CARBONYL

Condition	Minimum Respiratory Protection* Required Above 0.001 ppm
Greater than 0.001 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against nickel carbonyl. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Nickel Metal and Soluble Nickel Compounds

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all soluble nickel compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Nickel, metallic

- Formula: Ni
- Synonyms: Nickel catalyst; Raney nickel
- Appearance and odor: Silvery gray, metallic (or darker), odorless powder.

Nickel nitrate hexahydrate

- Formula: $Ni(NO_3)_2 \cdot 6H_2O$
- Synonyms: None
- Appearance and odor: Green, odorless solid.

Nickel sulfate hexahydrate

- Formula: $NiSO_4 \cdot 6H_2O$
- Synonyms: None
- Appearance and odor: Green, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nickel metal and soluble nickel compounds is 1 milligram of nickel metal and soluble nickel compounds per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit for nickel be reduced to 0.015 mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week, and that nickel be regulated as an occupational carcinogen. The NIOSH Criteria Document for Inorganic Nickel and the Special Occupational Hazard Review for Nickel Carbonyl should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Metallic nickel or soluble nickel compounds can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

Nickel fumes are respiratory irritants and may cause pneumonitis. Skin contact may cause an allergic skin rash. Nickel and its compounds have been reported to cause cancer of the lungs and sinuses. Nickel itself is not very toxic if swallowed, but its soluble salts are quite toxic and, if swallowed, may cause giddiness and nausea. Exposure to nickel carbonyl (by inhalation or skin absorption) may cause both initial and delayed symptoms. Initial symptoms include headache, dizziness, shortness of breath, and vomiting. These symptoms generally disappear when the worker is exposed to fresh air. The delayed symptoms may develop 12 to 36 hours after exposure. The shortness of breath returns, a blue color of the skin may appear, and a fever may develop. The exposed person may become delirious. In some cases the symptoms may run together. Death may occur.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nickel metal and soluble nickel compounds.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

902

• **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nickel metal and soluble nickel compounds at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to nickel metal and soluble nickel compounds would be expected to be at increased risk from exposure. Examination of the nasal cavities and lungs should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Nickel metal and soluble nickel compounds cause human lung damage and cancer of the lung. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Nickel metal and soluble nickel compounds are respiratory irritants. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Skin disease: Nickel metal and soluble compounds are defatting agents and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of these agents.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Metallic nickel and certain soluble nickel compounds as dust or fume cause sensitization dermatitis and probably produce cancer of the paranasal sinuses and the lung; nickel fume in high concentrations is a respiratory irritant. Severe but transient pneumonitis in two workers resulted from exposure to nickel fume; in one case, exposure was for 6 hours, and post-incident sampling suggested a nickel concentration of 0.26 mg/m³. "Nickel itch" is a dermatitis resulting from sensitization to nickel; the first symptom is usually itching, which occurs up to 7 days before skin eruption appears. The primary skin eruption is erythematous, or follicular; it may be followed by superficial discrete ulcers, which discharge and become crusted, or by eczema; in the chronic stages, pigmented or depigmented plaques may be formed. Nickel sensitivity, once acquired, is apparently not lost; recovery from the dermatitis usually occurs within 7 days of cessation of exposure, but may take several weeks. A worker who had developed cutaneous sensitization also developed apparent asthma from inhalation of nickel sulfate; immunologic studies showed circulating antibodies to the salt, and controlled exposure to a solution of nickel sulfate resulted in decreased pulmonary function and progressive dyspnea; the possibility of developing hypersensitivity pneumonitis could not be excluded. In animals, finely divided metallic nickel was carcinogenic when introduced into the pleural cavity, muscle tissue, and subcutaneous tissues; rats and guinea pigs exposed to a concentration of 15 mg/m³ of powdered metallic nickel developed malignant pulmonary neoplasms. Several epidemiologic studies have shown an increased incidence of cancer of the paranasal sinuses and lungs among workers in nickel refineries and factories; suspicion of carcinogenicity has been focused primarily on respirable particles of nickel, nickel subsulfide, nickel oxide, and on nickel carbonyl vapor. Many of the studies also included exposures to other suspected carcinogens.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Nickel, metallic**

1. Molecular weight: 58.7
2. Boiling point (760 mm Hg): 2730 C (4946 F)
3. Specific gravity (water = 1): 8.9
4. Vapor density (air = 1 at boiling point of metallic nickel): Not applicable
5. Melting point: 1453 C (2648 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Nickel nitrate hexahydrate**

1. Molecular weight: 290.8
2. Boiling point (760 mm Hg): 137 C (278 F) (loses water)
3. Specific gravity (water = 1): 2.05
4. Vapor density (air = 1 at boiling point of nickel nitrate hexahydrate): Not applicable
5. Melting point: 57 C (135 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 60
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Nickel sulfate hexahydrate**

1. Molecular weight: 262.8
2. Boiling point (760 mm Hg): 103 C (217 F) (loses water)
3. Specific gravity (water = 1): 2.07
4. Vapor density (air = 1 at boiling point of nickel sulfate hexahydrate): Not applicable
5. Melting point: 53 C (127 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 40
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Heat (nickel only)
2. Incompatibilities: Contact of nickel with strong acids may form flammable and explosive hydrogen gas.

Contact with sulfur may cause evolution of heat. Contact of nickel nitrate with wood and other combustibles may cause fire.

3. Hazardous decomposition products: Toxic gases and vapors (such as nickel carbonyl and oxides of nitrogen) may be released in a fire involving nickel or in the decompostion of nickel compounds.

4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable

2. Minimum ignition temperature: Not available

3. Minimum explosive concentration: Not available, but nickel sponge catalyst may ignite spontaneously in air.

4. Extinguishant: Dry powder, dry sand, dry dolomite, dry graphite

• **Warning properties**

Grant states that "workers employed in nickel plating involving nickel sulfate, sulfuric acid, and chlorine are said to have developed conjunctivitis and epiphora when ventilation was poor." Since, according to Grant, "both sulfuric acid mist and chlorine gas are known to cause burning and stinging of the eyes," and since the AIHA *Hygienic Guide* states that eye contact "does not present any problem peculiar to nickel," nickel metal and soluble compounds are not treated as eye irritants.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection on a cellulose membrane filter followed by treatment with nitric and perchloric acids, solution in nitric acid, and analysis with an atomic absorption spectrophotometer. An analytical method for nickel metal and soluble nickel compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).
number PB 258 433).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with powdered metallic nickel or solids or liquids containing soluble nickel compounds.

• If employees' clothing may have become contaminated with powdered metallic nickel or solid soluble nickel compounds, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with metallic nickel or soluble nickel compounds should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of metallic nickel or soluble nickel compounds from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the metallic nickel or soluble nickel compounds, the person performing the operation should be informed of these substances's hazardous properties.

• Non-impervious clothing which becomes contaminated with metallic nickel or soluble nickel compounds should be removed promptly and not reworn until the metallic nickel or soluble nickel compounds are removed from the clothing.

SANITATION

• Skin that becomes contaminated with metallic nickel or soluble nickel compounds should be promptly washed or showered with soap or mild detergent and water to remove any metallic nickel or soluble nickel compounds.

• Eating and smoking should not be permitted in areas where solids or liquids containing soluble nickel compounds are handled, processed, or stored.

• Employees who handle powdered metallic nickel or solids or liquids containing soluble nickel compounds should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

• Areas in which exposure to nickel metal and soluble nickel compounds may occur should be identified by

signs or appropriate means, and access to these areas should be limited to authorized persons.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nickel metal and soluble nickel compounds may occur and control methods which may be effective in each case:

Operation	Controls
Use during manufacture and fabricating of more than 3000 alloys; use in electronic tube parts, coins heavy machinery, tools, instrument parts, magnets, food and chemical processing equipment, flatware, jet engines, automotive parts, zippers, nickel anodes, surgical and dental instruments, and cooking utensils (they aid in corrosion- and heat-resistance, enhance ductibility, and increase thermal conductivity)	General dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during processing and refining of ore	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of nickel-iron alloys, and non-ferrous-nickel alloys	Local exhaust ventilation; general dilution ventilation
Use during fabrication of nickel-plated materials	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in chemical synthesis as starting material of complex compounds; use as catalysts in hydrogenation of fats/ oils	General dilution ventilation
Use in textile industry in dyeing and printing; and in ceramic industry in coloring	General dilution ventilation; local exhaust ventilation
Use of metal and salts during electroplating and electroless plating	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of nickel-iron alloys and non-ferrous-nickel alloys	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Skin Exposure**

If solids or liquids containing soluble nickel compounds get on the skin, immediately flush the contaminated skin with water. If solids of liquids containing soluble nickel compounds penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention. Metallic nickel should be removed from the skin by washing with soap or mild detergent and water.

- **Breathing**

If a person breathes in large amounts of metallic nickel of soluble nickel compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible. If any nickel carbonyl has been inhaled, get medical attention promptly.

- **Swallowing**

When metallic nickel or solids or liquids containing soluble nickel compounds have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If nickel metal and soluble nickel compounds are spilled, the following steps should be taken:

1. Ventilate area of spill.

2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquid containing nickel should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Nickel metal and soluble nickel compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nickel Ni," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Nickel (Except the Carbonyls)," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Committee on Medical and Biologic Effects of Environmental Pollutants, Division of Medical Sciences, National Research Council: *Nickel*, National Academy of Sciences, Washington, D.C., 1975.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• McConnell, L. H., et al.: "Asthma Caused by Nickel Sensitivity," *Annals of Internal Medicine*, 78:888-89

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Inorganic Nickel*, HEW Publication No. (NIOSH) 77-164, GPO No. 017-033-00219-3, U.S. Government Printing Office, Washington, D.C., 1977.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *NIOSH Special Occupational Hazard Review for Nickel Carbonyl*, HEW Publication No. (NIOSH) 77-184, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

* SPECIAL NOTE

Nickel metal and soluble nickel compounds appear on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding their carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980).

The International Agency for Research on Cancer (IARC) has evaluated the data on these chemicals and has concluded that they cause cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 11, 1976.

RESPIRATORY PROTECTION FOR NICKEL METAL AND SOLUBLE COMPOUNDS

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Dust or Mist Concentration	
5 mg/m³ or less	Any dust and mist respirator.
10 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator.
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
2000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

RESPIRATORY PROTECTION FOR NICKEL METAL AND SOLUBLE COMPOUNDS

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Dust, Mist, or Fume Concentration	
10 mg/m³ or less	Any fume respirator or high efficiency particulate respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
2000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Nicotine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_{14}N_2$
- Synonyms: 3-(1-Methyl-2-pyrrolidyl)pyridine
- Appearance and odor: Pale yellow to dark brown liquid with a slight fishy odor when warm.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nicotine is 0.5 milligram of nicotine per cubic meter of air (mg/m³) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nicotine can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may rapidly enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: The action of nicotine is rapid either after breathing it, swallowing it, or absorbing it through the skin. Exposure to it may cause a burning sensation of the mouth and throat, abdominal pain, nausea, vomiting, and diarrhea. It may also cause headache, sweating, dizziness, hearing and visual disturbances, confusion, weakness, and incoordination. The heart may beat irregularly or stop. Trembling and convulsions, faintness, shortness of breath, and collapse may occur which may be followed by death from respiratory paralysis. Exposure of the eyes and skin may cause irritation. Nicotine has caused abnormalities in the offspring of laboratory animals.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nicotine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nicotine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the nervous system and cardiovascular system should be stressed.

2. Periodic Medical Examination: The aforementioned medical examination should be repeated on an annual basis.

- **Summary of toxicology**

Nicotine in solution causes a transient stimulation, followed by depression or paralysis of the central nervous system, peripheral autonomic ganglia, and nerve endings in skeletal muscle; it also directly stimulates smooth muscle. Many fatal human cases of nicotine intoxication have occurred, usually as a result of accidental or suicidal ingestion of nicotine insecticides. Nicotine is readily absorbed through the skin; in fatal cases of intoxication, death nearly always occurs within 1 hour and has occurred within 1 minute; the fatal adult dose is about 60 mg. Symptoms include nausea, salivation, abdominal pain, vomiting, diarrhea, cold sweat, headache, dizziness, disturbed hearing and vision, confusion, weakness, and incoordination. Initially, respiration is deep and rapid, blood pressure is elevated, and the pulse is slow; intense vagal stimulation may cause transient cardiac standstill or paroxysmal atrial fibrillation; the pupils are generally constricted. Excitation of the central nervous system results in tremor and sometimes clonic-tonic convulsions. As central nervous system

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulatio

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

999

depression ensues the pupils dilate, the blood pressure falls, and the pulse becomes rapid and often irregular; faintness, prostration, dyspnea, and paralysis of respiratory muscles are followed by death. Recovery usually occurs if the victim survives 1 to 4 hours. Skeletal system malformations occurred in the offspring of pregnant mice injected subcutaneously with nicotine between days 9 to 11 of pregnancy.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 162
  2. Boiling point (760 mm Hg): 266 C (511 F)
  3. Specific gravity (water = 1): 1.0
  4. Vapor density (air = 1 at boiling point of nicotine): 5.6
  5. Melting point: −79 C (−110 F)
  6. Vapor pressure at 20 C (68 F): 0.0425 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions below 60 C (140 F)
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids may cause violent spattering.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving nicotine.
  4. Special precautions: Nicotine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 95 C (203 F) (calculated)
  2. Autoignition temperature: 244 C (471 F)
  3. Flammable limits in air, % by volume: Lower: 0.7; Upper: 4.0
  4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical
- **Warning properties**
  1. Odor Threshold: No quantitative information is available.
  2. Eye Irritation Level: Grant reports one case where exposure caused "a severe pain, much conjunctival reaction and corneal infiltration. Eventually the eye healed with partial opacification of the cornea."
  3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of nicotine, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of nicotine on resin with subsequent desorption with ethyl acetate and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure nicotine may be used. An analytical method for nicotine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).
404).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid nicotine.
- Clothing which has had any possibility of being contaminated with liquid nicotine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of nicotine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the nicotine, the person performing the operation should be informed of nicotine's hazardous properties.
- Where there is any possibility of exposure of an employee's body to liquid nicotine, facilities for quick

drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with liquid nicotine should be removed immediately and not reworn until the nicotine is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid nicotine contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid nicotine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid nicotine should be immediately washed or showered with soap or mild detergent and water to remove any nicotine.

• Eating and smoking should not be permitted in areas where liquid nicotine is handled, processed, or stored.

• Employees who handle liquid nicotine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nicotine may occur and control methods which may be effective in each case:

Operation	Controls
Application as a pesticide and fumigant on vegetable crops, fruit, grasses and turf, and greenhouse plants and crops	Personal protective equipment
Formulation of pesticide products and fumigants	Process enclosure; local exhaust ventilation; general mechanical ventilation; personal protective equipment
Liberation as a by-product during tobacco processing and manufacture of tobacco products	Process enclosure; local exhaust ventilation; general mechanical ventilation; personal protective equipment
Extraction and handling of nicotine	Process enclosure; local exhaust ventilation; general mechanical ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid nicotine or solutions of nicotine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid nicotine or solutions of nicotine get on the skin, immediately flush the contaminated skin with water. If liquid nicotine or solutions of nicotine soak through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of nicotine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid nicotine or solutions of nicotine have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If nicotine is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Nicotine may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nicotine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products*(3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas. Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 37 - Nicotine*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1973.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Nishimura, H., and Nakai, K.: "Development Anomalies in Offspring of Pregnant Mice Treated with Nicotine," *Science*, 127:877-878, 1958.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR NICOTINE

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate or Vapor Concentration	
5 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
25 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
35 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 35 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of nicotine; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 35 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Nitric Acid

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: HNO_3
- Synonyms: Aqua fortis; white fuming nitric acid (WFNA); red fuming nitric acid (RFNA); hydrogen nitrate
- Appearance and odor: Colorless, yellow, or red fuming liquid with a suffocating, acrid odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nitric acid is 2 parts of nitric acid per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 5 milligrams of nitric acid per cubic meter of air (mg/m^3). NIOSH has recommended a permissible exposure limit of 2 ppm averaged over a work shift of up to ten hours per day, forty hours per week. The NIOSH Criteria Document for Nitric Acid should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nitric acid can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Nitric acid vapor or mist is an irritant of the eyes, nose, throat, and skin. Liquid nitric acid or high concentrations of nitric acid vapor may cause severe burns of the eyes with permanent damage. Liquid nitric acid or high concentrations of nitric acid vapor may produce skin burns and ulcers. Nitric acid may stain the skin a bright yellow. Exposure to high concentrations of nitric acid vapor may cause severe breathing difficulties which may be delayed in onset and may also cause pneumonia. Swallowing nitric acid may cause burns of the mouth, throat, and stomach.

2. Long-term Exposure: Repeated or prolonged exposure to nitric acid mists or strong concentrations of nitric acid vapors may cause erosion of the exposed teeth.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nitric acid.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nitric acid at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory tract, skin, and teeth should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Nitric acid causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Nitric acid is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Eye disease: Nitric acid is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

—Skin disease: Weak nitric acid is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

901

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis or at some other frequency to be determined by the responsible physician.

• **Summary of toxicology**

Nitric acid vapor or mist is an irritant of the eyes, mucous membranes, and skin. When nitric acid is exposed to air or comes in contact with organic matter, it decomposes to yield a mixture of toxic oxides of nitrogen, including nitric oxide and nitrogen dioxide. Exposure to high concentrations of nitric acid vapor or mist causes pneumonitis and pulmonary edema which may be fatal; onset of symptoms may be delayed for 4 to 30 hours. In contact with the eyes, the liquid produces severe burns which may result in permanent damage and visual impairment. On the skin, the liquid or concentrated vapor produces immediate, severe and penetrating burns; concentrated solutions cause deep ulcers and stain the skin a bright yellow or yellowish-brown color. The vapor and mist may erode the exposed teeth. Ingestion of the liquid will cause immediate pain and burns of the mouth, esophagus, and gastrointestinal tract.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 63 (solute)

2. Boiling point (760 mm Hg): 121.6 C (251 F) (for "constant boiling," 68%); 84 C (183 F) (white fuming nitric acid); 60 C (140 F) (red fuming nitric acid)

3. Specific gravity (water = 1): 1.41 (constant boiling); 1.5 (white fuming); 1.55 (red fuming)

4. Vapor density (air = 1 at boiling point of nitric acid): 2 – 3 approximately

5. Melting point: −41 C (−42 F) (for "constant boiling," 68%); −41.6 C (−43 F) (white fuming); −52 C (−61 F) (red fuming)

6. Vapor pressure at 20 C (68 F): 2.9 mm Hg (HNO_3) (constant boiling), 2.6 mm Hg (H_2O) (constant boiling); 62 mm Hg (white fuming); 103 mm Hg (red fuming)

7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions

8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause containers to burst and liberate toxic oxides of nitrogen.

2. Incompatibilities: Reacts explosively with combustible organic or readily oxidizable materials such as wood, turpentine, metal powders, hydrogen sulfide, etc. Contact with strong bases may cause violent spattering.

3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen) may be released when nitric acid decomposes.

4. Special precautions: Nitric acid will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible, but is a strong oxidizer.

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of nitric acid.

2. Eye Irritation Level: The AIHA *Hygienic Guide*, concerning eye contact with nitric acid, states that "nitric acid produces very severe immediate damage which may result in permanent damage and visual impairment."

3. Other Information: The AIHA *Hygienic Guide* notes that "'nitrous fumes,' expressed in terms of nitrogen dioxide, may cause immediate irritation of the throat at concentrations as low as 62 ppm."

4. Evaluation of Warning Properties: Patty points out that "nitric acid manufacture is more hazardous than hydrochloric acid manufacture in that . . . the oxides of nitrogen have inadequate warning properties in low, toxic concentrations." For the purposes of this guideline, nitric acid is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Nitric acid may be measured by collection of nitric acid in a midget impinger, followed by ultraviolet spectrophotometric analysis. An analytical method for nitric acid is in the *NIOSH Manual of Analytical Methods*, 2nd

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid nitric acid or liquids containing nitric acids having a pH equal to or less than 2.5.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solutions containing nitric acid having a pH greater than 2.5.

• Clothing contaminated with nitric acid should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of nitric acid from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the nitric acid, the person performing the operation should be informed of nitric acid's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid nitric acid or solutions containing nitric acid having a pH equal to or less than 2.5, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with nitric acid should be removed immediately and not reworn until the nitric acid is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid nitric acid or solutions containing nitric acid contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid nitric acid or solutions containing nitric acid having a pH equal to or less than 2.5, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with nitric acid should be immediately washed or showered to remove any nitric acid.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nitric acid may occur and control methods which may be effective in each case:

Operation	Controls
Use in metallurgy as a pickling agent; in metal refining, ore recovery, metal etching, and photoengraving	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in acidulation of phosphate rock and manufacture of nitrogen solutions for use in fertilizer industry	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a laboratory reagent; in wood pulping industry	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during inorganic synthesis in manufacture of fertilizers, explosives, herbicides, antibiotics, meat-curing, pickling, ceramics, and pharmaceuticals	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during organic synthesis in manufacture of nitrating and oxidizing agents, nylons, foams, lubricants, insecticides, dyes, explosives, photographic films, lacquers, and celluloids	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If nitric acid or strong concentrations of nitric acid vapors get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If nitric acid or strong concentrations of nitric acid vapors get on the skin, immediately flush the contaminated skin with water. If nitric acid soaks through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of nitric acid, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration.

Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When nitric acid has been swallowed and the person is conscious, give the person large quantities of water immediately to dilute the nitric acid. Do not attempt to make the exposed person vomit. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If nitric acid is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Flush with copious quantities of water and neutralize with alkaline material (such as soda ash, lime, etc)..

• Waste disposal method:

Nitric acid may be disposed of by neutralizing with water and alkaline material (such as soda ash, lime, etc). and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nitric Acid," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Nitric Acid," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 60 – Nitric Acid*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-5, Nitric Acid*, Washington, D.C., 1961.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Nitric Acid*, HEW Publication No. (NIOSH) 76-141, GPO No. 017-033-00169-3, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR NITRIC ACID

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate or Vapor Concentration	
250 mg/m³ or less	A chemical cartridge respirator with a full facepiece providing protection against nitric acid.**
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister providing protection against nitric acid.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 250 mg/m³*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-oxidizable sorbents and providing protection against nitric acid.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Nitric acid is an oxidizer and should not come in contact with oxidizable materials. Some cartridges and canisters may contain oxidizable materials, such as activated charcoal, and therefore and should not be used to provide protection against nitric acid. Only non-oxidizable sorbents are allowed.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of nitric acid; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 250 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Nitric Oxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: NO
- Synonyms: Nitrogen monoxide
- Appearance and odor: Colorless gas with a sharp, sweet odor. In high concentrations, nitric oxide turns brown rapidly in air.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nitric oxide is 25 parts of nitric oxide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 30 milligrams of nitric oxide per cubic meter of air (mg/m³). NIOSH has recommended a permissible exposure limit of 25 ppm (30 mg/m³) averaged over a work shift of up to 10 hours per day, 40 hours per week. The NIOSH Criteria Document for Oxides of Nitrogen should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nitric oxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

Nitric oxide changes into nitrogen dioxide in air. Nitrogen dioxide is more toxic than nitric oxide and may cause severe breathing difficulties which may be delayed in onset. Nitrogen dioxide may also cause irritation of the eyes, nose, throat, and wet skin. Exposure of animals to nitric oxide has caused drowsiness, unconsciousness, and death.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nitric oxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nitric oxide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system, respiratory tract, and cardiovascular system should be stressed.

—14" x 17" chest roentgenogram: Exposure to nitric oxide involves simultaneous exposure to nitrogen dioxide which causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Exposure to nitric oxide involves simultaneous exposure to nitrogen dioxide which is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Cardiovascular disease: Persons with cardiac disease may be at increased risk. An electrocardiogram should be performed on workers over 40 years of age and where indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis or as otherwise indicated by the responsible physician.

- **Summary of toxicology**

Nitric oxide (NO) causes narcosis in animals. Exposure of mice to 2500 ppm for 6 or 7 minutes caused narcosis, and death occurred within 12 minutes. Some early reports attributed the toxicity of nitric oxide to the formation of methemoglobin; however, more recent studies indicate that nitric oxide reacts in vitro with normal (ferrous) hemoglobin but in exposed animals this interaction does not occur and no methemoglobin is

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

909

formed. Nitric oxide is converted spontaneously in air to nitrogen dioxide; hence, some of the latter gas is invariably present whenever nitric oxide is found in the air. At concentrations below 50 ppm, however, this reaction is slow, and frequently substantial concentrations of nitric oxide may occur with negligible quantities of nitrogen dioxide. Nitrogen dioxide may cause delayed pulmonary edema and irritation of the eyes, nose, throat, and wet skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 30
2. Boiling point (760 mm Hg): −152 C (-241 F)
3. Specific gravity (water = 1): 1.27 (at boiling point)
4. Vapor density (air = 1 at boiling point of nitric oxide): 1.0
5. Melting point: −164 C (−263 F)
6. Vapor pressure at 20 C (68 F): 26,000 mm Hg (500 psig, cylinder pressure)
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause cylinders to burst.
2. Incompatibilities: Contact with all combustible materials, chlorinated hydrocarbons, ammonia, carbon disulfide, many metals, fluorine, and ozone may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen) may be released when nitric oxide decomposes.
4. Special precautions: Nitric oxide will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible, but strong oxidizing agent.

- **Warning properties**

1. Odor Threshold: May gives odor thresholds for nitric oxide of 0.3 ppm and 1 ppm.
2. Eye Irritation Level: According to Patty, nitric oxide is not an irritant. It is oxidized in air to NO_2, however, and NO_2 is known to produce eye irritation.
3. Evaluation of Warning Properties: Since the odor threshold of nitric oxide is well below the permissible exposure limit, nitric oxide is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Nitric oxide may be measured by the collection of nitric oxide on a solid sorbent, followed by extraction with triethanolamine and subsequent spectrophotometric analysis. Detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure nitric oxide may be used. An analytical method for nitric oxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nitric oxide may occur and control methods which may be effective in each case:

Operation	Controls
Liberation of fumes caused by direct combination of nitrogen and oxygen at elevated temperatures; action of dilute nitric acid on some metals; oxidation of nitrogenous materials	Local exhaust ventilation; general dilution ventilation; personal protective equipment

Use as an intermediate in synthesis of nitric acid, acrylonitrile, hydroxylamine, nitrosyl halides, nitrosyl hydrogen sulfate, nitrogen dioxide	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as decomposition agent in certain gaseous products; additive to rocket propellants; bleaching of rayon; laboratory research	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of nitric oxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If nitric oxide is leaked or released in hazardous concentrations, the following steps should be taken:
1. Ventilate area of leak or release to disperse the gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nitric Oxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Gray, E. L.: "Oxides of Nitrogen: Their Occurre Toxicity, Hazard," *A.M.A. Archives of Industrial Hea* 19:479-486, 1959.

• May, J.: "Solvent Odor Thresholds for the Eva tion of Solvent Odors in the Atmosphere," *Stu Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety Health, U.S. Department of Health, Education, Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Oxides of Nitrogen*, HEW Publication No. (NIOSH) 76-149, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR NITRIC OXIDE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Gas Concentration	
100 ppm or less	Any chemical cartridge respirator with a full facepiece and cartridge(s) containing non-oxizidable sorbents and providing protection against nitric oxide.**
	A gas mask with a chin-style or a front- or back-mounted canister containing non-oxidizable sorbents and providing protection against nitric oxide.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 100 ppm*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-oxidizable sorbents and providing protection against nitric oxide.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Nitric oxide is an oxidizer and should not come in contact with oxidizable materials. Some cartridges and canisters may contain oxidizable materials, such as activated charcoal, and therefore and should not be used to provide protection against nitric oxide. Only non-oxidizable sorbents are allowed.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of nitric oxide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 100 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

1002

Occupational Health Guideline for p-Nitroaniline

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_6N_2O_2$
- Synonyms: Azoic diazo component 37; para-nitroaniline; 4-nitroaniline; para-aminonitrobenzene; PNA; 1-amino-4-nitrobenzene; fast red 2G base; fast red GG base
- Appearance and odor: Yellow crystals with a pungent, faint, ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for p-nitroaniline is 1 part of p-nitroaniline per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 6 milligrams of p-nitroaniline per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

p-Nitroaniline can affect the body if it comes in contact with the skin or eyes, is inhaled, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: p-Nitroaniline may cause a darkening or bluish coloring of the lips ("blue lip") and of the skin. Irritation of the nose and throat, headache, dizziness, weakness, nausea, shortness of breath, and rapid beating of the heart may occur. The overexposed person may become unconscious, cease breathing, and die.

2. Long-term Exposure: Prolonged overexposure may produce blue-colored lips and skin, and difficult breathing.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to p-nitroaniline.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to p-nitroaniline at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, liver, and cardiovascular system should be stressed.

—A complete blood count: p-Nitroaniline has been shown to cause methemoglobinemia. Persons with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Liver function tests: Since liver damage has been observed in humans exposed to p-nitroaniline, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determinations should be performed if overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

p-Nitroaniline absorption, whether from inhalation of the vapor or absorption of the solid through skin, causes anoxia due to the formation of methemoglobin; jaundice and anemia have been reported. Signs and symptoms of overexposure are due to the loss of oxygen-carrying capacity of the blood. Rapid absorption through the

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

intact skin is frequently the main route of entry. The onset of symptoms of methemoglobinemia is often insidious and may be delayed for up to 4 hours; headache is commonly the first symptom and may become quite intense as the severity of methemoglobinemia progresses. Cyanosis develops early in the course of intoxication, first in the lips, nose, and ear lobes, and is usually recognized by fellow workers. Cyanosis occurs when the methemoglobin concentration is 15% or more. The individual usually feels well, has no complaints, and is insistent that nothing is wrong until the methemoglobin concentration approaches approximately 40%. At concentrations of over 40% there usually is weakness and dizziness; up to a 70% concentration there may be ataxia, dyspnea on mild exertion, tachycardia, nausea, vomiting, and drowsiness. Ingestion of alcohol aggravates the toxic effects of p-nitroaniline. The substance is mildly irritating to the eyes and may cause some corneal damage.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 138
  2. Boiling point (760 mm Hg): 336 C (637 F)
  3. Specific gravity (water = 1): 1.437
  4. Vapor density (air = 1 at boiling point of p-nitroaniline): 4.76
  5. Melting point: 146 C (293 F)
  6. Vapor pressure at 20 C (68 F): 0.00015 mm Hg
  7. Solubility in water, g/100 g water at 18.5 C (65 F): 0.08 (slight)
  8. Evaporation rate (butyl acetate = 1): 22.6
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Strong oxidizers and moisture may result in spontaneous heating.
  3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide and carbon monoxide) may be released in a fire involving p-nitroaniline.
  4. Special precautions: Liquid p-nitroaniline will attack some forms of plastics, coatings, and rubber.
- **Flammability**
  1. Flash point: 199 C (390 F) (closed cup)
  2. Autoignition temperature: 180 C (356 F)
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Dry chemical and carbon dioxide for small fires.
- **Warning properties**
  1. Odor Threshold: The Manufacturing Chemists Association (MCA) states that p-nitroaniline is odorless.
  2. Eye Irritation Level: p-Nitroaniline, according to the MCA, "is mildly irritating to the eyes and may cause some corneal damage." For the purposes of this guideline, quarter- and half-facepiece respirators are allowed up to 60 mg/m^3 (PF—10).
  3. Evaluation of Warning Properties: Since the MCA states that p-nitroaniline is odorless and is only mildly irritating to the eyes, it is treated as a material with poor warning properties. The concentration in saturated air at 20 C could result in a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for p-nitroaniline is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid p-nitroaniline or liquids containing p-nitroaniline.
- If employees' clothing may have become contaminated with solid p-nitroaniline, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with p-nitroaniline should be placed in closed containers for storage until it can be

discarded or until provision is made for the removal of p-nitroaniline from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the p-nitroaniline, the person performing the operation should be informed of p-nitroaniline's hazardous properties.

• Where exposure of an employee's body to solid p-nitroaniline or liquids containing p-nitroaniline may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with p-nitroaniline should be removed immediately and not reworn until the p-nitroaniline is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where solid p-nitroaniline or liquids containing p-nitroaniline may contact the eyes.

SANITATION

• Skin that becomes contaminated with p-nitroaniline should be immediately washed or showered with soap or mild detergent and water to remove any p-nitroaniline.

• Workers subject to skin contact with solid p-nitroaniline should wash any areas of the body which may have contacted p-nitroaniline at the end of each work day.

• Eating and smoking should not be permitted in areas where solid p-nitroaniline is handled, processed, or stored.

• Employees who handle solid p-nitroaniline or liquids containing p-nitroaniline should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to p-nitroaniline may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during use in synthesis and subsequent product preparation, such as grinding, containerization, etc.	Process enclosure; local exhaust ventilation; butyl rubber protective clothing; medical supervision; work force rotation; whole-body protection
Liberation during production of p-phenylenediamine; during production of intermediates for dyestuff manufacture; during antioxidation and antiozonation operations in rubber manufacture	Process enclosure; local exhaust ventilation; butyl rubber protective clothing; medical supervision; work force rotation; whole-body protection
Liberation during use as a gasoline-gum inhibitor; during use as an intermediate in pharmaceutical synthesis	Process enclosure; local exhaust ventilation; butyl rubber protective clothing; medical supervision; work force rotation; whole-body protection

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If p-nitroaniline or liquids containing p-nitroaniline get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If p-nitroaniline or liquids containing p-nitroaniline get on the skin, immediately flush the contaminated skin with water. If p-nitroaniline or liquids containing p-nitroaniline soak through the clothing, remove the clothing immediately and flush the skin with water. If solid p-nitroaniline penetrates through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention as soon as possible.

• **Breathing**

If a person breathes in large amounts of p-nitroaniline, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When p-nitroaniline has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If p-nitroaniline is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

p-Nitroaniline may be disposed of:

1. By making packages of p-nitroaniline in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving p-nitroaniline in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Aniline Products: *Material Safety Data Sheet – p-Nitroaniline.*

• American Conference of Governmental Industrial Hygienists: "p-Nitroaniline," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Aniline," *Hygienic Guide Series*, Detroit, Michigan, 1955.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-94, p-Nitroaniline*, Washington, D.C., 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Wetherhold, J. M., et al.: "Hemoglobin Analysis for Aromatic Nitro and Amino Compound Exposure Control," *American Industrial Hygiene Association Journal*, 19:396-405, 1959.

RESPIRATORY PROTECTION FOR P-NITROANILINE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Particulate and Vapor Concentration	
60 mg/m³ (10 ppm) or less	Any supplied-air respirator. Any self-contained breathing apparatus.
300 mg/m³ (50 ppm) or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 300 mg/m³ (50 ppm) or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Nitrobenzene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5NO_2$
- Synonyms: Nitrobenzol; oil of mirbane
- Appearance and odor: Pale yellow to dark brown, oily liquid with an odor like black paste shoe polish. It can be a solid at temperatures below 5.1 C (41 F).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nitrobenzene is 1 part of nitrobenzene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 5 milligrams of nitrobenzene per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nitrobenzene can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It is readily absorbed through the skin, either as liquid or vapor. Even a small amount absorbed from clothes or shoes may cause toxic symptoms.

- **Effects of overexposure**

1. Short-term Exposure: Nitrobenzene affects the ability of blood to carry oxygen. A bluish discoloration of the skin may occur with headache, irritability, dizziness, weakness, nausea, vomiting, shortness of breath, drowsiness, and unconsciousness. If treatment is not given promptly, death may occur. The onset of symptoms may be delayed. Direct contact with the eyes or skin may cause mild irritation. Ingestion of alcohol may cause aggravation of symptoms.

2. Long-term Exposure: Repeated or prolonged exposure to nitrobenzene may cause anemia. An allergic skin rash may occur.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nitrobenzene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nitrobenzene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, liver, kidneys, and cardiovascular system should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Nitrobenzene has been shown to cause methemoglobinemia and may cause anemia. Those with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit. Observe for Heinz bodies.

—Urinalysis: The presence of p-nitrophenol and p-aminophenol in the urine is an indication of exposure to nitrobenzene.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determinations should be performed at any time overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

Nitrobenzene absorption, whether from inhalation of the vapor or absorption of the liquid through skin, causes anoxia due to the formation of methemoglobin; chronic exposure produces anemia. In rabbits given

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1008

September 1978

subcutaneous injections of 0.75 g of nitrobenzene there was methemoglobin, sulfhemoglobin, Heinz body formation in erythrocytes, a marked decrease in hematocrit and hemoglobin levels, reticulocytosis, and mild damage to the liver and kidney. Vapor concentrations near 40 ppm resulted in intoxication of workers; exposure to vapor concentrations averaging 6 ppm caused headache and vertigo; small amounts of methemoglobin and sulfhemoglobin and some Heinz bodies were found in the blood. Signs and symptoms of overexposure are due to the loss of oxygen-carrying capacity of the blood. Rapid absorption through the intact skin is frequently the main route of entry. The onset of symptoms of methemoglobinemia is often insidious and may be delayed for up to 4 hours; headache is commonly the first symptom and may become quite intense as the severity of methemoglobinemia progresses. Cyanosis develops early in the course of intoxication, first in the lips, the nose, and the ear lobes, often recognized by fellow workers. Cyanosis often occurs when the methemogoblin concentration is 15% or more. The individual may feel well, have no complaints, and may insist that nothing is wrong until the methemoglobin concentration approaches approximately 40%. At methemoglobin concentrations of over 40% there usually is weakness and dizziness; at up to 70% concentration there may be ataxia, dyspnea on mild exertion, tachycardia, nausea, vomiting, and drowsiness. Ingestion of alcohol aggravates the toxic effects of nitrobenzene. p-Nitrophenol and p-aminophenol are metabolites of nitrobenzene, and their presence in the urine is an indication of exposure. Nitrobenzene is mildly irritating to the eyes; it may produce dermatitis due to primary irritation or sensitization.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 123.1
  2. Boiling point (760 mm Hg): 211 C (412 F)
  3. Specific gravity (water = 1): 1.2
  4. Vapor density (air = 1 at boiling point of nitrobenzene): 4.3
  5. Melting point: 5.1 C (41 F)
  6. Vapor pressure at 20 C (68 F): Much less than 1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.19
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with concentrated nitric acid or nitrogen tetroxide may cause fires and explosions. Contact with caustics and chemically active metals such as tin and zinc can cause evolution of much heat and fumes.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving nitrobenzene.
  4. Special precautions: Liquid nitrobenzene will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 88 C (190 F) (closed cup)
  2. Autoignition temperature: 482 C (900 F)
  3. Flammable limits in air, % by volume: Lower: 1.8
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Both Stern and May report that the odor threshold of nitrobenzene is 1.9 ppm.
  2. Eye Irritation Level: Browning states that nitrobenzene causes "only slight transient (eye) irritation." Grant states that "the most reliably established ocular effects are secondary to discoloration of the blood from methemoglobinemia, and consist of brown discoloration of the vessels of the fundus and the conjunctiva."
  3. Evaluation of Warning Properties: Since the odor threshold of nitrobenzene is within twice the permissible exposure limits, nitrobenzene is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of nitrobenzene in an adsorption tube containing silica gel, followed by desorption with methanol, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure nitrobenzene may be used. An analytical method for nitrobenzene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to

be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid nitrobenzene.

• If employees' clothing has had any possibility of being contaminated with liquid nitrobenzene, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with liquid nitrobenzene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of nitrobenzene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the nitrobenzene, the person performing the operation should be informed of nitrobenzene's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid nitrobenzene, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with nitrobenzene should be removed immediately and not reworn until the nitrobenzene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid nitrobenzene may contact the eyes.

SANITATION

• Skin that becomes contaminated with nitrobenzene should be immediately washed or showered with soap or mild detergent and water to remove any nitrobenzene.

• Workers subject to skin contact with liquid nitrobenzene should wash with soap or mild detergent and water any areas of the body which may have contacted nitrobenzene at the end of each work day.

• Eating and smoking should not be permitted in areas where liquid nitrobenzene is handled, processed, or stored.

• Employees who handle liquid nitrobenzene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nitrobenzene may occur and control methods which may be effective in each case:

Operation	Controls
Use in production of chemical intermediates	Process enclosure; local exhaust ventilation; personal protective equipment
Use in solvent refining of lubricating oils; use in production of intermediates in synthesis of rubber chemicals, photographic chemicals, explosives, liquid propellants, and pharmaceuticals	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a solvent in specialized surface coatings; use as a solvent in organic synthesis	Process enclosure; local exhaust ventilation; personal protective equipment
Use as perfume in manufacture of toilet and household soaps; use in synthesis of insecticides and germicides	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid nitrobenzene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid nitrobenzene gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid nitrobenzene soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of nitrobenzene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration.

Keep the affected person warm and at rest. Get medical attention as soon as possible.

• Swallowing

When liquid nitrobenzene has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid or solid nitrobenzene is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If in the liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. If in the solid form, allow to melt and handle as indicated in (2) above.

• Waste disposal methods:

Nitrobenzene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in sealed containers in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nitrobenzene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Nitrobenzene," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Chambers, J. V., and O'Neill, F. J.: "Nitrobenzene Poisoning," *British Journal of Industrial Medicine*, 3:22, p. 102, 1946.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Ikeda, M., and Kita, A.: "Excretion of p-Nitrophenol and p-Aminophenol in the Urine of a Patient Exposed to Nitrobenzene," *British Journal of Industrial Medicine*, 21:210-213, 1964.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saunders, Philadelphia, 1960.

• Linch, A. L.: "Biological Monitoring for Industrial Exposure to Cyanogenic Aromatic Nitro and Amino Compounds," *American Industrial Hygiene Association Journal*, 35:426-432, 1974.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-21, Nitrobenzene*, Washington, D.C., 1967.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR NITROBENZENE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
10 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
50 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of nitrobenzene; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 200 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for p-Nitrochlorobenzene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: 1,4-$ClC_6H_4NO_2$
- Synonyms: PNCB; 4-chloronitrobenzene; PCNB; p-chloronitrobenzene; 1-chloro-4-nitrobenzene
- Appearance and odor: Yellow solid with a sweet odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for p-nitrochlorobenzene is 1 milligram of p-nitrochlorobenzene per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

p-Nitrochlorobenzene can affect the body if it is inhaled, comes in contact with the eyes or skin, or swallowed. It is readily absorbed through the skin. Even a small amount absorbed from clothes or shoes may cause toxic symptoms.

- **Effects of overexposure**

1. Short-term Exposure: p-Nitrochlorobenzene affects the ability of the blood to carry oxygen normally. A bluish discoloration of the skin may occur with headache, irritability, dizziness, weakness, nausea, vomiting, shortness of breath, drowsiness, and unconsciousness. If treatment is not given promptly, death may occur. The onset of symptoms may be delayed. p-Nitrochlorobenzene may also cause an unpleasant taste. The ingestion of alcohol may cause increased susceptibility to the effects of p-nitrochlorobenzene. The earliest effect may be a bluish color of the skin, especially of the lips. If the lack of oxygen becomes severe, drowsiness, headache, nausea, and vomiting may occur. If oxygen lack is very severe, it may cause unconsciousness and even death. It will also cause the mouth and breath to smell of bitter almonds.

2. Long-term Exposure: Repeated or prolonged exposure to p-nitrochlorobenzene may cause anemia and skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to p-nitrochlorobenzene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to p-nitrochlorobenzene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, liver, kidneys, and cardiovascular system should be stressed.

—A complete blood count: p-Nitrochlorobenzene has been shown to cause methemoglobinemia and anemia. Those with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit. Observe for Heinz bodies.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determinations should be performed at any time overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

Absorption of p-nitrochlorobenzene, whether by inhalation of vapor or dust or by absorption of the solid through the skin, causes anoxia due to the formation of methemoglobin. Application of the solid dissolved in

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

olive oil to the skin of rabbits caused methemoglobinemia, the formation of Heinz bodies in erythrocytes, anemia, hematuria, and hemoglobinuria. Signs and symptoms of overexposure are due to the loss of oxygen-carrying capacity of the blood. Rapid absorption through the intact skin is frequently the main route of entry. The onset of symptoms of methemoglobinemia is often insidious and may be delayed for up to 4 hours; headache is commonly the first symptom and may become quite intense as the severity of methemoglobinemia progresses. Cyanosis develops early in the course of intoxication, first in the lips, the nose, and the ear lobes, and may be recognized by fellow workers. Cyanosis occurs when the methemoglobin concentration is 15% or more. The individual may feel well, have no complaints, and may insist that nothing is wrong until the methemoglobin concentration approaches approximately 40%. At methemoglobin concentrations of over 40% there usually is weakness and dizziness; at up to 70% concentration there may be ataxia, dyspnea on mild exertion, tachycardia, nausea, vomiting, and drowsiness. The ingestion of alcohol aggravates the toxic effects of p-nitrochlorobenzene. Four workers exposed for a period of 2 to 4 days to an unmeasured concentration of the vapor developed methemoglobinemia; an unpleasant taste in mouth and anemia developed during the week after exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 157.6
2. Boiling point (760 mm Hg): 242 C (468 F)
3. Specific gravity (water = 1): 1.37
4. Vapor density (air = 1 at boiling point of p-nitrochlorobenzene): 5.4
5. Melting point: 83 C (181 F)
6. Vapor pressure at 20 C (68 F): Much less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.003
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: None hazardous
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen, hydrogen chloride, and carbon monoxide) may be released in a fire involving p-nitrochlorobenzene.
4. Special precautions: Liquid p-nitrochlorobenzene will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 127 C (261 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Foam, carbon dioxide, dry chemical

- **Warning properties**

According to Grant, nitrochlorobenzene (NCB), "like nitrobenzene, has been observed to cause methemoglobinemia, with discoloration of the conjunctiva reflecting the change in the color of the blood." NCB is not known to be an eye irritant, however.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of p-nitrochlorobenzene in an absorption tube containing silica gel, followed by desorption with methanol, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure p-nitrochlorobenzene may be used. An analytical method for p-nitrochlorobenzene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with p-nitrochlorobenzene or liquids containing p-nitrochlorobenzene, where skin contact may occur.

• If employees' clothing may have become contaminated with p-nitrochlorobenzene, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with p-nitrochlorobenzene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of p-nitrochlorobenzene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the p-nitrochlorobenzene, the person performing the operation should be informed of p-nitrochlorobenzene's hazardous properties.

• Where exposure of an employee's body to liquids containing p-nitrochlorobenzene may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes wet with liquids containing p-nitrochlorobenzene should be removed immediately and not reworn until the p-nitrochlorobenzene is removed from the clothing.

SANITATION

• Skin that becomes wet with liquids containing p-nitrochlorobenzene should be immediately washed or showered with soap or mild detergent and water to remove any p-nitrochlorobenzene.

• Skin that becomes wet with p-nitrochlorobenzene should be promptly washed or showered with soap or mild detergent and water to remove any p-nitrochlorobenzene.

• Workers subject to skin contact with p-nitrochlorobenzene should wash with soap or mild detergent and water any areas of the body which may have contacted p-nitrochlorobenzene at the end of each work day.

• Eating and smoking should not be permitted in areas where p-nitrochlorobenzene or liquids containing p-nitrochlorobenzene are handled, processed, or stored.

• Employees who handle p-nitrochlorobenzene or liquids containing p-nitrochlorobenzene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to p-nitrochlorobenzene may occur and control methods which may be effective in each case:

Operation	Controls
Use in production of chemical intermediates for manufacture of pesticides, fungicides, and preservatives; production of chemical intermediates for manufacture of sulfur and azo-fast dyes; synthesis of intermediates in manufacture of pharmaceuticals, rubber chemicals, antioxidants, gasoline gum inhibitors, corrosion inhibitors, and photographic chemicals	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If p-nitrochlorobenzene or liquids containing p-nitrochlorobenzene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If p-nitrochlorobenzene or liquids containing p-nitrochlorobenzene get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If p-nitrochlorobenzene or liquids containing p-nitrochlorobenzene penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of p-nitrochlorobenzene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When p-nitrochlorobenzene or liquids containing p-nitrochlorobenzene have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency

rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If p-nitrochlorobenzene is spilled, the following steps should be taken:

1. Ventilate area of spill.

2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

p-Nitrochlorobenzene may be disposed of:

1. By making packages of p-nitrochlorobenzene in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving p-nitrochlorobenzene in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "p-Nitrochlorobenzene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "p-Nitrochlorobenzene," *Hygienic Guide Series*, Detroit, Michigan.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Linch, A. L.: "Biological Monitoring for Industrial Exposure to Cyanogenic Aromatic Nitro and Amino Compounds," *American Industrial Hygiene Association Journal*, 35:426-432, 1974.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• National Fire Protection Association: *Fire Protection Guide on Hazardous Materials* (5th ed.), National Fire Protection Association, Boston, 1975.

• Pacseri, I., et al.: "Threshold and Toxic Limits of Some Amino and Nitro Compounds," *A.M.A. Archives of Industrial Health*, 18:1-8, 1958.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Renshaw, A., and Ashcroft, G. V.: "Four Cases of Poisoning by Mononitrochlorobenzene and One by Acetanilide Occurring in a Chemical Works: With an Explanation of the Toxic Symptoms Produced," *Journal of Industrial Hygiene*, 8:67-73, 1926.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

• Watrous, R. M., and Schulz, H. N.: "Cyclohexylamine, p-Chloronitrobenzene, 2-Aminopyridine: Toxic Effects in Industrial Use," *Industrial Medicine and Surgery*, 19:317-320, 1950.

RESPIRATORY PROTECTION FOR p-NITROCHLOROBENZENE

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any dust and mist respirator, except single-use.
10 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 1000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Nitroethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_2H_5NO_2$
- Synonyms: None
- Appearance and odor: Colorless liquid with a mild, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nitroethane is 100 parts of nitroethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 310 milligrams of nitroethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nitroethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

In man, mild skin irritation has occured from repeated exposure of the skin. Animal exposure to nitroethane has produced irritation of the respiratory tract with breathing difficulties which may be delayed in onset. Irritation of the eyes, anesthesia, and death have also occured.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nitroethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nitroethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from nitroethane exposure.

—Chronic respiratory disease: Nitroethane causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of nitroethane might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Nitroethane causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Nitroethane causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: Nitroethane is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Nitroethane is a mild skin irritant. In animals, nitroethane vapor is narcotic and a pulmonary irritant and also causes liver damage. Rabbits died from exposure to 5000 ppm for 3 hours; exposure to 2500 ppm for 3 hours was not fatal. Effects were lacrimation, dyspnea, pulmonary rales, and, in a few animals, pulmonary edema. Twitching and jerking movements of the head and extremities were observed; convulsions were rare and of brief duration. Stupor or narcosis at high concentra-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

tions was rapidly reversible. Autopsy of animals exposed to lethal concentrations showed mild to severe liver damage and non-specific changes in the kidneys. No systemic effects have been reported in humans. The liquid is a mild skin irritant due to solvent action.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 75.1
2. Boiling point (760 mm Hg): 114 C (237 F)
3. Specific gravity (water = 1): 1.05
4. Vapor density (air = 1 at boiling point of nitroethane): 2.6
5. Melting point: −90 C (−130 F)
6. Vapor pressure at 20 C (68 F): 15.6 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 4.5
8. Evaporation rate (butyl acetate = 1): 1.2

- **Reactivity**

1. Conditions contributing to instability: Overheating of closed containers may cause detonation.
2. Incompatibilities: Contact with amines, strong acids, and alkalies may sensitize nitroethane so that it will readily explode. Contact with strong oxidizers may cause fires and explosions. Mixtures of nitroethane and hydrocarbons (or other combustible materials) are highly flammable. Contact with some metal oxides may cause decomposition and development of pressure.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving nitroethane.
4. Special precautions: Liquid nitroethane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 27.8 C (82 F) (closed cup)
2. Autoignition temperature: 414 C (778 F)
3. Flammable limits in air, % by volume: Lower: 3.4; Upper: Data not available
4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical

- **Warning properties**

1. Odor Threshold: Patty states that "the odors of nitroparaffins are easily detectable, and concentrations below 200 ppm are disagreeable to most observers. The odor and sensory symptoms are not dependable warning properties."
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that the vapors of nitroethane "are noticeably irritating at concentrations above 100 ppm but cannot be relied upon for warning properties." At 500 ppm and above, strong eye (and respiratory tract) irritation has been observed in animals.
3. Evaluation of Warning Properties: Patty states that "the odor and sensory symptoms (of the nitroparaffins) are not dependable warning properties."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for nitroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid nitroethane.
- Clothing wet with liquid nitroethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of nitroethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the nitroethane, the person performing the operation should be informed of nitroethane's hazardous properties.
- Any clothing which becomes wet with liquid nitroethane should be removed immediately and not reworn until the nitroethane is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid nitroethane may contact the eyes.

SANITATION

• Skin that becomes wet with liquid nitroethane should be promptly washed or showered with soap or mild detergent and water to remove any nitroethane.

• Employees who handle liquid nitroethane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nitroethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in coatings and adhesives on cellulose esters and synthetic resins	Process enclosure; local exhaust ventilation; personal protective equipment
Use as an intermediate in synthesis of organic dyes, insecticides, pesticides, nitroplasticizers, pharmaceuticals, and other organic chemicals	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as a propellant; as a reaction-media fluid; as an extraction solvent in petroleum fractionation; use as a recrystallization solvent	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid nitroethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid nitroethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid nitroethane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of nitroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid nitroethane has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid nitroethane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels and burn in a suitable combustion chamber which allows burning in an unconfined condition and is equipped with an appropriate effluent gas cleaning device. Large quantities can be collected, diluted in fuel oil, and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Liquid nitroethane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Liquid nitroethane may be disposed of by diluting with fuel oil and by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nitroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Nitroethane," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR NITROETHANE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Nitrogen Dioxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: NO_2 and N_2O_4
- Synonyms: Nitrogen tetroxide; NTO; dinitrogen tetroxide; nitrogen peroxide
- Appearance and odor: Dark brown fuming liquid or gas with a pungent, acrid odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nitrogen dioxide is a ceiling of 5 parts of nitrogen dioxide per million parts of air (ppm) (*Federal Register*, Vol. 43, No. 237, pp. 57601-03, 8 December 1978). This may also be expressed as 9 milligrams of nitrogen dioxide per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to a ceiling level of 1 ppm (1.8 mg/m^3) averaged over a 15-minute period. The NIOSH Criteria Document for Oxides of Nitrogen should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nitrogen dioxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to nitrogen dioxide may cause severe breathing difficulties which are usually delayed in onset and which may cause death. Recovery may be slow (2 to 3 weeks) with possible relapse and possible permanent lung damage. Pneumonia may occur. Irritation of the eyes, nose, throat, and wet skin may occur with acute exposures.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nitrogen dioxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nitrogen dioxide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory tract and cardiovascular system should be stressed.

—14" x 17" chest roentgenogram: Nitrogen dioxide causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Nitrogen dioxide is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Cardiovascular disease: Persons with cardiac disease may be at increased risk. An electrocardiogram should be performed on workers over 40 years of age and where indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis or as otherwise indicated by the responsible physician.

- **Summary of toxicology**

Nitrogen dioxide gas is a respiratory irritant; it causes pulmonary edema and rarely, among survivors, bronchiolitis obliterans. Brief exposure of humans to concentrations of about 250 ppm causes cough, production of mucoid or frothy sputum, and increasing dyspnea. Within 1 to 2 hours the person may develop pulmonary edema with tachypnea, cyanosis, and fine crackles and wheezes throughout the lungs, and tachycardia. Alter-

---

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

natively, there may be only increasing dyspnea and cough over several hours, the symptoms then gradually subside over a 2- to 3-week period. The condition may then enter a second stage of abruptly increasing severity; fever and chills precede a relapse with increasing dyspnea, cyanosis, and recurring pulmonary edema. Death may occur either in the initial or second stage of the disease; a severe second stage may follow a relatively mild initial stage. The subject who survives the second stage usually recovers over 2 to 3 weeks; however, some do not return to normal, but experience varying degrees of impaired pulmonary function. The radiographic features in the acute initial stage vary from normal to those of typical pulmonary edema; most reports mention a pattern of nodular shadows on the chest film at the outset. The roentgenogram may then clear, only to show miliary mottling as the second stage commences, progressing to the development of a confluent pattern. Results of pulmonary function tests in the acute stage show reduction in lung volume and diffusing capacity; similar findings are recorded in the second stage. Pathologic examination of the acute lesion shows extensive mucosal edema and inflammatory cell exudation. The delayed lesion shows the histologic appearance of bronchiolitis obliterans; small bronchi and bronchioles contain an inflammatory exudate which tends to undergo fibrinous organization, finally obliterating the lumen. The effects expected in humans from exposure to nitrogen dioxide for 60 minutes are: 100 ppm, pulmonary edema and death; 50 ppm, pulmonary edema with possible subacute or chronic lesions in the lungs; 25 ppm, respiratory irritation and chest pain. A concentration of 50 ppm is moderately irritating to the eyes and nose; 25 ppm is irritating to some people.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 46 and 92
2. Boiling point (760 mm Hg): 21 C (70 F)
3. Specific gravity (water = 1): 1.45 (liquid)
4. Vapor density (air = 1 at boiling point of nitrogen dioxide): 2.83
5. Melting point: −11.2 C (11.8 F)
6. Vapor pressure at 20 C (68 F): 720 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions (reacts to form nitric acid and nitric oxide)
8. Evaporation rate (butyl acetate = 1): Much greater than 1

- **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause cylinders to explode.
2. Incompatibilities: Contact with all combustible materials, chlorinated hydrocarbons, ammonia, and carbon disulfide may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen) may be released when nitrogen dioxide decomposes.
4. Special precautions: Nitrogen dioxide will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible, but strong oxidizing agent.

- **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* reports an odor threshold of 5 ppm.
2. Eye Irritation Level: According to Grant, "the gas at a concentration in approximately 70 ppm in air causes irritation of the eyes and nose evident in guinea pigs, rabbits, monkeys, and dogs during the first hour of exposure. At this concentration the gas has been lethal to most of the animals if exposed for eight hours, and under these conditions corneal opacities have been produced in the rabbits. The corneas of rabbits that survived such exposures did not improve under observation during twenty days. However, the gas at concentrations up to 20 ppm in air and exposure of four hours has produced no significant effect on the corneas of rabbits . . . . Exposure of the same magnitude repeated daily for more than a month also has not been damaging to the eye." The *Documentation of TLV's* reports that according to Patty, 10-20 ppm "were mildly irritant to the eyes . . . ."
3. Other Information: The AIHA *Hygienic Guide* states that "exposures of relatively short duration to concentrations above 5 ppm produce cough and irritation of the respiratory tract."
4. Evaluation of Warning Properties: Through its odor and irritant effects, nitrogen dioxide can be detected slightly above the recommended permissible exposure limit. For the purposes of this guideline, therefore, nitrogen dioxide is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of nitrogen dioxide. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of gas in a reagent-filled impinger with a subsequent spectrophotometric analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure nitrogen dioxide may be used. An analytical method for nitrogen dioxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed.,

Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid nitrogen dioxide.

• Clothing contaminated with nitrogen dioxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of nitrogen dioxide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the nitrogen dioxide, the person performing the operation should be informed of nitrogen dioxide's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid nitrogen dioxide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with nitrogen dioxide should be removed immediately and not reworn until the nitrogen dioxide is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid nitrogen dioxide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid nitrogen dioxide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with nitrogen dioxide should be immediately washed or showered to remove any nitrogen dioxide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nitrogen dioxide may occur and control methods which may be effective in each case:

Operation	Controls
Use during metal surface treatment with nitric acid; in production of intermediates in manufacture of sulfuric acid, nitric acid, and fertilizers	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation of fumes during engine maintenance, synthesis of dyes, manufacture of nitrocellulose paints, lacquers, and storage of silage in agricultural operations; production and handling of rocket propellants	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation of fumes during detonation of explosives	Personal protective equipment
Use in chemical synthesis during nitration operations	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid nitrogen dioxide or strong concentrations of nitrogen dioxide vapor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid nitrogen dioxide or strong concentrations of nitrogen dioxide vapor get on the skin, immediately flush the contaminated skin with water. If liquid nitrogen dioxide or strong concentrations of nitrogen dioxide vapor penetrate through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**
If a person breathes in large amounts of nitrogen dioxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When liquid nitrogen dioxide has been swallowed and if the person is conscious, immediately give the person large amounts of water to dilute the nitrogen dioxide. Do not attempt to make the unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If nitrogen dioxide is spilled or leaked, the following steps should be taken:
1. Ventilate area of spill or leak to disperse gas.
2. If in the liquid form, allow to vaporize.
3. If in the gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nitrogen Dioxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• American Industrial Hygiene Association: "Nitroge Dioxide," *Hygienic Guide Series*, Detroit, Michigar 1956.
• American Industrial Hygiene Association Toxicology Committee: "Emergency Exposure Limits: Nitrogen Dioxide,"*American Industrial Hygiene Association Journal*, 25:580-582, 1964.
• *American National Standard Acceptable Concentrations - Nitrogen Dioxide*: ANSI-Z37.13-1971, American National Standards Institute, Inc., New York, 1971.
• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
• *Federal Register*, Vol. 43, No. 237, pp. 57601-03, 8 December 1978.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• *Hygienic Information Guide No. 46 - Nitrogen Dioxide*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.
• Morgan, W. K. C., and Seaton, A.: *Occupational Lung Diseases*, Saunders, Philadelphia, 1975.
• Morley, R., and Silk, S. J.: "The Industrial Hazard from Nitrous Fumes," *Annals of Occupational Hygiene*13:101-107, 1970.
• National Institute for Occupational Safety and Health. U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Oxides of Nitrogen*, HEW Publication No. (NIOSH) 76-149, U.S. Government Printing Office, Washington, D.C., 1976.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Scott, E. G., and Hunt, W. B., Jr.: "Silo Filler's Disease," *Chest*, 63:701-706, 1973.

RESPIRATORY PROTECTION FOR NITROGEN DIOXIDE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Gas Concentration	
50 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) containing non-oxidizable sorbents and providing protection against nitrogen dioxide.**
	A gas mask with a chin-style or a front- or back-mounted canister containing non-oxidizable sorbents and providing protection against nitrogen dioxide.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 50 ppm*** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-oxidizable sorbents and providing protection against nitrogen dioxide.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Nitrogen dioxide is an oxidizer and should not come in contact with oxidizable materials. Some cartridges and canisters may contain oxidizable materials, such as activated charcoal, and therefore should not be used to provide protection against nitrogen dioxide. Only non-oxidizable sorbents are allowed.

***Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of nitrogen dioxide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 50 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Nitrogen Trifluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: NF_3
- Synonyms: None
- Appearance and odor: Colorless gas with a moldy odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nitrogen trifluoride is 10 parts of nitrogen trifluoride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 29 milligrams of nitrogen trifluoride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nitrogen trifluoride can affect the body if it is inhaled.

- **Effects of overexposure**

There are no reports of human intoxication from nitrogen trifluoride. In animals, nitrogen trifluoride can affect the ability of the blood to carry oxygen by forming methemoglobin. In man, methemoglobin formation may cause a bluish discoloration of the skin, drowsiness, dizziness, nausea, rapid heart beat, headache, shortness of breath, and unconsciousness.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nitrogen trifluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nitrogen trifluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, cardiovascular system, nervous system, liver, and kidneys should be stressed.

—A complete blood count: Nitrogen trifluoride has been shown to cause methemoglobinemia in animals. Persons with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determinations should be performed if overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

Nitrogen trifluoride gas causes anoxia due to the formation of methemoglobin in animals. Rats died from exposure to 10,000 ppm for 60 to 70 minutes; the methemoglobin concentrations at the time of death were equivalent to 60 to 70% of available hemoglobin. Animals exposed to nearly lethal concentrations suffered severe respiratory distress and cyanosis due to methemoglobinemia; severely affected animals showed incoordination, collapse and convulsions. Rats repeatedly exposed to 100 ppm for 4-½ months appeared normal, but autopsy findings indicated injury to the liver and kidneys. There are no reports of human intoxication from nitrogen trifluoride; however, the expected effects of methemoglobinemia in humans would result from anoxia and include cyanosis, evident

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

especially in the lips, nose, and ear lobes; other effects are weakness, dizziness, and severe headache.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 71
  2. Boiling point (760 mm Hg): −129 C (−200 F)
  3. Specific gravity (water = 1): 1.54 (liquid)
  4. Vapor density (air = 1 at boiling point of nitrogen trifluoride): 2.5
  5. Melting point: −206.8 C (−340 F)
  6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: Particularly hazardous under pressure; can react spontaneously due to shock or heat.
  2. Incompatibilities: Contact of nitrogen trifluoride with oxidizable materials (such as ammonia, carbon monoxide, methane, hydrogen, and hydrogen sulfide), chemically active metals, and oxides (such as silica (sand)) may cause fires and explosions. Mixtures of nitrogen trifluoride and water vapor may explode when ignited by high energy sources. It can react violently with grease or oil.
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible by itself, but can react explosively with reducing materials.
  2. See 29 CFR 1910.101 for specific regulations on storage of compressed gas cylinders.
- **Warning properties**
  1. Odor Threshold: According to the *Documentation of TLV's*, "NF_3 provides no odor-warning properties at potentially dangerous levels."
  2. Eye Irritation Level: The ILO states that "nitrogen trifluoride is strikingly less irritating than elemental fluorine, chlorine trifluoride, and oxygen difluoride." Information is not available concerning the threshold of eye irritation.
  3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of nitrogen trifluoride, and since the *Documentation of TLV's* states that "NF_3 provides no odor-warning properties at potentially dangerous levels," this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for nitrogen trifluoride had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nitrogen trifluoride may occur and control methods which may be effective in each case:

Operation	Controls
Use in the manufacture of flash cubes; use in welding, brazing, and cutting of metals using hydrogen-nitrogen trifluoride torch	Process enclosure; local exhaust ventilation; personal protective equipment
Use in research as an oxidizer for rocket and other high-energy fuels	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of tetrafluorohydrazine	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of nitrogen trifluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If nitrogen trifluoride is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nitrogen Trifluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dost, F. N., et al.: "Toxicology of Nitrogen Trifluoride," *Toxicology and Applied Pharmacology*, 17:585-596, 1970.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• Torkelson, T. R., et al.: "Preliminary Toxicologic Studies on Nitrogen Trifluoride," *Toxicology and Applied Pharmacology*, 4:770-781, 1962.

• Vernot, E. H., et al.: "Acute Inhalation Toxicology and Proposed Emergency Exposure Limits of Nitrogen Trifluoride," *Toxicology and Applied Pharmacology*, 26:1-13, 1973.

RESPIRATORY PROTECTION FOR NITROGEN TRIFLUORIDE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Gas Concentration	
100 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against nitrogen trifluoride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Nitromethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3NO_2
- Synonyms: None
- Appearance and odor: Colorless liquid with a mild, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nitromethane is 100 parts of nitromethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 250 milligrams of nitromethane per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nitromethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

In man, mild skin irritation has occurred from repeated exposure of the skin. Animal exposure to nitromethane has produced irritation of the respiratory tract, with breathing difficulties which might be delayed in onset. Irritation of the eyes, anesthesia, convulsion, and death have also occurred.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nitromethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nitromethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from nitromethane exposure.

—Chronic respiratory disease: Nitromethane causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of nitromethane might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: Nitromethane causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Convulsive disorders: Nitromethane causes convulsions in animals. Persons with a history of such disorders may be more susceptible to the effects of this agent.

—Kidney disease: Nitromethane causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Skin disease: Nitromethane is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Nitromethane is a mild skin irritant due to its solvent action. In animals the vapor affects the central nervous system by causing convulsions and narcosis and is a mild pulmonary irritant. It also causes liver damage in animals. Rabbits died from exposure to 10,000 ppm for 6 hours; there was weakness, ataxia and muscular incoor-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

dination followed by convulsions after a latent period. This concentration for 3 hours was not fatal. Autopsy of animals exposed to lethal concentrations revealed focal necrosis in the liver and moderate kidney damage. Lower concentrations produced slight irritation of the respiratory tract, followed by mild narcosis, weakness, and salivation, but no evidence of eye irritation. However, a single monkey exposed to 1000 ppm for eight 6-hour exposures died. No systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 61
2. Boiling point (760 mm Hg): 101.2 C (214 F)
3. Specific gravity (water = 1): 1.14
4. Vapor density (air = 1 at boiling point of nitromethane): 2.1
5. Melting point: −29 C (−20 F)
6. Vapor pressure at 20 C (68 F): 27.8 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 9.5
8. Evaporation rate (butyl acetate = 1): 1.39

- **Reactivity**

1. Conditions contributing to instability: Overheating of closed containers may cause detonation.
2. Incompatibilities: Contact with amines, strong acids, and alkalies may sensitize nitromethane so that it will readily explode. Contact with strong oxidizers may cause fires and explosions. Mixtures of nitromethane and hydrocarbons (or other combustible materials) are highly flammable. Contact with some metallic oxides may cause decomposition and development of pressure.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving nitromethane.
4. Special precautions: Liquid nitromethane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 35 C (95 F) (closed cup)
2. Autoignition temperature: 418 C (785 F)
3. Flammable limits in air, % by volume: Lower: 7.3; Upper: Data not available
4. Extinguishant: Alcohol foam, carbon dioxide, and dry chemical

- **Warning properties**

1. Odor Threshold: According to the AIHA *Hygienic Guide*, "the odor is very strong above 100 ppm and irritating at 200 ppm, but cannot be relied on for warning properties." No further explanation is offered. Patty also states, however, that "the odors of nitroparaffins are easily detectable, and concentrations below 200 ppm are disagreeable to most observers. The odor and sensory symptoms are not dependable warning properties."
2. Eye Irritation Level: The *Hygienic Guide* states that "severe eye and respiratory irritation was noted in animals at 500 ppm and above." This is not specifically stated to be the threshold of eye irritation.
3. Evaluation of Warning Properties: Patty states that "the odor and sensory symptoms (of nitroparaffins) are not dependable warning properties."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for nitromethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid nitromethane.
- Clothing wet with liquid nitromethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of nitromethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the nitromethane, the person performing the operation should be informed of nitromethane's hazardous properties.

• Any clothing which becomes wet with liquid nitromethane should be removed immediately and not reworn until the nitromethane is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid nitromethane may contact the eyes.

SANITATION

• Skin that becomes wet with liquid nitromethane should be promptly washed or showered to remove any nitromethane.

• Employees who handle liquid nitromethane should wash their hands thoroughly before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nitromethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in coatings and adhesives on cellulose esters and synthetic resins	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during application by dipping, roller coating, tumbling, knifing, or application of coatings and adhesives	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as an intermediate in synthesis of organic dyes, textiles, surfactants, insecticides, pharmaceuticals, and explosives	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as a propellant or fuel additive; use as a reaction-media fluid for Friedel-Crafts reaction; use as a recrystallization solvent; use as a solvent in manufacture of coatings and adhesives on cellulose esters or synthetic resins	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as a stabilizer for halogenated alkanes, aerosol formulations, and paste formulations for inks	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid nitromethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid nitromethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid nitromethane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of nitromethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid nitromethane has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid nitromethane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels and burn in a suitable combustion chamber which allows burning in an unconfined condition and is equipped with an effluent gas cleaning device. Large quantities can be collected, diluted in fuel oil, and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Liquid nitromethane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:
Liquid nitromethane may be disposed of by diluting with fuel oil and atomizing in a suitable combustion chamber equipped with an effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nitromethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Nitromethane," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR NITROMETHANE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1-Nitropropane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CH_2CH_2NO_2$
- Synonyms: None
- Appearance and odor: Colorless liquid with a mild, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1-nitropropane is 25 parts of 1-nitropropane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 90 milligrams of 1-nitropropane per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for 1-nitropropane from 25 ppm to 15 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1-Nitropropane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1-Nitropropane causes irritation of the eyes and respiratory tract, headache, nausea, vomiting, and diarrhea.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1-nitropropane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1-nitropropane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1-nitropropane exposure.

—Chronic respiratory disease: 1-Nitropropane causes respiratory irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1-nitropropane might cause exacerbation of symptoms due to its irritant properties.

—Liver disease: 1-Nitropropane causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: 1-Nitropropane causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1-Nitropropane vapor is an eye irritant and in animals causes mild respiratory irritation and severe liver damage. Rabbits died from exposure to 5,000 ppm for 3 hours, but 10,000 ppm for 1 hour was not lethal. Effects were conjunctival irritation, lacrimation, slow respiration with some rales, muscular incoordination, ataxia, and weakness. Autopsy of animals exposed to lethal concentrations revealed severe fatty infiltration of the liver and moderate kidney damage. Human volunteers exposed to over 100 ppm noted eye irritation. There are no reports of systemic effects in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1. Molecular weight: 89.1

2. Boiling point (760 mm Hg): 131.6 C (268 F)

3. Specific gravity (water = 1): 1.0

4. Vapor density (air = 1 at boiling point of 1-nitropropane): 3.1

5. Melting point: −108 C (−162 F)

6. Vapor pressure at 20 C (68 F): 7.5 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): 1.4

8. Evaporation rate (butyl acetate = 1): 0.8

• **Reactivity**

1. Conditions contributing to instability: Overheating in closed containers may cause violent explosion.

2. Incompatibilities: Even though no detonation of 1-nitropropane has been reported, contact with amines, strong acids, and alkalies may cause 1-nitropropane to become unstable. Contact with strong oxidizers may cause fires and explosions. Mixtures of 1-nitropropane and hydrocarbons (or other combustible materials) are highly flammable. Contact with some metal oxides may cause decomposition and development of pressure.

3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving 1-nitropropane.

4. Special precautions: Liquid 1-nitropropane will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 35.6 C (96 F) (closed cup)

2. Autoignition temperature: 420.6 C (789 F)

3. Flammable limits in air, % by volume: Lower: 2.2; Upper: Data not available

4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that "the odor (of nitropropane) is detectable at 300 ppm but not at 80 ppm."

2. Eye Irritation Level: Grant states that "tests of nitropropane vapor on human volunteers have established that a sensation of eye irritation is noted at a concentration of 150 ppm in air."

3. Evaluation of Warning Properties: Since the odor and irritation thresholds of nitropropane are not within three times the permissible exposure limit, it is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for 1-nitropropane had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Clothing wet with liquid 1-nitropropane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1-nitropropane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1-nitropropane, the person performing the operation should be informed of 1-nitropropane's hazardous properties.

• Any clothing which becomes wet with liquid 1-nitropropane should be removed immediately and not reworn until the 1-nitropropane is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid 1-nitropropane may contact the eyes.

SANITATION

• Employees who handle liquid 1-nitropropane should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1-nitropropane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a thinner and solvent for cellulose compounds, lacquers, and dopes; in vinyl resins for industrial coatings and printing inks; in synthetic finish removers,; and for oil- and spirit-soiuble dyes of molded plastics	Process enclosure; local exhaust ventilation; personal protective equipment
Use as an extraction solvent for purification, separation, recrystallization, and recovery for natural and synthetic resins, tars, coating materials, fats, and oils	Local exhaust ventilation; personal protective equipment
Use as a reaction medium in polymer technology, as a catalyst, initiator, and solvent	Local exhaust ventilation; personal protective equipment
Use in organic chemical synthesis for preparation of amines, nitrated alcohols, and acids, and chloronitroparaffins	Local exhaust ventilation; personal protective equipment
Use in manufacture of explosives	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid 1-nitropropane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid 1-nitropropane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid 1-nitropropane soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1-nitropropane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid 1-nitropropane has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid 1-nitropropane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels and burn in a suitable combustion chamber which allows burning in an unconfined condition and is equipped with an appropriate effluent gas cleaning device. Large quantities can be collected, diluted in fuel oil, and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Liquid 1-nitropropane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Liquid 1-nitropropane may be disposed of by diluting in fuel oil and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1-Nitropropane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "1-Nitropropane," *Hygienic Guide Series*, Detroit, Michigan, 1960.

• Browning, E. *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
• Grant, W. M. *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Deichmann, W. B., and Gerarde, H. W., *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Silverman, L., et al.: "Further Studies on Sensory Response to Certain Industrial Solvent Vapors," *Journal of Industrial Hygiene and Toxicology*, 28:262-266, 1946.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR 1-NITROPROPANE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
150 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
1250 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2300 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2300 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Nitrotoluene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Ortho: $2\text{-}NO_2C_6H_4CH_3$; Meta: $3\text{-}NO_2C_6H_4CH_3$; Para: $4\text{-}NO_2C_6H_4CH_3$
- Synonyms: Orthonitrotoluene; o-nitrotoluol; metanitrotoluene; m-nitrotoluol; paranitrotoluene; p-nitrotoluol
- Appearance and odor: Ortho: Yellow liquid or solid with a weak aromatic odor; Meta: Yellow liquid or solid with a weak aromatic odor; Para: Pale yellow solid with a weak aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for nitrotoluene is 5 parts of nitrotoluene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 30 milligrams of nitrotoluene per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for nitrotoluene from 5 ppm to 2 ppm with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Nitrotoluene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It is readily absorbed through the skin.

- **Effects of overexposure**

Nitrotoluene may affect the ability of the blood to carry oxygen. This may cause a bluish discoloration of the skin, irritability, drowsiness, nausea, rapid pulse, headache, weakness, shortness of breath, and unconsciousness.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to nitrotoluene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to nitrotoluene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, nervous system, gastrointestinal system, and cardiovascular system should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Nitrotoluene has been shown to cause methemoglobinemia. Persons with blood disorders may be at increased risk from exposure. A complete blood count should be performed, including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determinations should be performed if overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

Nitrotoluene, whether absorbed as vapor by inhalation or as liquid through the skin, has a potential for producing methemoglobin and subsequent anoxia. Signs and symptoms of overexposure are due to the loss of oxygen-carrying capacity of the blood. The onset of symptoms of methemoglobinemia is insidious and may be delayed up to 4 hours; headache is commonly ne

---

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

first symptom and may become quite intense as the severity of methemoglobinemia progresses. Cyanosis occurs when the methemoglobin concentration is 15% or more. Cyanosis develops early in the course of intoxication, first in the lips, the nose, and the ear lobes, and is usually recognized by fellow workers. Until the methemoglobin concentration approaches approximately 40%, the individual usually feels well, has no complaints, and will insist that nothing is wrong. At methemoglobin concentrations of over 40%, there usually is weakness and dizziness; at up to 70% concentration there may be ataxia, dyspnea on mild exertion, tachycardia, nausea, vomiting, and drowsiness.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 137.1
2. Boiling point (760 mm Hg): Ortho: 222 C (432 F); Meta: 232 C (450 F); Para: 238 C (460 F)
3. Specific gravity (water = 1): Ortho: 1.16; Meta: 1.16; Para: 1.3
4. Vapor density (air = 1 at boiling point of nitrotoluene): 4.7
5. Melting point: Ortho: −4 C (25 F); Meta: 16 C (61 F); Para: 52 C (126 F)
6. Vapor pressure at 20 C (68 F): Ortho and Meta: 0.15 mm Hg; Para: 0.12 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Ortho: 0.06; Meta: 0.05; Para: 0.004
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers or sulfuric acid may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving nitrotoluene.
4. Special precautions: Nitrotoluene will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Ortho: 106 C (223 F) (closed cup); Meta: 101 C (214 F); Para: 106 C (223 F)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Lower: Ortho: 2.2 (calculated); Meta and para: 1.6 (calculated)
4. Extinguishant: Carbon dioxide, dry chemical, foam

- **Warning properties**

1. Odor Threshold: Information is not available.
2. Eye Irritation Level: Nitrotoluene is not known to be an eye irritant.
3. Evaluation of Warning Properties: This substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using a silica gel adsorption tube with subsequent desorption using methanol and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure nitrotoluene may be used. An analytical method for nitrotoluene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid or liquid nitrotoluene.
- Non-impervious clothing which becomes contaminated with nitrotoluene should be removed promptly and not reworn until the nitrotoluene is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where solid or liquid nitrotoluene may contact the eyes.

SANITATION

• Skin that becomes contaminated with nitrotoluene should be promptly washed or showered with soap or mild detergent and water to remove any nitrotoluene.
• Eating and smoking should not be permitted in areas where solid nitrotoluene is handled, processed, or stored.
• Employees who handle solid or liquid nitrotoluene should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to nitrotoluene may occur and control methods which may be effective in each case:

Operation	Controls
Use in the manufacture of toluidines for the production of dyes, intermediates for vulcanization accelerators, gasoline inhibitors, and flotation agents; use as an analytical reagent	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in the manufacture of dinitrotoluenes for production of explosives; manufacture of nitrotoluene-sulfonic acids for production of azo and stilbene dyes	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis for intermediates of dyes, sun screening agents, and fuchsin – a red dye used in textile and leather industries	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If solid or liquid nitrotoluene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If solid or liquid nitrotoluene gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If solid or liquid nitrotoluene penetrates through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately
• **Breathing**
If a person breathes in large amounts of nitrotoluene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When solid or liquid nitrotoluene has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If nitrotoluene is spilled or leaked, the following steps should be taken:
1. Ventilate area of spill or leak.
2. For small quantities of liquid nitrotoluene, absorb on paper towels. For small quantities of solid nitrotoluene, sweep onto paper or other suitable material. Remove to a safe place (such as a fume hood) and burn the paper. Large quantities of liquid nitrotoluene can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Large quantities of solid nitrotoluene can be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
• Waste disposal methods:
Nitrotoluene may be disposed of:
1. For liquid nitrotoluene, by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing liquid nitrotoluene in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. By making packages of solid nitrotoluene in paper or

other suitable material or by dissolving in a flammable solvent (such as alcohol) and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Nitrotoluene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Linch, A. L.: "Biological Monitoring for Industrial Exposure to Cyanogenic Aromatic Nitro and Amino Compounds," *American Industrial Hygiene Association Journal*, 35:426-432, 1974.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.). Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR NITROTOLUENE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor or Particulate Concentration	
50 ppm or 280 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
200 ppm or 1120 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 200 ppm or 1120 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Octachloronaphthalene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}Cl_8$
- Synonyms: Halowax 1051
- Appearance and odor: Pale, yellow solid with an aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for octachloronaphthalene is 0.1 milligram of octachloronaphthalene per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Octachloronaphthalene can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. Every effort should be made to prevent skin, eye, oral, or inhalation contact with this material.

- **Effects of overexposure**

Overexposure to octachloronaphthalene may cause an acne-like skin rash. It may also injure the liver, resulting in such effects as fatigue, dark urine, yellow jaundice, and possibly death.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to octachloronaphthalene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to octachloronaphthalene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Octachloronaphthalene may cause liver damage. A profile of liver function should be performed by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Octachloronaphthalene may be regarded, mainly by analogy to the lower chlorinated naphthalenes such as the penta- and hexachlor derivatives, as probably toxic to the liver and the skin. There is no information on the effects of inhalation of vapor or dust on man. Ingestion experiments on cattle suggest that the octachlor is more toxic but less readily absorbed than the hexachlor derivative. Exposure of workers by inhalation or skin absorption to mixtures of chlorinated naphthalenes with a lower chlorine content has caused a severe acne-form dermatitis termed chloracne, as well as serious liver injury.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 403.7
2. Boiling point (760 mm Hg): 410 C (770 F) (approximately)
3. Specific gravity (water = 1): 2.0
4. Vapor density (air = 1 at boiling point of octachloronaphthalene): 13.9

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEAL . AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

10 11

5. Melting point: 185 C (365 F)

6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide and toxic chloride fumes) may be released in a fire involving octachloronaphthalene.

4. Special precautions: None

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: No quantitative information is available.

2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "eye injury has not proved to be troublesome with the chloronaphthalenes."

3. Evaluation of Warning Properties: There are no quantitative data relating warning properties to air concentrations of octachloronaphthalene; therefore, this substance is treated as a material with poor warning properties. The concentration of octachloronaphthalene in saturated air at 20 C could present a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of octachloronaphthalene on a filter, followed by extraction with hexane, and gas chromatographic analysis. An analytical method for octachloronaphthalene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with molten octachloronaphthalene.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid octachloronaphthalene or liquids containing octachloronaphthalene.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with octachloronaphthalene vapors from the heated material.

• If employees' clothing may have become contaminated with solid octachloronaphthalene, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with octachloronaphthalene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of octachloronaphthalene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the octachloronaphthalene, the person performing the operation should be informed of octachloronaphthalene's hazardous properties.

• Non-impervious clothing which becomes contaminated with molten octachloronaphthalene should be removed immediately and not reworn until the octachloronaphthalene is removed from the clothing.

• Non-impervious clothing which becomes contaminated with solid octachloronaphthalene or liquids containing octachloronaphthalene should be removed promptly and not reworn until the octachloronaphthalene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of molten octachloronaphthalene contacting the eyes.

• Employees should be provided with and required to use splash-proof safety goggles where solid octachloronaphthalene or liquids containing octachloronaphthalene may contact the eyes.

SANITATION

• Workers subject to skin contact with octachloronaphthalene should wash with soap or mild detergent and water any areas of the body which may have contacted octachloronaphthalene at the end of each work day.

• Skin that becomes contaminated with octachloronaphthalene should be promptly washed or showered with soap or mild detergent and water to remove any octachloronaphthalene.

• Eating and smoking should not be permitted in areas where solid octachloronaphthalene is handled, processed, or stored.

• Employees who handle solid octachloronaphthalene or liquids containing octachloronaphthalene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to octachloronaphthalene may occur and control methods which may be effective in each case:

Operation	Controls
Use during manufacture of electric equipment as an insulating material; pouring molten solvent or finely ground solid materials; dipping; peeling and covering insulated cable with fabric	Local exhaust ventilation; general dilution with intake and exhaust fans; personal protective equipment
Liberation from use of electrical equipment insulated with octachloronaphthalene/ pentachloro-naphthalene	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an inert compound of resins or polymers for coating or impregnating textiles, wood, and paper to impart flame resistance, water proofness, and fungicidal and insecticidal properties	Process enclosure; local exhaust ventilation; general dilution with intake and exhaust fans; personal protective equipment
Use as an additive for cutting oil in various operations performed on metals	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an additive to special lubricants in crankcase oil, lubricants for farm machinery, and extreme-pressure lubricants	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solid octachloronaphthalene or liquids containing octachloronaphthalene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. If molten octachloronaphthalene gets into the eyes, immediately flush the eyes with large amounts of water to remove heat. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If non-impervious clothing becomes contaminated with octachloronaphthalene, remove and clean the clothing before wearing it again. If non-impervious clothing becomes heavily contaminated, it should be destroyed. If solid octachloronaphthalene or liquids containing octachloronaphthalene get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If skin irritation persists after washing, get medical attention. If molten octachloronaphthalene gets on the skin or non-impervious clothing, immediately flush the affected area with large amounts of water to remove heat. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of octachloronaphthalene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When octachloronaphthalene has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If octachloronaphthalene is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquids containing octachloronaphthalene should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Octachloronaphthalene may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Octachloronaphthalene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chloronaphthalenes," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koppers Corporation: *Material Safety Data Sheet - Octachloronaphthalene.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR OCTACHLORONAPHTHALENE

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
1 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Octane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_8H_{18}
- Synonyms: Normal octane
- Appearance and odor: Colorless liquid with a gasoline-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for octane is 500 parts of octane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2350 milligrams of octane per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be reduced to 75 ppm (350 mg/m³) averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 385 ppm (1800 mg/m³) averaged over a 15-minute period. The NIOSH Criteria Document for Alkanes should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Octane can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to octane may cause irritation of the eyes, nose, and skin, and drowsiness. Exposure to higher air concentrations may cause unconsciousness and death.

2. Long-term Exposure: Prolonged overexposure may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to octane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to octane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central and peripheral nervous systems and the skin should be stressed.

—Skin disease: Octane is a skin defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although octane is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although octane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of octane might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: The aforementioned medical examinations should be performed on an annual basis.

- **Summary of toxicology**

Octane vapor is a mild narcotic and mucous membrane irritant. Mice exposed at concentrations of 6600 to 13,700 ppm demonstrated signs of narcosis in 30 to 90 minutes. The narcotic concentration is approximately 8000 ppm, while the fatal concentration for animals is

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

near 13,500 ppm. Repeated or prolonged skin contact with the liquid results in drying and cracking skin due to defatting action. No chronic systemic effects have been reported in humans. Aspiration may cause chemical pneumonia.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 114.2
  2. Boiling point (760 mm Hg): 126 C (258 F)
  3. Specific gravity (water = 1): 0.7
  4. Vapor density (air = 1 at boiling point of octane): 3.9
  5. Melting point: −56.7 C (−70 F)
  6. Vapor pressure at 20 C (68 F): 11 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.04 (approximately)
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving octane.
  4. Special precautions: Octane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 13.3 C (56 F) (closed cup)
  2. Autoignition temperature: 220 C (428 F)
  3. Flammable limits in air, % by volume: Lower: 1.0; Upper: 6.5
  4. Extinguishant: Foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Summer and May both report an odor threshold of 150 ppm for octane.
  2. Eye Irritation Level: According to the *Handbook of Organic Industrial Solvents*, "irritation occurs as exposure exceeds threshold limit."
  3. Evaluation of Warning Properties: Because of its low thresholds of odor and irritation, octane is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of octane. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of octane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure octane may be used. An analytical method for octane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid octane.
- Any clothing which becomes wet with liquid octane should be removed immediately and not reworn until the octane is removed from the clothing.
- Clothing wet with liquid octane should be placed in closed containers for storage until it can be discarded or

until provision is made for the removal of octane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the octane, the person performing the operation should be informed of octane's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where liquid octane may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to octane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes wet with liquid octane should be promptly washed or showered with soap or mild detergent and water to remove any octane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to octane may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of gasoline, rocket fuel, and of fuel cells, and in combustion studies	General dilution ventilation; local exhaust ventilation
Use as an industrial solvent as lacquer diluent, phosphate manufacture, and preparation of liquid soaps and detergents	General dilution ventilation; local exhaust ventilation
Use in azeotropic mixtures for printing ink manufacture, and separation distillation	General dilution ventilation; local exhaust ventilation
Use as an additive and solvent in polymer manufacture	General dilution ventilation; local exhaust ventilation
Use in manufacture of benzene, toluene, and xylene aromatics	Process enclosure; local exhaust ventilation; personal protective equipment
Use in laboratory procedures and studies	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a blowing agent for foam rubber used in rocket propellants	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If octane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If octane gets on the skin, promptly wash the contaminated skin using soap or mild detergent. If octane soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of octane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If octane has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If octane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Octane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Octane may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Octane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Hexane," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents, Technical Guide No. 6* (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Alkanes*, HEW Publication No. (NIOSH) 77-151, GPO No. 017-033-00213-4, U.S. Government Printing Office. Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

RESPIRATORY PROTECTION FOR OCTANE

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Mineral Oil Mist

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_nH_{2n+2} where n = 16 and up
- Synonyms: The mist of petroleum-based: white mineral oil; cutting oils; heat-treating oils; hydraulic oils; cable oil; transformer oil; lubricating oils; drawing oils
- Appearance and odor: Mist with an odor like burned lube oil generated from petroleum-base or white mineral petroleum oil.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for mineral oil mist is 5 milligrams of mineral oil mist per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Mineral oil mist can affect the body if it is inhaled.

- **Effects of overexposure**

Inhalation of mineral oil mist may cause adverse respiratory effects.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to mineral oil mist.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to mineral oil mist at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from mineral oil mist exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of mineral oil mist might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Prolonged exposure to mineral oil mist may cause a dermatitis. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Inhalation of mineral oil mist in high concentrations may cause pulmonary effects, although this has rarely been reported. A single case of lipoid pneumonitis suspected to have been caused by exposure to very high concentrations of oil mist was reported in 1950; this occurred in a cash register serviceman, whose heavy exposure occurred over 17 years of employment: no other cases have been recorded. Experimental animal exposure studies to white mineral oil mist (untreated, and with no additions) for repeated daily 6-hour exposures for 1 year at 5 mg/m^3 were entirely negative in all criteria used for measuring response. A similar study at 100 mg/m^3 resulted in some slight changes in some but not all species exposed; no histologic changes of significance were noted. Exposure to oil mist did not appear to accelerate the production of lung tumors in a lung-tumor-susceptible strain of mice. A second parallel study of sulfurized, solvent-extracted naphthenic-base oil to which animals were exposed daily at 50 mg/m^3 for 18 months failed to reveal a single animal with any sort of injury or indisposition as a result of the oil mist inhalation. A review of exposures to mineral oil mist averaging 15 mg/m^3 (but often higher) in several industries disclosed a striking lack of reported cases of illness related to these exposures. A study of oil mist

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

exposures in machine shops, at mean concentrations of 3.7 mg/m³ and maximum of 110 mg/m³, showed no increase in respiratory symptoms or decrement in respiratory performance attributable to oil mist inhalation among men employed for many years. There is no evidence to suggest any relation between in- halation of oil mist and lung cancer. On the other hand, there are some reported cases of skin cancer from contact with certain oils. Contact with liquid oils may cause dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: Not pertinent
  2. Boiling point (760 mm Hg): 360 C (680 F)
  3. Specific gravity (water = 1): 0.8 – 0.9
  4. Vapor density (air = 1 at boiling point of mineral oil mist): Not applicable
  5. Melting point: Very low
  6. Vapor pressure at 20 C (68 F): Very low
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Flash point: 135 C (275 F) (closed cup)
  2. Autoignition temperature: 260 – 371 C (500 – 700 F)
  3. Flammable limits in air, % by volume: Not applicable
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**

Mineral oil mist is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of mineral oil mist on a filter, followed by treatment with chloroform and analysis by fluorescence spectrophotometry. An analytical method for mineral oil mist is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid mineral oil.
- Non-impervious clothing which becomes wet with liquid mineral oil should be removed promptly and not reworn until the mineral oil mist is removed from the clothing.

SANITATION

- Skin that becomes wet with liquid mineral oil should be promptly washed or showered with soap or mild detergent and water to remove any mineral oil mist.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to mineral oil mist may occur and control methods which may be effective in each case:

Operation	Controls
Use as a coolant or quenching agent in machine shop operations and metal fabrication; during coating and cleaning in foundry operations	Process enclosure; local exhaust ventilation; general mechanical ventilation
Use in steel rolling operations; use in lubricating and cleaning of machinery	Process enclosure; local exhaust ventilation; general mechanical ventilation
Use in pressroom operations in printing	Mist suppression; local exhaust ventilation; general mechanical ventilation
Use in mine drilling operations	Process enclosure; local exhaust ventilation; general mechanical ventilation
Use as an insecticide	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Skin Exposure**

If skin becomes wet with mineral oil mist, wash the contaminated skin using soap or mild detergent and water. If mineral oil mist penetrates through the clothing, remove the clothing and wash the skin using soap or mild detergent and water.

• **Breathing**

If a person breathes in large amounts of mineral oil mist, move the exposed person to fresh air at once.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or releases until cleanup has been completed.

• If mineral oil mist is released in hazardous concentrations, ventilate area of release to disperse the mist.

• If mineral oil mist is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber.

• Waste disposal methods:

Mineral oil mist may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Oil Mist (Mineral)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Ely, T. S., et al.: "A Study of Mortality, Symptoms, and Respiratory Function in Humans Occupationally Exposed to Oil Mist," *Journal of Occupational Medicine*, 12:253-261, 1970.

• Goldstein, D. H., et al.: "An Epidemiologic Study of an Oil Mist Exposure," *Archives of Environmental Health*, 21:600-603, 1970.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hendricks, N. V., et al.: "A Review of Exposures to Oil Mist," *Archives of Environmental Health*, 4:139-145, 1962.

• Lippmann, M., and Goldstein, D. H.: "Oil-Mist Studies, Environmental Evaluation and Control," *Archives of Environmental Health*, 21:591-599, 1970.

• Proudfit, J. P., et al.: "Chronic Lipid Pneumonia Following Occupational Exposure," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 1:105-111, 1950.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

RESPIRATORY PROTECTION FOR MINERAL OIL MIST

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
25 mg/m³ or less	Any mist respirator, except single-use.
50 mg/m³ or less	Any mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
250 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
2,500 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 2,500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Organo (Alkyl) Mercury

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all organo (alkyl) mercury compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Ethylmercuric chloride

- Formula: C_2H_5HgCl
- Synonyms: Chloroethylmercury; ceresan
- Appearance and odor: Colorless, odorless solid.

Dimethylmercury

- Formula: $(CH_3)_2Hg$
- Synonyms: Mercury dimethyl
- Appearance and odor: Colorless liquid with a weak, sweetish odor.

Diethylmercury

- Formula: $(C_2H_5)_2Hg$
- Synonyms: Mercury diethyl
- Appearance and odor: Colorless liquid with a weak, sweetish odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for organo (alkyl) mercury is 0.01 milligram of organo (alkyl) mercury per cubic meter of air (mg/m^3) averaged over an eight-hour work shift, with a ceiling level of 0.04 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Organo (alkyl) mercury can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Organo (alkyl) mercury compounds may cause damage to the central nervous system and are irritants of the eyes, respiratory tract, and skin. Symptoms of methyl and ethyl mercury intoxication may occur weeks to months after an acute exposure to toxic concentrations. The symptoms of acute and chronic intoxication from both compounds are similar and include numbness and tingling of the lips, hands and feet, staggering, joint pain, narrowing of vision, hearing difficulties, and emotional disturbances. With severe intoxication the symptoms are usually irreversible. Severe intoxication also results in periods of spasticity and jerking movements of the arms and legs, head or shoulders, and bouts of groaning, moaning, shouting, or crying. Other symptoms are dizziness, increased watering of the mouth, watering of the eyes, nausea, vomiting, and diarrhea or constipation. Infants born to mothers who have been exposed to large amounts of methyl mercury have shown mental retardation and cerebral palsy with convulsions. The symptoms of exposure to methoxyethyl mercury are loss of appetite, diarrhea, weight loss, and fatigue. Kidney damage has occurred. The alkyl mercury halides are irritating to the eyes, upper respiratory tract, and skin and may cause severe skin rash and burns. Allergic skin rashes may occur.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to organo (alkyl) mercury.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

• **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to organo (alkyl) mercury at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system, the kidneys, and eyes should be stressed. The skin should be examined for evidence of chronic disorders.

—Blood test: Analysis of the blood for mercury may be useful in monitoring absorption.

—Urinalysis: Since kidney damage has been observed in humans exposed to organo mercury, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Organo (alkyl) mercury compounds cause dysfunction of the central nervous system and irritate the eyes, mucous membranes, and and skin. Symptoms of methyl and ethyl mercury intoxication may occur weeks to months after an acute exposure to toxic concentrations. The symptoms of acute and chronic intoxication from both compounds are similar and include numbness and tingling of the lips, hands, and feet; ataxia; dysarthria; concentric constriction of the visual fields (tunnel vision); impairment of hearing; and emotional disturbances. With severe intoxication, the symptoms are usually irreversible. Severe intoxication also results in incontinence, periods of spasticity and jerking movements of the limbs, head or shoulders, and bouts of groaning, moaning, shouting, or crying; less frequent symptoms are dizziness, hypersalivation, lacrimation, nausea, vomiting, and diarrhea or constipation. An epidemic of intoxication from ingestion of fish contaminated with methyl mercury occurred in the Minamata district in Japan, and methyl mercury intoxication is often referred to as Minamata disease. Infants born to mothers with exposure to large amounts of methyl mercury had mental retardation and cerebral palsy with convulsions; methyl mercury has a strong effect on cell division and chromosome segregation, which may produce chromosomal alterations. The biological half-life in humans for methyl mercury is about 70 days; since elimination is slow, irregular, and individualized, there is a considerable risk of an accumulation of mercury to toxic levels. A precise relationship between atmospheric levels and concentrations of mercury in blood or urine cannot be shown. Clinical observations indicate that concentrations of 50 to 100 ug mercury/100 ml of whole blood may be associated with symptoms of intoxication; concentrations around 10 to 20 ug mercury/100 ml are not associated with symptoms. In a study of 20 workers engaged in the manufacture of organic mercurials and exposed for 6 years to mercury concentrations in air between 0.01 and 0.1 mg/m^3, there was no evidence of physical impairment or clinical laboratory abnormalities. The symptoms of exposure to methoxyethyl mercury are anorexia, diarrhea, weight loss, and fatigue, and are probably due to inorganic mercury; kidney damage with albuminuria, and occasionally a nephrotic syndrome, has occurred. The alkyl mercury halides are irritating to the eyes, mucous membranes, and skin and may cause severe dermatitis and burns; skin sensitization has occasionally occurred.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Ethylmercuric chloride**

1. Molecular weight: 265.1
2. Boiling point (760 mm Hg): Sublimes above 40 C (104 F)
3. Specific gravity (water = 1): 3.48
4. Vapor density (air = 1 at boiling point of ethylmercuric chloride): 9.2
5. Melting point: 192 C (378 F)
6. Vapor pressure at 20 C (68 F): Much less than 1
7. Solubility in water, g/100 g water at 20 C (68 F): 0.00014
8. Evaporation rate (butyl acetate = 1): Data not available

• **Physical data—Dimethylmercury**

1. Molecular weight: 230.7
2. Boiling point (760 mm Hg): 95 C (203 F)
3. Specific gravity (water = 1): 3.2
4. Vapor density (air = 1 at boiling point of dimethylmercury): 7.9
5. Melting point: −80 C (−112 F) (approximately)
6. Vapor pressure at 20 C (68 F): 50 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Data not available

• **Physical data—Diethylmercury**

1. Molecular weight: 258.7
2. Boiling point (760 mm Hg): 159 C (318 F)
3. Specific gravity (water = 1): 2.5
4. Vapor density (air = 1 at boiling point of diethylmercury): 8.9
5. Melting point: Data not available (very low)
6. Vapor pressure at 20 C (68 F): 2 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Elevated temperatures cause decomposition to flammable and explosive hydrocarbon gases.
2. Incompatibilities: Contact with strong oxidizers such as chlorine may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases

and vapors (such as toxic mercury fumes and carbon monoxide) may be released in a fire involving organo (alkyl) mercury.

4. Special precautions: Liquid organo (alkyl) mercury will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: Ethylmercuric chloride: Not applicable; Dimethylmercury and diethylmercury: Data not available

2. Autoignition temperature: Data not available

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Dry chemical, foam, carbon dioxide

• **Warning properties**

1. Odor Threshold: The American National Standards Institute (ANSI) states that many alkyl mercury compounds "are disagreeable in odor."

2. Irritation Levels: ANSI states that "the organomercurials are severe skin, eye, and mucous membrane irritants. The first complaints following surface contact may be delayed for several hours and are usually those of local warmth and redness, which progress to blistering. In cases of repeated exposure, skin sensitization may occur."

3. Evaluation of Warning Properties: Not all alkyl mercury compounds have adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of organo (alkyl) mercury. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

An analytical method for organo (alkyl) mercury is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with organo (alkyl) mercury or liquids containing organo (alkyl) mercury.

• If employees' clothing has had any possibility of being contaminated with organo (alkyl) mercury or liquids containing organo (alkyl) mercury, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with organo (alkyl) mercury should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of organo (alkyl) mercury from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the organo (alkyl) mercury, the person performing the operation should be informed of organo (alkyl) mercury's hazardous properties.

• Where there is any possibility of exposure of an employee's body to organo (alkyl) mercury or liquids containing organo (alkyl) mercury, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with organo (alkyl) mercury should be removed immediately and not reworn until the organo (alkyl) mercury is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of organo (alkyl) mercury or liquids

containing organo (alkyl) mercury contacting the eyes.
• Where there is any possibility that employees' eyes may be exposed to organo (alkyl) mercury or liquids containing organo (alkyl) mercury, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with organo (alkyl) mercury should be immediately washed or showered with soap or mild detergent and water to remove any organo (alkyl) mercury.
• Workers subject to skin contact with organo (alkyl) mercury or liquids containing organo (alkyl) mercury should wash with soap or mild detergent and water any areas of the body which may have contacted organo (alkyl) mercury at the end of each work day.
• Eating and smoking should not be permitted in areas where organo (alkyl) mercury or liquids containing organo (alkyl) mercury are handled, processed, or stored.
• Employees who handle organo (alkyl) mercury or liquids containing organo (alkyl) mercury should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to organo (alkyl) mercury may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during manufacture/ production for use as fungicides and slimicides	Replacement/ substitution; dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during processing mercury ore and during mining and extraction operations	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in treating and disinfecting of seeds and bulbs	Replacement/ substitution; general dilution ventilation; personal protective equipment
Liberation during utilization (spraying) of seeds and bulbs	Replacement/ substitution; general dilution ventilation; personal protective equipment
Use as a wood, timber, and paper preservative and slimicide; liberation during analysis at seed control stations	Replacement/ substitution; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If organo (alkyl) mercury or solutions containing organo (alkyl) mercury compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with these chemicals.
• **Skin Exposure**
If solid organo (alkyl) mercury or solutions containing organo (alkyl) mercury get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If solid organo (alkyl) mercury or solutions containing organo (alkyl) mercury penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention.
• **Breathing**
If a person breathes in large amounts of organo (alkyl) mercury, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When organo (alkyl) mercury has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If organo (alkyl) mercury compounds are spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. If in the solid form, collect for reclamation or disposal in sealed containers in a secured sanitary landfill.
4. If in the liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and reclaimed or collected for reclamation or disposal in sealed containers in a secured sanitary landfill.

• Waste disposal methods:

Organo (alkyl) mercury may be disposed of:

1. If in the solid form, by collecting for reclamation or for disposal in sealed containers in a secured sanitary landfill.
2. If in the liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and reclaimed or collected for reclamation or disposal in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Organo (Alkyl) Mercury," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• *American National Standard Acceptable Concentrations - Organo (Alkyl) Mercury*: ANSI-Z37.30-1969, American National Standards Institute, Inc., New York, 1969.

• Dinman, B. D., et al.: "Organic Mercury - Environmental Exposure, Excretion, and Prevention of Intoxication in Its Manufacture," *A.M.A. Archives of Industrial Health*, 18:248-260, 1958.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Goldwater, L. J., et al.: "Absorption and Excretion of Mercury in Man. IV. Tolerance to Mercury," *Archives of Environmental Health*, 7:568-573, 1968.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1974.

• Lofroth, G.: "Methylmercury - A Review of Health Hazards and Side Effects Associated with the Emission of MercCompounds into Natural Systems," Pamphlet No. D: R-101, Chlorine Institute, Inc., New York, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Report of an International Committee: "Maximum Allowable Concentrations of Mercury Compounds," *Archives of Environmental Health*, 19:891-905, 1969.

• Rustam, H., et al.: "Evidence for a Neuromuscular Disorder in Methylmercury Poisoning - Clinical and Electrophysiological Findings in Moderate to Severe Cases," *Archives of Environmental Health*, 30:190-195, 1975.

• Stauden, A. (ex. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

RESPIRATORY PROTECTION FOR ORGANO (ALKYL) MERCURY

Condition	Minimum Respiratory Protection* Required Above 0.01 mg/m³
Particulate or Vapor Concentration	
0.5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 10 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organo (alkyl) mercury vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of organo (alkyl) mercury; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 10 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Osmium Tetroxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: OsO_4
- Synonyms: Osmic acid
- Appearance and odor: Colorless to pale yellow solid with a sharp, choking, chlorine-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for osmium tetroxide is 0.002 milligrams of osmium tetroxide per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for osmium tetroxide a Threshold Limit Value of 0.0002 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Osmium tetroxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to osmium tetroxide may cause severe eye damage accompanied by irritation with tearing. This may occur several hours after exposure has ceased. After exposure, halos may be seen around lights. Exposure to osmium tetroxide may also cause severe irritation of the nose, throat, and bronchial tubes with cough, wheezing, shortness of breath, and pneumonia. In addition, exposure to this chemical may also cause skin burns, skin rash, skin discoloration, and kidney damage.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to osmium tetroxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to osmium tetroxide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from osmium tetroxide exposure.

—Eye disease: Osmium tetroxide is an eye irritant and in workers has caused symptoms and signs of keratitis epithelia with corneal edema. Persons with pre-existing eye disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of osmium tetroxide might cause exacerbation of symptoms due to its irritant properties.

—Kidney disease: Osmium tetroxide causes mild kidney damage in animals. Persons with pre-existing kidney disease may be more susceptible to the effects of this agent.

—Skin disease: Osmium tetroxide is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Osmium tetroxide as dust or vapor is a severe irritant of the eyes and respiratory tract. Rabbits exposed for 30 minutes to vapor at estimated concentrations of 130 mg/m^3 developed irritation of mucous membranes and labored breathing; at autopsy there was bronchopneumonia, as well as slight kidney damage. A laboratory investigator exposed to a high concentration of vapor experienced a sensation of chest constriction and diffi-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

culty in breathing. Irritation of the eyes is usually the first symptom of exposure to low concentrations of the vapor; lacrimation, a gritty feeling in the eyes, and the appearance of rings around lights are frequently reported; in most cases, recovery occurs within a few days. Workers exposed to fume concentrations up to 0.6 mg/m³ developed lacrimation, visual disturbances, and, in some cases, frontal headache, conjunctivitis, and cough. Application of a drop of 1% solution of osmium tetroxide to a rabbit eye caused severe corneal damage; there was permanent opacity and superficial vascularization. Osmium compounds have a caustic action on the skin resulting in eczema and dermatitis. Osmium tetroxide is a very irritating material to the skin due to its ability to precipitate protein.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 2.54
2. Boiling point (760 mm Hg): 130 C (266 F) (sublimes well below boiling point)
3. Specific gravity (water = 1): 4.9
4. Vapor density (air = 1 at boiling point of osmium tetroxide): 8.8
5. Melting point: 42 C (108 F)
6. Vapor pressure at 20 C (68 F): 7 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 7
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with hydrochloric acid will cause formation of poisonous chlorine gas. Contact with easily oxidized organic materials may cause fires and explosions.
3. Hazardous decomposition products: None
4. Special precautions: None

- **Flammability**

1. Not combustible

- **Warning properties**

1. Odor Threshold: According to Hunter, osmium tetroxide has an irritating odor, but no quantitative information is available concerning the odor threshold.
2. Eye Irritation Level: Grant states that "the eyes are particularly susceptible to injury by vapors of osmium tetroxide. With sufficient concentrations a sensation of irritation with lacrimation and sensation of foreign body is induced immediately. This may be accompanied by irritation of the nose and throat . . . . Concentrations of vapor which do not cause immediate sensation of irritation have an insidious cumulative action with a latent period before the onset of smarting and lacrimation, which may be delayed from 1 to several hours after start of exposure. In either case the symptoms and signs are those of keratitis epithelialis with corneal epithelial edema . . . . No permanent effect has been noted, even when several episodes of keratitis epithelialis have been experienced." Grant later states, however, that application of a drop of 1% solution of osmium tetroxide on rabbit eyes resulted in "moderate permanent opacity."
3. Evaluation of Warning Properties: Since there is no quantitative information relating warning properties to air concentrations of osmium tetroxide, and since this is such an extremely toxic substance, it should be treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for osmium tetroxide had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with osmium tetroxide or liquids containing osmium tetroxide, where skin contact may occur.
- If employees' clothing may have become contaminated with solid osmium tetroxide, employees should

change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with osmium tetroxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of osmium tetroxide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the osmium tetroxide, the person performing the operation should be informed of osmium tetroxide's hazardous properties.

• Non-impervious clothing which becomes contaminated with osmium tetroxide should be removed promptly and not reworn until the osmium tetroxide is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid osmium tetroxide or liquids containing osmium tetroxide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solid or liquid osmium tetroxide or liquids containing osmium tetroxide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with osmium tetroxide should be promptly washed or showered to remove any osmium tetroxide.

• Eating and smoking should not be permitted in areas where solid or liquid osmium tetroxide or liquids containing osmium tetroxide are handled, processed, or stored.

• Employees who handle solid or liquid osmium tetroxide or liquids containing osmium tetroxide should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to osmium tetroxide may occur and control methods which may be effective in each case:

Operation	Controls
By-product during refining and processing of osmiridium and other platinum metal ores; during production of alloys; during casting and annealing operations in manufacture of specialty metal products	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an intermediate for separation of metals and ores of osmium from platinum; use as a catalyst for oxidizing agent in organic synthesis; use as a staining and fixing agent in pathological and histological analysis; use as a laboratory reagent	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If osmium tetroxide gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid or liquid osmium tetroxide or liquids containing osmium tetroxide get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If solid or liquid osmium tetroxide or liquids containing osmium tetroxide penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of osmium tetroxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When osmium tetroxide has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If solid or liquid osmium tetroxide or liquids containing osmium tetroxide are spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquid containing osmium tetroxide should be absorbed in vermiculite, dry sand, earth, or a similar material.

- Waste disposal method:

Osmium tetroxide may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Osmium Tetroxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- American Industrial Hygiene Association: "Osmium and Its Compounds," *Hygienic Guide Series*, Detroit, Michigan, 1968.
- Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.
- Brunot, F. R.: "The Toxicity of Osmium Tetroxide," *Journal of Industrial Hygiene*, 15:136, 1933.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.
- Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- McLaughlin, A. I. G., et al.: "Toxic Manifestations of Osmium Tetroxide," *British Journal of Industrial Medicine*, 3:183-186, 1946.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR OSMIUM TETROXIDE

Condition	Minimum Respiratory Protection* Required Above 0.002 mg/m³
Particulate and Vapor Concentration	
0.1 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask with a high efficiency filter providing protection against osmium tetroxide vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Oxalic Acid

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $HOOCCOOH\text{-}2H_2O$
- Synonyms: Oxalic acid dihydrate; ethanedioic acid
- Appearance and odor: Colorless, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for oxalic acid is 1 milligram of oxalic acid per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Oxalic acid can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may slowly enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to either solid or liquid oxalic acid can cause severe burns of the skin, eyes, and linings of the respiratory tract. A number of deaths have occurred from swallowing oxalic acid. The symptoms appear rapidly and include shock, collapse, and convulsive seizures. Such cases may also have marked kidney damage.

2. Long-term Exposure: Prolonged or repeated skin contact with oxalic acid solutions may cause pain and discoloration of the fingers. This may go on to gangrene.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to oxalic acid.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to oxalic acid at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from oxalic acid exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of oxalic acid might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Oxalic acid is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Oxalic acid may cause kidney damage. Special consideration should be given to exposing those with impaired renal function.

—Eye disease: Oxalic acid is a severe eye irritant and may cause tissue damage. Those with pre-existing eye problems may be at increased risk from exposure.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Oxalic acid as a dust or in solution irritates the eyes, mucous membranes, and skin. There is little reported information on industrial exposures, although chronic inflammation of the upper respiratory tract has been described in a worker exposed to hot vapors (probably an aerosol) arising from oxalic acid. Solutions are irritating to the skin after prolonged exposure and may cause localized pain, with cyanosis of the fingers and even gangrenous changes. Splashes in the eye produce epithelial damage from which recovery is usually prompt. Fatalities have been reported following ingestion of as little as 5 g; the onset of symptoms is rapid, including those of shock, collapse, and convulsions;

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

there may be marked renal damage, with deposition of calcium oxalate in the lumen of the renal tubules.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 126.1
  2. Boiling point (760 mm Hg): Sublimes at 149 – 160 C (300 – 320 F) with partial decomposition
  3. Specific gravity (water = 1): 1.5
  4. Vapor density (air = 1 at boiling point of oxalic acid): 4.3
  5. Melting point: 101.5 C (215 F)
  6. Vapor pressure at 20 C (68 F): Less than 0.001 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 10
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with silver compounds may form explosive silver oxalate salt.
  3. Hazardous decomposition products: Toxic gases and vapors (such as formic acid and carbon monoxide) may be released in a fire involving oxalic acid.
  4. Special precautions: None
- **Flammability**
  1. Flash point: None by standard tests
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Water spray, dry chemical, or carbon dioxide
- **Warning properties**

Grant reports that "oxalic acid, a crystalline solid, readily soluble in water, has caused burns of the human eye in a few instances when solutions accidentally came in contact with the eye. The injury has been epithelial, and recovery has been prompt, the epithelium regenerating usually within two days . . . ." Grant observed that the application of a 5% solution for 30 seconds to rabbit eyes caused "coagulation of the epithelium, but the cornea recovered within six days." Since oxalic acid is readily soluble in water, the dust and mists of solutions of this material are treated as eye irritants for the purposes of this guideline. No quantitative information is available concerning the concentrations which produce eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for oxalic acid had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with oxalic acid or liquids containing oxalic acid.
- If employees' clothing may have become contaminated with oxalic acid or liquids containing oxalic acid, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with oxalic acid should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of oxalic acid from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the oxalic acid, the person performing the operation should be informed of oxalic acid's hazardous properties.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of oxalic acid or liquids containing oxalic acid contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to oxalic acid or liquids containing oxalic acid, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with oxalic acid should be promptly washed or showered to remove any oxalic acid.
- Eating and smoking should not be permitted in areas where oxalic acid or liquids containing oxalic acid are handled, processed, or stored.
- Employees who handle oxalic acid or liquids containing oxalic acid should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to oxalic acid may occur and control methods which may be effective in each case:

Operation	Controls
Use in metal cleaning and polishing operations for automobile radiators, boilers, and railroad cars to remove carbonaceous deposits from steel	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in textile cleaning and bleaching operations for rust, ink, and stain; bleaching of cotton and other fabrics; removal of discoloration from bleeding dyes; use as a sour in treatment of woolen and other piece goods; use in stripping and finishing operations in textile manufacture	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in bleaching and tanning of hides in leather manufacture	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during miscellaneous bleaching operations of wood, rosin, and cork	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of household and industrial cleaning and bleaching agents for metal and wood cleaning, cleaning preparations, disinfectants, and wax and grease removal	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in metallurgical processing of tin and extraction and purification of rare earth and actinide metals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in synthesis of other chemicals for manufacture of dyes, blue-print photography, and acids and starch hydrolysis	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in extraction and purification operations for chemicals, natural gums, and tall oil	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in lithography and photoengraving operations; use as an analytical reagent; use in manufacture of inks and lacquers; and in synthesis of pharmaceuticals	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If oxalic acid or liquids containing oxalic acid get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If oxalic acid or liquids containing oxalic acid get on the skin, promptly flush the contaminated skin with water. If oxalic acid or liquids containing oxalic acid penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of oxalic acid, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration.

Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When oxalic acid or liquids containing oxalic acid have been swallowed and the person is conscious, give the person large quantities of water immediately to dilute the oxalic acid. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If oxalic acid is spilled, the following steps should be taken:

1. Ventilate area of spill.

2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Oxalic acid may be disposed of:

1. By making packages of oxalic acid in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving oxalic acid in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Oxalic Acid," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hooker Chemical Company: *Material Safety Data Sheet – Oxalic Acid*, Industrial Chemicals Division, Niagara Falls, New York, 1972.

• Howard, C.: "Chronic Poisonining by Oxalic Acid," *Journal of Industrial Hygiene*, 14(8), pp. 283-90, 1932.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Klauder, J. V., et al.: "Industrial Uses of Fluorine and Oxalic Acid Compounds," *Archives of Industrial Health*, 12:412, 1955.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR OXALIC ACID

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Oxygen Difluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: OF_2
- Synonyms: Difluorine monoxide; fluorine monoxide
- Appearance and odor: Colorless gas with a foul odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for oxygen difluoride is 0.05 part of oxygen difluoride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.1 milligram of oxygen difluoride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Oxygen difluoride can affect the body if it is inhaled or if strong concentrations of oxygen difluoride gas contact the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation of oxygen difluoride has produced severe headaches in humans. Although there are no reports regarding the effects of exposure to this chemical on the eyes or skin of humans, it would be expected that contact of the gas under pressure with the eyes or skin would cause burns. In animal experiments, inhalation of oxygen difluoride has caused tearing, shortness of breath, muscular weakness, vomiting, severe breathing difficulties (which are sometimes delayed in onset), and death.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to oxygen difluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to oxygen difluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the lungs and eyes should be stressed.

—14" x 17" chest roentgenogram: Oxygen difluoride causes lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Oxygen difluoride is a severe pulmonary irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Oxygen difluoride gas is a severe respiratory irritant. In monkeys and dogs, the LC50 was 26 ppm for 60 minutes; signs of toxicity were lacrimation, dyspnea, muscular weakness, and vomiting; at autopsy, massive pulmonary edema and hemorrhage were observed. In mice, exposure to a low concentration (1 ppm for 60 minutes) produced tolerance to subsequent exposures 8 days later at levels which would otherwise have been fatal (4.25 ppm for 60 minutes). In humans, inhalation of the gas at fractions of a ppm produced intractable headache. Although there are no reports of effects on the eyes or skin of humans, it would be expected that

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

the gas under pressure impinging upon the eyes or skin would produce serious burns.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 54
2. Boiling point (760 mm Hg): −145 C (−229 F)
3. Specific gravity (water = 1): 1.5 (liquid at boiling point)
4. Vapor density (air = 1 at boiling point of oxygen difluoride): 1.86
5. Melting point: −224 C (−371 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): 0.02 (reacts slowly)
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Temperatures greater than 250 C (482 F) will cause oxygen difluoride to decompose and cause pressure increases in cylinders.
2. Incompatibilities: Contact with all combustible materials, chlorine, bromine, iodine, platinum, and many other metals, metal oxides, and moist air may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen fluoride and carbon monoxide) may be released when oxygen difluoride decomposes.
4. Special precautions: Oxygen difluoride will attack some forms of plastics, rubber, and coatings. See 29 CFR 1910.101 for specific regulations on storage of compressed gas cylinders.

- **Flammability**

1. Not combustible, but strong oxidizing agent

- **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that "the odor of oxygen difluoride can be detected by some persons at 0.1 ppm and by most at 0.5 ppm. The odor, however, may not be relied upon for warning purposes, as it is not characteristic and because olfactory fatigue develops rapidly."
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "no signs of irritation of the external mucosa of the eye were observed in rats subjected to the lethal exposure of 15 ppm oxygen difluoride for 15 minutes."
3. Evaluation of Warning Properties: Since the *Hygienic Guide* points out that "olfactory fatigue develops rapidly" upon exposure to oxygen difluoride, and since no other quantitative information is available relating its warning properties to air concentrations, this gas is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for oxygen difluoride had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to oxygen difluoride may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during use as an oxidizer in rocket propellants	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If strong concentrations of oxygen difluoride gas get into the eyes, wash eyes immediately with large

amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately.

• **Skin Exposure**

If strong concentrations of oxygen difluoride gas get on the skin, immediately wash the skin with large quantities of water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of oxygen difluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If oxygen difluoride is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty with a mixed solution of caustic soda and slaked lime.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Oxygen Difluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Oxygen Difluoride," *Hygienic Guide Series*, Detroit, Michigan, 1967.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Davis, H. V.: "Acute Toxicity of Oxygen Difluoride," *Proceedings of the First Annual Conference on Environmental Toxicology*, AMRL-TR-70-102, Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio, pp. 329-340, 1970.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dibbell, D. G., et al.: "Hydrofluoric Acid Burns of the Hand," *Journal of Bone and Joint Surgery*, 52A:931-936, 1970.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Lester, D., and Adams, W. R.: "The Inhalational Toxicity of Oxygen Difluoride," *American Industrial Hygiene Association Journal*, 26:562-567, 1965.

RESPIRATORY PROTECTION FOR OXYGEN DIFLUORIDE

Condition	Minimum Respiratory Protection* Required Above 0.05 ppm
Gas Concentration	
0.5 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 0.5 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-oxidizable sorbents and providing protection against oxygen difluoride.*** Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of oxygen difluoride; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 0.5 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

***Oxygen difluoride is an strong oxidizer and should not come in contact with oxidizable materials. Some cartridges and canisters may contain oxidizable materials, such as activated charcoal, and therefore should not be used to provide protection against oxygen difluoride. Only non-oxidizable sorbents should be used.

Occupational Health Guideline for Ozone

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: O_3
- Synonyms: None
- Appearance and odor: Colorless gas with a sharp, characteristic odor; it can be smelled at concentrations below the permissible exposure level.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ozone is 0.1 part of ozone per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.2 milligram of ozone per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ozone affects the body by being inhaled or by irritating the eyes, nose, and throat.

- **Effects of overexposure**

When a person is exposed to very low concentrations of ozone for even a brief period of time, the person may notice a sharp, irritating odor. As the concentration of ozone increases, the ability to smell it may decrease. Irritation of the eyes, dryness of the nose and throat, and cough may be experienced. If the ozone concentration continues to rise, more severe symptoms may develop. These may include headache, upset stomach, or vomiting, pain or tightness in the chest, shortness of breath or tiredness, which may last for several days to weeks. Finally, with higher levels of exposure, the lungs may be damaged and death may occur.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ozone.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ozone at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the heart and lungs should be stressed.

—14" x 17" chest roentgenogram: Ozone may cause lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Ozone is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

Ozone is extremely irritating to the upper and lower respiratory tract. The characteristic odor is readily detectable at low concentrations (0.01 ppm to 0.05 ppm). Ozone produces local irritation of the eyes and mucous membranes and may cause pulmonary edema at high exposure. Systemically, ozone has been reported to mimic the effects of ionizing radiation, and may cause damage to chromosomal structures. A partial tolerance appears to develop with repeated exposures. Although most effects are acute, the possibility of chronic lung impairment should be considered, based upon animal experimentation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1. Molecular weight: 48
2. Boiling point (760 mm Hg): −112 C (−169.6 F)
3. Specific gravity (water = 1): Not applicable
4. Vapor density (air = 1 at boiling point of ozone): 1.65
5. Melting point: −192 C (−313 F)
6. Vapor pressure at 20 C (68 F): Not applicable
7. Solubility in water, g/100 g water at 20 C (68 F): 0.00003 (3 ppm)
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Ozone spontaneously decomposes under all ordinary conditions, so that it is not encountered except in the immediate vicinity of where it was formed. The decomposition is speeded by solid surfaces and by many chemical substances.
2. Incompatibilities: Ozone is a powerful oxidizing agent and reacts with all oxidizable materials, both organic and inorganic. Some reaction products are highly explosive.
3. Hazardous decomposition products: None
4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: Not applicable
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Use large amounts of water spray.

• **Warning properties**

1. Odor Threshold: Both Summer and May report an odor threshold for ozone of 0.1 ppm.
2. Irritation Levels: Grant reports that "at concentrations greater than 1 ppm in air, ozone has been found irritating to the eyes and nose and injurious to the respiratory tract. Concentrations of 2 to 3.7 ppm caused sensation of irritation to normal human eyes within 6 minutes."
3. Evaluation of Warning Properties: Since the odor threshold of ozone is at the permissible exposure limit, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of ozone in an impinger containing potassium iodide in sodium hydroxide, followed by treatment with phosphoric-sulfamic acid reagent, and spectrophotometric analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure ozone may be used. An analytical method for ozone is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to ozone may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during welding operations with inert gas-shielded arc welding devices	Local exhaust ventilation; canister respirator; shielding (to block rays)
Liberation during welding operations with argon-shielded, bare-wire arc welding (especially stainless steel, aluminum, and aluminum alloy containing silicon)	Large-volume local exhaust; general dilution ventilation; direct fresh air supply; shielding (to block rays)
Liberation during arc welding operations in confined spaces	Direct fresh air supply
Liberation during production of ozone	Process enclosure; local exhaust ventilation

Operation	Controls
Liberation during oxidizing process of fine organic chemicals production (primarily ozolaic acid)	Process enclosure; local exhaust ventilation
Liberation during operations involving high-intensity ultraviolet light (plasma torch operations, glass blowing, hot metal operations, photoengraving operations, and use of mercury vapor lamps, direct copying machines, and projecting equipment)	Process enclosure; local exhaust ventilation; general dilution ventilation
Liberation during operations involving high-voltage electrical equipment (spectrographic and fluorometric apparatus, electroplating operations, high-volt linear accelerators, and electrostatic precipitators)	Local exhaust ventilation
Liberation during operations involving ozonizing process in treatment of water, industrial waste, and sewage; during air purification	Local exhaust ventilation; process enclosure; respiratory protective equipment
Liberation during drilling, cutting, and welding operations utilizing laser radiation	Local exhaust or general dilution ventilation
Liberaton during bleaching operations (textiles, paper, pulp, waxes, starch, sugar, teflon, and synthetic fibers); during refining of mineral oils and their derivatives; during processing of perfumes, vanilin, amd camphor; during aging and drying operations (wood, wines, whiskies, varnishes, and printing inks)	Process enclosure; local exhaust ventilation
Liberation during food preserving operations for mold and bacteria control in food storage and deodorization	Exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If ozone gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible.

- **Breathing**

If a person breathes in large amounts of ozone, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. When breathing is difficult, properly trained personnel may assist the affected person by administering 100% oxygen. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.
- If ozone is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas.

REFERENCES

• American Industrial Hygiene Association: "Ozone," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hallett, W.: "Effect of Ozone and Cigarette Smoke on Lung Function," *Archives of Environmental Health*, 17:295-306, 1965.

• Jaffe, L. S.: "The Biological Effects of Ozone on Man and Animals," *American Industrial Hygiene Association Journal*, pp. 267-277, May-June 1967.

• King, M. E.: "Toxicity of Ozone," *Industrial Medicine and Surgery*, 32:93-94, 1963.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stokinger, H. E.: "Ozone Toxicology," *Archives of Environmental Health*, 10:517-519, 1965.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

1009

RESPIRATORY PROTECTION FOR OZONE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Vapor Concentration	
1 ppm or less	Any chemical cartridge respirator with a cartridge(s) containing non-oxidizable sorbents and providing protection against ozone. Any supplied-air respirator. Any self-contained breathing apparatus.
5 ppm or less	A chemical cartridge respirator with a full facepiece and a cartridge(s) containing non-oxidizable sorbents and providing protection against ozone. A gas mask with a chin-style or a front- or back-mounted canister containing non-oxidizable sorbents and providing protection against ozone. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-oxidizable sorbents and providing protection against ozone. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Paraquat

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: (a) $C_{12}H_{14}N_2Cl_2$; (b) $C_{12}H_{14}N_2(CH_3SO_4)_2$
- Synonyms: (a) 1,1'-dimethyl-4,4'-bipyridinium dichloride; (b) 1,1'-dimethyl-4,4'-bipyridinium bis (methosulfate)
- Appearance and odor: Odorless, colorless solid

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for paraquat is 0.5 milligram of paraquat per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for paraquat a Threshold Limit Value of 0.1 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Paraquat can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to paraquat may cause irritation of the eyes, nose, throat, and skin. It may also cause nose bleeding and abnormalities or loss of fingernails. Exposure to mixtures of paraquat and a related compound, diquat, may cause serious and permanent injury to the eyes. Swallowing paraquat may cause burning in the mouth and throat, nausea, vomiting, abdominal pain, diarrhea, heart, kidney, and lung damage, and liver damage with yellow jaundice.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to paraquat.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to paraquat at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory system, heart, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Paraquat causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Paraquat is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Urinalysis: Since kidney damage has been observed in humans exposed to paraquat, a urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Since liver damage has been observed in humans exposed to paraquat, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Paraquat as a mist or aerosol is an irritant of the eyes, mucous membranes, and skin. In rats exposed to aero-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1082

September 1978

sols of paraquat, the LC50 for 6 hours was 1 mg/m@3@; death was delayed and resulted from pulmonary hemorrhage and edema. In a study of 30 workers spraying paraquat over a 12 week period, approximately 50% of them had minor irritation of the eyes or nose; 1 worker had an episode of epistaxis. Of 296 spray operators with skin exposure described as gross and prolonged, 55 had damaged fingernails; the most common lesion was transverse white bands of discoloration, but loss of nail surface, transverse ridging, gross deformity of the nail plate, and loss of nails also occurred. Paraquat is commonly combined in commercial herbicides with diquat, a related compound; in several instances the commercial preparations splashed in the eyes have caused serious injury. There have been loss of corneal and conjunctival epithelium, mild iritis, and residual corneal scarring. In contrast, in the eye of a rabbit, one drop of a 50% aqueous solution of pure paraquat caused slow development of mild conjunctival inflammation, and pure diquat proved even less irritating. Presumably the surfactants present in the commercial preparations are responsible for the severe eye injuries in humans. The results from injection or ingestion of paraquat are in marked contrast to the irritant effects usually encountered from occupational exposure. Intraperitoneal injection or oral administration to rats at doses which caused delayed death resulted in a peculiar proliferative lesion in the lung; there was alveolar, perivascular, and peribronchial edema, with cellular proliferation into the alveolar walls resulting in large solid areas of the lung with no air-containing cavities. There are several reports of fatal accidental ingestion by humans; in 2 cases, one person ingested about 114 ml of a 20% solution, while the other was believed to have taken only a mouthful of the liquid, most of which was rejected immediately; the former died after 7 days and the latter after 15 days. Initial symptoms included burning in the mouth and throat, nausea, vomiting, and abdominal pain with diarrhea. After 2 to 3 days, signs of liver and kidney toxicity developed including jaundice, oliguria, and albuminuria; there were E.C.G. changes suggesting toxic myocarditis with conduction defects. Shortly before death there was respiratory distress; at autopsy, findings in the lung included hemorrhage, edema, and massive solid areas which were airless owing to fibroblastic proliferation in the alveolar walls and elsewhere. There is no evidence that inhalation or skin absorption causes the rapid progressive pulmonary fibrosis and injury to the heart, liver, and kidneys occurring from ingestion.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: (a) 257.2; (b) 408
2. Boiling point (760 mm Hg): Decomposes at 175–180 C (347–356 F)
3. Specific gravity (water = 1): Data not available
4. Vapor density (air = 1 at boiling point of paraquat): Not applicable
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Very soluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, oxides of nitrogen and sulfur, and carbon monoxide) may be released when paraquat decomposes.
4. Special precautions: None

- **Flammability**

1. Not combustible

- **Warning properties**

Grant states that "in tests on rabbit eyes pure paraquat at 50% concentration caused only mild superficial inflammation, developing in twelve hours and clearing in two to four days with no damage to the cornea."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for paraquat is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforce-

ment and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with paraquat or solutions containing paraquat, where skin contact may occur.

• Clothing contaminated with paraquat should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of paraquat from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the paraquat, the person performing the operation should be informed of paraquat's hazardous properties.

• Where exposure of an employee's body to paraquat or solutions containing paraquat may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with paraquat should be removed immediately and not reworn until the paraquat is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where paraquat or solutions containing paraquat may contact the eyes.

SANITATION

• Skin that becomes contaminated with paraquat should be immediately washed or showered to remove any paraquat.

• Eating and smoking should not be permitted in areas where paraquat or solutions containing paraquat are handled, processed, or stored.

• Employees who handle paraquat or solutions containing paraquat should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to paraquat may occur and control methods which may be effective in each case:

Operation	Controls
Use as an agricultural herbicide, desiccant, defoliation agent during pre-harvest; use as an herbicide for non-agricultural purposes on highway margins, around commercial buildings; use to control aquatic weeds	Personal protective equipment
Manufacture, formulation, and processing of paraquat and aqueous solutions of the salts	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If paraquat or solutions containing paraquat get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If paraquat or solutions containing paraquat get on the skin, immediately flush the contaminated skin with water. If paraquat or solutions containing paraquat soak through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of paraquat, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When paraquat or solutions containing paraquat have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If paraquat is spilled, the following steps should be taken:

1. Ventilate area of spill.

2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing paraquat should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Paraquat may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Paraquat," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Bullivant, C. M.: "Accidental Poisoning by Paraquat: Report of Two Cases in Man," *British Medical Journal*, 1:1272-1273, 1966.

• Cant, J. S. and Lewis, D. R. H.: "Ocular Damage Due to Paraquat and Diquat," *British Medical Journal, 2:224, 1968.*

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Clark, D. G., et al.: "The Toxicity of Paraquat," *British Journal of Industrial Medicine*, 23:126-132, 1966.

• Gage, J. C.: "Toxicity of Paraquat and Diquat Aerosols Generated by a Size-selective Cyclone: Effect of Particle Size Distribution," *British Journal of Industrial Medicine*, 25:304-314, 1968.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hearn, C. E. D., and Keir, W.: "Nail Damage in Spray Operators Exposed to Paraquat," *British Journal of Industrial Medicine*, 28:399-403, 1971.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

• Swan, A. A. B.: "Exposure of Spray Operators to Paraquat," *British Journal of Industrial Medicine*, 26:322-329, 1969.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• Toner, P. G., et al.: "Fine Structure of the Lung Lesion in a Case of Paraquat Poisoning," *Journal of Pathology*, 102:182-185, 1970.

RESPIRATORY PROTECTION FOR PARAQUAT

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate Concentration	
1.5 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 1.5 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of paraquat; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 1.5 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Parathion

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_2H_5O)_2$ $PSOC_6H_4NO_2$
- Synonyms: O,O-Diethyl-O,p-nitrophenyl phosphorothioate; ethyl parathion
- Appearance and odor: Yellow to dark brown liquid with a characteristic odor, like garlic.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for parathion is 0.1 milligram of parathion per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be reduced to 0.05 mg/m^3. The NIOSH Criteria Document for Parathion should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Parathion can affect the body if it is inhaled, comes in contact with the eyes or skin, or if swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: After inhalation of parathion, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of vision, tearing, runny nose, headache, and watering of the mouth. After swallowing parathion, loss of appetite, nausea, vomiting, abdominal cramps and diarrhea may appear within two hours. After skin absorption, sweating and twitching in the area of absorption may occur, usually within 15 minutes to four hours. With severe intoxication by all routes, in addition to the above symptoms, weakness, generalized twitching, and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, irregular or slow heartbeat, convulsions and coma may occur.

2. Long-term Exposure: Repeated exposure to parathion may make a person more susceptible to the effects of this and related chemicals. Repeated exposure to concentrations which are too small to produce symptoms after a single exposure may result in the onset of symptoms.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to parathion.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to parathion at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system, eyes, and attention to the cholinesterase levels in the blood should be stressed. The skin should be examined for evidence of chronic disorders.

—Cholinesterase determination: Parathion causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the serum and erythrocytes should be determined by using

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

medically acceptable biochemical tests prior to any new period of exposure.

2. *Periodic Medical Examinction:* The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determination. This test should be performed at four-week intervals, except for those employees in areas which may involve intense exposure, for whom the test should be repeated weekly. If any employee works with parathion more than 12 hours per day, he should be tested every 3 weeks. Employees should also be tested at any time overexposure is suspected or signs or symptoms of toxicity appear. Any employee having a 30 to 40% decrease in cholinesterase should be removed from exposure and placed under medical observation.

• **Summary of toxicology**

Parathion is an anticholinesterase agent; absorption may occur from inhalation of the vapor or mist, from skin absorption of the liquid, or from ingestion. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nervous system and skeletal and smooth muscle secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms may occur promptly or may be delayed for up to 12 hours. After inhalation respiratory and ocular effects are the first to appear, , often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects, such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption, localized sweating and muscular fasciculations in the immediate area occur usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures, and is increased by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels, and cardiac irregularities including complete heart block may occur; these effects may sometimes be reversed by establishing adequate pulmonary ventilation. Complete symptomatic recovery usually occurs within 1 week; increased susceptibility to the effects of anticholinesterase agents persists for weeks after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects. A few drops of technical parathion in the eyes of animals have produced lacrimation and moderate conjunctivitis. The minimum lethal oral dose of parathion for humans has been estimated to range from less than 10 mg up to 120 mg. In a study of 115 workers exposed to parathion under varying conditions, the majority excreted significant amounts of p-nitrophenol (a metabolite of parathion) in the urine, while only those with heavier exposures had a measurable decrease in blood cholinesterase.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 291.3
2. Boiling point (760 mm Hg): 375 C (707 F) (calculated)
3. Specific gravity (water = 1): 1.27
4. Vapor density (air = 1 at boiling point of parathion): Not applicable
5. Melting point: 6 C (43 F) (pure grade); 0 C (32 F) (technical grade)
6. Vapor pressure at 20 C (68 F): 0.0004 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): .00002
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Temperatures above 100 C (212 F) may cause decomposition so that containers burst.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen, phosphorus, sulfur, and carbon monoxide) may be released when parathion decomposes.
4. Special precautions: Parathion will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: The odor threshold of parathion is 0.04 ppm (American Society of Testing Materials Bulletin).
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "a few drops of technical parathion in animals has produced immediate blinking, lacrimation, and moderate conjunctivitis. Pupil constriction was also observed, with a return to normal size and reaction the following day. Eye contact with 1% aqueous suspensions of 15% wettable powders did not show evidence of irritation or other obvious reaction."
3. Evaluation of Warning Properties: Since the odor threshold of parathion is so low, parathion is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• General

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• Method

Sampling and analyses may be performed by collection of parathion using a filter with subsequent recovery with iso-octane and gas chromatographic analysis. A detailed analytical method for parathion may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22161, under the title "NIOSH Analytical Methods for Set T" (order number PB 262 404).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with parathion.

• If employees' clothing has had any possibility of being contaminated with parathion, employees should change into uncontaminated clothing before leaving the work premises.

• Where there is any possibility of exposure of an employee's body to parathion, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with parathion should be removed immediately and not reworn until the parathion is removed from the clothing.

• Clothing which has had any possibility of being contaminated with parathion should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of parathion from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the parathion, the person performing the operation should be informed of parathion's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid parathion contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to parathion, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with parathion should be immediately washed or showered with soap or mild detergent and water to remove any parathion.

• Workers subject to skin contact with parathion should wash with soap or mild detergent and water any areas of the body which may have contacted parathion at the end of each work day.

• Eating and smoking should not be permitted in areas where parathion is handled, processed, or stored.

• Employees who handle parathion should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to parathion may occur and control methods which may be effective in each case:

Operation	Controls
Application as a pesticide on agricultural crops, vegetables and ornamentals and on agricultural premises	Personal protective equipment
Formulation for use as an insecticide	Process enclosure; personal protective equipment
Manufacture of parathion	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If parathion or parathion mists get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If parathion or parathion mists get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If parathion or parathion mists penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of parathion, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When parathion has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If parathion is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation, or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Parathion may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Parathion," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Parathion," *Hygienic Guide Series*, Detroit, Michigan, 1969.

• "American Society of Testing Materials Bulletin," *Journal of American Water Works Association*, 57:1016, 1965.

• Arterberry, J. D., et al.: "Exposure to Parathion – Measurement by Blood Cholinesterase Level and Urinary p-Nitrophenol Excretion," *Archives of Environmental Health*, 3:476-485, 1961.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• *Hygienic Information Guide No. 27 – Parathion*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koelle, G. B. (ed.): "Cholinesterases and Anticholinesterase Agents," Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Parathion*, HEW Publication No. (NIOSH) 76-190, GPO No. 017-033-00195-2, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch

Agriculture, Canada, 1973.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR PARATHION

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate or Vapor Concentration	
1 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust, fume, and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
20 mg/m³ or less	A powered air-purifying respirator with an organic vapor cartridge and high efficiency particulate filter, including pesticide respirators which meet the requirements of this class. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 20 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of parathion; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 20 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Pentaborane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: B_5H_9
- Synonyms: Stable pentaborane, pentaboron anhydride
- Appearance and odor: Colorless liquid with a strong, pungent odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for pentaborane is 0.005 part of pentaborane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.01 milligram of pentaborane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Pentaborane can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to low concentrations of pentaborane may cause lightheadedness, drowsiness, nervousness, lack of coordination, and tremors. The onset of these symptoms may be delayed as long as 48 hours. After exposure to higher concentrations, the onset of symptoms may be prompt and may include the above symptoms plus spasms of the face, neck, arms, legs, and abdomen. After severe exposure, convulsions may occur. In animals impairment of liver and kidney function has been reported. Also, in animals, the vapor has caused severe irritation of the eyes and the liquid has caused inflammation of the skin.

2. Long-term Exposure: Prolonged exposure to low concentrations of pentaborane may cause headache, fatigue, drowsiness, the inability to concentrate, and the lack of coordination.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to pentaborane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to pentaborane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of convulsive disorders would be expected to be at increased risk from exposure. Examination of the nervous system, liver, and kidneys should be stressed. The skin and eyes should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Pentaborane vapor affects the nervous system and causes signs of both hyperexcitability and narcosis. Exposure of rats to 10 ppm for 2 hours was fatal; effects included weakness, incoordination, corneal opacities, tremors, and convulsions; other animal studies have indicated that kidney and liver damage may occur. In humans, the onset of symptoms may be delayed up to 48 hours after exposure; dizziness, headache, and drowsiness are common; other symptoms include fatigue, incoordination, and tremor. After exposure to higher concentrations, the onset of symptoms may be prompt and include tonic spasms of the muscles of the face,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

neck, abdomen, and extremities; after severe exposures, convulsive seizures may occur. The results of exposure to animals for 60 minutes are: 8 ppm, some decrement in performance of learned tasks and slight signs of toxicity; 15 ppm, convulsions; 30 ppm, convulsions and death. Severe irritation and corneal opacity of the eyes of test animals occurred from exposure to the vapor; the liquid on the skin of animals caused acute inflammation.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 63.1
2. Boiling point (760 mm Hg): 58.4 C (137 F)
3. Specific gravity (water = 1): 0.63
4. Vapor density (air = 1 at boiling point of pentaborane): 2.2
5. Melting point: −47 C (−52 F)
6. Vapor pressure at 20 C (68 F): 171 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts slowly to form hydrogen gas
8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Temperatures above 150 C (302 F) cause decomposition and pressure buildup in containers.
2. Incompatibilities: Pentaborane reacts with oxidizers to form highly explosive mixtures. Contact with halogens or halogenated compounds may cause explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as boron acids) may be released in a fire involving pentaborane.
4. Special precautions: Pentaborane will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 30 C (86 F) (closed cup when pure); impure material ignites spontaneously in air
2. Autoignition temperature: 35 C (95 F) (impure material ignites at lower temperatures)
3. Flammable limits in air, % by volume: Lower: 0.42; Upper: Not obtainable
4. Extinguishant: Let small fires burn. Water spray, foam, dry chemical, and carbon dioxide will decrease intensity of large fires. Do not use halogenated extinguishing fluids.

• **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that pentaborane has a characteristic odor, but that it is "not a reliable index of exposure." According to a technical bulletin from Callery Chemical Company, the median detectable concentration of pentaborane by odor is 2.5 mg/m@3@, which is many times greater than the permissible exposure limit.
2. Eye Irritation Level: Pentaborane vapor is not known to be an eye irritant.
3. Evaluation of Warning Properties: Since the odor threshold is many times greater than the permissible exposure limit of pentaborane, and since there is no other quantitative information relating warning properties to air concentrations of pentaborane, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for pentaborane had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid pentaborane, where skin contact may occur.

• Clothing wet with liquid pentaborane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of pentaborane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the pentaborane, the person performing the operation should be informed of pentaborane's hazardous properties.

• Where exposure of an employee's body to liquid pentaborane may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
• Any clothing which becomes wet with liquid pentaborane should be removed immediately and not reworn until the pentaborane is removed from the clothing.
• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid pentaborane contacting the eyes.
• Where there is any possibility that employees' eyes may be exposed to liquid pentaborane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes wet with liquid pentaborane should be immediately washed or showered with soap or mild detergent and water to remove any pentaborane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to pentaborane may occur and control methods which may be effective in each case:

Operation	Controls
Use in chemical research as jet and rocket fuels, catalysts, corrosion inhibitor-fluxing agents, and oxygen scavengers	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a chemical intermediate (higher boranes, alkyl boranes— ethyl pentaborane and various hydrides); these are not industrial chemicals	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If liquid pentaborane or strong concentrations of pentaborane vapor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention promptly. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid pentaborane or strong concentrations of pentaborane vapor get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid pentaborane or strong concentrations of pentaborane vapor penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of pentaborane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When liquid pentaborane has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If pentaborane is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Pentaborane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of pentaborane vapors are permitted.
• Waste disposal method:
Pentaborane may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Pentaborane," *Documentation of the*

ly in rats produced temporary impairment of liver samples. Several short-time interval samples (up to 30

Threshold Limit Values for Substances in Workroom Air (3rd ed., 2nd printing), Cincinnati, 1974.
• American Industrial Hygiene Association: "Pentaborane," *Hygienic Guide Series*, Detroit, Michigan, 1958.
• American Industrial Hygiene Association: "Pentaborane: Emergency Exposure Limits," *American Industrial HyAssociation Journal*, 27:193-195, 1966.
• American Industrial Hygiene Association: "Pentaborane-9," *Hygienic Guide Series*, Detroit, Michigan, 1966.
• Callery Chemical Company: *Technical Bulletin CT-1300 – Pentaborane.*
• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
• Holzmann, R. T. (ed.): *Production of the Boranes and Related Research*, Academic Press, New York, 1967.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Krackow, E. H.: "Toxicity and Health Hazards of Boron Hydrides," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 8:335-339, 1953.
• Lowe, H. J., and Freeman, G.: "Boron Hydride (Borane) Intoxication in Man," *A.M.A. Archives of Industrial Health*, 16:523-533, 1957.
• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-84, Boron Hydrides*, Washington, D.C., 1967.
• Roush, G., Jr.: "The Toxicology of the Boranes," *Journal of Occupational Medicine*, 1:46-52, January 195
• Rozendaal, H. M.: "Clinical Observations on the Toxicology of Boron Hydrides," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 4:257-260, 1951.
• Schecter, P.: "Toxicity of High-Energy Fuels," *A.M.A. Archives of Industrial Health*, Vol. 17:362-366, M
• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.
• Weir, F. W., and Meyers, F. H.: "The Similar Pharmacologic Effects of Pentaborane, Decaborane and Reserpine," *Industrial Medicine and Surgery*, 35:696-701, 1966.

• Any clothing which becomes wet with liquid pentane

Operation

Controls

RESPIRATORY PROTECTION FOR PENTABORANE

Condition	Minimum Respiratory Protection* Required Above 0.005 ppm
Vapor Concentration	
0.05 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
0.25 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
3 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 3 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against pentaborane. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Pentachloronaphthalene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_3Cl_5$
- Synonyms: Halowax 1013
- Appearance and odor: Pale, yellow solid with an aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for pentachloronaphthalene is 0.5 milligram of pentachloronaphthalene per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Pentachloronaphthalene can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. Every effort should be made to prevent skin, eye, oral, or inhalation contact with this material.

- **Effects of overexposure**

Overexposure to pentachloronaphthalene causes headache and dizziness. Prolonged overexposure to pentachloronaphthalene may cause an acne-like skin rash. It may also injure the liver, resulting in such effects as fatigue, dark urine, yellow jaundice, and possibly death.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to pentachloronaphthalene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to pentachloronaphthalene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Pentachloronaphthalene may cause liver damage. A profile of liver function should be performed by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Pentachloronaphthalene is a severe hepatic toxin, with marked effects upon the skin. While a solid at room temperature, the heated liquid produces a hazardous vapor. Rats exposed to the vapor of a mixture of hexa- and pentachloronaphthalene at average concentrations of 1.16 mg/m^3 for 16 hours daily up to 4-½ months showed definite liver injury, while 8.8 mg/m^3 produced some mortality and severe liver injury. The most striking human response to prolonged skin contact with the solid, or to shorter term inhalation of hot vapors, is chloracne. This is an acne-form skin eruption characterized by papules, large comedones and pustules, chiefly affecting the face, neck, arms, and legs. Pruritic erythematous and vasculoerythematous reactions have also been reported. Skin lesions are often accompanied by symptoms of systemic effects, including headache, vertigo, and anorexia. Liver damage characterized by toxic jaundice, which may progress to fatal hepatic necrosis, results from the inhalation of higher concentrations of the hot fumes of the molten substance. Skin absorption

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

1097

has been demonstrated in animals and is suspected in man.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 300.5
2. Boiling point (760 mm Hg): 327 to 371 C (620 to 700 F)
3. Specific gravity (water = 1): 1.67
4. Vapor density (air = 1 at boiling point of pentachloronaphthalene): 10.4
5. Melting point: 120 C (248 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide and toxic chloride fumes) may be released in a fire involving pentachloronaphthalene.
4. Special precautions: None

- **Flammability**

1. Not combustible

- **Warning properties**

1. Odor Threshold: No quantitative information is available.
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "eye injury has not proved to be troublesome with the chloronaphthalenes;" nonetheless, they specifically state that "if respirators are used, they should be of the full-facepiece type approved by the U. S. Bureau of Mines for disperoids or organic vapors."
3. Evaluation of Warning Properties: There are no quantitative data relating warning properties to air concentrations of pentachloronaphthalene; therefore, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent ...at inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of pentachloronaphthalene with a filter and a bubbler containing iso-octane, followed by gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure pentachloronaphthalene may be used. An analytical method for pentachloronaphthalene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with molten pentachloronaphthalene.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid pentachloronaphthalene or liquids containing pentachloronaphthalene.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with pentachloronaphthalene vapors from the heated material.
- If employees' clothing may have become contaminated with solid pentachloronaphthalene, employees

should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with pentachloronaphthalene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of pentachloronaphthalene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the pentachloronaphthalene, the person performing the operation should be informed of pentachloronaphthalene's hazardous properties.

• Non-impervious clothing which becomes contaminated with molten pentachloronaphthalene should be removed immediately and not reworn until the pentachloronaphthalene is removed from the clothing.

• Non-impervious clothing which becomes contaminated with solid pentachloronaphthalene or liquids containing pentachloronaphthalene should be removed promptly and not reworn until the pentachloronaphthalene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of molten pentachloronaphthalene contacting the eyes.

• Employees should be provided with and required to use splash-proof safety goggles where solid pentachloronaphthalene or liquids containing pentachloronaphthalene may contact the eyes.

SANITATION

• Workers subject to skin contact with pentachloronaphthalene should wash with soap or mild detergent and water any areas of the body which may have contacted pentachloronaphthalene at the end of each work day.

• Skin that becomes contaminated with pentachloronaphthalene should be promptly washed or showered with soap or mild detergent and water to remove any pentachloronaphthalene.

• Eating and smoking should not be permitted in areas where solid pentachloronaphthalene is handled, processed, or stored.

• Employees who handle solid pentachloronaphthalene or liquids containing pentachloronaphthalene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to pentachloronaphthalene may occur and control methods which may be effective in each case:

Operation	Controls
Use during manufacture of electric equipment as an insulating material; pouring molten solvent or finely ground solid materials; dipping; peeling and covering insulated cable with fabric	Local exhaust ventilation; general dilution with intake and exhaust fans; personal protective equipment
Liberation from use of electrical equipment insulated with octachloronaphthalene/ pentachloronaphthalene	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an inert compound of resins or polymers for coating or impregnating textiles, wood, and paper to impart flame resistance, water proofness, and fungicidal and insecticidal properties	Process enclosure; local exhaust ventilation; general dilution with intake and exhaust fans; personal protective equipment
Use as an additive for cutting oil in various operations performed on metals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an additive to special lubricants in crankcase oil, lubricants for farm machinery, and extreme-pressure lubricants	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solid pentachloronaphthalene or liquids containing pentachloronaphthalene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. If molten pentachloronaphthalene gets into the eyes, immediately flush the eyes with large amounts of water to remove heat. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If non-impervious clothing becomes contaminated with pentachloronaphthalene, remove and clean the clothing before wearing again. If non-impervious clothing becomes heavily contaminated, it should be destroyed. If solid pentachloronaphthalene or liquids containing

pentachloronaphthalene get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If irritation persists after washing, get medical attention. If molten pentachloronaphthalene gets on the skin or non-impervious clothing, immediately flush the affected area with large amounts of water to remove heat. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of pentachloronaphthalene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When pentachloronaphthalene has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If pentachloronaphthalene is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquids containing pentachloronaphthalene should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Pentachloronaphthalene may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Pentachloronaphthalene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chloronaphthalenes," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Greenburg, L., et al.: "The Systemic Effects Resulting from Exposure to Certain Chlorinated Hydrocarbons," *Journal of Industrial Hygiene and Toxicology*, 21:29-38, 1939.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kleinfeld, M., et al.: "Clinical Effects of Chlorinated Naphthalene Exposure," *Journal of Occupational Medicine*, 14:377-379, 1972.

• Koppers Corporation: *Material Safety Data Sheet - Pentachloronaphthalene.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR PENTACHLORONAPHTHALENE

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any supplied-air respirator.** Any self-contained breathing apparatus.**
25 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
1000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Pentachlorophenol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_6Cl_5OH
- Synonyms: PCP; penta
- Appearance and odor: Light brown solid with a pungent odor when hot.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for pentachlorophenol is 0.5 milligram of pentachlorophenol per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Pentachlorophenol can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to pentachlorophenol may cause irritation of the eyes and respiratory tract. Bronchitis has been reported to occur. Systemic effects from either a large exposure or repeated smaller exposures include weakness, loss of appetite, nausea, vomiting, shortness of breath, chest pain, excessive sweating, headache, and dizziness. In fatal cases the temperature is often very high and death may occur as early as three hours after the onset of symptoms. The risk of serious intoxication is greater in hot weather. Persons with decreased liver or kidney functions are more susceptible to poisoning from this chemical. Repeated exposure to pentachlorophenol may cause an acne-like skin rash and liver damage. Commercial pentachlorophenol may be contaminated with dioxin compounds which are much more toxic than pentachlorophenol.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to pentachlorophenol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to pentachlorophenol at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the cardiovascular system, eyes, upper respiratory tract, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders. Analysis of the urine for pentachlorophenol may be helpful in estimating the extent of absorption.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Pentachlorophenol dust and mist cause irritation of the eyes and upper respiratory tract; absorption results in an increase in metabolic rate and hyperpyrexia; prolonged skin exposure causes an acneform dermatitis. Human exposure to dust or mist concentrations greater than 1 mg/m^3 causes pain in the nose and throat, violent sneezing, and cough; 0.3 mg/m^3 may cause some nose irritation; persons acclimated to pentachlorophenol can tolerate concentrations up to 2.4 mg/m^3. Pentachlorophenol readily penetrates the skin; systemic intoxication is cumulative and has been fatal. Intoxication is characterized by weakness, anorexia, weight loss, and profuse sweating; there also may be headache, dizziness, nausea, vomiting, dyspnea, and chest pain. In fatal cases, the body temperature is frequently extremely high and

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

1102

death has occurred as early as 3 hours after the onset of symptoms. The risk of serious intoxication is increased during hot weather; persons with impaired liver or kidney function are more susceptible to the effects of pentachlorophenol. The dust, mist, and vapor cause eye irritation. Prolonged exposure of workers has caused an acneform dermatitis; 10 workers engaged in production of pentachlorophenol for 5 to 10 months developed a widely disseminated skin eruption characterized by small and large furuncles, brown pigmentation, and some cicatrization; 7 workers also developed severe bronchitis; all but 1 worker still showed signs of extensive acne more than a year after cessation of exposure, and 4 still complained of bronchitis. On the skin, solutions of pentachlorophenol as dilute as 1% may cause irritation if contact is repeated or prolonged.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 266.3
2. Boiling point (760 mm Hg): 311 C (592 F) (decomposes)
3. Specific gravity (water = 1): 2.0
4. Vapor density (air = 1 at boiling point of pentachlorophenol): Not applicable
5. Melting point: 182 – 190 C (360 – 374 F)
6. Vapor pressure at 20 C (68 F): 0.00017 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.002
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: None.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, chlorinated phenols, and carbon monoxide) may be released when pentachlorophenol decomposes.
4. Special precautions: None.

- **Flammability**

1. Not combustible

- **Warning properties**

1. Odor Threshold: The AIHA *Hygienic Guide* states that pentachlorophenol has a characteristic odor. No quantitative information is available, however, concerning the odor threshold of this substance.
2. Irritation Levels: The *Documentation of TLV's* states that "dusts are particularly irritating to the eyes and nose, in concentrations appreciably greater than 1 mg/m³, but some irritation of the nose may occur at 0.3 mg/m³. Hardened workers can tolerate up to 2.4 mg/m³."
3. Evaluation of Warning Properties: Through its irritant effects, pentachlorophenol can be detected within three times of the permissible exposure limit. For the purposes of this guideline, therefore, pentachlorophenol is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for pentachlorophenol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with pentachlorophenol or liquids containing pentachlorophenol.
- If employees' clothing has had any possibility of being contaminated with pentachlorophenol or liquids containing pentachlorophenol, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with pentachlorophenol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of pentachlorophenol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the pentachlorophenol, the person performing the operation should be informed of pentachlorophenol's hazardous properties.

• Where there is any possibility of exposure of an employee's body to pentachlorophenol or liquids containing pentachlorophenol, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with pentachlorophenol should be removed immediately and not reworn until the pentachlorophenol is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of pentachlorophenol or liquids containing pentachlorophenol contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to pentachlorophenol or liquids containing pentachlorophenol, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with pentachlorophenol should be immediately washed or showered with soap or mild detergent and water to remove any pentachlorophenol.

• Workers subject to skin contact with pentachlorophenol or liquids containing pentachlorophenol should wash with soap or mild detergent and water any areas of the body which may have contacted pentachlorophenol at the end of each work day.

• Eating and smoking should not be permitted in areas where pentachlorophenol or liquids containing pentachlorophenol are handled, processed, or stored.

• Employees who handle pentachlorophenol or liquids containing pentachlorophenol should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to pentachlorophenol may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of preservatives, pesticides, and fungicides	Process enclosure; local exhaust ventilation; personal protective equipment
Application as a preservative for wood, starch, paint, adhesives, leather, latex, and oils; use in slime-algae control; use as a pesticide, herbicide, and snail control agent	Personal protective equipment
Manufacture of pentachlorophenol	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If pentachlorophenol or liquids containing pentachlorophenol get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If pentachlorophenol or liquids containing pentachlorophenol get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If pentachlorophenol or liquids containing pentachlorophenol penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of pentachlorophenol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When pentachlorophenol or liquids containing pentachlorophenol have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency

rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If pentachlorophenol is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and depost in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing pentachlorophenol should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Pentachlorophenol may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Pentachlorophenol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Pentachlorophenol and Sodium Pentachlorophenate," *Hygienic GuideSeries*, Detroit, Michigan, 1970.

• Baader, E. W., and Bauer, H. J.: "Industrial Intoxication Due to Pentachlorophenol," *Industrial Medicine and Surgery*, 20:286-290, 1951.

• Bergner, H., et al.: "Industrial Pentachlorophenol Poisoning in Winnipeg," *Canadian Medical Association Journal*, 92:448-451, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saunders, Philadelphia, 1960.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

1105

RESPIRATORY PROTECTION FOR PENTACHLOROPHENOL

Condition	Minimum Respiratory Protection* Required Above 0.5 mg/m³
Particulate or Vapor Concentration	
2.5 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class.** Any supplied-air respirator.** Any self-contained breathing apparatus.**
25 mg/m³ or less	Any chemical cartridge respirator with a full facepiece, an organic vapor cartridge(s), and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust, fume, and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
150 mg/m³ or less	

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Pentane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_5H_{12}
- Synonyms: Normal pentane
- Appearance and odor: Colorless liquid with a gasoline-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for pentane is 1000 parts of pentane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2950 milligrams of pentane per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be reduced to 120 ppm (350 mg/m³) averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 610 ppm (1,800 mg/m³) averaged over a 15-minute period. The NIOSH Criteria Document for Alkanes should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Pentane can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to pentane may cause drowsiness and irritation of the eyes and nose. Greater exposure may cause unconsciousness and death.

2. Long-term Exposure: Prolonged overexposure may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to pentane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to pentane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central and peripheral nervous systems and the skin should be stressed.

—Skin disease: Pentane is a skin defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although pentane is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although pentane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of pentane might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: The aforementioned examinations should be performed on an annual basis.

- **Summary of toxicology**

Pentane vapor is a mild narcotic and mucous membrane irritant. Exposure to 90,000 to 120,000 ppm resulted in narcosis in animals in 5 to 6 minutes; 130,000 ppm was fatal, with respiratory arrest occurring within 5 minutes of the start of exposure. Pentane injected subcutaneous-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1107

ly in rats produced temporary impairment of liver function and moderate neutropenia. While other aliphatic hydrocarbons produce drowsiness and mild irritation of the eyes and nose in human subjects, no symptoms resulted from exposure to pentane vapor for 10 minutes at 5000 ppm. Repeated or prolonged skin contact results in drying and cracking due to defatting action. No chronic systemic effects have been reported in humans. Aspiration may cause chemical pneumonia.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 72.2
  2. Boiling point (760 mm Hg): 36 C (97 F)
  3. Specific gravity (water = 1): 0.63
  4. Vapor density (air = 1 at boiling point of pentane): 2.5
  5. Melting point: −129 C (−200 F)
  6. Vapor pressure at 20 C (68 F): 426 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.04
  8. Evaporation rate (butyl acetate = 1): 28.6
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving pentane.
  4. Special precautions: Pentane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: −49 C (−57 F) (closed cup)
  2. Autoignition temperature: 260 C (500 F)
  3. Flammable limits in air, % by volume: Lower: 1.5; Upper: 7.8
  4. Extinguishant: Foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold of 2.2 ppm. The *Hygienic Guide* states that "the odor threshold of pentane vapor is approximately the same as the recommended maximal concentration of 1000 ppm."
  2. Eye Irritation Level: Pentane is not a known eye irritant.
  3. Evaluation of Warning Properties: Since its odor threshold is at or below the permissible exposure limit, pentane is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of pentane. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of pentane vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure pentane may be used. An analytical method for pentane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid pentane.

• Any clothing which becomes wet with liquid pentane should be removed immediately and not reworn until the pentane is removed from the clothing.

• Clothing wet with liquid pentane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of pentane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the pentane, the person performing the operation should be informed of pentane's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where liquid pentane may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to pentane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes wet with liquid pentane should be promptly washed or showered with soap or mild detergent and water to remove any pentane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to pentane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a gasoline additive for automotive, aviation, and farm equipment	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in synthesis of amyl chlorides for intermediates in manufacture of paint and lacquer solvents, tube oil additives, hydraulic fluids, pesticides, paint removers, solvent extenders, and miscellaneous petrochemicals; use in synthesis of polychlorocyclopentanes as intermediates in manufacture of fire-resistant polyester resins and paints, dye intermediates, insecticides, and plasticizers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a blowing agent for polymeric foams	Local exhaust ventilation; general dilution ventilation
Use as a raw material in synthesis of olefins for synthetic rubber and other petrochemicals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in solvent extraction processes; use as a general laboratory solvent; use as a medium solvent for polymerization reactions	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a component of lighter fluids and blow-torch fuel	Local exhaust ventilation; general dilution ventilation
Use as a heat-exchange medium in manufacture of artificial ice; use in manufacture of low-temperature thermometers; use in manufacture of polystyrene beads for styrofoam production	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If pentane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If pentane gets on the skin, promptly wash the contaminated skin with water. If pentane soaks through the clothing, remove the clothing immediately and wash the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of pentane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If pentane has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If pentane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Pentane should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Pentane may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Pentane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Heptane," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• American Industrial Hygiene Association: "Hexane," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• American Industrial Hygiene Association: "Pentane," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Alkanes*, HEW Publication No. (NIOSH) 77-151, GPO No. 017-033-00213-4, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Swann, H. E., Jr., et al.: "Acute Inhalation Toxicology of Volatile Hydrocarbons," *American Industrial Hygiene Association Journal*, 35:511-518, 1974.

• Wirtschafter, Z. T., and Cronyn, M. W.: "Relative Hepatotoxicity: Pentane, Trichloroethylene, Benzene, Carbon Tetrachloride," *American Industrial Hygiene Association Journal*, 9:180-185, 1964.

RESPIRATORY PROTECTION FOR PENTANE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
5000 ppm or less	A gas mask with a chin-style or front- or back-mounted organic vapor canister. Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Perchloromethyl Mercaptan

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CCl_3SCl
- Synonyms: PMM; trichloromethylsulfur chloride; trichloromethanethiol; perchloromethanethiol
- Appearance and odor: Pale yellow, oily liquid with a foul-smelling, strong acrid odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for perchloromethyl mercaptan is 0.1 part of perchloromethyl mercaptan per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.8 milligram of perchloromethyl mercaptan per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Perchloromethyl mercaptan can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Inhalation of perchloromethyl mercaptan vapor may cause irritation of the eyes, nose, throat, and lungs as well as nausea. An exposure to this chemical by inhalation and skin contact has caused severe breathing difficulty and death. Liver and kidney damage also occurred following this exposure. The liquid splashed on the skin or in the eyes will cause irritation.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to perchloromethyl mercaptan.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to perchloromethyl mercaptan at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory tract, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney damage has been observed in humans exposed to perchloromethyl mercaptan, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—14" x 17" chest roentgenogram: Perchloromethyl mercaptan causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Perchloromethyl mercaptan is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—Liver function tests: Perchloromethyl mercaptan has been reported to cause liver damage in humans. A profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Perchloromethyl mercaptan vapor is a severe respiratory irritant and lacrimator. Mice and cats exposed for 15 minutes at 45 ppm died within 1 to 2 days from

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1112

September 1978

pulmonary edema; 3-hour exposures at 9 ppm killed 50% of mice; repeated exposures over 3 months at 1 ppm resulted in the death of some mice. Eye irritation begins at 10 mg/m^3 (1.3 ppm). Exposure at higher concentrations causes marked irritation of the eyes, throat, and bronchi, as well as nausea. Three chemical workers were observed following accidental exposures to perchloromethyl mercaptan; two survived episodes of pulmonary edema, while the third died after 36 hours. The fatality resulted from a spill of the liquid on clothing and floor with exposure to the vapor. At autopsy, there was necrotizing tracheitis, massive hemorrhagic pulmonary edema, marked toxic nephrosis, and vacuolization of centrolobular hepatic cells. The liquid splashed on the skin may be expected to cause irritation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 185.9
2. Boiling point (760 mm Hg): 149 C (300 F)
3. Specific gravity (water = 1): 1.7
4. Vapor density (air = 1 at boiling point of perchloromethyl mercaptan): 6.4
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): 65 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble, reacts slowly to form hydrochloric acid, carbon dioxide, and sulfur.
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Perchloromethyl mercaptan decomposes at elevated temperatures to give carbon tetrachloride and sulfur monochloride. The decomposition is rapid at 149 C (300 F), the boiling point.
2. Incompatibilities: Contact with alkalies and amines may cause rapid decomposition. Contact with hot iron causes formation of toxic carbon tetrachloride vapor. Contact with hot water causes formation of hydrochloric acid, sulfur, and carbon dioxide.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon tetrachloride, sulfur monochloride, hydrogen chloride, sulfur dioxide, and carbon monoxide) may be released in a fire involving perchloromethyl mercaptan.
4. Special precautions: Perchloromethyl mercaptan will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible

- **Warning properties**

1. Odor Threshold: By analogy with other mercaptans, perchloromethyl mercaptan is assumed to have an odor threshold below the permissible exposure limit. In addition, the following odor thresholds for different mercaptans can be found in May: n-butyl mercaptan, 0.00082 ppm; i-butyl mercaptan, 0.00054 ppm; i-pentyl mercaptan, 0.00021 ppm; i-amyl mercaptan, 0.00043 ppm; allyl mercaptan, 0.00005 ppm; crotyl mercaptan, 0.00016 and 0.000056 ppm; benzyl mercaptan, 0.0026 and 0.00035 ppm.
2. Eye Irritation Level: Grant states that perchloromethyl mercaptan "is a stink and tear gas that has been of military interest." No quantitative information is available, however, concerning the levels which produce eye discomfort.
3. Other Information: Grant states that this substance is a respiratory tract irritant.
4. Evaluation of Warning Properties: Since the odor threshold of perchloromethyl mercaptan is considerably below the permissible exposure limit and odor may be present within a properly functioning respirator, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for perchloromethyl mercaptan had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid perchloromethyl mercaptan.
• Clothing wet with perchloromethyl mercaptan should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of perchloromethyl mercaptan from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the perchloromethyl mercaptan, the person performing the operation should be informed of perchloromethyl mercaptan's hazardous properties.
• Non-impervious clothing which becomes wet with liquid perchloromethyl mercaptan should be removed promptly and not reworn until the perchloromethyl mercaptan is removed from the clothing.
• Employees should be provided with and required to use splash-proof safety goggles where liquid perchloromethyl mercaptan may contact the eyes.

SANITATION

• Skin that becomes wet with liquid perchloromethyl mercaptan should be promptly washed or showered with soap or mild detergent and water to remove any perchloromethyl mercaptan.
• Employees who handle liquid perchloromethyl mercaptan should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to perchloromethyl mercaptan may occur and control methods which may be effective in each case:

Operation	Controls
Use in chemical synthesis for agricultural and dye chemicals; use as an organic intermediate	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If liquid perchloromethyl mercaptan or strong concentrations of perchloromethyl mercaptan vapors get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid perchloromethyl mercaptan gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid perchloromethyl mercaptan soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of perchloromethyl mercaptan, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When liquid perchloromethyl mercaptan has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If perchloromethyl mercaptan is spilled or leaked, the following steps should be taken:
1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.
• Waste disposal methods:
Perchloromethyl mercaptan may be disposed of:
1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By dissolving in a combustible solvent, such as alcohol, and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• Althoff, H.: "Todliche Perchlormethylmercaptan - Intoxikation," *Archiv fur Toxikologie*, 31:121-135, 1973.
• American Conference of Government Industrial Hygienists: "Perchloromethyl Mercaptan," *Documentation of the Threshold Limit Values for Substances in*

Workroom Air (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR PERCHLOROMETHYL MERCAPTAN

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Vapor Concentration	
1ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Perchloryl Fluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: ClO_3F
- Synonyms: None
- Appearance and odor: Colorless gas with a characteristic sweet odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for perchloryl fluoride is 3 parts of perchloryl fluoride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 13.5 milligrams of perchloryl fluoride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Perchloryl fluoride can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

Perchloryl fluoride may cause respiratory irritation. The liquid, if allowed to remain in contact with the skin, may cause a burn. Animal exposures have produced severe breathing difficulties which have sometimes been delayed in onset. Also in animals, perchloryl fluoride can affect the ability of the blood to carry oxygen by forming methemoglobin. In man, methemoglobin formation may cause a bluish discoloration of the skin, drowsiness, dizziness, rapid heart beat, nausea, headache, shortness of breath, and unconsciousness.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to perchloryl fluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to perchloryl fluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory tract, blood, cardiovascular system, nervous system, and liver should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Perchloryl fluoride has been shown to cause methemoglobinemia in animals. Persons with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—14" x 17" chest roentgenogram: Perchloryl fluoride causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Perchloryl fluoride is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when other signs and symptoms of respiratory disease occur. Methemoglobin determinations should be performed if overexposure is suspected or signs and symptoms of toxicity occur.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1116

September 1978

• **Summary of toxicology**

Perchloryl fluoride gas is a respiratory irritant in humans and in animals causes the formation of methemoglobin. Dogs exposed to 450 ppm or 620 ppm for 4 hours developed hyperpnea, cyanosis, incoordination, and convulsions; methemoglobin levels were 29% and 71%, respectively. In dogs which died from exposure, there was lung damage consisting of alveolar collapse and hemorrhage; pigment deposition in the liver, spleen, and bone marrow was observed. Repeated exposure of three species of animals to 185 ppm for 7 weeks caused the death of more than half of them, guinea pigs being the most susceptible; all of the animals developed dyspnea, cyanosis, methemoglobinemia, alveolar edema, and pneumonitis. With similar repeated exposure of animals to 104 ppm for 6 weeks, the fluoride levels were increased by a factor of 20 to 30 in the blood, 5 to 8 in the urine, and 12 in the rat femur. One report states that workers suffered symptoms of upper respiratory irritation from brief exposure to unspecified concentrations. Perchloryl fluoride has the potential to form methemoglobin in man; the effects of methemoglobinemia are due to anoxia and include cyanosis, evident especially in the lips, nose, and earlobes; other effects are weakness, dizziness, and severe headache. The liquid is reported to produce moderately severe burns with prolonged skin contact.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 102.5
2. Boiling point (760 mm Hg): −46.7 C (−52 F)
3. Specific gravity (water = 1): 1.41 (liquid at 25 C)
4. Vapor density (air = 1 at boiling point of perchloryl fluoride): 3.5
5. Melting point: −146 C (−231 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): 0.06
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Containers may explode when heated above 500 C (932 F).
2. Incompatibilities: Contact with combustible materials, strong bases, amines, and finely divided metals may cause fires and explosions. Contact with readily oxidizable materials such as hydrogen sulfide, charcoal, sawdust, lampblack, etc. yields explosive products.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen fluoride and chlorine) may be released when perchloryl fluoride decomposes.
4. Special precautions: Perchloryl fluoride will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible by itself, but is a strong oxidizing agent
2. See 29 CFR 1910.101 for special regulations on storage of compressed gas cylinders.

• **Warning properties**

1. Odor Threshold: Sax states that the odor of perchloryl fluoride "can be detected as low as 10 ppm, although this cannot be relied upon as an indication of toxic concentrations in air."
2. Eye Irritation Level: Grant states that in industry "irritation of the eyes and nose has been reported when fluoride concentration has reached 5 mg/m³ of air." Perchloryl fluoride is not specifically known to be an eye irritant.
3. Evaluation of Warning Properties: Since Sax notes that the odor "cannot be relied upon as an indication of toxic concentrations in air," and since there is no other quantitative information relating warning properties to air concentrations of perchloryl fluoride, this substance is treated like a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for perchloryl fluoride had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid perchloryl fluoride or vessels containing liquid perchloryl fluoride.

• Non-impervious clothing which becomes contaminated with liquid perchloryl fluoride should be removed immediately and not reworn until the perchloryl fluoride has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid perchloryl fluoride may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to perchloryl fluoride may occur and control methods which may be effective in each case:

Operation	Controls
Use as a liquid oxidizer in rocket fuels, fuels used in cutting and welding, torches and chemical machinery	Process enclosure or adequate safety shields; local exhaust ventilation; personal protective equipment
Use in chemical synthesis in oxidation, ammonolysis, fluorination, perchlorylation, and etherification	Process enclosure or adequate safety shields; local exhaust ventilation; personal protective equipment
Use in flame photometry for analysis of different elements; miscellaneous uses for manufacture of fuel cells, gaseous dielectric for transformers, explosives, and metal processing	Process enclosure or adequate safety shields; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Skin Exposure**

If liquid perchloryl fluoride gets on the skin, immediately flush the perchloryl fluoride from the contaminated skin. If liquid perchloryl fluoride penetrates through the clothing, remove the clothing immediately and flush the skin with water. If irritation or burns are present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of perchloryl fluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If perchloryl fluoride is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Perchloryl Fluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Boysen, J. E.: "Health Hazards of Selected Rocket Propellants," *Archives of Environmental Health*, 7:77-81, 1963.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Greene, E. A., et al.: *The Inhalation Toxicity of Perchloryl Fluoride*, CRDLR 3010, U.S. Army Chemical Research and Development Laboratories, Army Chemical Center, Maryland, 1960.

• Greene, E. A., et al.: *Toxicity of Perchloryl Fluoride, an Interim Report*, CWL Technical Memorandum 26-5,U.S. Army Chemical Warfare Laboratories, Army Chemical Center, Maryland, 1958.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

RESPIRATORY PROTECTION FOR PERCHLORYL FLUORIDE

Condition	Minimum Respiratory Protection* Required Above 3 ppm
Vapor Concentration	
30 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
150 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
400 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode and containing non-combustible sorbents.
Greater than 400 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-combustible sorbents and providing protection against perchloryl fluoride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Petroleum Distillates (Naphtha)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_6H_{14} – C_7H_{16} – C_{8H_1}
- Synonyms: Petroleum naphtha; aliphatic petroleum naphtha; petroleum ether (95 to 115 C); naphtha, petroleum
- Appearance and odor: Colorless liquid with an odor like gasoline and kerosene.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for petroleum distillates is 500 parts of petroleum distillates per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2000 milligrams of petroleum distillates per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be reduced to 350 mg/m³ averaged over a work shift of up to 10 hours per day, 40 hours per week.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Petroleum distillates can affect the body if they are inhaled, come in contact with the eyes or skin, or are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to petroleum distillates may cause dizziness, drowsiness, headache, and nausea. They may also cause irritation of the eyes, throat, and skin.

2. Long-term Exposure: Prolonged overexposure may cause drying and cracking of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to petroleum distillates.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to petroleum distillates at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from petroleum distillates exposure.

—Skin disease: Petroleum distillates are skin defatting agents and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of these agents.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of petroleum distillates might cause exacerbation of symptoms due to their irritant properties.

—Liver disease: Although petroleum distillates are not known as liver toxins in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although petroleum distillates are not known as kidney toxins in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The vapors of petroleum distillates are mild narcotics and mucous membrane irritants. There have been few toxicologic studies, either on animals or man. While 4000 to 7000 ppm are tolerated for 1 hour by human subjects, symptoms of narcosis, such as dizziness and drowsiness, occur at those concentrations. Continuing

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

1120

exposure may produce signs of inebriation, followed by headache or nausea. Exposure at 10,000 to 20,000 ppm is regarded as immediately hazardous to life. The higher boiling fractions may produce irritation of the eyes, nose, and throat in addition to symptoms of mild narcosis. The liquid is a defatting agent, and repeated or prolonged skin contact results in drying and cracking of the skin. No chronic systemic effects have been reported from widespread industrial use. If benzene is present in the distillate, however, the hazard of both acute and chronic poisoning is increased; the presence of elevated phenol in the urine is indicative of benzene exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 100 (approximately)
2. Boiling point (760 mm Hg): 30 to 127 C (86 to 260 F)
3. Specific gravity (water = 1): 0.74
4. Vapor density (air = 1 at boiling point of petroleum distillates): 3.4 (approximately)
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F). 40 mm Hg (approximately)
7. Solubility in water, g/100 g water at 20 C (68 F): 0.04 (approximately)
8. Evaporation rate (butyl acetate = 1): 10 (approximately)

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving petroleum distillates.
4. Special precautions: Petroleum distillates will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: −40 to 20 C (−40 to 68 F) (closed cup)
2. Autoignition temperature: 232 to 260 C (450 to 500 F)
3. Flammable limits in air, % by volume: Lower: 1; Upper: 6
4. Extinguishant: Foam, carbon dioxide, dry chemical

- **Warning properties**

1. Odor Threshold: The odor thresholds of the main constituents of petroleum naphtha (i. e., heptane, octane, pentane, etc.) are below the individual permissible exposure limits.
2. Eye Irritation Level: According to Gafafer, the naphthes irritate the conjunctiva. The American Petroleum Institute states that irritation of the conjunctiva may occur "when the eyes are exposed to high vapor concentrations (of petroleum naphtha) in air. The irritation is mild and transitory." No quantitative information is available concerning the threshold of eye irritation, however.
3. Evaluation of Warning Properties: Since the odor of each of the main constituents of petroleum naphtha is detectable at concentrations below the respective permissible exposure limits, petroleum naphtha is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of petroleum distillates vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure petroleum distillates may be used. An analytical method for petroleum distillates is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid petroleum distillates.

• Clothing wet with liquid petroleum distillates should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of petroleum distillates from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the petroleum distillates, the person performing the operation should be informed of petroleum distillates' hazardous properties.

• Any clothing which becomes wet with liquid petroleum distillates should be removed immediately and not reworn until the petroleum distillates are removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid petroleum distillates may contact the eyes.

SANITATION

• Skin that becomes wet with liquid petroleum distillates should be promptly washed or showered with soap or mild detergent and water to remove any petroleum distillates.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to petroleum distillates may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during degreasing operations	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as solvents in rubber industry during manufacture of waterproof cloth, shoe adhesives, and rubber tires	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as extractants; use in preparation of paint, varnish, and lacquer as solvents, diluents, or thinners; use as solvents in pesticides	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use during dry cleaning operations	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If petroleum distillates get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If petroleum distillates get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If petroleum distillates soak through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of petroleum distillates, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If petroleum distillates have been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If petroleum distillates are spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Petroleum distillates should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Petroleum distillates may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

- American Industrial Hygiene Association: "Petroleum Naphtha," *Hygienic Guide Series*, Detroit, Michigan, 1969.
- American Petroleum Institute: "Petroleum Distillates," *API Toxicological Reviews*, New York.
- Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
- Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
- Gafafer, W. M. (ed.): "Occupational Diseases: A Guide to Their Recognition," U.S. Public Health Service Publication No. 1097, 1964.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- Pagnotto, L. D., et al.: "Industrial Benzene Exposure from Petroleum Naphtha: I. Rubber Coating Industry," *American Industrial Hygiene Association Journal*, 22:417-421, 1961.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR PETROLEUM DISTILLATES (NAPHTHA)

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
10,000 ppm or less	A gas mask with a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phenol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_6H_5OH
- Synonyms: Carbolic acid; monohydroxybenzene
- Appearance and odor: Colorless to pink solid or thick liquid with a characteristic, sweet, tarry odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phenol is 5 parts of phenol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 19 milligrams of phenol per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be changed to 20 mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling of 60 mg/m^3 averaged over a 15-minute period. The NIOSH Criteria Document for Phenol should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phenol can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Phenol has a marked corrosive effect on any tissue. When it comes in contact with the eyes, it may cause severe damage and blindness. On contact with the skin, it does not cause pain but causes a whitening of the exposed area. If the chemical is not removed promptly, it may cause a severe burn, or systemic poisoning. Systemic effects may occur from any route of exposure, especially after skin contact.

2. Long-term Exposure: Repeated or prolonged exposure to phenol may cause chronic phenol poisoning. The symptoms of chronic poisoning include vomiting, difficulty in swallowing, diarrhea, lack of appetite, headache, fainting, dizziness, dark urine, mental disturbances, and possibly a skin rash. Liver damage and discoloration of the skin may occur.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phenol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phenol at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of convulsive disorders or abnormalities of the skin, respiratory tract, liver, or kidneys would be expected to be at increased risk from exposure. Examination of the liver, kidneys, and respiratory tract should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Darkening of the urine has occurred in persons exposed to phenol after accidental ingestion or skin contact. A urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment. Urinary phenol is useful if good individual background levels are available.

—Liver function tests: Since liver damage has been observed in humans exposed to phenol, a profile of liver function should be performed by using a medically acceptable array of biochemical tests.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1121

September 1978

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Phenol in the vapor form or in solution is an irritant to the eyes, mucous membranes, and skin; systemic absorption causes central nervous system effects as well as liver and kidney damage. Sudden collapse is characteristic of gross overexposure. In animals, prolonged inhalation of the vapor at 30 to 60 ppm induced respiratory difficulty, lung damage, and paralysis. Systemic absorption by animals caused muscle twitching and severe convulsions. There are no reports of human fatalities from inhalation of the vapor, although one case of severe poisoning has been reported. Ingestion of lethal amounts (as little as 1 g) cause severe burns of the mouth and throat, marked abdominal pain, cyanosis, muscular weakness, collapse, coma, and death; tremors, convulsions, or muscle twitching were occasionally observed but were not severe. A laboratory technician repeatedly exposed to unknown vapor concentrations and liquid spilled on the skin developed anorexia, weight loss, weakness, muscle aches and pain, and dark urine; during several months of nonexposure there was gradual improvement in his condition, but after brief reexposure he suffered an immediate worsening of symptoms with prompt darkening of the urine and tender enlargement of the liver. Brief intermittent industrial exposures to vapor concentrations of 48 ppm of phenol (accompanied by 8 ppm of formaldehyde) caused marked irritation of eyes, nose, and throat. Concentrated phenol solutions are severely irritating to the human eye and cause conjunctival swelling; the cornea becomes white and hypesthetic; loss of vision has occurred in some cases. Solutions of phenol have a marked corrosive action on any tissue on contact; on skin, there is local anesthesia and a white discoloration, and the area may subsequently become gangrenous; severe dermatitis will result from contact with dilute solutions, and prolonged exposure may result in ochronosis. In workers making phenol-formaldehyde plastic, the urinary level of total phenol, free plus conjugated, was proportional to the air concentration of phenol up to 12.5 mg/m³ of workroom air. Mice were treated twice weekly for 72 weeks by application of 1 drop of a 10% solution of phenol in benzene to the shaved dorsal skin; after 52 weeks of treatment there were papillomas in 5 of 14 mice, and 1 fibrosarcoma appeared at 58 weeks.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 94.11
2. Boiling point (760 mm Hg): 182 C (359 F)
3. Specific gravity (water = 1): 107 (solid); 1.05 (liquid)
4. Vapor density (air = 1 at boiling point of phenol): 3.24
5. Melting point: 41 C (106 F)
6. Vapor pressure at 20 C (68 F): 0.36 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 8.4
8. Evaporation rate (butyl acetate = 1): Less than 0.01

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers (especially calcium hypochlorite) may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving phenol.
4. Special precautions: Liquid phenol will attack some forms of plastics, rubber, and coatings. Hot liquid phenol will attack aluminum, magnesium, lead, and zinc metals.

• **Flammability**

1. Flash point: 79 C (174 F) (closed cup)
2. Autoignition temperature: 715 C (1319 F)
3. Flammable limits in air, % by volume: Lower: 1.7; Upper: 8.6
4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical

• **Warning properties**

1. Odor Threshold: Summer reports that the odor threshold of phenol is 3 ppm; the Manufacturing Chemists Association reports 0.3 ppm; Thienes and Haley report 5 ppm.
2. Irritation Levels: The *Documentation of TLV's* reports that intermittent exposures to 48 ppm phenol have been observed to produce eye, nose, and throat irritation. Formaldehyde was also present in this atmosphere at a concentration of 8 ppm. The Respirator Review Committee considers the source of the eye irritation to be the 8 ppm formaldehyde rather than the phenol.
3. Evaluation of Warning Properties: Since the odor threshold of phenol is at or below the permissible exposure limit, phenol is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of phenol. Each measurement

should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of phenol in a bubbler containing sodium hydroxide, followed by treatment with sulfuric acid, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure phenol may be used. An analytical method for phenol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solid or liquid phenol or liquids containing phenol.

• If employees' clothing has had any possibility of being contaminated with solid or liquid phenol or liquids containing phenol, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with solid or liquid phenol or liquids containing phenol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of phenol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the phenol, the person performing the operation should be informed of phenol's hazardous properties.

• Where there is any possibility of exposure of an employee's body to solid or liquid phenol or liquids containing phenol, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with phenol should be removed immediately and not reworn until the phenol is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid phenol or liquids containing phenol contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solid or liquid phenol or liquids containing phenol, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with phenol should be immediately washed or showered with soap or mild detergent and water to remove any phenol.

• Any clothing which becomes wet with liquid phenol or liquids containing phenol should be removed immediately and not reworn until the phenol is removed from the clothing.

• Eating and smoking should not be permitted in areas where solid or liquid phenol or liquids containing phenol are handled, processed, or stored.

• Employees who handle solid or liquid phenol or liquids containing phenol should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phenol may occur and control methods which may be effective in each case:

Operation	Controls
Application and curing of bonding resin in plywood manufacture; application and curing of molding resins in manufacture of molded articles, such as	Process enclosure; local exhaust ventilation; personal protective equipment

electrical appliances, automotive parts, foundry sand molds, and utensil handles; manufacture of friction materials, bonded abrasives, coated abrasives, wood particle board, and insulation materials	
Use in industrial coatings in drum and can linings, milk and beer-processing equipment, water tanks and air-conditioning equipment, decorative laminates, and textile coatings	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of thermosetting phenolic resins, epoxy, polycarbonate, phenoxy, and polysulfone; synthesis of aprolactam for use in nylon 6 fibers, plastics, and films	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of agricultural chemicals and intermediates; synthesis of pharmaceuticals, rubber and plastic plasticizers, antioxidants, curing agents, and intermediates	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of stabilizers and preservatives for dyes, perfumes, and fungicides	Process enclosure; local exhaust ventilation; personal protective equipment
Use during solvent refining of lubrication oil and wax; use in synthesis of additives for gasoline and lubricating fluids and intermediates	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of intermediates in polyester production; production of corrosion-resistant polyester and polyester polyols; use in synthesis of dye intermediates	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of surface-active agents and detergent intermediates; in synthesis of explosives	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of disinfectant agents and products for industrial and household use	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of synthetic cresols and xylenols	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If solid or liquid phenol or liquids containing phenol get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If solid or liquid phenol or liquids containing phenol get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If solid or liquid phenol or liquids containing phenol penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

- **Breathing**

If a person breathes in large amounts of phenol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When solid or liquid phenol or liquids containing phenol have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If phenol is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill.
2. If in the solid form, for small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber.
3. If in the liquid form, for small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber.

• Waste disposal methods:

Phenol may be disposed of:

1. If in the solid form, by making packages of phenol in paper or other flammable material and burning in a suitable combustion chamber, or by dissolving phenol in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber.
2. If in the liquid form, by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill, or by atomizing the liquid in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phenol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Phenol," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Boutwell, R. K., and Bosch, D. K.: "The Tumor-promoting Action of Phenol and Related Compounds for Mouse Skin," *Cancer Research*, 19:413-424, 1959.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Community Air Quality Guides: "Phenol and Cresol," *American Industrial Hygiene Association Journal*, 30:425-428, 1969.

• Deichmann, W. B., and Witherup, S.: "Phenol Studies VI: The Acute and Comparative Toxicity of Phenol and o-, m-, and p-Cresols for Experimental Animals," *Journal of Pharmacolology and Experimental Therapy*, 80, 233, 1944.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 40 - Phenol*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1968.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-4, Phenol*, Washington, D.C., 1964.

• Merliss, R. R.: "Phenol Marasmus," *Journal of Occupational Medicine*, 14:55-56, 1972.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Phenol*, HEW Publication No. (NIOSH) 76-196, GPO No. 017-033-00184-7, U.S. Government Printing Office, Washington, D.C., 1976.

• Ohtsuji, H., and Ikeda, M.: "Quantitative Relationship between Atmospheric Phenol Vapour and Phenol in the Urine of Workers in Bakelite Factories," *British Journal of Industrial Medicine*, 29:70-73, 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - Phenol*, New York, 1966.

RESPIRATORY PROTECTION FOR PHENOL

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor or Particulate Concentration	
50 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s). Any supplied-air respirator. Any self-contained breathing apparatus.
100 ppm or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 100 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of phenol; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 100 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Phenyl Ether

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_6H_5)_2O$
- Synonyms: Diphenyl ether; diphenyl oxide
- Appearance and odor: Colorless solid or liquid with a somewhat disagreeable odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phenyl ether is 1 part of phenyl ether per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 7 milligrams of phenyl ether per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phenyl ether can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to phenyl ether vapor or mist may cause nausea and irritation of the eyes and nose.

2. Long-term Exposure: Prolonged or repeated exposure to undiluted phenyl ether liquid may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phenyl ether.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phenyl ether at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from phenyl ether exposure.

—Skin disease: Phenyl ether can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although phenyl ether is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although phenyl ether is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of phenyl ether might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Phenyl ether irritates the skin and eyes and has an objectionable odor which may cause nausea. The liquid appears to be low in oral toxicity, but little information on its physiologic effects is available. The acute lethal dose for rats and guinea pigs is 4 g/kg. Animals that survived oral doses of 1 to 2 g/kg showed some injury to the liver, kidneys, spleen, and thyroid. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1130

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 170.2
  2. Boiling point (760 mm Hg): 259 C (498 F)
  3. Specific gravity (water = 1): 1.1
  4. Vapor density (air = 1 at boiling point of phenyl ether): 5.86
  5. Melting point: 27 C (81 F) (maximum value)
  6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.0021
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving phenyl ether.
  4. Special precautions: Phenyl ether will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 115 C (239 F) (closed cup)
  2. Autoignition temperature: 620 C (1148 F)
  3. Flammable limits in air, % by volume: Lower: 0.8; Upper: 1.5
  4. Extinguishant: Foam dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold for phenyl ether of 0.01 ppm, and Stern reports 0.001 ppm
  2. Eye Irritation Level: The *Documentation of TLV's* states that "effects of . . . eye application (of phenyl ether) resemble closely those found for the eutectic mixture with diphenyl; phenyl ether in concentrated, prolonged exposures is somewhat irritating but is not so in dilution." The phenyl ether-diphenyl mixture is known to produce eye irritation at 3-4 ppm (Grant).
  3. Evaluation of Warning Properties: Since the odor threshold of phenyl ether is lower than the permissible exposure limit, this substance is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of phenyl ether vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure phenyl ether may be used. An analytical method for phenyl ether is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid or solid phenyl ether.
- Non-impervious clothing which becomes contaminated with liquid or solid phenyl ether should be removed promptly and not reworn until the phenyl ether is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where liquid or solid phenyl ether may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid or solid phenyl ether should be promptly washed or showered with soap or mild detergent and water to remove any phenyl ether.
- Employees who handle liquid or solid phenyl ether should wash their hands thoroughly with soap or mild

detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phenyl ether may occur and control methods which may be effective in each case:

Operation	Controls
Use as a high-temperature, heat-transfer medium as Dowtherm A, Thermax, Diphyl, and Gilotherm	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as an organic intermediate in organic synthesis resulting in epoxy resins, other phenol-based heat-resistant resins, polysulfone resins, high-temperature lubricants, surfactants, specialty plasticizers, varnishes, phenol-formaldehyde resins, artificial sweetners, insecticides, preservatives, fire retardants, and adhesives	General dilution ventilation; personal protective equipment
Use as an odorant in the manufacture of soaps and perfumes; use as a flavoring agent in manufacture of food products	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If phenyl ether gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If phenyl ether gets on the skin, promptly wash the contaminated skin using soap or mild detergent together with powdered pumice, borax, or other suitable cleanser. If phenyl ether soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent together with powdered pumice, borax, or other suitable cleansers. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of phenyl ether, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When phenyl ether has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If phenyl ether is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb or scoop up on paper. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed; however, if this is not practical, collect, dissolve in an appropriate solvent, and atomize in a suitable combustion chamber.

• Waste disposal method:

Phenyl ether may be disposed of by dissolving in appropriate solvent and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phenyl Ether," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Dow Chemical Company: *Material Safety Data Sheet – Diphenyl Oxide, Technical*, Midland, Michigan, 1971.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.

RESPIRATORY PROTECTION FOR PHENYL ETHER

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
50 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s) with a full facepiece and dust and mist filter(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister with a full facepiece and dust and mist filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 ppm or less	A powered air-purifying chemical cartridge respirator with a full facepiece, organic vapor cartridge, and high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phenyl Ether-Biphenyl Mixture

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_6H_5)_2O$ and $C_6H_5C_6H_5$
- Synonyms: Dowtherm A; diphenyl oxide-diphenyl mixture
- Appearance and odor: Straw-colored liquid that darkens on use with an aromatic, somewhat disagreeable odor

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phenyl ether-biphenyl mixture is 1 part of phenyl ether-biphenyl mixture per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 7 milligrams of phenyl ether-biphenyl mixture per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for phenyl ether-biphenyl mixture from 1 ppm to 0.5 ppm as a vapor.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phenyl ether-biphenyl mixture can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to phenyl ether-biphenyl mixture may cause irritation of the eyes, nose, and skin. It may also cause nausea.

2. Long-term Exposure: Repeated or prolonged contact may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phenyl ether-biphenyl mixture.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phenyl ether-biphenyl mixture at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from phenyl ether-biphenyl mixture exposure.

—Skin disease: Phenyl ether-biphenyl mixture can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although phenyl ether-biphenyl mixture is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although phenyl ether-biphenyl mixture is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of phenyl ether-biphenyl mixture might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Phenyl ether-biphenyl mixture is primarily an irritant to

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

eyes, skin, and upper respiratory tract. Repeated 8-hour exposures at 182 mg/m³ of a vapor-mist mixture were lethal to some animals within 1-½ months. Long-term (6-month) studies of four species at 7 to 10 ppm showed no significant adverse effects, although these concentrations are extremely nauseating to human subjects and painfully irritating to the eyes and nose. While 1 ppm is tolerable to most individuals, the odor at 0.1 ppm may be objectionable to some. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 166 (average)
2. Boiling point (760 mm Hg): 257 C (495 F)
3. Specific gravity (water = 1): 1.05 to 1.07
4. Vapor density (air = 1 at boiling point of phenyl ether-biphenyl mixture): 5.7 (average)
5. Melting point: 12 C (54 F)
6. Vapor pressure at 25 C (77 F): 0.08 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0014
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving phenyl ether-biphenyl mixture.
4. Special precautions: Phenyl ether-biphenyl mixture will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 124 C (255 F) (open cup)
2. Autoignition temperature: 621 C (1150 F)
3. Flammable limits in air, % by volume: Lower: 0.5; Upper: 6.2 (at 500 F)
4. Extinguishant: Foam, dry chemical, carbon dioxide

- **Warning properties**

1. Odor Threshold: Patty states, "Experience with human subjects has indicated that concentrations of vapors of Dowtherm A ranging from 0.1 to 1 ppm are readily detected by the olfactory organs and are unpleasant, sometimes producing nausea." The *Documentation of TLV's* states that a TLV of 1 ppm is recommended "to prevent disagreeable, nauseating odor for the majority of exposed workers. As little as 0.1 ppm may be objectionable to some sensitized, exposed individuals. The TLV of 1 ppm is sufficiently low to prevent serious toxic effects but may not eliminate all objectionable symptoms."
2. Irritation Levels: Grant states that "when concentrations of 3 or 4 ppm in air are reached, there is irritation of the eyes, nose, and throat."
3. Evaluation of Warning Properties: Through its odor and irritant effects, phenyl ether-biphenyl mixture can be detected at a concentration within 3 times the permissible exposure limit. For the purposes of this guideline, this mixture is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of phenyl ether-biphenyl mixture in an adsorption tube containing silica gel, followed by desorption with benzene, and gas chromatographic analysis. An analytical method for phenyl ether-biphenyl mixture is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact

with liquid or solid phenyl ether-biphenyl mixture.
• Non-impervious clothing which becomes contaminated with liquid or solid phenyl ether-biphenyl mixture should be removed promptly and not reworn until the phenyl ether-biphenyl mixture is removed from the clothing.
• Employees should be provided with and required to use dust- and splash-proof safety goggles where liquid or solid phenyl ether-biphenyl mixture may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid or solid phenyl ether-biphenyl mixture should be promptly washed or showered with soap or mild detergent and water to remove any phenyl ether-biphenyl mixture.
• Employees who handle liquid or solid phenyl ether-biphenyl mixture should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phenyl ether-biphenyl mixture may occur and control methods which may be effective in each case:

Operation	Controls
Use in chemical, petroleum, and nuclear industry as a high-transfer medium used in heating and cooling processes – marked as Dowtherm A, Termax, Diphyl, and Gilotherm	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a dye carrier (dyeing aid) for printing and dyeing polyester textiles	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If phenyl ether-biphenyl mixture gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If phenyl ether-biphenyl mixture gets on the skin, promptly wash the contaminated skin using soap or mild detergent together with powdered pumice, borax, or other suitable cleansers. If phenyl ether-biphenyl mixture soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent together with powdered pumice, borax, or other suitable cleaners. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of phenyl ether-biphenyl mixture, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When phenyl ether-bisphenyl mixture has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If phenyl ether-biphenyl mixture is spilled or leaked, the following steps should be taken:
1. Ventilate area of spill or leak.
2. For small quantities, absorb or scoop up on paper. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities may be reclaimed; however, if this is not practical, dissolve in an appropriate solvent and atomize in a suitable combustion chamber.
• Waste disposal method:
Phenyl ether-biphenyl mixture may be disposed of by dissolving in an appropriate solvent and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phenyl Ether-Diphenyl Mixture," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Dow Chemical Company: *Material Safety Data Sheet - Phenyl Ether-Biphenyl Mixture.*
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR PHENYL ETHER-BIPHENYL MIXTURE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
50 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s) with a full facepiece and dust and mist filter(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister with a full facepiece and dust and mist filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 ppm or less	A powered air-purifying chemical cartridge respirator with a full facepiece, organic vapor cartridge, and high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for p-Phenylene Diamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_8N_2$
- Synonyms: p-Diaminobenzene; 1,4-diaminobenzene
- Appearance: White to light purple or brown solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for p-phenylene diamine is 0.1 milligram of p-phenylene diamine per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

p-Phenylene diamine can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: p-Phenylene diamine may cause irritation of the throat.

2. Long-term Exposure: Repeated or prolonged exposure may cause allergy with asthma or skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to p-phenylene diamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to p-phenylene diamine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to p-phenylene diamine would be expected to be at increased risk from exposure. Examination of the respiratory system should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

p-Phenylene diamine dust is a skin and respiratory system sensitizer and may produce bronchial asthma and dermatitis in exposed workers. In cats, the minimal fatal peroral dose was 0.1 g/kg. Solutions administered orally or parenterally to animals caused a peculiar and selective edema of the conjunctivae, nose, lips, tongue, and neck. Inflammatory reactions of the pharynx and larynx have been reported in workers. Very small quantities of the dust have caused asthmatic attacks in workers after periods of exposure ranging from 3 months to 10 years. A dilute aqueous solution placed in the eye of a rabbit caused mild transient conjunctival edema. This compound may cause contact dermatitis through sensitization.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 108.1
2. Boiling point (760 mm Hg): 267 C (512 F)
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of p-phenylene diamine): 3.71
5. Melting point: 141 C (286 F)
6. Vapor pressure at 20 C (68 F): Very low
7. Solubility in water, g/100 g water at 20 C (68 F): 4.7
8. Evaporation rate (butyl acetate = 1): Data not

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

available

- **Reactivity**

1. Conditions contributing to instability: Heat; light
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving p-phenylene diamine.
4. Special precautions: None

- **Flammability**

1. Flash point: 155.5 C (312 F) (closed cup)
2. Autoignition temperature: Data not available
3. Minimum explosive concentration: 0.025 g/l
4. Extinguishant: Carbon dioxide, dry chemical

- **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of p-phenylene diamine.
2. Eye Irritation Level: Gleason reports that p-phenylene diamine in the eye produces "chemosis, lacrimation, exophthalmos ophthalmia, and even permanent blindness." Kirk and Othmer report that p-phenylene diamine "is responsible for keratoconjunctivitis, swollen conjunctiva, and eczema of the eyelids." Grant provides similar information, but no quantitative data are given.
3. Evaluation of Warning Properties: p-Phenylene diamine is treated as material with poor warning properties, since no quantitative data are available relating warning properties to air concentrations of p-phenylene diamine.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.). Williams and Wilkins, Baltimore, 1969.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for p-phenylene diamine had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with p-phenylene diamine or liquids containing p-phenylene diamine, where skin contact may occur.

• If employees' clothing may have become contaminated with p-phenylene diamine or liquids containing p-phenylene diamine, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with p-phenylene diamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of p-phenylene diamine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the p-phenylene diamine, the person performing the operation should be informed of p-phenylene diamine's hazardous properties.

• Non-impervious clothing which becomes contaminated with p-phenylene diamine should be removed promptly and not reworn until the p-phenylene diamine is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where p-phenylene diamine or liquids containing p-phenylene diamine may contact the eyes.

SANITATION

• Workers subject to skin contact with p-phenylene diamine or liquids containing p-phenylene diamine should wash with soap or mild detergent and water any areas of the body which may have contacted p-phenylene diamine at the end of each work day.

• Skin that becomes contaminated with p-phenylene diamine should be promptly washed or showered with soap or mild detergent and water to remove any p-phenylene diamine.

• Eating and smoking should not be permitted in areas where p-phenylene diamine or liquids containing p-phenylene diamine are handled, processed, or stored.
• Employees who handle p-phenylene diamine or liquids containing p-phenylene diamine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to p-phenylene diamine may occur and control methods which may be effective in each case:

Operation	Controls
Use in dye and dyestuff intermediates for fur, hair, leather, cotton, and synthetics	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in photographic application as a fine-grain developing agent, for preparation of color developers, and for photochemical measurements; use in polymer technology for manufacture of Fiber B, and as a cross-linking agent; use as a catalyst; use in preparation of epoxy resins, synthetic fibers, heat-resistant polymers, and coatings for leather, paper, and textiles	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in rubber technology for natural and synthetic rubber for vulcanization, as an antioxidant, accelerator, and stabilizer	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in organic synthesis in preparation of antioxidants for petroleum fuels; preparation of grease thickeners, electrical insulators, and rust removers	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in laboratory as an analytical reagent, and as a special solvent	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If p-phenylene diamine or liquids containing p-phenylene diamine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If p-phenylene diamine or liquids containing p-phenylene diamine get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If p-phenylene diamine or liquids containing p-phenylene diamine penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of p-phenylene diamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When p-phenylene diamine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If p-phenylene diamine is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

p-Phenylene diamine may be disposed of:

1. By making packages of p-phenylene diamine in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving p-phenylene diamine in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "p-Phenylene Diamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baer, R. L., et al.: "The Most Common Contact Allergens," *Archives of Dermatology*, 108:74-78, 1973.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products5(3rd ed.), Williams and Wilkins, Baltimore, 1969.*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Saruta, N., Yamaguchi, S., and Nakatomi, Y.: "Sarcoma Produced by Subdermal Administration of Paraphenylenediamine," *Kyushu Journal of Medical Science*, 9:94-101, 1958.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR p-PHENYLENE DIAMINE

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate or Vapor Concentration	
5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
25 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 25 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against p-phenylene diamine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phosdrin

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3O)_2PO_2C(CH_3)=CHCOOCH$
- Synonyms: Mevinphos (R); 2-carbomethoxy-1-methylvinyl dimethyl phosphate
- Appearance and odor: Colorless or yellow liquid with a weak odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phosdrin is 0.1 milligram of phosdrin per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phosdrin can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: After inhalation of phosdrin, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of vision, tearing, runny nose, headache, and watering of the mouth. After swallowing phosdrin, loss of appetite, nausea, vomiting, abdominal cramps and diarrhea may appear within two hours. After skin absorption, sweating and twitching in the area of absorption may occur, usually within 15 minutes to four hours. With severe intoxication by all routes, in addition to the above symptoms, weakness, generalized twitching and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, irregular or slow heartbeat, convulsions, and coma may occur.

2. Long-term Exposure: Repeated exposure to phosdrin may make a person more susceptible to the effects of this and related chemicals. Repeated exposure to concentrations which are too small to produce symptoms after a single exposure may result in the onset of symptoms.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phosdrin.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phosdrin at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system, and attention to the cholinesterase levels in the blood should be stressed. The skin should be examined for evidence of chronic disorders.

—Cholinesterase determination: Phosdrin (Mevinphos) causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the serum and erythrocytes should be determined by using medically acceptable biochemical tests prior to any new period of exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determi-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1143

nation which should be performed quarterly or at any time overexposure is suspected or signs and symptoms of toxicity occur.

• **Summary of toxicology**

Phosdrin (Mevinphos) is an anticholinesterase agent; absorption may occur from inhalation of the vapor or mist, from skin absorption of the liquid, or from ingestion. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nervous system, skeletal and smooth muscle, and secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms may occur promptly or may be delayed for up to 12 hours. After inhalation, respiratory and ocular effects are the first to appear, often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects, such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption, localized sweating and muscular fasciculations in the immediate area occur usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures and is increased by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels, and cardiac irregularities including complete heart block may occur; these effects may sometimes be reversed by establishing adequate pulmonary ventilation. Complete symptomatic recovery usually occurs within 1 week; increased susceptibility to the effects of anticholinesterase agents persists for several weeks after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects. In two cases of moderate intoxication from Mevinphos, urinary excretion of dimethylphosphate (a metabolite of Mevinphos) was almost complete 50 hours after exposure; although a number of other organophosphorus pesticides also yield dimethylphosphate, the presence of significant amounts of this metabolite in the urine may be useful in estimating the absorption of Mevinphos.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 224
2. Boiling point (760 mm Hg): 325 C (617 F)
3. Specific gravity (water = 1): 1.24
4. Vapor density (air = 1 at boiling point of phosdrin): Not applicable
5. Melting point: −56 C (−69 F) (pour point)
6. Vapor pressure at 20 C (68 F): 0.003 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Phosdrin decomposes vigorously when heated above 300 C (572 F) and will cause containers to burst.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as phosphoric acid mist and carbon monoxide) may be released in a fire involving phosdrin.
4. Special precautions: Phosdrin will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 79 C (175 F) (open cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of phosdrin.
2. Eye Irritation Level: Phosdrin is not known to be an eye irritant.
3. Evaluation of Warning Properties: Since no quantitative information is available relating its warning properties to air concentrations, phosdrin is treated as a material with poor warning properties. The concentration of phosdrin in saturated air at 20 C could result in a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for phosdrin is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with phosdrin.

• Clothing which has had any possibility of being contaminated with phosdrin should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of phosdrin from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the phosdrin, the person performing the operation should be informed of phosdrin's hazardous properties.

• Where there is any possibility of exposure of an employee's body to phosdrin, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with phosdrin should be removed immediately and not reworn until the phosdrin is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid phosdrin contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to phosdrin, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with phosdrin should be immediately washed or showered to remove any phosdrin.

• Eating and smoking should not be permitted in areas where phosdrin is handled, processed, or stored.

• Employees who handle phosdrin should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phosdrin may occur and control methods which may be effective in each case:

Operation	Controls
Application as an insecticide on agricultural crops, fruits, and vegetables; for ornamentals in greenhouses; use as an insecticide in sewage treatment plants	Personal protective equipment
Formulation and mixing for insecticidal application	Local exhaust ventilation; personal protective equipment
Manufacture of phosdrin	Local exhaust ventilation; personal protective equipment; process enclosure

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If phosdrin or phosdrin mists get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If phosdrin or phosdrin mists get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If phosdrin or phosdrin mists penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of phosdrin, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When phosdrin has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If phosdrin is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Phosdrin may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phosdrin (Mevinphos)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• Holmes, J. H., et al.: "Short-Term Toxicity of Mevinphos in Man," *Archives of Environmental Health*, 29:84-89, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koelle, G. B. (ed.): "Cholinesterases and Anticholinesterase Agents," Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

RESPIRATORY PROTECTION FOR PHOSDRIN

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate or Vapor Concentration	
1mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
40 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 40 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of phosdrin; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 40 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Phosgene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $COCl_2$
- Synonyms: Carbonyl chloride; carbon oxychloride; chloroformyl chloride
- Appearance and odor: Colorless liquid or gas with a sweet odor like hay at low concentrations and a sharp pungent odor at high concentrations.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phosgene is 0.1 part of phosgene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.4 milligram of phosgene per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be changed to 0.1 ppm averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 0.2 ppm averaged over a 15-minute period. The NIOSH Criteria Document for Phosgene should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phosgene can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Phosgene, after a minute or so of exposure to low concentrations, may cause cough and discomfort in the chest and irritation of the nose and throat. Higher concentrations may cause painful coughing with respiratory irritation. Phosgene may cause pulmonary edema with coughing, shortness of breath, and production of frothy sputum. This can be fatal. Pulmonary edema may occur many hours after exposure. The gas may irritate the eyes. If liquid phosgene is splashed on the skin or eyes, it may cause burns.

2. Long-term Exposure: No known effect

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phosgene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phosgene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed.

—14" x 17" chest roentgenogram: Phosgene may cause acute lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec and 25— 75): Phosgene is reported to cause pulmonary function impairment. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Phosgene gas is a severe respiratory irritant. The least concentration claimed to be capable of causing immediate irritation of the human throat is 3 ppm; 4 ppm causes immediate irritation of the eyes; 4.8 ppm causes cough; brief exposure to 50 ppm may be rapidly fatal. With moderate exposure, the presenting symptoms are often a dryness or a burning sensation in the throat, vomiting, pain in the chest, and dyspnea. The onset of symptoms

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1148

September 1978

of severe respiratory distress may be delayed for up to 72 hours, the latent interval depending upon the concentration and duration of exposure. The delayed onset of pulmonary edema is characterized by cough, abundant quantities of foamy sputum, progressive dyspnea, and severe cyanosis. Pulmonary edema may progress to pneumonia, and cardiac failure may intervene. The gas in concentrations of 1 to 2 ppm causes eye discomfort, and higher concentrations are likely to cause lacrimation and conjunctivitis; splashes of liquid phosgene in the eye may produce severe irritation. Skin contact with the liquid may cause severe burns.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 98.9
2. Boiling point (760 mm Hg): 8.2 C (46.7 F)
3. Specific gravity (water = 1): 1.4
4. Vapor density (air = 1 at boiling point of phosgene): 3.4
5. Melting point: −128 C (−198 F)
6. Vapor pressure at 20 C (68 F): Not pertinent
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts with water
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with moisture causes slow decomposition to form hydrogen chloride with carbon dioxide.
3. Hazardous decomposition products: Toxic gases and vapors (such as chlorine and carbon monoxide) may be released when phosgene decomposes, but these gases are less toxic than phosgene itself.
4. Special precautions: Liquid phosgene will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible

- **Warning properties**

1. Odor Threshold: The odor threshold of phosgene has been reported as 0.125 ppm by the ILO, 0.5 to 1.0 ppm by Thienes and Haley, and 0.5 ppm by both Patty and May. The *MCA states in its Chemical Safety Data Sheet*, however, that "the gas has the ability to condition the sense of smell so that the characteristic odor can be detected only briefly at the time of initial exposure."
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "the vapor of phosgene in concentrations of 1 to 2 ppm causes a scratchy sensation of the eyes, and higher concentrations are likely to cause lacrimation and conjunctivitis." They also state that within a few minutes 5 ppm might cause eye irritation.
3. Other Information: Patty notes that concentrations below 10 ppm produce mild irritation of the mucous membranes, and concentrations above 10 ppm can produce serious irritation. At 2 ppm, irritation of the nose and throat is "barely detectable." The *Documentation of TLV's* reports that 3 ppm has been claimed to be the lowest concentration causing irritation of the throat. Stecher notes, however, that phosgene is "an insidious poison, as it is not irritating immediately, even when fatal concentrations are inhaled."
4. Evaluation of Warning Properties: Since phosgene has the ability "to condition the sense of smell so that the characteristic odor can be detected only briefly at the time of initial exposure," and since the threshold of eye, nose, and throat irritation are many times higher than the permissible exposure limit, phosgene has been treated as a material with poor warning properties. In addition, according to Stecher, the irritant effects of phosgene are delayed, giving no warning that harmful concentrations are being inhaled.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of phosgene. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of phosgene in a midget impinger containing a solution of nitrobenzylpyridine, followed by colorimetric analysis. An analytical method for phosgene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not

technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, full facepiece respirator, gloves, face shields (eight-inch minimum), and other appropriate protective clothing where skin contact with liquid phosgene may occur.

• Where there is any possibility of exposure of an employee's body to liquid phosgene, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes wet with liquid phosgene should be removed immediately while using quick drenching facilities and not reworn until the phosgene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid phosgene contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to phosgene, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes wet with liquid phosgene should be immediately washed or showered with very large quantities of water to remove any phosgene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phosgene may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during open-flame cutting of certain metals in presence of chlorinated hydrocarbons	Insolation of operations from chlorinated hydrocarbons; local exhaust ventilation; personal protective equipment
Liberation from synthesis of isocyanates in manufacture of polyurethane plastics; alkyl isocyanates in pesticide manufacture; polycarbonated resins for molded plastics, dyestuffs, and pharmaceuticals	Process enclosure; local exhaust ventilation
Liberation during fire-extinguishing with agents containing chlorinated hydrocarbons	Material substitution; personal protective equipment
Liberation during sand bleaching operations in glass manufacture	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If phosgene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If phosgene gets on the skin, immediately flush the contaminated skin with large quantities of water. If phosgene soaks through the clothing, remove the clothing immediately while using a quick drenching facility and flush the skin with large quantities of water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of phosgene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If phosgene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency

rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If phosgene is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty. Water spray may be used to knock down the vapor.
3. If in the liquid form, allow to vaporize.

• Waste disposal methods:

Phosgene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

ADDITIONAL INFORMATION

To find additional information on phosgene, look up phosgene in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards
• NIOSH Criteria Document for Phosgene (February 1976)

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phosgene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Phosgene," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• Cucinell, S. A.: "Review of the Toxicity of Long-Term Phosgene Exposure," *Archives of Environmental Health*, 28:272-275, 1974.

• Gross, P., et al.: "Chronic Pneumonitis Caused by Phosgene," *Archives of Environmental Health*, 10:768-775, 1965.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-95, Phosgene*, Washington, D.C., 1

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Phosgene*, HEW Publication No. (NIOSH) 76-137, GPO No. 017-033-00134-1, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck & Co., Inc., Rahway, New Jersey, 1968.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR PHOSGENE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Gas Concentration	
1 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
2 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against phosgene. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phosphine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: PH_3
- Synonyms: Hydrogen phosphide; phosphorus hydride; phosphorated hydrogen
- Appearance and odor: Colorless gas with a characteristic fishy odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phosphine is 0.3 part of phosphine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.4 milligram of phosphine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phosphine can affect the body if it is inhaled.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation of phosphine may cause coughing, shortness of breath, and severe breathing difficulty. This breathing difficulty may not appear until several hours after exposure has ceased. It may also cause thirst, nausea, vomiting, stomach pain, diarrhea, back pain, a feeling of coldness, fainting, and death.

2. Long-term Exposure: Not known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phosphine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phosphine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from phosphine exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of phosphine might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Phosphine gas is a severe pulmonary irritant and an acute systemic poison; it has caused both sudden death and delayed death due to pulmonary edema. Workers exposed intermittently to concentrations up to 35 ppm, but averaging below 10 ppm, complained of nausea, vomiting, diarrhea, chest tightness and cough, headache, and dizziness; no evidence of cumulative effects was noted. Single severe exposures cause similar signs and symptoms, as well as excessive thirst, muscle pain, chills, sensation of pressure in the chest, dyspnea, syncope, and stupor.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 34.04
2. Boiling point (760 mm Hg): −87.8 C (−126 F)
3. Specific gravity (water = 1): Liquid = 0.75 at boiling point
4. Vapor density (air = 1 at boiling point of phosphine): 1.17
5. Melting point: −134 C (−209 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1153

7. Solubility in water, g/100 g water at 20 C (68 F): 0.04

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Overheated cylinders may explode.

2. Incompatibilities: Contact with air or any other oxidizer such as chlorine, etc., will cause ignition of phosphine. Phosphine reacts with acids, halogenated hydrocarbons, and moisture.

3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of phosphorus, phosphoric acid mist, and hydrogen) may be released in a fire involving phosphine.

4. Special precautions: Phosphine is an unusually reactive and poisonous substance, and is usually handled in small quantities only.

• **Flammability**

1. Flash point: Not applicable

2. Autoignition temperature: Spontaneously flammable at room temperature

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Shut off flow of gas. Carbon dioxide may extinguish the fire, but it will re-ignite spontaneously. If the fire is in a safe location, let the fire burn.

• **Warning properties**

1. Odor Threshold: May reports an odor threshold for phosphine of 0.02 ppm. Although Patty states that the limit of perceptibility is 1.5 to 3.0 ppm, the experience of industrial users confirms the odor threshold given by May.

2. Eye Irritation Level: Grant states that "although numerous instances of poisoning of human beings and experimental animals (from phosphine) have been reported, no characteristic ocular or visual effects are known."

3. Evaluation of Warning Properties: Since the odor of phosphine can be detected at a concentration well below the permissible exposure limit, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for phosphine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phosphine may occur and control methods which may be effective in each case:

Operation	Controls
Use as a doping agent in manufacture of solid-state components for electronic circuits and in manufacture of lasers	Local exhaust ventilation; personal protective equipment
Use in preparation of alkyl and aryl phosphonium halides in textile treatment; use in organic intermediates; use as curing catalysts for epoxy resins, polymerization initiators, and condensation catalysts	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a fumigant for stored grain	Local exhaust ventilation; personal protective equipment

Liberation during drilling, machining, and grinding of ductile iron; during quenching of alloys or sludges; during cleaning of rusty metal in phosphoric acid; and during welding of steel coated with phosphate rust-proofing agents	Local exhaust ventilation; personal protective equipment
Liberation during manufacture and use of acetylene; during extraction of phosphorus, and use of inorganic phosphorus compounds use of phosphorus sesquisulfide in manufacture of safety matches and calcium phosphide in pyrotechnics	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of phosphine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If phosphine is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

• Waste disposal method:

Phosphine may be disposed of by burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phosphine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Phosphine," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Harger, P. N., and Spolyar, L. W.: "Toxicity of Phosphine, with a Possible Fatality from This Poison," *A.Archives of Industrial Health*, 18:497-504, 1958.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Jones, A. T., et al.: "Environmental and Clinical Aspects of Bulk Wheat Fumigation with Aluminum Phosphide," *American Industrial Hygiene Association Journal*, 25:376-379, 1964.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR PHOSPHINE

Condition	Minimum Respiratory Protection* Required Above 0.3 ppm
Gas Concentration	
3 ppm or less	Any chemical cartridge respirator with a cartridge(s) providing protection against phosphine. Any supplied-air respirator. Any self-contained breathing apparatus.
15 ppm or less	A chemical cartridge respirator with a full facepiece and a cartridge(s) providing protection against phosphine. A gas mask with a chin-style or a front- or back-mounted canister providing protection against phosphine. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 200 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against phosphine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phosphoric Acid

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: H_3PO_4
- Synonyms: White phosphoric acid; ortho-phosphoric acid; 85% phosphoric acid; meta-phosphoric acid
- Appearance and odor: Viscous, colorless, odorless liquid which can solidify at temperatures below 21 C (70 F).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phosphoric acid is 1 milligram of phosphoric acid per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phosphoric acid can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Solid phosphoric acid or its solutions may cause skin burns. Contact with the eyes may produce irritation and eye burns. Exposure to phosphoric acid vapor or mist may cause irritation of the eyes, nose, and throat.

2. Long-term Exposure: Repeated or prolonged exposure may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phosphoric acid.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phosphoric acid at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from phosphoric acid exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of phosphoric acid dust or mist might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Phosphoric acid dust, mist, or solutions may cause dermatitis. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Phosphoric acid mist is an irritant to the eyes, upper respiratory tract, and skin. The solid is especially irritating to skin in the presence of moisture. Unacclimated workers could not endure exposure to fumes of phosphorus pentoxide (the anhydride of phosphoric acid) at a concentration of 100 mg/m^3; exposure to concentrations between 3.6 and 11.3 mg/m^3 produced coughing. Concentrations of 0.8 to 5.4 mg/m^3 were noticeable but not uncomfortable. There is no evidence that phosphorus poisoning can result from contact with phosphoric acid. The risk of pulmonary edema resulting from the inhalation of mist or spray is remote. A dilute solution buffered to pH 2.5 caused a moderate brief stinging sensation but no injury when dropped in the human eye. A 75% solution will cause severe skin burns.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 98

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1157

2. Boiling point (760 mm Hg): 260 C (500 F)
3. Specific gravity (water = 1): 1.7
4. Vapor density (air = 1 at boiling point of phosphoric acid): 3.4
5. Melting point: 21 C (70 F)
6. Vapor pressure at 20 C (68 F): 0.0285 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with strong caustics can cause liberation of much heat and violent spattering. Contact with most metals causes formation of flammable and explosive hydrogen gas.
3. Hazardous decomposition products: Toxic gases and vapors (such as phosphoric acid fume) may be released when phosphoric acid decomposes.
4. Special precautions: Liquid phosphoric acid will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Phosphoric acid mist can cause irritation of the eyes and respiratory tract, according to the *Hygienic Guide*. No quantitative information is given, however. Deichmann and Gerarde note that since phosphoric acid "has a low vapor pressure at room temperature, it is not irritating to the eyes or respiratory tract, unless introduced into the atmosphere as a spray or mist."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of phosphoric acid on a cellulose membrane filter, followed by leaching with hot water, chemical reaction, and spectrophotometric analysis. An analytical method for phosphoric acid is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solid or liquid phosphoric acid or solutions containing greater than 1.6% ortho-phosphoric acid by weight or any concentration of meta-phosphoric acid.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solutions containing 1.6% or less ortho-phosphoric acid by weight.

• If employees' clothing may have become contaminated with solid phosphoric acid, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with phosphoric acid should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of phosphoric acid from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the phosphoric acid, the person performing the operation should be informed of phosphoric acid's hazardous properties.

• Where there is any possibility of exposure of an employee's body to solid or liquid phosphoric acid or solutions containing phosphoric acid, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with phosphoric acid should be removed immediately and not reworn until the phosphoric acid is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid phosphoric acid or solutions containing phosphoric acid contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solid or liquid phosphoric acid or solutions containing more than 1.6% ortho-phosphoric acid by weight, or any concentration of meta-phosphoric acid, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with phosphoric acid should be immediately washed or showered to remove any phosphoric acid.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phosphoric acid may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of aluminum products in bright dipping operations; use in cleaning, electropolishing, and pickling in manufacture of steel, brass, bronze, and copper during surface treatment and rust-proofing operations	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of intermediates in manufacture of soil fertilizers; use in manufacture of livestock and poultry feed	Process enclosure; local exhaust ventilation; personal protective equipment
Use during synthesis of detergent and soap builders and water-treatment chemicals; use as an acidulant and flavor agent in manufacture of carbonated beverages and jellies and preserves	Process enclosure; personal protective equipment
Use in manufacture of food products, intermediates, and food additives; use as an antioxidant and preservative; use in wood, textile, polyurethane foam flame-retardant processing and production of flame-retardant agents	Process enclosure; personal protective equipment
Use in manufacture of cleaning preparations and disinfectants	Process enclosure; personal protective equipment
Use as a bonding agent in manufacture of refactory bricks; use during lithography and photoengraving operations	Process enclosure; personal protective equipment
Use as a catalyst in synthesis of other chemicals; use in synthesis of textile and leather processing chemicals, clays, ceramics, cements, and clay-thinning agents for drilling mud formulations	Process enclosure; personal protective equipment
Use in synthesis of pharmaceuticals and pharmaceutical intermediates and in the extraction of penicillin; use as a laboratory reagent	Process enclosure; personal protective equipment
Use during manufacture of opal glass; during manufacture of dental cements and dentrifice adhesives, adhesive gums, and synthetic rubber; and in the manufacture of electric lights	Process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If phosphoric acid gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If phosphoric acid gets on the skin, immediately flush the contaminated skin with water. If phosphoric acid soaks through the clothing, remove the clothing immediately and flush the skin with water.

• **Breathing**

If a person breathes in large amounts of phosphoric acid, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When phosphoric acid has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If phosphoric acid is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If in the solid form, collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.
3. If in the liquid form, collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Liquid phosphoric acid may be disposed of by absorbing in vermiculite, dry sand, earth, or a similar material and diposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phosphoric Acid," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Phosphoric Acid," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Industrial Bio-Test Laboratories: *Phosphoric Acid.*

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-70, Phosphoric Acid*, Washington, D.C., 1958.

• National Institute for Occupational Safety and Health: "Hazard Entry No. 156 — Phosphoric Acid," *Hazard Process Index.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR PHOSPHORIC ACID

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate or Vapor Concentration	
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phosphorus Pentachloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: PCl_5
- Synonyms: None
- Appearance and odor: Pale yellow solid with an odor like hydrochloric acid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phosphorus pentachloride is 1 milligram of phosphorus pentachloride per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phosphorus pentachloride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to phosphorus pentachloride may cause irritation of the eyes and respiratory tract. Cases of bronchitis have resulted from exposure to this chemical. Severe breathing difficulties may occur. These breathing difficulties may be delayed in onset several hours after exposure has ceased. Phosphorus pentachloride on the skin may cause burning and irritation of the skin.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phosphorus pentachloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phosphorus pentachloride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, skin, and eyes should be stressed.

—14" x 17" chest roentgenogram: Phosphorus pentachloride causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Phosphorus pentachloride is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Phosphorus pentachloride fume is a severe irritant of the eyes and mucous membranes. Exposure of mice to 120 ppm for 10 minutes was fatal. In humans, the fume causes irritation of the eyes and respiratory tract, and cases of bronchitis have resulted from exposure; although not reported, delayed onset of pulmonary edema may occur. The material on the skin could be expected to cause dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 208.3
2. Boiling point (760 mm Hg): 167 C (333 F) (sublimes)
3. Specific gravity (water = 1): 1.6
4. Vapor density (air = 1 at boiling point of phos-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1162

phorus pentachloride): Not applicable (reacts rapidly with water in air)

5. Melting point: 167 C (333F) (sublimes)

6. Vapor pressure at 20 C (68 F): Less than 1

7. Solubility in water, g/100 g water at 20 C (68 F): Reacts to form hydrogen chloride and phosphoric acid

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: High temperatures may cause containers to burst. Exposure to moisture will cause the development of pressure in closed containers.

2. Incompatibilities: Contact with water will cause violent spattering and formation of toxic hydrogen chloride gas and phosphoric acid mist. Phosphorus pentachloride reacts with magnesium oxide, chemically active metals such as sodium and potassium, and with alkalies.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosphoric acid mist, and carbon monoxide) may be released in a fire involving phosphorus pentachloride.

4. Special precautions: Phosphorus pentachloride will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: Patty states that phosphorus pentachloride "has a pungent, unpleasant odor." No quantitative information is available concerning the odor threshold, however.

2. Irritation Levels: Patty states that the "vapor or fume is very irritant to all mucous membranes, including the lungs." No quantitative information is available concerning the threshold of eye irritation, however.

3. Evaluation of Warning Properties: Since no quantitative information is available relating its warning properties to air concentrations, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for phosphorus pentachloride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with phosphorus pentachloride or liquids containing phosphorus pentachloride.

• If employees' clothing may have become contaminated with solid phosphorus pentachloride, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with phosphorus pentachloride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of phosphorus pentachloride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the phosphorus pentachloride, the person performing the operation should be informed of phosphorus pentachloride's hazardous properties.

• Where there is any possibility of exposure of an employee's body to phosphorus pentachloride or liquids containing phosphorus pentachloride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with phosphorus pentachloride should be removed immediately and not reworn until the phosphorus pentachloride is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of phosphorus pentachloride or liquids containing phosphorus pentachloride contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to phosphorus pentachloride or liquids

containing phosphorus pentachloride, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with phosphorus pentachloride should be immediately washed or showered to remove any phosphorus pentachloride.
• Eating and smoking should not be permitted in areas where solid phosphorus pentachloride is handled, processed, or stored.
• Employees who handle phosphorus pentachloride or liquids containing phosphorus pentachloride should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phosphorus pentachloride may occur and control methods which may be effective in each case:

Operation	Controls
Use as a chlorinating agent in organic synthesis or chemical reactant for aryl or alkyl acids and salts, ketones, aldehydes, and synthesis of phosphorus compounds	Local exhaust ventilation; personal protective equipment
Use as a catalyst in organic synthesis in production of polyethylene from ethylene	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If phosphorus pentachloride or liquids containing phosphorus pentachloride get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If phosphorus pentachloride or liquids containing phosphorus pentachloride get on the skin, immediately flush the contaminated skin with water. If phosphorus pentachloride or liquids containing phosphorus pentachloride penetrate through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention.
• **Breathing**
If a person breathes in large amounts of phosphorus pentachloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
If phosphorus pentachloride or liquids containing phosphorus pentachloride have been swallowed and the person is conscious, give him large quantities of water immediately to dilute the phosphorus pentachloride. Do not attempt to make the exposed person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If phosphorus pentachloride is spilled, the following steps should be taken:
1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill, or
3. Cover with sodium bicarbonate or an equal mixture of soda ash and slaked lime, dilute carefully with small spray of water, then excess water, and dispose in a secured sanitary landfill.
• Waste disposal method:
See 2 and 3 above.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phosphorus Pentachloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Henderson, Y., and Haggard, H. W.: *Noxious Gases*, Reinhold, New York, 1927.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR PHOSPHORUS PENTACHLORIDE

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate or Vapor Concentration	
10 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and/or gases and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phosphorus Pentasulfide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: P_2S_5 or P_4S_{10}
- Synonyms: Phosphorus persulfide; regular phosphorus pentasulfide; reactive phosphorus pentasulfide; distilled phosphorus pentasulfide; undistilled phosphorus pentasulfide
- Appearance and odor: Greenish-yellow solid with the odor of rotten eggs.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phosphorus pentasulfide is 1 milligram of phosphorus pentasulfide per cubic meter of air (mg/m³) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phosphorus pentasulfide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Phosphorus pentasulfide on contact with water (including the water normally found in air) may produce hydrogen sulfide. This is a primary health hazard associated with phosphorus pentasulfide. Hydrogen sulfide is a very dangerous chemical. It smells like rotten eggs, but at high concentrations paralyzes the sense of smell so that the odor will not be noticed. Hydrogen sulfide acts as an irritant to the eyes and respiratory tract and can produce severe breathing difficulties which may not occur until a number of hours after exposure has ceased. High concentrations of hydrogen sulfide can stop breathing immediately and cause death. Phosphorus pentasulfide, if allowed to remain on the skin, may cause irritation. On contact with the eyes, it may cause serious irritation which may be delayed for a matter of hours.

2. Long-term Exposure: Repeated exposure to hydrogen sulfide released from contact of water with phosphorus pentasulfide will increase a person's sensitivity to hydrogen sulfide so that irritation of the eyes, coughing, dizziness, headache, and tiredness and other systemic effects may occur more readily.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phosphorus pentasulfide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phosphorus pentasulfide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, central nervous system, eyes, and skin should be stressed.

—14" x 17" chest roentgenogram: Phosphorus pentasulfide in contact with water will release hydrogen sulfide, which causes respiratory impairment. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Phosphorus pentasulfide in contact with water will release hydrogen sulfide, which causes respiratory impairment. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1166

indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

• **Summary of toxicology**

Phosphorus pentasulfide dust irritates the eyes and skin. Since it is readily converted in the presence of moisture to hydrogen sulfide gas and phosphoric acid, its inhalation toxicology is based on hydrogen sulfide. The latter is a rapidly acting systemic poison which causes respiratory paralysis with consequent asphyxia at high concentrations; it is an irritant of the eyes and respiratory tract at low concentrations. Inhalation of high concentrations of hydrogen sulfide, 1000 to 2000 ppm, may cause coma after a single breath and may be rapidly fatal; convulsions may also occur. Exposure to concentrations of hydrogen sulfide above 50 ppm for 1 hour may produce acute conjunctivitis with pain, lacrimation, and photophobia; in severe form this may progress to keratoconjunctivitis and vesiculation of the corneal epithelium. In low concentrations, hydrogen sulfide may cause headache, fatigue, irritability, insomnia, and gastrointestinal disturbances; in somewhat higher concentrations, it affects the central nervous system, causing excitement and dizziness. Prolonged exposure to 250 ppm may cause pulmonary edema. Prolonged exposure to concentrations as low as 50 ppm may cause rhinitis, pharyngitis, bronchitis, and pneumonitis. Repeated exposure to hydrogen sulfide results in increased susceptibility, so that eye irritation, cough, and systemic effects may result from concentrations previously tolerated without any effect. Rapid olfactory fatigue can occur at high concentrations.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 222.3 (or 444.6)
2. Boiling point (760 mm Hg): 513 C (955 F)
3. Specific gravity (water = 1): Bulk density powder = 1.3; solid = 2.1; liquid = 1.7
4. Vapor density (air = 1 at boiling point of phosphorus pentasulfide): Not applicable
5. Melting point: 275 C (527 F)
6. Vapor pressure at 300 C (572 F): 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts to form hydrogen sulfide and liberate heat
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Heat, particularly in presence of moisture or moist air
2. Incompatibilities: Contact with water, alcohols, and strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide, hydrogen sulfide, phosphorus pentoxide, phosphoric acid fume, and carbon monoxide) may be released in a fire involving phosphorus pentasulfide.
4. Special precautions: None listed

• **Flammability**

1. Flash point: Data not available
2. Autoignition temperature: 260 – 290 C (500 – 544 F) (dust); 275 C (527 F) (liquid) (approximately)
3. Minimum explosive concentration: Data not available
4. Extinguishant: Dry chemical, carbon dioxide, dry sand for small fires

• **Warning properties**

1. Odor Threshold: The MCA states that phosphorus pentasulfide reacts with moisture to liberate hydrogen sulfide. Phosphorus pentasulfide, according to the MCA, has a "characteristic hydrogen sulfide odor."
2. Eye Irritation Level: Phosphorus pentasulfide itself is not a known eye irritant. Hydrogen sulfide, however, which is liberated when the compound comes into contact with atmospheric moisture, is known to produce eye (and respiratory) irritation after 1 hour at 50 to 100 ppm (MCA).
3. Evaluation of Warning Properties: Since hydrogen sulfide "paralyzes" olfactory nerves at high concentrations "and, therefore, cannot be detected by odor," phosphorus pentasulfide is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for phosphorus pentasulfide had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or c' · ed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforce-

ment and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with phosphorus pentasulfide or liquids containing phosphorus pentasulfide.

• If employees' clothing may have become contaminated with solid phosphorus pentasulfide, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with phosphorus pentasulfide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of phosphorus pentasulfide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the phosphorus pentasulfide, the person performing the operation should be informed of phosphorus pentasulfide's hazardous properties.

• Non-impervious clothing which becomes contaminated with phosphorus pentasulfide should be removed promptly and not reworn until the phosphorus pentasulfide is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where phosphorus pentasulfide or liquids containing phosphorus pentasulfide may contact the eyes.

SANITATION

• Skin that becomes contaminated with phosphorus pentasulfide should be promptly washed or showered with soap or mild detergent and water to remove any phosphorus pentasulfide.

• Eating and smoking should not be permitted in areas where solid phosphorus pentasulfide is handled, processed, or stored.

• Employees who handle phosphorus pentasulfide or liquids containing phosphorus pentasulfide should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phosphorus pentasulfide may occur and control methods which may be effective in each case:

Operation	Controls
Use in preparation of lubrication oil additives for low-lead gas and reduction of air pollution	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If phosphorus pentasulfide or liquids containing phosphorus pentasulfide get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid phosphorus pentasulfide gets on the skin, dust it off immediately and then flush the contaminated skin with water. If phosphorus pentasulfide or liquids containing phosphorus pentasulfide penetrate through the clothing, remove the clothing promptly and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of phosphorus pentasulfide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When phosphorus pentasulfide or liquids containing phosphorus pentasulfide have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If phosphorus pentasulfide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and

burn in a safe place (such as a fume hood) Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device, or

3. Cover with sodium bicarbonate or an equal mixture of soda ash and slaked lime, dilute carefully with small spray of water, then excess water, and dispose in a secured sanitary landfill.

• Waste disposal methods:

Phosphorus pentasulfide may be disposed of:

1. By making packages of phosphorus pentasulfide in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving phosphorus pentasulfide in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

3. See 2 and 3 above.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phosphorus Pentasulfide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (cd.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-71, Phosphorus Pentasulfide*, Washington, D.C., 1958.

• Milby, T. H.: "Hydrogen Sulfide Intoxication – Review of the Literature and Report of Unusual Accident Resulting in Two Cases of Nonfatal Poisoning," *Journal of Occupational Medicine, 4:431-437, 1962.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR PHOSPHORUS PENTASULFIDE

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
10 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
750 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 750 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against hydrogen sulfide and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phosphorus Trichloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: PCl_3
- Synonyms: Phosphorus chloride
- Appearance and odor: Colorless to yellow fuming liquid with an odor like hydrochloric acid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phosphorus trichloride is 0.5 part of phosphorus trichloride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 3 milligrams of phosphorus trichloride per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for phosphorus trichloride from 0.5 ppm to 0.2 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phosphorus trichloride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Phosphorus trichloride is a severe irritant of the eyes, mucous membranes, and skin and may produce severe burns. Inhalation of the vapor may cause irritation of the respiratory tract. It may produce severe breathing difficulties which may be delayed as much as a day in onset. Phosphorus trichloride on contact with the eyes may produce severe burns with permanent eye damage. Swallowing phosphorus trichloride may produce burns of the mouth, throat, and stomach.

2. Long-term Exposure: Repeated inhalation of phosphorus trichloride may cause chronic cough and wheezing.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phosphorus trichloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phosphorus trichloride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, skin, eyes, and kidneys should be stressed.

—14" x 17" chest roentgenogram: Phosphorus trichloride causes lung damage in humans. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Phosphorus trichloride causes delayed pulmonary edema. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Phosphorus trichloride vapor is a severe irritant of the eyes, mucous membranes, and skin. These effects result primarily from the action of the strong acids, hydrochloric acid and acids of phosphorus, formed with water. In rats, the LC50 was 104 ppm for 4 hours; at autopsy, the chief finding was nephrosis; pulmonary

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

damage was negligible. Inhalation by humans could be expected to cause injury ranging from mild bronchial spasm to severe pulmonary edema; the onset of severe respiratory symptoms may be delayed for 2 to 6 hours, and after moderate exposure the onset may not occur until 12 to 24 hours later. Prolonged or repeated exposure to low concentrations may induce chronic cough and wheezing; pulmonary changes are non-fibrotic and non-progressive. Phosphorus trichloride causes severe burns in contact with the eyes, skin, or mucous membranes. Although ingestion is unlikely to occur in industrial use, it will cause burns of the mouth, throat, esophagus, and stomach.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 137.4
2. Boiling point (760 mm Hg): 75.9 C (168 F)
3. Specific gravity (water = 1): 1.57
4. Vapor density (air = 1 at boiling point of phosphorus trichloride): 4.75
5. Melting point: −112 C (−169 F)
6. Vapor pressure at 20 C (68 F): 100 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts violently to form hydrogen chloride
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat may cause containers to burst. Containers may burst if water enters them.
2. Incompatibilities: Contact with water or alcohol may cause fires and explosions, particularly when in contact with combustible organic matter. Phosphorus trichloride reacts with chemically active metals such as sodium, potassium, and aluminum or with strong nitric acid.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosphine, diphosphine, phosphoric acid, and carbon monoxide) may be released when phosphorus trichloride decomposes.
4. Special precautions: Phosphorus trichloride will attack some forms of plastics, rubber, and coatings. In the presence of moisture, phosphorus trichloride will severely corrode most metals.

- **Flammability**

1. Not combustible

- **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold. The MCA notes that this substance has a pungent odor.
2. Eye Irritation Level: Grant states that "experimentally in cats a concentration of 2 to 4 ppm in air in the course of 6 hours has caused conjunctivitis."
3. Other Information: Grant points out that the vapors are irritating to the respiratory tract also. The *Documentation of TLV's* states that a concentration of 0.7 ppm "was somewhat irritating to animals."
4. Evaluation of Warning Properties: Since phosphorus trichloride causes irritation at only 0.7 ppm, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for phosphorus trichloride had been published by NIOSH.

- **Method**

An analytical method for phosphorus trichloride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

can be discarded or until provision is made for the removal of phosphorus trichloride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the phosphorus trichloride, the person performing the operation should be informed of phosphorus trichloride's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid phosphorus trichloride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with phosphorus trichloride should be removed immediately and not reworn until the phosphorus trichloride is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid phosphorus trichloride contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid phosphorus trichloride, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with phosphorus trichloride should be immediately washed or showered to remove any phosphorus trichloride.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phosphorus trichloride may occur and control methods which may be effective in each case:

Operation	Controls
Use during synthesis of plasticizers and intermediates; and production of intermediates and during chemical synthesis of dyes, pharmaceuticals, other chlorinating agents, and other organic chemicals	Process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of pesticide intermediates and surfactants	Process enclosure; local exhaust ventilation; personal protective equipment
Use during deposition of metallic coatings; use in treatment of polypropylene before drying in manufacture of knitted fabrics	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid phosphorus trichloride or strong concentrations of phosphorus trichloride vapors get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid phosphorus trichloride gets on the skin, immediately flush the contaminated skin with water. If liquid phosphorus trichloride soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of phosphorus trichloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If liquid phosphorus trichloride has been swallowed and the person is conscious, give him large quantities of water immediately to dilute the phosphorus trichloride. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid phosphorus trichloride is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material, or;
3. Cover with sodium bicarbonate or an equal mixture of soda ash and slaked lime, dilute carefully with a small spray of water, then excess water, and dispose in a secured sanitary landfill.

• Waste disposal method:

Phosphorus trichloride may be disposed of by absorbing in vermiculite, dry sand, earth, or a similar material and disposing in a secured sanitary landfill or as in 3 above.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phosphorus Trichloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-27, Phosphorus Trichloride*, Washington, D.C., 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Weeks, M. H., et al.: "Acute Vapor Toxicity of Phosphorus Oxychloride, Phosphorus Trichloride and Methyl Phosphonic Dichloride," *American Industrial Hygiene Association Journal*, 25:470-475, 1964.

RESPIRATORY PROTECTION FOR PHOSPHORUS TRICHLORIDE

Condition	Minimum Respiratory Protection* Required Above 0.5 ppm
Vapor Concentration	
25 ppm or less	Any chemical cartridge respirator with a full facepiece and cartridge(s) containing non-oxidizable sorbents and providing protection against phosphorus trichloride. A gas mask with a chin-style or a front- or back-mounted canister containing non-oxidizable sorbents and providing protection against phosphorus trichloride Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
50 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 50 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-oxidizable sorbents and providing protection against phosphorus trichloride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phosphorus (Yellow)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: P_4
- Synonyms: White phosphorus; WP; phosphorus, elemental, white
- Appearance and odor: White to yellow, soft, waxy solid which gives off acrid fumes on exposure to air.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phosphorus (yellow) is 0.1 milligram of phosphorus (yellow) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phosphorus (yellow) can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: The vapors of burning phosphorus (yellow) are irritating to the nose, throat, and lungs. Severe breathing difficulties may occur. The onset of these difficulties may be delayed for several hours. Phosphorus (yellow) on contact with the skin may ignite and produce severe skin burns with blistering. Phosphorus (yellow) is especially hazardous to the eyes and may produce severe damage. When phosphorus (yellow) is swallowed, after a delay of a few hours, nausea, vomiting, and abdominal pain may occur. The vomit may smell like garlic and glow in the dark. After 24 to 36 hours, the symptoms may go away. In a few hours or 2 or 3 days, the nausea, vomiting, and abdominal pain may reappear with diarrhea and a yellow color to the skin. Death may occur.

2. Long-term Exposure: Repeated or prolonged exposure to phosphorus (yellow) can cause "phossy jaw" with pain and swelling of the jaw, toothaches, loosening of the teeth and destruction of the jawbone. Chronic exposure to phosphorus (yellow) can also cause weakness, anemia, loss of appetite, stomach complaints, cough, and paleness. In addition, chronic exposure to phosphorus (yellow) may cause bones to become brittle and break.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phosphorus (yellow).

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phosphorus (yellow) at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, respiratory tract, liver, and kidneys should be stressed. Particular attention should be given to the jaw and teeth. The skin should be examined for evidence of chronic disorders.

—Dental examination: Phosphorus exposure may aggravate existing dental disorders such as caries, periodontal disease, retained roots, and cysts which may predispose to toxic necrosis of the jaw. Dental examination including x-rays should be performed.

—Liver function tests: Since liver damage has been observed in humans exposed to phosphorus, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

—Complete blood count: Phosphorus exposure may cause anemia. A complete blood count should be per-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

formed including red and white blood cell count, a differential count of a stained blood smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an semi-annual basis.

• **Summary of toxicology**

Yellow phosphorus fume irritates the respiratory tract and eyes; the solid in contact with the skin produces deep thermal burns; prolonged absorption of phosphorus causes necrosis of facial bones. Yellow phosphorus spontaneously burns in air, and the vapors released are irritating to the respiratory tract. The early signs of systemic intoxication by phosphorus are abdominal pain, jaundice, and a garlic odor of the breath; prolonged intake may cause anemia, cachexia, and necrosis of bone, typically the maxilla and mandible. Complaints of possible overexposure among phosphorus workers may be toothache and excessive salivation; there may be dull red appearance of the oral mucosa; one or more teeth may loosen, followed by pain and swelling of the jaw; healing may be delayed following dental procedures such as extractions; with necrosis of bone, sequestra may develop with sinus tract formation. In a series of 10 cases, the shortest period of exposure to phosphorus fume leading to bone necrosis was 10 months (2 cases) and the longest was 18 years. Yellow phosphorus fume causes severe eye irritation with blepharospasm, photophobia, and lacrimation; the solid in the eye produces severe injury. Phosphorus burns on the skin are deep and painful; a firm eschar is produced and is surrounded by vesiculation.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 123.9
2. Boiling point (760 mm Hg): 279 C (535 F)
3. Specific gravity (water = 1): 1.82
4. Vapor density (air = 1 at boiling point of phosphorus (yellow)): 4.4
5. Melting point: 44 C (111 F)
6. Vapor pressure at 20 C (68 F): 0.026 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0003
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Light causes formation of yellow or red color.
2. Incompatibilities: Contact with air and all oxidizing agents (including elemental sulfur) will cause fires and explosions. Contact with strong caustics will cause formation of poisonous and flammable phosphine gas.
3. Hazardous decomposition products: Toxic gases and vapors (such as phosphoric acid fume) may be released in a fire involving phosphorus (yellow).
4. Special precautions: Liquid phosphorus (yellow) will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: Ignites spontaneously in air at or above 30 C (86 F)
2. Autoignition temperature: 30 C (86 F)
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Water, carbon dioxide, sand, warth, dry chemical

• **Warning properties**

Grant states that yellow phosphorus fumes are "irritating to the respiratory tract and cause severe ocular irritation with blepharospasm, photophobia, and lacrimation. Particles of white phosphorus (yellow phosphorus) are caustic and seriously damaging in contact with tissues."

No quantitative information is available concerning the concentrations that produce eye irritation, however.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for phosphorus (yellow) is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use flame-retardant clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solid or liquid phosphorus (yellow).
- Clothing contaminated with phosphorus (yellow) should be placed underwater in closed containers for storage until it can be discarded or until provision is made for the removal of phosphorus (yellow) from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the phosphorus (yellow), the person performing the operation should be informed of phosphorus (yellow)'s hazardous properties.
- Where there is any possibility of exposure of an employee's body to solid or liquid phosphorus (yellow), facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes contaminated with phosphorus (yellow) should be removed immediately and not reworn until the phosphorus (yellow) is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid phosphorus (yellow) contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to solid or liquid phosphorus (yellow), an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with phosphorus (yellow) should be immediately washed or showered with soap or mild detergent and water to remove any phosphorus (yellow).
- Workers subject to skin contact with solid or liquid phosphorus (yellow) should wash with soap or mild detergent and water any areas of the body which may have contacted phosphorus (yellow) at the end of each work day.
- Eating and smoking should not be permitted in areas where solid or liquid phosphorus (yellow) are handled, processed, or stored.
- Employees who handle solid or liquid phosphorus (yellow) should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phosphorus (yellow) may occur and control methods which may be effective in each case:

Operation	Controls
Use in synthesis of high purity phosphoric acid salts for use as fertilizers, water treatment chemicals, food products, beverages, and dentrifices; use in synthesis of inorganic phosphorus compounds for use as pesticides, flame retardants for plastics and fibers, and gasoline and lube oil additives; use in synthesis of inorganic and organic compounds	Process enclosure; local exhaust ventilation; general dilution ventilation
Use in manufacture of phosphorus alloys for introduction into low carbon steel, copper alloys, copper pipe, and bronze	Process enclosure; local exhaust ventilation; general dilution ventilation
Use in manufacture of explosives, munitions, and pyrotechnics for military use	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a catalyst in synthesis of acrylonitrile and organic bromine compounds	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during conversion of yellow phosphorus to red phosphorus for manufacture of wood and paper safety matches	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as an ingredient of rat poison and roach powders	Material substitution

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If phosphorus (yellow) gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If phosphorus (yellow) gets on the skin, immediately flush the contaminated skin with water. If phosphorus (yellow) penetrates through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately. The skin should be kept wet until medical attention is obtained to prevent any remaining phosphorus (yellow) from burning.

• **Breathing**

If a person breathes in large amounts of phosphorus (yellow), move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When phosphorus (yellow) has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If phosphorus (yellow) is spilled, the following step should be taken:

1. Immediately douse the spill with water and cover with wet sand or dirt.

• Waste disposal method:

Phosphorus (yellow), after solidification and covering with wet sand or dirt, may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phosphorus (Yellow)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• *American National Standard Acceptable Concentrations - Phosphorus (Yellow)*: American National Standards Institute, Inc., New York.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Fleming, A. J. (ed.), et al.: *Modern Occupational Medicine* (2d ed. rev.), Lea Febiger, Philadelphia, 1960.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hughes, J. P. W., et al.: "Phosphorus Necrosis of the Jaw: A Present-Day Study," *British Journal of Industrial Medicine*, 19:83-99, 1962.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• *Hygienic Information Guide No. 62 - Phosphorus (Yellow)*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saunders, Philadelphia, 1960.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-16, Phosphorus (Elemental)*, Washington, D.C., 1947.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Plunkett, E. R.: *Handbook of Industrial Toxicology*, Chemical Publishing Company, Inc., New York, 1966.

• Rubitsky, H. J., and Myerson, R. M.: "Acute Phosphorus Poisoning," *Archives of Internal Medicine*, 83:164-178, 1949.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Summerlin, W. T., et al.: "White Phosphorus Burns and Massive Hemolysis," *Journal of Trauma*, 7:476-484, 1967.

RESPIRATORY PROTECTION FOR PHOSPHORUS (YELLOW)

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Phthalic Anhydride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_4(CO)_2O$
- Synonyms: PAN
- Appearance and odor: White solid with a characteristic choking odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for phthalic anhydride is 2 parts of phthalic anhydride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 12 milligrams of phthalic anhydride per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has recommended for phthalic anhydride a Threshold Limit Value of 1 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Phthalic anhydride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Phthalic anhydride causes irritation of the eyes, nose, throat, and skin. The irritant effects are worse on moist surfaces. If phthalic anhydride is held in contact with the skin as under clothes or shoes, skin burns may occur. Inhalation of the dust or vapors may cause coughing, sneezing, or nosebleeds. Inhalation may cause attacks of asthma in persons who have previously had asthma.

2. Long-term Exposure: Repeated or prolonged exposure to phthalic anhydride may cause a skin rash or chronic eye irritation. Repeated exposures may also cause an allergic type of skin rash. It may cause bronchitis and asthma.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to phthalic anhydride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to phthalic anhydride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to phthalic anhydride would be expected to be at increased risk from exposure. Examination of the eyes, respiratory tract, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Phthalic anhydride in the form of vapor, fume, or dust irritates the eyes; it is both an irritant and sensitizer of the skin and respiratory tract, and may produce asthma on repeated exposure. Cats repeatedly exposed to 3700 mg/m³ became drowsy, lost appetite and vomited; liver and kidney injury occurred. In workers, air concentrations of 30 mg/m³ caused conjunctivitis; at 25 mg/m³ there were signs of mucous membrane irritation. Workers exposed to undetermined concentrations of mixed vapors of phthalic acid and phthalic anhydride developed conjunctivitis, bloody nasal discharge, atrophy of the nasal mucosa, hoarseness, cough, occasional bloody

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1180

September 1978

sputum, and bronchitis. A report of emphysema among workers exposed to phthalic anhydride is questionable. Several cases of bronchial asthma resulted; there was skin sensitization with occasional urticaria and eczematous response. Phthalic anhydride is a direct but delayed irritant of the skin; it is more severely irritating in contact with water, due to the pronounced effects of the phthalic acid which is formed. Prolonged or repeated exposure also may cause dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 148
  2. Boiling point (760 mm Hg): 284 C (543 F)
  3. Specific gravity (water = 1): 1.5
  4. Vapor density (air = 1 at boiling point of phthalic anhydride): 5.1
  5. Melting point: 131 C (268 F)
  6. Vapor pressure at 20 C (68 F): Less than 0.05 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.62 (reacts slowly)
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as phthalic acid fumes and carbon monoxide) may be released in a fire involving phthalic anhydride.
  4. Special precautions: Liquid phthalic anhydride will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 151 C (304 F) (closed cup)
  2. Autoignition temperature: 570 C (1058 F)
  3. Flammable limits in air, % by volume (at elevated temperatures): Lower: 1.7; Upper: 10.4
  4. Minimum explosive dust concentration: 0.015 g/l
  5. Extinguishant: Carbon dioxide, dry chemical, foam
- **Warning properties**

According to both Patty and the *Hygienic Guide*, exposure to a concentration of 30 mg/m³ causes "definite conjunctival irritation." This concentration is not stated specifically to be the threshold of eye irritation, however.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of phthalic anhydride on a cellulose membrane filter, followed by treatment with aqueous ammonia, hydrolysis, and anlysis with a high-performance liquid chromatograph. An analytical method for phthalic anhydride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid phthalic anhydride or liquids containing phthalic anhydride.
- If employees' clothing may have become contaminated with solid phthalic anhydride, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with phthalic anhydride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of phthalic anhydride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the phthalic anhydride, the person performing the operation should be informed of phthalic anhydride's hazardous properties.

• Non-impervious clothing which becomes contaminated with phthalic anhydride should be removed immediately and not reworn until the phthalic anhydride is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where solid phthalic anhydride or liquids containing phthalic anhydride may contact the eyes.

SANITATION

• Skin that becomes contaminated with phthalic anhydride should be immediately washed or showered with soap or mild detergent and water to remove any phthalic anhydride.

• Employees who handle solid phthalic anhydride or liquids containing phthalic anhydride should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to phthalic anhydride may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of plasticizers for use in polyvinyl chloride, polyvinyl acetate, copolymer resins, cellulosic plastics, alkyd resins, and nondrying oils or natural resins to enhance properties; manufacture of unsaturated polyester resins for use in structural building parts, swimming pools, automotive parts, and luggage	Process enclosure; general dilution ventilation
Use in synthesis of dyes; use in manufacture of chemicals and chemical intermediates for production of insecticides, insect repellants, chemical reagents, urethane polymers, perfumes, and weed killers	Process enclosure; general dilution ventilation; personal protective equipment
Use in manufacture of pharmaceuticals and pharmaceutical intermediates; manufacture of metallic and acid salts; manufacture of epoxy resins as curing and hardening agents	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of fire retardants for use as components of polyester resins	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If phthalic anhydride gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid phthalic anhydride or liquids containing phthalic anhydride get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If solid phthalic anhydride or liquids containing phthalic anhydride penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of phthalic anhydride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When phthalic anhydride has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If phthalic anhydride is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Liquid containing phthalic anhydride should be absorbed in vermiculite, dry sand, earth, or a similar material for disposal in a secured sanitary landfill.

• Waste disposal methods:

Phthalic anhydride may be disposed of:

1. By making packages of phthalic anhydride in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving phthalic anhydride in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
3. Liquid containing phthalic anhydride should be absorbed in vermiculite, dry sand, earth, or a similar material and deposited in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Phthalic Anhydride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Phthalic Anhydride," *Hygienic Guide Series*, Detroit, Michigan, 1967.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Industrial Bio-Test Laboratories: *Phthalic Anhydride.*

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-61, Phthalic Anhydride.* Washington, D.C., 1956.

• National Institute for Occupational Safety and Health: "Hazard Entry No. 161 — Phthalic Anhydride," *Hazard Process Index.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Shick, D., and Glick, D. (eds.): *Methods of Biochemical Analysis*, Vol. 32, Interscience, New York, 1974.

RESPIRATORY PROTECTION FOR PHTHALIC ANHYDRIDE

Condition	Minimum Respiratory Protection* Required Above 2 ppm
Particulate or Vapor Concentration	
100 ppm or 600 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1670 ppm or 10,000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1670 ppm or 10,000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Picric Acid

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $HOC_6H_2(NO_2)_3$
- Synonyms: 2,4,6-Trinitrophenol; lyddite; pertite; shimose; melinite
- Appearance and odor: Odorless yellow solid or paste.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for picric acid is 0.1 milligram of picric acid per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Picric acid can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed.

- **Effects of overexposure**

Exposure to picric acid dust and fume may cause eye and skin irritation. The dust and solutions of picric acid may cause an allergic skin rash. The skin and hair may be stained yellow. Inhalation of high concentrations of dust has caused unconsciousness, weakness, muscle pain, and kidney problems. Swallowing picric acid may cause a bitter taste, headache, dizziness, nausea, vomiting, and diarrhea. High doses may cause destruction of the red blood cells and damage to the kidneys and liver with blood in the urine. High doses such as these may color the skin and other tissues yellow and cause yellow tinted vision.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to picric acid.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to picric acid at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to picric acid may be at increased risk from exposure. Examination of the kidneys, liver, and blood should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney damage has been observed in humans exposed to picric acid, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Since liver damage has been observed in humans exposed to picric acid, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Picric acid dust causes sensitization dermatitis. This usually occurs on the face, especially around the mouth and the sides of the nose; the condition progresses from edema, through the formation of papules and vesicles, to ultimate desquamation. The skin and hair of workers handling picric acid are stained yellow. Inhalation of high concentrations of the dust by one worker caused temporary coma followed by weakness, myalgia, anuria, and later polyuria. Following ingestion of 2 to 5 g of picric acid, which has a bitter taste, there may be

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

headache, vertigo, nausea, vomiting, diarrhea, yellow coloration of the skin, hematuria, and albuminuria; high doses cause destruction of erythrocytes, hemorrhagic nephritis, and hepatitis. High doses which cause systemic intoxication will color all tissues yellow, including the conjunctiva and aqueous humor, and cause apparent yellow-tinted vision. Corneal injury has resulted from a splash of a solution of picric acid into the eyes; dust or fume may cause eye irritation which may be aggravated by sensitization.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 229.1
2. Boiling point (760 mm Hg): Greater than 300 C (572 F); explodes
3. Specific gravity (water = 1): 1.6 – 1.76
4. Vapor density (air = 1 at boiling point of picric acid): Not applicable
5. Melting point: 122 C (252 F)
6. Vapor pressure at 20 C (68 F): Much less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 1.4
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Explodes above 300 C (572 F)
2. Incompatibilities: Contact with copper, lead, zinc, and other metals (or with their salts) can form salts of picric acid that are initiators and much more sensitive to shock than picric acid itself. Shock-sensitive salts also include ammonium salts and calcium salts; the calcium salt may form when picric acid comes into contact with plaster or concrete.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving picric acid.
4. Special precautions: Protect from shock.

- **Flammability**

1. Flash point: 150 C (302 F) (closed cup)
2. Autoignition temperature: 300 C (572 F) (approx).
3. Impact sensitivity (minimum fall of a 2 kg weight to cause at least one explosion in ten trials): 82 cm
4. Explosion temperature (temperature required to cause explosion in 5 seconds): 322 C (612 F)
5. Flammable limits in air, % by volume: Data not available
6. Extinguishant: Water. Do not attempt to extinguish massive fires.

- **Warning properties**

The ILO states, "The effects of picric acid on the eyes include irritation, corneal injury and strange visual effects, e.g. yellow appearance of objects, and yellow colouring of the tissues." Grant also states that "picric acid dust or fumes cause irritation of the eyes of men and animals, and this may be aggravated by sensitization." No quantitative information is available concerning the air concentrations which produce these effects, however. Information is not available concerning the threshold of eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with a subsequent chemical analysis of the adsorption tube. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure picric acid may be used. An analytical method for picric acid is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing

necessary to prevent skin contact with solid picric acid or liquids containing picric acid, where skin contact may occur.

- If employees' clothing may have become contaminated with picric acid, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing which may have become contaminated with picric acid should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of picric acid from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the picric acid, the person performing the operation should be informed of picric acid's hazardous properties.
- Non-impervious clothing which becomes contaminated with picric acid should be removed promptly and not reworn until the picric acid is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where solid picric acid or liquids containing picric acid may contact the eyes.

SANITATION

- Workers subject to skin contact with solid picric acid or liquids containing picric acid should wash any areas of the body which may have contacted picric acid at the end of each work day.
- Skin that becomes contaminated with picric acid should be promptly washed or showered with soap or mild detergent and water to remove any picric acid.
- Eating and smoking should not be permitted in areas where solid picric acid or liquids containing picric acid is handled, processed, or stored.
- Employees who handle solid picric acid or liquids containing picric acid should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to picric acid may occur and control methods which may be effective in each case:

Operation	Controls
Use in munitions and explosives manufacturing	Material substitution; process enclosure; local exhaust ventilation; personal protective equipment
Use in synthesis of dyes and dye intermediates in textile industry; use in manufacture of medicinals; use in etching of metal on printing plates of copper, steel, or other metals	Material substitution; process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of pyrotechnics and compounds for pyrotechnics as color intensifiers and as an oxidizer in matches	Material substitution; process enclosure; local exhaust ventilation; personal protective equipment
Use as a chemical reagent in identification, isolation, and purification of other compounds; use in manufacture of colored glass; and in the manufacture of electric batteries	Material substitution; process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If picric acid or liquids containing picric acid get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If picric acid or liquids containing picric acid get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If picric acid or liquids containing picric acid penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of picric acid, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When picric acid or liquids containing picric acid have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to

vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If picric acid is spilled, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill.
3. Attempt to reclaim spilled material; however, do not sweep or burn unless this is supervised by explosive experts.

• Waste disposal method:

Picric acid may be disposed of only by explosives experts.

ADDITIONAL INFORMATION

To find additional information on picric acid, look up picric acid in the following documents:

• Medical Surveillance for Chemical Hazards

• Respiratory Protection for Chemical Hazards

• Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Picric Acid," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Harris, A. H., et al.: "Hematuria Due to Picric Acid Poisoning at a Naval Anchorage in Japan," *American Journal of Public Health*, 36:727-733, 1946.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, Vol. 2, McGraw-Hill, New York, 1971.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• Schwartz, L.: "Dermatitis from Explosives," *Journal of the American Medical Association*, 125:186-190, 1

• Sunderman, F. W., et al.: "Studies of the Effects of Ammonium Picrate on Man and Certain Experimental Animals," *Journal of Industrial Hygiene and Toxicology*, 27:241-248, 1945.

• von Oettingen, W. F.: *The Aromatic Amino and Nitro Compounds, Their Toxicity and Potential Dangers, A Review of the Literature*, Public Health Bulletin No. 271, U.S. Public Health Service, U.S. Government Printing Office, Washington, D.C., 1941.

RESPIRATORY PROTECTION FOR PICRIC ACID

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
0.5 mg/m³ or less	Any dust and mist respirator, except single-use.**
1 mg/m³ or less	Any dust and mist respirator, except single-use respirator or quarter-mask.**
	Any fume respirator or high efficiency particulate filter respirator.**
	Any supplied-air respirator.**
	Any self-contained breathing apparatus.**
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter.
	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 100 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Pival

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{14}H_{14}O_3$
- Synonyms: 2-Pivalyl-1,3-indandione; pivalyl; tert-butyl-valone; 2-pivaloyl-1,3-indandione; 1,3-dioxo-2-pivaloy-lindane; pindone
- Appearance and odor: The technical material, which is a 0.5% concentrate in an inert solid, is a bright yellow solid with almost no odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Pival is 0.1 milligram of Pival per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Pival may be absorbed by swallowing, or indirectly by inhalation, and is probably not significantly absorbed through the skin.

- **Effects of overexposure**

Pival causes no immediate symptoms. Swallowing Pival, particularly in repeated smaller doses, may cause generalized bleeding, such as nose bleeds, excessive bleeding of minor cuts, smoky urine, or black, tarry stools. A person may experience stomach and back pain one to several days after being exposed to Pival.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Pival.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Pival at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination, including a complete blood count: The effects of overexposure from Pival can be enhanced or mimicked in individuals who have blood disorders with bleeding tendencies or with diseases that cause internal bleeding, such as peptic ulcer. Also, those with chronic liver disease may be increased risk, as are those on therapeutic doses of anticoagulants.

—Prothrombin time: The principal action of Pival is to reduce the level of prothrombin, prolonging the prothrombin time. This test is critical to the monitoring of exposed employees.

2. Periodic Medical Examination: At three months from the first exposure and annually thereafter, the employer should make available to the employee medical procedures listed under the preplacement examination. Also, if an employee develops signs or symptoms associated with Pival exposure at any time during employment, the employer should provide medical examinations to the employee.

- **Summary of toxicology**

Pival is a vitamin K antagonist, inhibiting prothrombin formation. Since repeated doses have a cumulative effect, a toxic concentration may be reached after several days of exposure to small doses. In rats, the ingestion of a single large dose of Pival causes rapid death due to pulmonary and visceral congestion without hemorrhage and may not be related to vitamin K antagonism. Death in animals from chronic exposure is due to multiple internal hemorrhage.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 230
2. Boiling point (760 mm Hg): Data not available

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1130

3. Specific gravity (water = 1): 1.06
4. Vapor density (air = 1 at boiling point of Pival): Data not available
5. Melting point: 110 C (230 F)
6. Vapor pressure at 20 C (68 F): Data not available
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0018
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Very high temperatures
2. Incompatibilities: None known
3. Hazardous decomposition products: None known
4. Special precautions: None known

• **Flammability**

1. Not flammable

• **Warning properties**

Pival is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for Pival had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• If employees' clothing may have become contaminated with Pival, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with Pival should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of Pival from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the Pival, the person performing the operation should be informed of Pival's hazardous properties.

SANITATION

• Eating and smoking should not be permitted in areas where Pival is handled, processed, or stored.

• Employees who handle Pival should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Pival may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during mixing and packaging operations in pesticide formulations	Local exhaust ventilation; respiratory protective equipment; separation of food storage and eating area from work area
Liberation during mixing and blending of pesticide formulation with other materials (cereal bait, liquid, etc).	Local exhaust ventilation; respiratory protective equipment; separation of food storage and eating area from work area
Liberation during synthesis of substance; during use as an intermediate in pharmaceutical synthesis	Local exhaust ventilation; respiratory protective equipment; separation of food storage and eating area from work area
Liberation during container reclamation, process clean-up, etc.	Local exhaust ventilation; respiratory protective equipment; separation of food storage and eating area from work area

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If Pival gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Swallowing**

When Pival has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If Pival is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Pival may be disposed of:

1. By making packages of Pival in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving Pival in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Pival," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Beauregard, J. R., Tusing, T. W., and Hannal, R. F., "Toxicology and Antidotal Studies on 2-Pivalyl-1, 3-Indandione (Pival), an Anticoagulant Rodenticide," *Agricultural Food and Chemistry*, 3:2, pp. 124-127, February 1955.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Los Alamos Scientific Laboratory, unpublished documentation on respirator use recommendations, 1974.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• USDHEW: "Operational Memoranda on Economic Poisons," Public Health Service, Communicable Disease Center, Atlanta, Georgia, 1956, pp. 81-84.

RESPIRATORY PROTECTION FOR PIVAL

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
0.5 mg/m³ or less	Any dust and mist respirator, except single-use respirators.
1 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. Any high efficiency particulate filter respirator with a full facepiece.
100 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use respirators. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Soluble Platinum Salts (as Platinum)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all soluble platinum salts (as platinum). Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Sodium chloroplatinate

- Formula: $Na_2PtCl_6 \cdot 6H_2O$
- Synonyms: None
- Appearance and odor: Yellow-orange, odorless solid.

Ammonium chloroplatinate

- Formula: $(NH_4)_2PtCl_4$
- Synonyms: Ammonium hexachloroplatinate
- Appearance: Yellow-orange solid.

Platinum tetrachloride

- Formula: $PtCl_4$
- Synonyms: Platinum (IV) chloride
- Appearance: Brown-red crystals.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for soluble platinum salts is 0.002 milligram of soluble platinum salts (as platinum) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Soluble platinum salts can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Soluble platinum salts may cause irritation of the eyes, nose, and throat.

2. Long-term Exposure: Repeated exposure to soluble platinum salts may cause both respiratory and skin allergies. The respiratory reaction starts with sneezing and a runny nose. These effects may be followed by chest tightness, shortness of breath, blue discoloration of the skin, and wheezing. The skin reaction consists of an itchy red rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to soluble platinum salts.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to soluble platinum salts at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to soluble platinum salts would be expected to be at increased risk from exposure. Examination of the respiratory system should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Soluble platinum salts in the form of dusts and sprays cause asthma, skin sensitization, and eye irritation; elemental platinum does not produce these effects.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1134

Workers repeatedly exposed to platinum salts in concentrations of from 2 to 20 ug/m^3 of workroom air developed irritation of the nose and upper respiratory tract with sneezing and running of the eyes, leading to cough, chest tightness, asthmatic wheezing with dyspnea and cyanosis, which became progressively more severe with further exposure. A relative lymphocytosis is commonly present. Skin exposure results in contact dermatitis with pruritis and urticaria; an eczematous eruption often results. Some exposed individuals experience both dermal and respiratory effects due to sensitization; the majority of individuals exposed repeatedly to platinum salts develop some allergic symptoms. Removal from platinum salt exposure results in almost immediate relief of asthma; the dermatitis usually clears in 1 to 2 days but may be persistent. In the eyes, the dusts cause a burning sensation, lacrimation, and conjunctival hypermia sometimes associated with photophobia.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data—Sodium chloroplatinate**
  1. Molecular weight: 561.9
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): 2.5
  4. Vapor density (air = 1 at boiling point of soluble platinum salts): Not applicable
  5. Melting point. Loses water at 100 C (212 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 50
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Physical data—Ammonium chloroplatinate**
  1. Molecular weight: 443.9
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): 3.1
  4. Vapor density (air = 1 at boiling point of soluble platinum salts): Not applicable
  5. Melting point: Decomposes
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.7
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Physical data—Platinum tetrachloride**
  1. Molecular weight: 336.9
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): 4.3
  4. Vapor density (air = 1 at boiling point of soluble platinum salts): Not applicable
  5. Melting point: Decomposes at 370 C (698 F)
  6. Vapor pressure at 20 C (68 F): Not applicable
  7. Solubility in water, g/100 g water at 25 C (77 F): 58.7
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: High temperatures may cause formation of poisonous chlorine gas.
  2. Incompatibilities: None
  3. Hazardous decomposition products: Toxic gases and vapors (such as chlorine) may be released when chlorine-containing soluble platinum salts decompose.
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Grant reports that "the dusts of soluble platinum salts cause a burning sensation in the eyes, lacrimation, and conjunctival hyperemia, sometimes associated with photophobia, which suggests that the corneal epithelium may be involved." However, no quantitative information concerning the concentrations of the dusts which produce these symptoms is given.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of soluble platinum salts on a filter, followed by treatment with nitric and perchloric acids, solution in acid, and atomic absorption analysis. An analytical method for soluble platinum salts is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).
(order number PB 265 029).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforce-

ment and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with soluble platinum salts or liquids containing soluble platinum salts, where skin contact may occur.

• If employees' clothing may have become contaminated with soluble platinum salts or liquids containing soluble platinum salts, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with soluble platinum salts should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of soluble platinum salts from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the soluble platinum salts, the person performing the operation should be informed of soluble platinum salts's hazardous properties.

• Non-impervious clothing which becomes contaminated with soluble platinum salts should be removed promptly and not reworn until the soluble platinum salts are removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where soluble platinum salts or liquids containing soluble platinum salts may contact the eyes.

SANITATION

• Skin that becomes contaminated with soluble platinum salts should be promptly washed or showered to remove any soluble platinum salts.

• Eating and smoking should not be permitted in areas where soluble platinum salts or liquids containing soluble platinum salts are handled, processed, or stored.

• Employees who handle soluble platinum salts or liquids containing soluble platinum salts should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to soluble platinum salts may occur and control methods which may be effective in each case:

Operation	Controls
Use as catalysts in production of high octane gasoline; nitric and sulfuric acids; vinyl esters, petrochemicals, and pharmaceuticals	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use and re-use in reclamation of platinum ore; use in electroplating industry	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in photographic and related industries as a photographic paper sensitizer	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If soluble platinum salts or liquids containing soluble platinum salts get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If soluble platinum salts or liquids containing soluble platinum salts get on the skin, promptly flush the contaminated skin with water. If soluble platinum salts or liquids containing soluble platinum salts penetrate through the clothing, remove the clothing promptly and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of soluble platinum salts, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When soluble platinum salts or liquids containing soluble platinum salts have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Under-

stand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If soluble platinum salts or liquids containing soluble platinum salts are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquids containing soluble platinum salts should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Soluble platinum salts may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Platinum (Soluble Salts as Pt)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Campbell, F., et al.: "Dermal Irritancy of Metal Compounds," *Archives of Environmental Health*, 30:168-170, April 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• Levene, G. M.: "Platinum Sensitivity," *British Journal of Dermatology*, 85:590-593, 1971.

• Parrot, J. L., et al.: "Platinum and Platinosis - Allergy and Histamine Release Due to Some Platinum Salts," *Archives of Environmental Health*, 19:685-691, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

RESPIRATORY PROTECTION FOR SOLUBLE PLATINUM SALTS (AS PLATINUM)

Condition	Minimum Respiratory Protection* Required Above 0.002 mg/m³
Particulate Concentration	
0.1 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter and a full facepiece, helmet, or hood.
4 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 4 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Portland Cement

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Typically mixture of: 2 $CaO\text{-}SiO_2$, 3 $CaO\text{-}Al_2O_3$, 3 $CaO\text{-}SiO_2$, 4 $CaO\text{-}Al_2O_3\text{-}Fe_2O_3$
- Synonyms: Hydraulic cement; cement
- Appearance and odor: Odorless gray powder containing less than 1% crystalline silica.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Portland cement is 50 million particles of Portland cement per cubic foot of air (mppcf) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended that the permissible exposure limit be reduced to 30 mppcf.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Portland cement can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to Portland cement may cause irritation of the eyes, nose, and skin. It may cause chronic irritation of the eyes, nose ulcers, and skin rashes. Allergic skin rashes may also occur. Repeated exposure over a long period to time to cement dust has produced x-ray changes of the lungs and an increased amount of wheezing, shortness of breath, and cough with sputum Exposure for a long period of time to very high concentrations of Portland cement may cause cough with phlegm.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Portland cement.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Portland cement at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory tract and eyes should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Portland cement mixtures have been reported to cause x-ray changes. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Portland cement mixtures may cause signs of respiratory impairment. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Portland cement dust irritates the eyes and causes dermatitis. There are reports of increased incidence of bronchitis and chest x-ray changes after prolonged heavy exposure to undefined mixtures of cement and other dusts. Exposure to cement can cause chronic conjunctivitis, blepharitis, and ulcers of the nose. Repeated and prolonged skin contact with cement can result in dermatitis of the hands, forearms, and feet; this is a primary irritant dermatitis and may be complicated in some instances by a secondary contact sensitivity to

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1109

hexavalent chromium. In a study of 95 cement workers, 15 had a mild dermatitis of the hands, which consisted of xerosis with erythema and mild scaling; 20 workers had a more active disorder manifested by eczematous lesions with vesicles, erythema, and fissures; when all 95 workers were patch tested with 0.25% potassium dichromate, one person had a mild reaction and the others were negative. In one survey of 2278 cement workers, it was concluded that exposure to finished Portland cement caused no significant findings on chest roentgenograms even after heavy and prolonged exposures. However, in a follow-up study of 195 of these workers after further exposure of 17 to 20 years, 13 showed increases in lung markings on roentgenograms; an additional 6 workers, who had been exposed largely to raw dusts which contained varying amounts of free silica, had marked linear exaggeration with ill-defined micronodular shadows, but no symptoms referable to the chest. In contrast, a more recent study of 847 cement workers with at least 5 years of exposure to levels ranging from 14 to 3020 mppcf in cement plants revealed that symptoms such as cough, expectoration, exertional dyspnea, wheezing, and chronic bronchitis syndromes were consistently more frequent than in a group of 460 control workers; a higher prevalance of these symptoms was also found in nonsmokers exposed to cement than in a control group of nonsmokers.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: Variable
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): Much greater than 1
  4. Vapor density (air = 1 at boiling point of Portland cement): Not applicable
  5. Melting point: Not applicable
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Grant states that Portland cement "is a fine, gray, alkaline powder which is made by firing a mixture of limestone, alumina, and silica. It is mixed with water, sand, and stones to make concrete. While this mixture is still fluid or plastic, it is sufficiently alkaline to injure the corneal epithelium. A splash in the eye causes smarting and burning sensation, and induces corneal edema. The victim may immediately see colored rings or haloes about lights. Superficial injuries of the conjuctiva may also occur.

"Portland cement or concrete is not as dangerous as mortar, which contains a greater amount of free calcium hydroxide (lime) and is more strongly alkaline. Splashes of mortar cause 'lime burns,' which may be very severe if irrigation is not performed promptly. After concrete or mortar have been mixed and set, they slowly become less alkaline and less apt to cause chemical injury of the eye.

"In one instance, squamous carcinoma in the conjunctiva and epithelioma of the cornea developed two years after slight injuries of the conjunctiva by cement particles, but the relationship was uncertain."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for Portland cement had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch

minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with powdered Portland cement or liquids containing Portland cement.

• Non-impervious clothing which becomes contaminated with Portland cement should be removed promptly and not reworn until the Portland cement is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where powdered Portland cement or liquids containing Portland cement may contact the eyes.

SANITATION

• Skin that becomes contaminated with powdered Portland cement or liquids containing Portland cement should be promptly washed or showered with soap or mild detergent and water to remove any Portland cement.

• Eating and smoking should not be permitted in areas where powdered Portland cement is handled, processed, or stored.

• Employees who handle powdered Portland cement or liquids containing Portland cement should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Portland cement may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from manufacture, mixing, and transfer of concretes	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of mortars for building blocks, bricks, stone, and pre-cast items; as a moisture sealant for exterior of concrete blocks	Process enclosure; local exhaust ventilation; personal protective equipment
Use in concrete on highway paving; domestic and commercial building construction; use in pre-cast concrete articles; use in construction of agricultural stone; use in light-weight concrete, terrazzo, stucco, asbestos cement products, gas and foamed concretes, interior surfaces, and exterior surfaces	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If powdered Portland cement or liquids containing Portland cement get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If powdered Portland cement or liquids containing Portland cement get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If powdered Portland cement or liquids containing Portland cement penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of Portland cement, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When Portland cement has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If Portland cement is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Portland cement may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Portland Cement," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kalacic, I.: "Chronic Nonspecific Lung Disease in Cement Workers," *Archives of Environmental Health*, 26:78-83, 1973.

• Kalacic, I.: "Ventilatory Lung Function in Cement Workers," *Archives of Environmental Health*, 26:84-85, 1973.

• Perone, V. B., et al.: "The Chromium, Cobalt, and Nickel Contents of American Cement and Their Relationship to Cement Dermatitis," *American Industrial Hygiene Association Journal*, 35:301-306, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sander, O. A.: "Roentgen Resurvey of Cement Workers," *A.M.A. Archives of Industrial Health*, 17:96-103, 1958.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Zenz, C.: *Occupational Medicine - Principles and Practical Applications*, Year Book Publishers Company, Inc Chicago, 1975.

RESPIRATORY PROTECTION FOR PORTLAND CEMENT

Condition	Minimum Respiratory Protection* Required Above 50 mppcf
Particulate Concentration	
250 mppcf or less	Any dust respirator.
500 mppcf or less	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
2500 mppcf or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
25,000 mppcf or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 25,000 mppcf or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Propane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CH_2CH_3$
- Synonyms: Dimethylmethane
- Appearance and odor: Colorless, odorless gas (a foul-smelling odorant is usually added).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for propane is 1000 parts of propane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 1800 milligrams of propane per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Propane can affect the body if it is inhaled.

- **Effects of overexposure**

Overexposure to propane may cause dizziness, disorientation, and excitation. Greater exposure may cause unconsciousness and death. Contact with liquefied propane may cause a freezing injury or frostbite.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to propane.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to propane at potentially hazardous levels.

- **Summary of toxicology**

Propane, a gas at ordinary temperatures, is an asphyxiant in very high concentrations. Guinea pigs exposed to concentrations of up to 5.5% propane by volume (55,000 ppm) for 1 to 2 hours showed tremors after 5 minutes, then nausea, retching and stupefaction; all survived and at autopsy had no significant tissue damage. Brief exposures to 10,000 ppm caused no symptoms in human subjects; 100,000 ppm produced slight dizziness in a few minutes of exposure but was not noticeably irritating to the eyes, nose, or respiratory tract. In the very few reports of accidental overexposure, there was disorientation, excitation, excessive salivation, headache, and vomiting. Liquid propane may cause frostbite.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 44.1
2. Boiling point (760 mm Hg): −42.1 C (−43.7 F)
3. Specific gravity (water = 1): 0.5 (liquid)
4. Vapor density (air = 1 at boiling point of propane): 1.6
5. Melting point: −187.7 C (−305.8 F)
6. Vapor pressure at 20 C (68 F): 8.6 atm.
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving propane.
4. Special precautions: Liquid propane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: Not applicable (gas)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1201

2. Autoignition temperature: 450 C (842 F)

3. Flammable limits in air, % by volume: Lower: 2.2; Upper: 9.5

4. Extinguishant: Stop flow of gas.

• **Warning properties**

1. Odor Threshold: Patty reports that the odor threshold of propane is 20,000 ppm.

2. Irritation Levels: According to Patty, exposure to concentrations as high as 100,000 ppm "is not noticeably irritating to the eyes, nose, or respiratory tract."

3. Evaluation of Warning Properties: Propane has poor warning properties. The odor threshold is 20 times the permissible exposure limit, and no noticeable irritation is produced at a concentration 100 times the permissible exposure limit.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by utilizing a combustible gas meter. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure propane may be used. An analytical method for propane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid propane or from contact with vessels containing liquid propane.

• Any clothing which becomes wet with liquid propane should be removed immediately and not reworn until the propane has evaporated.

• Employees should be provided with and required to use splash-proof safety goggles where liquid propane may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to propane may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from use as a component of liquid petroleum gas for commercial and industrial usage	General dilution ventilation
Use as feedstock in cracking process in production of ethylene and propylene and motor gasoline with high antiknock properties and stability	Process enclosure; general dilution ventilation
Use as a basic material in chemical synthesis for oxidation, alkylation, nitration, and chlorination	Process enclosure; general dilution ventilation
Use as a solvent and extractant in de-asphalting and degreasing of crude oils in production of lubricating oils, refining of fish and vegetable oils, extraction of oils from agricultural products, and segregate of specialty oils	Process enclosure; general dilution ventilation

Use as a refrigerant in chemical, petroleum refining, and gas processing operations, low-temperature crystallizers, and helium recovery from natural gas	Process enclosure; general dilution ventilation
Use as a fuel in welding and cutting operations; use in high-grade metallurgical work in which sulfur-free fuel is essential	General dilution ventilation
Use in oil wells to increase production of crude oil	Process enclosure
Use in desalination of water; use in hydrocarbon-fueled cells as source of power (experimental)	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquefied propane gets into the eyes, flush eyes immediately with large amounts of water. Do not use hot water for eye flushing. Get medical attention immediately.

- **Skin Exposure**

If liquefied propane gets on the skin, immediately flush the contaminated skin with water. If liquefied propane soaks through the clothing, remove the clothing immediately and flush the skin with water. Do not use hot water for skin flushing. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of propane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.
- If propane is leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of leak.
3. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

- Waste disposal method:

Propane may be disposed of by burning at a safe location or in a suitable combustion chamber.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Propane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Underwriters' Laboratories: *Propane*.

RESPIRATORY PROTECTION FOR PROPANE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
20,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 20,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

1207

Occupational Health Guideline for n-Propyl Acetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3COOCH_2CH_2CH_3$
- Synonyms: Propyl acetate; acetic acid n-propyl ester
- Appearance and odor: Colorless liquid with a mild, fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for n-propyl acetate is 200 parts of n-propyl acetate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 840 milligrams of n-propyl acetate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

n-Propyl acetate can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to n-propyl acetate may cause irritation of the eyes, nose, and throat. Severe overexposure may cause weakness, drowsiness, and unconsciousness.

2. Long-term Exposure: Prolonged overexposure may produce irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to n-propyl acetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to n-propyl acetate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from n-propyl acetate exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of n-propyl acetate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: n-Propyl acetate is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although n-propyl acetate is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although n-propyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The toxicologic effects of n-propyl acetate are chiefly irritation of the conjunctiva and upper respiratory tract, followed by narcosis. Cats exposed to 5300 ppm for 6 hours daily showed eye irritation and salivation; at 24,500 ppm there was narcosis and death. No chronic systemic effects have been reported in humans.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1208

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 102
  2. Boiling point (760 mm Hg): 101.6 C (215 F)
  3. Specific gravity (water = 1): 0.89
  4. Vapor density (air = 1 at boiling point of n-propyl acetate): 3.5
  5. Melting point: −95 C (−140 F)
  6. Vapor pressure at 20 C (68 F): 25 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 2
  8. Evaporation rate (butyl acetate = 1): 2.75
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalies, and strong acids may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving n-propyl acetate.
  4. Special precautions: n-Propyl acetate will dissolve many plastics and resins.
- **Flammability**
  1. Flash point: 14 C (58 F) (closed cup)
  2. Autoignition temperature: 450 C (842 F)
  3. Flammable limits in air, % by volume: Lower: 2; Upper: 8
  4. Extinguishant: Dry chemical, carbon dioxide, alcohol foam
- **Warning properties**
  1. Odor Threshold: According to the *Handbook of Organic Industrial Solvents*, the odor of n-propyl acetate is detectable at the permissible exposure limit.
  2. Eye Irritation Level: The *Handbook of Organic Industrial Solvents* states that n-propyl acetate "causes irritation of mucous membranes at the threshold limit."
  3. Evaluation of Warning Properties: Through its odor and irritant effects, n-propyl acetate can be detected at the TLV. For the purposes of this guideline, therefore, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of n-propyl acetate vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure n-propyl acetate may be used. An analytical method for n-propyl acetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid n-propyl acetate.
- Clothing wet with liquid n-propyl acetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of n-propyl acetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the n-propyl acetate, the person performing the operation should be informed of n-propyl acetate's hazardous properties.
- Any clothing which becomes wet with liquid n-propyl acetate should be removed immediately and not reworn until the n-propyl acetate is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid n-propyl acetate may contact the eyes.

SANITATION

- Skin that becomes wet with liquid n-propyl acetate should be promptly washed or showered with soap or

mild detergent and water to remove any n-propyl acetate.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to n-propyl acetate may occur and control methods which may be effective in each case:

Operation	Controls
Use in spray, brush, or dip application of lacquers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during application of adhesives; manufacture of lacquers and adhesives	Local exhaust ventilation; general dilution ventilation
Use as a solvent for rubber; during application of solvent for plastics, nitrocellulose, and cellulosic derivatives and resins; during brush or dip applications of lacquers; during preparation of flavoring agents and perfumes	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If n-propyl acetate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If n-propyl acetate gets on the skin, promptly flush the contaminated skin with water. If n-propyl acetate soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

- **Breathing**

If a person breathes in large amounts of n-propyl acetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When n-propyl acetate has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the affected person to vomit by having him touch the back of the throat with his finger or by giving him large amounts (one pint or more) of warm salt water (two tablespoons of salt per pint of water). Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If n-propyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. n-Propyl acetate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

- Waste disposal methods:

n-Propyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "n-Propyl Acetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – n-Propyl Acetate*, New York, 1965.
• von Oettingen, W. F.: "The Aliphatic Acids and Their Esters: Toxicity and Potential Dangers," *A.M.A. Archives of Industrial Health*, 21:28-65, 1960.

RESPIRATORY PROTECTION FOR N-PROPYL ACETATE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
8000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 8000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Propyl Alcohol

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CH_2CH_2OH$
- Synonyms: n-Propyl alcohol; 1-propanol; ethyl carbinol
- Appearance and odor: Colorless liquid with a mild, non-residual, alcoholic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for propyl alcohol is 200 parts of propyl alcohol per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 500 milligrams of propyl alcohol per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Propyl alcohol can affect the body if it is swallowed, is inhaled, or comes in contact with the skin or eyes.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to high air concentrations of propyl alcohol may cause mild irritation of the eyes, nose, and throat. Drowsiness, headaches, and incoordination may also occur. Swallowing propyl alcohol may cause drowsiness, unconsciousness, and death. Gastrointestinal pain, cramps, nausea, vomiting, and diarrhea may also result from swallowing this alcohol.

2. Long-term Exposure: Prolonged skin exposure may cause drying and cracking of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to propyl alcohol.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to propyl alcohol at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from propyl alcohol exposure.

—Skin disease: Propyl alcohol is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although propyl alcohol is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although propyl alcohol is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of propyl alcohol might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The principal action of propyl alcohol is that of a mild narcotic, but it may also act as an upper respiratory tract irritant. Mice exposed to vapor developed ataxia in 90 to 120 minutes at 3250 ppm; deep narcosis occurred after 240 minutes' exposure at 4100 ppm. Propyl alcohol is absorbed, oxidized, and eliminated more rapidly than

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1212

is ethyl alcohol. Skin absorption has been demonstrated in animals, as well as mild irritation of the skin on repeated exposure due to defatting action. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 60
  2. Boiling point (760 mm Hg): 97 C (207 F)
  3. Specific gravity (water = 1): 0.8
  4. Vapor density (air = 1 at boiling point of propyl alcohol): 2.1
  5. Melting point: −126 C (−195 F)
  6. Vapor pressure at 20 C (68 F): 15 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 1.3
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving propyl alcohol.
  4. Special precautions: Propyl alcohol will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 15 C (59 F) (closed cup)
  2. Autoignition temperature: 440 C (824 F)
  3. Flammable limits in air, % by volume: Lower: 2.1; Upper: 13.5
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Both Summer and May report odor thresholds of 30 ppm.
  2. Eye Irritation Level: n-Propyl alcohol, according to Grant, resembles "ethyl alcohol in physical and toxic properties." Grant states that a vapor concentration of 2500 ppm has "no notable effect on the eyes." The AIHA *Hygienic Guide* notes that above 5500 ppm, some eye and nasal irritation occur.
  3. Evaluation of Warning Properties: Since the odor threshold of n-propyl alcohol is below the permissible exposure limit (200 ppm), it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of propyl alcohol vapors using an adsorption tube with subsequent desorption with 2-propanol in carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure propyl alcohol may be used. An analytical method for propyl alcohol is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

number PB 246 148).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid propyl alcohol.
- Clothing wet with liquid propyl alcohol should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of propyl alcohol from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the propyl alcohol, the person performing the operation should be informed of propyl alcohol's hazardous properties.
- Any clothing which becomes wet with liquid propyl alcohol should be removed immediately and not reworn until the propyl alcohol is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid propyl alcohol may contact the eyes.

SANITATION

• Skin that becomes wet with liquid propyl alcohol should be promptly washed or showered to remove any propyl alcohol.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to propyl alcohol may occur and control methods which may be effective in each case:

Operation	Controls
Liberation and use during spray application of surface coatings containing solvent, polystyrene coatings, and dopes	Local exhaust ventilation; personal protective equipment
Liberation during use as a chemical intermediate in organic synthesis	Local exhaust ventilation; general dilution ventilation
Use during printing on plastic film and sheeting with polyamide-based inks	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during textile and leather processing	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in application of surface coatings other than spray or heat in nitrocellulose lacquers, dopes, and polystyrene coatings	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture and packaging of surface coatings as a solvent in nitrocellulose lacquers, dopes, polystyrene coatings, inks, dyes, textiles, leather finishes, and artists' fixatives; manufacture of cleaning preparations and polishing agents	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in extraction of vegetable oils, castor oil, and pharmaceuticals; use during cleaning and degreasing operations	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during cellulose processing; spinning of acrylonitrile; manufacture of brake fluids	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If propyl alcohol gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If propyl alcohol gets on the skin, flush the contaminated skin with water. If propyl alcohol soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of propyl alcohol, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When propyl alcohol has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If propyl alcohol is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.

3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Propyl alcohol should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Propyl alcohol may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Propyl Alcohol," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Propyl Alcohol," *Hygienic Guide Series*, Detroit, Michigan, 1961.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Propyl Alcohol*, New York, 1972.

RESPIRATORY PROTECTION FOR PROPYL ALCOHOL

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
1000 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).
2000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
4000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 4000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for n-Propyl Nitrate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_3H_8NO_3$
- Synonyms: None
- Appearance and odor: Colorless to pale yellow liquid with an ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for n-propyl nitrate is 25 parts of n-propyl nitrate per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 110 milligrams of n-propyl nitrate per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

n-Propyl nitrate can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Animal studies show that n-propyl nitrate causes temporary low blood pressure and may affect the ability of the blood to carry oxygen by forming methemoglobin. In man, methemoglobin formation may cause bluish discoloration of the skin, headache, weakness, drowsiness, nausea, rapid heart beat, shortness of breath, and unconsciousness.

2. Long-term Exposure: In animals repeated or prolonged exposure to n-propyl nitrate has caused irritation and thickness of the skin. It may also cause anemia.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to n-propyl nitrate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to n-propyl nitrate at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, cardiovascular system, skin, nervous system, and kidneys should be stressed.

—A complete blood count: n-Propyl nitrate has been shown to cause methemoglobinemia in animals. Persons with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determinations should be performed if overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

n-Propyl nitrate vapor causes anoxia due to the formation of methemoglobin. Exposure of rats to 10,000 ppm for 4 hours caused nasal irritation, dyspnea, methemoglobinemia, weakness, cyanosis, and death. In dogs repeatedly exposed to 260 ppm for 26 weeks, hemoglobinuria and mild anemia appeared during the first 2 weeks of exposure but then subsided. n-Propyl nitrate may induce hypotension in animals by direct action on vascular muscles. The liquid when placed into the eyes of rabbits caused mild transient inflammation with no evidence of corneal damage. The liquid applied to the skin of rabbits daily for 10 days caused staining, inflam-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1217

mation, and thickening of the skin but no evidence of systemic toxicity. n-Propyl nitrate has the potential to form methemoglobin in man; the effects of methemoglobinemia result from anoxia and include cyanosis especially evident in the lips, nose, and ear lobes; other effects are weakness, dizziness, and severe headache.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 105.1
  2. Boiling point (760 mm Hg): 111 C (231 F)
  3. Specific gravity (water = 1): 1.06
  4. Vapor density (air = 1 at boiling point of n-propyl nitrate): 3.6
  5. Melting point: Less than −101 C (−150 F)
  6. Vapor pressure at 20 C (68 F): 18 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with either strong oxidizers or with combustibles may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving n-propyl nitrate.
  4. Special precautions: n-Propyl nitrate will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 20 C (68 F) (closed cup)
  2. Autoignition temperature: 175 C (347 F)
  3. Flammable limits in air, % by volume: Lower: 2; Upper: 100
  4. Extinguishant: Foam, dry chemical
- **Warning properties**
  1. Odor Threshold: According to the *Documentation of TLV's*, "the odor is stated to be detectable at 50 ppm and above."
  2. Eye Irritation Level: n-Propyl nitrate is not known to be an eye irritant.
  3. Evaluation of Warning Properties: Since its odor threshold is only twice the permissible exposure limit, n-propyl nitrate is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure n-propyl nitrate may be used. An analytical method for n-propyl nitrate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid n-propyl nitrate.
- Clothing wet with n-propyl nitrate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of n-propyl nitrate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the n-propyl nitrate, the person performing the operation should be informed of n-propyl nitrate's hazardous properties.
- Non-impervious clothing which becomes contaminated with n-propyl nitrate should be removed promptly and any clothing which becomes wet with liquid n-propyl nitrate should be removed immediately and not reworn until the n-propyl nitrate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid n-propyl nitrate may contact the eyes.

SANITATION

• Skin that becomes contaminated with n-propyl nitrate should be promptly washed or showered with soap or mild detergent and water to remove any n-propyl nitrate.
• Employees who handle liquid n-propyl nitrate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to n-propyl nitrate may occur and control methods which may be effective in each case:

Operation	Controls
Use in liquid rocket propellants	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If liquid n-propyl nitrate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If liquid n-propyl nitrate gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid n-propyl nitrate soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention promptly.
• **Breathing**
If a person breathes in large amounts of n-propyl nitrate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When liquid n-propyl nitrate has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If n-propyl nitrate is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, stir with a solution of sodium hydroxide or soda ash in water until oily layer disappears, then flush. Large quantities can be burned under the supervision of personnel qualified to dispose of explosives. Liquid n-propyl nitrate should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed tc preclude the formation of explosive concentrations of n-propyl nitrate vapors are permitted.
• Waste disposal method:
n-Propyl nitrate may be disposed of as described above.

REFERENCES

• Acme Company: *Protection Guide – n-Propyl Nitrate.*
• American Conference of Governmental Industrial Hygienists: "n-Propyl Nitrate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Boysen, J. E.: "Health Hazards of Selected Rocket Propellants," *Archives of Environmental Health*, 7:77-81, 1963.
• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.
• Hood, D. B.: "Toxicity of n-Propyl Nitrate and Isopropyl Nitrate," Haskell Laboratory for Toxicology and Industrial Medicine Report No. 21-53, E. I. duPont de Nemours and Company, Wilmington, Delaware, 1953.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.
• Murtha, E. F., et al.: "Some Pharmacological Effects of N-Propyl Nitrate," *Journal of Pharmacology and*

Experimental Therapeutics, 118:77-83, 1956.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Rinehart, W. E., et al.: "Studies on the Toxicity of n-Propyl Nitrate Vapor," *American Industrial Hygiene Association Journal*, 19:80-83, 1958.

RESPIRATORY PROTECTION FOR N-PROPYL NITRATE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
250 ppm or less	Any chemical cartridge respirator with a cartridge containing non-combustible sorbents and providing protection against n-propyl nitrate. Any supplied-air respirator. Any self-contained breathing apparatus.
1000 ppm or less	Any chemical cartridge respirator with a full facepiece and a cartridge containing non-combustible sorbents and providing protection against n-propyl nitrate. A gas mask with a chin-style or a front- or back-mounted canister containing non-combustible sorbents and providing protection against n-propyl nitrate. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
2000 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask containing non-combustible sorbents and providing protection against n-propyl nitrate. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

1220

Occupational Health Guideline for Propylene Dichloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3CHClCH_2Cl$
- Synonyms: 1,2-Dichloropropane
- Appearance and odor: Colorless liquid with an odor like chloroform.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for propylene dichloride is 75 parts of propylene dichloride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 350 milligrams of propylene dichloride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Propylene dichloride can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to propylene dichloride causes eye and skin irritation and may cause drowsiness or lightheadedness.

2. Long-term Exposure: Prolonged overexposure to propylene dichloride may affect the liver and kidneys.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to propylene dichloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to propylene dichloride at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from propylene dichloride exposure.

—Skin disease: Propylene dichloride can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Propylene dichloride is known as a liver toxin in animals and justifies consideration before exposing persons with impaired liver function.

—Kidney disease: Propylene dichloride is known as a kidney toxin in animals and justifies special consideration before exposing persons with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of propylene dichloride might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Propylene dichloride vapor is a narcotic and an eye irritant. At 2200 ppm for 7 hours, guinea pigs developed severe conjunctival swelling, as well as signs of respiratory irritation and incoordination; some died after 5 daily exposures, showing severe liver injury, some kidney injury, and occasional adrenal changes. Repeated inhalation of 1000 ppm caused some deaths among dogs after 24 exposures of 7 hours' duration, and among rats after only 7 exposures. There was early onset of lacrimation, eye irritation, and incoordination. Liver damage was the main finding in the animals that died. At 400 ppm, rats and guinea pigs exposed for up to 140

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1231

daily 7-hour exposures showed no ill effects and no histologic changes. However, of a group of C3H-strain mice exposed at 400 ppm, some died; others developed hepatomas, a finding of equivocal significance. Propylene dichloride is mildly irritating to human skin, and some skin absorption may occur from exposure to the liquid. The undiluted liquid is moderately irritating to the eyes but does not cause permanent injury.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 113
  2. Boiling point (760 mm Hg): 96.1 C (205 F)
  3. Specific gravity (water = 1): 1.16
  4. Vapor density (air = 1 at boiling point of propylene dichloride): 3.9
  5. Melting point: −100 C (−148 F)
  6. Vapor pressure at 20 C (68 F): 39.5 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.26
  8. Evaporation rate (butyl acetate = 1): Greater than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions. Strong acids may cause decomposition.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide and hydrogen chloride) may be released in a fire involving propylene dichloride.
  4. Special precautions: Propylene dichloride will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 15.6 C (60 F) (closed cup)
  2. Autoignition temperature: 557 C (1035 F)
  3. Flammable limits in air, % by volume (at 100 C): Lower: 3.4; Upper: 14.5
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports an odor threshold of 50 ppm. The AIHA *Hygienic Guide* states that "human subjects described the odor as 'strong' at 130 to 190 ppm and 'not noticeable' at 15 to 23 ppm."
  2. Eye Irritation Level: According to Grant, "exposure of guinea pigs to 2200 ppm in air for many hours until most were dead caused lacrimation and swelling of the lids and conjunctiva. To the extent that the corneas were left unprotected, bluish discoloration of the corneas and infection developed. Rabbits exposed to the same conditions showed little irritation." No quantitative information is available concerning the threshold of eye irritation. No ill effects have been observed in animals chronically exposed to 400 ppm.
  3. Evaluation of Warning Properties: Since the odor threshold of propylene dichloride is below the permissible exposure limit, this substance is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of propylene dichloride vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure propylene dichloride may be used. An analytical method for propylene dichloride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).
PB 265 026).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid propylene dichloride.
- Clothing wet with liquid propylene dichloride should be placed in closed containers for storage until it can be

discarded or until provision is made for the removal of propylene dichloride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the propylene dichloride, the person performing the operation should be informed of propylene dichloride's hazardous properties.

• Any clothing which becomes wet with liquid propylene dichloride should be removed immediately and not reworn until the propylene dichloride is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid propylene dichloride may contact the eyes.

SANITATION

• Skin that becomes wet with liquid propylene dichloride should be promptly washed or showered with soap or mild detergent and water to remove any propylene dichloride.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to propylene dichloride may occur and control methods which may be effective in each case:

Operation	Controls
Use as a soil fumigant for protection of fruit and nut crops, field crops, beets, and tobacco against nemotodes	Adequate ventilation; personal protective equipment
Use in cleaning, degreasing, and spot removal operations including paint and varnish removal	Local exhaust ventilation; personal protective equipment
Use during rubber compouding and vulcanizing operations	Local exhaust ventilation; personal protective equipment
Use during extraction processing of fats, oils, lactic acid, and petroleum waxes	Local exhaust ventilation; personal protective equipment
Use in the manufacture of tetrachloroethylene and propylene oxide	Local exhaust ventilation; personal protective equipment
Use as an additive and lead scavenger in antiknock fluids	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If propylene dichloride gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If propylene dichloride gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If propylene dichloride soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of propylene dichloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When propylene dichloride has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If propylene dichloride is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Propylene dichloride should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Propylene dichloride may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Propylene Dichloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Propylene Dichloride," *Hygienic Guide Series*, Detroit, Michigan, 1967.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Heppel, L. A., et al.: "Toxicology of 1, 2-Dichloropropane (Propylene Dichloride) I. Studies on Effects of Daily Inhalations," *Journal of Industrial Hygiene and Toxicology*, 28:1-8, 1946.

• Heppel, L. A., Highman, B., and Peake, E. G.: "Toxicology of 1,2-Dichloropropane (Propylene Dichloride) IV. Effects of Repeated Exposures to a Low Concentration of the Vapor," *Journal of Industrial Hygiene and Toxicology*, 30:189-191, 1948.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

RESPIRATORY PROTECTION FOR PROPYLENE DICHLORIDE

Condition	Minimum Respiratory Protection* Required Above 75 ppm
Vapor Concentration	
400 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).
	Any supplied-air respirator.
	Any self-contained breathing apparatus.
2000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Propylene Imine*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_6H_7N
- Synonyms: 2-Methylaziridine
- Appearance and odor: Fuming, colorless liquid with a strong, ammonia-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for propylene imine is 2 parts of propylene imine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 5 milligrams of propylene imine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Propylene imine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to propylene imine causes eye irritation.

2. Long-term Exposure: Repeated doses fed to animals have been shown to cause cancer.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to propylene imine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to propylene imine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, breasts, eyes, nervous system, and blood should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Propylene imine has been shown to cause granulocytic leukemia in rats repeatedly exposed to oral doses as little as 10 mg/kg. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Propylene imine vapor is a carcinogen in animals. This compound has also caused eye irritation. Exposure of rats to 500 ppm for 4 hours was fatal, but inhalation for 2 hours resulted in no deaths. Rats given 20 mg/kg by gavage twice weekly suffered from advanced flaccid paralysis after 18 weeks, and the mortality rate was high; at 10 mg/kg, paralysis occurred to a lesser extent after 30 weeks; granulocytic leukemia, squamous cell carcinoma of the ear duct, and brain tumors (glioma) were observed in different animals; females showed mammary adenocarcinomas, a number of which metastasized to the lung. When placed in the eye of a rabbit, a 5% aqueous solution produced corneal damage; it is also said to have caused injury to human eyes, but details have not been provided.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1225

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 57
2. Boiling point (760 mm Hg): 66 C (151 F)
3. Specific gravity (water = 1): 0.8
4. Vapor density (air = 1 at boiling point of propylene imine): 2
5. Melting point: −65 C (−85 F)
6. Vapor pressure at 20 C (68 F): Data not available
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat; contact with acids
2. Incompatibilities: Contact with acids will cause violent polymerization that may burst containers. Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving propylene imine.
4. Special precautions: Liquid propylene imine will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: −4 C (25 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, carbon dioxide, alcohol foam

- **Warning properties**

1. Odor Threshold: No quantitative information is available.
2. Eye Irritation Level: The ILO reports that "no industrial injuries (from propylene imine) have been reported, other than severe eye burns." According to Grant, the liquid "has caused severe damage when applied to rabbit eyes, similar in severity to 28% ammonium hydroxide." Patty reports that propylene imine causes acute effects which are similar to those caused by ethylene imine. Among the acute effects produced by ethylene imine are eye, nose, and throat irritation. For the purposes of this guideline, therefore, propylene imine is treated as an eye irritant.
3. Evaluation of Warning Properties: Since there are no available quantitative data relating the warning properties of propylene imine to air concentrations, it is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for propylene imine had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid propylene imine, where skin contact may occur.
- Clothing contaminated with propylene imine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of propylene imine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the propylene imine, the person performing the operation should be informed of propylene imine's hazardous properties.
- Where exposure of an employee's body to liquid propylene imine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes wet with propylene imine or non-impervious clothing which becomes contaminated with propylene imine should be removed immediately and not reworn until the propylene imine is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid propylene imine contacting the eyes.
• Where there is any possibility that employees' eyes may be exposed to liquid propylene imine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with propylene imine should be immediately washed or showered to remove any propylene imine.
• Eating and smoking should not be permitted in areas where liquid propylene imine is handled, processed, or stored.
• Employees who handle liquid propylene imine should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to propylene imine may occur and control methods which may be effective in each case:

Operation	Controls
Use as a polymer modifier to improve physical properties of polymer; to improve wet adhesion, brushability and freeze-to-thaw stability of paints, improve shrink-proofing agents of woolen textiles, and improve electrical properties of wire-coating materials	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of polypropylene imines and polymers for coating materials, adhesives, chelating agents, emulsifying agents, and fire-proofing agents in textile, rubber, paint, ink, and paper industries	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a chemical intermediate in pharmaceutical and chemical industries	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If propylene imine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If propylene imine gets on the skin, immediately flush the contaminated skin with water. If propylene imine soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of propylene imine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When propylene imine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
• If propylene imine is spilled or leaked, the following steps should be taken:
1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Dilute with water spray until no longer flammable. Add 4% acetic acid (vinegar) solution to the diluted spill until vinegar odor of acid is present, and flush the diluted and neutralized spill. Liquid propylene imine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.
• Waste disposal and neutralization methods:
Propylene imine may be disposed of:
1. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. If larger quantities, by diluting with water, then adding acetic acid in excess of that required to neutralize the propylene imine.

ADDITIONAL INFORMATION

To find additional information on propylene imine, look up propylene imine in the following documents:

- Medical Surveillance for Chemical Hazards
- Respiratory Protection for Chemical Hazards
- Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Propylene Imine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
- Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.
- Smyth, H. F., et al.: "Further Experience with the Range-Finding Test in the Industrial Toxicology Laboratory," *Journal of Industrial Hygiene and Toxicology*, 30:1, p. 63, 1942.
- Ulland, B., et al.: "Carcinogenicity of Industrial Chemicals Propylene Imine and Propane Sultone," *Nature*, 230:460-461, 1971.

RESPIRATORY PROTECTION FOR PROPYLENE IMINE

Condition	Minimum Respiratory Protection* Required Above 2 ppm
Vapor Concentration	
100 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against propylene imine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Propylene Oxide *

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CH_3CHOCH_2
- Synonyms: 1,2-Epoxypropane; propene oxide; methyloxirane
- Appearance and odor: Colorless liquid with an ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for propylene oxide is 100 parts of propylene oxide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 240 milligrams of propylene oxide per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for propylene oxide from 100 ppm to 20 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Propylene oxide can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

Overexposure to propylene oxide may cause irritation of the eyes, nose, throat, and lungs. Contact with propylene oxide liquid may cause skin or eye irritation or burns.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to propylene oxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to propylene oxide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from propylene oxide exposure.

—Skin disease: Propylene oxide can cause dermatitis. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although propylene oxide is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although propylene oxide is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of propylene oxide might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Propylene oxide is a severe irritant and a mild depressant of the central nervous system. Excessive exposure of animals to vapors caused irritation of the eyes, upper respiratory tract, and lungs, as well as central nervous system effects characterized by ataxia, incoordination, and general depression. The LC50 for single exposures of rats was 3600 ppm, while 400 to 500 ppm was lethal

---

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

to some rats on repeated daily exposures. The predominant effect was lung irritation and infection. All animals tolerated repeated exposures of 100 ppm without effects. Reported adverse effects on man have been confined to injury to the eyes, and skin. The vapor is irritating to the eyes and the liquid causes corneal burns. When confined to the skin, as from wearing contaminated clothing or shoes, the material and water solutions as dilute as 10% are likely to cause irritation, blistering, and even burns upon single, short exposures. Some evidence indicates that solutions more dilute than 10% may be more irritating than the undiluted propylene oxide. No chronic systemic effects have been reported in humans.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 58
  2. Boiling point (760 mm Hg): 34 C (94 F)
  3. Specific gravity (water = 1): 0.83
  4. Vapor density (air = 1 at boiling point of propylene oxide): 2.0
  5. Melting point: −112 C (−170 F)
  6. Vapor pressure at 20 C (68 F): 442 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 40.5
  8. Evaporation rate (butyl acetate = 1): 33.7
- **Reactivity**
  1. Conditions contributing to instability: Heat; contact with acids and caustics
  2. Incompatibilities: Anhydrous metal chlorides such as iron or aluminum chloride, strong acids, caustics, and peroxides cause polymerization with liberation of heat.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving propylene oxide.
  4. Special precautions: Propylene oxide will attack some forms of plastics, rubber, and coatings. No acetylide-forming metals such as copper or copper alloys should be in contact with propylene oxide.
- **Flammability**
  1. Flash point: −37 C (−35 F) (closed cup)
  2. Autoignition temperature: 748 C (1378 F)
  3. Flammable limits in air, % by volume: Lower: 2.1; Upper: 37.0
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Patty states that "the median detectable concentration of propylene oxide vapors is reported to be 200 ppm with 95% confidence limits of 114 to 353 ppm. The odor is described as sweet, alcoholic, and like natural gas, ether, or benzene."
  2. Eye Irritation Level: Grant reports that "exposure of monkeys and rabbits to 457 ppm of vapor in air for 7 hours daily had no adverse effect, but in rats and guinea pigs it irritated the eyes and induced lung edema."

The AIHA *Hygienic Guide*, Patty, the *Documentation of TLV's*, and several other sources all note that propylene oxide causes eye irritation. However, no quantitative information is available, concerning the threshold of eye irritation.

3. Evaluation of Warning Properties: Patty states that "neither odor nor irritation can be relied upon to warn of the presence of vapor concentrations not suitable for prolonged and repeated exposure. Odor and/or irritation will warn of the presence of acutely dangerous concentrations." Since it appears that Patty considers any vapor concentrations above 100 ppm (the ACGIH threshold limit for 1961) "not suitable for prolonged and repeated exposure," propylene oxide is considered to have adequate warning properties for the purposes of this guideline. The median of the detectable odor concentrations (200 ppm) is only twice the permissible exposure limit. The chronic exposure data given in the *Documentation of TLV's* quoted below do not indicate that 200 ppm causes any toxic effects.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of propylene oxide vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure propylene oxide may be used. An analytical method for propylene oxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of

respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid propylene oxide.
- Clothing wet with liquid propylene oxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of propylene oxide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the propylene oxide, the person performing the operation should be informed of propylene oxide's hazardous properties.
- Where there is any possibility of exposure of an employee's body to liquid propylene oxide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with liquid propylene oxide or any clothing which becomes wet with liquid propylene oxide should be removed immediately and such clothing should not be reworn until the propylene oxide is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid propylene oxide may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid propylene oxide should be immediately washed or showered to remove any propylene oxide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to propylene oxide may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of polypropylene glycol and polyether polyols in production of polyurethane foam; manufacture of propylene glycol for use as a solvent, emulsifier, and mold inhibitor; manufacture of dipropylene glycol for use as a solvent, ink formulations, and glycol esters for solvents, oil additives, and hydraulic brake fluids	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a chemical intermediate in the production of lubricants, surfactants, and miscellaneous chemicals for pharmaceutical, petroleum, textile, rubber, and soap industries	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a low-boiling solvent for cellulose derivatives, hydrocarbons, commercial gums, and various resins	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a fumigant (moth-proofing agent), herbicide, germicide, insecticide, and stabilizer of vinyl resin lacquers and discoloration preventer of hydrocarbons	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a food preservative as a fungicide and fumigant	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during hydroxypropylating of wheat flour in order to modify it to mix readily with water	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If propylene oxide gets into the eyes, wash eyes immediately with large amounts of water for 15 minutes, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If propylene oxide gets on the skin, immediately wash the contaminated skin with water if propylene oxide has not already evaporated. If propylene oxide soaks through the clothing, remove the clothing immediately and flush the skin with water. If there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of propylene oxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If propylene oxide has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If propylene oxide is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities may be collected, dissolved in alcohol of greater molecular weight than butyl alcohol, and atomized in a suitable combustion chamber. Propylene oxide should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Propylene oxide may be disposed of by dissolving in alcohol of greater molecular weight than butyl alcohol and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Propylene Oxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Propylene Oxide," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Dow Chemical Company: "Alkylene Oxides from Dow," *Product Bulletin*, Midland, Michigan, 1963.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Propylene Oxide*, New York, 1971.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 11, 1976.

RESPIRATORY PROTECTION FOR PROPYLENE OXIDE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
2000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2000 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of propylene oxide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 2000 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Pyrethrum

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: The synonyms and molecular weights listed below correspond to the various components of pyrethrum whose formulas are listed here: 1) $C_{21}H_{28}O_3$; 2) $C_{22}H_{28}O_5$; 3) $C_{20}H_{28}O_3$; 4) $C_{21}H_{28}O_5$; 5) $C_{21}H_{30}O_3$; 6) $C_{23}H_{30}O_5$
- Synonyms: 1) Pyrethrin I; 2) Pyrethrin II; 3) Cinerin I; 4) Cinerin II; 5) Jasmolin I; 6) Jasmolin II
- Appearance and odor: Viscous brown resin or solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for pyrethrum is 5 milligrams of pyrethrum per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Pyrethrum can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

The chief effect from exposure to pyrethrum is skin rash particularly on moist areas of the skin. The rash may be associated with intense itching and blister formation. Hay fever-like symptoms, wheezing, and breathing difficulties may occur from exposure to this chemical. An allergic reaction causing weakness and collapse may occur in sensitive individuals. Pyrethrum may irritate the eyes. In animals, effects of intoxication include convulsions and paralysis.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to pyrethrum.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to pyrethrum at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from pyrethrum exposure.

—Chronic respiratory disease: In persons with chronic respiratory disease and especially asthma, the inhalation of pyrethrum might cause exacerbation of symptoms due to its sensitizing properties.

—Skin disease: Pyrethrum can cause dermatitis which may be allergic in nature. Persons with preexisting skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Pyrethrum dust causes dermatitis and occasionally sensitization. In animals, effects of intoxication are excitation, convulsions, muscular fasciculations, and tetanic paralysis. The chief effect in humans from exposure to pyrethrum is dermatitis. The usual lesion is a mild erythematous dermatitis with vesicles, papules in moist areas, and intense pruritis; a bullous dermatitis may develop. In a study of workers engaged in processing pyrethrum powder, 30% had erythema, skin roughening, and pruritis which subsided upon cessation of exposure. One of these workers had an anaphylactic type reaction; shortly after entering a dust laden room, the facial skin turned red and the person felt a sensation of burning and itching; the cheeks and eyes rapidly became swollen and pruritis became severe; the entire condition disappeared in 2 days after removal from

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1235

exposure. Some persons exhibit sensitivity similar to pollinosis with sneezing, nasal discharge, and nasal stuffiness. A few cases of asthma due to pyrethrum mixtures have been reported; some of the individuals involved had a previous history of asthma with allergy to a wide spectrum of substances.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 1) 328.4; 2) 372.4; 3) 316.4; 4) 360.4; 5) 330.4; 6) 374.4;
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 1 (approximately)
4. Vapor density (air = 1 at boiling point of pyrethrum): Not applicable
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: None.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: None.
4. Special precautions: None.

- **Flammability**

1. Flash point. 82– 88 C (180– 190 F) (open cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Carbon dioxide, foam, dry chemical

- **Warning properties**

Since the vapor pressure of pyrethrum is essentially zero, warning properties are not considered.

Grant states that pyrethrum "is an insecticide powder which may cause allergic reaction and contact dermatitis. Transient conjunctival edema and hyperemia may be induced. The constituents pyrethrin I and II in pure form are said to be irritating to the eyes and mucous membranes. No persistent ocular disturbance from pyrethrum or its derivatives appears to have been reported."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for pyrethrum is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with pyrethrum or liquids containing pyrethrum where skin contact may occur.
- If employees' clothing may have become contaminated with pyrethrum or liquids containing pyrethrum, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with pyrethrum should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of pyrethrum from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the pyrethrum, the person performing the operation should be informed of pyrethrum's hazardous properties.
- Non-impervious clothing which becomes contaminated with pyrethrum should be removed promptly and not reworn until the pyrethrum is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where pyrethrum or liquids containing pyrethrum may contact the eyes.

SANITATION

• Skin that becomes contaminated with pyrethrum should be promptly washed or showered with soap or mild detergent and water to remove any pyrethrum.
• Employees who handle pyrethrum or liquids containing pyrethrum should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to pyrethrum may occur and control methods which may be effective in each case:

Operation	Controls
Application as an insecticide on pre- and post-harvest agricultural crops; cattle and poultry, food cartons, and confined areas	Good personal hygiene
Manufacture of pyrethrum	Good personal hygiene
Formulation of scabicides and parasiticides for medical and veterinary use	Good personal hygiene

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If pyrethrum or liquids containing pyrethrum get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.
• **Skin Exposure**
If pyrethrum or liquids containing pyrethrum get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If pyrethrum or liquids containing pyrethrum penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of pyrethrum, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When pyrethrum or liquids containing pyrethrum have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If pyrethrum is spilled, the following steps should be taken:
1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber.
• Waste disposal methods:
Pyrethrum may be disposed of:
1. By making packages of pyrethrum in paper or other flammable material and burning in a suitable combustion chamber.
2. By dissolving pyrethrum in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Pyrethrum," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Casida, J. E. (ed.): *Pyrethrum - The Natural Insecticide*, Academic Press, New York, 1973.
• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products*

(3rd ed.), Williams and Wilkins, Baltimore, 1969.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.
• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

1238

RESPIRATORY PROTECTION FOR PYRETHRUM

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
50 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
250 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered air-purifying respirator with an organic vapor cartridge and high efficiency particulate filter, including pesticide respirators which meet the requirements of this class. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5000 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of pyrethrum; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 5000 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Pyridine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_5H_5N
- Synonyms: None
- Appearance and odor: Colorless or yellow liquid with a penetrating, sickening odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for pyridine is 5 parts of pyridine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 15 milligrams of pyridine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Pyridine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to pyridine may cause irritation of the eyes, skin, and lining of the respiratory tract. Heavy exposure may also cause gastrointestinal disturbances with diarrhea, abdominal pain, and nausea, weakness, headache, dizziness, difficulty in sleeping, nervousness, and back pain with urinary frequency. Damage to the liver and kidneys may occur. There is some evidence that permanent central nervous system damage may occur.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to pyridine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to pyridine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Kidney damage has been reported from oral administration of pyridine to humans for therapeutic purposes. A urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Pyridine may cause liver damage. A profile of liver function should be performed by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Pyridine vapor is a mild irritant to eyes and mucous membranes, and at high concentrations causes narcosis. In animals the major effects from administration of large doses by any route are local irritation and narcosis, while repeated feeding results in kidney and liver injury. Fatal injury to the liver and kidney has been reported from the prolonged oral administration of 1.8 to 2.5 ml daily for human therapeutic purposes. Workers exposed repeatedly to vapor concentrations averaging 125 ppm developed nausea and anorexia, as well as headache, dizziness, nervousness, and insomnia; in some cases, lower abdominal or back discomfort with urinary frequency was observed without associated evidence of liver or kidney damage. The possibility of permanent central nervous system injury is suggested by some case

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-12:0

September 1978

reports. Chemical plant workers exposed to pyridine at a concentration of 6 to 12 ppm developed headache, temporary vertigo, nervousness, sleeplessness, nausea, and vomiting. In the eye of a rabbit a 40% solution caused corneal necrosis. Skin irritation may result from prolonged or repeated contact with the vapor and liquid.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 79
  2. Boiling point (760 mm Hg): 115.3 C (239 F)
  3. Specific gravity (water = 1): 0.98
  4. Vapor density (air = 1 at boiling point of pyridine): 2.72
  5. Melting point: −42 C (−43.6 F)
  6. Vapor pressure at 20 C (68 F): 18 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids will cause violent spattering.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving pyridine.
  4. Special precautions: Liquid pyridine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 20 C (68 F) (closed cup)
  2. Autoignition temperature: 482 C (900 F)
  3. Flammable limits in air, % by volume: Lower: 1.8; Upper: 12.4
  4. Extinguishant: Alcohol foam, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: Stern reports an odor threshold of 0.23 ppm, Summer reports 0.012 ppm, and May reports 0.013 ppm. The AIHA *Hygienic Guide*, however, notes that the odor "is an unreliable guide to concentrations exceeding 5 ppm. Olfactory fatigue occurs quickly."
  2. Eye Irritation Level: Grant reports that the vapor of pyridine is irritating to the eyes, but he gives no quantitative information.
  3. Other Information: Grant reports that pyridine vapors cause respiratory tract irritation, but no quantitative information is given. Persons who handle pyridine report that although olfactory fatigue occurs rapidly, a definite taste remains, thus giving adequate warning of exposure.
  4. Evaluation of Warning Properties: Although olfactory fatigue occurs rapidly upon exposure to pyridine, a definite taste remains. For this reason, pyridine is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of pyridine vapors using an adsorption tube with subsequent desorption with methylene chloride and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure pyridine may be used. An analytical method for pyridine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with liquid pyridine or solutions containing pyridine, where skin contact may occur.
- Clothing contaminated with pyridine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of

pyridine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the pyridine, the person performing the operation should be informed of pyridine's hazardous properties.

- Where exposure of an employee's body to liquid pyridine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with pyridine should be removed promptly and not reworn until the pyridine is removed from the clothing.
- Any clothing which becomes wet with liquid pyridine should be removed immediately and not reworn until the pyridine is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid pyridine or solutions containing pyridine contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid pyridine or solutions containing pyridine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with pyridine should be immediately washed or showered to remove any pyridine.
- Employees who handle liquid pyridine or solutions containing pyridine should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to pyridine may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of pharmaceuticals such as antihistamines, vitamins, medicinals, CNS stimulants, and local anesthetics	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent in manufacture of polycarbonate resins used in hand tools, small appliances, camera parts, safety helmets, and electrical connectors	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a starting material in manufacture of chemical intermediates and products; use in manufacture of rubber accelerators, epoxy resins, and pharmaceuticals	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a solvent reaction medium or catalyst in paint manufacture, carbohydrate treatment, drug manufacture, and rubber manufacture; use as a reagent in chemical analysis	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in textile treatment as a water-proofing agent; use as a denaturant for ethyl alcohol; use as a coupling assistant in azo dye manufacture; use in purification of mercury fulminate in explosives manufacture	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
During thermal decomposition of flexible polyurethane foams	Personal protective equipment
Use as an inhibitor and for preparation of inhibitors; use in oil and gas well drilling	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid pyridine or solutions containing pyridine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid pyridine or solutions containing pyridine get on the skin, immediately flush the contaminated skin with water. If liquid pyridine or solutions containing pyridine penetrate through the clothing, remove the cloth-

ing immediately and wash the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of pyridine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When pyridine has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If pyridine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Pyridine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Pyridine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Pyridine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Pyridine," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Industrial Bio-Test Laboratories: *Pyridine*.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List IV," *Archives of Industrial Hygiene*, 4:2, 119-121, 1951.

• Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

• Teisinger, J.: "Mild Chronic Intoxication with Pyridine," *Journal of Industrial Hygiene and Toxicology*, 30:58, 1948.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR PYRIDINE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
250 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vap cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canist
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
3600 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressu demand or other positive pressure mode or with a full facepiece, helmet, or ho operated in continuous-flow mode.
Greater than 3600 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressu demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with full facepiece operated in pressure-demand or other positive pressure or contir ous-flow mode and an auxiliary self-contained breathing apparatus operated pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressu demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection fr airborne concentrations of pyridine; however, this equipment should be selected, used, and maintained under t immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 36 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be wo

Occupational Health Guideline for Quinone

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: OC_6H_4O
- Synonyms: p-Benzoquinone
- Appearance and odor: Pale yellow solid with an acrid odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for quinone is 0.1 part of quinone per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.4 milligram of quinone per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Quinone can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

If quinone comes in contact with the skin or the lining of the nose and throat, it may cause irritation, discoloration, redness, swelling, and blistering. Prolonged contact with the skin may cause ulceration. Contact with the eyes may cause irritation, discoloration, and damage which may produce vision difficulties and may be permanent.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to quinone.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to quinone at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of congenital or acquired eye defects would be expected to be at increased risk from exposure. Persons with poor visual acuity from high degrees of astigmatism, keratoconus, or pre-existing corneal injury should be excluded from repeated, uncontrolled exposure to quinone vapor. Examination of the eyes and skin should be stressed.

—Opthalmic examination: Quinone causes eye damage in humans. An opthalmic examination should be performed, including visual acuity and slit-lamp inspection of the cornea.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Quinone is a solid with appreciable vapor pressure, and the vapor or dust is very hazardous to the eyes. Acute exposure causes conjunctival irritation, and in some cases corneal edema, ulceration and scarring; transient eye irritation may be noted above 0.1 ppm and becomes marked at 1 to 2 ppm. Chronic exposure causes the gradual development of changes characterized as: (1) brownish discoloration of the conjunctiva and cornea confined to the intrapalpebral fissure, (2) small opacities of the cornea, and (3) structural corneal changes which result in loss of visual acuity. The pigmentary changes are reversible, but the more slowly developing structural changes in the cornea may progress. Although pigmentation may occur with less than 5 years of exposure, serious injury. Skin contact may cause irritation and

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

12:5

September 1978

this is uncommon and usually is not associated with serious injury. Skin contact may cause irritation and staining. Systemic effects from industrial exposure have not been reported. Skin cancer has been reported in mice painted with a quinone solution. A 0.1% or 0.25% solution of quinone in benzene was applied to the skin of mice daily or every other day; of 87 mice surviving for 200 days, 9 had papillomas of the skin, 3 had cancer of the skin, and 8 had lung cancer.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 108.1
  2. Boiling point (760 mm Hg): Sublimes
  3. Specific gravity (water = 1): 1.32
  4. Vapor density (air = 1 at boiling point of quinone): 3.7
  5. Melting point: 113 C (235 F)
  6. Vapor pressure at 20 C (68 F): 0.1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 1.5
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as quinone fumes and carbon monoxide) may be released in a fire involving quinone.
  4. Special precautions: Quinone will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: Data not available
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Water spray, dry chemical, carbon dioxide
- **Warning properties**
  1. Odor Threshold: According to the AIHA *Hygienic Guide*, the "odor of quinone is not readily apparent at 0.1 ppm." Grant, however, reports that the "vapors are perceptible by smell to human beings at about 0.1 ppm in air." According to the *Hygienic Guide*, olfactory fatigue occurs upon exposure to quinone.
  2. Eye Irritation Level: The *Hygienic Guide* states that "transient eye irritation may be noted above 0.1 ppm and becomes marked at 1 to 2 ppm." Grant states that "at 0.5 ppm the vapors are irritating to the eyes and at 3.0 ppm they are very irritating."
  3. Evaluation of Warning Properties: The *Hygienic Guide* states that "exposure evaluation by odor and irritant effects is not adequate to assure safety because: 1) the odor of quinone is not readily apparent at 0.1 ppm, 2) olfactory fatigue occurs, and 3) repeated exposure to levels causing sensory irritation may cause chronic eye injury." For these reasons, quinone is treated as a material with poor warning properties. The concentration of quinone in saturated air at 20 C could result in a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for quinone is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with quinone, where skin contact may occur.
- If employees' clothing has had any possibility of being contaminated with quinone, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with quinone should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of quinone from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the quinone, the person performing the operation should be informed of quinone's hazardous properties.

• Where exposure of an employee's body to solid quinone or liquids containing quinone may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with quinone should be removed immediately and not reworn until the quinone is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of quinone or liquids containing quinone contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solid quinone or liquids containing quinone, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with quinone should be immediately washed or showered with soap or mild detergent and water to remove any quinone.

• Workers subject to skin contact with quinone should wash with soap or mild detergent and water any areas of the body which may have contacted quinone at the end of each work day.

• Eating and smoking should not be permitted in areas where quinone is handled, processed, or stored.

• Employees who handle quinone should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to quinone may occur and control methods which may be effective in each case:

Operation	Controls
Use as an oxidizing agent in synthesis of organic chemicals and intermediates; in photography—developer hydroquinone; in agriculture in production of insecticides and fungicides; in pharmaceutical industry for production of cortisone and addition compound with barbituates	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in polymer and resins industry as an inhibitor and retarder-antioxidant, curing agent, and catalyst	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a toner and intensifier in photographic industry; as a tanning agent for leather industry	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of quinhydrone electrodes for use for pH determinations	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solid quinone or liquids containing quinone get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If quinone gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If quinone penetrates through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of quinone, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as

soon as possible.

• **Swallowing**

When quinone has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If quinone is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Quinone may be disposed of:

1. By making packages of quinone in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving quinone in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Quinone," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Quinone," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Anderson, B.: "Corneal and Conjunctival Pigmentation Among Workers Engaged in Manufacture of Hydroquinone," *Archives of Ophthalmology*, 38:812-826, 1947.

• Anderson, B., and Oglesby, F.: "Corneal Changes from Quinone-Hydroquinone Exposure," *A.M.A. Archives of Ophthalmology*, 59:495-501, 1958.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Takizawa, N.: "On the Carcinogenic Action of Certain Quinones," *Proceedings of the Imperial Academy*, 16:309-312, 1940.

RESPIRATORY PROTECTION FOR QUINONE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Particulate or Vapor Concentration	
5 ppm or 20 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
75 ppm or 300 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 75 ppm or 300 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Rhodium Metal Fume and Dusts (as Rhodium)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Rh
- Synonyms: None
- Appearance: Gray fume or dust.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for rhodium metal fume and dusts is 0.1 milligram of rhodium metal fume and dusts (as rhodium) per cubic meter of air (mg/m³) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

None: See "Summary of toxicology."

- **Effects of overexposure**

1. Short-term Exposure: None known.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to rhodium metal fume and dusts.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to rhodium metal fume and dusts at potentially hazardous levels.

- **Summary of toxicology**

No toxic effects of rhodium metal fume and dusts have been reported from animal experiments or from observations on human beings.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 102.9
  2. Boiling point (760 mm Hg): Above 2500 C (4532 F)
  3. Specific gravity (water = 1): 12.4
  4. Vapor density (air = 1 at boiling point of rhodium metal fume and dusts): Not applicable
  5. Melting point: 1966 C (3570 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Rhodium metal fume and dusts are not known to be eye irritants.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of rhodium metal fume and dusts on a filter, followed by

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1250

treatment with nitric acid, solution in hydrochloric acid, treatment with potassium bisulfate, and atomic absorption spectrophotometric analysis. An analytical method for rhodium metal fume and dusts is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to rhodium metal fume and dusts may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during manufacture of platinum alloys for use in thermocouples, windings for resistance furnaces, laboratory crucibles and catalysts for chemical processing, and preparation of dental castings	General dilution ventilation; local exhaust ventilation
Liberation during production and casting of rhodium powder during refining and recovery	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in applying thin reflective coatings by sublimation to scientific instruments, radio and radar equipment, searchlight reflectors, cinema projections, and headlight reflectors	General dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of rhodium metal fume and dusts, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When rhodium metal dust has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention.

SPILL AND DISPOSAL PROCEDURES

• If potentially hazardous amounts of rhodium metal fume and dusts are spilled or inadvertently released, the following steps should be taken:

1. Ventilate area of spill or release.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Rhodium metal dusts may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Rhodium as Rh." *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR RHODIUM METAL FUME AND DUSTS (AS RHODIUM)

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
0.5 mg/m³ or less	Any dust and mist respirator.
1 mg/m³ or less	Any fume respirator or high efficiency particulate respirator. Any dust and mist respirator, except single-use or quarter-mask respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Soluble Rhodium Salts (as Rhodium)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all soluble rhodium salts. Physical and chemical properties of one specific compound are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION—Hydrated rhodium trichloride

- Formula: $RhCl_3 \cdot xH_2O$
- Synonyms: Soluble rhodium trichloride; rhodium chloride
- Appearance and odor: Red-brown, odorless solid or liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for soluble rhodium salts is 0.001 milligram of soluble rhodium salts (as rhodium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Soluble rhodium salts may affect the body if they are inhaled or if they come in contact with the eyes or skin. They may also affect the body if they are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: None known in humans

2. Long-term Exposure: None known in humans

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to soluble rhodium salts.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to soluble rhodium salts at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from soluble rhodium salts exposure.

—Eye disease: Rhodium chloride has caused eye damage in animals. Persons with pre-existing eye disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although rhodium is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Central nervous system disorders: Rhodium trichloride has caused central nervous system damage in animals. Individuals with pre-existing central nervous system disorders may be more susceptible.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Toxicologic data on the soluble salts of rhodium are meager; however, solutions of salts splashed in the eye may cause mild irritation. Rhodium trichloride was found to have chemotherapeutic action against certain viruses in mice, but no mention was made of toxicity. The LD50 for rhodium trichloride in rabbits by intravenous injection was 215 mg/kg; the clinical signs presented shortly after injection were increasing lethargy and waning respiration. There were no abnormal findings at autopsy, and the rapid onset of death suggested central nervous system effects. A solution of rhodium chloride in a rabbit eye gave a delayed injurious reaction; a 0.1-M solution adjusted to pH 7.2 with ammonium hydroxide was placed for 10 minutes in a rabbit eye after the corneal epithelium had been removed; an orange color-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1253

ation of the cornea occurred, which faded to faint yellow within 8 weeks. During the first 2 to 3 weeks, the cornea was slightly hazy; in the third week white opacities gradually developed, and finally there was extensive opacification and vascularization. Systemic effects have not been reported from industrial exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data—Hydrated rhodium trichloride**

1. Molecular weight: Greater than 209
2. Boiling point (760 mm Hg): 800 C (1472 F) (sublimes)
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of soluble rhodium salts): Not applicable
5. Melting point: 100 C (212 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Less than 0.1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Very soluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: At temperatures above 100 C(212 F), some decomposition may occur.
2. Incompatibilities: None
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride or chlorine) may be released when rhodium trichloride decomposes.
4. Special precautions: None

- **Flammability**

1. Not combustible

- **Warning properties**

The only rhodium salt for which information is available concerning toxic effects on the eye is rhodium chloride. Grant states that "rhodium chloride has been tested on a rabbit's eye and was found to give a peculiar delayed injurious reaction. A 0.1-M clear, dark-red solution prepared and adjusted to pH 7.2 with ammonium hydroxide was applied for 10 minutes to the eye after the corneal epithelium had been removed by scraping. This exposure caused orange coloration of the cornea, fading to faint yellow in the course of 2 months. During the first 2 to 3 weeks the cornea was not opaque, but was slightly hazy. In the third week, however, irregular white opacities gradually developed. Ultimately the cornea became extensively opacified and vascularized."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of soluble rhodium salts on a filter, followed by treatment with nitric acid and perchloric acid, solution in aicd, and atomic absorption spectrophotometric analysis. An analytical method for soluble rhodium salts is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4). Analytical Methods for Set M" (order number PB 265 029).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with soluble rhodium salts or liquids containing soluble rhodium salts.
- Clothing contaminated with soluble rhodium salts should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of soluble rhodium salts from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the soluble rhodium salts, the person performing the operation should be informed of soluble rhodium salts's hazardous properties.
- Non-impervious clothing which becomes contaminated with soluble rhodium salts should be removed promptly and not reworn until the soluble rhodium salts are removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where soluble rhodium salts or liquids containing soluble rhodium salts may contact the eyes.

SANITATION

• Skin that becomes contaminated with soluble rhodium salts should be promptly washed or showered to remove any soluble rhodium salts.
• Eating and smoking should not be permitted in areas where soluble rhodium salts or liquids containing soluble rhodium salts are handled, processed, or stored.
• Employees who handle soluble rhodium salts or liquids containing soluble rhodium salts should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to soluble rhodium salts may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during refining and extraction of metal from platinum ores	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in electroplating baths for finishing scientific instruments, camera fittings, radio equipment, and jewelry; use in laboratory for research	General dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If soluble rhodium salts or liquids containing soluble rhodium salts get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention.
• **Skin Exposure**
If soluble rhodium salts or liquids containing soluble rhodium salts get on the skin, flush the contaminated skin with water. If soluble rhodium salts or liquids containing soluble rhodium salts penetrate through the clothing, remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of soluble rhodium salts, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When soluble rhodium salts or liquids containing soluble rhodium salts have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If soluble rhodium salts are spilled, the following steps should be taken:
1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquid containing soluble rhodium salts should be absorbed in vermiculite, dry sand, earth, or a similar material.
• Waste disposal method:
Soluble rhodium salts may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Rhodium as Rh," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.
• Campbell, L., et al.: "Dermal Irritancy of Metal Compounds," *Archives of Environmental Health*, 30:168-70, April 1975.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.
• Hunter, D.: *Diseases of Occupations* (4th ed.). Little, Brown, Boston, 1969.
• International Labour Office: *Encyclopedia of Occupa-*

tional Health and Safety, McGraw-Hill, New York, 1971.

• Landolt, R. R., et al.: "Studies on the Toxicity of Rhodium Trichloride in Rats and Rabbits," *Toxicology and Applied Pharmacology*, 21:589-590, 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

RESPIRATORY PROTECTION FOR SOLUBLE RHODIUM SALTS (AS RHODIUM)

Condition	Minimum Respiratory Protection* Required Above 0.001 mg/m³
Particulate Concentration	
0.01 mg/m³ or less	Any high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
0.05 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
2 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Ronnel

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3O)_2PSOC_6H_2Cl_3$
- Synonyms: Fenchlorphos; O,O-dimethyl O-(2,4,5-trichlorophenyl) phosphorothioate
- Appearance and odor: White to tan waxy solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for ronnel is 15 milligrams of ronnel per cubic meter of air (mg/m^3) averaged over an eight-hour work shift (*Federal Register*, Vol. 43, p. 57603, 8 December 1978).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Ronnel can affect the body if it is inhaled or if it comes in contact with the eyes. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Ronnel is one of the least toxic of the organophosphate insecticides. Very large exposures are required to cause symptoms. In animal experiments, ronnel has caused watering of the mouth, tremors, diarrhea, small pupils, and respiratory distress. Ronnel powder is irritating to the eye in rabbits.

2. Long-term Exposure: In animals ronnel has caused liver and kidney damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to ronnel.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to ronnel at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from ronnel exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of ronnel might cause exacerbation of symptoms due to an anticholinesterase effect.

—Liver disease: Ronnel causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Ronnel causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Ronnel is a weak cholinesterase inhibitor. It affects primarily the pseudoesterases of the blood plasma rather than the erythrocyte acetylcholinesterase. In male rats, the oral LD50 was 1.7 g/kg; effects were salivation, tremors, diarrhea, miosis, and respiratory distress – all attributed to the anticholinesterase effect of ronnel. Rats fed 50 mg/kg body weight in the diet for 105 days developed slight liver and kidney damage. When a small amount of ronnel powder was placed in the eye of a rabbit, there were slight discomfort and transient conjunctival irritation which subsided within 48 hours. In an experiment on humans in which 50 subjects received 3 applications per week for 3 weeks of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

127

gauze saturated with a 10% suspension of ronnel in sesame oil, there were no significant effects on the skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 321.5
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): 1.48
  4. Vapor density (air = 1 at boiling point of ronnel): Not applicable
  5. Melting point: 35 C (95 F)
  6. Vapor pressure at 20 C (68 F): 0.0008 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.0044
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: Temperatures above 150 C (300 F) may cause explosive decomposition and formation of toxic gases.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide, dimethyl sulfide, trichlorophenol, etc., and carbon monoxide) may be released when ronnel decomposes.
  4. Special precautions: Melted ronnel will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**

Ronnel may cause mild eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for ronnel is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with ronnel or liquids containing ronnel.
- If employees' clothing may have become contaminated with ronnel or liquids containing ronnel, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with ronnel should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of ronnel from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the ronnel, the person performing the operation should be informed of ronnel's hazardous properties.
- Non-impervious clothing which becomes contaminated with ronnel should be removed promptly and not reworn until the ronnel is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where ronnel or liquids containing ronnel may contact the eyes.

SANITATION

- Skin that becomes contaminated with ronnel should be promptly washed or showered with soap or mild detergent and water to remove any ronnel.
- Eating and smoking should not be permitted in areas where solid ronnel is handled, processed, or stored.
- Employees who handle ronnel or liquids containing ronnel should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations

which exposure to ronnel may occur and control methods which may be effective in each case:

Operation	Controls
Use as an insecticide and pest control agent for agricultural and livestock operations	General dilution ventilation; personal protective equipment
Formulation of insecticides for agricultural and livestock use	General dilution ventilation; personal protective equipment
Use as an insecticide for fruits	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If ronnel or liquids containing ronnel get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If ronnel or liquids containing ronnel get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If ronnel or liquids containing ronnel penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of ronnel, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When ronnel or liquids containing ronnel have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If ronnel is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Molten ronnel should be absorbed in vermiculite, dry sand, earth, or a similar material.

- Waste disposal method:

Ronnel may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Ronnel," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
- Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.
- *Federal Register*, Vol. 43, p. 57603, 8 December 1978.
- Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.
- Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.
- McCollister, D. D., et al.: "Toxicological Studies of O,O-Dimethyl-O-(2,4,5-trichlorophenyl) Phosphorothioate (Ronnel) in Laboratory Animals," *Agricultural and Food Chemistry*, 7:689-693, 1959.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.
- Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR RONNEL

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Particulate Concentration	
150 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust, fume, and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust, fume, and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
7500 mg/m³ or less	A powered air-purifying respirator with an organic vapor cartridge and high efficiency particulate filter, including pesticide respirators which meet the requirements of this class. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 7500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Rotenone

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{23}H_{22}O_6$
- Synonyms: Rotenone, commercial; tubatoxin; "cube"; derrin
- Appearance and odor: Colorless to red, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for rotenone is 5 milligrams of rotenone per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Rotenone can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to rotenone may cause irritation of the eyes and skin. Symptoms of absorption of rotenone dust (inferred mostly from animal studies) include numbness of the mouth, nausea, vomiting, gastric pain, pulmonary irritation, trembling, loss of coordination, convulsions, stupor, and cessation of breathing. In animal experiments, exposure to rotenone dust has caused liver and kidney damage and has produced tumors.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to rotenone.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to rotenone at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system, eyes, respiratory tract, and liver should be stressed.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Rotenone dust affects the nervous system and causes convulsions in animals. Animals repeatedly fed derris powder (a botanical source containing 9.6% rotenone) at levels from 312 to 5000 ppm developed focal liver necrosis and mild kidney damage. Of 40 female rats given daily intraperitoneal injections of rotenone in sunflower oil of 1.7 mg/kg for 42 days, over 60% developed mammary tumors 6 to 11 months after the end of treatment; most of the tumors were mammary adenomas; one was a differentiated adenocarcinoma; none of the control animals had tumors when examined 19 months after treatment. The lethal oral dose in humans is estimated to be 0.3 to 0.5 g/kg. In humans, inhalation of dust is expected to cause pulmonary irritation. Symptoms of absorption in humans (inferred mostly from animal studies) may include numbness of oral mucous membranes, nausea, vomiting, and abdominal pain. There may be muscle tremors, incoordination, clonic convulsions, and stupor. The dust is irritating to the eyes and skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 394.4
2. Boiling point (760 mm Hg): Decomposes

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

1261

3. Specific gravity (water = 1): 1 (approximately)
4. Vapor density (air = 1 at boiling point of rotenone): Not applicable
5. Melting point: 163 C (325 F) or 181 C (358 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.00002
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: None.
4. Special precautions: None.

• **Flammability**

1. Flash point: Data not available
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Foam, carbon dioxide, dry chemical, water.

• **Warning properties**

Since the vapor pressure of rotenone is negligible, warning properties are not considered.
Rotenone is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for rotenone is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with rotenone or liquids containing rotenone.

• If employees' clothing has had any possibility of being contaminated with rotenone or liquids containing rotenone, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with rotenone should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of rotenone from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the rotenone, the person performing the operation should be informed of rotenone's hazardous properties.

• Non-impervious clothing which becomes contaminated with rotenone should be removed promptly and not reworn until the rotenone is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where rotenone or liquids containing rotenone may contact the eyes.

SANITATION

• Skin that becomes contaminated with rotenone should be promptly washed or showered with soap or mild detergent and water to remove any rotenone.

• Eating and smoking should not be permitted in areas where rotenone or liquids containing rotenone is handled, processed, or stored.

• Employees who handle rotenone or liquids containing rotenone should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to rotenone may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of pesticides	Process enclosure; local exhaust ventilation; wet methods
Application on agricultural crops and livestock as an insecticide and ascaricide	Personal protective equipment
Manufacture of rotenone	Process enclosure; local exhaust ventilation; wet methods; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If rotenone or liquids containing rotenone get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If rotenone or liquids containing rotenone get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If rotenone or liquids containing rotenone penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of rotenone, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When rotenone or liquids containing rotenone have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If rotenone is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities can be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber.

• Waste disposal methods:

Rotenone may be disposed of

1. By making packages of rotenone in paper or other flammable material and burning in a suitable combustion chamber.
2. By dissolving rotenone in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Rotenone," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Gosalvez, M., and Merchan, J.: "Induction of Rat Mammary Adenomas with the Respiratory Inhibitor Rotenone," *Cancer Research*, 33:3047-3050, 1973.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

RESPIRATORY PROTECTION FOR ROTENONE (COMMERCIAL)

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
50 mg/m³ or less	Any chemical cartridge respirator with an organic vapor cartridge(s) and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. Any supplied-air respirator. Any self-contained breathing apparatus.
250 mg/m³ or less	A chemical cartridge respirator with a full facepiece, organic vapor cartridge(s), and dust and mist filter(s), including pesticide respirators which meet the requirements of this class. A gas mask with a chin-style or a front- or back-mounted organic vapor canister and dust and mist filter, including pesticide respirators which meet the requirements of this class. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered air-purifying respirator with an organic vapor cartridge and high efficiency particulate filter, including pesticide respirators which meet the requirements of this class. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Selenium and Its Inorganic Compounds (as Selenium)*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all selenium and its inorganic compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Selenium

- Formula: Se
- Synonyms: Selenium, metallic; selenium, elemental
- Appearance and odor: Black, gray, or red odorless solid.

Sodium selenite

- Formula: Na_2SeO_3
- Synonyms: None
- Appearance and odor: Colorless and odorless solid.

Sodium selenate

- Formula: Na_2SeO_4
- Synonyms: None
- Appearance and odor: Colorless and odorless solid.

Selenium dioxide

- Formula: SeO_2
- Synonyms: None
- Appearance and odor: Colorless and odorless solid.

Selenium oxychloride

- Formula: $SeOCl_2$
- Synonyms: None
- Appearance: Colorless to yellow liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for selenium and its inorganic compounds is 0.2 milligram of selenium and its inorganic compounds (as selenium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Selenium, sodium selenite, sodium selenate, or selenium dioxide can affect the body if they are inhaled, if they come in contact with the eyes or skin, or if they are swallowed. Selenium oxychloride and selenium dioxide may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Inhalation of large quantities of selenium dioxide or selenium oxychloride may cause severe breathing difficulties which may not appear for several hours after exposure. Skin contact with selenium dioxide or selenium oxychloride may cause skin burns. Skin exposure to selenium dioxide dust may cause a skin rash. Splashes of selenium dioxide may cause eye irritation. Selenium dioxide dust may cause "rose eye," an allergy of the eyelids in which they may become puffy.

2. Long-term Exposure: Prolonged exposure to selenium, sodium selenite, sodium selenate, or selenium dioxide may cause paleness, coated tongue, stomach disorders, nervousness, metallic taste and a garlic odor of the breath. Fluid in the abdominal cavity, damage to the liver and spleen, and anemia have been reported in animals. Prolonged skin contact with selenium oxide or selenium oxychloride may cause skin sensitization.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1205

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to selenium and its inorganic compounds.

• **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to selenium and its inorganic compounds at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to selenium, or with a history of other chronic respiratory disease, gastrointestinal disturbances, disorders of liver or kidneys, or recurrent dermatitis would be expected to be at increased risk from exposure. Examination of the eyes, respiratory system, liver, kidneys, and blood should be stressed. The skin should be examined for evidence of chronic disorders. Special consideration should be given to women of childbearing age since the possibility that selenium may be teratogenic might place these women in a high risk group.

—Urinalysis: Proper function of the kidneys is necessary to validate levels of selenium in the urine. A urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Selenium causes liver damage and tumors in animals. A profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Elemental selenium and certain selenium compounds as dusts, vapors, and fumes irritate the eyes, upper respiratory tract, and skin. Animals exposed to selenium anhydride at a concentration of 150 mg/m^3 for 4 hours developed conjunctivitis, pulmonary edema, and convulsions preceding death; there were degenerative changes in the liver, kidneys, spleen, and heart. Prolonged feeding of animals with diets containing selenium in amounts of 5 to 15 ppm caused hepatic necrosis, hemorrhage, and cirrhosis; marked and progressive anemia occurred in some species. The possibility of teratogenic effects from exposure to selenium has been raised, based upon observations in animals, but it has not been established in man. Eleven of 53 rats developed adenoma or low-grade carcinoma in cirrhotic livers, and four others had advanced adenomatoid hyperplasia, after having survived for 18 to 24 months on diets containing 5, 7, or 10 ppm of selenium; no tumors occurred in 73 rats surviving less than 18 months, although after 3 months cirrhosis was frequent. In control rats 18 to 24 months of age, the incidence of spontaneous hepatic tumors was less than 1%. A group of workers briefly exposed to high concentrations of selenium fume developed severe irritation of the eyes, nose, and throat, followed by headaches; transient dyspnea occurred in one case. In workers exposed to an undetermined concentration of selenium oxide there was bronchospasm and dyspnea, followed within 12 hours by chills, fever, headache, and bronchitis, leading to pneumonitis in a few cases; all were asymptomatic within a week. In a study of workers in a selenium plant, workroom air levels ranged from 0.2 to 3.6 mg/m^3, while urinary levels ranged from below 0.10 to 0.43 mg/l; the chief complaints were garlic odor of the breath, metallic taste, gastrointestinal disturbances, and skin eruptions. An accidental spray of selenium dioxide, in unspecified form and concentration, into the eyes of a chemist caused superficial burns of the skin and immediate irritation of the eyes; within 16 hours vision was blurred, and the lower portions of both corneas appeared dulled; 16 days after the accident the corneas were normal. Acute burns of the skin can be caused by selenium oxychloride and selenium oxide, which are highly vesicant. Contact with the fume of heated selenium dioxide caused an acute, weeping dermatitis, with the development of hypersensitivity in some cases.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Selenium**

1. Molecular weight: 78.96
2. Boiling point (760 mm Hg): 685 C (1265 F)
3. Specific gravity (water = 1): 4.45 to 4.8
4. Vapor density (air = 1 at boiling point of selenium): Not applicable
5. Melting point: 150 C (302 F)
6. Vapor pressure at 20 C (68 F): Less than 0.001 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Sodium selenite**

1. Molecular weight: 173
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 3.1
4. Vapor density (air = 1 at boiling point of sodium selenite): Not applicable
5. Melting point: 710 C (1310 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Less than 0.001 mg Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 85
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Sodium selenate**

1. Molecular weight: 188.9
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 3.1

4. Vapor density (air = 1 at boiling point of sodium selenate): Not applicable
5. Melting point: Decomposes
6. Vapor pressure at 20 C (68 F): Less than 0.001 mm Hg
7. Solubility in water, g/200 g water at 20 C (68 F): 83
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Selenium dioxide**

1. Molecular weight: 110.9
2. Boiling point (760 mm Hg): 315 C (599 F) (sublimes)
3. Specific gravity (water = 1): 3.95
4. Vapor density (air = 1 at boiling point of selenium dioxide): Not applicable
5. Melting point: 340 C (644 F)
6. Vapor pressure at 20 C (68 F): 0.001 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 257
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Selenium oxychloride**

1. Molecular weight: 165.9
2. Boiling point (760 mm Hg): 176 C (349 F)
3. Specific gravity (water = 1): 2.42
4. Vapor density (air = 1 at boiling point of selenium oxychloride): 5.7
5. Melting point: 10.8 C (51 F)
6. Vapor pressure at 20 C (68 F): 0.35 mm approximately
7. Solubility in water, g/100 g water at 20 C (68 F): Decomposes
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None hazardous
2. Incompatibilities: Contact of selenium with acids may cause formation of poisonous hydrogen selenide gas. Contact of selenium with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors may be released in a fire involving selenium, sodium selenite, sodium selenate, selenium dioxide, and selenium oxychloride.
4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: Selenium: Data not available; sodium selenite, sodium selenate, selenium dioxide, and selenium oxychloride: Not applicable
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: For selenium, water

• **Warning properties**

The *Documentation of TLV's* notes that "Clinton reported intense irritation of eyes, nose, and throat, followed by headache, in a group of workers briefly exposed to high concentrations of selenium fume." The ILO reports that "persons who work in atmospheres containing selenium dioxide dust may develop a condition known among the workers as 'rose eye,' a pink allergy of the eyelids, which often become puffy. There is usually also a conjunctivitis of the palpebral conjunctiva but rarely of the bulbar conjunctiva." The *Hygienic Information Guide* for selenium states that "in contact with the eye, selenium compounds exert a rapid irritant action leading to inflammation." Grant reports that both selenium dioxide and selenium sulfide can produce toxic effects on the eye. Quantitative information concerning air concentrations of selenium compounds which cause eye irritation is not available.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of selenium and its inorganic compounds on a filter, followed by treatment with acid and atomic absorption spectrophotometric analysis. An analytical method for selenium and its inorganic compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which

includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with selenium oxychloride or liquids containing selenium oxychloride.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with selenium, sodium selenite, sodium selenate, or liquids containing these compounds.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with selenium dioxide or liquids containing selenium dioxide, where skin contact may occur.
- If employees' clothing has had any possibility of being contaminated with selenium oxychloride, sodium selenite,sodium selenate, selenium dioxide, or liquids containing these compounds, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing which has had any possibility of being contaminated with selenium oxychloride, sodium selenite, sodium selenate, or selenium dioxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of contaminant from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the contaminant, the person performing the operation should be informed of contaminant's hazardous properties.
- Where there is any possibility of exposure of an employee's body to selenium, selenium oxychloride, sodium selenite, sodium selenate, selenium dioxide, or liquids containing these compounds, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with selenium, sodium selenite, sodium selenate, selenium dioxide or liquids containing these compounds should be removed promptly and not reworn until the contaminant is removed from the clothing.
- Non-impervious clothing which becomes contaminated with selenium oxychloride should be removed immediately and not reworn until the selenium oxychloride is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of selenium dioxide, selenium oxychloride, or liquids containing these compounds contacting the eyes.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where sodium selenite, sodium selenate, or liquids containing these compounds may contact the eyes.
- Where there is any possibility that employees' eyes may be exposed to selenium oxychloride, selenium dioxide, or liquids containing these compounds, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Workers subject to skin contact with selenium oxychloride, sodium selenite, sodium selenate, selenium dioxide, or liquids containing these compounds should wash any areas of the body which may have contacted selenium oxychloride, sodium selenite, sodium selenate, selenium dioxide, or liquids containing these compounds at the end of each work day.
- Skin that becomes contaminated with selenium, sodium selenite, sodium selenate, selenium dioxide, or liquids containing these substances should be promptly washed or showered to remove any contaminant.
- Skin that becomes contaminated with selenium oxychloride should be immediately washed or showered to remove any selenium oxychloride.
- Eating and smoking should not be permitted in areas where selenium oxychloride, sodium selenite, sodium selenate, selenium dioxide, or liquids containing these compounds are handled, processed, or stored.
- Employees who handle selenium oxychloride, sodium selenite, sodium selenate, selenium dioxide, or liquids containing these compounds should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to selenium and its inorganic compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during mining recovery, and purification and manufacture of selenium compounds	Local exhaust ventilation; general dilution ventilation; personal protective equipment

Operation	Controls
Use in glassware industry for decolorization of fiberglass, scientific glassware, vehicular tail lights, traffic and other signal lenses, and infrared equipment; use in manufacture of electrical components in welding, transformers, semiconductors, photoelectric cells, etc.	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of photography and photocopy devices; manufacture of dyes, pigments, and colored glazes for metal etching and for printing on glass	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of lubricating oils and extreme pressure lubricants as antioxidants and detergency improvers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in rubber industry for manufacture and use as vulcanization accelerators and antioxidants; use in manufacture of pharmaceuticals, fungicides, and dermatitis control	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a catalyst for hardening fats for soaps, waxes, edible fats, and plastics	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of insecticides, parasiticides, bactericides, and herbicides for agricultural and citrus crops	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of flame-proofing agents on textiles and electric cables	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of delayed action blasting caps	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as solvents in paint and varnish removers; rubber, resin, and glue solvent; use for organic synthesis in oxidation, hydrogenation, and dehyrogenation	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in refining of copper, silver, gold, or nickel ores or during recycling of scrap metal	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in miscellaneous operations in manufacture of insect repellants, activators, hardeners, special ceramic materials, plasticizers, and mercury vapor detectors	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use for preparation of feed additives for poultry and swine	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If selenium or its inorganic compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with these chemicals.

- **Skin Exposure**

If selenium or its inorganic compounds get on the skin, immediately wash the contaminated skin. If selenium, sodium selenite, sodium selenate, or selenium dioxide soak through the clothing, remove the clothing immediately and wash the skin. If irritation persists after washing, get medical attenti n. .

- **Breathing**

If a person breathes .. large amounts of selenium sodium selenite, sodium selenate, or selenium dioxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration.

Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When selenium, sodium selenite, sodium selenate, selenium oxychloride, or selenium dioxide have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If selenium or its inorganic compounds are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing selenium and its inorganic compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Selenium and its inorganic compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Selenium Compounds (as Se)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Selenium and Compounds," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Cerwenka, E. A., Jr., and Cooper, W. C.: "Toxicology of Selenium and Tellurium and Their Compounds," *Archives of Environmental Health*, 3:189-200, 1961.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

1969.

• Glover, J. R.: "Selenium and Its Industrial Toxicology," *Industrial Medicine*, 39(1):50-54, January 1970.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Halverson, A. W., et al.: "Development of Hemolytic Anemia in Rats Fed Selenite," *Toxicology and Applied Pharmacology*, 17:151-159, 1970.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• *Hygienic Information Guide No. 59 – Selenium Compounds (as Se)*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1974.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Nelson, A. A., et al.: "Liver Tumors Following Cirrhosis Caused by Selenium in Rats," *Cancer Research*, 3:230-236, 1943.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Robertson, D. S. F.: "Selenium – A Possible Teratogen?," *Lancet*, 1:518-519, 1970.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• SPECIAL NOTE

Selenium and its inorganic compounds (as selenium) appear on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding their carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980).

RESPIRATORY PROTECTION FOR SELENIUM AND ITS INORGANIC COMPOUNDS (AS SELENIUM)

Condition	Minimum Respiratory Protection* Required Above 0.2 mg/m³
Particulate Concentration	
10 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode. A powered air-purifying respirator with a high efficiency particulate filter and a full facepiece, helmet, or hood.
Greater than 100 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator with a full facepiece. Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

1271

Occupational Health Guideline for Selenium Hexafluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: SeF_6
- Synonyms: None
- Appearance: Colorless gas.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for selenium hexafluoride is 0.05 part of selenium hexafluoride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.4 milligram of selenium hexafluoride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Selenium hexafluoride can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

Animal experiments have shown selenium hexafluoride to be a severe respiratory irritant which has produced severe breathing difficulties. These breathing difficulties may be delayed in onset.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to selenium hexafluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to selenium hexafluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory tract should be stressed.

—14" x 17" chest roentgenogram: Selenium hexafluoride causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Selenium hexafluoride is a severe pulmonary irritant in animals. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when signs and symptoms of respiratory disease occur.

- **Summary of toxicology**

Selenium hexafluoride gas is a severe respiratory irritant in animals. Exposure of four animal species to 10 ppm for 4 hours was fatal; 5 ppm for 4 hours was not fatal but caused pulmonary edema, while 1 ppm produced no effects. Animals exposed to 5 ppm for 1 hour daily for 5 days developed signs of pulmonary injury; 1 ppm for the same time period caused no detectable effects.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 193
2. Boiling point (760 mm Hg): −35 C (−31 F)
3. Specific gravity (water = 1): 2.3 (liquid)
4. Vapor density (air = 1 at boiling point of selenium hexafluoride): 6.7
5. Melting point: −39 C (−38 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble; reacts slowly

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: Data not available
  4. Special precautions: None
- **Flammability**
  1. Not combustible
  2. See 29 CFR 1910.101 for specific regulations on storage of compressed gas cylinders.
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold of selenium hexafluoride.
  2. Eye Irritation Level: There is no indication in the available toxicological information that selenium hexafluoride produces eye irritation. Concerning fluorides, however, Grant states that "irritation of the eyes and nose has been reported when fluoride concentration has reached 5 mg/m^3 of air."
  3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of selenium hexafluoride, this compound is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with a subsequent chemical analysis of the adsorption tube. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure selenium hexfluoride may be used. An analytical method for selenium hexafluoride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to selenium hexafluoride may occur and control methods which may be effective in each case:

Operation	Controls
Use as a gaseous electric insulator	Process enclosure; local exhaust ventilation; personal protective equipment
Use during production of selenium hydroxide and hydrofluoric acid, selenium and nitrogen	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Breathing**

If a person breathes in large amounts of selenium hexafluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.
- If selenium hexafluoride is leaked, the following steps should be taken:

1273

1. Ventilate area of leak.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped in place, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Selenium Hexafluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Selenium and Compounds," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR SELENIUM HEXAFLUORIDE

Condition	Minimum Respiratory Protection* Required Above 0.05 ppm
Gas Concentration	
0.5 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
2.5 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against selenium hexafluoride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Amorphous Silica

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: SiO_2
- Synonyms: Diatomite; silicon dioxide (amorphous); diatomaceous earth; diatomaceous silica
- Appearance and odor: Colorless to gray odorless powder.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for amorphous silica is 20 million particles of amorphous silica per cubic foot of air (mppcf) averaged over an eight-hour work shift, or the quotient of 30 mg/m³ divided by the percent of silica present. The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for amorphous silica from 20 mppcf to 6 mg/m³ total dust (all sampled dust) and 3 mg/m³ for respirable dust.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Amorphous silica can affect the body if it is inhaled or if it comes in contact with the eyes.

- **Effects of overexposure**

Prolonged inhalation of amorphous silica including uncalcined diatomaceous earth may produce x-ray changes in the lungs without disability. Prolonged inhalation of calcined diatomaceous earth may cause silicosis with scarring of the lungs, cough, and shortness of breath.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to amorphous silica.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to amorphous silica at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed.

—14" x 17" chest roentgenogram: Although the contribution of amorphous silica including natural diatomaceous earth to the development of pneumoconiosis is unclear, surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Since persons with impaired pulmonary function may be at increased risk from exposure to amorphous silica, periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Amorphous silica, including natural diatomaceous earth, is usually considered to be of low toxicity; however, pure amorphous silica is rarely found, and diatomaceous earth usually contains some amount of crystalline silica. When converted partially to a crystalline form by calcination, the dust of diatomaceous earth produces pulmonary fibrosis. Repeated exposure of guinea pigs to natural diatomaceous earth for periods up to 50 weeks to average concentrations ranging from 60 to 124 mg/m³ caused thickening of the alveolar septa by infiltration of macrophages, accumulation of large numbers of multinuclear cells containing dust particles, and lymphadenopathy, but no proliferation of connective tissue. In a study of diatomaceous earth workers,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1275

those employed in the quarry for more than 5 years and exposed only to natural diatomaceous earth had no significant roentgenologic changes; of others employed for more than 5 years in the milling process and exposed to calcined material, 17% had simple pneumoconiosis and 23% had the confluent form, probably the result of fibrogenic action of the crystalline silica formed by calcination of the naturally occurring mineral. In humans, calcined diatomaceous earth pneumoconiosis is characterized roentgenographically by fine linear and/or minute nodular shadows, either or both of which may be accompanied by conglomerate fibrosis; in the simple phase of the disease, the upper lobes, are affected more than the lower lobes and the condition progresses by an increase in the apparent number of the nodules, which rarely attain the density or size of nodules often seen in quartz silicosis. In the early confluent stage of the disease, the linear and nodular changes in the upper lung fields become more circumscribed and homogeneous; histologically, there is an absence of the focal, discrete, hyaline nodules or the whorled pattern of collagenous fibers of typical silicosis. The majority of experimental rats exposed to synthetic submicron amorphous silica at 1.5 mg/ft³ of air died from pulmonary vascular obstruction coupled with pulmonary insufficiency. Rats that survived recovered almost completely after 6 months.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 60.1
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): 2.65
  4. Vapor density (air = 1 at boiling point of amorphous silica): Not applicable
  5. Melting point: 1700 C (3100 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with fluorine, oxygen dilfuoride, and chlorine trifluoride will cause fire.
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Grant states that "particles of silica predominantly in the range of 2u to 3u introduced into the corneal stroma of rabbit eyes cause very little reaction."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of amorphous silica in an impinger, followed by dust counting utilizing an optical microscope. An analytical method for amorphous silica is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to amorphous silica may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during preparation by crushing, screening, calcining, and packing operations for industrial processes	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during mining and quarrying operations in extraction	Process enclosure; local exhaust ventilation; personal protective equipment

Operation	Controls
Use in manufacture of insulating materials including firebrick, insulation blocks, pipe covering, roofing felt, and asbestos panels	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a filter medium in food and beverage manufacture including sugar refining, brewing, wine and spirit manufacture, soft drinks, and purification of oils and fats	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of construction bonding materials including stucco, concrete, cement, plaster, and asphalt; manufacture of abrasive cleaning and polishing agents including scouring and polishing soaps and powders	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of surface coatings as porous extender and flattening agent in paint; as a filler agent for paints, lacquers, and varnishes; filler in paper manufacture, agricultural chemicals, and mineral filler in manufacture of plastics and vinyls	Process enclosure; local exhaust ventilation; personal protective equipment
Use in dry grinding operations including grinding and polishing with natural abrasive wheels; manufacture of absorbent floor cleaning agents for use in industry, refineries, and gas stations; use as a parting powder in foundry operations	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of pharmaceuticals and as a constituent of pill masses, dentifrices, and salves; use in pottery manufacture in glazes and bodies; use in water treatment; use as a carrier for nickel catalysts in petroleum and petrochemical industries	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If amorphous silica including diatomaceous earth gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or releases until cleanup has been completed.

• If amorphous silica is spilled or potentially hazardous quantities are released, the following steps should be t

1. Ventilate area of spill or release.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Amorphous silica may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Silica (Amorphous)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Silica (Amorphous)," *Hygienic Guide Series*, Detroit, Michigan, 1958.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Cooper, W C., and Cralley, L. J.: "Pneumoconiosis in Diatomite Mining and Processing," U.S. Public Health Service Publication No. 601, U.S. Government Printing Office, Washington, D.C., pp. 62-96, 1958.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dutra, F. R.: "Diatomaceous Earth Pneumoconiosis," *Archives of Environmental Health,* 11:613-617, 619, 1

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969. /*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Oechsli, W. R., et al.: "Diatomite Pneumoconiosis: Roentgen Characteristics and Classification," *American Journal of Roentgenology, Radium Therapy and Nuclear Medicine,* 85:263-270, 1961.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Schepers, G. W. H., et al.: "The Biological Action of Degussa Submicron Amorphous Silica Dust (Dow Corning Silica). I. Inhalation Studies on Rats," *A.M.A. Archives of Industrial Health,* 16:125-146, 1957.

• Smart, R. H., and Anderson, W. M.: "Pneumoconiosis Due to Diatomaceous Earth - Clinical and X-Ray Aspects," *Industrial Medicine and Surgery,* 21:509-518, 1952.

• Tebbens, B. D., and Beard, R. R.: "Experiments on Diatomaceous Earth Pneumoconiosis. I. Natural Diatomaceous Earth in Guinea Pigs," *A.M.A. Archives of Industrial Health,* 16:55-63, 1957.

RESPIRATORY PROTECTION FOR AMORPHOUS SILICA (INCLUDING NATURAL AND DIATOMACEOUS EARTH)

Condition	Minimum Respiratory Protection* Required Above 20 mppcf
Particulate Concentration	
100 mppcf or less	Any dust and mist respirator.
200 mppcf or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
1000 mppcf or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 mppcf or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 10,000 mppcf or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Crystalline Silica

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: SiO_2
- Synonyms: Quartz; coesite; cristobalite; tridymite
- Appearance and odor: Colorless, odorless solid. (Crystalline silica may be a component of many mineral dusts).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for crystalline silica is (for respirable dust) 10 milligrams silica per cubic meter of air (mg/m³) divided by the percent SiO_2 2 averaged over an eight-hour work shift, and(for total dust) 30 mg/m³ divided by the percent SiO_2 2 averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit changed to 50 micrograms respirable free silica per cubic meter of air (ug/m³) averaged over a work shift of up to 10 hours per day, 40 hours per week. Uncontrolled abrasive blasting with silica sand presents such a severe silicosis hazard that NIOSH has recommended that silica sand, or other materials containing more than one percent free silica, be prohibited as an abrasive substance in abrasive blasting operations. The NIOSH Criteria Document for Crystalline Silica should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Crystalline silica can affect the body if it is inhaled.

- **Effects of overexposure**

Exposure to crystalline silica dust may cause scarring of the lungs with cough and shortness of breath. This is called "Silicosis."

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to crystalline silica.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to crystalline silica at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system and cardiovascular system should be stressed.

—14" x 17" chest roentgenogram: Crystalline silica causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Crystalline silica is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Crystalline silica or quartz dust causes silicosis, a form of disabling, progressive, and sometimes fatal pulmonary fibrosis characterized by the presence of typical nodulation in the lungs. The earliest lesions are seen in the region of the respiratory bronchioles. Lymphatics become obliterated by infiltration with dust-laden macrophages and granulation tissue. Morphologically, the typical lesion of silicosis is a firm nodule composed of concentrically arranged bundles of collagen. These nodules usually measure between 1 to 10 mm in diameter and appear around blood vessels and beneath the pleura, as well as in mediastinal lymph nodes. There

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1230

may be conglomeration of nodules as the disease progresses, leading to massive fibrosis. Histologically, the silicotic nodule consists of a relatively acellular, avascular core of hyalinized reticulin fibers arranged concentrically and blending with collagen fibers toward the periphery, which has well-defined borders. The particles of silica responsible for the reaction are birefringent and can be visualized under polarized light if they exceed 1 micrometer in diameter. Silica in the lungs can be identified by x-ray diffraction studies and by incinerating a portion of the lung, with subsequent analysis of the ash. The silica content of the normal lung should not exceed 0.2% dry weight. The clinical signs and symptoms of silicosis tend to be progressive with continued exposure to quantities of dust containing free silica, with advancing age, and with continued smoking habits. Symptoms may also be exacerbated by pulmonary infections and cardiac decompensation. Symptoms include cough, dyspnea, wheezing, and repeated nonspecific chest illnesses. Impairment of pulmonary function may be progressive. In individual cases there may be little or no decrement when simple discrete nodular silicosis is present, but when nodulations become larger or when conglomeration occurs, recognizable cardiopulmonary impairment tends to occur. Progression of symptoms usually continues after dust exposure ceases. While there may be a factor of individual susceptibility to a given exposure to silica dust, the risk of onset and the rate of progression of the pulmonary lesion is clearly related to the character of the exposure (dust concentration and duration). The disease tends to occur after an exposure measured in years rather than months. Occasionally, exposures to very high concentrations occur in short periods of time in occupations such as sandblasters and tunnel workers; in these cases of acute or rapidly-developing silicosis there may be severe respiratory symptoms resulting in death. It is generally accepted that silicosis predisposes to active tuberculosis, and that the combined disease tends to be more rapidly progressive than uncomplicated silicosis. A group of 972 granite-shed workers was studied to relate exposure levels to incidence of silicosis. The workers were grouped according to average exposure levels: 3 – 9, 20, 27 – 44, 37–60 particles per cubic foot (mppcf). Those with the highest dust exposure showed development of early silicosis in 40% of the workers after 2 years and 100% after 4 years of exposure. The development of silicosis in the remaining workers appeared to be proportional to the dust exposure. At the second highest exposure level (27-44 mppcf), early stages of silicosis appeared after 4 years of exposure and more advanced stages developed by the seventh year. In the group exposed at an average of 20 mppcf there was little indication of severe effects upon the health of the workers. In the lowest exposure group, where the average dust concentration was 6 mppcf (range 3 to 9 mppcf), there was no indication of any untoward effects of dust exposure on workers.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 60.1
  2. Boiling point (760 mm Hg): 2230 C (4046 F)
  3. Specific gravity (water = 1): 2.2– 3.0
  4. Vapor density (air = 1 at boiling point of crystalline silica): Not applicable
  5. Melting point: 1600 C (2912 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, oxygen difluoride, etc. may cause fires.
  3. Hazardous decomposition products: None
  4. Special precautions: Crystalline silica is attacked by hydrogen fluoride (or hydrofluoric acid).
- **Flammability**
  1. Not combustible
- **Warning properties**

Grant states that crystalline silica "has been observed to cause fibrotic nodules in the eye analogous to pulmonary silicosis. Particles of silica predominantly in the range of 2u to 3u introduced into the corneal stroma of rabbit eyes cause very little reaction. The same particles introduced into the anterior chamber sink to the bottom of the chamber and in the course of three to five weeks cause an inflammatory reaction with formation of fibrotic nodules in the iridocorneal angle. The reaction is quite different and more severe than that induced by brickdust, glass, or magnesium silicate . . . .

"An apparently unique report of involvement of the cornea in foundry workers who developed pulmonary silicosis has described gradual decrease in visual acuity due to corneal opacities in the pupillary area and has reported spectroscopic analytical evidence of an abnormally high silicon content in the cornea."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of crystalline silica on a filter, followed by an x-ray diffraction analysis. A detailed analytical method for

diffraction analysis. An analytical method for crystalline silica is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to crystalline silica may occur and control methods which may be effective in each case:

Operation	Controls
Use in metallurgy industry for foundry molds, iron and steel castings, flux in smelting basic ores	Local exhaust ventilation; general dilution ventilation; wet process; personal protective equipment
Use in manufacture of fiberglass for electrical insulation, chemical filtration, and reinforcing fabrics	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation from refining of sand for production of quartz	Process enclosure; local exhaust ventilation; water spray; personal protective equipment
Use in ceramics industry; use as an abrasive in scouring and polishing soaps and powders, flint sand paper, metal polishes, and sand blast work	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in processing synthetic quartz	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of refractories and building products; use in manufacture of electrical instruments for piezoelectric properties	Local exhaust ventilation; general dilution ventilation; wet process; personal protective equipment
Use in grading and classification of electronic and optical grade quartz	Local exhaust ventilation; general dilution ventilation
Use in manufacture of optical equipment in prisms, wedges, and lenses	Local exhaust ventilation; general dilution ventilation; wet process; personal protective equipment
Use in a variety of processes as paint extender, lining for acid towers, in the chemical industry in dental composition, in rocket engines and spacecraft, and graining lithographic plates	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during granite and similar material processing	Local exhaust ventilation; general dilution ventilation; wet process; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If crystalline silica dust gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of crystalline silica dust, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or releases until cleanup has been completed.

• If crystalline silica is spilled or released in hazardous concentrations, the following steps should be taken:

1. Ventilate area of spill or release.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Crystalline silica may be disposed of in a secured sanitary landfill.

ADDITIONAL INFORMATION

To find additional information on crystalline silica, look up crystalline silica in the following documents:

• Medical Surveillance for Chemical Hazards

• Respiratory Protection for Chemical Hazards

• Personal Protection and Sanitation for Chemical Hazards

• NIOSH Criteria Document for Crystalline Silica (November 1974)

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Silica (Quartz)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Silica (Free Silica, Silicon Dioxide)," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Crystalline Silica*, HEW Publication No. (NIOSH) 75-120, GPO No. 017-033-00050, U.S. Government Printing Office, Washington, D.C., 1974.

• Zenz, C.: *Occupational Medicine - Principles and Applications*, Year Book Medical Publishers, Chicago, 1975

RESPIRATORY PROTECTION FOR CRYSTALLINE SILICA

Condition	Minimum Respiratory Protection* Required Above X** mg/m³
Particulate Concentration	
5X** mg/m³ or less	Any dust respirator.
10X** mg/m³ or less	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50X** mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500X** mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 500X** mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**X indicates the permissible exposure as defined above.

Occupational Health Guideline for Silver Metal and Soluble Silver Compounds

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to metallic silver and all soluble silver compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Silver, metallic

- Formula: Ag
- Synonyms: None
- Appearance and odor: Characteristic white metallic solid with no odor.

Silver nitrate

- Formula: $AgNO_3$
- Synonyms: Argerol; lunar caustic
- Appearance and odor: Colorless and odorless solid which may become gray on storage.

Silver fluoride

- Formula: AgF
- Synonyms: None
- Appearance and odor: Yellow-white, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for silver metal and soluble silver compounds is 0.01 milligram of silver metal and soluble silver compounds per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for silver metal and soluble silver compounds from 0.01 mg/m^3 to 0.1 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Silver or soluble silver compounds can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

Silver or soluble silver compounds can cause discoloration or blue-gray darkening of the eyes, nose, throat, and skin. Silver nitrate is strongly corrosive and can cause burns and permanent damage to the eyes and can burn the skin.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to silver metal or soluble silver compounds.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to silver metal and soluble silver compounds at potentially hazardous levels:

1. Initial Medical Examination:

—Examination of the nasal septum, eyes, and skin for evidence of pigmentation: The purpose is to establish a baseline for future observations of silver deposition in tissues.

2. Periodic Medical Examination: The aforementioned

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1235

medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

The dust of silver and its soluble compounds cause argyria, the local or generalized impregnation of the mucous membranes, skin, and eyes with silver. Localized argyria occurs in the skin, eyes, nasal septum and throat, where gray-blue patches of pigmentation are formed without evidence of tissue reaction. Generalized argyria is recognized by the widespread pigmentation of the skin and may be seen first in the conjunctiva, with some localization in the inner canthus. Argyrosis of the respiratory tract has been described in two workers involved in the manufacture of silver nitrate; their only symptom was mild, chronic bronchitis; bronchoscopy revealed tracheobronchial pigmentation; biopsy of the nasal mucous membrane showed silver deposition in the subepithelial area. A total body burden from 1 to 5 g of silver will lead to generalized argyria. Silver, once deposited in the body, is poorly excreted in the urine in amounts detectable by spectrochemical methods. Silver nitrate (lunar caustic) may cause irritation, ulcers, and discoloration of skin; if ingested, it may cause abdominal pain and gastroenteritis.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Silver, metallic**

1. Molecular weight: 107.9
2. Boiling point (760 mm Hg): 2200 C (3992 F)
3. Specific gravity (water = 1): 10.4
4. Vapor density (air = 1 at boiling point of metallic silver): Not applicable
5. Melting point: 966 C (1771 F)
6. Vapor pressure at 20 C (68 F): Negligible
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Silver nitrate**

1. Molecular weight: 169.9
2. Boiling point (760 mm Hg): 444 C (831 F) (decomposes)
3. Specific gravity (water = 1): 4.4
4. Vapor density (air = 1 at boiling point of silver nitrate): Not applicable
5. Melting point: 209 C (408 F)
6. Vapor pressure at 20 C (68 F): Negligible
7. Solubility in water, g/100 g water at 20 C (68 F): 245
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Silver fluoride**

1. Molecular weight: 126.9
2. Boiling point (760 mm Hg): 1159 C (2119 F) (approximately)
3. Specific gravity (water = 1): 5.8
4. Vapor density (air = 1 at boiling point of silver fluoride): Not applicable
5. Melting point: 435 C (815 F)
6. Vapor pressure at 20 C (68 F): Negligible
7. Solubility in water, g/100 g water at 20 C (68 F): 64
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact of metallic silver and soluble silver compounds with acetylene may cause formation of silver acetylide that is sensitive to shock. Contact with ammonia may cause formation of compounds that are explosive when dry. Contact with strong hydrogen peroxide solutions will cause violent decomposition to oxygen gas.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen) may be released when some soluble silver compounds decompose.
4. Special precautions: Soluble silver compounds will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Most soluble silver compounds are not combustible. However, silver nitrate is a strong oxidizing material capable of increasing the flammability of combustible, organic, or other readily oxidizable materials. The following soluble silver compounds are explosives and should be stored and handled in accordance with 29 CFR 1910.109: silver acetylide, silver azide, silver fulminate, silver oxalate mixtures, silver styphnate, silver tartarate mixtures, and silver tetrazene.

• **Warning properties**

According to Stecher "many silver salts are irritating . . . to mucous membranes." Grant notes that many simple silver salts and silver ammonium compounds are injurious to the eye. According to Grant, "a great many reports have been published describing argyrosis of the eye, either from local contact with silver compounds or as a part of a generalized argyrosis from systemic absorption of silver or its compounds." Since there are inadequate data to assess the effects on the eye at or near the permissible exposure limit, for the purposes of this guideline, silver metal and soluble silver compounds are considered to have poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for silver metal and soluble si r

compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with powdered metallic silver or solids or liquids containing soluble silver compounds, where skin contact may occur.
- If employees' clothing may have become contaminated with solids or liquids containing soluble silver compounds, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with metallic silver or soluble silver compounds should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of substances from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the substances, the person performing the operation should be informed of substances' hazardous properties.
- Non-impervious clothing which becomes contaminated with metallic silver or soluble silver compounds should be removed promptly and not reworn until the metallic silver or soluble silver compounds are removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of powdered metallic silver or solids or liquids containing soluble silver compounds contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to silver nitrate or solutions containing 5 percent or more silver nitrate by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with metallic silver or soluble silver compounds should be promptly washed or showered to remove any metallic silver or soluble silver compounds.
- Eating and smoking should not be permitted in areas where metallic silver or solids or liquids containing soluble silver compounds are handled, processed, or stored.
- Employees who handle powdered metallic silver or solids or liquids containing soluble silver compounds should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to silver metal and soluble silver compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during mining and purification from ore; during refining from secondary sources	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of silver nitrate for use in photography, mirrors, plating, inks, dyes, and porcelain; and as germicides, antiseptics, caustics, and analytical reagents	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of silver salts as catalysts in oxidation-reduction and polymerization reactions; in chemical synthesis; in glass manufacture, in silver-plating, in photography, as laboratory reagents, and in medicine	Process enclosure; local exhaust ventilation; personal protective equipment

Operation	Controls
Liberation from manufacture and casting of alloys; during fabrication of silver metal, alloys, and bi-metals for electrical uses; and during electroplating operations and fabrication of solders and brazing alloys; during manufacture and use of photographic chemicals and materials; during manufacture of mirrors, and during manufacture of silver powder pigments and paints	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during manufacture of silver powder pigments and paints; during manufacture of mirrors; during manufacture of photographic chemicals and materials	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If powdered metallic silver or solids or liquids containing soluble silver compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If powdered metallic silver or solids or liquids containing soluble silver compounds get on the skin, flush the contaminated skin with water. If powdered metallic silver or solids or liquids containing soluble silver compounds penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation is present after washing, get medical attention. Other silver compounds should be removed by promptly flushing the skin with water.

• **Breathing**

If a person breathes in large amounts of silver metal or soluble silver compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If silver nitrate or other corrosive soluble silver compounds have been swallowed and the person is conscious, give him large quantities of water immediately to dilute the silver nitrate or other corrosive silver compounds. Do not attempt to make the exposed person vomit. Get medical attention immediately. When non-corrosive soluble silver compounds have been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If powdered silver metal or soluble silver compounds are spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing silver metal or soluble silver compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Silver metal and soluble silver compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Silver," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Buckley, W. R., et al.: "Localized Argyria. II. Clinical Nature of the Silver Containing Particles," *Archives of Dermatology*, 92:697-705, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products5(3rd ed.), Williams and Wilkins, Baltimore, 1969.*
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.
• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity,* U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

RESPIRATORY PROTECTION FOR SILVER METAL AND SOLUBLE SILVER COMPOUNDS

Condition	Minimum Respiratory Protection* Required Above 0.01 mg/m³
Particulate Concentration	
0.5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter.
20 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 20 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Soapstone

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $3\,MgO{\cdot}4SiO_2{\cdot}H_2O$
- Synonyms: Massive talc; steatite
- Appearance and odor: Slippery solid with no odor. (Soapstone contains less than 10% tremolite and less than 1% crystalline silica).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for soapstone is 20 million particles of soapstone per cubic foot of air (mppcf) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Soapstone can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

Exposure to soapstone may cause scarring of the lungs. Shortness of breath, cough, enlargement of the ends of the fingers and heart failure may occur with this condition. Workers exposed to soapstone have been found to have an increased amount of cancer of the lungs and pleura.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to soapstone.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to soapstone at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the lungs and cardiovascular system should be stressed.

—14" x 17" chest roentgenogram: Soapstone contains fibrous talc which can cause pneumoconiosis and lung cancer. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Soapstone contains fibrous talc which is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Soapstone dust contains varying percentages of fibrous talc, which causes fibrotic pneumoconiosis and an increased incidence of cancer of the lungs and pleura. In the development of talc pneumoconiosis or talcosis, the subject initially is symptom-free, but cough and dyspnea develop as the disease progresses; cyanosis, digital clubbing, and cor pulmonale occur in advanced cases. The disease progresses slowly, even in the absence of continued exposure; occasionally, the disease may progress rapidly, with death occurring within a few years of a very heavy exposure. In an epidemiologic study of 260 workers with 15 or more years of exposure to commercial talc dust containing talc, tremolite, anthophyllite, carbonate dusts, and a small amount of free silica, the mortality rate from cancer of the lungs and pleura was four times greater than expected; in addition, a major cause of death among these workers was cor pulmonale, a result of the pneumoconiosis.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1976

-1200

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Formula weight: 379.2
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): 2.7 – 2.8
  4. Vapor density (air = 1 at boiling point of soapstone): Not applicable
  5. Melting point: Not applicable
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

According to the *Documentation of TLV's*, "soapstone does not have a precise mineralogic connotation. Many rocks of variable composition are sometimes so designated. Massive talc is sometimes called soapstone or steatite. The terms are not synonymous, and some forms of soapstone have as little as 50% talc." Grant states that "talc employed in fulling of cloth is said to have caused conjunctival inflammation resulting in symblepharon, severe enough to require surgery in some instances."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for soapstone had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to soapstone may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from mining, quarrying, and blasting of soapstone	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of acid-proof coverings in floors, tables, sinks, etc.; use in switch-board panels for high electrical resistance; use in Kraft process of pulp manufacture; use in fume cupboards and fireless cookers; use in crayons for marking cloth, metal, and glass	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If soapstone gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of soapstone, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Under-

1231

stand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or releases until cleanup has been completed.

• If hazardous amounts of soapstone are spilled or released, the following steps should be taken:

1. Ventilate area of spill or release.

2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Soapstone may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Soapstone," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Blejer, H. P., and Arlon, R.: "Talc: A Possible Occupational and Environmental Carcinogen," *Journal of Occupational Medicine*, 15:92-97, 1973.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kleinfeld, M., et al.: "Effect of Talc Dust Inhalation on Lung Function," *Archives of Environmental Health*, 10:431-437, 1965.

• Kleinfeld, M., et al.: "Lung Function in Talc Workers – A Comparative Physiologic Study of Workers Exposed to Fibrous and Granular Talc Dusts," *Archives of Environmental Health*, 9:559-566, 1964.

• Kleinfeld, M., et al.: "Mortality Among Talc Miners and Millers in New York State," *Archives of Environmental Health*, 14:663-667, 1967.

• Kleinfeld, M., et al.: "Mortality Experiences Among Talc Workers: A Follow-up Study," *Journal of Occupational Medicine*, 16:345-349, 1974.

• Kleinfeld, M., et al.: "Talc Pneumoconiosis – A Report of Six Patients with Postmortem Findings," *Archives of Environmental Health*, 7:107-121, 1963.

• Morgan, W. K. C., and Seaton, A.: *Occupational Lung Diseases*, Saunders, Philadelphia, 1975.

• Spiegel, R. M.: "Medical Aspects of Talc" in A. Goodwin (ed.), *Proceedings of the Symposium on Talc*, Washington, D.C., May 8, 1973, Bureau of Mines Report No. 8639, U.S. Government Printing Office, Washington, D.C., pp. 97-102, 1973.

-1232

RESPIRATORY PROTECTION FOR SOAPSTONE

Condition	Minimum Respiratory Protection* Required Above 20 mppcf
Particulate Concentration	
100 mppcf or less	Any dust respirator.
200 mppcf or less	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
1000 mppcf or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 mppcf or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter.
Greater than 10,000 mppcf or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Sodium Fluoroacetate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2FCOONa$
- Synonyms: 1080; sodium monofluoroacetate; SFA
- Appearance and odor: Fluffy, white, odorless hygroscopic solid (sometimes dyed black).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sodium fluoroacetate is 0.05 milligram of sodium fluoroacetate per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Sodium fluoroacetate can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Sodium fluoroacetate may cause vomiting, apprehension, hallucinations, tingling of the nose and face, numbness of the face and facial twitching. It may also cause excitation and convulsions. Depression may occur after and between convulsive episodes. The heart may beat irregularly or stop. Symptoms are often delayed 30 minutes to two hours after swallowing this chemical.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sodium fluoroacetate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sodium fluoroacetate at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of convulsive disorders or cardiovascular disease would be expected to be at increased risk from exposures. Examination of the nervous system, heart, lungs, and kidneys should be stressed.

—Urinalysis: Since kidney damage has been observed in humans exposed to sodium fluoroacetate, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—An electrocardiogram: Sodium fluoroacetate causes cardiac arrhythmias. Periodic surveillance of the heart is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Sodium fluoroacetate as the dust or in solution is highly toxic and causes convulsions and ventricular fibrillation. Fluoroacetate is metabolized to fluorocitrate, which blocks the tricarboxylic acid cycle, an essential element of energy production in mammalian cells. Estimates of the lethal oral dose in humans range from 2 to 10 mg/kg. Onset of symptoms after ingestion is frequently delayed for 30 minutes to 2 hours; effects are vomiting, apprehension, auditory hallucinations, nystagmus, tingling sensation of nose, numbness of face, facial twitching, and epileptiform convulsions. After a period of several hours there may be pulsus alternans, long sequences of ectopic heartbeats (often multifocal), tachycardia, ventricular fibrillation, and death. In a fatal

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1201

case of ingestion, autopsy findings included hemorrhagic pulmonary edema and degeneration of renal tubules.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 100
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): Greater than 1
  4. Vapor density (air = 1 at boiling point of sodium fluoroacetate): Not applicable
  5. Melting point: 200 C (392 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 111
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None.
  2. Incompatibilities: None.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen fluoride and carbon monoxide) may be released when sodium fluoroacetate decomposes.
  4. Special precautions: None.
- **Flammability**
  1. Not combustible
- **Warning properties**

Sodium fluoroacetate is not known to be an eye irritant. Grant describes some effects on the eye caused by this compound, but these are systemic effects.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for sodium fluoroacetate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with sodium fluoroacetate or solutions containing sodium fluoroacetate.

• If employees' clothing has had any possibility of being contaminated with sodium fluoroacetate or solutions containing sodium fluoroacetate, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with sodium fluoroacetate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of sodium fluoroacetate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the sodium fluoroacetate, the person performing the operation should be informed of sodium fluoroacetate's hazardous properties.

• Where there is any possibility of exposure of an employee's body to sodium fluoroacetate or solutions containing sodium fluoroacetate, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with sodium fluoroacetate should be removed immediately and not reworn until the sodium fluoroacetate is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where sodium fluoroacetate or solutions containing sodium fluoroacetate may contact the eyes.

SANITATION

• Skin that becomes contaminated with sodium fluoroacetate should be immediately washed or showered to remove any sodium fluoroacetate.

• Workers subject to skin contact with sodium fluoroacetate or solutions containing sodium fluoroacetate should wash any areas of the body which may have contacted sodium fluoroacetate at the end of each work

day.

• Eating and smoking should not be permitted in areas where sodium fluoroacetate or solutions containing sodium fluoroacetate are handled, processed, or stored.

• Employees who handle sodium fluoroacetate or solutions containing sodium fluoroacetate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sodium fluoroacetate may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of pesticides	Local exhaust ventilation; personal protective equipment
Use in hand or aircraft application for pest control	Personal protective equipment; material substitution (product replacement)
Manufacture of sodium fluoroacetate	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If sodium fluoroacetate or solutions containing sodium fluoroacetate get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If sodium fluoroacetate or solutions containing sodium fluoroacetate get on the skin, immediately flush the contaminated skin with water. If sodium fluoroacetate or solutions containing sodium fluoroacetate penetrate through the clothing, remove the clothing promptly and flush the skin with water. If irritation is present after washing, get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of sodium fluoroacetate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When sodium fluoroacetate or solutions containing sodium fluoroacetate have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If sodium fluoroacetate is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing sodium fluoroacetate should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Sodium fluoroacetate may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Sodium Fluoroacetate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Harrisson, J. W. E., et al.: "Acute Poisoning with Sodium Fluoroacetate (Compound 1080)," *Journal of the American Medical Association*, 149:1520-1522, 1952.

• Harrisson, J. W. E., et al.: "Fluoroacetate (1080) Poisoning," *Industrial Medicine and Surgery*, 21:440-442, 1952.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.
• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

RESPIRATORY PROTECTION FOR SODIUM FLUOROACETATE

Condition	Minimum Respiratory Protection* Required Above 0.05 mg/m³
Particulate Concentration	
0.25 mg/m³ or less	Any dust and mist respirator, except single-use.
0.5 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
2.5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Sodium Hydroxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: NaOH
- Synonyms: Caustic soda, soda lye, lye
- Appearance and odor: White, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sodium hydroxide is 2 milligrams of sodium hydroxide per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be changed to a ceiling of 2 mg/m^3 over a 15-minute period. The NIOSH Criteria Document for Sodium Hydroxide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Sodium hydroxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Sodium hydroxide is a strong alkali and is corrosive to any tissue with which it comes in contact. Effects from inhalation of the dusts and mists will vary from mild irritation to destructive burns depending on the severity of exposure. Severe pneumonitis may occur. Sodium hydroxide as a solid or in dusts, mists or solutions may cause irritation of the eyes and, with greater exposure, severe burns with possible blindness. Contact of the skin with sodium hydroxide as a solid or in dusts, mists or solutions may cause skin irritation and, with greater exposure, severe burns with scarring. Swallowing solid sodium hydroxide or solutions of sodium hydroxide may cause severe burns of the mouth, throat, and stomach. Death may result. Severe scarring of the throat may occur on recovery after swallowing sodium hydroxide. An increased number of esophageal cancer cases have been reported to occur in individuals who have scarring of the esophagus from swallowing sodium hydroxide.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sodium hydroxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sodium hydroxide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes and respiratory tract should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Sodium hydroxide causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Sodium hydroxide is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Sodium hydroxide is a strong alkali; the mist, dust and solutions cause severe injury to the eyes, mucous mem-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1208

branes, and skin. Although inhalation is usually of secondary importance in industrial exposures, the effects from the dust or mist will vary from mild irritation of the nose at 2 mg/m³ to severe pneumonitis, depending on the severity of exposure. The greatest industrial hazard is rapid tissue destruction of eyes or skin upon contact with either the solid or with concentrated solutions. Contact with the eyes causes disintegration and sloughing of conjunctival and corneal epithelium, corneal opacification, marked edema, and ulceration; after 7 to 13 days either gradual recovery begins, or there is progression of ulceration and corneal opacification. Complications of severe eye burns are symblepharon (adhesion of the lid to the eyeball) with overgrowth of the cornea by a vascularized membrane, progressive or recurrent corneal ulceration, and permanent corneal opacification. On the skin, solutions of 25 to 50% cause the sensation of irritation within about 3 minutes; with solutions of 4%, this does not occur until after several hours. If not removed from the skin, severe burns with deep ulceration will occur; exposure to the dust or mist may cause multiple small burns, with temporary loss of hair. Ingestion produces severe pain in the esophagus and stomach, corrosion of the lips, mouth, tongue, and pharynx and the vomiting of large pieces of mucosa; cases of squamous cell carcinoma of the esophagus have occurred with latent periods of 12 to 42 years after ingestion; these cancers may have been sequelae of tissue destruction and possibly scar formation rather than from a direct carcinogenic action of sodium hydroxide itself.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 40
  2. Boiling point (760 mm Hg): 1390 C (2534 F)
  3. Specific gravity (water = 1): 2.13
  4. Vapor density (air = 1 at boiling point of sodium hydroxide): Not applicable
  5. Melting point: 310 C (590 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 50
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with water, acids, flammable liquids, and organic halogen compounds, especially trichloroethylene, may cause fires and explosions. Contact with metals such as aluminum, tin, and zinc causes formation of flammable hydrogen gas. Contact with nitromethane and other similar nitro compounds causes formation of shock-sensitive salts.
  3. Hazardous decomposition products: None
  4. Special precautions: Sodium hydroxide will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**

Grant states that sodium hydroxide "is severely injurious to all tissues, and causes some of the most severe injuries of the eye. The serious problem presented by sodium hydroxide and other alkalies which cause devastating injuries of the eye have been succinctly and well described by Stanley, emphasizing particularly the dangers of caustic household drain cleaners that contain sodium hydroxide.

"The effects of splashes of sodium hydroxide on the eyes of human beings have been described innumerable times . . . . Damage of the cornea, conjunctiva, and episcleral tissues is usual, but damage of intraocular structures is relatively rare."

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of sodium hydroxide. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of sodium hydroxide in a glass bubbler containing hydrochloric acid, followed by subsequent titration. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure sodium hydroxide may be used. An analytical method for sodium hydroxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 1, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00267-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental

concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with sodium hydroxide or solutions of sodium hydroxide.

• If employees' clothing may have become contaminated with solid sodium hydroxide, employees should change into uncontaminated clothing before leaving the work premises.

• Where there is any possibility of exposure of an employee's body to sodium hydroxide or solutions of sodium hydroxide, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with sodium hydroxide should be removed immediately and not reworn until the sodium hydroxide is removed from the clothing.

• Clothing contaminated with sodium hydroxide should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of sodium hydroxide from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the sodium hydroxide, the person performing the operation should be informed of sodium hydroxide's hazardous properties.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of sodium hydroxide or solutions of sodium hydroxide contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to sodium hydroxide or solutions of sodium hydroxide, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with sodium hydroxide should be immediately washed or showered to remove any sodium hydroxide.

• Eating and smoking should not be permitted in areas where sodium hydroxide or solutions containing sodium hydroxide are stored.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sodium hydroxide may occur and control methods which may be effective in each case:

Operation	Controls
Use in chemical manufacture; explosives manufacture; use in boiler water and as a laboratory reagent; use in pH control in textiles, paper, and chemical industries	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of synthetic fibers and plastics	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of pulp and paper; in pulping Kraft process; manufacture of insulating board	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in metal processing and refining; use in petroleum refining for removal of sulfur compounds; as a flotation reagent; as a modifier and slime depressant; in pH control	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of soaps and detergents; as a saponifying agent; use in metal cleaning; in laundering, bleaching, and dishwashing; use in drain cleaners and oven cleaners	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in food processing to peel fruits and vegetables, process olives, and refine vegetable oils	Local exhaust ventilation; general dilution ventilation; personal protective equipment

Use in glass manufacture as a source of sodium oxide	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If sodium hydroxide, as a solid or in dusts, mists, or solutions, get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If sodium hydroxide, as a solid or in dusts, mists, or solutions, gets on the skin, immediately flush the contaminated skin with water. If sodium hydroxide, as a solid or in dusts, mists, or solutions, penetrates through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of sodium hydroxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If solutions of sodium hydroxide have been swallowed and the person is conscious, give him large quantities of water immediately to dilute the sodium hydroxide. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If sodium hydroxide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Dilute with water and neutralize with 6 molar hydrochloric acid.

• Waste disposal method:

Sodium hydroxide may be disposed of in sealed containers in a secured sanitary landfill.

ADDITIONAL INFORMATION

To find additional information on sodium hydroxide, look up sodium hydroxide in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards
• NIOSH Criteria Document for Sodium Hydroxide (September 1975)

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Sodium Hydroxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• *Hygienic Information Guide No. 36 – Sodium Hydroxide*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-9, Sodium Hydroxide*, Washington, D.C., 1974.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Sodium Hydroxide*, HEW Publication No. (NIOSH) 76-105, GPO No. 017-033-00110, U.S. Government Printing Office, Washington, D.C., 1975.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Inaustrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• von Oettingen, W. F.: *Poisoning: A Guide to Clinical Diagnosis and Treatment* (2nd ed.), Saunders, Philadelphia, 1958.

RESPIRATORY PROTECTION FOR SODIUM HYDROXIDE

Condition	Minimum Respiratory Protection* Required Above 2 mg/m³
Particulate Concentration	
100 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
200 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator with a full facepiece, except single-use. Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of sodium hydroxide; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 200 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Stibine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: SbH_3
- Synonyms: Hydrogen antimonide; antimony trihydride
- Appearance and odor: Colorless gas with a disagreeable odor like hydrogen sulfide.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for stibine is 0.1 part of stibine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.5 milligram of stibine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Stibine can affect the body if it is inhaled.

- **Effects of overexposure**

1. Short-term Exposure: Stibine may cause destruction of the red blood cells with headache, nausea, weakness, and back and abdominal pain. It may later cause dark red urine, yellow jaundice, kidney damage, and death. It may also cause lung irritation.

2. Long-term Exposure: Not known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to stibine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to stibine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, liver, and kidneys should be stressed.

—A complete blood count: Stibine causes red blood cell hemolysis. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Urinalysis: Since kidney damage has been observed in humans exposed to stibine, a urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Since liver damage has been observed in humans exposed to stibine, a profile of liver function should be performed by using a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Stibine gas is an extremely toxic hemolytic agent which causes injury to the liver and kidneys; it also may be a lung irritant. Guinea pigs exposed to 65 ppm for 1 hour developed hemoglobinuria, followed within a few days by profound anemia. Cats and dogs exposed to 40-45 ppm for 1 hour developed pulmonary edema, and some died within 24 hours. Acute exposures to humans would be expected to cause rapid destruction of red blood cells, hemoglobinuria, anuria, jaundice, and death. Workers exposed to a mixture of gases of stibine, arsine, and hydrogen sulfide developed headache, weakness, nausea, abdominal and lumbar pain, hematuria, and profound anemia.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1303

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 124.8
  2. Boiling point (760 mm Hg): −17 C (1 F)
  3. Specific gravity (water = 1): Liquid = 2.2 at boiling point
  4. Vapor density (air = 1 at boiling point of stibine): 4.34
  5. Melting point: −88 C (−126 F)
  6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.1
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Stibine reacts with acids, halogenated hydrocarbons, oxidizers, and moisture.
  3. Hazardous decomposition products: Antimony and hydrogen will be released when stibine decomposes.
  4. Special precautions: None
- **Flammability**
  1. Flash point: Not applicable (gas)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Stop flow of gas.
- **Warning properties**
  1. Odor Threshold: Patty states that "stibine has an extremely unpleasant odor that can serve as a warning; whether the threshold of odor detection is sufficiently low to prevent injury is uncertain." No quantitative information is available concerning the odor threshold of stibine.
  2. Eye Irritation Level: Stibine is not known to be an eye irritant.
  3. Evaluation of Warning Properties: Since there is no quantitative information relating warning properties to air concentrations of stibine, this gas is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of stibine on mercuric chloride-impregnated silica gel, followed by extraction with concentrated hydrochloric acid, and colorimetric analysis. An analytical method for stibine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to stibine may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from treatment of scum formed on surface of molten metals treated with acid	Process enclosure; local exhaust ventilation; general dilution ventilation
Liberation during charging as storage batteries	Local exhaust ventilation; general dilution ventilation
Liberation from alloys of antimony compounds which come in contact with reducing acids	Process enclosure; local exhaust ventilation; general dilution ventilation
Liberation from purification of antimony by electrolysis	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as a chemical intermediate and in chemical synthesis	Process enclosure; local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of stibine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If stibine is leaked or released, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Control source of stibine formation.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Stibine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Stibine," *Hygienic Guide Series*, Detroit, Michigan, 1960.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR STIBINE

Condition	Minimum Respiratory Protection* Required Above 0.1 ppm
Gas Concentration	
1 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
5 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
40 ppm or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 40 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against stibine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Stoddard Solvent

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: Generally C_8 through C_{11} paraffins (85%) and aromatics (15%)
- Synonyms: Dry cleaning safety solvent; mineral spirits
- Appearance and odor: Colorless liquid with kerosene-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for Stoddard solvent is 500 parts of Stoddard solvent per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 2950 milligrams of Stoddard solvent per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit for refined petroleum products, including Stoddard solvent, be reduced to 350 mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 1800 mg/m^3 measured over a 15-minute period. The NIOSH Criteria Document for Refined Petroleum Products should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Stoddard solvent can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to Stoddard solvent causes irritation of the eyes, nose, and throat, and may cause dizziness. Very high air concentrations may cause unconsciousness and death.

2. Long-term Exposure: Prolonged overexposure to the liquid may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to Stoddard solvent.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to Stoddard solvent at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the employee at increased risk, and to establish a baseline for future health monitoring. Examination of the skin, liver, blood, urine, and central nervous system should be stressed.

—Skin: Stoddard solvent is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver function tests: Stoddard Solvent may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

—Urinalysis: The kidneys may be affected by Stoddard solvent. Since kidney damage has been observed from exposure, a urinalysis should be performed to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—A complete blood count: A complete blood count should be performed, including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Respiratory system examination: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of Stoddard solvent might cause exacerbation of symptoms due to its irritant properties.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1307

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Stoddard solvent vapor is a mild narcotic and a mucous membrane irritant. Since it contains both aliphatic and aromatic hydrocarbons in varying concentrations, toxicologic opinion is based upon deductions as to the relative health hazard of the different fractions. The vapor of the aliphatic fractions is chiefly nonane and isodecane. The aromatic component is considered to be more toxic. Stoddard solvent has an odor threshold of about 4 to 5 mg/m³ and olfactory fatigue has been observed in about 6 minutes at low concentrations. Eye irritation was reported in a test exposure of human subjects at 850 mg/m³. Industrial exposures to unknown but fairly high concentrations over long periods have resulted in headaches, eye, nose, and throat irritation, fatigue, marrow hypoplasia and, in extreme cases, death. Dermal exposures to the liquid solvent have caused dermatitis and jaundice.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 144 (approximately)
2. Boiling point (760 mm Hg): 150 to 200 C (302 to 392 F)
3. Specific gravity (water = 1): 0.78
4. Vapor density (air = 1 at boiling point of Stoddard solvent): 5
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): 2 mm Hg (estimate)
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Less than 1

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving Stoddard solvent.
4. Special precautions: Stoddard solvent will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 38.7 to 60 C (102 to 140 F) (closed cup)
2. Autoignition temperature: 226 to 260 C (440 to 500 F)
3. Flammable limits in air, % by volume: Lower: 0.8
4. Extinguishant: Carbon dioxide, dry chemical, foam

• **Warning properties**

1. Odor Threshold: May gives an odor threshold of 30 ppm for Stoddard solvent (mineral spirits). According to the AIHA *Hygienic Guide* for Stoddard solvent, "most Stoddard solvents have a petroleum odor that is perceptible at about 1 ppm."
2. Eye Irritation Level: Grant states that "the vapor of Stoddard solvent is perceptively irritating to human eyes at 400 ppm."
3. Evaluation of Warning Properties: Through its odor and irritant effects, Stoddard solvent can be detected below the permissible exposure limit. For the purposes of this guideline, therefore, Stoddard solvent is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of Stoddard solvent. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of Stoddard solvent vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure Stoddard solvent may be used. An analytical method for Stoddard solvent is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed

vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid Stoddard solvent.

• Clothing wet with liquid Stoddard solvent should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of Stoddard solvent from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the Stoddard solvent, the person performing the operation should be informed of Stoddard solvent's hazardous properties.

• Any clothing which becomes wet with liquid Stoddard solvent should be removed promptly and not reworn until the Stoddard solvent is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid Stoddard solvent may contact the eyes.

SANITATION

• Skin that becomes wet with liquid Stoddard solvent should be promptly washed or showered with soap or mild detergent and water to remove any Stoddard solvent.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to Stoddard solvent may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in dry cleaning industry	Process enclosure; local exhaust ventilation; personal protective equipment
Use in paint and varnish industries	General dilution ventilation
Use as a solvent for printing inks and textile-printing industries	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of aerosol sprays as a solvent for paints, varnishes, and insecticides	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of sprays for pesticides, herbicides, household cleaners, and silicone compounds	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a solvent and thinner in protective coating materials	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in metal cleaning and degreasing; and in leather degreasing	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a general solvent in fabric waterproofing, processing of synthetic yarns, extraction of fats and oils, as a tackifying agent for rubber, in rubber cements, and in polishes	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If Stoddard solvent gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If Stoddard solvent gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If Stoddard solvent soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of Stoddard solvent, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration.

Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If Stoddard solvent has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If Stoddard solvent is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Stoddard solvent should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Stoddard solvent may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Stoddard Solvent," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Stoddard Solvent," *Hygienic Guide Series*, Detroit, Michigan, 1975.

• Davis, A., et al.: "The Effects on Human Volunteers of Exposure to Air Containing Gasoline Vapor," *Archives of Environmental Health*, 1:548-554, 1960.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Refined Petroleum Products*, HEW Publication No. (NIOSH) 77-192, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

-1320

RESPIRATORY PROTECTION FOR STODDARD SOLVENT

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Strychnine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{21}H_{22}N_2O_2$
- Synonyms: None
- Appearance and odor: Colorless, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for strychnine is 0.15 milligram of strychnine per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Strychnine affects the body after it is swallowed. There are no literature sources to indicate that strychnine presents a significant hazard from skin or eye exposure.

- **Effects of overexposure**

After swallowing strychnine, effects usually occur within 10 to 30 minutes and include stiffness of the face and neck muscles, increased excitability, restlessness, and apprehension. These symptoms may progress to repeated convulsions and death.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to strychnine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to strychnine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from strychnine exposure.

—Convulsive disorders: Strychnine causes convulsions. Persons with a history of convulsive disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Strychnine is a potent convulsant. In humans the mean lethal oral dose is approximately 100 to 120 mg. After ingestion, effects usually occur within 10 to 30 minutes and include stiffness of the face and neck muscles, increased reflex excitability, restlessness, apprehension, and heightened acuity of perception. Any sensory stimulus may produce a violent motor response which in the early stages of intoxication tends to be a coordinated extensor thrust and in later stages it may be a tetanic convulsion with opisthotonos; anoxia and cyanosis develop rapidly. Between convulsions, muscular relaxation is complete, breathing is resumed, and cyanosis lessens. Because sensation is unaffected, the convulsions are painful and lead to overwhelming fear; as many as 10 convulsions separated by intervals of 10 to 15 minutes may be experienced, but death often occurs after the second to fifth convulsion and even the first convulsion may be fatal if sustained; death is commonly due to asphyxia.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 334.4
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.36
4. Vapor density (air = 1 at boiling point of strychnine): Not applicable
5. Melting point: 268 C (547 F)
6. Vapor pressure at 20 C (68 F): Essentially zero

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1312

September 1978

7. Solubility in water, g/100 g water at 20 C (68 F): 0.02

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None.

2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released when strychnine decomposes.

4. Special precautions: None.

• **Flammability**

1. Not combustible

• **Warning properties**

Strychnine is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for strychnine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• If employees' clothing has had any possibility of being contaminated with strychnine or liquids containing strychnine, employees should change into uncontaminated clothing before leaving the work premises.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with strychnine where skin contact may occur.

• Clothing which has had any possibility of being contaminated with strychnine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of strychnine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the strychnine, the person performing the operation should be informed of strychnine's hazardous properties.

SANITATION

• Eating and smoking should not be permitted in areas where strychnine or liquids containing strychnine are handled, processed, or stored.

• Skin that becomes contaminated with strychnine or liquids containing strychnine should be promptly washed or showered to remove any strychnine.

• Employees who handle strychnine or liquids containing strychnine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to strychnine may occur and control methods which may be effective in each case:

Operation	Controls
Application and formulation of medicinals and pesticides	Personal protective equipment
Manufacture of strychnine	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If strychnine or liquids containing strychnine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention. Contact lenses should not be worn

when working with this chemical.

• **Skin Exposure**

If strychnine or liquids containing strychnine get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If strychnine or liquids containing strychnine penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of strychnine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When strychnine or liquids containing strychnine have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If strychnine is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquid containing strychnine should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Strychnine may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Strychine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

RESPIRATORY PROTECTION FOR STRYCHNINE

Condition	Minimum Respiratory Protection* Required Above 0.15 mg/m³
Particulate Concentration	
0.75 mg/m³ or less	Any dust respirator, except single-use.
1.5 mg/m³ or less	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
3 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. A powered air-purifying respirator with a high efficiency particulate filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 3 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Styrene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5CH=CH_2$
- Synonyms: Phenylethylene; vinylbenzene; cinnamene; styrene monomer
- Appearance and odor: Colorless liquid with a sweet aromatic odor at low concentrations. Sharp, penetrating, and disagreeable odor at higher concentrations.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for styrene is 100 parts of styrene per million parts of air (ppm) averaged over an eight-hour work shift, with a ceiling level of 200 ppm and an acceptable peak of 600 ppm for 5 minutes in any three-hour period. The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for styrene from 100 ppm to 50 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Styrene can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Styrene may irritate the eyes, nose, throat, and skin. High concentrations may cause a person to become sleepy or to become unconscious.
2. Long-term Exposure: Repeated skin contact with styrene may produce a skin rash.
3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to styrene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to styrene at potentially hazardous levels:
1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from styrene exposure.

—Central nervous system disorders: Since exposure to styrene vapor or liquid on the skin has been observed to result in central nervous system depression and occasional abnormalities in the electroencephalogram, persons with pre-existing disorders may be unusually susceptible to these effects.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of styrene might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Skin disease: Styrene is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Kidney disease: Although styrene is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Liver disease: Although styrene is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Exposure to concentrations of styrene above 200 ppm

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1315

September 1978

causes irritation of the eyes and upper respiratory tract. There is cracking and inflammation of the skin due to defatting. Higher exposures depress the central nervous system. Electroencephalographic changes have been reported. Styrene is excreted fairly rapidly in the urine, largely as hippuric acid.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 104
  2. Boiling point (760 mm Hg): 145 C (293 F)
  3. Specific gravity (water = 1): 0.90
  4. Vapor density (air = 1 at boiling point of styrene): 3.6
  5. Melting point: −30.6 C (−23 F)
  6. Vapor pressure at 20 C (68 F): 4.5 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.03
  8. Evaporation rate (butyl acetate = 1): 0.49
- **Reactivity**
  1. Conditions contributing to instability: Styrene is stabilized by a polymerization inhibitor (often tert-butylcatechol). If this is not present in adequate concentrations, styrene can polymerize and explode its container. The polymerization is also speeded up by temperatures above 66 C (150 F).
  2. Incompatibilities: Avoid contact with oxidizing agents and catalysts for vinyl polymerization, such as peroxides, strong acids, and aluminum chloride.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving styrene. Styrene fumes are very acrid.
  4. Special precautions: Styrene will corrode copper and copper alloys and dissolve rubber.
- **Flammability**
  1. Flash point: 32 C (90 F) (closed cup)
  2. Autoignition temperature: 490 C (914 F)
  3. Flammable limits in air, % by volume: Lower: 1.1; Upper: 6.1
  4. Extinguishant: Dry cemical, foam, or carbon dioxide
- **Warning properties**
  1. Odor Threshold: May reports that the odor threshold of styrene is 0.08 ppm.
  2. Eye Irritation Level: The AIHA *Hygienic Guide* reports that "styrene vapor at concentrations of 200 to 400 ppm was found to have transient irritant effects on the eyes."
  4. Evaluation of Warning Properties: Since the odor threshold of styrene is below the permissible exposure limit, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of styrene. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Peak Above Ceiling Evaluation**

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of styrene. Each measurement should consist of a 30-minute sample or a series of consecutive samples totalling 30 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of styrene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure styrene may be used. An analytical method for styrene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National

Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid styrene.

• Clothing wet with liquid styrene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of styrene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the styrene, the person performing the operation should be informed of styrene's hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid styrene should be removed promptly and not reworn until the styrene is removed from the clothing.

• Any clothing which becomes wet with liquid styrene should be removed immediately and not reworn until the styrene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid styrene may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid styrene should be promptly washed or showered with soap or mild detergent and water to remove any styrene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to styrene may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during spray-up manufacture of glass fiber, reinforced styrene-polyester articles	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during spray application of styrene polyester surface coatings	Process enclosure; local exhaust ventilation; personal protective equipment
Use during hand lay-up of glass fibers, reinforced styrene-polyester articles	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during molding of articles or potting electrical components with polystyrene	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during manufacture of tires and other rubber goods using styrene-butadiene elastomers (SBR)	General dilution ventilation
Use in manufacture of concretes	General dilution ventilation; personal protective equipment
Use during bag lay-up manufacture of glass fiber, reinforced styrene-polyester articles; during use of surface coatings containing styrene-butadiene copolymer resins	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during die molding of articles made from styrene-polyester resins; during brush application of surface coatings	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in process operations for production of polystyrene, acrylonitrile-butadiene styrene (ABS), styrene-acrylonitrile (SAN), and styrene-butadiene copolymers	Local exhaust ventilation; personal protective equipment
Use in manufacture of surface coatings; use in miscellaneous processes as an elastomer, intermediate, or starting material; use during manufacture of ion-exchange resins (styrene-divinylbenzene copolymer)	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If styrene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If styrene gets on the skin, promptly flush the contaminated skin with water. If styrene soaks through the clothing, remove the clothing immediately and flush the skin with water When there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of styrene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If styrene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If styrene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Combustion may be improved by mixing with a more flammable liquid.

• Waste disposal methods:

Styrene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber. Combustion may be improved by mixing with a more flammable liquid.

REFERENCES

• American Industrial Hygiene Association: "Styrene," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Dutkiewicz, T., and Tyras, H.: Skin Absorption of Toluene, Styrene, and Xylene by Man," *British Journal of Industrial Medicine*, 25:243, 1968.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-1372, 1946.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• Wolf, M. A., et al.: "Toxicological Studies of Certain Alkylated Benzenes and Benzene," *Archives of Industrial Health*, 14:4, 387-398, 1956.

• Zielhuis, R. L.: "Systemic Toxicity from Exposure to Epoxy Resins, Hardeners, and Styrene," *Journal of Occupational Medicine*, 3:25-29, 1961.

RESPIRATORY PROTECTION FOR STYRENE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
400 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).** Any supplied-air respirator.** Any self-contained breathing apparatus.**
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

1339

Occupational Health Guideline for Sulfur Dioxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: SO_2
- Synonyms: None
- Appearance and odor: Colorless gas with a characteristic pungent odor. It can be a liquid at temperatures below −10 C (14 F).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sulfur dioxide is 5 parts of sulfur dioxide per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 13 milligrams of sulfur dioxide per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to 0.5 ppm as a time-weighted average for up to a 10-hour work shift, 40-hour work week. For more detailed information, the NIOSH Criteria Document for Sulfur Dioxide and the NIOSH testimony presented at the Department of Labor's Public Hearing on a Proposed Standard for Sulfur Dioxide should be consulted.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Sulfur dioxide can affect the body if it is inhaled or if it comes in contact with the eyes or skin.

- **Effects of overexposure**

Sulfur dioxide gas is intensely irritating to the eyes and respiratory tract causing burning of the eyes and tearing, coughing, and chest tightness. It may cause severe breathing difficulties. Severe exposures to sulfur dioxide may cause a person to stop breathing. Liquid sulfur dioxide may cause eye burns with loss of vision and skin burns.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sulfur dioxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sulfur dioxide at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes and respiratory tract should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Sulfur dioxide causes human lung irritation. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Sulfur dioxide is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Sulfur dioxide gas is a severe irritant of the eyes, mucous membranes, and skin. Its irritant properties are due to the rapidity with which it forms sulfurous acid on contact with moist membranes. In combination with certain particulate matter and/or oxidants, the effects may be markedly increased. Approximately 90% of all sulfur dioxide inhaled is absorbed in the upper respiratory passages, where most effects occur; however, high concentrations may produce respiratory paralysis and pulmonary edema. Exposure to concentrations of 10 to 50 ppm for 5 to 15 minutes causes irritation of the eyes,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1321

nose, and throat, rhinorrhea, choking, cough, and, in some instances, reflex bronchoconstriction with increased pulmonary resistance. Some 10 to 20% of the healthy young adult population is estimated to be hypersusceptible to the effects of sulfur dioxide, while the phenomenon of adaptation to irritating concentrations is a recognized occurrence in experienced workers. Workers repeatedly exposed to 10 ppm experienced upper respiratory irritation and some nosebleeds, but the symptoms did not occur at 5 ppm; in another study, initial cough and irritation did occur at 5 ppm and 13 ppm, but subsided after 5 minutes of exposure. In a human experimental study with the subjects breathing through the mouth, brief exposure to 13 ppm caused a 73% increase in pulmonary flow resistance; 5 ppm resulted in a 40% increase; 1 ppm produced no effects. Exposure of the eyes to liquid sulfur dioxide from pressurized containers causes corneal burns and opacification resulting in a loss of vision. The liquid on the skin produces skin burns from the freezing effect of rapid evaporation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 64.1
2. Boiling point (760 mm Hg): −10 C (14 F)
3. Specific gravity (water = 1): 1.46 (liquid)
4. Vapor density (air = 1 at boiling point of sulfur dioxide): 2.26
5. Melting point: −75.5 C (−104 F)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): 10
8. Evaporation rate (butyl acetate = 1): Much greater than 1

- **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause containers to burst.
2. Incompatibilities: Contact with some powdered metals and with alkali metals such as sodium or potassium may cause fires and explosions.
3. Hazardous decomposition products: None.
4. Special precautions: Liquid sulfur dioxide will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible
2. Compressed gas cylinders containing sulfur dioxide should be stored in accordance with 29 CFR 1910.101.

- **Warning properties**

1. Odor Threshold: The *Documentation of TLV's* reports that "Henderson and Haggard gave the odor threshold as 3 to 5 ppm."
2. Eye Irritation Level: Patty states that "20 ppm is the least amount irritating to the eyes."
3. Other Information: Patty states that "sulfur dioxide is an irritant gas: 6 to 12 ppm causes immediate irritation to nose and throat. Three tenths to 1 ppm can be detected by the average individual, probably by taste rather than by odor, and 3 ppm has an easily noticeable odor."
4. Evaluation of Warning Properties: Through odor and taste, sulfur dioxide can be detected at or below the permissible exposure limit. Nose and throat irritation occur within three times the permissible exposure limit. For the purposes of this guideline, therefore, sulfur dioxide is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of gas in a hydrogen peroxide-filled impinger with a subsequent chemical analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure sulfur dioxide may be used. An analytical method for sulfur dioxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with liquid sulfur dioxide or from contact with vessels containing liquid sulfur dioxide.
- Any clothing which becomes wet with liquid sulfur dioxide should be removed immediately and not reworn until the sulfur dioxide has evaporated.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid sulfur dioxide contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid sulfur dioxide, an eye-wash fountain should be provided within the immediate work area for emergency use.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sulfur dioxide may occur and control methods which may be effective in each case:

Operation	Controls
Use as bleaching and preservative agent in wood and pulp, sugar and food preparation industries; as a selective antiseptic in food industry and as a fumigating agent in ships	Process enclosure and/or local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as solvent in oil refineries; during synthesis in chemical, petroleum, textile, pharmaceutical, tanning, photography, metal, and rubber industries	Process enclosure and/or local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as refrigerant in commercial refrigerators	Process enclosure and/or local exhaust ventilation; general dilution ventilation; personal protective equipment
Use during extraction, enrichment, and recovery processes in mining and metallurgy industry	Process enclosure and/or local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in miscellaneous processes during leather tanning, special glass manufacture, water treatment, textile processing, and chrome waste treatment	Process enclosure and/or local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid sulfur dioxide or strong concentrations of sulfur dioxide gas get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid sulfur dioxide gets on the skin, immediately flush the contaminated skin with water. If liquid sulfur dioxide penetrates through the clothing, remove the clothing immediately and flush the skin with water. If irritation or burns are present after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of sulfur dioxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If sulfur dioxide is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak to disperse gas.
2. If in gaseous form, stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
3. If in liquid form, allow to vaporize.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Sulfur Dioxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Sulfur Dioxide," *Hygienic Guide Series*, Detroit, Michigan, 1955.

• American Petroleum Institute: "Sulfur Dioxide," *API Toxicological Reviews*, New York, 1963.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-52, Sulfur Dioxide*, Washington, D.C., 1953.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Sulfur Dioxide*, HEW Publication No. (NIOSH) 74-111, GPO No. 017-033-00029, U.S. Government Printing Office, Washington, D.C., 1974.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *NIOSH Testimony before Department of Labor Hearing for a Proposed Standard for Sulfur Dioxide*, Washington, D.C., 1977.

• "Occupational Exposure to Sulfur Dioxide," *Federal Register*, 40:54520-54534, November 24, 1975.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Whittenberger, J. L., and Frank, R. N.: "Human Exposures to Sulfur Dioxide," *Archives of Environmental Health*, 7:244-245, 1963.

-1321

RESPIRATORY PROTECTION FOR SULFUR DIOXIDE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Gas Concentration	
20 ppm or less	Any chemical cartridge respirator with a cartridge(s) providing protection against sulfur dioxide.**
	Any supplied-air respirator.**
	Any self-contained breathing apparatus.**
100 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) providing protection against sulfur dioxide.
	A gas mask with a chin-style or a front- or back-mounted canister providing protection against sulfur dioxide.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against sulfur dioxide.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Sulfur Monochloride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: S_2Cl_2
- Synonyms: Sulfur chloride; sulfur subchloride
- Appearance and odor: Amber to red fuming, oily liquid with a pungent, nauseating, and irritating odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sulfur monochloride is 1 part of sulfur monochloride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 6 milligrams of sulfur monochloride per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Sulfur monochloride can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Vapors of sulfur monochloride may cause coughing, and tearing and burning of the eyes which may be delayed in onset. Inhalation of high concentrations of sulfur monochloride may cause severe difficulty in breathing and symptoms of chemical pneumonia. If splashed on the skin, sulfur monochloride liquid may cause irritation, and, if allowed to remain on the skin, a burn. If the liquid is splashed in the eyes, it may produce severe, immediate damage and scarring.

2. Long-term Exposure: Repeated exposure of the skin, eyes, or upper respiratory tract to sulfur monochloride may cause chronic irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sulfur monochloride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sulfur monochloride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, skin, and eyes should be stressed.

—14" x 17" chest roentgenogram: Sulfur monochloride is a respiratory irritant. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Sulfur monochloride is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Sulfur monochloride is a severe irritant of the eyes, mucous membranes, and skin. On contact with water it decomposes to form hydrogen chloride and sulfur dioxide; since this occurs rapidly, it acts primarily as an upper respiratory irritant and does not ordinarily reach the lungs. Exposure of mice to 150 ppm for 1 minute is fatal. In humans, exposure to the vapor causes lacrimation and cough; exposure to high concentrations may cause pulmonary edema. Concentrations of 2 to 9 ppm are reported to be mildly irritating. Splashes of the

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

-1308

liquid in the eyes will produce severe immediate damage which may result in permanent scarring. The liquid on the skin will produce irritation and burns if not removed.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 135
2. Boiling point (760 mm Hg): 138 C (280 F)
3. Specific gravity (water = 1): 1.7
4. Vapor density (air = 1 at boiling point of sulfur monochloride): 4.66
5. Melting point: −76 C (−105 F)
6. Vapor pressure at 20 C (68 F): 6.8 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts violently, forming hydrochloric acid
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Temperatures above 300 C (572 F) cause decomposition to toxic chlorine gas and solid sulfur.
2. Incompatibilities: Contact with peroxides, oxides of phosphorus, and some organic matter may cause fires and explosions. Contact with water causes a violent reaction, forming hydrogen chloride gas (or hydrochloric acid), which may corrode metal containers and form flammable hydrogen gas.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, sulfur dioxide, hydrogen sulfide, and carbon monoxide) may be released in a fire involving sulfur monochloride.
4. Special precautions: Sulfur monochloride will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 118.5 C (245 F) (closed cup)
2. Autoignition temperature: 234 C (453 F)
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Carbon dioxide, dry chemical

- **Warning properties**

1. Odor Threshold: No information is available concerning the odor threshold of sulfur monochloride.
2. Eye Irritation Level: According to Grant, "even 2 to 9 ppm in air are said to be mildly irritating to the eyes."
3. Evaluation of Warning Properties: Since sulfur monochloride causes eye irritation within twice the permissible exposure limit, this substance is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for sulfur monochloride had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid sulfur monochloride.
- Clothing contaminated with sulfur monochloride should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of sulfur monochloride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the sulfur monochloride, the person performing the operation should be informed of sulfur monochloride's hazardous properties.
- Where there is any possibility of exposure of an employee's body to liquid sulfur monochloride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with sulfur monochloride should be removed immediately and not reworn until the sulfur monochloride is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any

possibility of liquid sulfur monochloride contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid sulfur monochloride, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with sulfur monochloride should be immediately washed or showered to remove any sulfur monochloride.

• Employees who handle liquid sulfur monochloride should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sulfur monochloride may occur and control methods which may be effective in each case:

Operation	Controls
Use for production of white vulcanized oils used for coating and impregnating textiles; use as natural and synthetic rubber extenders and modifying agents in erasers, and extruded rubber goods	Process enclosure; local exhaust ventilation; personal protective equipment
Use with unsaturated fatty acids in production of additives to extreme pressure lubricants and cutting oils	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a cross-linking catalyst in polymer technology; use in chemical synthesis for production of intermediates for dyes, pharmaceuticals, insecticides, and war gases	Process enclosure; local exhaust ventilation; personal protective equipment
Use for treatment of drying oils for production of varnishes, inks, paints, and cements; use for cold vulcanizing of thin rubber articles; use as a solvent for sulfur and sulfur compounds	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid sulfur monochloride or strong concentrations of sulfur monochloride vapor get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid sulfur monochloride or strong concentrations of sulfur monochloride vapor get on the skin, immediately flush the contaminated skin with water. If liquid sulfur monochloride or strong concentrations of sulfur monochloride vapor penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of sulfur monochloride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If liquid sulfur monochloride has been swallowed and the person is conscious, give the person large quantities of water immediately to dilute the sulfur monochloride. Do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If sulfur monochloride is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Spray on a thick layer of a (1:1) mixture of dry soda ash and slaked lime. Mix and spray on water slowly, then add large amounts of water. The neutralized solution can then be disposed in a secured sanitary landfill.

• Waste disposal method:

Sulfur monochloride may be disposed of by using (2) above.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Sulfur Monochloride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-77, Sulfur Monochloride*, Washington, D.C., 1960.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (4th ed.), Van Nostrand Reinhold, New York, 1975.

RESPIRATORY PROTECTION FOR SULFUR MONOCHLORIDE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
10 ppm or less	A chemical cartridge respirator with a full facepiece and cartridge(s) for hydrogen chloride and sulfur dioxide.
	A gas mask with a chin-style or a front- or back-mounted canister for hydrogen chloride and sulfur dioxide.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 10 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against hydrogen chloride and sulfur dioxide.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Sulfur Pentafluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: S_2F_{10}
- Synonyms: Disulfur decafluoride
- Appearance and odor: Colorless liquid or gas with an odor like sulfur dioxide.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sulfur pentafluoride is 0.025 part of sulfur pentafluoride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.25 milligram of sulfur pentafluoride per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Sulfur pentafluoride can affect the body if it is inhaled. No data could be found in the literature which specifically reported possible effects of eye or skin contact with the liquid or the effects of ingestion.

- **Effects of overexposure**

1. Short-term Exposure: In animals, inhalation has been reported to cause severe breathing difficulties.

2. Long-term Exposure: Not known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sulfur pentafluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sulfur pentafluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system and the cardiovascular system should be stressed.

—14" x 17" chest roentgenogram: Sulfur pentafluoride causes lung damage in animals. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Sulfur pentafluoride is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or by signs and symptoms of respiratory disease.

- **Summary of toxicology**

Sulfur pentafluoride vapor is a severe pulmonary irritant. Exposure of rats to 1 ppm for 16 to 18 hours was fatal; 0.5 ppm caused pulmonary edema and hemorrhage; 0.1 ppm caused irritation of the lungs; 0.01 ppm had no discernible effects. Nonfatal exposure of rats for 1 hour to 10 ppm caused pulmonary hemorrhage. In rabbits the LD50 for intravenous injection of a lecithin emulsion of sulfur pentafluoride was 5.8 mg/kg; at autopsy the chief lesion was massive pulmonary edema with frequent hemorrhage, apparently a result of widespread endothelial damage to the cardiovascular system.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 254
2. Boiling point (760 mm Hg): 29 C (84 F)
3. Specific gravity (water = 1): 2.08 (at 0 C)
4. Vapor density (air = 1 at boiling point of sulfur

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

pentafluoride): 8.75

5. Melting point: −55 C (−67 F)

6. Vapor pressure at 20 C (68 F): 561 mm Hg

7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble

8. Evaporation rate (butyl acetate = 1): Much greater than 1

• **Reactivity**

1. Conditions contributing to instability: Temperatures above 400 C (752 F) cause decomposition and development of pressure in containers.

2. Incompatibilities: None

3. Hazardous decomposition products: None

4. Special precautions: None

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: No quantitative information is available.

2. Eye Irritation Level: According to the International Labour Office (ILO), "no data are available on its effects on the upper respiratory tract and conjunctivae."

3. Evaluation of Warning Properties: Since no quantitative information available relating its warning properties to air concentrations, sulfur pentafluoride is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for sulfur pentafluoride had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid sulfur pentafluoride or liquids containing sulfur pentafluoride.

• Clothing contaminated with sulfur pentafluoride should be stored in such a manner that the sulfur pentafluoride is not dispersed until it can be discarded, or until provision is made for the removal of sulfur pentafluoride from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the sulfur pentafluoride, the person performing the operation should be informed of sulfur pentafluoride's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid sulfur pentafluoride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with sulfur pentafluoride should be removed immediately and not reworn until the sulfur pentafluoride is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid sulfur pentafluoride or liquids containing sulfur pentafluoride contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid sulfur pentafluoride or liquids containing sulfur pentafluoride, an eye-wash fountain should be provided within the immediate work area for emergency use.

• Employees should immediately evacuate the area whenever sulfur pentafluoride is accidentally released into the workplace air.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sulfur pentafluoride may occur and control methods which may be effective in each case:

1331

Operation	Controls
Liberation as a by-product during synthesis of sulfur hexafluoride (This compound is considered more toxic than phosgene and is not produced commercially).	Provisions should be made to exit vapors so that they are absorbed by activated alumina and soda lime

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid sulfur pentafluoride or liquids containing sulfur pentafluoride get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid sulfur pentafluoride or liquids containing sulfur pentafluoride get on the skin, immediately flush the contaminated skin with water. If liquid sulfur pentafluoride or liquids containing sulfur pentafluoride penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation is present after washing, get medical attention immediately.

- **Breathing**

If a person breathes in large amounts of sulfur pentafluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

If liquid sulfur pentafluoride or liquids containing sulfur pentafluoride have been swallowed and the person is conscious, give him large quantities of water immediately to dilute the sulfur pentafluoride. Do not attempt to make the exposed person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND LEAK PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.
- If sulfur pentafluoride is spilled or leaked, the following steps should be taken:

1. Ventilate area of leak.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.
3. If liquid, allow liquid to evaporate.

ADDITIONAL INFORMATION

To find additional information on sulfur pentafluoride, look up sulfur pentafluoride in the following documents:

- Medical Surveillance for Chemical Hazards
- Respiratory Protection for Chemical Hazards
- Personal Protection and Sanitation for Chemical Hazards

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Sulfur Pentafluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Greenberg, L. A., and Lester, D.: "The Toxicity of Sulfur Pentafluoride," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 2:350-352, 1950.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Saunders, J. P., et al.: "Some Physiological Effects of Disulfur Decafluoride (S_2F_{10}) after Intravenous Injection in Dogs," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 8:436-445, 1953.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
- Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

RESPIRATORY PROTECTION FOR SULFUR PENTAFLUORIDE

Condition	Minimum Respiratory Protection* Required Above 0.025 ppm
Vapor Concentration	
0.25 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
1 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 1 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against acid gases. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Sulfuric Acid

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: H_2SO_4
- Synonyms: Oil of vitriol
- Appearance and odor: Colorless to dark brown, oily, odorless liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sulfuric acid is 1 milligram of sulfuric acid per cubic meter of air (mg/m³) averaged over an eight-hour work shift. NIOSH has recommended a permissible exposure limit of 1 mg/m³ averaged over a work shift of up to 10 hours per day, 40 hours per week. The NIOSH Criteria Document for Sulfuric Acid should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Sulfuric acid can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Sulfuric acid may cause irritation of the eyes, nose, and throat. Breathing in the mist or vapor may cause teeth erosion or the mouth to become sore and also difficulty in breathing. Splashes in the eyes or on the skin will cause severe skin burns.

2. Long-term Exposure: Repeated or prolonged exposure to dilute solutions of sulfuric acid may cause irritation of the skin. Repeated or prolonged exposure to mists or vapors of sulfuric acid may cause erosion of the teeth, chronic irritation of the eyes, or chronic inflammation of the nose, throat, and bronchial tubes.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sulfuric acid.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sulfuric acid at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, eyes, and teeth should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Sulfuric acid may cause acute lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Sulfuric acid is reported to cause pulmonary function impairment. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

Sulfuric acid mist severely irritates the eyes, respiratory tract, and skin. Concentrated sulfuric acid destroys tissue due to its severe dehydrating action, whereas the dilute form acts as a milder irritant due to acid properties. The LC50 of mist of 1-micron particle size for an 8 hour exposure was 50 mg/m³ for adult guinea pigs and 18 mg/m³ for young animals. Continuous exposure of guinea pigs to 2 mg/m³ for 5 days caused pulmonary edema and thickening of the alveolar walls; exposure of guinea pigs to 2 mg/m³ for 1 hour caused an increase in

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1301

pulmonary airway resistance from reflex bronchoconstriction. A worker sprayed in the face with liquid fuming sulfuric acid suffered skin burns of the face and body, as well as pulmonary edema from inhalation. Sequelae were pulmonary fibrosis, residual bronchitis, and pulmonary emphysema; in addition, necrosis of the skin resulted in marked scarring. In human subjects, concentrations of about 5 mg/m^3 were objectionable, usually causing cough, an increase in respiratory rate, and impairment of ventilatory capacity. Workers exposed to concentrations of 12.6 to 35 mg/m^3 had a markedly higher incidence of erosion and discoloration of teeth than was noted in unexposed individuals. Splashed in the eye, the concentrated acid causes extremely severe damage, often leading to blindness, whereas dilute acid produces more transient effects from which recovery may be complete. Repeated exposure of workers to the mist causes chronic conjunctivitis, tracheobronchitis, stomatitis, and dermatitis, as well as dental erosion. While ingestion of the liquid is unlikely in ordinary industrial use, the highly corrosive nature of the substance may be expected to produce serious mucous membrane burns of the mouth and esophagus.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 98
2. Boiling point (760 mm Hg): 270 C (518 F)
3. Specific gravity (water = 1): 1.84
4. Vapor density (air = 1 at boiling point of sulfuric acid): 3.4
5. Melting point: 3 C (37 F)
6. Vapor pressure at 20 C (68 F): Less than 0.001 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact of acid with organic materials (such as chlorates, carbides, fulminates, and picrates) may cause fires and explosions. Contact of acid with metals may form toxic sulfur dioxide fumes and flammable hydrogen gas.
3. Hazardous decomposition products: Toxic gases and vapors (such as sulfuric acid fume, sulfur dioxide, and carbon monoxide) may be released when sulfuric acid decomposes.
4. Special precautions: Liquid sulfuric acid will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Sulfuric acid is not combustible by itself, but is highly reactive and capable of igniting finely divided combustible materials on contact. Fires involving small amounts of combustibles may be smothered with dry chemical. Water applied directly to sulfuric acid causes evolution of heat and splattering.

- **Warning properties**

The International Labour Office (ILO) reports that sulfuric acid, in liquid or vapor form, can cause eye irritation, but no quantitative information is given. The NIOSH criteria document for sulfuric acid states that Bushtueva exposed 10 human subjects to different concentrations of sulfuric acid aerosol. At a concentration of 1.1 to 2.4 mg/m^3, 40% of the subjects experienced eye irritation.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of sulfuric acid on a cellulose membrane filter, followed by extraction with distilled water and isopropyl alcohol, treatment with perchloric acid, and titration with barium perchlorate. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure sulfuric acid may be used. An analytical method for sulfuric acid is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid sulfuric acid or solutions containing more than 1% sulfuric acid by weight.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solutions containing 1% or less sulfuric acid by weight.
- Where there is any possibility of exposure of an employee's body to liquid sulfuric acid or solutions containingmore than 1% sulfuric acid by weight, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with sulfuric acid should be removed immediately and not reworn until the sulfuric acid is removed from the clothing.
- Clothing contaminated with sulfuric acid should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of sulfuric acid from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the sulfuric acid, the person performing the operation should be informed of sulfuric acid's hazardous properties.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid sulfuric acid or solutions containing sulfuric acid contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid sulfuric acid or solutions containimore than 1% sulfuric acid by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with sulfuric acid should be immediately washed or showered to remove any sulfuric acid.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sulfuric acid may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of phosphoric acid and fertilizers	Process enclosure; local exhaust ventilation; personal protective equipment
Use in petroleum refining as an alkylation catalyst for production of high-octane gasoline, production of jet fuels, kerosene, lube and white oils, oil additives, and preparation of cracking catalysts	Process enclosure; local exhaust ventilation; personal protective equipment
Use during manufacture of pigments and dyes, and dyestuff intermediates	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of industrial and military explosives	Process enclosure; local exhaust ventilation; personal protective equipment
Use in production of alcohols, phenols, and inorganic sulfates	Process enclosure; local exhaust ventilation; personal protective equipment
Use in ore leaching and processing; use in metal cleaning and plating; manufacture of electrogalvanized wire; anodizing of metal; electroplating	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of detergents	Process enclosure; local exhaust ventilation; personal protective equipment
Use in coke-oven gas refining; use in plastics industry for manufacture of rayon, cellophane, cellulose, acetate, caprolactam, and others; use in lead storage batteries as electrolyte	Process enclosure; local exhaust ventilation; personal protective equipment
Use in food processing in manufacture of brewing sugars for beer, manufacture of glucose, refining of mineral and vegetable oils	Process enclosure; local exhaust ventilation; personal protective equipment

Operation	Controls
Use for preparation of insecticides; use in manufacture of natural and synthetic rubber	Process enclosure; local exhaust ventilation; personal protective equipment
Use for gas drying to dry acid and corrosive gases; use in treatment of industrial water for pH control	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of textiles and leather for treatment of wool, pickling leather, as a dye assist, as a solvent for vat dyes, and in fabric finishing	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a laboratory reagent as a solvent and for chemical analysis; use in chemical synthesis in preparation of acids, intermediates for medicinals, gas, esters, and fatty acids	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid sulfuric acid or solutions containing sulfuric acid get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid sulfuric acid or solutions containing sulfuric acid get on the skin, immediately flush the contaminated skin with water. If liquid sulfuric acid or solutions containing sulfuric acid penetrate through the clothing, remove the clothing immediately and flush the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of sulfuric acid, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If liquid sulfuric acid or solutions containing sulfuric acid have been swallowed and the person is conscious, give him large quantities of water immediately to dilute the sulfuric acid. Do not attempt to make the exposed person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If sulfuric acid is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect spilled or leaked material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Sulfuric acid should be absorbed in vermiculite, dry sand, earth, or a similar material. It may also be diluted and neutralized.

• Waste disposal method:

Sulfuric acid may be placed in sealed containers or absorbed in vermiculite, dry sand, earth, or a similar material and disposed of in a secured sanitary landfill. It may also be diluted and neutralized.

REFERENCES

• Amdur, M. O., et al.: "Inhalation of Sulfuric Acid Mist by Human Subjects," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 6:305-313, 1952.

• Amdur, M. O., et al.: "Toxicity of Sulfuric Acid Mist to Guinea Pigs," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 5:318-329, 1952.

• American Conference of Governmental Industrial Hygienists: "Sulfuric Acid," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Sulfuric Acid," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• American Petroleum Institute: "Sulfuric Acid," *API Toxicological Reviews*, New York.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-20, Sulfuric Acid*, Washington, D.C., 1963.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Sulfuric Acid*, HEW Publication No. (NIOSH) 74-128, GPO No. 017-033-00034, U.S. Government Printing Office, Washington, D.C., 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Sim, V. M., and Pattle, R. E.: "Effect of Possible Smog Irritants on Human Subjects," *Journal of the American Medical Association*, 165:15, pp. 1908-1913, December 1957.

• Treon, J. F., et al.: "Toxicity of Sulfuric Acid Mist," *Archives of Industrial Hygiene and Occupational Medicine*, 2:716-34, 1950.

RESPIRATORY PROTECTION FOR SULFURIC ACID

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
50 mg/m³ or less	A gas mask with a chin-style or a front- or back-mounted acid gas canister with a high efficiency particulate filter.
	A high efficiency particulate filter respirator with a full facepiece.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 100 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A gas mask with a chin-style or a front- or back-mounted acid gas canister with a high efficiency particulate filter.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Sulfuryl Fluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: SO_2F_2
- Synonyms: None
- Appearance and odor: Colorless and odorless gas.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for sulfuryl fluoride is 5 parts of sulfuryl fluoride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 20 milligrams of sulfuryl fluoride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Sulfuryl fluoride can affect the body if it is inhaled or if it comes in contact with the eyes.

- **Effects of overexposure**

1. Short-term Exposure: Animal experiments have shown that inhalation of sulfuryl fluoride may cause shaking, convulsions, and severe breathing difficulties. Human exposure to a mixture of sulfuryl fluoride and an irritant gas caused nausea, vomiting, crampy abdominal pain, itching, reddening of the eyes, nose, and throat, and minor lung changes. These effects were of short duration.

2. Long-term Exposure: Animal experiments have shown that repeated exposure to sulfuryl fluoride may cause mottled teeth and kidney and lung injury.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to sulfuryl fluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to sulfuryl fluoride at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system and the central nervous system should be stressed.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Sulfuryl fluoride gas is a respiratory irritant and a depressant of the central nervous system. Although there are few details, exposure of animals to an unspecified but high concentration caused signs of narcosis and, in some instances, tremor, convulsions, and pulmonary edema, repeated exposure caused lung and kidney injury. A worker who was exposed to an undetermined concentration of a mixture of sulfuryl fluoride and an undesignated irritant gas for 4 hours developed nausea, vomiting, abdominal pain, and pruritis; examination revealed conjunctivitis, rhinitis, pharyngitis, diffuse rhonchi, and paresthesia of the right leg, all of which rapidly subsided.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 102.1
2. Boiling point (760 mm Hg): −55.2 C (−67 F)
3. Specific gravity (water = 1): 1.36 (liquid)
4. Vapor density (air = 1 at boiling point of sulfuryl fluoride): 3.5
5. Melting point: −136.7 C (−213 F)
6. Vapor pressure at 20 C (68 F): Greater than 1

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1309

atmosphere

7. Solubility in water, g/100 g water at 20 C (68 F): 0.16

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: High temperatures may cause cylinders to burst.

2. Incompatibilities: None

3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide and hydrogen fluoride) may be released when sulfuryl fluoride decomposes.

4. Special precautions: See 29 CFR 1910.101 for specific regulations on storage of compressed gas cylinders.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: Spector states that sulfuryl fluoride is odorless.

2. Eye Irritation Level: Baskin states that sulfuryl fluoride is severely irritating to the eyes. Other sources do not mention this severe eye irritation, however, and no quantitative information is available concerning the threshold of eye irritation. Gleason states that "chronic exposure . . . . to 100 ppm resulted in no adverse effects on rats, rabbits, guinea pigs, or monkeys."

3. Other Information: Baskin states that sulfuryl fluoride is severely irritating to the mucous membranes of the respiratory tract. No quantitative information is available concerning the threshold of this irritation, however.

4. Evaluation of Warning Properties: Since sulfuryl fluoride is odorless, and since no quantitative information is available relating its irritant effects to air concentrations, this substance is treated as a material with poor warning properties. Taxay states that sulfuryl fluoride has no warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for sulfuryl fluoride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to sulfuryl fluoride may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during use as an insecticidal fumigant for control of dry wood termites and other structural pests	Process enclosure; mix with alerting gas

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If strong concentrations of sulfuryl fluoride gas get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Breathing**

If a person breathes in large amounts of sulfuryl fluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Under-

stand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.
- If sulfuryl fluoride is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty into a mixed solution of caustic soda and slaked lime.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Sulfuryl Fluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.
- Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969
- Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.
- Taxay, E. P.: "Vikane Inhalation," *Journal of Occupational Medicine*, 8:425-426, 1966.

RESPIRATORY PROTECTION FOR SULFURYL FLUORIDE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Gas Concentration	
50 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
250 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against sulfuryl fluoride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

6. Vapor pressure at 20 C (68 F): Essentially zero

7. Solubility in water, g/100 g water at 20 C (68 F): 0.03

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Temperatures above 158 C (316 F) may cause sealed metal containers to burst.

2. Incompatibilities: None.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride and carbon monoxide) may be released when 2,4,5-T decomposes.

4. Special precautions: None.

• **Flammability**

1. Not combustible

• **Warning properties**

2,4,5-T is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for 2,4,5-T is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

SANITATION

• Eating and smoking should not be permitted in areas where 2,4,5-T is handled, processed, or stored.

• Employees who handle 2,4,5-T should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 2,4,5-T may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of herbicides and plant hormones	Process enclosure; local exhaust ventilation; personal protective equipment
Application as herbicide, defoliant, and plant hormone	Personal protective equipment
Manufacture of 2,4,5-T	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 2,4,5-T gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 2,4,5-T or liquids containing 2,4,5-T get on the skin, wash the contaminated skin using soap or mild detergent and water. If 2,4,5-T or liquids containing 2,4,5-T soak through the clothing, remove the clothing and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 2,4,5-T, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 2,4,5-T or liquids containing 2,4,5-T have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical

Occupational Health Guideline for 2,4,5-T *

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $Cl_3C_6H_2OCH_2COOH$
- Synonyms: 2,4,5-Trichlorophenoxyacetic acid
- Appearance and odor: Colorless to tan odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 2,4,5-T is 10 milligrams of 2,4,5-T per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

2,4,5-T can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to 2,4,5-T may cause abdominal pain, nausea, vomiting, diarrhea, and blood in the stool. It may also cause irritation of the skin. Common contaminants of commercial preparations of 2,4,5-T may cause acne and liver damage. Animal experiments have shown that these contaminants may produce damage in unborn rats.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 2,4,5-T.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 2,4,5-T at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver and attention to gastrointestinal complaints should be stressed. The skin should be examined for evidence of chronic disorders.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

2,4,5-T (2,4,5-trichlorophenoxyacetic acid) is of low toxicity. The oral LD50 for dogs is in the range of 100 mg/kg or higher; effects are limited to a slight or moderate stiffness in the hind legs with development of ataxia. Contaminants of commercial preparations of 2,4,5-T have been 2,3,7,8-tetrachlorodibenzo-p-dioxin, a potent animal teratogen, and 2,3,6,7-tetrachlorodibenzo-p-dioxin (TCDD), a potent acnegenic agent which is hepatotoxic in animals; they are present as unwanted side products of synthesis of 2,4,5-T. In a study of 73 workers in a 2,4,5-T manufacturing plant, 13 had moderate to severe acneform dermatitis (chloracne) and 22 had gastrointestinal complaints such as nausea, vomiting, diarrhea, abdominal pain, or blood in the stool; no significant liver dysfunction was found; although no air sample results were reported, the chloracne was thought to be a result of exposure to TCDD. 2,4,5-T dust is a slight irritant of the skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 255.5
2. Boiling point (760 mm Hg): Decomposes above melting point
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of 2,4,5-T): Not applicable
5. Melting point: 158 C (316 F) (decomposition)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1312

attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If 2,4,5-T is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquid containing 2,4,5-T should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

2,4,5-T may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "2,4,5-T (2,4,5-Trichlorophenoxacetic Acid)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. I.. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Drill, V. A., and Hiratzka, T.: "Toxicity of 2,4-Dichlorophenoxyacetic Acid and 2,4,5-Trichlorophenoxyacetic Acid," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 7:61-67, 1953.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Khera, K. S., and McKinley, W. P.: "Pre- and Post-Natal Studies on 2,4,5-Trichlorophenoxyacetic Acid, 2,4-Dichlorophenoxyacetic Acid and Their Derivatives in Rats," Toxicology and Applied Pharmacology, 22:14-28, 1972.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Poland, A. P., et al.: "A Health Survey of Workers in a 2,4-D and 2,4,5-T Plant," *Archives of Environmental Health*, 22:316-327, 1971.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

* SPECIAL NOTE

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 15, 1977.

RESPIRATORY PROTECTION FOR 2,4,5-T

Condition	Minimum Respiratory Protection* Required Above 10 mg/m³
Particulate Concentration	
50 mg/m³ or less	Any dust and mist respirator, except single-use.
100 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
500 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 5000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Talc (Non-Asbestos Form)

INTRODUCTION

This guideline is intended as a source of information for employers, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: No specific formula
- Synonyms: Hydrous magnesium silicate; steatite talc; non-fibrous talc; non-asbestiform talc
- Appearance and odor: Odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for talc is 20 million particles of talc per cubic foot of air (mppcf) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for talc (non-asbestos form) from 20 mppcf to 15 mppcf or 2 mg/m³ respirable dust.

•Method

At the time of publication of this guideline, no measurement method for talc had been published by NIOSH.

HEALTH HAZARD INFORMATION

• Routes of exposure

Talc can affect the body if it is inhaled or if it comes in contact with the eyes.

• Effects of overexposure

Repeated inhalation of non-asbestos form of talc dust might cause scarring of the lungs with shortness of breath, chronic cough, and heart failure. The non-asbestos form of talc may cause irritation of the eyes in the same manner as nuisance dusts.

• Reporting signs and symptoms

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to talc.

• Recommended medical surveillance

The following medical procedures should be made available to each employee who is exposed to talc at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the lungs and cardiovascular system should be stressed.

—14" x 17" chest roentgenogram: The non-asbestos form of talc may have the potential to cause pulmonary fibrosis and cancer. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Talc is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• Summary of toxicology

The non-asbestos form of talc, also termed nonfibrous, has been reported to cause talcosis although this is controversial. It has not been proven to cause the effects produced by exposure to fibrous talc: fibrotic pneumoconiosis and an increased incidence of cancer of the lungs and pleura. In a study of 20 workers exposed for 10 to 36 years to talc described as "pure," at levels ranging from 15 to 35 mppcf, no evidence of pneumoconiosis was found. In another study which compared the pulmonary function of workers exposed to either fibrous or nonfibrous talc, it was concluded that while the fibrous form was the more pathogenic type, both talcs produced pulmonary fibrosis; no data were presented to document the types of talc involved. An epidemiologic study of 260 workers with 15 or more

---

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

years of exposure to commercial talc dust containing pure talc, plus tremolite, anthophyilite, carbonate dusts, and a small amount of free silica revealed a fourfold greater than expected proportional mortality from cancer of the lungs and pleura; in addition, a major cause of death was cor pulmonale, a result of the pneumoconiosis; the effects were likely due to the asbestos-form contaminants. The role of nonfibrous talc in these disease states could not be assessed.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 295
  2. Boiling point (760 mm Hg): Not applicable
  3. Specific gravity (water = 1): 2.5 – 2.8
  4. Vapor density (air = 1 at boiling point of talc): Not applicable
  5. Melting point: 900 – 1000 C (1652 – 1832 F) (loses water)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Talc is not reported to be a significant eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of talc in an impinger, followed by dust counting utilizing an optical microscope. A detailed analytical method for talc may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22161, under the title "NIOSH Analytical Methods for Set R" (order number PB 262 403).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to talc may occur and control methods which may be effective in each case:

Operation	Controls
Use in cosmetic industry as face powder, body or dusting powder, soap, and toilet preparations; in pharmaceutical industry in tablets, pills, salves, and lotions	General dilution ventilation; dust collecting system; wet grinding; personal protective equipment
Liberation during mining and processing by crushing, drying, milling, and upgrading by flotation	General dilution ventilation; dust collecting system; wet grinding; personal protective equipment
Use as a filler and selective absorbent in paper industry; use in ceramics industry in high quality electronic products as insulation; use as a selective absorbent in rubber and plastics reinforcing; use in cleaning up oil spills	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid proce-

dures and send for first aid or medical assistance.

• **Eye Exposure**

If the non-asbestos form of talc gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If talc is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Talc may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Talc (Fibrous)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Conference of Governmental Industrial Hygienists: "Talc (Non-Asbestiform)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Blejer, H. P., and Arlon, R.: "Talc: A Possible Occupational and Environmental Carcinogen," *Journal of Occupational Medicine*, 15:92-97, 1973.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hogue, W. L., and Mallette, F. S.: "A Study of Workers Exposed to Talc and Other Dusting Compounds in the Rubber Industry," *Journal of Industrial Hygiene and Toxicology*, 31:359-364, 1949.

• Kleinfeld, M., et al.: "Effect of Talc Dust Inhalation on Lung Function," *Archives of Environmental Health*, 10:431-437, 1965.

• Kleinfeld, M., et al.: "Lung Function in Talc Workers - A Comparative Physiologic Study of Workers Exposed to Fibrous and Granular Talc Dusts," *Archives of Environmental Health*, 9:559-566, 1964.

• Kleinfeld, M., et al.: "Mortality Among Talc Miners and Millers in New York State," *Archives of Environmental Health*, 14:663-667, 1967.

• Kleinfeld, M., et al.: "Mortality Experiences Among Talc Workers: A Follow-up Study," *Journal of Occupational Medicine*, 16:345-349, 1974.

• Spiegel, R. M.: "Medical Aspects of Talc" in A. Goodwin (ed.), *Proceedings of the Symposium on Talc*, Washington, D.C., May 8, 1973, Bureau of Mines Report No.8639, U.S. Government Printing Office, Washington, D.C., pp.97-102, 1973.

RESPIRATORY PROTECTION FOR TALC (NON-ASBESTOS FORM)

Condition	Minimum Respiratory Protection* Required Above 20 mppcf
Particulate Concentration	
100 mppcf or less	Any dust and mist respirator.
200 mppcf or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
1000 mppcf or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 mppcf or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 mppcf or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Tantalum Metal and Oxide Dusts

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

Metallic tantalum

- Formula: Ta
- Synonyms: None
- Appearance and odor: Gray-black, odorless solid.

Tantalum pentoxide

- Formula: Ta_2O_5
- Synonyms: None
- Appearance: Colorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tantalum is 5 milligrams of tantalum per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tantalum can affect the body if it is inhaled.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tantalum.

- **Recommended medical surveillance**

Routine medical examinations should be provided to each employee who is exposed to tantalum at potentially hazardous levels.

- **Summary of toxicology**

Tantalum dust has a low order of toxicity but has produced transient inflammatory lesions in the lungs of animals. Intratracheal administration of tantalum oxide to guinea pigs produced transient bronchitis, interstitial pneumonitis, and hyperemia. There were some slight residual sequelae in the form of focal hypertrophic emphysema and organizing pneumonitis around metallic deposits; there was slight epithelial hyperplasia in the bronchi and bronchioles.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data—Metallic tantalum**

1. Molecular weight: 180.9
2. Boiling point (760 mm Hg): 5425 C (9997 F)
3. Specific gravity (water = 1): 16.6
4. Vapor density (air = 1 at boiling point of tantalum): Not applicable
5. Melting point: 2980 C (5396 F)
6. Vapor pressure at 20 C (68 F): 0 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Physical data—Tantalum pentoxide**

1. Molecular weight: 441.89
2. Boiling point (760 mm Hg): Not applicable
3. Specific gravity (water = 1): 8.2
4. Vapor density (air = 1 at boiling point of tantalum pentoxide): Not applicable
5. Melting point: 1800 C (3272 F)
6. Vapor pressure at 20 C (68 F): Not applicable
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity—Metallic tantalum**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact of tantalum (metallic dust) with strong oxidizers may cause fires and explo-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1379

sions.

3. Hazardous decomposition products: None

4. Special precautions: None

• **Flammability-Metallic tantalum**

1. Flash point: Not applicable

2. Minimum ignition temperature: 300 C (572 F) (layer); 630 C (1166 F) (cloud)

3. Minimum explosion dust concentration: Less than 0.2 g/l

4. Extinguishant: Dry sand, dry dolomite, and dry graphite

• **Warning properties**

Tantalum is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for tantalum is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tantalum metal and oxide dusts may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during refining ores, manufacture of tantalum compounds, metal, and alloys	General dilution ventilation; local exhaust ventilation
Use in fabrication for manufacture of electronic equipment such as electrolytic capacitors used in solid-state circuitry for computers, instrumentation, and consumer items, and high-voltage surge arrestors	General dilution ventilation; local exhaust ventilation
Use in fabrication of metals for manufacture of chemical and metallurgical processing equipment and heat exchanger	General dilution ventilation; local exhaust ventilation
Use in fabrication of refractory non-ferrous alloys for nuclear and aerospace applications; use in manufacture of tantalum carbide for working machinery; use in manufacture of surgical metals, mesh, and clips; use in manufacture of special optical glass; and use in manufacture and repair of glass-lined equipment	General dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of metallic tantalum dust or tantalum oxide dust, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposur
If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES—Metallic tantalum and tantalum pentoxide

• Persons not wearing protective equipment should be restricted from areas of spills until cleanup has been completed.

• If potentially hazardous amounts of metallic tantalum or tantalum pentoxide are spilled or released, the following steps should be taken:

1. Remove all ignition sources in the case of a spill or release of metallic tantalum dust.
2. Ventilate area of spill or release.
3. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.

• Waste disposal method:

Tantalum and tantalum pentoxide may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tantalum (Metal and Oxide Dusts)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Cochran, K. W., et al.: "Acute Toxicity of Zirconium, Strontium, Lanthanum, Cesium, Tantalum and Yttrium," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, I(6):537-50, June 1950.

• Delahant, A. B.: "An Experimental Study of the Effects of Rare Metals on Animal Lungs," *A.M.A. Archives of Industrial Health*, 12:116-120, 1955.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schepers, G. W. H.: "The Biologic Action of Tantalum Oxide," *A.M.A. Archives of Industrial Health*, 12:121-123, 1955.

RESPIRATORY PROTECTION FOR TANTALUM

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Dust or Mist Concentration	
25 mg/m³ or less	Any dust and mist respirator.
50 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator.
Dust, Mist, or Fume Concentration	
50 mg/m³ or less	Any fume respirator or high efficiency particulate respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
250 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
5000 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
10,000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for TEDP

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_2H_5)_4P_2S_2O_5$
- Synonyms: Tetraethyl pyrophosphorodithionate; sulfotepp; tetraethyl dithionopyrophosphate; tetraethyl dithiopyrophosphate
- Appearance and odor: Yellow liquid wtih a garlic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for TEDP is 0.2 milligram of TEDP per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

TEDP can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: After inhalation of TEDP, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of vision, tearing, runny nose, headache, and watering of the mouth. After swallowing TEDP, loss of appetite, nausea, vomiting, abdominal cramps, and diarrhea may appear within 2 hours. After skin absorption, sweating and twitching in the area of absorption may occur usually within 15 minutes to four hours. With severe intoxication by all routes, in addition to all the above symptoms, weakness, generalized twitching, and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, irregular or slow heartbeat, convulsions, and coma may occur.

2. Long-term Exposure: Repeated exposure to levels of TEDP may make a person more susceptible to the effects of this and related chemicals. Repeated exposure to concentrations which are too small to produce symptoms after a single exposure may result in the onset of symptoms.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to TEDP.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to TEDP at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system, and attention to the cholinesterase levels in the blood should be stressed.

—Cholinesterase determination: TEDP causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the serum and erythrocytes should be determined by using medically acceptable biochemical tests prior to new period of exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determination which should be performed quarterly or at any

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1351

time overexposure is suspected or signs and symptoms of toxicity occur.

• **Summary of toxicology**

TEDP (tetraethyl dithionopyrophosphate) is an anticholinesterase agent; absorption may occur from inhalation of the mist, by skin absorption, or ingestion of the liquid. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nervous system, skeletal and smooth muscles, and secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms occurs promptly and almost always within 12 hours. After inhalation, respiratory and ocular effects are the first to appear, often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption, localized sweating and muscular fasciculations in the immediate area occur usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures and is increased by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels, and cardiac irregularities including complete heart block may occur; these effects may sometimes be reversed by establishing adequate pulmonary ventilation. Complete symptomatic recovery usually occurs within one week; increased susceptibility to the effects of anticholinesterase agents persists for one to several days after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 322.2
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.19
4. Vapor density (air = 1 at boiling point of TEDP): Not applicable
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Very low
7. Solubility in water, g/100 g water at 20 C (68 F): 0.0025
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause containers to burst.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide, phosphoric acid mist, and carbon monoxide) may be released when TEDP decomposes.
4. Special precautions: TEDP will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: No quantitative information available concerning the odor threshold of TEDP.
2. Eye Irritation Level: TEDP is not known to be an eye irritant.
3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of TEDP, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for TEDP had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted

are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with TEDP.

• Clothing contaminated with TEDP should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of TEDP from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the TEDP, the person performing the operation should be informed of TEDP's hazardous properties.

• Where there is any possibility of exposure of an employee's body to TEDP, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with TEDP should be removed immediately and not reworn until the TEDP is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of TEDP contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to TEDP, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with TEDP should be immediately washed or showered with soap or mild detergent and water to remove any TEDP.

• Eating and smoking should not be permitted in areas where TEDP is handled, processed, or stored.

• Employees who handle TEDP should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to TEDP may occur and control methods which may be effective in each case:

Operation	Controls
Formulation of insecticides	Process enclosure; local exhaust ventilation; personal protective equipment
Application of insecticide by aerosol or fumigation on flowering plants in commercial greenhouses	Personal protective equipment
Manufacture of TEDP	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If TEDP or formulations containing TEDP get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If TEDP or formulations containing TEDP get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If TEDP or formulations containing TEDP penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of TEDP, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When TEDP or formulations containing TEDP have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If TEDP is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.

3. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

TEDP may be disposed of by absorbing in vermiculite, dry sand, earth, or a similar material and disposing in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "TEDP (Tetraethyl Dithionopyrophosphate)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koelle, G. B. (ed.): *Cholinesterases and Anticholinesterase Agents*, Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

1357

RESPIRATORY PROTECTION FOR TEDP

Condition	Minimum Respiratory Protection* Required Above 0.2 mg/m³
Particulate or Vapor Concentration	
2 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
10 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
35 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 35 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of TEDP; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 35 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Tellurium and Compounds (as Tellurium)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all tellurium and compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Tellurium

- Formula: Te
- Synonyms: Tellurium, metallic
- Appearance and odor: Odorless, grayish-colored solid with a metallic luster.

Hydrogen telluride

- Formula: H_2Te
- Synonyms: Tellurium hydride
- Appearance and odor: Colorless gas with a characteristic odor like arsenic.

Potassium tellurite

- Formula: K_2TeO_3
- Synonyms: None
- Appearance and odor: White, odorless solid.

Sodium tellurate

- Formula: $Na_2H_4TeO_6$
- Synonyms: Sodium tellurate dihydrate
- Appearance and odor: White, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tellurium and compounds (as tellurium) is 0.1 milligram of tellurium and compounds (as tellurium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tellurium and compounds can affect the body if they are inhaled, come in contact with the eyes or skin, or are swallowed. They may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Tellurium, hydrogen telluride, potassium tellurite, or sodium tellurate causes garlic odor of the breath and sweat, dryness of the mouth, metallic taste, sleepiness, loss of appetite, and nausea. Tellurium dioxide exposure may cause a temporary loss of sweat function.

2. Long-term Exposure: Tellurium hydride is highly toxic. It has produced irritation of the lungs and destruction of red blood cells in animals.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tellurium and compounds.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tellurium and compounds at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from tellurium and compounds exposure.

—Skin disease: Tellurium can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1353

September 1978

—Neurologic disorders: By analogy to effects observed in experimental animals, tellurium may adversely affect the nervous system in man.

—Blood disease: Hydrogen telluride is reported to cause hemolysis in animals. Persons with pre-existing blood disorders may be at increased risk from exposure.

—Chronic respiratory disease: Hydrogen telluride and other gaseous compounds of tellurium are reported to cause pulmonary effects. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of certain compounds of tellurium might cause exacerbation of symptoms.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination. The concentration of tellurium in the urine may be informative when exposures are high. Garlic odor of the breath is a sensitive sign of tellurium exposure.

• **Summary of toxicology**

Fume or dust of tellurium and its compounds causes garlic odor of the breath and malaise in humans. In animals, acute tellurium intoxication results in restlessness, tremor, diminished reflexes, paralysis, convulsions, somnolence, coma, and death. Tellurium compounds are more toxic than the metal. Administration to pregnant rats of 500 to 3000 ppm tellurium in the diet resulted in high incidence of hydrocephalic offspring. Weaning rats fed elemental tellurium at a level of 1% (10,000 ppm) in the diet developed a neuropathy characterized by segmental demyelination; remyelination and functional recovery occurred despite continued administration of tellurium. Iron foundry workers exposed to concentrations between 0.01 to 0.1 mg/m³ complained of garlic odor of the breath and sweat, dryness of the mouth and metallic taste, somnolence, anorexia, and occasional nausea; urinary concentrations ranged from zero to 0.06 mg/l; somnolence and metallic taste in the mouth did not appear with regularity until the level of tellurium in the urine was at least 0.01 mg/l. Skin lesions in the form of scaly, itching patches and loss of sweat function occurred in workers exposed to tellurium dioxide in an electrolytic lead refinery. Hydrogen telluride is highly toxic and has caused pulmonary irritation and hemolysis of red blood cells in animals; this gas is very unstable, however, and its occurrence as an actual industrial hazard is unlikely.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Tellurium**

1. Molecular weight: 127.6
2. Boiling point (760 mm Hg): 1390 C (2534 F)
3. Specific gravity (water = 1): 6.24
4. Vapor density (air = 1 at boiling point of tellurium): Not applicable
5. Melting point: 450 C (842 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Hydrogen telluride**

1. Molecular weight: 129.6
2. Boiling point (760 mm Hg): −2 C (28 F)
3. Specific gravity (water = 1): 2.6 (liquid)
4. Vapor density (air = 1 at boiling point of hydrogen telluride): 4.5
5. Melting point: −50 C (−58 F)
6. Vapor pressure at 20 C (68 F): 1600 mm Hg approximately
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Potassium tellurite**

1. Molecular weight: 253.8
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): Data not available
4. Vapor density (air = 1 at boiling point of potassium tellurite): Not applicable
5. Melting point: 450 C (842 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Very soluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Sodium tellurate**

1. Molecular weight: 273.6
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): Data not available
4. Vapor density (air = 1 at boiling point of sodium tellurate): Not applicable
5. Melting point: 170 C (338 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 0.8
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None. (Hydrogen telluride is unstable, but is rarely worked with as such).
2. Incompatibilities: Contact of tellurium metal or hydrogen telluride with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: None
4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable
2. Minimum ignition temperature: a) Tellurium: 340 C (644 F) (layer); 550 C (1022 F) (cloud); b) Hydrogen telluride: Data not available; c) Potassium tellurite and d) sodium tellurate: Not applicable
3. Flammable limits in air, % by volume: Tellurium, potassium tellurite, and sodium tellurate: Not applicable; Hydrogen telluride: Data not available
4. Extinguishant: Tellurium: Water; Hydrogen telluride: Rarely handled as such; Potassium tellurite and

sodium tellurate: Not applicable

• **Warning properties**

Tellurium is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection on a cellulose membrane filter followed by treatment with nitric and perchloric acids, solution in nitric acid, and analysis with an atomic absorption spectrophotometer. An analytical method for tellurium and compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).
PB 258 433).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent the skin from becoming frozen from contact with hydrogen telluride or from contact with vessels containing hydrogen telluride.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with potassium tellurite, sodium tellurate, or liquids containing these compounds.

• If employees' clothing may have become contaminated with potassium tellurite, sodium tellurate, or liquids containing these compounds, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with potassium tellurite or sodium tellurate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of contaminant from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the contaminant, the person performing the operation should be informed of contaminant's hazardous properties.

• Any clothing which becomes wet with liquid hydrogen telluride should be removed immediately and not reworn until the hydrogen telluride has evaporated.

• Non-impervious clothing which becomes contaminated with potassium tellurite should be removed promptly and not reworn until the potassium tellurite is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid hydrogen telluride may contact the eyes.

SANITATION

• Skin that becomes contaminated with potassium tellurite should be promptly washed or showered to remove any contaminant.

• Eating and smoking should not be permitted in areas where potassium tellurite, sodium tellurate, or liquids containing these compounds are handled, processed, or stored.

• Employees who handle potassium tellurite, sodium tellurate, or liquids containing these compounds should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tellurium and compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during recovery, purification, and packaging	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during manufacture of alloys with copper, steel, lead, tin, silver, magnesium, nickel, and phosphorus; during use in manufacture of cast iron; liberation during refining of various minerals	Process enclosure or local exhaust ventilation; personal protective equipment
Liberation during use in manufacture of natural and synthetic rubber and plastics	Process enclosure or local exhaust ventilation; personal protective equipment
Use in manufacture of tellurium compounds used as insecticides, germicides, fungicides, and photographic print toners	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during use in ceramic colorants and glass manufacture; during manufacture of thermoelectric devices for cooling boxes, solar energy converters, and small control apparatus; during manufacture of electronic devices such as batteries, solar cells, and semiconductors, and during manufacture of tellurium compounds	Process enclosure or local exhaust ventilation; personal protective equipment
Liberation during refining of various minerals; during use as a catalyst for acrylic monomer production	Process enclosure or local exhaust ventilation; personal protective equipment
Use in manufacture of tellurium compounds used as insecticides, germicides, fungicides, and photographic print toners	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If tellurium and compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

- **Skin Exposure**

If tellurium and compounds get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If tellurium and compounds penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. Get medical attention promptly.

- **Breathing**

If a person breathes in large amounts of tellurium and compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When tellurium and compounds have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If tellurium and compounds are spilled, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing tellurium and compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.
3. For hydrogen telluride, stop flow of gas.

- Waste disposal method:

Tellurium and compounds may be disposed of in sealed containers in a secured sanitary landfill.

1332

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tellurium," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Tellurium," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Cerwenka, E. A., and Cooper, W. C.: "Toxicology of Selenium and Tellurium and Their Compounds," *Archives of Environmental Health*, 3:189, 196-200, 1961.

• Cooper, W. C., (ed.): *Tellurium*, Van Nostrand Reinhold New York, 1971.

• DeMeio, R. H.: "The Toxicity of Ingested Elementary Tellurium for Rats and Rat Tissues," *Journal of Industrial Hygiene*, 28(5), 229-232, 1946.

• Duckett, S.: "Fetal Encephalopathy Following Ingestion of Tellurium," *Experientia*, 26:1239-1241, 1970.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 34 - Tellurium*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1971.

• Lampert, P., et al.: "Tellurium Neuropathy," *Acta Neuropathologica (Berl.)*, 15:308-317, 1970.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Plunkett, E. R.: *Handbook of Industrial Toxicology*, Chemical Publishing Company, Inc., New York, 1966.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd. ed. rev.), Lea and Febiger, Philadelphia, 1957.

RESPIRATORY PROTECTION FOR TELLURIUM AND COMPOUNDS (AS TELLURIUM)

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
0.5 mg/m³ or less	Any dust and mist respirator, except single-use.
1 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
50 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 50 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any high efficiency particulate filter respirator. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

1331

Occupational Health Guideline for Tellurium Hexafluoride

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: TeF_6
- Synonyms: None
- Appearance and odor: Colorless gas with a repulsive odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tellurium hexafluoride is 0.02 part of tellurium hexafluoride per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 0.2 milligram of tellurium hexafluoride per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tellurium hexafluoride can affect the body if it is inhaled.

- **Effects of overexposure**

1. Short-term Exposure: Tellurium hexafluoride may cause a garlic odor to the breath, headaches, and difficulty in breathing. Tellurium exposure experience with animals indicates that delayed severe breathing difficulties might occur.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tellurium hexafluoride.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tellurium hexafluoride at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from tellurium hexafluoride exposure.

—Chronic respiratory disease: Tellurium hexafluoride causes respiratory irritation. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of tellurium hexafluoride might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Tellurium hexafluoride gas is a severe respiratory irritant. Animals exposed to 1 ppm for 4 hours developed pulmonary edema; 5 ppm for 4 hours was fatal. Human experience has indicated that exposure to tellurium hexafluoride causes headache and dyspnea. No systemic effects have been reported from industrial exposure, but relatively few studies are available.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 241.6
2. Boiling point (760 mm Hg): −38.4 C (−38 F) (sublimes)
3. Specific gravity (water = 1): Not applicable
4. Vapor density (air = 1 at boiling point of tellurium hexafluoride): 8.3
5. Melting point: −37.8 C (−36 F) (triple-point)
6. Vapor pressure at 20 C (68 F): Greater than 1 atmosphere
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts slowly
8. Evaporation rate (butyl acetate = 1): Not perti-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1335

nent

- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen fluoride) may be released when tellurium hexafluoride decomposes.
  4. Special precautions: See 29 CFR 1910.101 for specific regulations on storage of compressed gas cylinders.
- **Flammability**
  1. Not combustible
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold of tellurium hexafluoride. The *Documentation of TLV's*, however, notes that this gas has an unpleasant odor.
  2. Eye Irritation Level: Tellurium hexafluoride is not known to be an eye irritant.
  3. Evaluation of Warning Properties: Since no quantitative information is available relating its warning properties to air concentrations, this compound is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of tellurium hexafluoride using an adsorption tube, followed by desorption with sodium hydroxide and atomic absorption spectrophotometric analysis. An analytical method for tellurium hexafluoride is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tellurium hexafluoride may occur and control methods which may be effective in each case:

Operation	Controls
Use in scientific studies on physical and chemical properties such as magnetic spin, force constants spectra, electron diffraction, crystal structure, and corrosive action	Process enclosure; local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Breathing**

If a person breathes in large amounts of tellurium hexafluoride, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.
- If tellurium hexafluoride is leaked, the following steps should be taken:

1. Ventilate area of leak to disperse gas.
2. Stop flow of gas. If source of leak is a cylinder and the leak cannot be stopped inplace, remove the leaking cylinder to a safe place in the open air, and repair the leak or allow the cylinder to empty.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tellurium Hexafluoride," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Tellurium," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Cerwenka, E. A., Jr., and Cooper, W. C.: "Toxicology of Selenium and Tellurium and Their Compounds," *Archives of Environmental Health*, 3:189-200, 1961.

• Cooper, W. C.: *Tellurium*, Van Nostrand Reinhold, New York, 1971.

RESPIRATORY PROTECTION FOR TELLURIUM HEXAFLUORIDE

Condition	Minimum Respiratory Protection* Required Above 0.02 ppm
Gas Concentration	
0.2 ppm or less	Any supplied-air respirator. Any self-contained breatning apparatus.
1 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 1 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against tellurium hexafluoride. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for TEPP

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_2H_5)_4P_2O_7$
- Synonyms: Tetraethyl pyrophosphate, commercial 40%; ethyl pyrophosphate; bladan; nifost; vapotone; tetron; killax; mortopal
- Appearance and odor: Colorless to amber liquid with a faint fruity odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for TEPP is 0.05 milligram of TFPP per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

TEPP can affect the body if it is inhaled or if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: After inhalation of TEPP, breathing and eye effects are the first to appear. These include tightness of the chest, wheezing, a bluish discoloration of the skin, small pupils, aching in and behind the eyes, blurring of vision, tearing, runny nose, headache, and watering of the mouth. After swallowing TEPP, loss of appetite, nausea, vomiting, abdominal cramps, and diarrhea may appear within 2 hours. After skin absorption, sweating and twitching in the area of absorption may occur usually within 15 minutes to 4 hours. With severe intoxiciation by all routes, in addition to the above symptoms, weakness, generalized twitching and paralysis may occur and breathing may stop. In addition, dizziness, confusion, staggering, slurred speech, generalized sweating, irregular or slow heartbeat, convulsions, and coma may occur.

2. Long-term Exposure: Repeated exposure to TEPP may make a person more susceptible to the effects of this and related chemicals. Repeated exposure to concentrations which are too small to produce symptoms after a single exposure may result in the onset of symptoms.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to TEPP.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to TEPP at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of reduced pulmonary function, convulsive disorders, or recent exposure to anticholinesterase agents would be expected to be at increased risk from exposure. Examination of the respiratory system, nervous system, cardiovascular system, and attention to the cholinesterase levels in the blood should be stressed.

—Cholinesterase determination: TEPP causes depressed levels of activity of cholinesterase in the serum and erythrocytes. The cholinesterase activity in the serum and erythrocytes should be determined by using medically acceptable biochemical tests prior to new period of exposure.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, with the exception of the cholinesterase determination which should be performed quarterly or at any

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1339

time overexposure is suspected or signs or symptoms of toxicity occur.

• **Summary of toxicology**

TEPP (tetraethyl pyrophosphate) is an anticholinesterase agent; absorption may occur from inhalation of the mist, by skin absorption, or by ingestion of the liquid. Signs and symptoms of overexposure are caused by the inactivation of the enzyme cholinesterase, which results in the accumulation of acetylcholine at synapses in the nervous system, skeletal and smooth muscle, and secretory glands. The sequence of the development of systemic effects varies with the route of entry. The onset of signs and symptoms occurs promptly and almost always within 12 hours. After inhalation, respiratory and ocular effects are the first to appear, often within a few minutes after exposure. Respiratory effects include tightness in the chest and wheezing due to bronchoconstriction and excessive bronchial secretion; laryngeal spasms and excessive salivation may add to the respiratory distress; cyanosis may also occur. Ocular effects include miosis, aching in and behind the eyes (attributed to ciliary spasm), blurring of distant vision, tearing, rhinorrhea, and frontal headache. After ingestion, gastrointestinal effects such as anorexia, nausea, vomiting, abdominal cramps, and diarrhea appear within 15 minutes to 2 hours. After skin absorption, localized sweating and muscular fasciculations in the immediate area occur usually within 15 minutes to 4 hours; skin absorption is somewhat greater at higher ambient temperatures, and is increased by the presence of dermatitis. With severe intoxication by all routes, an excess of acetylcholine at the neuromuscular junctions of skeletal muscle causes weakness aggravated by exertion, involuntary twitchings, fasciculations, and eventually paralysis; the most serious consequence is paralysis of the respiratory muscles. Effects on the central nervous system include giddiness, confusion, ataxia, slurred speech, Cheyne-Stokes respiration, convulsions, coma, and loss of reflexes. The blood pressure may fall to low levels, and cardiac irregularities including complete heart block may occur; these effects may sometimes be reversed by establishing adequate pulmonary ventilation. Complete symptomatic recovery usually occurs within one week; increased susceptibility to the effects of anticholinesterase agents persists for one to several days after exposure. Daily exposure to concentrations which are insufficient to produce symptoms following a single exposure may result in the onset of symptoms. Continued daily exposure may be followed by increasingly severe effects. Mild intoxication was reported in 15 people exposed to a dust of 1% TEPP under unusual conditions of static air; the predominant symptom was shortness of breath which occurred after breathing the dust-laden air for 30 minutes; symptoms rapidly abated after exposure was terminated.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 290.2
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.2
4. Vapor density (air = 1 at boiling point of TEPP): Not applicable
5. Melting point: Gradually sets to glass below 0 C (32 F)
6. Vapor pressure at 140 C (284 F): 1 mm
7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Temperatures above 150 C (300 F) cause decomposition with formation of flammable ethylene gas.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as phosphoric acid mist and carbon monoxide) may be released when TEPP decomposes.
4. Special precautions: TEPP will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of TEPP.
2. Eye Irritation Level: TEPP is not known to produce a local, irritant effect upon the eye. According to Grant, however, when absorbed by the eye, TEPP can cause visual disturbances.
3. Evaluation of Warning Properties: No quantitative information is available relating warning properties to air concentrations of TEPP. TEPP, therefore, is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for TEPP is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental

concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with TEPP.

• Clothing contaminated with TEPP should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of TEPP from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the TEPP, the person performing the operation should be informed of TEPP's hazardous properties.

• Where there is any possibility of exposure of an employee's body to TEPP, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with TEPP should be removed immediately and not reworn until the TEPP is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of TEPP contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to TEPP, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with TEPP should be immediately washed or showered to remove any TEPP.

• Eating and smoking should not be permitted in areas where TEPP is handled, processed, or stored.

• Employees who handle TEPP should wash the hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to TEPP may occur and control methods which may be effective in each case:

Operation	Controls
Application as a contact insecticide on agricultural and ornamental crops, including use in greenhouses	Personal protective equipment
Formulation of insecticides	General dilution ventilation; personal protective equipment
Manufacture of TEPP	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If TEPP or formulations containing TEPP get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If TEPP or formulations containing TEPP get on the skin, immediately wash the contaminated skin with water. If TEPP or formulations containing TEPP penetrate through the clothing, remove the clothing immediately and wash the skin with water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of TEPP, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When TEPP or formulations containing TEPP have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If TEPP is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

TEPP may be disposed of by absorbing in vermiculite, dry sand, earth, or a similar material and disposing in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "TEPP (Tetraethyl Pyrophosphate)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Goodman, L. S., and Gilman, A.: *The Pharmacological Basis of Therapeutics* (5th ed.), Macmillan, New York, 1975.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• Koelle, G. B. (ed.): *Cholinesterases and Anticholinesterase Agents*, Vol. 15 of *Handbuch der Experimentellen Pharmakologie*, Springer-Verlag, Berlin, 1963.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Quinby, G. E., and Doornink, G. M.: "Tetraethyl Pyrophosphate Poisoning Following Airplane Dusting," *Journal of the American Medical Association*, 191:95-100, 1965.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV). and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

RESPIRATORY PROTECTION FOR TEPP

Condition	Minimum Respiratory Protection* Required Above 0.05 mg/m³
Particulate or Vapor Concentration	
0.5 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
2.5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 10 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates, including pesticide respirators which meet the requirements of this class. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of TEPP; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 10 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Terphenyls

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{18}H_{14}$
- Synonyms: ortho-Terphenyl; meta-terphenyl; para-terphenyl; mixed terphenyls; diphenylbenzenes; triphenyls
- Appearance: Colorless or light yellow solids.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for terphenyls is a ceiling of 1 part of terphenyls per million parts of air (ppm). This may also be expressed as 9 milligrams of terphenyls per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has recommended for terphenyls a Threshold Limit Value of 0.5 ppm as a ceiling value.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Terphenyls can affect the body if they are inhaled, come in contact with the eyes or skin, or are swallowed.

- **Effects of overexposure**

Exposure to terphenyls may cause eye, skin, and respiratory irritation.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to terphenyls.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to terphenyls at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from terphenyls exposure.

—Skin disease: The hot vapors of the terphenyls have a primary irritant effect on the skin. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Chronic respiratory disease: Persons with acute or chronic respiratory diseases may be more susceptible to the effects of terphenyls, since transient changes in the mitochondria of alveolar cells have been demonstrated in the lungs of animals following such exposure.

—Liver disease: Persons with liver disease may be more susceptible to the effects of inhalation of terphenyls, since transient changes in hepatic cells have been demonstrated in the liver of animals following such exposure.

—Kidney disease: Although terphenyls are not recognized as renal toxins, the importance of this organ in the excretion of metabolites formed from absorbed terphenyls justifies special consideration in those with possible impairment of renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Experimental animals show conjunctival irritation from direct contact with terphenyls. Clinical studies of an exposed group of employees showed no ill effects from prolonged exposure to concentrations ranging from 0.1 to 0.9 mg/m³. Animals exposed to concentrations of three to five times these levels had slight cellular changes in the lungs and liver, as demonstrated by electron microscopy. Absorbed terphenyls are slowly metabolized and excreted in the urine as phenolic compounds and as glucuronides.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1976

1. Molecular weight: 230

2. Boiling point (760 mm Hg): 333 to 381 C (630 to 718 F)

3. Specific gravity (water = 1): 1.1 to 1.2

4. Vapor density (air = 1 at boiling point of terphenyls): Not applicable

5. Melting point: 56 to 213 C (133 to 415 F)

6. Vapor pressure at 20 C (68 F): Very low

7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: None

3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving terphenyls.

4. Special precautions: None

• **Flammability**

1. Flash point: 163 to 207 C (325 to 405 F) (open cup)

2. Autoignition temperature: Data not available

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Carbon dioxide or dry chemical

• **Warning properties**

The *Documentation of TLV's* states that "the available toxicologic data indicate that terphenyls may produce eye, skin, and respiratory irritation; they may also cause sensitization, but this has not been shown in man. Workers exposed to dust and vapor experienced marked irritation at concentrations in air above 10 mg/m³. On this basis, a threshold limit value of 1ppm (about 9.4 mg/m³) as a ceiling value is recommended to prevent irritation of the eye and respiratory tract."

MONITORING AND MEASUREMENT PROCEDURES

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of terphenyls. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of terphenyls on a filter, followed by leaching with carbon disulfide, and gas chromatographic analysis. An analytical method for terphenyls is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with molten terphenyls.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid terphenyls or liquids containing terphenyls.

• If employees' clothing may have become contaminated with solid terphenyls, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with terphenyls should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of terphenyls from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the terphenyls, the person performing the operation should be informed of terphenyls's hazardous properties.

• Where there is any possibility of exposure of an employee's body to molten terphenyls, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with terphenyls should be removed promptly and not reworn until the terphenyls are removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of molten terphenyls contacting the eyes.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where solid

terphenyls or solutions containing terphenyls may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to molten terphenyls, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with terphenyls should be promptly washed or showered with soap or mild detergent and water to remove any terphenyls.

• Employees who handle solid terphenyls or solutions containing terphenyls should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to terphenyls may occur and control methods which may be effective in each case:

Operation	Controls
Use during formulation of waxes, polishes, and resin body paints	Local exhaust ventilation; personal protective equipment
Liberation during application of resin body paints, solvents, waxes, and polishes	Personal protective equipment
Liberation during maintenance operations or following leaks in heat-transfer systems; during release of high-temperature lubricants; during distillation and other processing operations	Personal protective equipment
Liberation during manufacture of plastic scintillators; during process of flaking or crushing to produce solid terphenyls following distillation	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If terphenyls get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If terphenyls dust or solutions containing terphenyls get on the skin, promptly wash or shower to remove any terphenyls from the skin. If molten terphenyls get on the skin, immediately wash or shower the contaminated skin to remove any terphenyls from the skin. If molten terphenyls soak through the clothing, remove the clothing immediately and flush the skin with water. When there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of terphenyls, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If terphenyls have been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If terphenyls are spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, use a procedure similar to that for small quantities.

• Waste disposal methods:

Terphenyls may be disposed of:

1. By making packages of terphenyls in paper or other flammable material and burning in a suitable combustion chamber.
2. By dissolving terphenyls in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Terphenyls," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd

ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Cornish, H. H., et al.: "Toxicity and Metabolism of Ortho-, Meta-, and Para-Terphenyls," *American Industrial Hygiene Association Journal*, 23:372-378, 1962.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Weeks, J. L., and Lentle, B. C.: "Health Considerations in the Use of Organic Reactor Coolants," *Journal of Occupational Medicine*, 12:246-252, 1970.

RESPIRATORY PROTECTION FOR TERPHENYLS

Condition	Minimum Respiratory Protection* Required Above 9 mg/m³
Particulate Concentration	
450 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
3500 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 3500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1,1,2,2-Tetrachloro-1,2-Difluoroethane*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CCl_2F-CCl_2F
- Synonyms: Refrigerant 112; halocarbon 112
- Appearance and odor: Colorless liquid or solid with a slight ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,1,2,2-tetrachloro-1,2-difluoroethane is 500 parts of 1,1,2,2-tetrachloro-1,2-difluoroethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 4170 milligrams of 1,1,2,2-tetrachloro-1,2-difluoroethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,1,2,2-Tetrachloro-1,2-difluoroethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: 1,1,2,2-Tetrachloro-1,2-difluoroethane might cause irritation of the skin and eyes. It might also cause drowsiness and difficult breathing.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,1,2,2-tetrachloro-1,2-difluoroethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,1,2,2-tetrachloro-1,2-difluoroethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,1,2,2-tetrachloro-1,2-difluoroethane exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1,1,2,2-tetrachloro-1,2-difluoroethane might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,1,2,2-Tetrachloro-1,2-difluoroethane vapor is a narcotic. Rats exposed to 10,000 ppm for 1-½ to 2 hours showed signs of intoxication; concentrations of 20,000 to 30,000 ppm for the same period were fatal and caused pulmonary hemmorhages. In rats repeatedly exposed for 6 hours to 1,000 ppm, there were no clinical signs of toxicity; some showed slight changes in liver cells, and a few female rats had a decreased leukocyte count. The liquid applied to the intact skin of guinea pigs produced mild irritation in 24 hours. Instilled in the eyes of rabbits, it produced mild conjunctival irritation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 203.8
2. Boiling point (760 mm Hg): 92.8 C (199 F)
3. Specific gravity (water = 1): 1.65
4. Vapor density (air = 1 at boiling point of 1,1,2,2-tetrachloro-1,2-difluoroethane): 7
5. Melting point: 26 C (79 F)
6. Vapor pressure at 20 C (68 F): 40 mm Hg

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-13-78

7. Solubility in water, g/100 g water at 20 C (68 F): 0.012

8. Evaporation rate (butyl acetate = 1): Greater than 1

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Reacts with chemically active metals such as sodium, potassium, and beryllium, or with powdered aluminum, zinc, and magnesium.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, hydrogen fluoride, and carbon monoxide) may be released when 1,1,2,2-tetrachloro-1,2-difluoroethane decomposes.

4. Special precautions: 1,1,2,2-Tetrachloro-1,2-difluoroethane will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

No quantitative data are available relating warning properties of 1,1,2,2-tetrachloro-1,2-difluoroethane to its air concentrations. Therefore, this compound is treated as a material with poor warning properties. Deichmann and Gerarde report that 1,1,2,2-tetrachloro-1,2-difluoroethane is mildly irritating to rabbit eyes, but the levels at which irritation occurs are not given.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,1,2,2-tetrachloro-1,2-difluoroethane may be used. An analytical method for 1,1,2,2-tetrachloro-1,2-difluoroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).
(order number PB 265 028).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid or solid 1,1,2,2-tetrachloro-1,2-difluoroethane.

• Non-impervious clothing which becomes wet with liquid 1,1,2,2-tetrachloro-1,2-difluoroethane or contaminated with solid 1,1,2,2-tetrachloro-1,2-difluoroethane should be removed promptly and not reworn until the 1,1,2,2-tetrachloro-1,2-difluoroethane is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where liquid or solid 1,1,2,2-tetrachloro-1,2-difluoroethane may contact the eyes.

SANITATION

• Skin that becomes wet with liquid 1,1,2,2-tetrachloro-1,2-difluoroethane or contaminated with solid 1,1,2,2-tetrachloro-1,2-difluoroethane should be promptly washed or showered with soap or mild detergent and water to remove any 1,1,2,2-tetrachloro-1,2-difluoroethane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,1,2,2-tetrachloro-1,2-difluoroethane may occur and control methods which may be effective in each case:

Operation	Controls
Use in dry cleaning industry for wool, cotton, dacron, and leather materials in combination with other solvents as azeotropic mixture; use in electric or electronic industries for cleaning rosin fluxes from circuit boards, and cleaning solvent for complex electronic parts and magnetic tapes	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in polymer and plastics industry as blowing or foaming agent for cellular and microporous materials	Local exhaust ventilation
Use as solvent extractant for separation and purification of biological material; use as a dye solvent to give brighter colors, and to detect surface cracks or defects in metals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as corrosion inhibitors in brake fluid, surface coatings on electrical equipment, heat control of reactions, and propellants	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If 1,1,2,2-tetrachloro-1,2-difluoroethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If 1,1,2,2-tetrachloro-1,2-difluoroethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 1,1,2,2-tetrachloro-1,2-difluoroethane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of 1,1,2,2-tetrachloro-1,2-difluoroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When 1,1,2,2-tetrachloro-1,2-difluoroethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the person to vomit by having him touch the back of the throat with his finger or by giving him large amounts (one pint or more) of warm salt water (two tablespoons of salt per pint of water.) Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If 1,1,2,2-tetrachloro-1,2-difluoroethane is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If in the liquid form, collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.
3. If in the solid form, collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill.

- Waste disposal methods:

1,1,2,2-Tetrachloro-1,2-difluoroethane may be disposed of:

1. If in the liquid form, by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. If in the solid form, by disposing in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "1,1,2,2-Tetrachloro-1,2-Difluoroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Clayton, J. W., et al.: "Toxicity Studies on 1,1,2,2-

Tetrachloro-1,2-Difluoroethane and 1,1,1,2-Tetrachloro-2,2-Difluoroethane," *American Industrial Hygiene Association Journal*, 27:332-340, 1960.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

* SPECIAL NOTE

1,1,2,2-Tetrachloro-1,2-difluoroethane appears on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding its carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980).

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 20, 1979.

RESPIRATORY PROTECTION FOR 1,1,2,2-TETRACHLORO-1,2-DIFLUOROETHANE

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
5000 ppm or less	Any supplied-air respirator.
	Any self-contained breathing apparatus.
15,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 15,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

1331

Occupational Health Guideline for 1,1,1,2-Tetrachloro-2,2-Difluoroethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: CCl_3-$CClF_2$
- Synonyms: Halocarbon 112a; refrigerant 112a; 2,2-difluoro-1,1,1,2-tetrachloroethane
- Appearance and odor: Colorless liquid or solid with a slight ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,1,1,2-tetrachloro-2,2-difluoroethane is 500 parts of 1,1,1,2-tetrachloro-2,2-difluoroethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 4170 milligrams of 1,1,1,2-tetrachloro-2,2-difluoroethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,1,1,2-Tetrachloro-2,2-difluoroethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: 1,1,1,2-Tetrachloro-2,2-difluoroethane might cause irritation of the skin and eyes. It might also cause drowsiness and difficulty in breathing.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,1,1,2-tetrachloro-2,2-difluoroethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,1,1,2-tetrachloro-2,2-difluoroethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,1,1,2-tetrachloro-2,2-difluoroethane exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1,1,1,2-tetrachloro-2,2-difluoroethane might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,1,1,2-Tetrachloro-2,2-difluoroethane vapor is a narcotic. Rats exposed to 10,000 ppm for 1-½ to 2 hours showed signs of intoxication, and concentrations of 20,000 to 30,000 ppm were fatal. Rats succumbing to 15,000 ppm for 4 hours evidenced pulmonary congestion and edema with some hemorrhage. Application in alcohol to the skin of rabbits produced severe irritation, while no irritation was reported when applied with dimethylphthalate. There are no reports of systemic effects in workers from industrial exposure.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 203.8
2. Boiling point (760 mm Hg): 92 C (197 F)
3. Specific gravity (water = 1): 1.65
4. Vapor density (air = 1 at boiling point of 1,1,1,2-tetrachloro-2,2-difluoroethane): 7
5. Melting point: 40.6 C (105 F)
6. Vapor pressure at 20 C (68 F): 40 mm Hg (approximately)

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

DHEW (NIOSH) Publication No. 78-183

September 1978

7. Solubility in water, g/100 g water at 20 C (68 F): 0.012

8. Evaporation rate (butyl acetate = 1): Greater than 1

- **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Reacts with chemically active metals such as sodium, potassium, and beryllium, or with powdered magnesium, aluminum, and zinc.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, hydrogen fluoride, and carbon monoxide) may be released when 1,1,1,2-tetrachloro-2,2-difluoroethane decomposes.

4. Special precautions: 1,1,1,2-Tetrachloro-2,2-difluoroethane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible

- **Warning properties**

No quantitative data are available relating warning properties to air concentrations of of this compound. Therefore, for the purposes of this guideline, it is treated as a material with poor warning properties.

1,1,1,2-Tetrachloro-2,2-difluoroethane is not a known eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,1,1,2-tetrachloro-2,2-difluoroethane may be used. An analytical method for 1,1,1,2-tetrachloro-2,2-difluoroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid or solid 1,1,1,2-tetrachloro-2,2-difluoroethane.
- Non-impervious clothing which becomes contaminated with liquid or solid 1,1,1,2-tetrachloro-2,2-difluoroethane should be removed promptly and not reworn until the 1,1,1,2-tetrachloro-2,2-difluoroethane is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where liquid or solid 1,1,1,2-tetrachloro-2,2-difluoroethane may contact the eyes.

SANITATION

- Skin that becomes contaminated with liquid or solid 1,1,1,2-tetrachloro-2,2-difluoroethane should be promptly washed or showered with soap or mild detergent and water to remove any 1,1,1,2-tetrachloro-2,2-difluoroethane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,1,1,2-tetrachloro-2,2-difluoroethane may occur and control methods which may be effective in each case:

Operation	Controls
Use in dry cleaning industry for wool, cotton, dacron, and leather materials in combination with other solvents as azeotropic mixture; use in electric or electronic industries for cleaning rosin fluxes from circuit boards, and cleaning solvent for complex electronic parts and magnetic tapes	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in polymer and plastics industry as blowing or foaming agent for cellular and microporous materials	Local exhaust ventilation
Use as solvent extractant for separation and purification of biological material; use as a dye solvent to give brighter colors, and to detect surface cracks or defects in metals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as corrosion inhibitors in brake fluid, surface coatings on electrical equipment, heat control of reactions, and propellants	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 1,1,1,2-tetrachloro-2,2-difluoroethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 1,1,1,2-tetrachloro-2,2-difluoroethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 1,1,1,2-tetrachloro-2,2-difluoroethane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1,1,1,2-tetrachloro-2,2-difluoroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 1,1,1,2-tetrachloro-2,2-difluoroethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 1,1,1,2-tetrachloro-2,2-difluoroethane is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If in the liquid form, collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.
3. If in the solid form, collect spilled material in the most convenient and safe manner for reclamation.

• Waste disposal methods:

1,1,1,2-Tetrachloro-2,2-difluoroethane may be disposed of:

1. If in the liquid form, by absorbing it in vermiculite, dry sand, earth or a similar material
2. If in the solid form, by disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1,1,1,2-Tetrachloro-2,2-Difluoroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Clayton, J. W.: "Toxicity Studies on 1,1,2,2-Tetrachlo[illegible]-1,2-Difluoroethane and 1,1,1,2-Tetrachloro-2,2-Difluoroethane," *American Industrial Hygiene Association Journal*, 27:332-340, 1966.

way, Cincinnati, Ohio 45226.

-1334

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR 1,1,1,2-TETRACHLORO-2,2-DIFLUOROETHANE

Condition	Minimum Respiratory Protection* Required Above 500 ppm
Vapor Concentration	
5000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
15,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a half facepiece operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 15,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

-1005

Occupational Health Guideline for 1,1,2,2-Tetrachloroethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CHCl_2CHCl_2$
- Synonyms: Symmetrical-tetrachloroethane; acetylene tetrachloride; sym-tetrachlorethane
- Appearance and odor: Colorless or pale yellow liquid with a sickly sweet odor, like chloroform.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,1,2,2-tetrachloroethane is 5 parts of 1,1,2,2-tetrachloroethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 35 milligrams of 1,1,2,2-tetrachloroethane per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to 1 ppm ($6.87\ mg/m^3$) averaged over a 10-hour work shift. The NIOSH Criteria Document for 1,1,2,2-Tetrachloroethane should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,1,2,2-Tetrachloroethane can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Breathing in high concentrations of 1,1,2,2-tetrachloroethane may cause irritation of the eyes and nose, nausea, vomiting, and drowsiness. Liver and kidney damage may occur. If the exposure was severe, within a few hours a deep dusky coloration of the skin may appear, followed by unconsciousness and death. If the exposed worker is removed immediately, he may recover completely but should be placed under observation in case late symptoms appear. If the vapor or liquid of 1,1,2,2-tetrachloroethane gets into the eyes, it may cause watering and burning. It may cause serious eye damage unless immediate medical care is obtained.

2. Long-term Exposure: Prolonged or repeated exposure to 1,1,2,2-tetrachloroethane, either by breathing or by absorbing it through the skin, may cause fatigue, loss of appetite, tremors, weight loss, constipation, heart damage, blood changes, kidney damage, abdominal distress or pain, vomiting, dizziness, tenderness, liver damage with such symptoms as pain over the liver, dark urine, and yellow jaundice. Reproductive abnormalities have been noted in studies of animals following exposure to high levels of 1,1,2,2-tetrachloroethane. Prolonged or repeated skin contact with 1,1,2,2-tetrachloroethane may also cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,1,2,2-tetrachloroethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,1,2,2-tetrachloroethane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver, kidneys, and central nervous system should be stressed.

—Liver function tests: 1,1,2,2-Tetrachloroethane causes liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1338

—Urinalysis: Since kidney damage has also been observed from exposure, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

1,1,2,2-Tetrachloroethane is highly toxic to the liver and is a central nervous system depressant. Rats exposed to 500 ppm for 4 hours survived, but 1,000 ppm was fatal. Reports of industrial experience indicate that cases of mild intoxication have presented symptoms of gastrointestinal irritation (nausea, vomiting, abdominal pain, anorexia) and central nervous system effects (dizziness, headache, irritability, nervousness, insomnia); more severe exposure resulted in liver involvement (enlarged and tender liver, jaundice, bilirubinuria), nephritis (albuminuria and casts); and tremors of hands and eyelids. In cases of severe industrial intoxication, there was hepatic necrosis with jaundice, sometimes progressing to cirrhosis; individuals who died during the acute stage also showed cerebral edema and pulmonary edema with hemorrhage, as well as liver and kidney injury. One study reported that human subjects exposed to 335 ppm for 10 minutes or 186 ppm for 30 minutes noted a disagreeable odor; there were some upper respiratory irritation and central nervous system effects. Among a group of workers in India exposed to 20-65 ppm there was nausea, vomiting, and abdominal pain and a high incidence of tremor of the hands. Prolonged skin exposure may be expected to produce dermatitis due to defatting action. Eye damage has been reported.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

1. Molecular weight: 167.8
2. Boiling point (760 mm Hg): 146 C (295 F)
3. Specific gravity (water = 1): 1.6
4. Vapor density (air = 1 at boiling point of 1,1,2,2-tetrachloroethane): 5.8
5. Melting point: −42.5 C (−44.5 F)
6. Vapor pressure at 20 C (68 F): 8 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.29
8. Evaporation rate (butyl acetate = 1): 0.65

• **Reactivity**

1. Conditions contributing to instability: Heat; unusual exposure to light in the presence of air may form small amounts of phosgene.

2. Incompatibilities: Reacts with chemically active metals or with strong caustics. In the presence of steam, contact with hot iron, aluminum, and zinc may cause formation of toxic vapors.

3. Hazardous decomposition products: Toxic gases and vapors (such as phosgene, hydrogen chloride, chlorinated solvents, and carbon monoxide) may be released when 1,1,2,2-tetrachloroethane decomposes.

4. Special precautions: Liquid 1,1,2,2-tetrachloroethane will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Patty states that the odor of 1,1,2,2-tetrachloroethane is detectable at 5 ppm (3 ppm, according to Lehmann). Since the odor threshold is at (or below) the permissible exposure limit, this compound is treated as a material with good warning properties.

Grant indicates that this compound is not an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,1,2,2-tetrachloroethane may be used. An analytical method for 1,1,2,2-tetrachloroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

PB 265 028).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid 1,1,2,2-tetrachloroethane.

• Clothing contaminated with liquid 1,1,2,2-tetrachloroethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1,1,2,2-tetrachloroethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1,1,2,2-tetrachloroethane, the person performing the operation should be informed of 1,1,2,2-tetrachloroethane's hazardous properties.

• Where exposure of an employee's body to liquid 1,1,2,2-tetrachloroethane may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with liquid 1,1,2,2-tetrachloroethane should be removed immediately and not reworn until the 1,1,2,2-tetrachloroethane is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid 1,1,2,2-tetrachloroethane contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid 1,1,2,2-tetrachloroethane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid 1,1,2,2-tetrachloroethane should be immediately washed or showered with soap or mild detergent and water to remove any 1,1,2,2-tetrachloroethane.

• Eating and smoking should not be permitted in areas where liquid 1,1,2,2-tetrachloroethane is handled, processed, or stored.

• Employees who handle liquid 1,1,2,2-tetrachloroethane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,1,2,2-tetrachloroethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a chemical intermediate in manufacture of tetrachloroethylene and trichloroethylene; use in cleaning and extraction processes; use in chlorination of phthalic anhydride; use in manufacture of cyanogen chloride, polymers, and tetrachloro-alkylphenol	Local exhaust ventilation; general dilution ventilation
Use as a fumigant in greenhouses	Personal protective equipment
Use in manufacture of lacquers and varnishes, paint and varnish removers	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during use and preparation of insecticides and weed killers	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in cleaning and degreasing of metals	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a solvent in preparation of adhesives	Local exhaust ventilation
Use during addition to aliphatic alcohols and acetates to improve solvency for nitrocellulose and cellulose acetate as in photographic film	Local exhaust ventilation
Use in application of adhesives	General dilution ventilation; personal protective equipment
Use in refining of waxes and resins	Local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 1,1,2,2-tetrachloroetha gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical

attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 1,1,2,2-tetrachloroethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 1,1,2,2-tetrachloroethane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1,1,2,2-tetrachloroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 1,1,2,2-tetrachloroethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 1,1,2,2-tetrachloroethane is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

1,1,2,2-Tetrachloroethane may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

ADDITIONAL INFORMATION

To find additional information on 1,1,2,2-tetrachloroethane, look up 1,1,2,2-tetrachloroethane in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards
• NIOSH Criteria Document for 1,1,2,2-Tetrachloroethane (December 1976)

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1,1,2,2-Tetrachloroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products5(3rd ed.), Williams and Wilkins, Baltimore, 1969.*

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

Survey," *British Journal of Industrial Medicine*, 20:50-56, 1963.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-34, 1,1,2,2-Tetrachloroethane,* Washington, D.C., 1949.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to 1,1,2,2-Tetrachloroethane,* HEW Publication No. (NIOSH) 77-121, GPO No. 017-033-00179-1, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers,* U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR 1,1,2,2-TETRACHLOROETHANE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
50 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
150 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 150 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Tetrachloroethylene*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CCl_2 = CCl_2$
- Synonyms: Perchloroethylene; perchlorethylene; tetrachlorethylene; perk
- Appearance and odor: Colorless liquid with an odor like chloroform or ether.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tetrachloroethylene is 100 parts of tetrachloroethylene per million parts of air (ppm) averaged over an eight-hour work shift, with a ceiling level of 200 ppm and a maximum acceptable peak of 300 ppm for 5 minutes in any three-hour period. NIOSH has recommended that the permissible exposure limit be reduced to 50 ppm (339 mg/m³) averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 100 ppm (678 mg/m³) averaged over a 15-minute period. The NIOSH Criteria Document for Tetrachloroethylene should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tetrachloroethylene can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Tetrachloroethylene may cause headache, nausea, drowsiness, dizziness, incoordination, and unconsciousness. It may also cause irritation of the eyes, nose, and throat and flushing of the face and neck. In addition, it might cause liver damage with such findings as yellow jaundice and dark urine. The liver damage may become evident several weeks after the exposure.

2. Long-term Exposure: Prolonged or repeated overexposure to liquid tetrachloroethylene may cause irritation of the skin. It might also cause damage to the liver and kidneys.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tetrachloroethylene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tetrachloroethylene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver and the cardiovascular and neurological systems should be stressed. The skin should be examined for evidence of chronic disorders.

—Liver function tests: Tetrachloroethylene may cause liver damage. A profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

—Urinalysis: Since kidney damage has also been observed from exposure, a urinalysis should be obtained to include at minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Tetrachloroethylene vapor is a narcotic. Rats did not survive when exposed for longer than 12-18 minutes to 12,000 ppm; when exposed repeatedly to 470 ppm they showed liver and kidney injury. Cardiac arrhythmias

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1981

September 1978

attributed to sensitization of the myocardium to epinephrine have been observed with certain other chlorinated hydrocarbons, but exposure of dogs to concentrations of 5000 and 10,000 ppm tetrachloroethylene did not produce this phenomenon. Four human subjects were unable to tolerate 5000 ppm in a chamber for 6 minutes. They experienced vertigo, nausea, and mental confusion during the 10 minutes following cessation of exposure. In an industrial exposure to an average concentration of 275 ppm for 3 hours, followed by 1100 ppm for 30 minutes, a worker lost consciousness; there was apparent clinical recovery 1 hour after exposure but the monitored concentration of tetrachloroethylene in the patient's expired air diminished slowly over a 2-week period. Long-term industrial exposures have been reported to cause various neuropathies, such as numbness, trembling, neuritis, and defects of memory. During the second and third post-exposure weeks, the results of liver function tests became abnormal, suggesting that acute exposure had had a significant effect upon the liver. Other instances of liver injury following industrial exposure have been reported. Other effects on humans of inhalation of various concentrations are as follows: 2000 ppm, mild narcosis within 5 minutes; 600 ppm, sensation of numbness around the mouth, dizziness, and some incoordination after 10 minutes. In human experiments, 7-hour exposures at 100 ppm resulted in mild irritation of the eyes, nose, and throat; flushing of the face and neck; headache; somnolence; and slurred speech. Exposure of the skin to the liquid for 40 minutes resulted in a progressively severe burning sensation beginning within 5 to 10 minutes; the result was marked erythema, which subsided after 1 to 2 hours. The liquid sprayed into rabbits' eyes produced immediate pain and blepharospasm; patches of epithelium were lost, but the eyes recovered completely within 2 days.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 165.85
  2. Boiling point (760 mm Hg): 121.2 C (250 F)
  3. Specific gravity (water = 1): 1.62
  4. Vapor density (air = 1 at boiling point of tetrachloroethylene): 5.83
  5. Melting point: −22.4 C (−8 F)
  6. Vapor pressure at 20 C (68 F): 14 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.015
  8. Evaporation rate (butyl acetate = 1): 2.8
- **Reactivity**
  1. Conditions contributing to instability: Heat.
  2. Incompatibilities: Tetrachloroethylene reacts with strong oxidizers and chemically active metals such as barium, lithium, and beryllium.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released when tetrachloroethylene decomposes.
  4. Special precautions: Liquid tetrachloroethylene will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**
  1. Odor Threshold: Both May and Stern state that 50 ppm is the odor threshold for tetrachloroethylene.
  2. Eye Irritation Level: Grant reports that "exposure to high concentrations of (tetrachloroethylene) vapor causes mild sensation of irritation to the eyes, but serious injury is not likely." The exact concentrations producing irritation are not mentioned by Grant.

Spector, however, reports that after a 20- to 30-minute exposure to 206 to 235 ppm, eye irritation occurs in humans.

Patty reports "very slight irritation of the eyes" among humans at 106 ppm.

3. Other Information: Spector reports that a 10-minute exposure to 513 to 690 ppm produces nose and throat irritation.

4. Evaluation of Warning Properties: Since the odor threshold of tetrachloroethylene is below the permissible exposure limit, and since eye irritation occurs at a concentration only twice the permissible exposure limit, its warning properties are considered to be adequate.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of tetrachloroethylene. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Peak Above Ceiling Evaluation**

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of tetrachloroethylene. Each measurement should consist of a 30-minute sample or a series of consecutive samples totalling 30 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of

three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• Method

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure tetrachloroethylene may be used. An analytical method for tetrachloroethylene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid tetrachloroethylene.

• Non-impervious clothing which becomes contaminated with liquid tetrachloroethylene should be removed promptly and not reworn until the tetrachloroethylene is removed from the clothing.

• Clothing wet with liquid tetrachloroethylene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tetrachloroethylene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tetrachloroethylene, the person performing the operation should be informed of tetrachloroethylene's hazardous properties.

• Employees should be provided with and required to use splash-proof safety goggles where liquid tetrachloroethylene may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid tetrachloroethylene should be promptly washed or showered with soap or mild detergent and water to remove any tetrachloroethylene.

• Employees who handle liquid tetrachloroethylene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tetrachloroethylene may occur and control methods which may be effective in each case:

Operation	Controls
Use as dry cleaning solvent; as degreasing and metal cleaning agent; in vapor degreasing of metal parts	Local exhaust ventilation; general dilution; personal protective equipment
Use as chemical intermediate in production of fluorocarbons, pesticides, and trichloroacetic acid	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as scouring, sizing, desizing, solvent and greaser remover in processing and finishing of textiles	Local exhaust ventilation; general dilution; personal protective equipment
Use as general industrial solvent in rubber, textile, printing, soap, and paint remover industries	Local exhaust ventilation; general dilution; personal protective equipment
Use as extraction agent for vegetable and mineral oils and in pharmaceutical industry; as vermifuge; as laundry treatment for presoaking and as drying medium in metal and wood industries	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If tetrachloroethylene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If tetrachloroethylene gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If tetrachloroethylene soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of tetrachloroethylene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When tetrachloroethylene has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If tetrachloroethylene is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Tetrachloroethylene may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Perchloroethylene (Tetrachloroethylene)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Tetrachloroethylene (Perchloroethylene)," *Hygienic Guide Series*, Detroit, Michigan, 1965.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Hygienic Information Guide No. 54 – Tetrachloroethylene*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1973.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-24, Tetrachloroethylene*, Washington, D.C.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Tetrachloroethylene*, HEW Publication No. (NIOSH) 76-185, NTIS No. PB266583, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Reinhardt, C. F., et al.: "Epinephrine-Induced Cardiac Arrhythmia Potential of Some Common Industrial Solvents," *Journal of Occupational Medicine*, 15:953-955, 1973.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Stern, A. C. (ed.): *Air Pollution* (2nd ed.), Academic Press, New York, 1968.

• Stewart, R. D.: "Acute Tetrachloroethylene Intoxication," *Journal of the American Medical Association*, 208:1490-1492, May 26, 1969.

• Stewart, R. D., and Dodd, H. C.: "Absorption of Carbon Tetrachloride, Trichloroethylene, Tetrachloroethylene, Methylene Chloride, and 1,1,1-Trichloroethane through the Human Skin," *Industrial Hygiene Journal*, September - October:439, 1964.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

* SPECIAL NOTE

Tetrachloroethylene appears on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding its carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980). The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 20, 1979.

RESPIRATORY PROTECTION FOR TETRACHLOROETHYLENE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
500 ppm or less	Any chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
	A gas mask with a chin-style or a front- or back-mounted organic vapor canister.
	Any supplied-air respirator with a full facepiece, helmet, or hood.
	Any self-contained breathing apparatus with a full facepiece.
Greater than 500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
	A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors.
	Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Tetrachloronaphthalene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_4Cl_4$
- Synonyms: Halowax; Seekay wax; nibren wax
- Appearance and odor: Colorless to pale yellow solid with an aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tetrachloronaphthalene is 2 milligrams of tetrachloronaphthalene per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tetrachloronaphthalene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin. Every effort should be made to prevent skin, eye, oral, or inhalation contact with this material.

- **Effects of overexposure**

Exposure to tetrachloronaphthalene may cause an acne-like rash. It may also injure the liver, resulting in such effects as fatigue, dark urine, and yellow jaundice.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tetrachloronaphthalene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tetrachloronaphthalene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver and skin should be stressed.

—Liver function tests: Tetrachloronaphthalene may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Tetrachloronaphthalene vapor and dust are toxic to the liver and the skin. Rats exposed to a mixture of trichloro- and tetrachloronaphthalene at 11 mg/m^3 for 16 hours daily for 2 ½ months showed slightly swollen and over-granular liver cells. An acne-form dermatitis (chloracne) developed in workers after four months exposure to an unknown concentration of wax containing a mixture of tetra- and pentachloronaphthalene; headache, fatigue, anorexia and vertigo were also noted. Liver function tests performed on five workers who exhibited the most severe cases of dermatitis showed values within the normal ranges; the duration of exposure varied from 4 to 9 months.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 265.8
2. Boiling point (760 mm Hg): 315 - 360 C (600 - 680 F)
3. Specific gravity (water = 1): 1.59 - 1.65
4. Vapor density (air = 1 at boiling point of tetrachloronaphthalene): 9.2

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1988

September 1978

5. Melting point: 115 C (239 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Much less than 1

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving tetrachloronaphthalene.
4. Special precautions: None reported

• **Flammability**

1. Flash point: 210 C (410 F) (open cup)
2. Autoignition temperature: None to boiling point
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Foam, carbon dioxide, dry chemical

• **Warning properties**

Since there are no quantitative data relating warning properties to air concentrations of tetrachloronaphthalene, this substance is treated as a material with poor warning properties. Its concentration in saturated air at 20 C could result in a significant exposure relative to the permissible exposure.

Even though the AIHA *Hygienic Guide* states that "eye injury has not proved to be troublesome with the chloronaphthalenes," tetrachloronaphthalene is treated as an eye irritant for the purposes of this guideline. A Koppers Corporation *Material Safety Data Sheet* states that the vapors or dust may irritate the eyes.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of tetrachloronaphthalene with a filter and a bubbler containing iso-octane, followed by gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure tetrachloronaphthalene may be used. An analytical method for tetrachloronaphthalene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a compiete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with molten tetrachloronaphthalene.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid tetrachloronaphthalene or liquids containing tetrachloronaphthalene.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with tetrachloronaphthalene fumes from the heated material.

• If employees' clothing may have become contaminated with solid tetrachloronaphthalene, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with tetrachloronaphthalene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tetrachloronaphthalene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tetrachloronaphthalene, the person performing the operation should be informed of tetrachloronaphthalene's hazardous properties.

• Non-impervious clothing which becomes contaminated with molten tetrachloronaphthalene should be

removed immediately and not reworn until the tetrachloronaphthalene is removed from the clothing.

• Non-impervious clothing which becomes contaminated with solid tetrachloronaphthalene or liquids containing tetrachloronaphthalene should be removed promptly and not reworn until the tetrachloronaphthalene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of molten tetrachloronaphthalene contacting the eyes.

• Employees should be provided with and required to use splash-proof safety goggles where solid tetrachloronaphthalene or liquids containing tetrachloronaphthalene may contact the eyes.

SANITATION

• Workers subject to skin contact with tetrachloronaphthalene should wash with soap or mild detergent and water any areas of the body which may have contacted tetrachloronaphthalene at the end of each work day.

• Skin that becomes contaminated with tetrachloronaphthalene should be promptly washed or showered with soap or mild detergent and water to remove any tetrachloronaphthalene.

• Eating and smoking should not be permitted in areas where tetrachloronaphthalene is handled, processed, or stored.

• Employees who handle tetrachloronaphthalene or liquids containing tetrachloronaphthalene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tetrachloronaphthalene may occur and control methods which may be effective in each case:

Operation	Controls
Use during manufacture of electric equipment as an insulating material: pouring, dipping, and peeling	Local exhaust ventilation; general dilution with intake and exhaust fans; personal protective equipment
Liberation during use of electrical equipment insulated with tetrachloronaphthalene	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an inert compound of resins or polymers for coating or impregnating textiles, wood, and paper to impart flame resistance, water proofness, and fungicidal and insecticidal properties	Process enclosure; local exhaust ventilation; general dilution with intake and exhaust fans; personal protective equipment
Use as an additive for cutting oil in various operations performed on metals	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an additive to special lubricants such as crankcase oil, lubricants for farm machinery, and extreme-pressure lubricants	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solid tetrachloronaphthalene or liquids containing tetrachloronaphthalene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. If molten tetrachloronaphthalene gets into the eyes, immediately flush the eyes with large amounts of water to remove heat. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid tetrachloronaphthalene or liquids containing tetrachloronaphthalene get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If skin irritation persists after washing, get medical attention. If molten tetrachloronaphthalene gets on the skin or non-impervious clothing, immediately flush the affected area with large amounts of water to remove heat. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of tetrachloronaphthalene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When tetrachloronaphthalene has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with

his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If tetrachloronaphthalene is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquids containing tetrachloronaphthalene should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Tetrachloronaphthalene may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tetrachloronaphthalene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chloronaphthalenes," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• Hunter, D., and Drinker, C. K., et al.: "The Problem of Possible Systemic Effects from Certain Chlorinated Hydrocarbons," *Journal of Industrial Hygiene and Toxicology*, 19:283, 1937.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Kleinfeld, M., et al.: "Clinical Effects of Chlorinated Naphthalene Exposure," *Journal of Occupational Medicine*, 14:377-379, 1972.

• Koppers Corporation: *Material Safety Data Sheet - Tetrachloronaphthalene.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR TETRACHLORONAPHTHALENE

Condition	Minimum Respiratory Protection* Required Above 2 mg/m³
Particulate Concentration	
20 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 20 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

1439

Occupational Health Guideline for Tetraethyl Lead

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $Pb(C_2H_5)_4$
- Synonyms: TEL; lead tetraethyl; motor fuel antiknock compound
- Appearance and odor: Colorless liquid (or dyed red, orange, or blue) with a slight musty odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tetraethyl lead is 0.075 milligrams of tetraethyl lead per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended that the permissible exposure limit be changed to 0.1 mg/m^3. The American Conference of Governmental Industrial Hygienists has recommended for tetraethyl lead a Threshold Limit Value of 0.1 mg/m^3 with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tetraethyl lead can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may readily enter the body through the skin.

- **Effects of overexposure**

The absorption by humans of a sufficient quantity of tetraethyl lead either briefly at a high rate or for prolonged periods at a lower rate may cause intoxication. The onset of symptoms may be delayed for up to eight days after termination of exposure. The milder toxic effects are difficulty in sleeping, tiredness, wild dreams, anxiety, trembling, spasms, slow heart beat, low body temperature, paleness, nausea and loss of appetite. More severe intoxication causes episodes of disorientation, hallucinations, grimacing, and intense activity which requires that the person be restrained. These episodes may convert into manic or violent convulsive seizures which may end in unconsciousness or death. Tetraethyl lead may cause irritation of the eyes. Fetal damage may occur from exposure of the mother to tetraethyl lead, by analogy to methyl mercury.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tetraethyl lead.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tetraethyl lead at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of mental disorders or hypotension would be expected to be at increased risk from exposure. Examination of the central nervous system and the cardiovascular system should be stressed.

—Urinalysis: Normal kidney function is considered necessary for biologic monitoring. A urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment. The concentration of lead should be determined. Urine specimens with a specific gravity less than 1.020 should be discarded and another sampled obtained.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that the determination of lead in the urine should be repeated quarterly.

- **Summary of toxicology**

Tetraethyl lead vapor affects the nervous system and

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1401

causes mental aberrations including psychosis, mania, and convulsions. Of 41 female Swiss mice which survived for 36 weeks after a single subcutaneous injection of 0.6 mg, 5 developed malignant lymphomas during the next 15 weeks; the significance of these data cannot be evaluated, because this tumor occurs spontaneously with a variable incidence in the mouse strain used. The absorption by humans of a sufficient quantity of tetraethyl lead, either briefly at a high rate (100 mg/m³ for 1 hour) or for prolonged periods at a lower rate, causes acute intoxication; chronic intoxication has not been observed. The onset of symptoms may be delayed for up to 8 days after termination of exposure. The milder manifestations of intoxication are insomnia, lassitude, lurid dreams, dream-like waking states of anxiety, tremor, hyperreflexia, spasmodic muscular contractions, bradycardia, hypotension, hypothermia, pallor, nausea, and anorexia. More severe intoxication causes recurrent or nearly continuous episodes of disorientation, hallucinations, facial contortions, and intense hyperactivity which requires that the individual be restrained. Such episodes may convert abruptly into manic or violent convulsive seizures which may terminate in coma and death. During intoxication there is a striking elevation of the rate of excretion of lead in the urine but only a negligible or slight elevation of the concentration of lead in the blood. In severe intoxication, the urine lead is rarely less than 350 ug/l of urine, while the blood lead is rarely more than 50 ug/100 g of blood. There is also a total absence of morphological or chemical abnormalities in the erythrocytes, in sharp contrast to intoxication caused by inorganic lead. In a mortality study of 592 workers, the mean exposure time was 17.9 years, and urinary lead levels during this period did not exceed 180 ug/l; the incidence of death in this group and in a control group of employees was less than that expected in the general population, and there were no peculiarities in the specific causes of death in either group. In a similar study of a different cohort of these exposed workers, there were no significant health differences when compared with a control group. Although tetraethyl lead may be irritating to the eyes, this effect is considered insignificant when compared with the effects on the central nervous system.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 323.4
2. Boiling point (760 mm Hg): Decomposes above 100 C (212 F)
3. Specific gravity (water = 1): 1.65
4. Vapor density (air = 1 at boiling point of tetraethyl lead): 8.3
5. Melting point: −138 to −130 C (−216 to −202 F)
6. Vapor pressure at 20 C (68 F): 0.2 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Temperatures above 100 C (212 F) cause decomposition and development of pressure that may cause containers to burst.
2. Incompatibilities: Contact with strong oxidizers, such as sulfuryl chloride or potassium permangonate, may cause fires and explosions.
3. Hazardous decomposition products: Toxic airborne substances (such as lead fumes and carbon monoxide) may be released in a fire involving tetraethyl lead.
4. Special precautions: Tetraethyl lead will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 93 C (200 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of tetraethyl lead. The AIHA *Hygienic Guide* states that this substance "has a characteristic sweetish odor, but the intensity of the odor is not adequate to warn of hazardous concentrations."
2. Eye Irritation Level: Grant states that "concerning local effects on the eye from direct contact, there was recorded by Leake in 1926 a strange account of a contamination of the eyes from a splash of gasoline containing tetraethyl lead, after which the patient was said to have been unable to see for three-fourths of an hour. In the course of two months the patient was reported improved and was found to have no corneal or ophthalmoscopic abnormality, but was thought to have slight mydriasis, photophobia, and contraction of the visual field. Very likely the initial difficulty in seeing was due to smarting sensation in the eyes and blepharospasm. The evidence of later eye abnormality in this case seems quite indefinite and questionable.

"I have tested high-test gasoline containing tetraethyl lead by dropping on rabbit eyes, and have found it to cause immediate pain and blepharospasm lasting several minutes. When the application was repeated ten times in the course of five minutes under local anesthesia, it produced conjunctival hyperemia and moderate flocculent discharge, but no damage to cornea or conjunctiva."

3. Evaluation of Warning Properties: Since there is no quantitative information relating warning properties to air concentrations of tetraethyl lead, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

-1402

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

An analytical method for tetraethyl lead is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with undiluted liquid tetraethyl lead or solutions containing more than 1.06 milliliters per liter (4 milliliters per gallon).

• Clothing contaminated with undiluted liquid tetraethyl lead or solutions containing more than 1.06 milliliters per liter (4 milliliters per gallon) should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tetraethyl lead from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tetraethyl lead, the person performing the operation should be informed of tetraethyl lead's hazardous properties.

• If employees' clothing has had any possibility of being contaminated with undiluted liquid tetraethyl lead or solutions containing more than 1.06 milliliters per liter (4 milliliters per gallon), employees should change into uncontaminated clothing before leaving the work premises.

• Non-impervious clothing which becomes contaminated with undiluted liquid tetraethyl lead or solutions containing more than 1.06 milliliters per liter (4 milliliters per gallon) should be removed immediately and not reworn until the tetraethyl lead is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid tetraethyl lead may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tetraethyl lead may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during manufacture in preparation of antiknock agents for fuels	Process enclsoure; local exhaust ventilation; personal protective equipment
Liberation during formulation at petroleum refinery for use as an antiknock agent	Local exhaust ventilation; total enclosure; personal protective devices

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid tetraethyl lead or strong concentrations of tetraethyl lead vapors get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid tetraethyl lead or strong concentrations of tetraethyl lead vapors get on the skin, immediately rinse the contaminated skin with kerosene or similar petroleum products, if readily available, then wash the skin using soap or mild detergent and water. If liquid tetraethyl lead or strong concentrations of tetraethyl lead vapors penetrate through the clothing, remove the clothing immediately and first rinse the skin with kerosene or similar petroleum products, if readily available, then wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of tetraethyl lead, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical

attention as soon as possible.

• **Swallowing**

When tetraethyl lead has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If tetraethyl lead is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Tetraethyl lead may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tetraethyl Lead," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Tetraethyl Lead," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Epstein, S. S., and Mantel, N.: "Carcinogenicity of Tetraethyl Lead," *Experientia*, 24:580-581, 1968.

• Fleming, A. J.: "Industrial Hygiene and Medical Control Procedures - Manufacture and Handling of Organic Lead Compounds," *Archives of Environmental Health*, 8:266-270, 1964.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Agency for Research on Cancer: *Some Inorganic and Organo-Metallic Compounds, Vol. 2 of IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man*, Lyon, France, 1973.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1974.

• *Registry of Toxic Effects of Chemical Substances*, U.S. Department of Health, Education, and Welfare, Rockville, Maryland, June 1975.

• Robinson, T. R.: "The Health of Long Service Tetraethyl Lead Workers," *Journal of Occupational Medicine* 18:31-40, 1976.

• Robinson, T. R.: "Twenty-Year Mortality of Tetraethyl Lead Workers," *Journal of Occupational Medicine*, 16:601-605, 1974.

• Sanders, L. W.: "Tetraethyllead Intoxication," *Archives of Environmental Health*, 8:270-277, 1964.

• Stauden, A. (ex. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

1401

RESPIRATORY PROTECTION FOR TETRAETHYL LEAD

Condition	Minimum Respiratory Protection* Required Above 0.075 mg/m³
Vapor Concentration	
0.75 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
3.75 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
40 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 40 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of tetraethyl lead; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 40 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Tetrahydrofuran

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: C_4H_8O
- Synonyms: Diethylene oxide; tetramethylene oxide; THF
- Appearance and odor: Colorless liquid with an ether-like odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tetrahydrofuran is 200 parts of tetrahydrofuran per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 590 milligrams of tetrahydrofuran per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tetrahydrofuran can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to tetrahydrofuran may cause irritation of the eyes and nose, nausea, dizziness, and headache.

2. Long-term Exposure: Prolonged or repeated exposure to tetrahydrofuran may cause drying of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tetrahydrofuran.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tetrahydrofuran at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from tetrahydrofuran exposure.

—Skin disease: Tetrahydrofuran can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although tetrahydrofuran is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although tetrahydrofuran is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of tetrahydrofuran might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Tetrahydrofuran is an anesthetic agent and a mild upper respiratory tract irritant. Exposure of animals to vapor above 3000 ppm for 8 hours daily for 20 days produced irritation of the upper respiratory tract. Some injury to the liver and kidneys was observed, which was possibly due to impurities, since other studies have not confirmed this finding. Concentrations above 25,000 ppm produced anesthesia, with a small margin of safety between anesthesia and death. Severe headaches were

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1408

September 1978

noted among technicians performing this experiment. Daily 6-hour exposures of dogs for 3 to 4 weeks at 200 ppm produced only a slight change in pulse pressure, but no other signs were noted, even when continued for a total of 9 weeks followed by an additional 3 weeks' exposure at nearly 400 ppm. This substance was irritating to the skin of rabbits when applied in aqueous solutions exceeding 20% concentration, although it has not been observed to be a significant skin irritant or sensitizer in industrial practice. No chronic systemic effects have been reported in humans, although nausea, dizziness, and headaches are said to occur with overexposure and are readily reversible in fresh air.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 72
  2. Boiling point (760 mm Hg): 66 C (151 F)
  3. Specific gravity (water = 1): 0.9
  4. Vapor density (air = 1 at boiling point of tetrahydrofuran): 2.5
  5. Melting point: −108 C (−163 F)
  6. Vapor pressure at 20 C (68 F): 145 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Miscible in all proportions
  8. Evaporation rate (butyl acetate = 1): 14.5
- **Reactivity**
  1. Conditions contributing to instability: Heat and sunlight
  2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving tetrahydrofuran.
  4. Special precautions: Tetrahydrofuran will attack some forms of plastics, rubber, and coatings. Storage in the presence of air and light causes the formation of explosive peroxides that remain dissolved in tetrahydrofuran. Containers may explode when their caps or stoppers are removed.
- **Flammability**
  1. Flash point: −14.5 C (6 F) (closed cup)
  2. Autoignition temperature: 321 C (610 F)
  3. Flammable limits in air, % by volume: Lower: 2; Upper: 11.8
  4. Extinguishant: Dry chemical, alcohol foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: May and Summer both report an odor threshold for tetrahydrofuran of 30 ppm.
  2. Eye Irritation Level: Sax reports that tetrahydrofuran is an eye irritant, and Stecher, Browning, and the ILO indicate that it is a mucous membrane irritant, but the concentrations which produce irritation are not given. The *Handbook of Organic Industrial Solvents* reports that tetrahydrofuran "may cause irritation to mucuous membranes at concentrations higher than the threshold limit," but no quantitative information is available concerning the threshold of eye irritation.
  3. Other Information: "The TLV of 200 ppm is recommended to protect against irritative effects and has a wide margin of safety for narcotic and systemic effects," according to the *Documentation of TLV's*.
  4. Evaluation of Warning Properties: Since the odor threshold of tetrahydrofuran is well below the permissible exposure limit, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of tetrahydrofuran vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure tetrahydrofuran may be used. An analytical method for tetrahydrofuran is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid tetrahydrofuran.

• Clothing wet with liquid tetrahydrofuran should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tetrahydrofuran from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tetrahydrofuran, the person performing the operation should be informed of tetrahydrofuran's hazardous properties.

• Any clothing which becomes wet with liquid tetrahydrofuran should be removed immediately and not reworn until the tetrahydrofuran is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid tetrahydrofuran may contact the eyes.

SANITATION

• Skin that becomes wet with liquid tetrahydrofuran should be promptly washed or showered to remove any tetrahydrofuran.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tetrahydrofuran may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in preparation of printing inks, adhesives, lacquers, and other coatings	General dilution ventilation; personal protective equipment
Use as a Grignard reagent in synthesis of motor fuels, vitamins, hormones, pharmaceuticals, synthetic perfumes, organometallic compounds and insecticides	General dilution ventilation; process enclosure; personal protective equipment
Use as an intermediate in the preparation of various chemicals, including adipic acid, butadiene, polytetramethylene, and acrylic acid	Process enclosure; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If tetrahydrofuran gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If tetrahydrofuran gets on the skin, promptly wash the contaminated skin with water. If tetrahydrofuran soaks through the clothing, remove the clothing immediately and flush the skin with water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of tetrahydrofuran, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When tetrahydrofuran has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If tetrahydrofuran is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected, dissolved in alcohol of greater molecular weight than butyl alcohol, and atomized in a suitable combustion chamber. Tetrahydrofuran should

not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Tetrahydrofuran may be disposed of by dissolving in alcohol of greater molecular weight than butyl alcohol, and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tetrahydrofuran," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association. "Tetrahydrofuran," *Hygienic Guide Series*, Detroit, Michigan, 1959.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Quaker Oats Company: *Material Safety Data Sheet - Tetrahydrofuran*, New York, 1965.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck & Co., Inc., Rahway, New Jersey, 1968.

• Summer, W.: *Odor Pollution of Air: Causes and Control*, L. Hill, London, 1975.

RESPIRATORY PROTECTION FOR TETRAHYDROFURAN

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style organic vapor canister.
10,000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
20,000 ppm or less	A powered air-purifying respirator with a full facepiece and organic vapor cartridge(s). A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 20,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Tetramethyl Lead

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $Pb(CH_3)_4$
- Synonyms: TML; lead tetramethyl; motor fuel antiknock compound
- Appearance and odor: Colorless liquid (or dyed red, orange, or blue) with a slight musty odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tetramethyl lead is 0.075 milligram of tetramethyl lead per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for tetramethyl lead a Threshold Limit Value of 0.150 mg/m^3 with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tetramethyl lead can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Although there have been no reports of human intoxication from tetramethyl lead exposure, animal experiments suggest that tetramethyl lead may cause toxic effects similiar to those produced by tetraethyl lead. Tetraethyl lead exposure effects range from difficulty in sleeping, bad dreams, restlessness, anxiety, nausea, and poor appetite to the more severe symptoms of acute mental disturbance characterized by delirium, violent behavior, convulsive seizures, unconsciousness, and death. Fetal damage may occur from exposure of the mother to tetramethyl lead by analogy to methyl mercury.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tetramethyl lead.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tetramethyl lead at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of mental disorders or hypotension would be expected to be at increased risk from exposure. Examination of the central nervous system and the cardiovascular system should be stressed.

—Urinalysis: Normal kidney function is considered necessary for biologic monitoring. A urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment. The concentration of lead should be determined. Urine specimens with a specific gravity of less than 1.020 should be discarded and another sample obtained.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that the determination of the concentration of lead in the urine should be repeated quarterly.

- **Summary of toxicology**

Tetramethyl lead affects the central nervous system in animals and causes signs of increased irritability. Oral administration of 108 mg/kg to rats caused some deaths; effects were tremors, marked hyperactivity, and convulsions. Tetramethyl lead intoxication in animals resembles that caused by tetraethyl lead (TEL), a close

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1411

homolog; human intoxication from tetramethyl lead has not been described. A description of human intoxication by TEL is given because of the severity of the effects and the likelihood that intoxication by tetramethyl lead would be similar. TEL effects range from insomnia, bad dreams, restlessness, anxiety, hypotension, nausea, and anorexia to the more severe symptoms of acute mental disturbances characterized by delirium, mania, convulsive seizures, and coma, sometimes followed by death.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 257.3
  2. Boiling point (760 mm Hg): 110 C (230 F)
  3. Specific gravity (water = 1): 1.99
  4. Vapor density (air = 1 at boiling point of tetramethyl lead): 6.5
  5. Melting point: −30 C (−22 F)
  6. Vapor pressure at 20 C (68 F): 22 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Temperatures above 100 C (212 F) cause decomposition and development of pressure that may cause containers to burst.
  2. Incompatibilities: Contact with strong oxidizers, such as sulfuryl chloride or potassium permangonate, may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as lead fumes and carbon monoxide) may be released in a fire involving tetramethyl lead.
  4. Special precautions: Tetramethyl lead will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 38 C (100 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Dry chemical, foam, carbon dioxide
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold of tetramethyl lead.
  2. Eye Irritation Level: Tetramethyl lead is not known to be an eye irritant.
  3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of tetramethyl lead, this substance is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for tetramethyl lead is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with undiluted liquid tetramethyl lead or solutions containing more than 1.06 milliliters per liter (4 milliliters per gallon).
- Clothing contaminated with undiluted liquid tetramethyl lead or solutions containing more than 1.06 milliliters liter (4 milliliters per gallon) of tetramethyl lead should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tetramethyl lead from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tetramethyl lead, the person performing the operation should be informed of tetramethyl lead's hazardous properties.
- Where there is any possibility of exposure of an

employee's body to undiluted liquid tetramethyl lead or solutiocontaining more than 1.06 milliliters per liter (4 milliliters per gallon) of tetramethyl lead, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with undiluted liquid tetramethyl lead or solutions containing more than 1.06 milliliters per liter (4 milliliters per gallon) of tetramethyl lead should be removed immediately and not reworn until the tetramethyl lead is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid tetramethyl lead may contact the eyes.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tetramethyl lead may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during manufacture in preparation of antiknock fluids	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during formulation at petroleum refinery for use as an antiknock fluid; mixed lead alkyls; as substitutes, in whole or in part, for tetraethyl lead in engine gasoline	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid tetramethyl lead or strong concentrations of tetramethyl lead vapors get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid tetramethyl lead or strong concentrations of tetramethyl lead vapors get on the skin, immediately rinse the contaminated skin with kerosene or similar petroleum products, if readily available, then wash the skin using soap or mild detergent and water. If liquid tetramethyl lead or strong concentrations of tetramethyl lead vapors penetrate through the clothing, remove the clothing immediately and first rinse the skin with kerosene or similar petroleum products, if readily available, then wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of tetramethyl lead, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When tetramethyl lead has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If tetramethyl lead is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Tetramethyl lead should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of tetramethyl lead vapors are permitted.

• Waste disposal method:

Tetramethyl lead may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tetramethyl Lead," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Tetramethyl Lead," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Baskin, A. D. (ed.): *Handling Guide for Potentially Hazardous Commodities*, Railway Systems and Management Association, Chicago, 1972.

• Castellino, N., et al., "Toxicity of Tetramethyl Lead Solutions to Mice and Rabbits," *British Journal of Industrial Medicine*, 20:63-65, 1963.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1974.

• *Registry of Toxic Effects of Chemical Substances*, U.S. Department of Health, Education, and Welfare, Rockville, Maryland, June 1975.

• Schepers, G. W. H.: "Tetraethyllead and Tetramethyllead - Comparative Experimental Pathology: Part I. Lead Absorption and Pathology," *Archives of Environmental Health*, 8:277-295, 1964.

• Stauden, A. (ex. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• deTreville, R. T. P., et al.: "Occupational Exposure to Organic Lead Compounds - The Relative Degree of Hazardin Occupational Exposure to Air-Borne Tetraethyllead and Tetramethyllead," *Archives of Environmental Health*, 5:532-536, 1962.

-1111

RESPIRATORY PROTECTION FOR TETRAMETHYL LEAD

Condition	Minimum Respiratory Protection* Required Above 0.075 mg/m³
Vapor Concentration	
0.7 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
3.5 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
40 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 40 mg/m³** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of tetramethyl lead; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 40 mg/m³, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for Tetranitromethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C(NO_2)_4$
- Synonyms: Tetan
- Appearance and odor: Colorless to pale yellow liquid or solid. The vapor has a pungent odor and causes tears.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tetranitromethane is 1 part of tetranitromethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 8 milligrams of tetranitromethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tetranitromethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Exposure to tetranitromethane may cause irritation of the eyes, upper respiratory tract and skin. It may also cause headaches, fatigue, and drowsiness. After prolonged exposure, the central nervous system and heart may be affected and difficult breathing may occur. Tetranitromethane has been reported to affect the ability of the blood to carry oxygen. This may result in a bluish discoloration of the skin, headache, weakness, irritability, drowsiness, shortness of breath, and unconsciousness.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tetranitromethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tetranitromethane at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory tract, eyes, blood, central nervous system, and liver should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Tetranitromethane causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Tetranitromethane is a respiratory irritant. Persons with impaired pulmonary function may be at increased risk from exposure. Periodic surveillance is indicated.

—A complete blood count: Tetranitromethane has been shown to cause methemoglobinemia in humans. Persons with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematrocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is necessary only when indicated by the results of pulmonary function testing, or when signs and symptoms of respiratory disease occur. Methemoglobin determinations should be performed if overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

Tetranitromethane vapor is a severe irritant of the eyes and respiratory tract. The LC50 for rats was 1230 ppm

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

for 36 minutes; effects were lacrimation, rhinorrhea, gasping, and cyanosis; pulmonary edema was present at autopsy. Repeated exposure to 3.65 ppm for 6 months caused the death of 60% of the rats; at autopsy there were signs of lung infection following acute pneumonitis. In three species of animals, intravenous injection caused methemoglobinemia, anemia, damage to the central nervous system, and edema of the lungs and liver. In workers, various studies showed that exposure caused irritation of the eyes, nose, and throat; dizziness, headache; chest pain, dyspnea; and occasionally skin irritation. Methemoglobinemia is stated to be a systemic effect from human exposure; symptoms result from anoxia and include cyanosis, evident especially in the lips, nose, and earlobes; other effects are weakness, dizziness, and severe headache. Concentrations in excess of 1 ppm will cause lacrimation and upper respiratory irritation, while 0.4 ppm may cause mild irritation. The liquid on the skin may cause mild burns.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 196
2. Boiling point (760 mm Hg): 126 C (259 F)
3. Specific gravity (water = 1): 1.64
4. Vapor density (air = 1 at boiling point of tetranitromethane): 6.8
5. Melting point: 14 C (57 F)
6. Vapor pressure at 20 C (68 F): 8.4 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Combustible organic matter wet with tetranitromethane may be highly explosive and susceptible to initiation by rather mild shocks.
2. Incompatibilities: Contact with hydrocarbons, alkalies, and metals may form explosive mixtures.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving tetranitromethane or when tetranitromethane decomposes.
4. Special precautions: Tetranitromethane will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Not combustible by itself, but is considered by some to be a weak explosive.

- **Warning properties**

1. Odor Threshold: Patty states that "tetranitromethane can be recognized by its characteristic acrid biting odor." No quantitative information is available, however, concerning its odor threshold.
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "the irritant property of tetranitromethane may serve as an index to the degree of exposure which can be tolerated, because concentrations in excess of 1 ppm will cause lacrimation and upper respiratory irritation. Concentrations as low as 0.4 ppm may cause mild irritation." Grant states that "the vapors of tetranitromethane are very irritating to the eyes, nose, and respiratory passages. It has been proposed for use as an irritant war gas. Animals are said to show evidence of irritation of the eyes rather quickly at concentrations from 3.3 to 25.2 ppm in air."
3. Evaluation of Warning Properties: Through its irritant effects, tetranitromethane can be detected below the permissible exposure limit. For the purposes of this guideline, therefore, tetranitromethane is treated as a material with good warning properties. It is a strong oxidizer.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by drawing tetranitromethane through ethyl acetate with subsequent gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure tetranitromethane may be used. An analytical method for tetranitromethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with solid or liquid tetranitromethane where skin contact may occur.

• Clothing which may have become contaminated with tetranitromethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tetranitromethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tetranitromethane, the person performing the operation should be informed of tetranitromethane's hazardous properties.

• Non-impervious clothing which becomes contaminated with tetranitromethane should be removed promptly and any clothing which becomes wet with liquid tetranitromethane should be removed immediately and not reworn until the tetranitromethane is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solid or liquid tetranitromethane contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solid or liquid tetranitromethane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with tetranitromethane should be promptly washed or showered with soap or mild detergent and water to remove any tetranitromethane.

• Eating and smoking should not be permitted in areas where tetranitromethane is handled, processed, or stored.

• Employees who handle solid or liquid tetranitromethane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tetranitromethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as an ingredient in manufacture of liquid explosives; use as an octane number improver in diesel fuels	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a laboratory analytical reagent as a nitrating agent; use in research in rocket propellants	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If solid or liquid tetranitromethane or strong concentrations of tetranitromethane vapors get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention promptly. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If solid or liquid tetranitromethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If solid or liquid tetranitromethane or penetrates through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of tetranitromethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When solid or liquid tetranitromethane have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If tetranitromethane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material. Avoid shock and friction if liquid spills on combustible matter such as wood and paper.

• Waste disposal method:

Liquid tetranitromethane may be disposed of by absorbing in vermiculite, dry sand, earth, or a similar material and disposing in a secured sanitary landfill. Solid tetranitromethane may be collected in the most convenient manner and disposed of in a secured sanitary landfill. Care should be taken when disposing, since tetranitromethane is a weak explosive.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tetranitromethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Tetranitromethane," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hager, K. F.: "Tetranitromethane," *Industrial and Engineering Chemistry*, 41:2168-2172, 1949.

• Horn, H. J.: "Inhalation Toxicology of Tetranitromethane," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 10:213-222, 1954.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 14:148-153, 1956.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

-113

RESPIRATORY PROTECTION FOR TETRANITROMETHANE

Condition	Minimum Respiratory Protection* Required Above 1 ppm
Vapor Concentration	
5 ppm or less	Any chemical cartridge respirator with a full facepiece and a cartridge containing non-combustible sorbents and providing protection against tetranitromethane. A gas mask with a chin-style or a front- or back-mounted canister containing non-combustible sorbents and providing protection against tetranitromethane. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A gas mask containing non-combustible sorbents and providing protection against tetranitromethane. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Tetryl

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(NO_2)_3C_6H_2N(NO_2)CH_3$
- Synonyms: 2,4,6-trinitrophenylmethylnitramine; N-methyl-N,2,4,6-tetranitroaniline; nitramine; tetralite
- Appearance and odor: Colorless to yellow, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tetryl is 1.5 milligrams of tetryl per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tetryl can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to tetryl may cause irritation of the eyes, nose, and throat. It may stain the skin and hair yellow. It may cause an allergic skin rash. Several days' exposure to high concentrations may cause headaches and nose bleeding. Occasionally, coughing and choking occur. Severe prolonged exposure may cause insomnia, nausea, vomiting, irritability, and anemia. In animals, it has caused liver and kidney damage, and severe breathing difficulties which may be delayed in onset.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tetryl.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tetryl at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to tetryl may be at increased risk from exposure. Examination of the respiratory tract, eyes, liver, central nervous system, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Tetryl has been shown to cause anemia in humans. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Tetryl dust causes severe sensitization dermatitis and irritation of the upper respiratory tract. Dogs injected subcutaneously with fatal doses showed degeneration of renal tubules, liver necrosis, and occasional pulmonary edema. Dermatitis in workers appears as early as the first week of exposure to the dust with itching of the eyes; there is a progression to erythema and edema occurring most often on the nasal folds, cheeks, and neck; papules and vesicles may develop; the remainder of the body is rarely affected. The severest forms show massive generalized edema with partial obstruction of the trachea due to swelling of the tongue and require

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1121

hospitalization; exfoliation usually occurs after the edema subsides. The majority of these effects occur between the 10th and 20th days of exposure; upon cessation of exposure there is rapid abatement of the mild symptoms, and after 3 to 10 days disappearance of physical signs. Contact with tetryl causes a bright yellow staining, most often seen on the palms, face, neck, and in the hair. The irritant effects on the upper respiratory tract range from the nares to the bronchi and cause burning, itching, sneezing, coryza, epistaxis, and cough; the symptoms may begin the first day of exposure or as late as the third month; upon removal from exposure the symptoms regress over 2 to 4 weeks. Other effects reported in tetryl workers are irritability, easy fatigability, malaise, headache, lassitude, insomnia, nausea, and vomiting. Anemia, either of the marrow depression or deficiency type, has been observed among tetryl workers. Conjunctivitis may be caused by rubbing the eyes with contaminated hands or by airborne dust; keratitis and iridocyclitis have occurred.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 287
2. Boiling point (760 mm Hg): 187 C (369 F) (explodes)
3. Specific gravity (water = 1): 1.6 – 1.7
4. Vapor density (air = 1 at boiling point of tetryl): Not applicable
5. Melting point: 129 C (264 F)
6. Vapor pressure at 20 C (68 F): Much less than 1
7. Solubility in water, g/100 g water at 20 C (68 F): 0.02
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Heat and shock
2. Incompatibilities: Contact of tetryl with some oxidizable materials may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving tetryl.
4. Special precautions: Protect from shock

- **Flammability**

1. Flash point: Explodes
2. Flammable limits in air, % by volume: Not applicable
3. Impact sensitivity (minimum fall of a 2 kg weight to cause at least one explosion in ten trials): 26 cm
4. Explosion temperature (temperature required to cause explosion in five seconds): 257 C (495 F)
5. Extinguishant: Water may be used on small fires. Do not attempt to extinguish large fires.

- **Warning properties**

Concerning the effects of tetryl on the eye, Grant states that "conjunctivitis may be caused by rubbing the eyes with contaminated hands, but more commonly airborne dust is responsible. Conjunctivitis is usually accompanied by dermatitis of the face, but may persist considerably longer than the skin rash. Keratitis and iridocyclitis are also said to have occurred in association with the conjunctivitis." No quantitative information is available concerning what concentrations in air produce the conjunctivitis, however.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of tetryl on a cellulose membrane filter with subsequent extraction with N,N-diethylethanolamine and spectrophotometric analysis. An analytical method for tetryl is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing

necessary to prevent repeated or prolonged skin contact with tetryl or liquids containing tetryl.

- If employees' clothing may have become contaminated with tetryl, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with tetryl should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tetryl from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tetryl, the person performing the operation should be informed of tetryl's hazardous properties.
- Non-impervious clothing which becomes contaminated with tetryl should be removed promptly and not reworn until the tetryl is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where tetryl or liquids containing tetryl may contact the eyes.

SANITATION

- Workers subject to skin contact with tetryl should wash any areas of the body which may have contacted tetryl at the end of each work day.
- Skin that becomes contaminated with tetryl should be promptly washed or showered with soap or mild detergent and water to remove any tetryl.
- Eating and smoking should not be permitted in areas where tetryl is handled, processed, or stored.
- Employees who handle tetryl or liquids containing tetryl should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tetryl may occur and control methods which may be effective in each case:

Operation	Controls
Use in the manufacture of explosives for use in blasting caps, boosters in high explosive shells, aircraft cannons, shells, and as a primer for less sensitive explosives; use during the formulation of binary explosives	Process enclosure; local exhaust ventilation; personal protective equipment
Use as a pH indicator	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If tetryl or liquids containing tetryl get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If tetryl or liquids containing tetryl get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If tetryl or liquids containing tetryl penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. Get medical attention promptly.

- **Breathing**

If a person breathes in large amounts of tetryl, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When tetryl or liquids containing tetryl have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If tetryl is spilled, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill.
3. Attempt to reclaim spilled material; however, do not sweep or burn unless this is supervised by explosives experts.

- Waste disposal method:

Tetryl may be disposed of only by explosives experts.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tetryl," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Bergman, B. B.: "Tetryl Toxicity: A Summary of Ten Years' Experience," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 5:10-20, 1952.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hardy, H. L., and Maloof, C. C.: "Evidence of Systemic Effect of Tetryl, With Summary of Available Literature," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 1:545-555, 1950.

• Hilton, J., and Swanston, C. N.: "Clinical Manifestations of Tetryl and Trinitrotoluene," *British Medical Journal*, 2:509-510, 1941.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, Vol. 2, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L.: "Dermatitis from Explosives," *Journal of the American Medical Association*, 125:186-190, 1944.

• Troup, H. B.: "Clinical Effects of Tetryl (CE Powder)," *British Journal of Industrial Medicine*, 3:20-21, 23, 1946.

• von Oettingen, W. F.: *The Aromatic Amino and Nitro Compounds. Their Toxicity and Potential Dangers. A Review of the Literature*, Public Health Bulletin No. 271, U.S. Public Health Service, U.S. Government Printing Office, Washington, D.C., 1941.

-1421

RESPIRATORY PROTECTION FOR TETRYL

Condition	Minimum Respiratory Protection* Required Above 1.5 mg/m³
Particulate Concentration	
7.5 mg/m³ or less	Any dust and mist respirator, except single-use.**
15 mg/m³ or less	Any dust and mist respirator, except single-use respirator or quarter mask.** Any fume respirator or high efficiency particulate filter respirator.** Any supplied-air respirator.** Any self-contained breathing apparatus.**
75 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1500 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter.
3000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 3000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Soluble Thallium Compounds

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all soluble thallium compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

• Names and Formulas: 1) Thallium sulfate: Tl_2SO_4; 2) Thallium acetate: $TlC_2H_3O_2$; 3) Thallium nitrate: $TlNO_3$

• Appearance and odor: Thallium sulfate, thallium acetate, and thallium nitrate are all colorless, odorless solids.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for soluble thallium compounds is 0.1 milligram of soluble thallium compounds per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

• **Routes of exposure**

Soluble thallium compounds can affect the body if they are inhaled or if they come in contact with the eyes or skin, or if they are swallowed. They may enter the body thorugh the skin.

• **Effects of overexposure**

Soluble thallium compounds are very toxic and cause cumulative intoxication. Many deaths have resulted from swallowing these compounds. Poisoning from industrial exposure has been rarely reported — those that have, were not fatal. Swallowing soluble thallium compounds may cause nausea, vomiting, diarrhea, abdominal pain, and bleeding from the gut. These symptoms are followed or accompanied by drooping of the eyelids, crossed eyes, weakness, numbness, and tingling of the arms and legs, trembling, and pain and tightness of the chest. The hair may fall out after two to three weeks. Severe intoxication may result in prostration, rapid heartbeat, convulsions, and psychosis. Recovery may be complete but permanent effects such as staggering, visual difficulties, trembling, and mental abnormalities have been reported. Liver and kidney damage have occurred. Repeated exposure over a prolonged period may produce variable symptoms. These may include loss of hair, soreness of the mouth, trembling, severe weight loss, and emotional disturbance.

• **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to soluble thallium compounds.

• **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to soluble thallium compounds at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes, nervous system, lungs, liver, kidneys, gastrointestinal tract, and body hair should be stressed.

—Urinalysis: Since kidney damage has been observed in humans exposed to thallium, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

L. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1408

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

Soluble thallium compounds are extremely toxic and cause a cumulative intoxication affecting primarily the nervous system and the body hair. Many deaths have resulted from ingestion. The lethal oral dose of thallium acetate for humans is estimated to be about 12 mg/kg body weight. Ingestion causes nausea, vomiting, diarrhea, abdominal pain and gastrointestinal hemorrhage, which usually occur within 1 to 3 days. These are followed or accompanied by ptosis, strabismus; peripheral neuritis, pain, weakness, and paresthesias in the legs, tremor; retrosternal tightness and chest pain. Severe alopecia usually occurs after 2 to 3 weeks and is pathognomonic of the toxic effects of thallium. Severe intoxication may result in prostration, tachycardia, blood pressure fluctuations, convulsive seizures, choreaform movements, and psychosis. Recovery may be complete, but permanent residual effects such as ataxia, optic atrophy, tremor, mental abnormalities, and footdrop have been reported. In cases of fatal intoxication, typical autopsy findings include pulmonary edema, necrosis of the liver, nephritis, and degenerative changes in peripheral axons. Prolonged ingestion of thallium produces a variable clinical picture which includes stomatitis, tremor, cachexia, polyneuropathy, alopecia, and emotional disturbance. In a study of 15 workers who had handled solutions of organic thallium salts over a 7.5-year period, 6 workers suffered thallium intoxication; chief complaints were abdominal pain, fatigue, weight loss, pain in the legs, and nervous irritability; 3 of the workers had albuminuria and 1 had hematuria.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data**

These data correspond to the the three substances identified above.

1. Molecular weight: 1) 504.81; 2) 263.41; 3) 266.4
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1) 6.8; 2) 3.7; 3) 5.5
4. Vapor density (air = 1 at boiling point of soluble thallium compounds): Not applicable
5. Melting point: 1) 632 C (1170 F); 2) 110 C (230 F); 3) 206 C (403 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 1) 4.87; 2) Very soluble; 3) 10
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None.
2. Incompatibilities: None.
3. Hazardous decomposition products: None.
4. Special precautions: None.

• **Flammability**

1. Flash point: Data not available
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Water, carbon dioxide, foam, dry chemical

• **Warning properties**

Grant describes some effects on the eye produced by systemic thallium poisoning. In addition, Grant states that "experiments concerned with the local effects of thallium on the eye suggest that contact of thallium salts with the eye, such as by accidental splash contamination, is unlikely to cause serious damage, especially if promptly washed away with water. Experimentally, a rather drastic exposure of a rabbit eye for ten minutes to a neutral saturated solution of thallium chloride, with the epithelium preliminarily removed to facilitate penetration, caused moderate edema and haze in the cornea, which gradually cleared from the periphery but left a nebulous area axially. Splash contact with intact epithelium presumably would be even less damaging."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection on a filter with a subsequent atomic absorption spectrophotometric analysis. An analytical method for soluble thallium compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted

are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with soluble thallium compounds where skin contact may occur.

• If employees' clothing may have become contaminated with soluble thallium compounds, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with soluble thallium compounds should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of soluble thallium compounds from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the soluble thallium compounds, the person performing the operation should be informed of soluble thallium compounds's hazardous properties.

• Non-impervious clothing which becomes contaminated with soluble thallium compounds should be removed promptly and not reworn until the soluble thallium compounds are removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where soluble thallium compounds may contact the eyes.

SANITATION

• Skin that becomes contaminated with soluble thallium compounds should be promptly washed or showered to remove any soluble thallium compounds.

• Eating and smoking should not be permitted in areas where soluble thallium compounds are handled, processed, or stored.

• Employees who handle soluble thallium compounds should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to soluble thallium compounds may occur and control methods which may be effective in each case:

Operation	Controls
Use in laboratory for analytical and research purposes	Local exhaust ventilation; personal protective equipment
Use in manufacture of special lenses, plates and prisms, medicinals, pyrotechnic products, and fuel additives for internal combustion engines	Local exhaust ventilation; personal protective equipment
Manufacture of soluble thallium compounds and application as a rodenticidal agent	Local exhaust ventilation; personal protective equipment; product substitution

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If soluble thallium compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If soluble thallium compounds get on the skin, promptly flush the contaminated skin with water. If soluble thallium compounds penetrate through the clothing, remove the clothing promptly and flush the skin with water. Get medical attention.

• **Breathing**

If a person breathes in large amounts of soluble thallium compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When soluble thallium compounds have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If soluble thallium compounds are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in a sealed container for disposal. Large quantities may be reclaimed; however, if this is not practical, collect spilled material in the most convenient and safe manner and deposit in sealed containers for disposal.
3. Liquids containing soluble thallium compounds may be absorbed in vermiculite, dry sand, earth, or a similar material and deposited in sealed containers for disposal.

• Waste disposal method

Soluble thallium compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Thallium," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Bank, W. J., et al.: "Thallium Poisoning," *Archives of Neurology* 26:456-464, 1972.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Paulson, G., et al.: "Thallium Intoxication Treated with Dithizone and Hemodialysis," *Archives of Internal Medicine*, 129:100-103, 1972.

• Richeson, E. M.: "Industrial Thallium Intoxication," *Industrial Medicine and Surgery*, 27:607-619, 1958.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR SOLUBLE THALLIUM COMPOUNDS

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Dust or Mist Concentration	
0.5 mg/m³ or less	Any dust and mist respirator, except single-use.
1 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator.
Dust, Mist, or Fume Concentration	
1 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
20 mg/m³ or less	A powered air-purifying respirator with a full facepiece, helmet, or hood, and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 20 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Thiram

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_{12}N_2S_4$
- Synonyms: Tetramethylthiuram disulfide
- Appearance: Colorless to cream solid (some commercial products are dyed blue).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for thiram is 5 milligrams of thiram per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Thiram can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

Thiram can cause irritation of the eyes, nose, throat, and skin. It may cause an allergic skin rash. Thiram is thought to have similar effects as antabuse which include nausea, vomiting, diarrhea, and loss of appetite. After ingestion of alcohol, individuals taking antabuse may experience skin redness, hives, itching, pulsating headache, flushing, sweating, nausea, vomiting, diarrhea, weakness, dizziness, and difficulty in breathing. Thiram has caused birth defects in offspring of animals given large doses of thiram by mouth.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to thiram.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to thiram at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from thiram exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of thiram might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Thiram is a skin sensitizer. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Thiram (tetramethylthiuram disulfide) dust irritates the respiratory tract, eyes, and skin, and causes sensitization dermatitis. Thiram was teratogenic (skeletal malformations) in hamsters given a single oral dose of 250 mg/kg during the period of organogenesis and in mice given oral doses of 5 to 30 mg/animal daily between days 6 and 17 of pregnancy. In exposed humans, sensitization dermatitis in the form of eczema has occurred on the hands, forearms, and feet. Thiram is thought to have similar toxic effects to antabuse, which include nausea, vomiting, diarrhea, and loss of appetite. Ingestion of ethanol by persons taking antabuse has caused a severe reaction characterized by a rapid skin response of a non-allergic nature, flushing, erythema, pruritis, urticaria, headache, nausea, vomiting, diarrhea, weakness, dizziness, and difficult breathing.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 240
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): 1.40
  4. Vapor density (air = 1 at boiling point of thiram): Not applicable
  5. Melting point: 140 C (284 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids or oxidizable materials may cause formation of toxic gases such as hydrogen sulfide.
  3. Hazardous decomposition products: Toxic gases and vapors (such as sulfur dioxide, carbon disulfide, and carbon monoxide) may be released in a fire involving thiram.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 89 C (192 F) (closed cup)
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Carbon dioxide, foam, dry chemical
- **Warning properties**

Warning properties are not considered since the vapor pressure is negligible.

Grant states that "as a dust or spray it is irritating to the eyes . . . ." No quantitative information is available concerning the eye irritation threshold, however.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of thiram on a membrane filter with subsequent chemical treatment and spectrophotometric analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure thiram may be used. An analytical method for thiram is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with thiram or liquids containing thiram, where skin contact may occur.
- If employees' clothing may have become contaminated with solid thiram, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with thiram should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of thiram from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the thiram, the person performing the operation should be informed of thiram's hazardous properties.
- Non-impervious clothing which becomes contaminated with thiram should be removed promptly and not reworn until the thiram is removed from the clothing.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where thiram or liquids containing thiram may contact the eyes.

SANITATION

- Skin that becomes contaminated with thiram should be promptly washed or showered with soap or mild detergent and water to remove any thiram.
- Eating and smoking should not be permitted in areas where thiram is handled, processed, or stored.

• Employees who handle thiram or liquids containing thiram should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to thiram may occur and control methods which may be effective in each case:

Operation	Controls
Use in rubber industry as an accelerator, peptizing agent, and vulcanizing agent	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during application as an agricultural fungicide as foliage spray for plants and trees, fruits and seeds	Handle mechanically; personal protective equipment
Use as a bacteri[illegible]t in commercial and [illegible]ical soap, antiseptics, sunburn oils and fats	Process enclosure; local exhaust ventilation; personal protective equipment
Liberation during use as an animal repellant on plants or trees	Handle mechanically; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If thiram or liquids containing thiram get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If thiram or liquids containing thiram get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If thiram or liquids containing thiram penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Swallowing**

When thiram or liquids containing thiram have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If thiram is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Thiram may be disposed of:

1. By making packages of thiram in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving thiram in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Thiram (Tetramethyl Thiuram Disulfide)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Council on Pharmacy and Chemistry: "A.M.A. Outlines of Information on Pesticides, Part I – Agricultural Fungicides," *Journal of the American Medical Association*, 157:237-239 1955.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products*(3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Robens, J. F.: "Teratologic Studies of Carbaryl, Diazinon, Norea, Disulfiram, and Thiram in Small Laboratory Animals," *Toxicology and Applied Pharmacology*, 15:152-163, 1969.

• Roll, R.: "Teratologische Untersuchungen mit

Thiram (TMTD) an zwei Mausestammen," *Archiv fur Toxikologie*, 27:173-186, 1971.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Shelley, W. B.: "Golf-Course Dermatitis Due to Thiram Fungicide," *Journal of the American Medical Association*, 188:415-417, 1964.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR THIRAM

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
50 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus. Any pesticide chemical cartridge respirator.
250 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. Any pesticide chin-style cartridge respirator with a full facepiece. A chin-style or a front- or back-mounted pesticide gas mask.
1500 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode. A powered air-purifying pesticide respirator with a full facepiece, helmet, or hood.
Greater than 1500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Inorganic Tin Compounds (as Tin)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all inorganic tin compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Tin

- Formula: Sn
- Synonyms: Tin, metallic
- Appearance and odor: Odorless, dull silvery metal.

Stannous chloride

- Formula: $SnCl_2$
- Synonyms: Tin(II) chloride; tin dichloride
- Appearance and odor: Odorless, colorless to brown solid.

Stannic chloride

- Formula: $SnCl_4$
- Synonyms: Tin(IV) chloride; tin tetrachloride
- Appearance and odor: Colorless to yellow fuming liquid with an acrid odor.

Stannous sulfate

- Formula: $SnSO_4$
- Synonyms: Tin(II) sulfate
- Appearance and odor: Odorless, colorless to brown solid.

Potassium stannate

- Formula: $K_2SnO_3H_2O$
- Synonyms: Potassium stannate trihydrate
- Appearance and odor: Odorless, colorless to brown solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for inorganic tin compounds (as tin) is 2 milligrams of inorganic tin compounds (as tin) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tin, stannous chloride, stannic chloride, stannous sulfate, or potassium stannate can affect the body if they are inhaled or if they come in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: In general, the toxicity of inorganic tin salts is low. These compounds may cause irritation of the eyes, nose, throat, and skin.

2. Long-term Exposure: None known

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to inorganic tin compounds.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to inorganic tin compounds at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from inorganic tin compounds exposure.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1405

—Skin disease: Certain inorganic tin compounds other than oxides are primary skin irritants. Persons with pre-existing skin disorders may be more susceptible to the effects of these agents.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of certain inorganic tin compounds might cause exacerbation of symptoms due to their irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

• **Summary of toxicology**

Inorganic tin compounds (except the oxides) irritate the eyes and skin. Subcutaneous injection of animals with sodium stannous tartrate at a daily dose of 12.5 mg/kg was fatal; death was preceeded by vomiting, diarrhea, and paralysis with twitching of the limbs. Daily administration to a dog of stannous chloride in milk at a level of 500 mg/kg produced paralysis after 14 months. Some inorganic tin compounds can cause skin or eye irritation because of acid or alkaline reaction produced with water; tin tetrachloride, stannous chloride, and stannous sulfate are strong acids; sodium and potassium stannate are strong alkalis.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Tin**

1. Molecular weight: 118.7
2. Boiling point (760 mm Hg): 2689 C (4873 F)
3. Specific gravity (water = 1): 5.8 to 7.3
4. Vapor density (air = 1 at boiling point of tin): Not applicable
5. Melting point: 232 C (450 F)
6. Vapor pressure at 20 C (68 F): Zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Stannous chloride**

1. Molecular weight: 189.6
2. Boiling point (760 mm Hg): 605 C (1121 F)
3. Specific gravity (water = 1): 3.95
4. Vapor density (air = 1 at boiling point of stannous chloride): Not applicable
5. Melting point: 247 C (477 F)
6. Vapor pressure at 20 C (68 F): Zero
7. Solubility in water, g/100 g water at 20 C (68 F): 90
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Stannic chloride**

1. Molecular weight: 260.5
2. Boiling point (760 mm Hg): 114 C (237 F)
3. Specific gravity (water = 1): 2.23
4. Vapor density (air = 1 at boiling point of stannic chloride): 9
5. Melting point: −33 C (−27 F)
6. Vapor pressure at 20 C (68 F): 18 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Stannous sulfate**

1. Molecular weight: 214.8
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): Data not available (greater than 1)
4. Vapor density (air = 1 at boiling point of stannous sulfate): Not applicable
5. Melting point: 300 C (572 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Zero
7. Solubility in water, g/100 g water at 20 C (68 F): 33
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Potassium stannate**

1. Molecular weight: 298.9
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 3.2
4. Vapor density (air = 1 at boiling point of potassium stannate): Not applicable
5. Melting point: 140 C (284 F) (decomposes)
6. Vapor pressure at 20 C (68 F): Zero
7. Solubility in water, g/100 g water at 20 C (68 F): 110
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: If moisture enters containers of stannic chloride, pressure may burst containers. At temperatures above 360 C (680 F), stannous sulfate decomposes to form toxic sulfur dioxide.

2. Incompatibilities: Contact of metallic tin with chlorine may cause adjacent combustible material to ignite. Contact of metallic tin with turpentine may cause fires and explosions. Contact of stannic chloride with water, alcohols, and amines may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors may be released in a fire involving the tin chlorides and stannous sulfate.

4. Special precautions: Stannic chloride will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: Not applicable
2. Minimum ignition temperature: a) Tin: 630 C (1166 F) (cloud); 430 C (806 F) (layer); For the other compounds: Not applicable
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: For tin, water; for the other compounds, not applicable.

• **Warning properties**

Acco ng to Grant, tin tetrachloride (stannic chloride) is "highly irritating to the eyes and mucous membranes.

The irritation presumably is attributable to the hydrochloric acid which is generated when stannic chloride reacts with water." The threshold of eye irritation is not given.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection on a cellulose membrane filter followed by treatment with nitric and sulfuric acids, solution in hydrochloric acid, and analysis with an atomic absorption spectrophotometer. An analytical method for inorganic tin compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid stannic chloride.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with stannous sulfate, potassium stannate, or liquids containing these compounds, where skin contact may occur.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with stannous chloride or liquids containing stannous chloride.

• If employees' clothing may have become contaminated with solid stannous chloride, stannous sulfate, or potassium stannate, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with stannous chloride, stannic chloride, stannous sulfate, or potassium stannate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of contaminant from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the contaminant, the person performing the operation should be informed of contaminant's hazardous properties.

• Where there is any possibility of exposure of an employee's body to liquid stannic chloride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Where exposure of an employee's body to stannous sulfate, potassium stannate, or liquids containing these compoumay occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with stannic chloride, stannous sulfate, or potassium stannate should be removed immediately and not reworn until the contaminant is removed from the clothing.

• Non-impervious clothing which becomes wet with stannous chloride should be removed promptly and not reworn until the stannous chloride is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of liquid stannic chloride, stannous sulfate or liquids containing stannous sulfate, or potassium stannate or liquids containing potassium stannate contacting the eyes.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where stannous chloride or liquids containing stannous chloride may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid stannic chloride, stannous sulfate or liquids containing stannous sulfate, or potassium stannate or liquids containing potassium stannate,

an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with stannic chloride, stannous sulfate, or potassium stannate should be immediately washed or showered to remove any contaminant.
- Skin that becomes wet with stannous chloride should be promptly washed or showered to remove any stannous chloride.
- Employees who handle stannous chloride, stannic chloride, stannous sulfate, or potassium stannate should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to inorganic tin compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from mining, roasting, and smelting of cassiterite ore; during foundry operations and finishing operations	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of stannic chloride in dyeing silk; manufacture of blueprint paper; as a perfume stabilizer in soap; in the preparation of lubricating oil additives; in treating glass surfaces; as a catalyst in manufacture of pharmaceuticals; and as a bleaching agent for sugar	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of stannous chloride in acidic electrotinning baths; manufacture of blueprint paper; as an antisludge agent in lubricating oils; as a perfume stabilizer in soap; as a catalyst in organic reactions; as an additive in drilling mud; in silvering of mirrors; and as a food additive	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use in production of stannous fluoride or stannous pyrophosphate for use tinning baths and for formulations for remineralization of teeth; use of stannous fluorborate in commercial tin-plating baths; use in production of sodium stannate	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use in production of potassium stannate; use of stannous perchlorate in tin-plating solutions; use of stannic chromate as a ceramic pigment	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of tin hydride to gas-phase plate tin on metal and ceramic surfaces; use of stannous sulfide as a pigment, as a catalyst, and in manufacture of bearing materials	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use in production of stannous sulfate for use in acidic electrotinning baths and in dyeing textiles	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use of stannous oleate or stannous 2-ethyl hexoate as a catalyst for urethane and other polymer foams and as a fabric water-repellant	Personal protective equipment
Use of stannous acetate as a catalyst and agent to promote exhaustion of dyes	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberation during use of heavy metal stannates as additives to ceramic dielectric materials	Process enclosure; local exhaust ventilation; personal protective equipment
Use of stannous tartrate in printing and dyeing of textiles	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment

Use of stannous oxalate as a catalyst in esterification reactions and in coal hydrogenation; use of stannic bromide for metallurgical separation of minerals in the laboratory	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If tin, stannous sulfate, or potassium stannate get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

- **Skin Exposure**

If inorganic tin compounds get on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If inorganic tin compounds penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of inorganic tin compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When inorganic tin compounds have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If tin, stannous chloride, stannic chloride, stannous sulfate, or potassium stannate are spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect spilled or leaked material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquid containing inorganic tin compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

- Waste disposal method:

Inorganic tin compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "Tin (Inorganic Compounds Except SnH_4, a*Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Barnes, J. M., and Stoner, H. B.: "The Toxicology of Tin Compounds," *Pharmacological Review*, 11:214-216, 229-231, 1959.
- Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.
- Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
- Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
- International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.
- Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.
- Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
- Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.
- Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR INORGANIC TIN COMPOUNDS (AS TIN)

Condition	Minimum Respiratory Protection* Required Above 2 mg/m^3
Particulate Concentration	
10 mg/m^3 or less	Any dust and mist respirator, except single-use.**
20 mg/m^3 or less	Any dust and mist respirator, except single-use or quarter-mask respirator.** Any fume or high efficiency particulate filter respirator.** Any supplied-air respirator.** Any self-contained breathing apparatus.**
100 mg/m^3 or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
400 mg/m^3 or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 400 mg/m^3 or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator with a full facepiece. Any escape self-contained breathing apparatus with a full facepiece.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Organic Tin Compounds (as Tin)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all organic tin compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Dibutyltin di-2-ethylhexoate

- Formula: $(C_4H_9)_2Sn(C_8H_{15}O_2)_2$
- Synonyms: Dibutyltin dioctoate
- Appearance and odor: Waxy solid with a weak odor.

Bis(tri-n-butyltin) oxide

- Formula: $((C_4H_9)_3Sn)_2O$
- Synonyms: TBTO
- Appearance and odor: Colorless to yellow liquid with a weak odor.

Triphenyltin chloride

- Formula: $(C_6H_5)_3SnCl$
- Synonyms: None
- Appearance and odor: Colorless to yellow solid with a characteristic odor.

Dibutyltin dichloride

- Formula: $(C_4H_9)_2SnCl_2$
- Synonyms: None
- Appearance: Light tan or colorless solid or semi-solid.

Dibutyltin diacetate

- Formula: $(C_4H_9)_2Sn(C_2H_3O_2)_2$
- Synonyms: None
- Appearance and odor: Colorless liquid with a weak vinegar odor.

Tetrabutyltin

- Formula: $(C_4H_9)_4Sn$
- Synonyms: Tetra-n-butyltin
- Appearance and odor: Colorless liquid with a distinct, characteristic odor.

Stannous 2-ethylhexoate

- Formula: $Sn(C_8H_{15}O_2)_2$
- Synonyms: Stannous octoate; tin octoate
- Appearance and odor: Pale yellow, viscous liquid with a characteristic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for organic tin compounds is 0.1 milligram of organic tin compounds (as tin) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended a permissible exposure limit of 0.1 milligram of tin per cubic meter of air averaged over a work shift of up to 10 hours per day, 40 hours per week. The NIOSH Criteria Document for Organotin Compounds should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Organic tin compounds can affect the body if they are inhaled or if they come in contact with the eyes or skin.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

They can also affect the body if they are swallowed and they may be absorbed through the skin.

• **Effects of overexposure**

Little is known of the toxicity of monoalkyl tin compounds except that the toxicity of monoethyl tin chloride is low. Dialkyl tin compounds have caused irritation of the skin and damage to the liver and bile ducts in animals. This has resulted in animal deaths from liver failure and peritonitis. Swallowing diethyl tin has caused permanent damage to the nervous system and deaths in humans. Trialkyl and tetraalkyl tin compounds have caused nervous system damage in animals. Trialkyl and dibutyl tins have caused skin burns in humans. Tetramethyl and tetraethyl tin have caused headache and vomiting in humans. Tributyl tin compounds have caused severe skin burns in humans.

• **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to organic tin compounds.

• **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to organic tin compounds at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system, eyes, liver, and urinary tract should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since some organic tin compounds may cause urinary retention, a urinalysis should be obtained to include, at a minimum, specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

—Liver function tests: Organic tin compounds cause hepatic necrosis in animals. A profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

—A complete blood count: Organic tin compounds cause hemolysis in animals. A complete blood count should be performed including a red cell count, a white cell count, a differential on a stained smear, as well as hemoglobin and hematocrit.

—Eye disease: Since some organic tin compounds may produce neurological damage, the eyes should be examined for such abnormalities as glaucoma and choked disc; general tests of visual acuity should be performed as well. In addition, evidence indicating past or present increased intracranial pressure should be evaluated.

—Cardiovascular system: An electrocardiogram should be performed on workers over 40 years of age and where indicated.

—Skin disease: Organic tin compounds are defatting agents and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of these agents.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

• **Summary of toxicology**

The organic tin compounds, chiefly solids and liquids, cause irritation of the eyes, throat, and skin; some produce cerebral edema, while others cause hepatic necrosis. Oral administration of a preparation of organic tin containing diethyltin di-iodide and up to 10% triethyltin for treatment of human furunculosis resulted in 217 cases of poisoning, 100 of which were fatal. After a latent period of 4 days there was severe persistent headache followed by vertigo, visual disturbances including photophobia, abdominal pain, vomiting, and urinary retention; the more severe cases showed transient or permanent paralysis and psychic disturbances. Residual symptoms in those who recovered included persistent headache, diminished visual acuity, partial paresis, focal anesthesia, and in four severe cases, flaccid paraplegia with incontinence. The most significant lesion found at necropsy was cerebral edema. Repeated oral administration to rats of 50 mg/kg of dibutyltin chloride resulted in inflammation of bile ducts and hepatic necrosis; repeated skin applications of 10 mg/kg caused severe local skin injury and bile duct damage. Triethyltin sulfate administered repeatedly to rats at 10 mg/kg caused tremors and paresis, which in some animals progressed to complete paralysis and death; it was equally toxic by mouth and by injection. In mice, tributyltin chloride had a marked hemolytic action, while dibutyl and tetrabutyl tin were less markedly hemolytic. Workers exposed to the vapor or fume of butyltin compounds developed sore throat and cough several hours after exposure. Chemical burns from organic tin compounds may result from only brief contact with the skin; pain is usually moderate and itching is the chief symptom; healing is usually complete within 7 to 10 days. When a worker was splashed in the face with a tributyltin compound, lacrimation and severe conjunctivitis appeared within minutes, despite immediate lavage, and persisted for 4 days; at the end of 7 days the eyes appeared normal.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Dibutyltin di-2-ethylhexoate**

1. Molecular weight: 522.7
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 1.07
4. Vapor density (air = 1 at boiling point of dibutyltin di-2-ethylhexoate): Not applicable
5. Melting point: 54 C (129 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Bis(tri-n-butyltin) oxide**

1. Molecular weight: 595.4

2. Boiling point (760 mm Hg): 254 C (489 F) at 50 mm Hg
3. Specific gravity (water = 1): 1.17
4. Vapor density (air = 1 at boiling point of bis(tri-n-butyltin)oxide): Not applicable
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Much less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Less than 20 ppm
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Triphenyltin chloride**

1. Molecular weight: 385.5
2. Boiling point (760 mm Hg): 240 C (464 F) at 13 mm Hg
3. Specific gravity (water = 1): Greater than 1
4. Vapor density (air = 1 at boiling point of triphenyltin chloride): Not applicable
5. Melting point: 106 C (223 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Dibutyltin dichloride**

1. Molecular weight: 303.8
2. Boiling point (760 mm Hg): 135 C (275 F) at 10 mm Hg
3. Specific gravity (water = 1): 1.36
4. Vapor density (air = 1 at boiling point of dibutyltin dichloride): Not applicable
5. Melting point: 43 C (109 F)
6. Vapor pressure at 20 C (68 F): 2 mm Hg/100 C (212 F)
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Dibutltin diacetate**

1. Molecular weight: 351
2. Boiling point (760 mm Hg): 144 C (291 F) at 10 mm Hg
3. Specific gravity (water = 1): 1.32
4. Vapor density (air = 1 at boiling point of dibutyltin diacetate): Not applicable
5. Melting point: 10 C (50 F)
6. Vapor pressure at 20 C (68 F): 1.3 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Tetrabutyltin**

1. Molecular weight: 347.2
2. Boiling point (760 mm Hg): 145 C (293 F) at 10 mm Hg
3. Specific gravity (water = 1): 1.06
4. Vapor density (air = 1 at boiling point of tetrabutyltin): Not applicable
5. Melting point: Less than −70 C (less than −94 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Slight
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Stannous 2-ethylhexoate**

1. Molecular weight: 404.7
2. Boiling point (760 mm Hg): Decomposes at 200 C (392 F)
3. Specific gravity (water = 1): 1.26
4. Vapor density (air = 1 at boiling point of stannous 2-ethylhexoate): Not applicable
5. Melting point: Less than −25 C (less than −13 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors may be released in a fire involving organic tin compounds.
4. Special precautions: Organic tin compounds will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: a) Dibutyltin di-2-ethylhexoate: Data not available; b) Bis(tri-n-butyltin) oxide: Greater than 100 C (212 F); c) Triphenyltin chloride: Data not available; d) Dibutyltin dichloride: 168 C (334 F); e) Dibutyltin diacetate: 143 C (289 F); f) Tetrabutyltin: 124 C (255 F); g) Stannous 2-ethylhexoate: 142 C (287 F)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Data not available (probably because too high boiling points)
4. Extinguishant: Water, foam, dry chemical, and carbon dioxide

• **Warning properties**

Concerning the toxicity of organic tin, Browning states "The eyes are rarely involved, but accidental splashing can cause lacrimation and intense suffusion of the conjunctiva which persists for several days, but with no permanent injury."

Grant lists several toxic effects produced by triethyltin on the eye, but these injuries are caused by systemic poisoning, not by a local effect on the eye.

The NIOSH Criteria Document cites Landa et al. as having observed eye and upper respiratory tract irritation from bis(tributyltin) oxide at an average air concentration of 0.05 mg/m³ measured as tin, but noted that this concentration may not be entirely accurate since the limit of sensitivity of the measurement method used was 0.1 mg/m³.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of organic tin compounds on a filter, followed by chemical treatment and subsequent spectrophotometric analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure organic tin compounds may be used. An analytical method for organic tin compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 1, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00267-3).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with triphenyltin chloride or liquids containing triphenyltin chloride.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with dibutyltin di-2-ethylhexoate or liquids containing dibutyltin di-2-ethylhexoate, liquid bis(tri-n-butyltin) oxide, solid or liquid dibutyltin diacetate, liquid tetrabutyltin, or liquid stannous 2-ethylhexoate.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with dibutyltin dichloride or liquids containing dibutyltin dichloride, where skin contact may occur.

• If employees' clothing has had any possibility of being contaminated with solid triphenyltin chloride or dibutyltin dichloride, employees should change into uncontaminated clothing before leaving the work premises.

• If employees' clothing may have become contaminated with solid dibutyltin di-2-ethylhexoate, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with dibutyltin di-2-ethylhexoate, bis(tri-n-butyltin) oxide, triphenyltin chloride, dibutyltin dichloride, dibutyltin diacetate, tetrabutyltin, or stannous 2-ethylhexoate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of contaminant from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the contaminant, the person performing the operation should be informed of contaminant's hazardous properties.

• Where there is any possibility of exposure of an employee's body to triphenyltin chloride or liquids containing triphenyltin chloride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Where exposure of an employee's body to dibutyltin dichloride or liquids containing dibutyltin dichloride may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with triphenyltin chloride or dibutyltin dichloride should be removed immediately and not reworn until the contaminant is removed from the clothing.

• Non-impervious clothing which becomes contaminated with dibutyltin di-2-ethylhexoate, bis(tri-n-butyltin) oxide,dibutyltin diacetate, tetrabutyltin, or stannous 2-ethylhexoate should be removed promptly and not reworn until the contaminant is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of triphenyltin chloride or liquids containing triphenyltin chloride contacting the eyes.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where dibutyltin di-2-ethylhexoate or liquids containing dibutyltin di-2-ethylhexoate, dibutyltin dichloride or liquids contain-

ing dibutyltin dichloride, liquid bis(tri-n-butyltin) oxide, solid or liquid dibutyltin diacetate, liquid tetrabutyltin, or liquid stannous 2-ethylhexoate may contact the eyes.

• Where there is any possibility that employees' eyes may be exposed to triphenyltin chloride or liquids containing triphenyltin chloride, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with triphenyltin chloride or dibutyltin dichloride should be immediately flushed with large amounts of water to remove any contaminant.

• Workers subject to skin contact with solid dibutyltin di-2-ethylhexoate, triphenyltin chloride, or dibutyltin dichloride should wash with soap or mild detergent and water any areas of the body which may have contacted any contaminant at the end of each work day.

• Skin that becomes contaminated with dibutyltin di-2-ethylhexoate, bis(tri-n-butyltin) oxide, dibutyltin diacetate, tetrabutyltin, or stannous 2-ethylhexoate should be promptly washed or showered with soap or mild detergent and water to remove any contaminant.

• Eating and smoking should not be permitted in areas where dibutyltin di-2-ethylhexoate, bis(tri-n-butyltin) oxide, dibutyltin dichloride, dibutyltin diacetate, or tetrabutyltin are handled, processed, or stored.

• Employees who handle dibutyltin di-2-ethylhexoate, bis(tri-n-butyltin) oxide, triphenyltin chloride, dibutyltin dichloride, dibutyltin diacetate, tetrabutyltin, or stannous 2-ethylhexoate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to organic tin compounds may occur and control methods which may be effective in each case:

Operation	Controls
Use as a stabilizing agent against degradation effects fo light, heat, and oxygen on poly vinyl chloride, neoprene, chlorinated polyethylenes, vinyl copolymers, silicones, and polyamides	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a catalyst in organic and inorganic synthesis in condensation, esterification, halogenation, hydrogenation, oxidation, and polymerization	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of insecticides, bactericides, fungicides, and molluscides; use as U.S. Food and Drug-sanctioned chemical on agricultural crops	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of rodent repellants for wire cable	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as veterinary medicine as poultry anthelmintic	General dilution ventilation
Use as a fuel additive and lubricant	Process enclosure

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If organic tin compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If dibutyltin di-2-ethylhexoate, bis(tri-n-butyltin) oxide, triphenyltin chloride, dibutyltin dichloride, dibutyltin diacetate, tetrabutyltin, or stannous 2-ethylhexoate get on the skin, immediately flush with large amounts of water, then wash with soap or mild detergent and water. If dibutyltin di-2-ethylhexoate, bis(tri-n-butyltin) oxide, triphenyltin chloride, dibutyltin dichloride, dibutyltin diacetate, tetrabutyltin, or stannous 2-ethylhexoate soak through the clothing, remove the clothing immediately and flush with large amounts of water and then wash using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of organic tin compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respi-

ration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When organic tin compounds have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If organic tin compounds are spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.

2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation, or for disposal in a secured sanitary landfill. Liquid containing organic tin compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Organic tin compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tin (Organic Compounds as Sn)," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Barnes, J. M., and Stoner, H. B.: "The Toxicology of Tin Compounds," *Pharmacological Reviews*, 11:211-231, 1959.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Lyle, W. H.: "Lesions of the Skin in Process Workers Caused by Contact with Butyl Tin Compounds," *British Journal of Industrial Medicine*, 15:193-196, 1958.

• Mazayev, V. T., et al.: "Experimental Investigation of the Toxic Effects of Tetraethyltin and Dichlorodibutyltin on the Animal Organism," *Journal of Hygiene, Epidemiology, Microbiology, and Immunology*, 15:115-120, 1971.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Organotin Compounds*, HEW Publication No. (NIOSH) 77-115, GPO No. 017-033-00203-7, U.S. Government Printing Office, Washington, D.C., 1976.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

RESPIRATORY PROTECTION FOR ORGANIC TIN COMPOUNDS (AS TIN)

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
1 mg/m³ or less	A chemical cartridge respirator with an organic vapor cartridge(s) and a dust and mist filter. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	Any chemical cartridge respirator with a full facepiece, an organic vapor cartridge(s), and high efficiency filter (s). Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
50 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 50 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Titanium Dioxide

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: TiO_2
- Synonyms: Rutile; anatase; brookite
- Appearance and odor: White powder with no odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for titanium dioxide is 15 milligrams of titanium dioxide (total dust) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for titanium dioxide a Threshold Limit Value of 10 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Titanium dioxide can affect the body if it is inhaled.

- **Effects of overexposure**

Slight change in the lungs may occur.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to titanium dioxide.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to titanium dioxide at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from titanium dioxide exposure.

—Chronic respiratory disease: Titanium dioxide is a nuisance dust. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of titanium dioxide might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Titanium dioxide dust is a mild pulmonary irritant. Rats repeatedly exposed to concentrations of 10 to 328 million particles per cubic foot of air for as long as 13 months showed small focal areas of emphysema, which were attributed to large deposits of dust; there was no evidence of any specific lesion being produced by titanium dioxide. Three of 15 workers who had been exposed to titanium dioxide dust showed radiographic signs in the lungs resembling "slight fibrosis," but disabling injury did not occur; the magnitude and duration of exposure were not specified. In the lungs of three workers involved in processing titanium dioxide pigments, deposits of the dust in the pulmonary interstitium were associated with cell destruction and slight fibrosis; the findings indicated that titanium dioxide is a mild pulmonary irritant.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 79.9
2. Boiling point (760 mm Hg): Less than 3000 C (less than 5432 F)
3. Specific gravity (water = 1): 3.9 – 4.2
4. Vapor density (air = 1 at boiling point of titanium dioxide): Not applicable
5. Melting point: 1640 C (2984 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1418

- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

According to Grant, titanium dioxide "is a white pigment which is insoluble in water and very inert. It has been introduced by tattooing into the corneas of rabbits and patients having corneal scars, and has caused permanent white coloration but no irritation." For the purposes of this guideline, therefore, titanium dioxide is not treated as an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of titanium dioxide on a filter, followed by treatment with nitric acid, solution by heating with sulfuric acid and ammonium sulfate, and atomic desorption spectrophotometric analysis. An analytical method for titanium dioxide is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to titanium dioxide may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during mining, purification, packaging, and distribution	General dilution ventilation; personal protective equipment
Use as a pigment in manufacture of paints, varnishes, and lacquers to impart whiteness, opacity, and brightness	General dilution ventilation; personal protective equipment
Use in manufacture of paper used in coatings and fillers to improve opacity and brightness; manufacture of paper, photographic papers, paper packaging, and cellophane coatings	General dilution ventilation; personal protective equipment
Use as a white pigment in manufacture of plastics; blow-molded plastic containers	General dilution ventilation; personal protective equipment
Use in manufacture of elastomers for use in tire sidewalls, footwear, floor mats, gloves, rainwear, and wall coverings; use in manufacture of floor coverings	General dilution ventilation; personal protective equipment
Use in manufacture of ceramics and glass for capacitors, electromechanical transducers, welding-rod coatings, and glass fibers	General dilution ventilation; personal protective equipment
Use in manufacture of printing inks for flexographic, gravure, and letter press inks; packaging, publication, offset, and screen processing inks	General dilution ventilation; personal protective equipment

Use in manufacture of coated fabrics and textiles on natural/ artificial leather, oilcloth, upholstery materials, and wall coverings; as a delustrant for acrylic, nylon, and spandex fibers	General dilution ventilation; personal protective equipment
Use in manufacture of building materials in roofing granules, ceiling tiles, cement-curing aids, and titanium carbide cutting tools	General dilution ventilation; personal protective equipment
Use in manufacture of cosmetics, food color additives, and synthetic diamonds	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of titanium dioxide, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If titanium dioxide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquid containing titanium dioxide should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Titanium dioxide may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Titanium Dioxide," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Titanium Dioxide," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Christie, H., et al.: "Pulmonary Effects of Inhalation of Titanium Dioxide by Rats," *American Industrial Hygiene Association Journal*, 24:42-46, 1963.

• Elo, R., et al.: "Pulmonary Deposits of Titanium Dioxide in Man," *Archives of Pathology*, 94:417-424, 1

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hamilton, A., and Hardy, H.: *Industrial Toxicology* (3rd ed.), Publishing Sciences Group, Acton, Massachusetts, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd ed. rev.), Lea and Febiger, Philadelphia, 1957.

RESPIRATORY PROTECTION FOR TITANIUM DIOXIDE

Condition	Minimum Respiratory Protection* Required Above 15 mg/m³
Dust or Mist Concentration	
75 mg/m³ or less	Any dust and mist respirator.
150 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator.
Dust, Mist, or Fume Concentration	
150 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
750 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
7,500 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 7,5000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Toluene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_5CH_3$
- Synonyms: Toluol; phenylmethane; methylbenzene
- Appearance and odor: Colorless liquid with an aromatic odor, like benzene.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for toluene is 200 parts of toluene per million parts of air (ppm) averaged over an eight-hour work shift, and during any such work shift, 300 ppm toluene may not be exceeded except that a peak of 500 ppm toluene is permitted for 10 minutes during the eight-hour work shift. NIOSH has recommended that the permissible exposure limit be reduced to 100 ppm toluene averaged over an eight-hour work shift with a ceiling level of 200 ppm averaged over a ten-minute period. The NIOSH Criteria Document for Toluene should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Toluene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Toluene may cause irritation of the eyes, respiratory tract, and skin. It may also cause fatigue, weakness, confusion, headache, dizziness, and drowsiness. Peculiar skin sensation may be produced such as a "pins and needles feeling" or numbness. Very high concentrations may cause unconsciousness and death. The liquid splashed in the eye may cause irritation and temporary damage. Inhalation may also cause difficulty in seeing in bright light. If liquid toluene is splashed in the eyes, it will cause temporary irritation.

2. Long-term Exposure: Repeated or prolonged exposure to liquid toluene may cause drying and cracking of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to toluene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to toluene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system, liver and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since proper kidney function is necessary for biologic monitoring, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment. The urine should be analyzed for hippuric acid to obtain a background level.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Hippuric acid level in urine may be an indicator of the level of toluene exposure.

- **Summary of toxicology**

Toluene vapor causes narcosis. Controlled exposure of human subjects to 200 ppm for 8 hours produced mild fatigue, weakness, confusion, lacrimation, and paresthesia; at 600 ppm for 8 hours there were also euphoria, headache, dizziness, dilated pupils and nausea; at 800

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1472

September 1978

ppm for 8 hours, symptoms were more pronounced, and after-effects included nervousness, muscular fatigue, and insomnia persisting for several days. Severe but reversible liver and kidney injury occurred in a person who was a glue-sniffer for 3 years; the chief component of the inhaled solvent was toluene (80% V/V); other ingredients were not listed. In workers exposed for many years to concentrations in the range of 80 to 300 ppm, there was no clinical or laboratory evidence of altered liver function. Toluene exposure does not result in the hematopoietic effects caused by benzene; the myelotoxic effects previously attributed to toluene are judged by more recent investigations to be the result of concurrent exposure to benzene present as a contaminant in the commercial toluene used. Most of the toluene absorbed from inhalation is metabolized to benzoic acid, conjugated with glycine in the liver to form hippuric acid, and excreted in the urine; the average amount of hippuric acid excreted in the urine by individuals not exposed to toluene is approximately 0.7 to 1.0 g/l of urine. The liquid splashed in the eyes of two workers caused transient corneal damage and conjunctival irritation; complete recovery occurred within 48 hours. Repeated or prolonged skin contact with liquid toluene has a defatting action, causing drying, fissuring, and dermatitis.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 92.1
  2. Boiling point (760 mm Hg): 111 C (231 F)
  3. Specific gravity (water = 1): 0.86
  4. Vapor density (air = 1 at boiling point of toluene): 3.14
  5. Melting point: −95 C (−139 F)
  6. Vapor pressure at 20 C (68 F): 22 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.05
  8. Evaporation rate (butyl acetate = 1): 2.24
- **Reactivity**
  1. Conditions contributing to instability: Containers may burst at elevated temperatures.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon dioxide and carbon monoxide) may be released in a fire involving toluene.
  4. Special precautions: Toluene will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 4 C (40 F) (closed cup)
  2. Autoignition temperature: 480 C (896 F)
  3. Flammable limits in air, % by volume: Lower: 1.27; Upper: 7.1
  4. Extinguishant: Carbon dioxide, dry chemical, foam
- **Warning properties**
  1. Odor Threshold: The American National Standards Institute (ANSI) states that "the odor of toluene is detectable by most people at concentrations in the range of 10 to 15 ppm. The odor has little value as a warning property."

Patty points out that olfactory fatigue occurs rapidly upon exposure to toluene.

2. Eye Irritation Level: Grant states that "the vapors of toluene cause noticeable sensation of irritation to human eyes at 300 to 400 ppm in air, but even at 800 ppm irritation is slight."

ANSI reports that "irritation of eyes, mucous membranes, and upper respiratory tract may occur while workers are exposed to low concentrations of toluene. There is a considerable range of variation (100 to 500 ppm) between individuals, some finding any concentration of toluene objectionable. Commercial grades of toluene vary in irritant properties."

3. Evaluation of Warning Properties: Because of its irritant effects, toluene is judged to have good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of toluene. Each measurement should consist of a ten (10) minute sample or series of consecutive samples totalling ten (10) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Peak Above Ceiling Evaluation**

Measurements to determine employee peak exposure should be taken during periods of maximum expected airborne concentration of toluene. Each measurement should consist of a 10-minute sample or a series of consecutive samples totalling 10 minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with a subsequent desorption of toluene with carbon disulfide and gas

chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure toluene may be used. An analytical method for toluene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

Methods for Set V" (order number PB 262 524).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid toluene.
- Any clothing which becomes wet with liquid toluene should be removed immediately and not reworn until the toluene is removed from the clothing.
- Clothing wet with toluene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of toluene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the toluene, the person performing the operation should be informed of toluene's hazardous properties.
- Employees should be provided with and required to use splash-proof safety goggles where liquid toluene may contact the eyes.
- Where there is any possibility that employees' eyes may be exposed to toluene, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes wet with liquid toluene should be promptly washed or showered with soap or mild detergent and water to remove any toluene.
- Employees who handle liquid toluene should wash their hands thoroughly with soap or mild detergent and water before eating or smoking.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to toluene may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent in pharmaceutical, chemical, rubber, and plastics industries; as a thinner for paints, lacquer, coatings, and dyes; as a paint remover; insecticides	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as starting material and intermediate in organic chemical and chemical synthesis industries	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use in manufacture of artificial leather; fabric and paper coatings; photogravure ink production; spray surface coating; as a diluent (cellulose ester lacquers)	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Use as constituent in formulation of automotive and aviation fuels	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid toluene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid toluene gets on the skin, promptly wash the contaminated skin using soap or mild detergent and

-1451

water. If liquid toluene soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of toluene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When toluene has been swallowed, get medical attention immediately. Do not attempt to make the exposed person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If toluene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. Toluene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of toluene vapors are permitted.

• Waste disposal method:

Toluene may be disposed of by atomizing in a suitable combustion chamber.

ADDITIONAL INFORMATION

To find additional information on toluene, look up toluene in the following documents:

• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards
• NIOSH Criteria Document for Toluene (July 1973)

These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Toluene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Toluene," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• *American National Standard Acceptable Concentrations – Toluene*: ANSI-Z37.12-1974, American National Standards Institute, Inc., New York, 1974.

• American Petroleum Institute: "Toluene," *API Toxicological Reviews*, New York, 1960.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Dow Chemical Company: *Material Safety Data Sheet – Toluene*, Midland, Michigan, 1972.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Toluene*, HEW Publication No. HSM 73-11023, GPO No. 017-033-00019, U.S. Government Printing Office, Washington, D.C., 1973.

• "Occupational Exposure to Toluene," *Federal Register*, 40:46206-46219, October 6, 1975.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Toluene*, New York, 1970.

RESPIRATORY PROTECTION FOR TOLUENE

Condition	Minimum Respiratory Protection* Required Above 200 ppm
Vapor Concentration	
500 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
2000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 2000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for o-Toluidine*

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3C_6H_4NH_2$
- Synonyms: Ortho-aminotoluene; o-methylaniline; 1-methyl-2-aminobenzene; 2-methylaniline
- Appearance and odor: Colorless to pale yellow liquid with a weak, aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for o-toluidine is 5 parts of o-toluidine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 22 milligrams of o-toluidine per cubic meter of air (mg/m³). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for o-toluidine from 5 ppm to 2 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

o-Toluidine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to o-toluidine may affect the ability of the blood to carry oxygen. The earliest effect from exposure to this chemical is a bluish discoloration of the lips, tongue, and finger nails. At first, if the oxygen lack is not severe, the exposed person may have a feeling of well being. As the lack of oxygen increases, effects such as drowsiness, headache, nausea, and vomiting may appear. If oxygen lack is very severe, it may cause unconsciousness and even death. Liquid toluidine is irritating to the eyes. Recovery from eye exposure may take a long time unless the eyes are flushed with water immediately. In addition, exposure to o-toluidine may cause bloody urine for a short time.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to o-toluidine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to o-toluidine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, kidneys, liver, and cardiovascular system should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: o-Toluidine has been shown to cause methemoglobinemia. Those with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Urinalysis: Since kidney damage has also been observed from exposure, a urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin determination should be performed when o-toluidine intoxication is suspected.

- **Summary of toxicology**

o-Toluidine absorption, whether from inhalation of the vapor or by skin absorption of the liquid, causes anoxia (due to the formation of methemoglobin), and hematu-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

ria. The earliest manifestations of poisoning in humans are headache and cyanosis of the lips, the mucous membranes, the fingernail beds, and the tongue. Minor degrees of hypoxia may lead to a temporary sense of well-being and exhilaration. As the lack of oxygen increases, however, there is growing weakness, dizziness, and drowsiness, leading to stupor, unconsciousness, and death if treatment is not prompt. Transient microscopic hematuria has been observed in o-toluidine workers, presumably of renal origin, since no alterations in the bladder mucosa were observed by cystoscopy. In the eye of a rabbit, the liquid caused a severe burn. Excessive drying of the skin may result from repeated or prolonged contact.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 107
  2. Boiling point (760 mm Hg): 199.7 C (391 F)
  3. Specific gravity (water = 1): 1.00
  4. Vapor density (air = 1 at boiling point of o-toluidine): 3.7
  5. Melting point: −16.3 C (−3 F)
  6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 1.5
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving o-toluidine.
  4. Special precautions: Liquid o-toluidine will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 85 C (185 F) (closed cup)
  2. Autoignition temperature: 482 C (900 F)
  3. Flammable limits in air, % by volume: Lower: 1.5 (calculated at flash point)
  4. Extinguishant: Carbon dioxide, dry chemical, foam
- **Warning properties**
  1. Odor Threshold: The Manufacturing Chemists Association reports that o-toluidine has an aromatic, aniline-like odor, but no information is available concerning the odor threshold of this substance. Aniline, o-toluidine, and xylidine, however, represent a family of chemical compounds with increasing methyl substitution. Since aniline has an odor threshold of 7 ppm and xylidine has an odor threshold of 0.0048 ppm, it is reasonable to assume that the aniline-like odor of o-toluidine is detectable at a concentration between 0.0048 and 7 ppm.
  2. Eye Irritation Level: o-Toluidine vapor is not known to be an eye irritant.
  3. Evaluation of Warning Properties: Since the odor threshold of o-toluidine is probably near the TLV, it is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of o-toluidine in an adsorption tube containing silica gel, followed by desorption with ethanol, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure o-toluidine may be used. An analytical method for o-toluidine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid o-toluidine.
- Clothing contaminated with o-toluidine should be placed in closed containers for storage until it can be

discarded or until provision is made for the removal of o-toluidine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the o-toluidine, the person performing the operation should be informed of o-toluidine's hazardous properties.

• Where exposure of an employee's body to liquid o-toluidine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with o-toluidine should be removed immediately and not reworn until the o-toluidine is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of liquid o-toluidine contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid o-toluidine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with o-toluidine should be immediately washed or showered with soap or mild detergent and water to remove any o-toluidine.

• Eating and smoking should not be permitted in areas where liquid o-toluidine is handled, processed, or stored.

• Employees who handle liquid o-toluidine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to o-toluidine may occur and control methods which may be effective in each case:

Operation	Controls
Use in dye industry in manufacture of dyes and dye intermediates; use in chemical industry in manufacture of organic chemicals and chemical intermediates	Process enclosure; general dilution ventilation; personal protective equipment
Use as a reagent chemical in blood sugar determinations	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid o-toluidine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid o-toluidine gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid o-toluidine soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of o-toluidine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid o-toluidine has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the person to vomit by having him touch the back of his throat with his finger or by giving him large amounts of warm water. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If o-toluidine is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.

2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

o-Toluidine may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "o-Toluidine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Jacobs, M.: *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, Interscience, New York, 1956.

• Lanza, A. J., and Goldberg, J. A. (eds.): *Industrial Hygiene*, Oxford University, London, 1939.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *AMA Archives of Industrial Health*, 14:148-153, 1956.

• Manufacturing Chemists Association, Inc.: *Chemical Safety Data Sheet SD-82, o-Toluidine*, Washington, D.C., 1961.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Smyth, H. F., Jr., et al.: "Range-Finding Toxicity Data: List VI," *American Industrial Hygiene Association Journal*, 23:95-96, 103, 1962.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

* SPECIAL NOTE

o-Toluidine appears on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding its carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980).

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 16, 1978.

RESPIRATORY PROTECTION FOR o-TOLUIDINE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
50 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
100 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 100 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

-1461

Occupational Health Guideline for Tributyl Phosphate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_4H_9O)_3PO$
- Synonyms: Tri-n-butyl phosphate; TBP
- Appearance and odor: Colorless to pale yellow, odorless liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for tributyl phosphate is 5 milligrams of tributyl phosphate per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for tributyl phosphate from 5 mg/m^3 to 2.5 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Tributyl phosphate can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Tributyl phosphate may cause irritation of the eyes, nose, and throat. It may also cause nausea and headache.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to tributyl phosphate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to tributyl phosphate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from tributyl phosphate exposure.

—Chronic respiratory disease: Tributyl phosphate causes respiratory irritation. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of tributyl phosphate might cause exacerbation of symptoms due to its irritant properties.

—Skin disease: Tributyl phosphate is a primary skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Tributyl phosphate vapor is a pulmonary irritant and, in animals, causes a moderate excitation of the nervous system. In rats, the oral LD50 is 3 g/kg; the effects are muscle twitching, weakness, dyspnea, and pulmonary edema. In vitro, tributyl phosphate causes weak inhibition of cholinesterases in human erythrocytes and plasma. Workers exposed to unspecified concentrations of vapor complained of headache and nausea; hot vapor was severely irritating to the eyes and throat. The liquid dropped on the eye of a rabbit caused temporary epithelial injury and discomfort. The liquid may be irritating to the skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 266
2. Boiling point (760 mm Hg): 293 C (560 F)
3. Specific gravity (water = 1): 0.97
4. Vapor density (air = 1 at boiling point of tributyl phosphate): Not applicable

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1432

5. Melting point: Less than −80 C (−112 F)
6. Vapor pressure at 20 C (68 F): Very low
7. Solubility in water, g/100 g water at 20 C (68 F): 0.1
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None
2. Incompatibilities: None
3. Hazardous decomposition products: Toxic gases and vapors (such as phosphoric acid fume and carbon monoxide) may be released in a fire involving tributyl phosphate.
4. Special precautions: Liquid tributyl phosphate will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 166 C (330 F) (closed cup)
2. Autoignition temperature: Higher than 482 C (900 F)
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Carbon dioxide, dry chemical, foam

• **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of tributyl phosphate.
2. Eye Irritation Level: Grant states that tributyl phosphate, "tested on rabbit eyes by application of a drop, . . . had an effect similar to ethyl alcohol, causing temporary epithelial injury and pain, a reaction graded 3 on a scale of 1 to 10 after 24 hours, but no permanent injury." According to the *Hygienic Guide*, some eye irritation occurs at vapor concentrations of ethyl alcohol which are greater than 5500 ppm. Tributyl phosphate and ethyl alcohol in liquid form produce similar effects on the eye.
3. Evaluation of Warning Properties: Since no quantitative information is available relating the warning properties of tributyl phosphate to air concentrations, this substance is treated as having poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of tributyl phosphate on a filter, followed by extraction with ether, and gas chromatographic analysis. An analytical method for tributyl phosphate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid tributyl phosphate.

• Clothing wet with liquid tributyl phosphate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of tributyl phosphate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the tributyl phosphate, the person performing the operation should be informed of tributyl phosphate's hazardous properties.

• Non-impervious clothing which becomes wet with liquid tributyl phosphate should be removed promptly and not reworn until the tributyl phosphate is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid tributyl phosphate may contact the eyes.

SANITATION

• Skin that becomes wet with liquid tributyl phosphate should be promptly washed or showered with soap or mild detergent and water to remove any tributyl phosphate.

• Employees who handle liquid tributyl phosphate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to tributyl phosphate may occur and control methods which may be effective in each case:

Operation	Controls
Use as an antifoaming agent or plasticizer in manufacture of surface coatings and adhesives for latex exterior paints, pigment coatings for paper, inks, lacquers, and synthetic enamel finishes, and during milling pigments	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use as a solvent in extraction of metals, including uranium, tharium, and rare earths in atomic energy processing	General dilution ventilation; local exhaust ventilation; personal protectve equipment
Use as a heat-exchange medium in aircraft engines	General dilution ventilation; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid tributyl phosphate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid tributyl phosphate gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid tributyl phosphate soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of tributyl phosphate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid tributyl phosphate has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid tributyl phosphate is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Liquid tributyl phosphate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Tributyl Phosphate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Ethyl Alcohol," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sabine, J. C., and Hayes, F. N.: "Anticholinesterase Activity of Tributyl Phosphate," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 6:174-177, 1952.

Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR TRIBUTYL PHOSPHATE

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate or Vapor Concentration	
50 mg/m³ or less	Any supplied-air respirator. Any self-contained breathing apparatus.
250 mg/m³ or less	A gas mask with a chin-style or a front- or back-mounted organic vapor cartridge and dust and mist filter. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1300 mg/m³ or less	A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 1300 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1,1,2-Trichloroethane *

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CHCl_2CH_2Cl$
- Synonyms: Vinyl trichloride; beta-trichloroethane
- Appearance and odor: Colorless liquid with a sweet odor, like chloroform.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,1,2-trichloroethane is 10 parts of 1,1,2-trichloroethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 45 milligrams of 1,1,2-trichloroethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,1,2-Trichloroethane can affect the body if it is inhaled if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: 1,1,2-Trichloroethane may cause irritation of the eyes and nose, drowsiness, incoordination, unconsciousness, and death. It might also cause liver and kidney damage.

2. Long-term Exposure: Repeated or prolonged exposure to 1,1,2-trichloroethane might cause liver or kidney damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,1,2-trichloroethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,1,2-trichloroethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,1,2-trichloroethane exposure.

—Liver disease: 1,1,2-Trichloroethane causes liver damage in animals and justifies consideration before exposing persons with impaired liver function.

—Kidney disease: 1,1,2-Trichloroethane causes kidney damage in animals and justifies special consideration in those with impaired renal function.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,1,2-Trichloroethane vapor is a potent narcotic. Injury to lungs, liver, and kidneys has been observed in animals. The lethal concentration for rats was 2000 ppm for 4 hours. Concentrations resulting in narcosis also caused irritation of the nose and eyes. Mice treated by intraperitoneal injection with anesthetic doses showed moderate hepatic dysfunction and renal dysfunction; at autopsy, there was centrolobular necrosis of the liver and tubular necrosis of the kidney. No human cases of intoxication or systemic effects from industrial exposure have been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 133.4
2. Boiling point (760 mm Hg): 113 C (236 F)
3. Specific gravity (water = 1): 1.43
4. Vapor density (air = 1 at boiling point of 1,1,2-trichloroethane): 4.55
5. Melting point: −37 C (−34 F)
6. Vapor pressure at 20 C (68 F): 18.8 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F):

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

-1165

0.45

8. Evaporation rate (butyl acetate = 1): Data not available

• **Reactivity**

1. Conditions contributing to instability: Heat.

2. Incompatibilities: Contact with strong oxidizers, strong caustics, and chemically active metals such as aluminum and magnesium powders, sodium or potassium may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving 1,1,2-trichloroethane.

4. Special precautions: Liquid 1,1,2-trichloroethane will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: None in normal test method

2. Autoignition temperature: Data not available

3. Flammable limits in air, % by volume: Lower: 6.0; Upper: 15.5 (high energy ignition source required)

4. Extinguishant: Foam, carbon dioxide, dry chemical

• **Warning properties**

1. Odor Threshold: Although 1,1,2-trichloroethane is known to have a sweet, chloroform-like odor, no quantitative data are available concerning the odor threshold of this substance.

2. Eye Irritation Level: Grant reports that high concentrations of the vapors are irritating to the eyes. The concentrations at which this irritation occurs are not stated.

3. Other Information: Grant reports that high concentrations of the vapors are irritating to the respiratory tract, but no quantitative information is given.

4. Evaluation of Warning Properties: Since no quantitative information is available relating the warning properties to air concentrations of 1,1,2-trichloroethane, this substance has been treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,1,2-trichloroethane may be used. An analytical method for 1,1,2-trichloroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 1,1,2-trichloroethane.

• Clothing wet with liquid 1,1,2-trichloroethane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1,1,2-trichloroethane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1,1,2-trichloroethane, the person performing the operation should be informed of 1,1,2-trichloroethane's hazardous properties.

• Non-impervious clothing which becomes contaminated with liquid 1,1,2-trichloroethane should be removed promptly and not reworn until the 1,1,2-trichloroethane is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid 1,1,2-trichloroethane may contact the eyes.

SANITATION

• Skin that becomes contaminated with liquid 1,1,2-trichloroethane should be promptly washed or showered with soap or mild detergent and water to remove any 1,1,2-trichloroethane.

• Eating and smoking should not be permitted in areas where liquid 1,1,2-trichloroethane is handled, processed, or stored.

• Employees who handle liquid 1,1,2-trichloroethane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,1,2-trichloroethane may occur and control methods which may be effective in each case:

Operation	Controls
Use in organic synthesis in production of vinylidene chloride	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 1,1,2-trichloroethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 1,1,2-trichloroethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 1,1,2-trichloroethane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1,1,2-trichloroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 1,1,2-trichloroethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 1,1,2-trichloroethane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. Collect for reclamation or absorb in vermiculite, dry sand, or a similar material.

• Waste disposal method:

1,1,2-Trichloroethane may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1,1,2-Trichloroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Klaassen, C. D., and Plaa, G. L.: "Relative Effects of Various Chlorinated Hydrocarbons on Liver and Kidney Function in Mice," *Toxicology and Applied Pharmacology*, 9:139-151, 1966.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – 1,1,2-Trichloroethane*, New York, 1972.

* SPECIAL NOTE

1,1,2-Trichloroethane appears on the OSHA "Candidate List" of chemicals being considered for further scientific review regarding its carcinogenicity (*Federal Register*, Vol. 45, No. 157, pp. 5372-5379, 12 August 1980).

The International Agency for Research on Cancer (IARC) has evaluated the data on this chemical and has concluded that it causes cancer. See *IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Man*, Volume 20, 1979.

RESPIRATORY PROTECTION FOR 1,1,2-TRICHLOROETHANE

Condition	Minimum Respiratory Protection* Required Above 10 ppm
Vapor Concentration	
500 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Trichloronaphthalene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_5Cl_3$
- Synonyms: Halowax; Seekay wax; nibren wax
- Appearance and odor: Colorless to pale yellow solid with an aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for trichloronaphthalene is 5 milligrams of trichloronaphthalene per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Trichloronaphthalene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

Exposure to trichloronaphthalene may cause an acne-like rash. It may also injure the liver, resulting in such effects as fatigue, dark urine, and yellow jaundice.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to trichloronaphthalene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to trichloronaphthalene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the liver and skin should be stressed.

—Liver function tests: Trichloronaphthalene may cause liver damage. A profile of liver function should be obtained by utilizing a medically acceptable array of biochemical tests.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Trichloronaphthalene vapor and dust are toxic to the liver and the skin. Rats exposed to a mixture of tri- and tetrachloronaphthalene at 11 mg/m^3, 16 hours daily for 2-½ months showed slightly swollen liver cells with granular cytoplasm. An industrial exposure to unknown concentrations caused a severe acne-form dermatitis (chloracne) in 50 workers (89% of the crew); initially there was pruritis, which progressed to an acute eczema and finally a subacute folliculitis of acne type affecting mainly the face, periorbital region, cheeks, and ears. Two workers experienced anorexia, nausea, and vertigo. No fatal cases of liver injury have been reported, but one instance of toxic hepatitis resulted from exposure to 3 mg/m^3.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 231.4
2. Boiling point (760 mm Hg): 304– 354 C (580–670 F)
3. Specific gravity (water = 1): 1.58
4. Vapor density (air = 1 at boiling point of trichloronaphthalene): 8.0
5. Melting point: 93 C (199 F)
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

8. Evaporation rate (butyl acetate = 1): Much less than 1

- **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Contact with strong oxidizing agents may cause fires and explosions.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving trichloronaphthalene.

4. Special precautions: None known.

- **Flammability**

1. Flash point: 200 C (392 F) (open cup).

2. Autoignition temperature: None to boiling point

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Foam, carbon dioxide, dry chemical

- **Warning properties**

Since there are no quantitative data relating warning properties to air concentrations of trichloronaphthalene, this substance is treated as a material with poor warning properties. The concentration of trichloronaphthalene in saturated air at 20 C could result in a significant exposure relative to the permissible exposure.

Even though the AIHA *Hygienic Guide* states that "eye injury has not proved to be troublesome with the chloronaphthalenes," trichloronaphthalene is treated as an eye irritant for the purposes of this guideline, as a Koppers Corporation *Material Safety Data Sheet* states that the vapors or dust may irritate the eyes.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of trichloronaphthalene on a filter and in a bubbler containing iso-octane, followed by extraction with iso-octane, and gas chromatographic analysis. An analytical method for trichloronaphthalene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with molten trichloronaphthalene.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid trichloronaphthalene or liquids containing trichloronaphthalene.
- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent skin contact with trichloronaphthalene fumes from the heated material.
- Non-impervious clothing which becomes contaminated with molten trichloronaphthalene should be removed immediately and not reworn until the trichloronaphthalene is removed from the clothing.
- Non-impervious clothing which becomes contaminated with solid trichloronaphthalene or liquids containing trichloronaphthalene should be removed promptly and not reworn until the trichloronaphthalene is removed from the clothing.
- If employees' clothing may have become contaminated with solid trichloronaphthalene, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with trichloronaphthalene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of trichloronaphthalene from the clothing. If the clothing is to be laundered or otherwise cleaned to

remove the trichloronaphthalene, the person performing the operation should be informed of trichloronaphthalene's hazardous properties.

- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of molten trichloronaphthalene contacting the eyes.
- Employees should be provided with and required to use dust- and splash-proof safety goggles where solid trichloronaphthalene or liquids containing trichloronaphthalene may contact the eyes.

SANITATION

- Workers subject to skin contact with trichloronaphthalene should wash with soap or mild detergent and water any areas of the body which may have contacted trichloronaphthalene at the end of each work day.
- Skin that becomes contaminated with trichloronaphthalene should be promptly washed or showered with soap or mild detergent and water to remove any trichloronaphthalene.
- Employees who handle trichloronaphthalene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to trichloronaphthalene may occur and control methods which may be effective in each case:

Operation	Controls
Use as an insulating material in pouring, dipping, and covering of electrical equipment	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation during use of electrical equipment	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an inert component for resins or polymers as a flame-resistant, water-proofing, and fungicidal/insecticidal agent in coatings for wood, textiles, and paper	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in catalytic chlorination of naphthalene to produce tetrachloronaphthalene and trichloronaphthalene; as a filler to impart flame resistance and improve electrical resistance to polymers; manufacture of special lubricants	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an additive for cutting oil	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as an additive to special lubricants in crankcase oil, lubricants for farm machinery, and as an extreme-pressure lubricant	General dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If solid trichloronaphthalene or liquids containing trichloronaphthalene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. If molten trichloronaphthalene gets into the eyes, immediately flush the eyes with large amounts of water to remove heat. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If solid trichloronaphthalene or liquids containing trichloronaphthalene get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If trichloronaphthalene soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention. If molten trichloronaphthalene gets on the skin or non-impervious clothing, immediately flush the affected area with large amounts of water to remove heat. Get medical attention immediately.

- **Breathing**

If a person breathes in large amounts of trichloronaphthalene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When trichloronaphthalene has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If trichloronaphthalene is spilled, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill.
3. For small quantities, sweep onto paper or other flammable material, place in an appropriate container and burn in a safe place (such as a fume hood.) Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Trichloronaphthalene may be disposed of:

1. By making packages of trichloronaphthalene in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.
2. By dissolving in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Trichloronaphthalene," *Documentation of the Threshold Limit Vaiues for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Chloronaphthalenes," *Hygienic Guide Series*, Detroit, Michigan, 1966.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• Hunter, D., and Drinker, C. K., et al.: "The Problem of Possible Systemic Effects from Certain Chlorinated Hydrocarbons," *Journal of Industrial Hygiene and Toxicology*, 19:283, 1937.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Koppers Corporation: *Material Safety Data Sheet – Trichloronaphthalene.*

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR TRICHLORONAPHTHALENE

Condition	Minimum Respiratory Protection* Required Above 5 mg/m³
Particulate Concentration	
50 mg/m³ or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 50 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for 1,2,3-Trichloropropane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_2ClCHClCH_2Cl$
- Synonyms: Allyl trichloride; glycerol trichlorohydrin; glycerin trichlorohydrin; trichlorohydrin
- Appearance and odor: Colorless liquid with a strong acid odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,2,3-trichloropropane is 50 parts of 1,2,3-trichloropropane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 300 milligrams of 1,2,3-trichloropropane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,2,3-Trichloropropane can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may be absorbed through the skin.

- **Effects of overexposure**

1. Short-term Exposure: 1,2,3-Trichloropropane may cause irritation of the eyes, nose, and throat. It might cause drowsiness and liver damage.

2. Long-term Exposure: 1,2,3-Trichloropropane might cause irritation from prolonged or repeated exposure.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,2,3-trichloropropane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,2,3-trichloropropane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,2,3-trichloropropane exposure.

—Skin disease: 1,2,3-Trichloropropane is a skin irritant. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: 1,2,3-Trichloropropane is known as a liver toxin in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Although 1,2,3-trichloropropane is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of 1,2,3-trichloropropane might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,2,3-Trichloropropane vapor is a narcotic, irritates the upper respiratory tract, and is toxic to the liver. Inhalation by mice of 30 mg/liter (5,000 ppm) for 20 minutes was fatal to 8 of 15 exposed; liver damage accounted for four additional deaths 7 to 10 days later; daily 10-minute exposures at 2,500 ppm for 10 days resulted in 7 deaths among 10 mice. In rabbits the liquid was an intense skin irritant and caused erythema, sloughing, and cracking. In an experimental human study, exposure to 100 ppm

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1475

was objectionable because of eye and throat irritation and unpleasant odor.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 147.4
  2. Boiling point (760 mm Hg): 156 C (313 F)
  3. Specific gravity (water = 1): 1.4
  4. Vapor density (air = 1 at boiling point of 1,2,3-trichloropropane): 5
  5. Melting point: −14.7 C (5 F)
  6. Vapor pressure at 20 C (68 F): 3.4 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Data not available
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Contact with active metals, strong caustics, or with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, phosgene, and carbon monoxide) may be released in a fire involving 1,2,3-trichloropropane.
  4. Special precautions: 1,2,3-Trichloropropane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Flash point: 73.3 C (164 F) (closed cup)
  2. Autoignition temperature: 304 C (579 F)
  3. Flammable limits in air, % by volume: Lower: 3.2%; Upper: 12.6%
  4. Extinguishant: Foam, carbon dioxide, dry chemical
- **Warning properties**

The *Documentation of TLV's* reports that "the vapor of 1,2,3-trichloropropane was objectionable to all subjects exposed at a concentration of 100 ppm because of eye irritation, throat irritation, and unpleasant odor." Since this concentration is only twice the permissible exposure limit, this compound is considered to have adequate warning properties.

As mentioned above, the *Documentation of TLV's* states that 100 ppm causes eye irritation. However, this is not reported as a threshold level.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,2,3-trichloropropane may be used. An analytical method for 1,2,3-trichloropropane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 1,2,3-trichloropropane.
- Clothing contaminated with liquid 1,2,3-trichloropropane should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of 1,2,3-trichloropropane from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the 1,2,3-trichloropropane, the person performing the operation should be informed of 1,2,3-trichloropropane's hazardous properties.
- Where exposure of an employee's body to liquid 1,2,3-trichloropropane may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Non-impervious clothing which becomes contaminated with liquid 1,2,3-trichloropropane should be re-

moved immediately and not reworn until the 1,2,3-trichloropropane is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid 1,2,3-trichloropropane contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to liquid 1,2,3-trichloropropane, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with liquid 1,2,3-trichloropropane should be immediately washed or showered with soap or mild detergent and water to remove any 1,2,3-trichloropropane.

• Eating and smoking should not be permitted in areas where liquid 1,2,3-trichloropropane is handled, processed, or stored.

• Employees who handle liquid 1,2,3-trichloropropane should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,2,3-trichloropropane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a solvent and extractant for resins, oils, fats, waxes, and chlorinated rubber; as a commercial solvent for degreasing metal parts	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in organic synthesis for the manufacture of other chemicals; use as a copolymer or telomer or cross-linking agent for sealing compounds	Process enclosure; local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 1,2,3-trichloropropane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 1,2,3-trichloropropane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 1,2,3-trichloropropane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1,2,3-trichloropropane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 1,2,3-trichloropropane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 1,2,3-trichloropropane is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

1,2,3-Trichloropropane may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

- American Conference of Governmental Industrial Hygienists: "1,2,3-Trichloropropane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
- Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
- Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
- Shell Chemical Company: *Material Safety Data Sheet - 1,2,3-Trichloropropane*, Houston, Texas.
- Smyth, H. F., et al.: "Range-Finding Toxicity Data, List VI," *American Industrial Hygiene Association Journal*, 23:95-107, 1962.
- Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies - 1,2,3-Trichloropropane*, New York, 1973.
- von Oettingen, W. F.: *The Halogenated Aliphatic, Olefinic, Cyclic, Aromatic, and Aliphatic-Aromatic Hydrocarbons Including the Halogenated Insecticides, Their Toxicity and Potential Dangers*, U.S. Public Health Service Publication No. 414, U.S. Government Printing Office, Washington, D.C., 1955.

RESPIRATORY PROTECTION FOR 1,2,3-TRICHLOROPROPANE

Condition	Minimum Respiratory Protection* Required Above 50 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1000 ppm** or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**Use of supplied-air suits may be necessary to prevent skin contact while providing respiratory protection from airborne concentrations of 1,2,3-trichloropropane; however, this equipment should be selected, used, and maintained under the immediate supervision of trained personnel. Where supplied-air suits are used above a concentration of 1000 ppm, an auxiliary self-contained breathing apparatus operated in positive pressure mode should also be worn.

Occupational Health Guideline for 1,1,2-Trichloro-1,2,2-Trifluoroethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CCl_2F\text{-}CClF_2$
- Synonyms: Halocarbon 113; Refrigerant 113; TTE
- Appearance and odor: Colorless liquid with an odor like carbon tetrachloride (at high concentrations).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for 1,1,2-trichloro-1,2,2-trifluoroethane is 1000 parts of 1,1,2-trichloro-1,2,2-trifluoroethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 7600 milligrams of 1,1,2-trichloro-1,2,2-trifluoroethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

1,1,2-Trichloro-1,2,2-trifluoroethane can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: 1,1,2-Trichloro-1,2,2-trifluoroethane may cause irritation of the eyes and throat or drowsiness. Breathing high concentrations may cause the heart to beat irregularly or to stop.

2. Long-term Exposure: 1,1,2-Trichloro-1,2,2-trifluoroethane on prolonged or repeated contact with the skin may cause skin irritation.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to 1,1,2-trichloro-1,2,2-trifluoroethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to 1,1,2-trichloro-1,2,2-trifluoroethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from 1,1,2-trichloro-1,2,2-trifluoroethane exposure.

—Skin disease: 1,1,2-Trichloro-1,2,2-trifluoroethane is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrythmias, the breathing of 1,1,2-trichloro-1,2,2-trifluoroethane might cause exacerbation of symptoms due to its sensitizing properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

1,1,2-Trichloro-1,2,2-trifluoroethane vapor is a narcotic. In guinea pigs exposed to 25,000 ppm, nasal irritation was rapidly apparent and incoordination occurred at 50,000 ppm after 30 minutes; death occurred after one hour at this level. In dogs, cardiac sensitization to epinephrine occurred at concentrations of 5,000 to 10,000 ppm. The liquid produced no irritation on the abraded or intact skin of guinea pigs; in the eyes of rabbits it produced mild conjunctivitis and minimal corneal dullness, which were reversible. In experimental human studies, exposure to 4,500 ppm for 30 to 100 minutes resulted in significant impairment in tests of manual dexterity and vigilance; subjects reported loss of concentration and a tendency to somnolence which disappeared 15 minutes after the exposure ended; at

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

damage, aplastic anemia, cyanosis, and dermatitis. Do not attempt to extinguish large fires.

1,500 ppm no effects were observed. More prolonged human exposures of 6 hours daily, 5 days per week for 2 weeks at concentrations of approximately 500 and 1,000 ppm resulted in no adverse effects, with the exception of mild throat irritation on the first day; there was no decrement in performance of complex mental tasks. The liquid dissolves the natural oils of the skin, and dermatitis may occur as a result of repeated contact.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 187.4
  2. Boiling point (760 mm Hg): 47.6 C (117.6 F)
  3. Specific gravity (water = 1): 1.55
  4. Vapor density (air = 1 at boiling point of 1,1,2-trichloro-1,2,2-trifluoroethane): 6.5
  5. Melting point: −35 C (−31 F)
  6. Vapor pressure at 20 C (68 F): 284 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.017
  8. Evaporation rate (butyl acetate = 1): Greater than 1
- **Reactivity**
  1. Conditions contributing to instability: Heat
  2. Incompatibilities: Reacts with chemically active metals such as calcium, powdered aluminum, zinc, magnesium and beryllium. Contact with magnesium alloys containing more than 2% magnesium may cause decomposition.
  3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen chloride, hydrogen fluoride, phosgene, and carbon monoxide) may be released when 1,1,2-trichloro-1,2,2-trifluoroethane decomposes.
  4. Special precautions: 1,1,2-Trichloro-1,2,2-trifluoroethane will attack some forms of plastics, rubber, and coatings.
- **Flammability**
  1. Not combustible
- **Warning properties**

Since the AIHA *Hygienic Guide* states that this compound is "nearly odorless," and since experimental evidence indicates that its irritant effects are only slight and transient at concentrations near the permissible exposure, it is treated as a material with poor warning properties.

There is no evidence to indicate that the vapor is an eye irritant. The *Documentation of TLV's* states that "no corneal injury or irritation" was observed in guinea pigs exposed to this substance. For the purposes of this guideline, therefore, it is not treated as an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure 1,1,2-trichloro-1,2,2-trifluoroethane may be used. An analytical method for 1,1,2-trichloro-1,2,2-trifluoroethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

(order number PB 265 028).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid 1,1,2-trichloro-1,2,2-trifluoroethane.
- Non-impervious clothing which becomes wet with liquid 1,1,2-trichloro-1,2,2-trifluoroethane should be removed promptly and not reworn until the 1,1,2-trichloro-1,2,2-trifluoroethane is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid 1,1,2-trichloro-1,2,2-trifluoroethane contacting the eyes.

SANITATION

• Skin that becomes wet with liquid 1,1,2-trichloro-1,2,2-trifluoroethane should be promptly washed or showered with soap or mild detergent and water to remove any 1,1,2-trichloro-1,2,2-trifluoroethane.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to 1,1,2-trichloro-1,2,2-trifluoroethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as a selective solvent in degreasing electrical equipment, photographic films, magnetic tapes, precision instruments, plastics, glass, elastomers, or metal components; as dry cleaning solvent for all fabrics, leather, and suedes.	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a refrigerant in commercial/industrial air conditioning and industrial process cooling	General dilution ventilation
Use as a chemical intermediate for dechloronization of chemicals in the manufacture of polymers, and copolymers in production of high-temperature lubricants	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as a foaming or blowing agent in the manufacture of polymers for flame retardancy	Process enclosure; local exhaust ventilation; general dilution ventilation
Use as a solvent in the textile industry; and as a solvent in special laboratory usage	Local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If 1,1,2-trichloro-1,2,2-trifluoroethane gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If 1,1,2-trichloro-1,2,2-trifluoroethane gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If 1,1,2-trichloro-1,2,2-trifluoroethane soaks through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of 1,1,2-trichloro-1,2,2-trifluoroethane, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When 1,1,2-trichloro-1,2,2-trifluoroethane has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the afflicted person to vomit by having him touch the back of his throat with his finger or by giving him syrup of ipecac as directed on the package. This non-prescription drug is available at most drug stores and drug counters and should be kept with emergency medical supplies in the workplace. Do not make an unconscious person vomit.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If 1,1,2-trichloro-1,2,2-trifluoroethane is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. Collect for reclamation or absorb in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

1,1,2-Trichloro-1,2,2-trifluoroethane may be disposed of by absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "1,1,2-Trichloro-1,2,2-Trifluoroethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "1,1,2-Trichloro-1,2,2-Trifluoroethane," *Hygienic Guide Series*, Detroit, Michigan, 1968.

• E. I. DuPont de Nemours and Company: *Freon Compounds and Safety – 1,1,2-Trichloro-1,2,2-Trifluoroethane*, Wilmington, Delaware.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Reinhardt, C. F., et al.: "Cardiac Sensitization Potential of Some Common Industrial Solvents," *Industrial Hygiene News Report*, 15:3-4, 1972.

• Stopps, G. J., and McLaughlin, M.: "Psychophysiological Testing of Human Subjects Exposed to Solvent Vapors," *American Industrial Hygiene Association Journal*, 28:43-50, 1967.

RESPIRATORY PROTECTION FOR 1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Vapor Concentration	
4500 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
Greater than 4500 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Triethylamine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_2H_5)_3N$
- Synonyms: None
- Appearance and odor: Colorless liquid with a fishy odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for triethylamine is 25 parts of triethylamine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 100 milligrams of triethylamine per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Triethylamine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Triethylamine causes irritation of the eyes, nose, and throat. If the liquid is splashed in the eyes, it may cause severe eye damage.

2. Long-term Exposure: Repeated or prolonged exposure to triethylamine may cause skin and lung irritation. Heart, liver, and kidney damage have been reported in animal experiments.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to triethylamine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to triethylamine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from triethylamine exposure.

—Chronic respiratory disease: Triethylamine causes lung irritation in animals. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of triethylamine might cause exacerbation of symptoms due to its irritant properties.

—Cardiovascular disease: Triethylamine causes myocardial degeneration in animals. In persons with impaired cardiovascular function, the inhalation of triethylamine might cause exacerbation of pre-existing disorders.

—Liver disease: Triethylamine causes liver damage in animals. The importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Triethylamine causes kidney damage in animals. The importance of this organ in the elimination of toxic substances justifies special consideration in those with impaired renal function.

—Eye disease: Triethylamine is an eye irritant and has caused corneal edema in workers. Persons with preexisting eye disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Triethylamine vapor is a primary irritant of mucous membranes and eyes. Exposure to 1000 ppm for 4 hours was lethal to rats. Rabbits survived exposures to 100 ppm daily for 6 weeks, but showed pulmonary irritation, myocardial degeneration, and cellular necrosis of

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

liver and kidney; at 50 ppm the effects on lung, liver, and kidney were less severe, but there was also damage to the cornea. In the eye of a rabbit, 1 drop of liquid triethylamine caused severe injury. Eye irritation and corneal edema in humans have been reported from industrial exposure. Closely related amines cause skin irritation.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 101.2
2. Boiling point (760 mm Hg): 89.5 C (193 F)
3. Specific gravity (water = 1): 0.73
4. Vapor density (air = 1 at boiling point of triethylamine): 3.5
5. Melting point: −115 C (−175 F)
6. Vapor pressure at 20 C (68 F): 54 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 5.5
8. Evaporation rate (butyl acetate = 1): 5.6

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with strong acids may cause violent spattering.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving triethylamine.
4. Special precautions: Liquid triethylamine will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: −6.7 C (20 F) (closed cup)
2. Autoignition temperature: 450 C (842 F)
3. Flammable limits in air, % by volume: Lower: 1.2; Upper: 8.0
4. Extinguishant: Alcohol foam, carbon dioxide, dry chemical

- **Warning properties**

1. Odor Threshold: Grant reports that triethylamine has a "strong ammoniacal odor," but no quantitative information concerning the odor threshold is available.
2. Eye Irritation Level: Grant reports that "chronic exposure of rabbits to triethylamine vapors at concentrations as low as 50 ppm in air causes multiple erosions of the cornea and conjunctiva . . . in the course of 6 weeks."
3. Other Information: Patty reports that rabbits repeatedly exposed to 50 ppm triethylamine over a 6-week period experienced lung irritation.
4. Evaluation of Warning Properties: Since information concerning the odor threshold is not available, and since the only quantitative information concerning its irritant effects is from chronic exposures, triethylamine is treated as a material with poor warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of triethylamine in a bubbler containing sulfuric acid, followed by treatment with sodium hydroxide, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure triethylamine may be used. An analytical method for triethylamine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid triethylamine.
- Clothing wet with liquid triethylamine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of

triethylamine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the triethylamine, the person performing the operation should be informed of triethylamine's hazardous properties.

- Where exposure of an employee's body to liquid triethylamine may occur, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.
- Any clothing which becomes wet with triethylamine or non-impervious clothing which becomes contaminated with triethylamine should be removed immediately and not reworn until the triethylamine is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid triethylamine or liquids containing triethylamine contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid triethylamine or liquids containing 1% or more of triethylamine by weight, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with triethylamine should be immediately washed or showered to remove any triethylamine.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to triethylamine may occur and control methods which may be effective in each case:

Operation	Controls
Use in polymer technology as a catalyst for curing epoxy resins, for polyurethane foams, and for thermosetting polymers; as a stabilizing agent and chain-transfer agent; use in preparation of film-forming resins, as a solvent, pH stabilizer, and to improve water solubility in polymers	Local exhaust ventilation; general dilution ventilation
Use in extraction and purification of antibiotics; use in herbicides and pesticides, and in preparation of emulsifiers for pesticides	Local exhaust ventilation; general dilution ventilation
Use in organic synthesis of quarternary ammonium compounds in textile-treating chemicals, emulsifiers, surfactants, in paper manufacture, non-nutritive sweeteners, ketenes, and salts	Local exhaust ventilation; general dilution ventilation
Use as a corrosion inhibitor and chemical stabilizer for chlorinated solvents, in transmission fluids, oil well piping, engine parts, and gum inhibitors for gasoline	Local exhaust ventilation; general dilution ventilation
Use in paints and coatings to control viscosity and to prevent livering; to develop water resistance in resins; as a pH stabilizer; and to improve gloss of appliance finishes	Local exhaust ventilation; general dilution ventilation
Use as a dye assist; miscellaneous uses in rocket fuels to shorten ignition delays; ingredient of photographic development accelerator, for drying of printing inks, and in carpet cleaners	Local exhaust ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If triethylamine or liquids containing triethylamine get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If triethylamine gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If triethylamine soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of triethylamine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When triethylamine has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If triethylamine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device. Triethylamine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal method:

Triethylamine may be disposed of by atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Triethylamine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Brieger, H., and Hodes, W. A.: "Toxic Effects of Exposure to Vapors of Aliphatic Amines," *A.M.A. Archives of Industrial Hygiene and Occupational Medicine*, 3:287-291, 1951.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, H. F., et al.: "Range-Finding Toxicity Data, List VI," *American Industrial Hygiene Association Journal*, 23:12, 95-107, 1962.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Union Carbide Corporation, Industrial Medicine and Toxicology Department: *Toxicology Studies – Triethylamine*, New York, 1970.

RESPIRATORY PROTECTION FOR TRIETHYLAMINE

Condition	Minimum Respiratory Protection* Required Above 25 ppm
Vapor Concentration	
1000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against triethylamine. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Trifluoromonobromomethane

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CBrF_3$
- Synonyms: Halocarbon 13B1, Refrigerant 13B1; bromotrifluoromethane; Halon 1301
- Appearance and odor: Colorless gas with a slight ethereal odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for trifluoromonobromomethane is 1000 parts of trifluoromonobromomethane per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 6100 milligrams of trifluoromonobromomethane per cubic meter of air (mg/m^3).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Trifluoromonobromomethane can affect the body if it is inhaled. It may also affect the body if the liquid comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Breathing high concentrations of trifluoromonobromomethane may cause lightheadedness. Breathing very high concentrations of trifluoromonobromomethane may cause the heart to beat irregularly or stop.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to trifluoromonobromomethane.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to trifluoromonobromomethane at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from trifluoromonobromomethane exposure.

—Cardiovascular disease: In persons with impaired cardiovascular function, especially those with a history of cardiac arrythmias, the breathing of trifluoromonobromomethane might cause exacerbation of symptoms due to its sensitizing properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Trifluoromonobromomethane vapor is a narcotic at high concentrations. In dogs and rats repeatedly exposed to 23,000 ppm there were no toxic signs or pathologic changes. Monkeys exposed to concentrations of 20% (200,000 ppm) became lethargic and suffered spontaneous cardiac arrhythmias within 5 to 40 seconds of exposure. In animal exposure studies at high levels, sensitization of the myocardium to epinephrine was reported. In human experiments designed to determine the safety of the substance as a firefighting agent in airplane cabins, exposure of three volunteers at 7% (70,000 ppm) for three minutes produced no cardiac anomalies.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 149
2. Boiling point (760 mm Hg): −57.8 C (−72 F)
3. Specific gravity (water = 1): 1.54 at 77 F

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

4. Vapor density (air = 1 at boiling point of trifluoromonobromomethane): 5

5. Melting point: −168 C (−270 F)

6. Vapor pressure at 20 C (68 F): Not pertinent

7. Solubility in water, g/100 g water at 20 C (68 F): 0.03

8. Evaporation rate (butyl acetate = 1): Not pertinent

• **Reactivity**

1. Conditions contributing to instability: Heat

2. Incompatibilities: Reacts with chemically active metals, calcium, or with powdered aluminum, zinc, and magnesium.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen bromide, carbonyl fluoride, hydrogen fluoride, and carbon monoxide) may be released when trifluoromonobromomethane decomposes.

4. Special precautions: Liquid trifluoromonobromomethane will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Trifluoromonobromomethane does not have adequate warning properties.

Trifluoromonobromomethane is not a known eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with methylene chloride and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure trifluoromonobromomethane may be used. An analytical method for trifluoromonobromomethane is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to trifluoromonobromomethane may occur and control methods which may be effective in each case:

Operation	Controls
Use as commercial and military fire extinguishant; use as a refrigerant for food processing and storage; use as a blowing agent to improve flame retardancy of rigid polyurethane foams	General dilution ventilation; local exhaust ventilation; personal protective equipment
Use in organic synthesis in production of olefin resins; use during the manufacture of hydraulic fluids as an erosion inhibitor	General dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation during use for special purposes in bubble chambers for ionization studies, in "quark" detection, and in radiation counters	General dilution ventilation; local exhaust ventilation; perosnal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of trifluoromonobromomethane, move the exposed person to fresh air at once. If breathing has stopped, perform

artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of leaks until cleanup has been completed.

• If trifluoromonobromomethane is leaked, the following steps should be taken:

1. Ventilate area of leak.
2. Stop flow of gas.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Trifluoromonobromomethane," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• E. I. DuPont de Nemours and Company: *Freon Compounds and Safety - Trifluoromonobromomethane*, Wilmington, Delaware.

• E. I. DuPont de Nemours and Company: *Freon Product Information - Trifluoromonobromomethane*, Wilmington, Delaware.

• National Academy of Sciences: "Symposium on An Appraisal of Halogenated Fire Extinguishing Agents," Washington, D. C., April 11-12, 1972.

• Smith, D. G., and Harris, D. J.: "Human Exposure to Halon 1301 (CBrF3) during Simulated Aircraft Cabin Fires," *Aerospace Medicine*, 44:198-201, 1973.

• Van Stee, E. W., and Back, K. C.: "Short Term Inhalation of Bromotrifluoromethane," *Toxicology and Applied Pharmacology*, 15:164-174, 1969.

RESPIRATORY PROTECTION FOR TRIFLUOROMONOBROMOMETHANE

Condition	Minimum Respiratory Protection* Required Above 1000 ppm
Gas Concentration	
10,000 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
50,000 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a half-facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 50,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Trinitrotoluene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3C_6H_2(NO_2)_3$
- Synonyms: TNT; trinitrotoluol; 2,4,6-trinitrotoluene; sym-trinitrotoluene
- Appearance and odor: Colorless to pale yellow, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for trinitrotoluene is 1.5 milligrams of trinitrotoluene per cubic meter of air (mg/m³) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for trinitrotoluene a Threshold Limit Value of 0.5 mg/m³ with a skin notation.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Trinitrotoluene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to trinitrotoluene can cause liver damage with yellow jaundice and anemia which may be fatal. It may also cause irritation of the eyes, nose, and throat with sneezing, cough, and sore throat. It may cause a skin rash and stain the skin, hair, and nails a yellowish color. It may affect the ability of the blood to carry oxygen. This may result in a bluish discoloration of the skin, weakness, drowsiness, shortness of breath and unconsciousness. In addition, it may cause muscular pains, heart irregularities, kidney irritation, cataracts of the eyes, menstrual irregularities, and nerve damage.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to trinitrotoluene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to trinitrotoluene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of asthma, allergies, or known sensitization to trinitrotoluene would be expected to be at increased risk from exposure. Examination of the blood, liver, eyes, cardiovascular system, nervous system, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Trinitrotoluene has been shown to cause aplastic anemia in humans. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Liver function tests: Since liver damage has been observed in humans exposed to trinitrotoluene, a profile of liver function should be obtained by using a medically acceptable array of biochemical tests.

—Urinalysis: Since kidney damage has been observed in humans exposed to trinitrotoluene, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on a semiannual basis.

- **Summary of toxicology**

Trinitrotoluene (TNT) dust or fume causes liver

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

damage, aplastic anemia, cyanosis, and dermatitis. There have been numerous fatalities of workers exposed to TNT in munitions plants; in a series of 22 fatal cases, 8 died from toxic hepatitis, 13 from aplastic anemia, and 1 from a combination of both. The vapor or dust can cause irritation of mucous membranes, resulting in sneezing, cough, and sore throat. Although intense or prolonged exposure to TNT may cause some cyanosis, it is not regarded as a strong producer of methemoglobin. Other occasional effects are leukocytosis or leukopenia, peripheral neuritis, muscular pains, cardiac irregularities, and renal irritation. Cataracts have been observed in a considerable proportion of chronically exposed workers; one report indicates that 26 of 61 workers with an average exposure of 8.4 years had a characteristic peripheral cataract. TNT causes sensitization dermatitis; the hands, wrists, and forearms are most commonly affected, but skin at friction points such as the collar line, belt line, and ankles is also often involved; erythema, papules, and an itchy eczema can be severe. The skin, hair, and nails of exposed workers may be stained yellow.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 227
2. Boiling point (760 mm Hg): 240 C (464 F) (explodes)
3. Specific gravity (water = 1): 1.65
4. Vapor density (air = 1 at boiling point of trinitrotoluene): Not applicable
5. Melting point: 81 C (178 F)
6. Vapor pressure at 85 C (185 F): 0.053 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 0.013
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: Slow decomposition occurs above 180 C (356 F). Exposure to light may increase impact sensitivity. Rapid heating may cause detonation.
2. Incompatibilities: Contact with strong oxidizers may cause fire. Contact with ammonia or with strong alkalies may increase sensitivity to shock. Can react vigorously with oxidizable materials.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving trinitrotoluene.
4. Special precautions: Protect from shock.

- **Flammability**

1. Flash point: Explodes
2. Impact sensitivity (minimum fall of a 2 kg weight to cause at least one explosion in ten trials): 100 cm
3. Explosion temperature (temperature required to cause explosion in five seconds): 475 C (887 F)
4. Extinguishant: Water may be used on small fires. Do not attempt to extinguish large fires.

- **Warning properties**

1. Odor Threshold: No quantitative information is available concerning the odor threshold of TNT.
2. Eye Irritation Level: Grant states that "irritation of the eyes and skin is not uncommon among munitions workers exposed to its dust and fumes." No quantitative information is available concerning the air concentrations which produce the eye irritation.
3. Evaluation of Warning Properties: Since no quantitative information is available relating warning properties to air concentrations of TNT, this substance is treated as a material with poor warning properties. The concentration in saturated air at 20 C might result in a significant exposure relative to the permissible exposure.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for trinitrotoluene had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solid trinitrotoluene or liquids containing trinitrotoluene.

• If employees' clothing may have become contaminated with solid trinitrotoluene, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which may have become contaminated with solid trinitrotoluene or liquids containing trinitrotoluene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of trinitrotoluene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the trinitrotoluene, the person performing the operation should be informed of trinitrotoluene's hazardous properties.

• Non-impervious clothing which becomes contaminated with trinitrotoluene should be removed promptly and not reworn until the trinitrotoluene is removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where solid trinitrotoluene or liquids containing trinitrotoluene may contact the eyes.

SANITATION

• Workers subject to skin contact with solid trinitrotoluene or liquids containing trinitrotoluene should wash with soap or mild detergent and water any areas of the body which may have contacted trinitrotoluene at the end of each work day.

• Skin that becomes contaminated with trinitrotoluene should be promptly washed or showered with soap or mild detergent and water to remove any trinitrotoluene.

• Eating and smoking should not be permitted in areas where solid trinitrotoluene or liquids containing trinitrotoluene are handled, processed, or stored.

• Employees who handle solid trinitrotoluene or liquids containing trinitrotoluene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to trinitrotoluene may occur and control methods which may be effective in each case:

Operation	Controls
Use in the manufacture of shells, bombs, grenades, and mines; use in commercial explosives, and propellant compositions	Process enclosure; local exhaust ventilation; personal protective equipment
Use in the production of intermediates for synthesis of dyestuffs and photographic chemicals	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If trinitrotoluene or liquids containing trinitrotoluene get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If trinitrotoluene or liquids containing trinitrotoluene get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If trinitrotoluene or liquids containing trinitrotoluene penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of trinitrotoluene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When trinitrotoluene or liquids containing trinitrotoluene have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If trinitrotoluene is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Attempt to reclaim spilled material; however, do not sweep or burn unless this is supervised by explosives experts.

• Waste disposal method:

Trinitrotoluene may be disposed of only by explosives experts.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Trinitrotoluene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Trinitrotoluene," *Hygienic Guide Series*, Detroit, Michigan, 1964.

• Crawford, M. A. D.: "Aplastic Anaemia due to Trinitrotoluene Intoxication," *British Medical Journal*, 2:430-437, 1954.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Bulletin of Supplementary Material for Clinical Toxicology of Commercial Products*, University of Rochester, 1969-1975.

• Goodwin, J. W.: "Twenty Years Handling TNT in a Shell Loading Plant," *American Industrial Hygiene Association Journal*, 33:41-44, 1972.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• Palmer, W. L., et al.: "Toxic Necrosis of the Liver from Trinitrotoluene," *Journal of the American Medical Association*, 123:1025-1027, 1943.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L.: "Dermatitis from Explosives," *Journal of the American Medical Association*, 125:186-190, 1944.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

RESPIRATORY PROTECTION FOR TRINITROTOLUENE

Condition	Minimum Respiratory Protection* Required Above 1.5 mg/m³
Particulate or Vapor Concentration	
15 mg/m³ or 1.5 ppm or less	Any supplied-air respirator. Any self-contained breathing apparatus.
75 mg/m³ or 7.5 ppm or less	Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
3000 mg/m³ or 300 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 3000 mg/m³ or 300 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors and particulates. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Triorthocresyl Phosphate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3C_6H_4O)_3PO$
- Synonyms: O-tritolyl phosphate; TCP; TOCP
- Appearance and odor: Colorless, odorless liquid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for triorthocresyl phosphate is 0.1 milligram of triorthocresyl phosphate per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Triorthocresyl phosphate can affect the body if it is inhaled, comes in contact with the eyes or skin, or swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Triorthocresyl phosphate may cause paralyses of the lower arms and legs if it is swallowed, inhaled (as a fog mist, or aerosol), or absorbed through the skin. Nausea, vomiting, diarrhea, and abdominal pain may occur shortly after exposure. These symptoms disappear and are followed, after a symptom-free period of 3 to 28 days, by the paralytic effect.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to triorthocresyl phosphate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to triorthocresyl phosphate at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the peripheral and central nervous systems should be stressed.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Triorthocresyl phosphate (TOCP) causes peripheral neuropathy with flaccid paralysis of the distal muscles of the upper and lower extremities, followed in some cases by a spastic paralysis. In affected cats and hens, extensive damage is observed in the spinal cord and sciatic nerves; damage to the myelin sheath and Schwann cells is secondary to the destructive lesion in the axon, which starts at the distal end of the longer axons. Thousands of people have been poisoned by the accidental ingestion of TOCP in contaminated foods and beverages; reports of intoxication from occupational exposure are rare. Shortly after ingestion there may be nausea, vomiting, diarrhea, and abdominal pain. After a symptom-free interval of 3 to 28 days most patients complain of sharp, cramplike pains in the calf muscles, and some of numbness and tingling in the feet and sometimes the hands. Within a few hours there is increasing weakness of the legs and feet, progressing to bilateral footdrop. After an interval of another 10 days, weakness of the fingers and wristdrop develop, but the paralysis is not usually as severe as occurs in the feet and legs; this process does not extend above the elbows; the thigh muscles are infrequently involved. Sensory changes, if they occur, are minor. With severe intoxication, lesions of the anterior horn cells and the pyramidal

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

tracts may also occur. Muscular weakness may increase over a period of several weeks or months; recovery may take months or years, and in 25 to 30% of cases permanent residual effects remain, usually confined to the lower limbs. Fatalities are rare and occur principally in those who have taken large quantities of TOCP in a short period of time; autopsy of six human cases revealed involvement of anterior horn cells and demyelination of nerve cells. The lethal dose for humans by ingestion is about 1.0 g/kg; severe paralysis has been produced by ingestion of 6 to 7 mg/kg. In workers engaged in the manufacture of aryl phosphates (including up to 20% TOCP) and exposed to concentrations of aryl phosphates at 0.2 to 3.4 mg/m^3, there was some inhibition of plasma cholinesterase but no correlation of this effect with degree of exposure or with minor gastrointestinal or neuromuscular symptoms. No effects on the eyes or skin have been reported; TOCP is readily absorbed through the skin without local irritant effects.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 368
2. Boiling point (760 mm Hg): 410 C (770 F) (decomposes)
3. Specific gravity (water = 1): 1.17
4. Vapor density (air = 1 at boiling point of triorthocresyl phosphate): Not applicable
5. Melting point: −33 C (−27 F)
6. Vapor pressure at 20 C (68 F): Very low (0.02 mm Hg at 150 C (302 F))
7. Solubility in water, g/100 g water at 20 C (68 F): 0.00003
8. Evaporation rate (butyl acetate = 1): Not applicable

- **Reactivity**

1. Conditions contributing to instability: None hazardous
2. Incompatibilities: None
3. Hazardous decomposition products: Toxic gases and vapors (such as phosphoric acid fume and carbon monoxide) may be released in a fire involving triorthocresyl phosphate.
4. Special precautions: Liquid triorthocresyl phosphate will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 225 C (437 F) (closed cup)
2. Autoignition temperature: 385 C (725 F)
3. Flammable limits in air, % by volume: Data not available
4. Extinguishant: Foam, carbon dioxide, dry chemical

- **Warning properties**

Triorthocresyl phosphate (TOCP) is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of triorthocresyl phosphate on a filter, followed by extraction with ether, and gas chromatographic analysis. An analytical method for triorthocresyl phosphate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid triorthocresyl phosphate.
- Clothing contaminated with triorthocresyl phosphate should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of triorthocresyl phosphate from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the triorthocresyl phosphate, the person

performing the operation should be informed of triorthocresyl phosphate's hazardous properties.

• Non-impervious clothing which becomes contaminated with triorthocresyl phosphate should be removed promptly and not reworn until the triorthocresyl phosphate is removed from the clothing.

SANITATION

• Skin that becomes contaminated with triorthocresyl phosphate should be promptly washed or showered with soap or mild detergent and water to remove any triorthocresyl phosphate.

• Eating and smoking should not be permitted in areas where liquid triorthocresyl phosphate is handled, processed, or stored.

• Employees who handle liquid triorthocresyl phosphate should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to triorthocresyl phosphate may occur and control methods which may be effective in each case:

Operation	Controls
Use as a flame retarder and plasticizer in chlorinated rubber, nitrile rubber and resins; use in hot extrusion, molding, or bulk forming of plasticized polyvinyl chloride	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use in coatings and adhesives based on plasticized cellulose esters and alkyds	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as a gasoline additive to control preignition	Personal protective equipment
Use as a hydraulic fluid and a heat exchange medium	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Use as a synthetic lubricant; as a waterproofing agent; as a primary component of adhesives for air filter media; use as a solvent mixture for nitrocellulose and other natural resins	Personal protective equipment
Use as an extraction solvent in recovery of phenol from gas-plant effluents and coke-oven waste waters	Personal protective equipment
Use in grinding media for pigments; use as an intermediate in synthesis of pharmaceuticals	General dilution ventilation; process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If liquid triorthocresyl phosphate gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If liquid triorthocresyl phosphate gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid triorthocresyl phosphate soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

• **Breathing**

If a person breathes in large amounts of triorthocresyl phosphate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When liquid triorthocresyl phosphate has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency

rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If liquid triorthocresyl phosphate is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.

2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Liquid triorthocresyl phosphate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Triorthocresyl Phosphate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Triorthocresyl Phosphate," *Hygienic Guide Series*, Detroit, Michigan, 1963.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• Hunter, D., et al.: "Toxic Polyneuritis Arising During the Manufacture of Tricresyl Phosphate," *British Journal of Industrial Medicine*, 1:227-231, 1944.

• Johnson, M. K.: "Delayed Neurotoxic Action of Some Organo-phosphorus Compounds," *British Medical Bulletin*, 25:231-235, 1969.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Susser, M., and Stein, Z.: "An Outbreak of Tri-Ortho-Cresyl Phosphate (T.O.C.P.) Poisoning in Durban," *British Journal of Industrial Medicine*, 14:111-120, 1957.

• Tabershaw, I. R., and Kleinfeld, M. K.: "Manufacture of Tricresyl Phosphate and Other Alkyl Phenyl Phosphates: An Industrial Hygiene Study. II. Clinical Effects of Tricresyl Phosphate," *A.M.A. Archives of Industrial Health*, 15:541-544, 1957.

• Tabershaw, I. R., et al.: "Manufacture of Tricresyl Phosphate and Other Alkyl Phenyl Phosphates: An Industrial Hygiene Study. I. Environmental Factors," *A.M.A. Archives of Industrial Health*, 15:537-540, 1957.

• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

• Vora, D. D., et al.: "Toxic Polyneuritis in Bombay due to Ortho-Cresyl-Phosphate Poisoning," *Journal of Neurology, Neurosurgery, and Psychiatry*, 25:234-242, 1962.

RESPIRATORY PROTECTION FOR TRIORTHOCRESYL PHOSPHATE

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
0.5 mg/m³ or less	Any dust and mist respirator, except single-use.
1 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
40 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 40 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust and mist respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Triphenyl Phosphate

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(C_6H_5O)_3PO$
- Synonyms: TPP; phenyl phosphate
- Appearance and odor: Colorless solid with a faint aromatic odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for triphenyl phosphate is 3 milligrams of triphenyl phosphate per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Triphenyl phosphate can affect the body if it is inhaled. It may also affect the body if it is swallowed.

- **Effects of overexposure**

Repeated exposure may cause minor changes in the blood enzymes. Animal exposures have produced muscle weakness and paralysis. These effects have not been reported in man.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to triphenyl phosphate.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to triphenyl phosphate at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from triphenyl phosphate exposure.

—Neuromuscular disorders: Triphenyl phosphate causes neurotoxic effects in animals. Persons with pre-existing neuromuscular disorders may be at increased risk.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Triphenyl phosphate is a neurotoxin in animals. When injected in cats it caused delayed paralysis. Two of 6 cats given a single intraperitoneal injection of triphenyl phosphate at 0.1 to 0.4 g/kg developed paralysis after 16 to 18 days. A group of 11 workers exposed to vapor, mist, or dust at an average concentration of 3.5 mg/m^3 and occasionally as high as 40 mg/m^3 for 8 to 10 years exhibited no signs of illness; the only positive finding was a slight but statistically significant reduction in erythrocyte cholinesterase activity. In workers engaged in the manufacture of aryl phosphates (including triphenyl phosphates and up to 20% triorthocresyl phosphate) and exposed to concentrations of aryl phosphates of 0.2 to 3.4 mg/m^3, there was some inhibition of plasma cholinesterase but no correlation of this effect with degree of exposure or with minor gastrointestinal or neuromuscular symptoms. The effects of triphenyl phosphate on the eye have not been reported; application in ethanol to the skin of mice produced no more irritation than was expected from the solvent.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 326
2. Boiling point (760 mm Hg): 370 C (698 F)
3. Specific gravity (water = 1): 1.27
4. Vapor density (air = 1 at boiling point of triphenyl phosphate): Not applicable
5. Melting point: 48.5 C (119 F)
6. Vapor pressure at 20 C (68 F): Very low (0.15 mm

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1502

Hg at 150 C (302 F))

7. Solubility in water, g/100 g water at 20 C (68 F): 0.001

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: None hazardous

2. Incompatibilities: None

3. Hazardous decomposition products: Toxic gases and vapors (such as phosphoric acid fume and carbon monoxide) may be released in a fire involving triphenyl phosphate.

4. Special precautions: Liquid triphenyl phosphate will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 220 C (428 F) (closed cup)

2. Autoignition temperature: Data not available

3. Flammable limits in air, % by volume: Data not available

4. Extinguishant: Carbon dioxide, dry chemical, foam

• **Warning properties**

Triphenyl phosphate is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection of triphenyl phosphate on a filter, followed by extraction with ether, and gas chromatographic analysis. An analytical method for triphenyl phosphate is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to triphenyl phosphate may occur and control methods which may be effective in each case:

Operation	Controls
Use as a flame-retardant and plasticizer in compounding of chlorinated rubber; use on coatings and adhesives	General dilution ventilation; process enclosure; local exhaust ventilation
Use in hot extrusion, molding, or other bulk forming plasticized cellulose acetates	General dilution ventilation; process enclosure; local exhaust ventilation
Use as a fireproofing agent in manufacture of roofing paper	General dilution ventilation; process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of triphenyl phosphate, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When triphenyl phosphate has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and

know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If triphenyl phosphate is spilled, the following steps should be taken:

1. Ventilate area of spill.

2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

• Waste disposal methods:

Triphenyl phosphate may be disposed of:

1. By making packages of triphenyl phosphate in paper or other flammable material and burning in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

2. By dissolving triphenyl phosphate in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Triphenyl Phosphate," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Triphenyl Phosphate," *Hygienic Guide Series*, Detroit, Michigan, 1970.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Hjorth, N.: "Contact Dermatitis from Cellulose Acetate Film," *Berufsdermatosen*, 2:2, pp.86-100, April 1964.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sutton, W. L., et al.: "Studies on the Industrial Hygiene and Toxicology of Triphenyl Phosphate," *Archives of Environmental Health*, 1:45-58, 1960.

• Tabershaw, I. R., and Kleinfeld, M. K.: "Manufacture of Tricresyl Phosphate and Other Alkyl Phenyl Phosphates: An Industrial Hygiene Study. II. Clinical Effects of Tricresyl Phosphate," *A.M.A. Archives of Industrial Health*, 15:541-544, 1957.

• Tabershaw, I. R., et al.: "Manufacture of Tricresyl Phosphate and Other Alkyl Phenyl Phosphates: An Industrial Hygiene Study. I. Environmental Factors," *A.M.A. Archives of Industrial Health*, 15:537-540, 1957.

-1501

RESPIRATORY PROTECTION FOR TRIPHENYL PHOSPHATE

Condition	Minimum Respiratory Protection* Required Above 3 mg/m³
Particulate Concentration	
15 mg/m³ or less	Any dust and mist respirator, except single-use.
30 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
150 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1500 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 1500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Turpentine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{10}H_{16}$ (approximately); minimum alpha-pinene content 40% by weight
- Synonyms: Gum spirits of turpentine; turps; wood turpentine; spirits of turpentine; sulfate wood turpentine; sulfate turpentine; gum turpentine; steam-distilled turpentine
- Appearance and odor: Colorless liquid with a characteristic, paint odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for turpentine is 100 parts of turpentine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 560 milligrams of turpentine per cubic meter of air (mg/m³).

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Turpentine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Overexposure to turpentine may cause irritation of the eyes, nose, throat, lungs, and skin. It may also cause headache, dizziness, and painful urination or dark-red urine. Greater exposure may cause unconsciousness and death.

2. Long-term Exposure: Prolonged overexposure causes skin irritation. Skin sensitization can occur.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to turpentine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to turpentine at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from turpentine exposure.

—Skin disease: Turpentine is a skin defatting agent and sensitizer and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

—Liver disease: Although turpentine is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Kidney disease: Turpentine has been reported to cause albuminuria and hematuria in humans and special consideration should be given to those with a history of impaired renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of turpentine might cause exacerbation of symptoms due to its irritant properties.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

Turpentine vapor is a mucous membrane irritant and, at higher concentrations, a convulsant. The LC50 for rats is 3590 ppm for 1 hour and 2150 ppm for 6 hours; hyperpnea, ataxia, tremors, and convulsions were noted. In cats, 1440 ppm produced disturbances in equilibrium and convulsions in 30 to 60 minutes; paralysis occurred in 150 to 180 minutes. In human subjects,

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1508

September 1978

750 to 1000 ppm for several hours caused irritation of the eyes, headache, dizziness, nausea, and tachycardia; 1878 ppm for 1 to 4 hours was considered definitely toxic. Heavy overexposure is also reported to cause irritation of the nose and throat, cough, headache, vertigo, and irritation of the kidneys and bladder manifested by transient albuminuria and hematuria. However, there is little evidence that turpentine vapor at lower concentrations is a chronic systemic poison. Liquid in the eye causes conjunctivitis and corneal burns; a vapor concentration of 75-200 ppm is said to be moderately irritating. The liquid is also a defatting agent and causes skin irritation. Some persons may develop skin hypersensitivity. Mild intoxication from skin absorption has been reported.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 136 (approximately)
2. Boiling point (760 mm Hg): 150 to 180 C (302 to 356 F)
3. Specific gravity (water = 1): 0.864
4. Vapor density (air = 1 at boiling point of turpentine): 4.7
5. Melting point: −50 to −60 C (−58 to −76 F)
6. Vapor pressure at 25 C (77 F): 5 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizing agents (especially chlorine) may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving turpentine.
4. Special precautions: Turpentine will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 35 C (95 F) (closed cup)
2. Autoignition temperature: 253 C (488 F)
3. Flammable limits in air, % by volume: Lower: 0.8
4. Extinguishant: Dry chemical, foam, carbon dioxide

- **Warning properties**

1. Odor Threshold: Patty states that "the odor of 200 ppm turpentine in air is readily noticeable."
2. Eye Irritation Level: Patty states that 200 ppm "is moderately irritating to the eyes and mucous membranes of the nasal passages."
3. Evaluation of Warning Properties: Through its odor and irritant effects, turpentine can be detected at a level within twice the permissible exposure limit. For the purposes of this guideline, turpentine is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of turpentine vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure turpentine may be used. An analytical method for turpentine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid turpentine.
- Clothing wet with liquid turpentine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of turpentine from the clothing. If the clothing is to be laundered or

otherwise cleaned to remove the turpentine, the person performing the operation should be informed of turpentine's hazardous properties.

• Any clothing which becomes wet with liquid turpentine should be removed immediately and non-impervious clothing which becomes contaminated with turpentine should be removed promptly and such clothing should not be reworn until the turpentine is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid turpentine may contact the eyes.

SANITATION

• Skin that becomes contaminated with turpentine should be promptly washed or showered with soap or mild detergent and water to remove any turpentine.

• Employees who handle liquid turpentine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to turpentine may occur and control methods which may be effective in each case:

Operation	Controls
Use in manufacture of synthetic pine oil; insecticides; and in beta-pinene resins, flavors, and perfumes	Local exhaust ventilation; process enclosure; personal protective equipment
Use in preparation of polishes; use in manufacture of synthetic camphor, and use in paints	Local exhaust ventilation; process enclosure; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If turpentine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If turpentine gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If turpentine soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of turpentine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If turpentine has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If turpentine is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Turpentine should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Turpentine may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Turpentine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Turpentine," *Hygienic Guide Series*, Detroit, Michigan, 1967.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Kirk, R., and Othmer, D.: *Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1968.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Stolman, A. (ed.): *Progress in Chemical Toxicology*, Academic Press, New York, 1965-1969.

• *Survey of Compounds Which Have Been Tested for Carcinogenic Activity*, U.S. Public Health Service Publication No. 149, Original, Supplements 1 and 2, 1961-1967, 1968-1969, and 1970-1971.

RESPIRATORY PROTECTION FOR TURPENTINE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
1900 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 1900 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Uranium and Insoluble Compounds (as Uranium)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all uranium and insoluble compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Metallic uranium

- Formula: U
- Synonyms: None
- Appearance: Heavy, silvery white metal which is pyrophoric when finely divided.
- Note: U238 is radioactive with a half life of 4,900,000,000 years.

Uranium octaoxide

- Formula: U_3O_8
- Synonyms: Pitchblende
- Appearance and odor: Black, odorless solid.

Uranium tetrafluoride

- Formula: UF_4
- Synonyms: None
- Appearance and odor: Green, odorless solid.

Uranium hydride

- Formula: UH_3
- Synonyms: None
- Appearance: Brownish black or brownish gray powder.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for uranium or insoluble compounds is 0.25 milligram of uranium or insoluble compounds (as uranium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for uranium or insoluble compounds (as uranium) a Threshold Limit Value of 0.2 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Uranium or insoluble compounds can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

Exposure to insoluble uranium compounds has been reported to cause an increase in cancer of the lymphatic and blood-forming tissues in man. Prolonged contact with the skin might cause radiation damage to the skin. Prolonged inhalation of insoluble uranium compounds has caused damage to the lungs of animals.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to uranium or insoluble compounds.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to uranium or insoluble compounds at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Exami-

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1510

nation of the respiratory system, blood, and lymphatic system should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Since uranium is deposited in the bone and is an alpha particle emitter, the function of the bone marrow is at risk. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—14" x 17" chest roentgenogram: Uranium or insoluble compounds cause lung damage in animals. Surveillance of the lungs is indicated.

—Urinalysis: Although not reported with insoluble uranium compounds, kidney damage has been reported due to uranium exposure. A urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. In addition, a determination of urinary uranium levels should be performed at any time overexposure is suspected or signs and symptoms of toxicity occur.

- **Summary of toxicology**

Insoluble compounds of uranium are less toxic than the soluble compounds. They are weakly radioactive and are principally alpha particle emitters; fibrotic changes have been observed in the lungs of animals after prolonged inhalation exposure, although radiation effects (other than possible carcinogenesis from absorbed uranium) have not been observed in humans. Both feeding and percutaneous toxicity studies on animals indicate that the insoluble uranium compounds are less toxic than the soluble compounds. Repeated exposures of three animal species to uranium dioxide dust at a concentration of 5 mg uranium/m^3 for periods up to 5 years resulted in no kidney injury; over 90% of the uranium found in the body was in the lungs and tracheobronchial lymph nodes (TLN). Fibrotic changes suggestive of radiation injury were seen occasionally in the TLN of dogs and monkeys and in the lungs of monkeys after exposure periods longer than 3 years; the estimated alpha dose to tissues was greater than 500 rads for lungs and 7000 rads for TLN. Rats injected with metallic uranium in the femoral marrow and in the chest wall developed sarcomata; whether this was due to metallocarcinogenic or radiocarcinogenic action could not be determined. The increased incidence of lung cancer reported among uranium miners is probably the result of exposure to radon gas and its particulate daughters, rather than to uranium dust. In a group of uranium mill workers, there was an excess of deaths from malignant disease of lymphatic and hematopoietic tissue; data from animal experiments suggested that this excess may have resulted from irradiation of lymph nodes by thorium-230, a disintegration product of uranium. Some absorbed uranium is deposited in bone; a potential risk of radiation effects on bone marrow has been postulated, but extensive clinical studies on exposed workers have disclosed no hematologic abnormalities. No evidence of chronic toxicity, either chemical or radiation, was observed for any uranium compound in the milling process during the first 6 years of the atomic energy program; all exposed workers were under very close medical surveillance. Prolonged skin contact with uranium compounds should be avoided because of potential radiation damage to basal cells; dermatitis has occurred as a result of handling uranium tetrafluoride.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data—Metallic uranium**
  1. Molecular weight: 238.03
  2. Boiling point (760 mm Hg): 3818 C (6904 F)
  3. Specific gravity (water = 1): 18.95
  4. Vapor density (air = 1 at boiling point of metallic uranium): Not applicable
  5. Melting point: 1133 C (2071 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Physical data—Uranium octaoxide**
  1. Molecular weight: 842.1
  2. Boiling point (760 mm Hg): Decomposes at 1300 C (2372 F)
  3. Specific gravity (water = 1): 7.31
  4. Vapor density (air = 1 at boiling point of uranium octaoxide): Not applicable
  5. Melting point: 1300 C (2372 F) (decomposes)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1):
- **Physical data—Uranium tetrafluoride**
  1. Molecular weight: 314
  2. Boiling point (760 mm Hg): 1417 C (2582 F) (sublimes)
  3. Specific gravity (water = 1): 6.7
  4. Vapor density (air = 1 at boiling point of uranium tetrafluoride): Not applicable
  5. Melting point: 969 C (1776 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Physical data—Uranium hydride**
  1. Molecular weight: 241
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): Data not available
  4. Vapor density (air = 1 at boiling point of uranium hydride): Not applicable
  5. Melting point: Decomposes
  6. Vapor pressure at 20 C (68 F): Essentially zero, except for decomposition products

7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble

8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Heat (uranium hydride). Uranium turnings and fines stored out-of-doors in closed containers under water or water-soluble oil will partially convert into the hydride and eventually ignite during hot weather.

2. Incompatibilities: Contact of uranium with carbon dioxide, carbon tetrachloride, or nitric acid will cause fires or explosions. Contact of uranium hydride with strong oxidizers may cause fires and explosions. Contact of uranium hydride with water will form flammable and explosive hydrogen gas. Contact of uranium hydride with halogenated hydrocarbons can be violent.

3. Hazardous decomposition products: Toxic gases and vapors (such as hydrogen fluoride and carbon monoxide) may be released when uranium or insoluble compounds decompose.

4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable

2. Minimum ignition temperature: Uranium: 20 C (68 F) (cloud); 100 C (212 F) (layer); Uranium hydride: 20 C (68 F) (cloud); 20 C (68 F) (layer)

3. Minimum explosive concentration: 60 grams/m³

4. Extinguishant: Dry powder, dry sand, graphite

• **Warning properties**

According to Grant, "several uranium compounds tested by dropping on the eyes of rabbits, guinea pigs, and rats have been found to cause severe eye damage as well as systemic poisoning. Compounds which have been found to cause moderately severe injury of the eyes are . . . uranium tetrafluoride, . . . uranium trioxide, uranium dioxide, and uranium peroxide . . . . The mildest damage was caused by the various uranium oxides."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for uranium or insoluble compounds had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solids or liquids containing uranium or insoluble compounds.

• If employees' clothing may have become contaminated with solids or liquids containing uranium or insoluble compounds, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing contaminated with uranium or insoluble compounds should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of uranium or insoluble compounds from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the uranium or insoluble compounds, the person performing the operation should be informed of the hazardous properties of these substances.

• Non-impervious clothing which becomes contaminated with uranium or insoluble compounds should be removed promptly and not reworn until the uranium or insoluble compounds are removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solids or liquids containing uranium or insoluble compounds contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solids or liquids containing uranium or insoluble compounds, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with uranium or insoluble compounds should be promptly washed or showered with soap or mild detergent and water to remove any uranium or insoluble compounds.
- Eating and smoking should not be permitted in areas where solids or liquids containing uranium or insoluble compounds are handled, processed, or stored.
- Employees who handle solids or liquids containing uranium or insoluble compounds should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to uranium or insoluble compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from mining, grinding, and milling of ores	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use of insoluble compounds as chemical intermediates in preparation of uranium compounds; use for nuclear technology	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in nuclear reactors as fuel and to pack nuclear fuel rods	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Liberation from burning of uranium metal chips and smelting operations	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in ceramics industry for pigments, coloring porcelain, painting on porcelain, and enamelling	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as catalysts for many reactions; in production of fluorescent glass	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If solids or liquids containing uranium or insoluble compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

- **Skin Exposure**

If solids or liquids containing uranium or insoluble compounds get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If solids or liquids containing uranium or insoluble compounds penetrate through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of uranium or insoluble compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When solids or liquids containing uranium or insoluble compounds have been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
- If uranium or insoluble compounds are spilled, the following steps should be taken:

1. Ventilate area of spill.

-1513

2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation. Liquid containing uranium or insoluble compounds should be absorbed in vermiculite, dry sand, earth, or a similar material. Uranium chips or turnings which are spilled should be covered with oil.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Uranium and Compounds as U," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Uranium (Natural) and Its Compounds," *Hygienic Guide Series*, Detroit, Michigan, 1969.

• Archer, V. E., et al.: "Cancer Mortality Among Uranium Mill Workers," *Journal of Occupational Medicine*, 15:11-14, 1973.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hawley, G. G. (ed.): *The Condensed Chemical Dictionary* (8th ed. rev.), Van Nostrand Reinhold, New York, 1971.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Leach, L. J., et al.: "A Five-Year Inhalation Study with Natural Uranium Dioxide (UO_2) Dust- I. Reand Biologic Effect in the Monkey, Dog and Rat," *Health Physics*, 18:599-612, 1970.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Voegtlin, C., and Hodge, H. C.: *Pharmacology and Toxicology of Uranium Compounds*, Vol. 1, McGraw Hill, New York, 1949,.

• Voegtlin, C., and Hodge, H. C.: *Pharmacology and Toxicology of Uranium Compounds*, Vol. 2, McGraw Hill, New York, 1949,.

RESPIRATORY PROTECTION FOR URANIUM AND INSOLUBLE COMPOUNDS (AS URANIUM)

Condition	Minimum Respiratory Protection* Required Above 0.25 mg/m³
Particulate Concentration	
2.5 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator approved for radon daughters or radionuclides. Any supplied-air respirator. Any self-contained breathing apparatus.
12.5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
30 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 30 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Soluble Uranium Compounds (as Uranium)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all soluble uranium compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Uranium hexafluoride

- Formula: UF_6
- Synonyms: None
- Appearance: Yellow, deliquescent solid.

Uranyl nitrate

- Formula: $UO_2(NO_3)_2$-$6H_2O$
- Synonyms: Uranium nitrate
- Appearance and odor: Yellow, odorless solid.

Uranyl sulfate

- Formula: UO_2SO_4-$3H_2O$
- Synonyms: None
- Appearance and odor: Yellow-green, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for soluble uranium compounds is 0.05 milligram of soluble uranium compounds (as uranium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. The American Conference of Governmental Industrial Hygienists has recommended for soluble uranium compounds a Threshold Limit Value of 0.2 mg/m^3.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Soluble uranium compounds can affect the body if they are inhaled or if they come in contact with the eyes or skin. They can also affect the body if they are swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Soluble uranium compounds may cause irritation of the eyes with damage, lung damage, and kidney damage.

2. Long-term Exposure: Repeated or prolonged skin exposure to soluble uranium compounds may cause radiation damage to the skin. Exposure to soluble uranium compounds has been reported to cause an increase in cancer of the lymphatic and blood-forming tissues of man.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to soluble uranium compounds.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to soluble uranium compounds at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system, blood, liver, lymphatic system, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—Urinalysis: Since kidney damage has been observed in humans exposed to uranium, a urinalysis should be performed, including at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

September 1978

—A complete blood count: Since uranium is deposited in the bone and is an alpha-particle emitter, the function of the bone marrow should be monitored. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. In addition, a determination of urinary uranium levels should be performed at any time overexposure is suspected or signs and symptoms of toxicity occur.

• **Summary of toxicology**

Soluble compounds of uranium as dust or mist are respiratory irritants and are toxic to the kidneys; uranium is weakly radioactive and emits alpha particles. Animals repeatedly exposed to dusts of soluble uranium compounds in concentrations from 3 to 20 mg/m³ died of pulmonary and renal damage; both feeding and percutaneous toxicity studies on animals indicate that the more soluble compounds are the most toxic. In animals, effects on the liver are a consequence of the acidosis and azotemia induced by renal dysfunction. Rats injected with metallic uranium in the femoral marrow and in the chest wall developed sarcomata; whether this was due to metallocarcinogenic or radiocarcinogenic action could not be determined. The increased incidence of lung cancer reported among uranium miners is probably the result of exposure to radon gas and its particulate daughters, rather than to uranium dust. In a group of uranium mill workers there was an excess of deaths from malignant disease of lymphatic and hematopoietic tissue; data from animal experiments suggested that this excess may have resulted from irradiation of lymph nodes by thorium-230, a disintegration product of uranium. Some absorbed uranium is deposited in bone; a potential risk of radiation effects on bone marrow has been postulated, but extensive clinical studies on exposed workers have disclosed no hematologic abnormalities. Accidental exposure of workers to a mixture of uranium hexafluoride, uranium oxyfluoride, hydrofluoric acid, and live steam caused lacrimation, conjunctivitis, shortness of breath, paroxysmal cough, rales in the chest, nausea, vomiting, skin burns, transitory albuminuria, and elevation of blood urea nitrogen. The persons having the greatest exposure showed the highest urinary uranium levels; in addition, their urinary abnormalities were the most severe; these were albuminuria plus red cells and casts in the urinary sediment. Blood urea nitrogen remained elevated for several weeks. The injurious effects observed on the skin, eyes, and respiratory tract apparently were caused by the irritant action of the fluoride ion, whereas the uranium was responsible for the transient renal changes. No evidence of chronic toxicity, either chemical or radiation, was observed for any uranium compound during the first 6 years of the atomic energy program; all exposed workers were under very close medical surveillance. Soluble uranium compounds tested on the eyes of animals caused severe eye damage as well as systemic poisoning; the anion and its hydrolysis products determine the degree of injury. A hot nitric acid solution of uranyl nitrate spilled on the skin caused skin burns, nephritis, and encephalopathy. Prolonged skin contact with uranium compounds should be avoided because of potential radiation damage to basal cells; dermatitis has occurred as a result of handling uranium hexafluoride.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Uranium hexafluoride**

1. Molecular weight: 352
2. Boiling point (760 mm Hg): 56 C (133 F) (sublimes)
3. Specific gravity (water = 1): 4.68
4. Vapor density (air = 1 at boiling point of uranium hexafluoride): 12 (approximately)
5. Melting point: 65 C (149 F)
6. Vapor pressure at 20 C (68 F): 109 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Reacts
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Uranyl nitrate**

1. Molecular weight: 502.1
2. Boiling point (760 mm Hg): 118 C (244 F)
3. Specific gravity (water = 1): 2.8
4. Vapor density (air = 1 at boiling point of uranyl nitrate): Not applicable
5. Melting point: 60.2 C (140 F) (loses water)
6. Vapor pressure at 20 C (68 F): None, except water of crystallization
7. Solubility in water, g/100 g water at 20 C (68 F): 67
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Uranyl sulfate**

1. Molecular weight: 420.1
2. Boiling point (760 mm Hg): Decomposes at 100 C (212 F) (loses water)
3. Specific gravity (water = 1): 3.3
4. Vapor density (air = 1 at boiling point of uranyl sulfate): Not applicable
5. Melting point: 100 C (212 F) (loses water)
6. Vapor pressure at 20 C (68 F): None, except water of crystallization
7. Solubility in water, g/100 g water at 20 C (68 F): 70
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability. None hazardous
2. Incompatibilities: Contact of uranyl nitrate with combustible material may cause fires and explosions. Uranium hexafluoride reacts with water to form hydrofluoric acid, a very corrosive substance.
3. Hazardous decomposition products: Toxic gases

and vapors (such as oxides of nitrogen and hydrofluoric acid) may be released in a fire involving soluble uranium compounds.

4. Special precautions: Uranium hexafluoride will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Not combustible

• **Warning properties**

Grant states that "several uranium compounds tested by dropping on the eyes of rabbits, guinea pigs, and rats have been found to cause severe eye damage as well as systemic poisoning. Compounds which have been found to cause moderately severe injury of the eyes are uranium pentachloride, uranium tetrachloride, uranyl nitrate, (and) uranyl fluoride . . . . Application of 1 mg of solid uranium pentachloride to the eyes of rabbits caused the most severe necrosis of conjunctivae and lids, and perforating ulceration of the cornea. The other chlorides and the nitrate were also severely damaging."

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

At the time of publication of this guideline, no measurement method for soluble uranium compounds had been published by NIOSH.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with solids or liquids containing uranium hexafluoride.

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with solids or liquids containing soluble uranium compounds.

• If employees' clothing has had any possibility of being contaminated with uranium hexafluoride, or if employees' clothing may have become contaminated with other soluble uranium compounds, employees should change into uncontaminated clothing before leaving the work premises.

• Clothing which has had any possibility of being contaminated with uranium hexafluoride or clothing contaminated with other soluble uranium compounds should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of soluble uranium compounds from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the soluble uranium compounds, the person performing the operation should be informed of soluble uranium compounds's hazardous properties.

• Where there is any possibility of exposure of an employee's body to solids or liquids containing uranium hexafluoride, facilities for quick drenching of the body should be provided within the immediate work area for emergency use.

• Non-impervious clothing which becomes contaminated with uranium hexafluoride should be removed immediately and non-impervious clothing which becomes contaminated with other soluble uranium compounds should be removed promptly and not reworn until the soluble uranium compounds are removed from the clothing.

• Employees should be provided with and required to use dust- and splash-proof safety goggles where there is any possibility of solids or liquids containing soluble uranium compounds contacting the eyes.

• Where there is any possibility that employees' eyes may be exposed to solids or liquids containing soluble uranium compounds, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

• Skin that becomes contaminated with uranium hexafluoride should be immediately washed or showered and skin that becomes contaminated with soluble uranium compounds should be promptly washed or showered to remove any soluble uranium compounds.

• Workers subject to skin contact with solids or liquids containing uranium hexafluoride should wash any areas of the body which may have contacted uranium hexafluoride at the end of each work day.
• Eating and smoking should not be permitted in areas where solids or liquids containing soluble uranium compounds are handled, processed, or stored.
• Employees who handle solids or liquids containing soluble uranium compounds should wash their hands thoroughly before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to soluble uranium compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during mining and purification of ore, during enrichment of elemental uranium; from recovery of process waste	Process enclosure; local exhaust ventilation; personal protective equipment
Use in fabrication of materials for military use and power plants	Process enclosure; local exhaust ventilation; personal protective equipment
Use as analytical reagents; use in chemical synthesis; use in manufacture of dyestuff intermediates and preparation of oxides	Process enclosure; local exhaust ventilation; personal protective equipment
Use in manufacture of ceramic glazes; use as photographic intensifiers and in x-ray technology; in miscellaneous uses for textile printing, tobacco printing, antifungal agents, electroplating additives, and bacterial oxidants	Process enclosure; local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Eye Exposure**
If solids or liquids containing soluble uranium compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with these chemicals.
• **Skin Exposure**
If solids or liquids containing soluble uranium compounds get on the skin, immediately flush the contaminated skin with water. If solids or liquids containing soluble uranium compounds penetrate through the clothing, remove the clothing immediately and flush the skin with water. If irritation is present after washing, get medical attention.
• **Breathing**
If a person breathes in large amounts of soluble uranium compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Swallowing**
When solids or liquids containing soluble uranium compounds have been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If soluble uranium compounds are spilled, the following steps should be taken:
1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner and deposit in sealed containers for reclamation or for disposal in a secured sanitary landfill. Liquid containing soluble uranium compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Uranium and Compounds as U," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• American Industrial Hygiene Association: "Uranium (Natural) and Its Compounds," *Hygienic Guide Series*, Detroit, Michigan, 1969.

• Archer, V. E., et al.: "Cancer Mortality Among Uranium Mill Workers," *Journal of Occupational Medicine*, 15:11-14, 1973.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saundefs, Philadelphia, 1960.

• Neuman, W. F.: "Urinary Uranium as a Measure of Exposure Hazard," *Industrial Medicine and Surgery*, 19:4, pp. 185-191, April 1950.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Schwartz, L., Tulipan, L., and Birmingham, D.: *Occupational Diseases of the Skin* (3rd ed. rev.), Lea and Febiger, Philadelphia, 1957.

• Spector, W. S. (Vols. I, II), Negherbon, W. O. (Vol. III), Grebe, R. M. (Vol. IV), and Dittmer, D. S. (Vol. V) (eds.): *Handbook of Toxicology*, Saunders, Philadelphia, 1956-1959.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Voegtlin, C., and Hodge, H. C.: *Pharmacology and Toxicology of Uranium Compounds*, Vol. 2, McGraw Hill, New York, 1949.

-1509

RESPIRATORY PROTECTION FOR URANIUM SOLUBLE COMPOUNDS (AS URANIUM)

Condition	Minimum Respiratory Protection* Required Above 0.05 mg/m³
Particulate Concentration	
2.5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece (not applicable for uranium halides). A chemical cartridge respirator with a full facepiece, acid gas cartridge(s), and high efficiency particulate filter (for uranium halides only). A gas mask with a chin-style or a front- or back-mounted acid gas canister and high efficiency particulate filter (for uranium halides only). Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
20 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter (not applicable for uranium halides). A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 20 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator with acid gas cartridge for uranium halides. Any gas mask providing protection against acid gases and particulates (for uranium halides only). Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Vanadium Pentoxide Dust

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: V_2O_5
- Synonyms: None
- Appearance and odor: Yellow-orange powder or dark gray flakes with no odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for vanadium pentoxide dust is a ceiling of 0.5 milligrams of vanadium pentoxide dust per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be reduced to a ceiling level of 0.05 mg/m^3 averaged over a 15-minute period. The NIOSH Criteria Document for Vanadium should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Vanadium pentoxide dust can affect the body if it is inhaled or if it comes in contact with the eyes or skin. It can also affect the body if it is swallowed.

- **Effects of overexposure**

1. Short-term Exposure: Vanadium pentoxide dust may cause irritation of the eyes, nose, throat, and respiratory tract. It may also cause bronchitis with wheezing and chest pain. A greenish discoloration of the tongue may occur.

2. Long-term Exposure: After symptoms have occurred following short-term exposure, repeated exposure may cause more severe symptoms of the same nature. In addition, repeated exposure may cause chronic bronchitis. Repeated or prolonged exposure may also cause an allergic skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to vanadium pentoxide dust.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to vanadium pentoxide dust at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes and respiratory system should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Vanadium pentoxide dust may cause respiratory impairment. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Vanadium pentoxide dust is reported to cause asthmatic-like symptoms. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing. Vanadium in the urine may be evidence of absorption and excretion of this element since vanadium is not normally found in human urine.

- **Summary of toxicology**

Vanadium pentoxide dust is a respiratory and eye irritant. Sixteen workers exposed to concentrations of dust (and possibly some fume) in excess of 0.5 mg/m^3 with a mean particle size in the micron and submicron range developed conjunctivitis, nasopharyngitis, hacking cough, fine rales, and wheezing; in three workers exposed to the highest concentrations, the onset of symptoms occurred at the end of the first workday. The

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1523

bronchospastic element in the more seriously ill persisted for 48 hours after removal from exposure; rales lasted for 3 to 7 days, and in several cases cough lasted for up to 14 days. Among those with acute intoxication there was increased severity of symptoms from subsequent exposures of lesser time and intensity. Urinary vanadium excretion was detectable in 12 of the workers for periods of up to 2 weeks; vanadium in the urine may be evidence of absorption and excretion of this element, since vanadium is not ordinarily found in human urine. Workers exposed to a mixture of ammonium metavanadate and vanadium pentoxide at concentrations near 0.25 mg/m³ developed green tongue, metallic taste, throat irritation, and cough. Another report of 36 workers examined 8 years after an acute respiratory reaction from vanadium pentoxide exposure indicated no evidence of either pneumoconiosis or emphysema, although six still had bronchitis with rhonchi resembling asthma and bouts of dyspnea. Two volunteers exposed to a concentration of 1 mg/m³ for 8 hours developed a persistent cough which lasted for 8 days; 21 days after the original exposure, re-exposure for 5 minutes to a heavy cloud of vanadium pentoxide dust occurred, and within 16 hours marked cough developed; the following day, rales and expiratory wheezes were present throughout the entire lung field, but pulmonary functions were normal. Subjects exposed to a concentration of 0.2 mg/m³ for 8 hours developed a loose cough the following morning; others exposed for 8 hours to 0.1 mg/m³ developed slight cough with increased mucus which lasted 3 to 4 days. Both eyes and skin are irritated by the dust or by contact with an acid solution of vanadium pentoxide; eczematous lesions have occurred, and in three cases there was an allergic response to patch tests with sodium vanadate.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 181.9
  2. Boiling point (760 mm Hg): 1750 C (3182 F) (decomposes)
  3. Specific gravity (water = 1): 3.36
  4. Vapor density (air = 1 at boiling point of vanadium pentoxide dust): Not applicable
  5. Melting point: 690 C (1274 F)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.1
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

According to Grant, vanadium pentoxide dust "causes a sensation of burning and irritation of the eyes, and signs of conjunctivitis . . . ." The eye irritation is accompanied by "irritation of the nose and throat. The respiratory irritation occurs at lower concentrations than does the ocular irritation. The local effects on the eye have also been observed in rabbits." The *Documentation of TLV's* states that "Gulko referred to eye and bronchial irritation from exposure at 0.5 to 2.2 mg/m³."

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of vanadium pentoxide dust. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vanadium pentoxide dust on a mixed cellulose ester membrane filter, followed by chemical treatment and atomic desorption spectrophotometric analysis. An analytical method for vanadium pentoxide dust is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1). ical Methods for Set 1" (order number PB 271 712).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

1523

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with vanadium pentoxide dust.
- Non-impervious clothing which becomes contaminated with vanadium pentoxide dust should be removed promptly and not reworn until the vanadium pentoxide dust is removed from the clothing.
- Clothing contaminated with vanadium pentoxide dust should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of vanadium pentoxide dust from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the vanadium pentoxide dust, the person performing the operation should be informed of vanadium pentoxide dust's hazardous properties.
- Employees should be provided with and required to use dust-resistant safety goggles where vanadium pentoxide dust may contact the eyes.

SANITATION

- Skin that becomes contaminated with vanadium pentoxide dust should be promptly washed or showered to remove any vanadium pentoxide dust.
- Eating and smoking should not be permitted in areas where vanadium pentoxide dust is generated in the handling, processing, or storing of vanadium pentoxide.
- Employees who handle vanadium pentoxide dust should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to vanadium pentoxide dust may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from cleaning and maintenance of furnaces, boilers, and gas turbines	Local exhaust ventilation; personal protective equipment
Liberation from mining and processing of ores; extraction from slag	Process enclosure; local exhaust ventilation (if possible); personal protective equipment
Liberation from use as a catalyst in the preparation of organic and inorganic compounds	Process enclosure; local exhaust ventilation (if possible); personal protective equipment
Liberation from chemical synthesis; use in manufacture of ultraviolet filter glass to prevent radiation injury and fading of fabrics	Process enclosure; local exhaust ventilation (if possible); personal protective equipment
Liberation from use in manufacture of afterburners for automobiles	Process enclosure; local exhaust ventilation (if possible); personal protective equipment
Liberation from use in textile industry as a catalyst to yield intensive black dyes; use in printing industry as a catalyst for formation of resinous black pigments from tar oils	Local exhaust ventilation
Liberation from use in ceramics industry in manufacture of ceramic pigments	Process enclosure; local exhaust ventilation
Liberation from use as a component of special steels in electric furnace steels, welding rods, and permanent magnets	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If vanadium pentoxide dust gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation persists after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If vanadium pentoxide dust gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If vanadium pentoxide dust penetrates through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

- **Breathing**

If a person breathes in large amounts of vanadium pentoxide dust, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When vanadium pentoxide dust has been swallowed, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If vanadium pentoxide is spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation, or for disposal in a secured sanitary landfill.

• Waste disposal method:

Vanadium pentoxide dust may be disposed of in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Vanadium V," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Vanadium Pentoxide," *Hygienic Guide Series*, Detroit, Michigan, 1957.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Hudson, T. G. F.: *Vanadium, Toxicology and Biological Significance*, Elsevier, New York, 1964.

• Hunter, D.: *Diseases of Occupations* (4th ed.), Little, Brown, Boston, 1969.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Vanadium*, HEW Publication No. (NIOSH) 77-222, U.S. Government Printing Office, Washington, D.C., 1977.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Sjoberg, S. G.: "Health Hazards in the Production and Handling of Vanadium Pentoxide," *Industrial Hygiene and Occupational Medicine*, 3:631, 1951.

• Stauden, A. (exec. ed.): *Kirk-Othmer Encyclopedia of Chemical Technology* (2nd ed.), Interscience, New York, 1972.

• Zenz, C., and Berg, B. A.: "Human Responses to Controlled Vanadium Pentoxide Exposure," *Archives of Environmental Health*, 14:709-712, 1967.

• Zenz, C., et al.: "Acute Vanadium Pentoxide Intoxication," *Archives of Environmental Health*, 5:542-546, 1962.

RESPIRATORY PROTECTION FOR VANADIUM PENTOXIDE DUST

Condition	Minimum Respiratory Protection* Required Above 0.05 mg/m³
Particulate Concentration	
25 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
70 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 70 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Vanadium Pentoxide Fume

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: V_2O_5
- Synonyms: None
- Appearance: Finely divided particulates dispersed in air.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for vanadium pentoxide fume is a ceiling of 0.1 milligrams of vanadium pentoxide fume per cubic meter of air (mg/m³). NIOSH has recommended that the permissible exposure limit be reduced to a ceiling level of 0.05 mg/m³ averaged over a 15-minute period. The NIOSH Criteria Document for Vanadium should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Vanadium pentoxide fume can affect the body if it is inhaled or if it comes in contact with the eyes.

- **Effects of overexposure**

1. Short-term Exposure: Vanadium pentoxide fume may cause irritation of the eyes, nose, throat, and respiratory tract. It may also cause bronchitis with wheezing and chest pain. A greenish discoloration of the tongue may occur.

2. Long-term Exposure: After symptoms have occured following acute exposure, repeated exposure may cause more severe symptoms of the same nature. In addition, repeated exposure may cause chronic bronchitis. Repeated or prolonged exposure may cause an allergic skin rash.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to vanadium pentoxide fume.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to vanadium pentoxide fume at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the eyes and respiratory system should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Vanadium pentoxide fume may cause respiratory impairment. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Vanadium pentoxide fume is reported to cause asthmatic-like symptoms. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing.

- **Summary of toxicology**

Vanadium pentoxide fume is a respiratory and eye irritant; the fume is recognized as being generally more toxic than dust of larger particle size, so similar effects from fume could be expected at lower concentrations. Sixteen workers exposed to concentrations of dust (and possibly some fume) in excess of 0.5 mg/m³ with a mean particle size in the micron and submicron range developed conjunctivitis, nasopharyngitis, hacking cough, fine rales, and wheezing; in three workers exposed to the highest concentrations, the onset of symptoms occurred at the end of the first workday. The

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

bronchospastic element in the more seriously ill persisted for 48 hours after removal from exposure; rales lasted for 3 to 7 days, and in several cases cough lasted for up to 14 days. Among those with acute intoxication there was increased severity of symptoms from subsequent exposures of lesser time and intensity. Urinary vanadium excretion was detectable in 12 of the workers for periods of up to 2 weeks; vanadium in the urine may be evidence of absorption and excretion of this element, since it is not ordinarily found in human urine. Workers exposed to a mixture of ammonium metavanadate and vanadium pentoxide at concentrations near 0.25 mg/m³ developed green tongue, metallic taste, throat irritation, and cough. Another report of 36 workers examined 8 years after an acute respiratory reaction from vanadium pentoxide exposure indicated no evidence of either pneumoconiosis or emphysema, although six still had bronchitis with rhonchi resembling asthma and bouts of dyspnea. Two volunteers exposed to dust at a concentration of 1 mg/m³ for 8 hours developed persistent cough which lasted for 8 days; 21 days after the original exposure, re-exposure for 5 minutes to a heavy cloud of vanadium pentoxide dust occurred, and within 16 hours marked cough developed; the following day, rales and expiratory wheezes were present throughout the entire lung field, but pulmonary functions were normal. Subjects exposed to dust at a concentration of 0.2 mg/m³ for 8 hours developed a loose cough the following morning; others exposed for 8 hours to 0.1 mg/m³ developed slight cough with increased mucus which lasted 3 to 4 days. Both eyes and skin are irritated by the dust or by contact with an acid solution of vanadium pentoxide; eczematous lesions have occurred, and in three cases there was an allergic response to patch tests with sodium vanadate.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 181.9
  2. Boiling point (760 mm Hg): 1750 C (3182 F) (for solid)
  3. Specific gravity (water = 1): 3.36 (for solid)
  4. Vapor density (air = 1 at boiling point of vanadium pentoxide fume): Not applicable
  5. Melting point: 690 C (1274 F) (for solid)
  6. Vapor pressure at 20 C (68 F): Essentially zero
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.1
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

By analogy to vanadium pentoxide dust, which "causes a sensation of burning and irritation of the eyes and signs of conjunctivitis," according to Grant, vanadium pentoxide fume is treated as an eye irritant for the purposes of this guideline. The *Documentation of TLV's* states that "Gulko referred to eye . . . irritation from exposures at 0.5 to 2.2 mg/m³" V_2O_5 dust.

MONITORING AND MEASUREMENT PROCEDURES

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of vanadium pentoxide fume. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of vanadium pentoxide fume on a mixed cellulose ester membrane filter, followed by chemical treatment and atomic desorption spectrophotometric analysis. An analytical method for vanadium pentoxide fume is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 5, 1979, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00349-1).

• Zenz, C., and Berg, B. A.: "Human Responses to Controlled Vanadium Pentoxide Exposure." *Archives of Environmental Health*, 14:709-712, 1967.

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with vanadium pentoxide fume.
• Employees should be provided with and required to use dust-resistant safety goggles where vanadium pentoxide fume may contact the eyes.

SANITATION

• Eating and smoking should not be permitted in areas where vanadium pentoxide fume is generated in the handling, processing, or storing of vanadium pentoxide.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to vanadium pentoxide fume may occur and control methods which may be effective in each case:

Operation	Controls
Liberation from production of pellets from electric furnaces	Local exhaust ventilation; personal protective equipment
Liberation from fabrication of alloys for use as an additive in special steels	Local exhaust ventilation; personal protective equipment
Liberation from metallurgical processes in furnaces	Process enclosure
Liberation from manufacture of semiconductors fused with sodium oxide	Process enclosure; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.
• **Breathing**
If a person breathes in large amounts of vanadium pentoxide fume, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
• **Rescue**
Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.
• If potentially hazardous amounts of vanadium pentoxide fume are inadvertently released, ventilate the area of the release to disperse the fume.

ADDITIONAL INFORMATION

To find additional information on vanadium pentoxide fume, look up vanadium pentoxide fume in the following documents:
• Medical Surveillance for Chemical Hazards
• Respiratory Protection for Chemical Hazards
• Personal Protection and Sanitation for Chemical Hazards
• NIOSH Criteria Document for Vanadium (August 1977)
These documents are available through the NIOSH Division of Technical Services, 4676 Columbia Parkway, Cincinnati, Ohio 45226.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Vanadium V," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• American Industrial Hygiene Association: "Vanadium Pentoxide," *Hygienic Guide Series*, Detroit, Michigan, 1957.
• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.
• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Hudson, T. G. F.: *Vanadium, Toxicology and Biological Significance*, Elsevier, New York, 1964.
• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Vanadium*, HEW Publication No. (NIOSH) 77-222, U.S. Government Printing Office, Washington, D.C., 1977.
• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.
• Zenz, C., and Berg, B. A.: "Human Responses to Controlled Vanadium Pentoxide Exposure," *Archives of EnviroHealth*, 14:709-712, 1967.
• Zenz, C., et al.: "Acute Vanadium Pentoxide Intoxication," *Archives of Environmental Health*, 5:542-546, 1962.

RESPIRATORY PROTECTION FOR VANADIUM PENTOXIDE FUME

Condition	Minimum Respiratory Protection* Required Above 0.05 mg/m³
Particulate Concentration	
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
70 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter. A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 70 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Vinyl Toluene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $CH_3C_6H_4CH=CH_2$
- Synonyms: Methylstyrene; tolylethylene; meta- and para-vinyltoluene (mixed isomers)
- Appearance and odor: Colorless liquid with a strong, disagreeable odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for vinyl toluene is 100 parts of vinyl toluene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 480 milligrams of vinyl toluene per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for vinyl toluene from 100 ppm to 50 ppm.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Vinyl toluene can affect the body if it is inhaled, is swallowed, or comes in contact with the eyes or skin.

- **Effects of overexposure**

1. Short-term Exposure: Vinyl toluene may cause irritation of the nose, throat, eyes, and skin. It may also cause drowsiness.

2. Long-term Exposure: Repeated exposure may cause irritation of the skin.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to vinyl toluene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to vinyl toluene at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from vinyl toluene exposure.

—Kidney disease: Although vinyl toluene is not known as a kidney toxin in humans, the importance of this organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of vinyl toluene might cause exacerbation of symptoms due to its irritant properties or psychic reflex bronchospasm.

—Liver disease: Although vinyl toluene is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

—Skin disease: Vinyl toluene is a defatting agent and can cause dermatitis on prolonged exposure. Persons with pre-existing skin disorders may be more susceptible to the effects of this agent.

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

- **Summary of toxicology**

The main toxic effect of vinyl toluene is irritation of the eyes, upper respiratory tract, and skin. With prolonged and repeated contact and absorption of high doses, there may be depression of the central nervous system.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1531

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 118
  2. Boiling point (760 mm Hg): 168 C (334 F)
  3. Specific gravity (water = 1): 0.92
  4. Vapor density (air = 1 at boiling point of vinyl toluene): 4.1
  5. Melting point: −77 C (−106 F)
  6. Vapor pressure at 20 C (68 F): 1.1 mm Hg
  7. Solubility in water, g/100 g water at 20 C (68 F): 0.009
  8. Evaporation rate (butyl acetate = 1): Less than 0.5
- **Reactivity**
  1. Conditions contributing to instability: Vinyl toluene is stabilized by a polymerization inhibitor (10 to 50 ppm of tert-butylcatechol). If this is not present in adequate concentrations, vinyl toluene can polymerize and explode in the container.
  2. Incompatibilities: Contact with oxidizing agents may cause fires and explosions. Also, catalysts for vinyl polymerization, such as peroxides, strong acids, and aluminum chloride should be avoided.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving vinyl toluene.
  4. Special precautions: None
- **Flammability**
  1. Flash point: 53 C (127 F) (closed cup)
  2. Autoignition temperature: 495 C (923 F)
  3. Flammable limits in air, % by volume: Lower: 0.1; Upper: 11
  4. Extinguishant: Dry chemical, carbon dioxide, or foam.
- **Warning properties**
  1. Odor Threshold: No quantitative information is available concerning the odor threshold of vinyl toluene.
  2. Irritation Levels: According to the ILO, vinyl toluene "gives rise to irritation of the nasal and conjunctival mucosae at 400 ppm and is detectable at 50 ppm."
  3. Evaluation of Warning Properties: Since the ILO reports that vinyl toluene is detectable at a concentration below the permissible exposure limit, it is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of vinyl toluene vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure vinyl toluene may be used. An analytical method for vinyl toluene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 2, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00260-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid vinyl toluene.
- Clothing wet with liquid vinyl toluene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of vinyl toluene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the vinyl toluene the person performing the operation should be informed of vinyl toluene's hazardous properties.
- Non-impervious clothing which becomes contaminated with liquid vinyl toluene should be removed promptly and not reworn until the vinyl toluene is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where liquid vinyl toluene may contact the eyes.

SANITATION

-1532

• Skin that becomes contaminated with liquid vinyl toluene should be promptly washed or showered with soap or mild detergent and water to remove any vinyl toluene.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to vinyl toluene may occur and control methods which may be effective in each case:

Operation	Controls
Use during spray applications of vinyl toluene polyester surface coatings	Local downdraft ventilation; personal protective equipment
Liberation during preparation of unsaturated polyester resins and alkyd coatings	Local downdraft ventilation
Use during application of specialty paints and varnishes	Local exhaust ventilation; personal protective equipment
Liberation during manufacture of thermoplastic moldings via extrusion, injection, stamping, or other processes	Local downdraft ventilation; general dilution ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If vinyl toluene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If vinyl toluene gets on the skin, promptly flush the contaminated skin with water. If vinyl toluene soaks through the clothing, remove the clothing immediately and flush the skin with water. When there is skin irritation, get medical attention.

• **Breathing**

If a person breathes in large amounts of vinyl toluene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

If vinyl toluene has been swallowed, do not induce vomiting. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If vinyl toluene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber. Combustion may be improved by mixing with a flammable liquid. Vinyl toluene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

• Waste disposal methods:

Vinyl toluene may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary landfill.
2. By atomizing in a suitable combustion chamber. Combustion may be improved by mixing with a flammable liquid.

REFERENCES

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Dow Chemical Company: *Material Safety Data Sheet – Vinyl Toluene*, Midland, Michigan.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Wolf, M. A., et al.: "Toxicological Studies of Certain Alkylated Benzenes and Benzene," *Archives of Industrial Health*, 14:387-398, 1956.

RESPIRATORY PROTECTION FOR VINYL TOLUENE

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
400 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s).** Any supplied-air respirator.** Any self-contained breathing apparatus.**
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
Greater than 5000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

**If eye irritation occurs, full-facepiece respiratory protective equipment should be used.

Occupational Health Guideline for Warfarin

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_{19}H_{16}O_4$
- Synonyms: 3-(alpha-Acetonylbenzyl)-4-hydroxycoumarin; WARF compound; compound 42; coumadin
- Appearance and odor: Colorless, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for warfarin is 0.1 milligram of warfarin per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Warfarin can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Repeated exposure to warfarin may cause bleeding difficulties by impairing the clotting ability of the blood. Problems which may occur include easy bruising, nose bleeds, vomiting blood, bloody or tar-like stools, and bloody urine. A single large dose has been reported to be capable of causing bleeding problems after several days' delay.

- **Reporting signs and symptoms:**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to warfarin.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to warfarin at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Persons with a history of blood disorders with bleeding tendencies would be expected to be at increased risk from exposure. Examination of the blood should be stressed.

—A complete blood count: Warfarin has been shown to cause hypoprothrombinemia in humans. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Prothrombin time: Warfarin has been shown to cause hypoprothrombinemia in humans. A quick 1-stage prothrombin time or a thrombotest should be performed.

—Urinalysis: Warfarin has been shown to cause an increased bleeding tendency. A urinalysis should be obtained with emphasis on examination for red blood cells as an early indicator of internal bleeding.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis.

- **Summary of toxicology**

Warfarin as the dust or in solution causes hypoprothrombinemia and vascular injury which results in internal hemorrhage. It suppresses the hepatic formation of prothrombin and of factors VII, IX, and X, causing a markedly reduced prothrombin activity of the blood; it also causes dilation and engorgement of blood vessels and an increase in capillary fragility. The inhibition of prothrombin formation does not become apparent until the prothrombin reserves are depleted, which usually requires exposure for a number of days. A single large

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1535

exposure may cause intoxication after a latency period of several days, but in a series of acute ingestion episodes there were no signs of hemorrhage or depression of plasma prothrombin. A farmer whose hands were intermittently wetted with a 0.5% solution of warfarin over a period of 24 days developed gross hematuria 2 days after the last contact with the solution; the following day, spontaneous hematomas appeared on the arms and legs. Within 4 days, there was also epistaxis, punctate hemorrhages of the palate and mouth, and bleeding from the lower lip. The bleeding time was over 30 minutes; the clotting time, 11 minutes, 30 seconds; prothrombin index, 17; and the prothrombin percentage (thrombotest), 5. Four days later, after treatment for 2 days with phytonadione, the values were in the normal range. Other effects of warfarin intoxication have included back pain, abdominal pain, vomiting, melena, and petechiae of the skin.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 308.3
  2. Boiling point (760 mm Hg): Decomposes
  3. Specific gravity (water = 1): Greater than 1
  4. Vapor density (air = 1 at boiling point of warfarin): Not applicable
  5. Melting point: 161 C (322 F)
  6. Vapor pressure at 20 C (68 F): Data not available
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None.
  2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
  3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving warfarin.
  4. Special precautions: None.
- **Flammability**
  1. Flash point: Not applicable
  2. Autoignition temperature: Data not available
  3. Flammable limits in air, % by volume: Data not available
  4. Extinguishant: Foam, carbon dioxide, dry chemical
- **Warning properties**

Warfarin is not known to be an eye irritant. It has produced hemorrhages in the retina, however, through its systemic toxicity (Grant).

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

An analytical method for warfarin is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 6, 1980, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00369-6).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with warfarin or liquids containing warfarin.
- If employees' clothing has had any possibility of being contaminated with warfarin or liquids containing warfarin, employees should change into uncontaminated clothing before leaving the work premises.
- Clothing contaminated with warfarin should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of warfarin from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the warfarin, the person performing the operation should be informed of warfarin's hazardous properties.
- Non-impervious clothing which becomes contaminated with warfarin should be removed promptly and not reworn until the warfarin is removed from the clothing.

SANITATION

• Skin that becomes contaminated with warfarin should be promptly washed or showered with soap or mild detergent and water to remove any warfarin.
• Eating and smoking should not be permitted in areas where warfarin or liquids containing warfarin are handled, processed, or stored.
• Employees who handle warfarin or liquids containing warfarin should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to warfarin may occur and control methods which may be effective in each case:

Operation	Controls
Application as a rodenticide	General dilution ventilation; personal protective equipment
Formulation of rodenticides	Local exhaust ventilation; general dilution ventilation; personal protective equipment
Manufacture of warfarin	Personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If warfarin dust gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with this chemical.

• **Skin Exposure**

If warfarin or liquids containing warfarin get on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If warfarin or liquids containing warfarin penetrate through the clothing, remove the clothing promptly and wash the skin using soap or mild detergent and water. Get medical attention promptly.

• **Breathing**

If a person breathes in large amounts of warfarin, move the exposed person to fresh air at once. If breathing has stopped perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When warfarin has been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.
• If warfarin is spilled, the following steps should be taken:
1. Ventilate area of spill.
2. For small quantities, sweep onto paper or other suitable material, place in an appropriate container and burn in a safe place (such as a fume hood). Large quantities may be reclaimed; however, if this is not practical, dissolve in a flammable solvent (such as alcohol) and atomize in a suitable combustion chamber.
• Waste disposal methods:
Warfarin may be disposed of:
1. By making packages of warfarin in paper or other flammable material and burning in a suitable combustion chamber.
2. By dissolving warfarin in a flammable solvent (such as alcohol) and atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Warfarin," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.
• Fristedt, B., and Sterner, N.: "Warfarin Intoxication from Percutaneous Absorption," *Archives of Environmental Health*, 11:205-208, 1965.
• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products* (3rd ed.), Williams and Wilkins, Baltimore, 1969.
• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.
• Hayes, W. J., Jr.: *Clinical Handbook on Economic Poisons, Emergency Information for Treating Poisoning*, U.S. Public Health Service Publication No. 476, U.S. Government Printing Office, Washington, D.C., 1963.
• Holvey, D. N. (ed.): *The Merck Manual of Diagnosis and Therapy* (12th ed.), Merck and Company, Inc., Rahway, New Jersey, 1972.
• International Labour Office: *Encyclopedia of Occupa-*

tional Health and Safety, McGraw-Hill, New York, 1971.
• Johnstone, R. T., and Miller, S. E.: *Occupational Disease and Industrial Medicine*, Saunders, Philadelphia, 1960.
• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.
• Spencer, E. Y.: *Guide to the Chemicals Used in Crop Protection* (6th ed.), Publication 1093, Research Branch Agriculture, Canada, 1973.
• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.
• Thienes, C. H., and Haley, T. J.: *Clinical Toxicology* (5th ed.), Lea and Febiger, Philadelphia, 1972.

RESPIRATORY PROTECTION FOR WARFARIN

Condition	Minimum Respiratory Protection* Required Above 0.1 mg/m³
Particulate Concentration	
0.5 mg/m³ or less	Any dust respirator, except single-use.
1 mg/m³ or less	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
5 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
100 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
200 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 200 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any dust respirator, except single-use. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Xylene

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $C_6H_4(CH_3)_2$
- Synonyms: Commercial xylene (xylol) is a mixture, mostly the meta-isomer. 1) O-xylene, ortho-xylene, 1,2-dimethylbenzene; 2) m-xylene, meta-xylene, 1,3-dimethylbenzene; 3) p-xylene, para-xylene, 1,4-dimethylbenzene
- Appearance and odor: Colorless liquids with aromatic odors (pure p-xylene is a solid below 12.7 C (55 F)).

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for xylene is 100 parts of xylene per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 435 milligrams of xylene per cubic meter of air (mg/m^3). NIOSH has recommended that the permissible exposure limit be changed to 100 ppm averaged over a work shift of up to ten hours per day, forty hours per week, with an acceptable ceiling level of 200 ppm averaged over a 10-minute period. The NIOSH Criteria Document for Xylene should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Xylene can affect the body if it is inhaled, if it comes in contact with the eyes or skin, or if it is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

1. Short-term Exposure: Xylene vapor may cause irritation of the eyes, nose, and throat. At high concentrations, xylene vapor may cause severe breathing difficulties which may be delayed in onset. At high concentrations, it may also cause dizziness, staggering, drowsiness, and unconsciousness. In addition, breathing high concentrations may cause loss of appetite, nausea, vomiting, and abdominal pain. Liquid xylene may be irritating to the eyes and skin. Exposure to high concentrations of xylene vapor may cause reversible damage to the kidneys and liver.

2. Long-term Exposure: Repeated or prolonged exposure to xylene may cause a skin rash. Repeated exposure of the eyes to high concentrations of xylene vapor may cause reversible eye damage.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to xylene.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to xylene at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the central nervous system, eyes, gastrointestinal tract, blood, liver, and kidneys should be stressed. The skin should be examined for evidence of chronic disorders.

—A complete blood count: Xylene has been shown to cause reversible hematopoietic depression in animals. A complete blood count should be performed, including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

—Liver function tests: Since liver damage has been observed in humans exposed to xylene, a profile of liver

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

- 1539

function should be obtained by using a medically acceptable array of biochemical tests.

—Urinalysis: Since kidney damage has been observed in humans exposed to xylene, a urinalysis should be obtained to include at a minimum specific gravity, albumin, glucose, and a microscopic on centrifuged sediment.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on a biannual basis.

• **Summary of toxicology**

Xylene vapor irritates the eyes, mucous membranes, and skin; at high concentrations it causes narcosis. In animals, xylene causes blood changes reflecting mild toxicity to the hematopoietic system. Repeated exposure of rabbits to 1150 ppm of a mixture of isomers of xylene for 40 to 55 days caused a reversible decrease in red and white cell count and an increase in thrombocytes; exposure to 690 ppm for the same time period caused only a slight decrease in the white cell count. Three painters working in a confined space of a fuel tank were overcome by xylene vapors estimated to be 10,000 ppm; they were not found until 18.5 hours after entering the tank, and one died from pulmonary edema shortly thereafter; the other two recovered completely in 2 days; both had temporary hepatic impairment (inferred from elevated serum transaminase levels) and one of them had evidence of temporary renal impairment (increased blood urea and reduced creatinine clearance). In humans, exposure to undetermined but high concentrations caused dizziness, excitement, drowsiness, incoordination and a staggering gait. Workers exposed to concentrations above 200 ppm complain of anorexia, nausea, vomiting, and abdominal pain. Brief exposure of humans to 200 ppm caused irritation of the eyes, nose, and throat. There are reports of reversible corneal vacuolation in workers exposed to xylene, or to xylene plus other volatile solvents. The liquid is a skin irritant and causes erythema, dryness, and defatting; prolonged contact may cause the formation of vesicles.

CHEMICAL AND PHYSICAL PROPERTIES

Data in the following section are presented for xylene's three isomers: 1) ortho, 2) meta, and 3) para.

• **Physical data**

1. Molecular weight: 106.2
2. Boiling point (760 mm Hg): 1) 144.4 C (292 F); 2) 138.9 C (282 F); 3) 138.3 C (281 F)
3. Specific gravity (water = 1): 1) 0.88; 2) 0.86; 3) 0.86
4. Vapor density (air = 1 at boiling point of xylene): 3.7
5. Melting point: 1) −25 C (−12 F); 2) −48 C (−54 F); 3) 13 C (55 F)
6. Vapor pressure at 20 C (68 F): 1) 7 mm Hg; 2) 9 mm Hg; 3) 9 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): 1) 0.00003; 2) 0.00003; 3) 0.00003
8. Evaporation rate (butyl acetate = 1): 1) 0.7; 2) 0.7; 3) 0.7

• **Reactivity**

1. Conditions contributing to instability: Elevated temperatures may cause containers to burst.
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as carbon monoxide) may be released in a fire involving xylene.
4. Special precautions: Xylene will attack some forms of plastics, rubber, and coatings.

• **Flammability**

1. Flash point: 1) 32 C (90 F) (closed cup); 2) 28.9 C (84 F); 3) 27.2 C (81 F)
2. Autoignition temperature: 1) 465 C (869 F); 2) 530 C (986 F); 3) 530 C (986 F)
3. Flammable limits in air, % by volume: Lower: 1) 1.0; 2) 1.1; 3) 1.1; Upper: 1) 6.0; 2) 7.0; 3) 7.0
4. Extinguishant: Foam, carbon dioxide, dry chemical

• **Warning properties**

1. Odor Threshold: Patty states that "the initial odor of 200 ppm has an intensity of approximately 3 and an irritation value of 1. As in most other instances, olfactory fatigue occurs rapidly and the odor is no longer detected at this concentration."
2. Eye Irritation Level: The AIHA *Hygienic Guide* states that "exposure to vapors at 200 ppm caused eye irritation in most of the persons tested. Lesions in the form of fine vacuoles in the cornea of cats exposed to commercial xylene vapors have been observed."
3. Other Information: The *Handbook of Industrial Organic Chemicals* states that xylene "may be irritating to eyes, nose and throat as exposure exceeds threshold limit." The *Hygienic Guide* notes that 200 ppm causes irritation of the nose and throat.
4. Evaluation of Warning Properties: Through its irritant effects, xylene can be detected within three times the permissible exposure limit. For the purposes of this guideline, therefore, xylene is treated as a material with good warning properties.

MONITORING AND MEASUREMENT PROCEDURES

• **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of xylene. Each measurement

should consist of a ten (10) minute sample or series of consecutive samples totalling ten (10) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

• **Method**

Sampling and analyses may be performed by collection of vapors using an adsorption tube with subsequent desorption with carbon disulfide and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure xylene may be used. An analytical method for xylene is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact with liquid or solid xylene.

• Clothing contaminated with xylene should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of xylene from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the xylene, the person performing the operation should be informed of xylene's hazardous properties.

• Any clothing which becomes wet with liquid xylene should be removed immediately and non-impervious clothing which becomes contaminated with xylene should be removed promptly and not reworn until the xylene is removed from the clothing.

• Employees should be provided with and required to use splash-proof safety goggles where liquid or solid xylene may contact the eyes.

SANITATION

• Skin that becomes contaminated with xylene should be promptly washed or showered with soap or mild detergent and water to remove any xylene.

• Employees who handle liquid or solid xylene should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to xylene may occur and control methods which may be effective in each case:

Operation	Controls
Use as an intermediate during manufacture of plastics, synthetic fibers, and mixed/pure isomers	Process enclosure; local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use as diluent or solvent in surface coatings, printing operations, and manufacture of rubber; degreasing agent in plastics and electronics manufacture; in organic synthesis reactions and manufacture of epoxy resins	Process enclosure; local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use in formulation of insecticides	Process enclosure; local exhaust ventilation; general mechanical ventilation; personal protective equipment
Use in manufacture of xylene-formaldehyde resins; pharmaceuticals, vitamins, leather; and as a sterilizing agent for cat-gut and in microscopy	Process enclosure; local exhaust ventilation; general mechanical ventilation; personal protective equipment

Operation	Controls
Use during blending of motor and aviation fuels	Process enclosure; local exhaust ventilation; general mechanical ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• Eye Exposure

If liquid or solid xylene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

• Skin Exposure

If liquid or solid xylene gets on the skin, promptly wash the contaminated skin using soap or mild detergent and water. If liquid or solid xylene penetrates through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. If irritation is present after washing, get medical attention.

• Breathing

If a person breathes in large amounts of xylene, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• Swallowing

When xylene has been swallowed, do not induce vomiting. Get medical attention immediately.

• Rescue

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.

• If xylene is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources.
2. Ventilate area of spill or leak.
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be reclaimed or collected and atomized in a suitable combustion chamber. Xylene should not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion. Sewers designed to preclude the formation of explosive concentrations of xylene vapors are permitted.
4. If the solid form, allow to melt and treat as in (3) above.

• Waste disposal method:

Xylene may be disposed of by atomizing in a suitable combustion chamber.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Xylene," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Xylene," *Hygienic Guide Series*, Detroit, Michigan, 1971.

• *American National Standard Acceptable Concentrations – Xylene*: ANSI-Z37.10-1971, American National Standards Institute, Inc., New York, 1971.

• American Petroleum Institute: "Xylene," *API Toxicological Reviews*, New York, 1960.

• Browning, E.: *Toxicity and Metabolism of Industrial Solvents*, Elsevier, New York, 1965.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Dow Chemical Company: *Material Safety Data Sheet – Xylene*, Midland, Michigan, 1973.

• Gerarde, H. W.: *Toxicology and Biochemistry of Aromatic Hydrocarbons*, Elsevier, Amsterdam, 1960.

• Gleason, M. N., Gosselin, R. E., Hodge, H. C., and Smith, R. P.: *Clinical Toxicology of Commercial Products5(3rd ed.), Williams and Wilkins, Baltimore, 1969.*

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• *Handbook of Organic Industrial Solvents*, Technical Guide No. 6 (4th ed.), American Mutual Insurance Alliance, Chicago, 1972.

• *Hygienic Information Guide No. 31 – Xylene*, Commonwealth of Pennsylvania, Department of Environmental Resources, Bureau of Occupational Health, 1972.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Xylene*, HEW Publication No. (NIOSH) 75-168, GPO No. 017-033-00075, U.S. Government Printing Office, Washington, D.C., 1975.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

RESPIRATORY PROTECTION FOR XYLENE (XYLOL)

Condition	Minimum Respiratory Protection* Required Above 100 ppm
Vapor Concentration	
1000 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s).
5000 ppm or less	A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
10,000 ppm or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 10,000 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Xylidine

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $(CH_3)_2C_6H_3NH_2$
- Synonyms: 2,4-Dimethylaniline, etc. (6 isomers); xylidine isomers; xylidines mixed o-m-p
- Appearance and odor: Pale yellow to brown liquid with a weak, aromatic amine odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for xylidine is 5 parts of xylidine per million parts of air (ppm) averaged over an eight-hour work shift. This may also be expressed as 25 milligrams of xylidine per cubic meter of air (mg/m^3). The American Conference of Governmental Industrial Hygienists has issued a Notice of Intended Changes of its recommended Threshold Limit Value for xylidine from 5 ppm to 2 ppm with a skin notation.

- Method

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Xylidine can affect the body if it is inhaled, comes in contact with the eyes or skin, or is swallowed. It may enter the body through the skin.

- **Effects of overexposure**

Exposure to xylidine may affect the ability of the blood to carry oxygen normally. The earliest effect may be a bluish discoloration of the skin, especially the lips. If the lack of oxygen becomes severe, a person may have drowsiness, headache, nausea, and vomiting. If oxygen lack is very severe, it may cause unconsciousness and even death. Heart, liver, and kidney damage have occurred in animals exposed to this chemical, but have not been reported in man.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to xylidine.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to xylidine at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the blood, lungs, liver, kidneys, and cardiovascular system should be stressed.

—A complete blood count: Xylidine has been shown to cause methemoglobinemia. Those with blood disorders may be at increased risk from exposure. A complete blood count should be performed including a red cell count, a white cell count, a differential count of a stained smear, as well as hemoglobin and hematocrit.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis. Methemoglobin concentration in blood should be determined when xylidine intoxication is suspected.

- **Summary of toxicology**

Xylidine absorption, whether from inhalation of the vapor or absorption of the liquid through skin, causes anoxia due to the formation of methemoglobin; lung, liver, and kidney damage results in experimental animals. Repeated exposure of cats to 138 ppm caused loss of leg coordination, cyanosis, prostration, and death; at autopsy there was pulmonary edema and lobular pneumonia, necrosis of the liver, and toxic nephrosis. In cats exposed to 132 ppm for 3 days the methemoglobin concentration was 55%; repeated exposure of cats to

These recommendations reflect good industrial hygiene and medical surveillance practices, and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

-1514

17.4 ppm caused toxic hepatitis and some deaths, while repeated exposure to 7.8 ppm caused no adverse effects. Liquid xylidine penetrated the skin of rabbits in sufficient quantity to cause cyanosis and death; there were no local effects on the skin. In humans, the onset of xylidine intoxication may be insidious, in that early warning signs of methemoglobinemia such as headache and dizziness are not always interpreted as being due to overexposure, and even mild cyanosis may not be recognized.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**

1. Molecular weight: 121.2
2. Boiling point (760 mm Hg): 212– 226 C (415–439 F)
3. Specific gravity (water = 1): 1.0
4. Vapor density (air = 1 at boiling point of xylidine): 4.17
5. Melting point: Data not available
6. Vapor pressure at 20 C (68 F): Less than 1 mm Hg
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Data not available

- **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with strong oxidizers may cause fires and explosions. Contact with hypochlorite bleaches may form chloroamines that are explosive substances.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving xylidine.
4. Special precautions: Liquid xylidine will attack some forms of plastics, rubber, and coatings.

- **Flammability**

1. Flash point: 96.7 C (206 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Lower: 1.5 (calculated at flash point)
4. Extinguishant: Carbon dioxide, dry chemical, foam

- **Warning properties**

1. Odor Threshold: May reports an odor threshold of 0.0048 ppm.
2. Eye Irritation Level: Xylidine is not known to be an eye irritant.
3. Evaluation of Warning Properties: Since the odor threshold of xylidine is below the permissible exposure limit, xylidine is treated as a material with adequate warning properties.

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

Sampling and analyses may be performed by collection of xylidine in an adsorption tube containing silica gel, followed by desorption with ethanol, and gas chromatographic analysis. Also, detector tubes certified by NIOSH under 42 CFR Part 84 or other direct-reading devices calibrated to measure xylidine may be used. An analytical method for xylidine is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).
(order number PB 250 159).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

- Employees should be provided with and required to use impervious clothing, gloves, face shields (eight-inch minimum), and other appropriate protective clothing necessary to prevent any possibility of skin contact with liquid xylidine.
- Clothing contaminated with xylidine should be placed in closed containers for storage until it can be discarded or until provision is made for the removal of xylidine from the clothing. If the clothing is to be laundered or otherwise cleaned to remove the xylidine, the person performing the operation should be informed of xylidine's hazardous properties.
- Where exposure of an employee's body to liquid xylidine may occur, facilities for quick drenching of the

body should be provided within the immediate work area for emergency use.

- Non-impervious clothing which becomes contaminated with xylidine should be removed immediately and not reworn until the xylidine is removed from the clothing.
- Employees should be provided with and required to use splash-proof safety goggles where there is any possibility of liquid xylidine contacting the eyes.
- Where there is any possibility that employees' eyes may be exposed to liquid xylidine, an eye-wash fountain should be provided within the immediate work area for emergency use.

SANITATION

- Skin that becomes contaminated with xylidine should be immediately washed or showered with soap or mild detergent and water to remove any xylidine.
- Eating and smoking should not be permitted in areas where liquid xylidine is handled, processed, or stored.
- Employees who handle liquid xylidine should wash their hands thoroughly with soap or mild detergent and water before eating, smoking, or using toilet facilities.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to xylidine may occur and control methods which may be effective in each case:

Operation	Controls
Use for manufacture of dyes; use in manufacture of curing agents, antioxidants, and antiozonants; use in polymer production	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use as a gasoline additive and for the manufacture of gasoline additives, detergents, and antiknock agents	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment
Use in manufacture of pharmaceuticals; in organic synthesis in preparation of wood preservatives, wetting agents for textiles, frothing agents for ore dressing, special lacquers, and metal complexes	Process enclosure; local exhaust ventilation; general dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

- **Eye Exposure**

If liquid xylidine gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

- **Skin Exposure**

If liquid xylidine gets on the skin, immediately wash the contaminated skin using soap or mild detergent and water. If liquid xylidine soaks through the clothing, remove the clothing immediately and wash the skin using soap or mild detergent and water. Get medical attention immediately.

- **Breathing**

If a person breathes in large amounts of xylidine, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

- **Swallowing**

When liquid xylidine has been swallowed, get medical attention immediately. If medical attention is not immediately available, get the person to vomit by having touch the back of his throat with his finger or by giving him large amounts of water. Do not make an unconscious person vomit.

- **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL, LEAK, AND DISPOSAL PROCEDURES

- Persons not wearing protective equipment and clothing should be restricted from areas of spills or leaks until cleanup has been completed.
- If xylidine is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood). Allow sufficient time for evaporating vapors to completely clear the hood ductwork. Burn the paper in a suitable location away from combustible materials. Large quantities can be collected and atomized in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

- Waste disposal methods:

Xylidine may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a secured sanitary

landfill.

2. By atomizing in a suitable combustion chamber equipped with an appropriate effluent gas cleaning device.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Xylidine," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Deichmann, W. B., and Gerarde, H. W.: *Toxicology of Drugs and Chemicals*, Academic Press, New York, 1969.

• Elkins, H. B.: *Chemistry of Industrial Toxicology* (2nd ed.), Wiley, New York, 1959.

• Fairhall, L. T.: *Industrial Toxicology* (2nd ed.), Williams and Wilkins, Baltimore, 1957.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Mangelsdorff, A. F.: "Treatment of Methemoglobinemia," *A.M.A. Archives of Industrial Health*, 14:148-153, 1956.

• May, J.: "Solvent Odor Thresholds for the Evaluation of Solvent Odors in the Atmosphere," *Staub-Reinhalt*, 26:9, 385-389, 1966.

• Sax, N. I.: *Dangerous Properties of Industrial Materials* (3rd ed.), Van Nostrand Reinhold, New York, 1968.

• Smyth, H. F., and Carpenter, C. P.: "Chemical Burns of the Rabbit Cornea," *American Journal of Ophthalmology*, 29:1363-72, 1946.

• Stecher, P. G. (ed.): *The Merck Index* (8th ed.), Merck Co., Inc., Rahway, New Jersey, 1968.

• Treon, J. F., et al.: "The Toxic Properties of Xylidine and Monomethylaniline," *Archives of Industrial Hygiene and Occupational Medicine*, 1:506-524, 1950.

1547

RESPIRATORY PROTECTION FOR XYLIDINE

Condition	Minimum Respiratory Protection* Required Above 5 ppm
Vapor Concentration	
50 ppm or less	Any chemical cartridge respirator with an organic vapor cartridge(s). Any supplied-air respirator. Any self-contained breathing apparatus.
150 ppm or less	A chemical cartridge respirator with a full facepiece and an organic vapor cartridge(s). A gas mask with a chin-style or a front- or back-mounted organic vapor canister. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece. A Type C supplied-air respirator with a half facepiece operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 150 ppm or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

1548

Occupational Health Guideline for Yttrium and Compounds (as Yttrium)

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

APPLICABILITY

The general guidelines contained in this document apply to all yttrium and compounds. Physical and chemical properties of several specific compounds are provided for illustrative purposes.

SUBSTANCE IDENTIFICATION

Yttrium metal

- Formula: Y
- Synonyms: None
- Appearance and odor: Odorless, silvery solid.

Yttrium nitrate hexahydrate

- Formula: $Y(NO_3)_3 \cdot 6H_2O$
- Synonyms: None
- Appearance and odor: Colorless to pink, odorless solid.

Yttrium chloride

- Formula: YCl_3
- Synonyms: None
- Appearance and odor: Colorless, odorless solid.

Yttrium oxide

- Formula: Y_2O_3
- Synonyms: None
- Appearance and odor: Colorless, odorless solid.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for yttrium and compounds is 1 milligram of yttrium and compounds (as yttrium) per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Animal experiments suggest that yttrium and compounds can affect the body if they are inhaled or if they come in contact with the eyes. These experiments also suggest that they can also affect the body if they are swallowed.

- **Effects of overexposure**

Long-term exposure: Yttrium chloride particles which have become embedded in the eye have caused chemical eye damage in humans. Animal studies have shown the yttrium and compounds have caused irritation of the lungs, lung damage, and liver damage.

- **Reporting signs and symptoms**

A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to yttrium and compounds.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to yttrium and compounds at potentially hazardous levels:

1. Initial Medical Screening: Employees should be screened for history of certain medical conditions (listed below) which might place the employee at increased risk from yttrium and compounds exposure.

—Chronic respiratory disease: In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of yttrium might cause exacerbation of symptoms due to its irritant properties.

—Eye disease: Yttrium may cause severe eye damage. Those with pre-existing eye problems may be at increased risk from exposure.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1549

2. Periodic Medical Examination: Any employee developing the above-listed conditions should be referred for further medical examination.

• **Summary of toxicology**

Yttrium and compounds have caused pulmonary irritation in animals. Systemic absorption of the citrate complex of yttrium by animals resulted in dyspnea and pulmonary edema; yttrium chloride produced liver edema, portal congestion, pleural effusion, and pulmonary hyperemia. Intraperitoneal injection of yttrium chloride in animals caused peritonitis with serous or hemorrhagic ascites. Intratracheal injection of 50 mg of yttrium oxide in rats produced diffuse sclerosis of the lungs. Application of a 0.1 M solution of yttrium chloride to the eyes of rabbits caused no injury; similar exposure of eyes from which the corneal epithelium had been removed resulted in immediate slight haziness of the cornea which subsequently became opaque and vascularized.

CHEMICAL AND PHYSICAL PROPERTIES

• **Physical data—Yttrium metal**

1. Molecular weight: 88.9
2. Boiling point (760 mm Hg): 2927 C (5300 F)
3. Specific gravity (water = 1): 4.47
4. Vapor density (air = 1 at boiling point of yttrium metal): Not applicable
5. Melting point: 1509 C (2748 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Yttrium nitrate hexahydrate**

1. Molecular weight: 383
2. Boiling point (760 mm Hg): Decomposes
3. Specific gravity (water = 1): 2.68
4. Vapor density (air = 1 at boiling point of yttrium nitrate hexahydrate): Not applicable
5. Melting point: 100 C (212 F) (loses water)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 142
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Yttrium chloride**

1. Molecular weight: 195.3
2. Boiling point (760 mm Hg): 1510 C (2750 F)
3. Specific gravity (water = 1): 2.67
4. Vapor density (air = 1 at boiling point of yttrium chloride): Not applicable
5. Melting point: 720 C (1328 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): 79
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Physical data—Yttrium oxide**

1. Molecular weight: 225.8
2. Boiling point (760 mm Hg): 4300 C (7772 F)
3. Specific gravity (water = 1): 4.84
4. Vapor density (air = 1 at boiling point of yttrium oxide): Not applicable
5. Melting point: 2416 C (4380 F)
6. Vapor pressure at 20 C (68 F): Essentially zero
7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble
8. Evaporation rate (butyl acetate = 1): Not applicable

• **Reactivity**

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact of yttrium nitrate with combustible materials may cause fires and explosions.
3. Hazardous decomposition products: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released when yttrium nitrate decomposes.
4. Special precautions: None

• **Flammability**

1. Flash point: Not applicable
2. Autoignition temperature: Not applicable
3. Flammable limits in air, % by volume: Not applicable
4. Extinguishant: Not applicable

• **Warning properties**

Yttrium is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

• **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

• **Method**

Sampling and analyses may be performed by collection on a cellulose membrane filter followed by treatment with nitric and perchloric acids, solution in hydrochloric acid, and analysis with an atomic absorption spectrophotometer. An analytical method for yttrium and compounds is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 3, 1977, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00261-4).

RESPIRATORS

• Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. How-

ever, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.

• In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

PERSONAL PROTECTIVE EQUIPMENT

• Employees should be provided with and required to use dust- and splash-proof safety goggles to prevent any possibility of eye contact with yttrium nitrate hexahydrate, yttrium chloride, yttrium oxide, or liquids containing these compounds.

• Where there is any possibility that employees' eyes may be exposed to yttrium nitrate hexahydrate, yttrium chloride, yttrium oxide, or liquids containing these compounds, an eye-wash fountain should be provided within the immediate work area for emergency use.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to yttrium and compounds may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during purification; and during manufacture of alloys	Local exhaust ventilation; personal protective equipment
Use in manufacture of red phosphorus used in color TV picture tubes; fluorescent and mercury vapor lamps	Local exhaust ventilation; personal protective equipment
Use in manufacture of yttrium-iron-garnet (YIG) and YAG (aluminum) for use as electronic components in telephones, radar and space communications networks; and as simulated diamonds	Local exhaust ventilation; personal protective equipment
Use in manufacture of ceramics for use in high temperature furnaces and high intensity incandescent lamps	Local exhaust ventilation; personal protective equipment
Use in manufacture of refractories for stable, high temperature, high strength composition	Local exhaust ventilation; personal protective equipment
Use in manufacture of lasers	Local exhaust ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Eye Exposure**

If yttrium and compounds get into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention. Contact lenses should not be worn when working with these chemicals.

• **Skin Exposure**

If yttrium and compounds get on the skin, wash the contaminated skin using soap or mild detergent and water. If irritation persists after washing, get medical attention.

• **Breathing**

If a person breathes in large amounts of yttrium or yttrium compounds, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Swallowing**

When yttrium and compounds have been swallowed and the person is conscious, give the person large quantities of water immediately. After the water has been swallowed, try to get the person to vomit by having him touch the back of his throat with his finger. Do not make an unconscious person vomit. Get medical attention immediately.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILL AND DISPOSAL PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of spills until cleanup has been completed.

• If yttrium and compounds are spilled, the following steps should be taken:

1. Ventilate area of spill.
2. Collect spilled material in the most convenient and safe manner for reclamation or for disposal in a secured sanitary landfill. Liquid containing yttrium and compounds should be absorbed in vermiculite, dry sand, earth, or a similar material.

• Waste disposal method:

Yttrium and compounds may be disposed of in sealed containers in a secured sanitary landfill.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Yttrium as Y," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• International Labour Office: *Encyclopedia of Occupational Health and Safety*, McGraw-Hill, New York, 1971.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

RESPIRATORY PROTECTION FOR YTTRIUM AND COMPOUNDS (AS YTTRIUM)

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
5 mg/m³ or less	Any dust and mist respirator, except single-use.
10 mg/m³ or less	Any dust and mist respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
500 mg/m³ or less	A powered air-purifying respirator with a high efficiency particulate filter. A Type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 500 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Zinc Chloride Fume

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: $ZnCl_2$
- Synonyms: None
- Appearance and odor: White fume with an acrid odor.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for zinc chloride fume is 1 milligram of zinc chloride fume per cubic meter of air (mg/m^3) averaged over an eight-hour work shift.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Zinc chloride fume can affect the body if it is inhaled or if it comes in contact with the eyes.

- **Effects of overexposure**

1. Short-term Exposure: Exposure to zinc chloride fume may cause shortness of breath, a feeling of constriction in the chest, abdominal pain, watering of the eyes, burning of the eyes and throat, and coughing with phlegm and bloody sputum. It may also cause a blue color of the skin and lips. In addition, it may cause pneumonia. Breathing difficulties may not appear for several hours after exposure has ceased. Fatal exposures have occurred.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to zinc chloride fume.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to zinc chloride fume at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed. The skin should be examined for evidence of chronic disorders.

—14" x 17" chest roentgenogram: Zinc chloride fume causes human lung damage. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Zinc chloride fume is reported to cause decreased pulmonary function. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing. Determination of zinc in the urine may be helpful in evaluating the extent of absorption.

- **Summary of toxicology**

Zinc chloride fume irritates the eyes, mucous membranes, and skin, and causes delayed pulmonary edema. Ten deaths and 25 cases of non-fatal injury occurred among 70 persons exposed to a high concentration of zinc chloride released from smoke generators; presenting symptoms were conjunctivitis (two with burns of the corneas), irritation of nose and throat, cough with copious sputum, dyspnea, constrictive sensation in the chest, stridor, retrosternal pain, nausea, epigastric pain, and pale gray cyanosis. Of the 10 fatalities, a few died immediately or in a few hours from pulmonary edema, while those who survived longer developed bronchopneumonia. Between the second and fourth days after exposure, almost all cases developed moist, adventitious sounds in the lungs, and the majority continued to

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

1553

present a pale cyanotic color; a prominent feature was the disparity between the severe symptoms and the paucity of physical signs in the lungs; recovery occurred within 1 to 6 weeks after the incident. A firefighter was fatally exposed to a high but undetermined concentration of zinc chloride fume from a smoke generator; on admission to the hospital, the patient complained of nausea, sore throat, and chest tightness aggravated by deep inspiration. He initially improved but then developed tachypnea, substernal soreness, fever, cyanosis, and coma; the lung fields were clear on auscultation despite diffuse pulmonary infiltrations seen on the chest roentgenogram; death occurred 18 days after exposure, and autopsy revealed active fibroblastic proliferation and cor pulmonale. Injection of zinc chloride solution into the testes of 49 Syrian hamsters resulted in areas of necrosis occupying about 25% of each testis; two embryonal carcinomata of the testis were found 10 weeks later at necropsy.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 136.3
  2. Boiling point (760 mm Hg): 732 C (1350 F) (for solid)
  3. Specific gravity (water = 1): 2.91 (solid)
  4. Vapor density (air = 1 at boiling point of zinc chloride fume): Not applicable
  5. Melting point: 283 C (541 F) (for solid)
  6. Vapor pressure at 20 C (68 F): Not applicable
  7. Solubility in water, g/100 g water at 25 C (77 F): 81
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: None
  3. Hazardous decomposition products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Grant states that "dilute solutions (0.2% to 1%) have long been used as astringent eye drops without difficulty, but concentrated solutions and pastes such as encountered industrially have caused very severe injuries of the cornea in numerous cases of accidental splash in the eye. . . . Guillery found that applying 10% zinc chloride solution for 4 to 5 minutes to a rabbit's eye caused loss of corneal endothelium and extensive infiltration." No information is available concerning the effects on the eye specifically of the fume of zinc chloride.

The *Documentation of TLV's* reports, "Elkins stated that zinc chloride is an irritant . . . . Ferry, in investigating a borderline condition, found that levels between 0.07 and 0.4 mg/m^3 for 30 minutes did not result in sensory effects. The fume is corrosive to metals at these levels, however."

MONITORING AND MEASUREMENT PROCEDURES

- **General**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Method**

At the time of publication of this guideline, no measurement method for zinc chloride fume had been published by NIOSH.

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to zinc chloride fume may occur and control methods which may be effective in each case:

1551

Operation	Controls
Liberation from fluxing iron/steel prior to galvanizing	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation from arc welding of galvanized iron and steel pipes	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation from fluxing agent in some solder composition	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation from vulcanizing and reclaiming processes for rubber	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation from solutions in glass and metal etching	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation from manufacture of dry cell batteries	Process enclosure; general dilution ventilation; local exhaust ventilation; personal protective equipment
Liberation from petroleum refining operations	Process enclosure; general dilution ventilation; local exhaust ventilation

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of zinc chloride fume, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.

• If potentially hazardous amounts of zinc chloride fume are inadvertently released, ventilate the area of the release to disperse the fume.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Zinc Chloride Fume," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Christensen, H. E., and Luginbyhl, T. L. (eds.): *NIOSH Toxic Substances List*, 1974 Edition, HEW Publication No. 74-134, 1974.

• Evans, E. H.: "Casualties Following Exposure to Zinc Chloride Smoke," *Lancet*, 2:368-370, 1945.

• Grant, W. M.: *Toxicology of the Eye* (2nd ed.), C. C. Thomas, Springfield, Illinois, 1974.

• Guthrie, J., and Guthrie, O. A.: "Embryonal Carcinomas in Syrian Hamsters after Intratesticular Inoculation of Zinc Chloride during Seasonal Testicular Growth," *Cancer Research*, 34:2612-2613, 1974.

• Johnson, F. A., and Stonehill, R. B.: "Chemical Pneumonitis from Inhalation of Zinc Chloride," *Diseases of the Chest*, 40:619-624, 1961.

• Johnstone, M. A., et al.: "Experimental Zinc Chloride Ocular Injury and Treatment with Disodium Edetate," *American Journal of Ophthamology*, 76:137-142, 1973.

• Milliken, J. A., et al.: "Acute Interstitial Pulmonary Fibrosis Caused by a Smoke Bomb," *Canadian Medical Association Journal*, 88:36-39, 1963.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Vallee, B. L.: "Zinc and Its Biological Significance," *A.M.A. Archives of Industrial Health*, 16:147-154, 1957.

RESPIRATORY PROTECTION FOR ZINC CHLORIDE FUME

Condition	Minimum Respiratory Protection* Required Above 1 mg/m³
Particulate Concentration	
10 mg/m³ or less	Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
50 mg/m³ or less	A high efficiency particulate filter respirator with a full facepiece. Any supplied-air respirator with a full facepiece, helmet, or hood. Any self-contained breathing apparatus with a full facepiece.
1000 mg/m³ or less	A powered air-purifying respirator with a full facepiece and a high efficiency particulate filter.
2000 mg/m³ or less	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode.
Greater than 2000 mg/m³ or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.
Escape	A high efficiency particulate filter respirator. Any escape self-contained breathing apparatus.

*Only NIOSH-approved or MSHA-approved equipment should be used.

Occupational Health Guideline for Zinc Oxide Fume

INTRODUCTION

This guideline is intended as a source of information for employees, employers, physicians, industrial hygienists, and other occupational health professionals who may have a need for such information. It does not attempt to present all data; rather, it presents pertinent information and data in summary form.

SUBSTANCE IDENTIFICATION

- Formula: ZnO
- Synonyms: None
- Appearance: White fume.

PERMISSIBLE EXPOSURE LIMIT (PEL)

The current OSHA standard for zinc oxide fume is 5 milligrams of zinc oxide fume per cubic meter of air (mg/m^3) averaged over an eight-hour work shift. NIOSH has recommended that the permissible exposure limit be changed to 5 mg/m^3 averaged over a work shift of up to 10 hours per day, 40 hours per week, with a ceiling level of 15 mg/m^3 averaged over a 15-minute period. The NIOSH Criteria Document for Zinc Oxide should be consulted for more detailed information.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

Zinc oxide fume can affect the body if it is inhaled.

- **Effects of overexposure**

1. Short-term Exposure: Zinc oxide fume causes a flu-like illness called metal fume fever. Symptoms of metal fume fever include headache, fever, chills, muscle aches, nausea, vomiting, weakness, and tiredness. The symptoms usually start several hours after exposure. The attack may last 6 to 24 hours. Metal fume fever is more likely to occur after a period away from the job (after weekends or vacations). High levels of exposure to zinc oxide fume may cause a metallic or sweet taste in the mouth, dryness and irritation of the throat, and coughing at the time of exposure.

2. Long-term Exposure: None known.

3. Reporting Signs and Symptoms: A physician should be contacted if anyone develops any signs or symptoms and suspects that they are caused by exposure to zinc oxide fume.

- **Recommended medical surveillance**

The following medical procedures should be made available to each employee who is exposed to zinc oxide fume at potentially hazardous levels:

1. Initial Medical Examination:

—A complete history and physical examination: The purpose is to detect pre-existing conditions that might place the exposed employee at increased risk, and to establish a baseline for future health monitoring. Examination of the respiratory system should be stressed.

—14" x 17" chest roentgenogram: Zinc oxide fume may cause respiratory impairment. Persons with pulmonary disease may be more susceptible to the effect os zinc oxide fume. Surveillance of the lungs is indicated.

—FVC and FEV (1 sec): Persons with pre-existing pulmonary disease may be more susceptible to the effects of zinc oxide fume. Periodic surveillance is indicated.

2. Periodic Medical Examination: The aforementioned medical examinations should be repeated on an annual basis, except that an x-ray is considered necessary only when indicated by the results of pulmonary function testing. Determination of zinc in the urine may be helpful in evaluating the extent of absorption.

- **Summary of toxicology**

Inhalation of zinc oxide fume causes an influenza-like illness termed metal fume fever. Heavy human exposure to zinc oxide fume may cause an immediate dryness and irritation of the throat, a sweet or metallic taste followed by substernal tightness and constriction in the chest, and a dry cough. Several hours following exposure the subject develops fever, lassitude, malaise, fatigue, frontal headache, low back pain, muscle cramps, and occasionally blurred vision, nausea, and vomiting.

These recommendations reflect good industrial hygiene and medical surveillance practices and their implementation will assist in achieving an effective occupational health program. However, they may not be sufficient to achieve compliance with all requirements of OSHA regulations.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Physical examination reveals fever, eventually followed by perspiration and chills, dyspnea, rales throughout the chest, and tachycardia; in some instances there has been a reversible reduction in pulmonary vital capacity; there is usually leukocytosis, which may amount to 12,000 to 16,000/MM3. An attack usually subsides after 6 to 12 hours but may last for up to 24 hours; recovery is usually complete. Most workers rapidly develop an immunity to these attacks, but it is as quickly lost; attacks tend to be more severe on the first day of the work-week. Only freshly formed fume causes the illness, presumably because flocculation occurs in the air; the larger particles that form are deposited in the upper respiratory tract and do not penetrate deeply into the lungs. Chills have been reported in workers from exposure to concentrations of zinc oxide fume below 5 mg/m^3.

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
  1. Molecular weight: 81.37
  2. Boiling point (760 mm Hg): Solid sublimes
  3. Specific gravity (water = 1): 5.6 (solid)
  4. Vapor density (air = 1 at boiling point of zinc oxide fume): Not applicable
  5. Melting point: Greater than 1800 C (greater than 3272 F)
  6. Vapor pressure at 20 C (68 F): Not applicable
  7. Solubility in water, g/100 g water at 20 C (68 F): Insoluble (solid)
  8. Evaporation rate (butyl acetate = 1): Not applicable
- **Reactivity**
  1. Conditions contributing to instability: None
  2. Incompatibilities: Zinc oxide fume may react violently with chlorinated rubber.
  3. Hazardous decomposiiton products: None
  4. Special precautions: None
- **Flammability**
  1. Not combustible
- **Warning properties**

Zinc oxide fume is not known to be an eye irritant.

MONITORING AND MEASUREMENT PROCEDURES

- **Eight-Hour Exposure Evaluation**

Measurements to determine employee exposure are best taken so that the average eight-hour exposure is based on a single eight-hour sample or on two four-hour samples. Several short-time interval samples (up to 30 minutes) may also be used to determine the average exposure level. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee).

- **Ceiling Evaluation**

Measurements to determine employee ceiling exposure are best taken during periods of maximum expected airborne concentrations of zinc oxide fume. Each measurement should consist of a fifteen (15) minute sample or series of consecutive samples totalling fifteen (15) minutes in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). A minimum of three (3) measurements should be taken on one work shift and the highest of all measurements taken is an estimate of the employee's exposure.

- **Method**

Sampling and analyses may be performed by collection of zinc oxide on a cellulose membrane filter, followed by solublizing the zinc with nitric acid and analyzing by atomic absorption spectrophotometry. An analytical method for zinc oxide fume is in the *NIOSH Manual of Analytical Methods*, 2nd Ed., Vol. 4, 1978, available from the Government Printing Office, Washington, D.C. 20402 (GPO No. 017-033-00317-3).

RESPIRATORS

- Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the permissible exposure level. However, there are some exceptions where respirators may be used to control exposure. Respirators may be used when engineering and work practice controls are not technically feasible, when such controls are in the process of being installed, or when they fail and need to be supplemented. Respirators may also be used for operations which require entry into tanks or closed vessels, and in emergency situations. If the use of respirators is necessary, the only respirators permitted are those that have been approved by the Mine Safety and Health Administration (formerly Mining Enforcement and Safety Administration) or by the National Institute for Occupational Safety and Health.
- In addition to respirator selection, a complete respiratory protection program should be instituted which includes regular training, maintenance, inspection, cleaning, and evaluation.

COMMON OPERATIONS AND CONTROLS

The following list includes some common operations in which exposure to zinc oxide fume may occur and control methods which may be effective in each case:

Operation	Controls
Liberation during brazing, welding, burning, and cutting of zinc and galvanized metals	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberation from founding of brass, copper, and zinc, and galvanizing of iron and steel	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberation from abrasive cleaning of galvanized metal surface	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberating during use as a ceramic flux	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberation during recovery of impure lead blast furnace slag; from manufacture of glass to increase brilliance and luster of glass	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberation from use as an intermediate in manufacture of other zinc compounds; in manufacture of electronic devices	General dilution ventilation; process enclosure; local exhaust ventilation; personal protective equipment
Liberation from use as a filler material in crushed stone industry	General dilution ventilation; personal protective equipment

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, institute first aid procedures and send for first aid or medical assistance.

• **Breathing**

If a person breathes in large amounts of zinc oxide fume, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

• **Rescue**

Move the affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

LEAK PROCEDURES

• Persons not wearing protective equipment and clothing should be restricted from areas of releases until cleanup has been completed.

• If potentially hazardous amounts of zinc oxide fume are inadvertently released, ventilate the area of the release to disperse the fume.

REFERENCES

• American Conference of Governmental Industrial Hygienists: "Zinc Oxide Fume," *Documentation of the Threshold Limit Values for Substances in Workroom Air* (3rd ed., 2nd printing), Cincinnati, 1974.

• American Industrial Hygiene Association: "Zinc Oxide," *Hygienic Guide Series*, Detroit, Michigan, 1969.

• Browning, E.: *Toxicity of Industrial Metals* (2nd ed.), Butterworths, London, 1969.

• Fishburn, C. W., and Zenz, C.: "Metal Fume Fever," *Journal of Occupational Medicine*, 11:142-144, 1969.

• Hamdi, E. A.: "Chronic Exposure to Zinc of Furnace Operators in a Brass Foundry," *British Journal of Industrial Medicine*, 26:126-134, 1969.

• McCord, C. P.: "Metal Fume Fever As an Immunological Disease," *Industrial Medicine and Surgery*, 29:101-107, 1960.

• National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare: *Criteria for a Recommended Standard . . . . Occupational Exposure to Zinc Oxide*, HEW Publication No. (NIOSH) 76-104, GPO No. 017-033-00109, U.S. Government Printing Office, Washington, D.C., 1975.

• Patty, F. A. (ed.): *Toxicology*, Vol. II of *Industrial Hygiene and Toxicology* (2nd ed. rev.), Interscience, New York, 1963.

• Rohrs, L. C.: "Metal-Fume Fever from Inhaling Zinc Oxide," *A.M.A. Archives of Industrial Health*, 16:42-47, 1957.

• Turner, J. A.: "An Occupational Dermatoconiosis Among Zinc Oxide Workers," *Public Health Reports*, 36:2727-2732, 1921.

• Vallee, B. L.: "Zinc and Its Biological Significance," *A.M.A. Archives of Industrial Health*, 16:147-154, 1957.