

This article was downloaded by: [CDC]

On: 21 February 2012, At: 13:22

Publisher: Taylor & Francis

Informa Ltd Registered in England and Wales Registered Number: 1072954 Registered office: Mortimer House, 37-41 Mortimer Street, London W1T 3JH, UK



Applied Occupational and Environmental Hygiene

Publication details, including instructions for authors and subscription information:

<http://www.tandfonline.com/loi/uaoh20>

A Checklist for Evaluating Cab Design of Construction Equipment

N. Kumar Kittusamy ^a

^a NIOSH's Spokane Research Lab, Washington

Available online: 30 Nov 2010

To cite this article: N. Kumar Kittusamy (2003): A Checklist for Evaluating Cab Design of Construction Equipment, Applied Occupational and Environmental Hygiene, 18:10, 721-723

To link to this article: <http://dx.doi.org/10.1080/10473220301446>

PLEASE SCROLL DOWN FOR ARTICLE

Full terms and conditions of use: <http://www.tandfonline.com/page/terms-and-conditions>

This article may be used for research, teaching, and private study purposes. Any substantial or systematic reproduction, redistribution, reselling, loan, sub-licensing, systematic supply, or distribution in any form to anyone is expressly forbidden.

The publisher does not give any warranty express or implied or make any representation that the contents will be complete or accurate or up to date. The accuracy of any instructions, formulae, and drug doses should be independently verified with primary sources. The publisher shall not be liable for any loss, actions, claims, proceedings, demand, or costs or damages whatsoever or howsoever caused arising directly or indirectly in connection with or arising out of the use of this material.

Ergonomics

A Checklist for Evaluating Cab Design of Construction Equipment

Scott Schneider, Column Editor

Reported by N. Kumar Kittusamy

Awkward postures during the operation of heavy construction equipment are a consequence of improper cab design and work procedures. Poor visibility of the task, limited room in the cab, excessive forces required to operate levers/pedals, and improper seat designs are some of the characteristics of a poorly designed cab. If not controlled, awkward posture of any body part can result in increased risk of fatigue, pain, or injury. Exposure to awkward postures, either repetitively or for prolonged periods, can lead to a variety of musculoskeletal disorders.

Laboratory studies have shown that non-neutral trunk postures (i.e., flexion, lateral bending, and/or twisting) caused increased levels of muscle fatigue and intervertebral disc pressure in the lower back.⁽¹⁾ Epidemiological studies have shown that flexion, lateral bending, and twisting of the trunk are factors in the development of low back pain.^(2,3) Spinal disc compression can increase substantially when the trunk changes from a neutral to a flexed posture.⁽⁴⁾ Furthermore, prolonged sitting can also result in an increased risk of low back pain.⁽⁵⁾

Laboratory studies of non-neutral shoulder postures have shown that prolonged elevation of the arms (abduction or flexion of the shoulder) causes extreme levels of muscle fatigue and discomfort.^(1,6) Hagberg⁽⁷⁾ demonstrated a positive relationship between shoulder elevation and increased risk of tendonitis in a cross-sectional field study. A relationship between non-neutral neck posture and the development of disorders has also been well documented.⁽⁸⁾

The objective of this article is to introduce a one-page checklist for evaluating cab design of construction equipment. The cab design evaluation checklist was developed, pilot-tested, and used to measure several characteristics of cab design

(see Table I). The checklist was based on a literature review and was then discussed with the operators of construction equipment. The draft checklist was then pilot-tested with input solicited from and incorporated by trainers, operating

TABLE I
A checklist for evaluating cab design of construction equipment

| | Yes | No | N/A | Comments |
|---|-----|----|-----|----------|
| I. Characteristics | | | | |
| 1. Is the seat height adjustable? | | | | 1 |
| 2. Can the seat be adjusted horizontally? | | | | 2 |
| 3. Is the seat set at proper height? | | | | 3 |
| 4. Does the seat have a back support? | | | | 4 |
| 5. Does the seat have a lumbar support? | | | | 5 |
| 6. Are there armrests available? | | | | 6 |
| 7. Are the armrests adjustable? | | | | 7 |
| 8. Are the armrests set at proper height? | | | | 8 |
| 9. Do you feel any vibration from the equipment through the seat? | | | | 9 |
| 10. Do you feel any vibration from the equipment through the floor? | | | | 10 |
| 11. Do you feel any vibration from the equipment through the controls? | | | | 11 |
| 12. Is the seat firmly mounted to the floor of the cab? | | | | 12 |
| 13. Can the seat be tilted backward? | | | | 13 |
| 14. Can the seat swivel? | | | | 14 |
| 15. Is the location of the controls or levers adjustable? | | | | 15 |
| 16. Can you easily reach the levers or controls? | | | | 16 |
| 17. Can you easily operate the levers or controls? | | | | 17 |
| 18. Can you easily reach the pedals? | | | | 18 |
| 19. Can you easily operate the pedals? | | | | 19 |
| 20. Is the cab area large enough (e.g., uncramped area) for you? | | | | 20 |
| 21. Do you have sufficient upward visibility? | | | | 21 |
| 22. Is your view of the operation obstructed (e.g., cab guards, pipes/hoses, etc.)? | | | | 22 |
| 23. Do you feel the cab is noisy? | | | | 23 |
| 24. Can you control the temperature of the cab? | | | | 24 |
| 25. Does the equipment have steps? | | | | 25 |
| 26. Does the equipment have handrails? | | | | 26 |
| 27. Can you easily open/close the cab doors? | | | | 27 |
| 28. Does the equipment have proper means for entering the cab? | | | | 28 |
| 29. Does the equipment have proper means for exiting the cab? | | | | 29 |
| II. Environmental | | | | |
| 30. Do you have a good general view of the ground? | | | | 30 |
| 31. Are the cab windows free from distracting reflections? | | | | 31 |

TABLE II
Background data of operators and equipment evaluated in this study

| Operator ^A | Characteristics of the operator | | | | Equipment information | | | |
|-----------------------|---------------------------------|-------------|-------|--------------|-----------------------|----------|--------|----------------|
| | Height (cm) | Weight (kg) | Age | Years of exp | Make | Model | Size | Type |
| 1 | 165 | 52 | 33 | 11 | Caterpillar | CAT 416B | Small | Loader/Backhoe |
| 2 | 178 | 129 | 49 | 30 | Caterpillar | CAT 446B | Small | Loader/Backhoe |
| 3 | 183 | 86 | 38 | 17 | John Deere | JD 710D | Small | Loader/Backhoe |
| 4 | 165 | 70 | 58 | 36 | Caterpillar | CAT M318 | Medium | Excavator |
| 5 | 178 | 100 | 56 | 40 | Caterpillar | CAT M318 | Medium | Excavator |
| 6 | 168 | 86 | 35 | 15 | Daewoo | DH 200W | Large | Excavator |
| 7 | 170 | 66 | 35 | 12 | Komatsu | PC 400LC | Large | Excavator |
| Mean | 172.4 | 84.2 | 43.4 | 23.0 | | | | |
| SD | 7.1 | 25.4 | 10.7 | 12.1 | | | | |
| Var | 50.4 | 644.6 | 113.6 | 145.3 | | | | |

^AOE #1 is a female; all others are male operators.

engineers, and apprentices. A case study is presented in which overall cab design scores were calculated for each type of equipment.

Case Study

The checklist was designed to be a systematic evaluation tool that could be used to assess the characteristics of a cab. A majority of the questions in the checklist were structured so that satisfactory ergonomic conditions resulted in affirmative answers to the questions. There were three questions that had to be worded in an inverse relationship to avoid ambiguity. If supplying a categorical answer was difficult, the answer was qualified by an overall assessment of the characteristics of concern.

After the evaluation of the cab design, an overall assessment score for the cab was calculated. This was done by assigning equal weights to each of the answers, and a percentage of affirmative answers were determined. The closer the calculation was to 100 percent, the better the design or the acceptability of the cab. Some features of the cab may be more important than others, but the simple approach of equal weights was considered here as used by Lifshitz and Armstrong.⁽⁹⁾

Equipment and Operators Studied

The study was performed at several different construction sites in the Greater Boston, Massachusetts area. Seven journey-level (experienced) operators

(6 males and 1 female) employed by two major contractors were studied (see Table II). The operators' ages ranged from 33 to 58 years (43.4 ± 10.7); experience ranged from 11 to 40 years (23 ± 12.1); height ranged from 165 cm to 183 cm (172.4 ± 7.1); and weight ranged from 52 kg to 129 kg (84.2 ± 25.4). Each operator used a different piece of construction equipment. Operators were briefed about the study, and they each signed a consent form to participate in this research.

Results

All seven equipment types listed in Table II were evaluated. The overall total cab score was calculated using all 31 questions in the cab design evaluation checklist. The results of the overall cab design score are summarized in Table III. The overall total cab design scores for the seven equipment types ranged from 71 to 87 percent, with a 6.5-percent standard deviation. The following concerns were found:

1. Seats did not have lumbar support in all of the equipment (100%).
2. In a majority of the equipment (86%), the vibration could be felt from the equipment through the floor.
3. In a majority of the equipment (86%), the temperature of the cab could not be controlled.

TABLE III
Evaluation of cab characteristics using the cab design checklist

| Operator | Equipment information | | | Overall total cab score ^A |
|----------|-----------------------|----------|----------------|--------------------------------------|
| | Make | Model | Type | |
| 1 | Caterpillar | CAT 416B | Loader/Backhoe | 74 |
| 2 | Caterpillar | CAT 446B | Loader/Backhoe | 74 |
| 3 | John Deere | JD 710D | Loader/Backhoe | 71 |
| 4 | Caterpillar | CAT M318 | Excavator | 87 |
| 5 | Caterpillar | CAT M318 | Excavator | 81 |
| 6 | Daewoo | DH 200W | Excavator | 81 |
| 7 | Komatsu | PC 400LC | Excavator | 71 |

^AOverall total cab score computed using all questions in the checklist.

4. In a majority of the equipment (71%), the locations of the controls and levers were not adjustable.
5. More than half of the equipment (57%) did not have adjustable armrests.
6. In more than half of the equipment (57%), vibrations were felt at the seats and at the controls.
7. The seat did not swivel in more than half of the equipment (57%).

Discussion and Conclusion

Postural requirements of work should be considered in the design of work procedures and equipment in construction. The relationship between awkward posture and the development of fatigue and musculoskeletal disorders has been reported in laboratory and epidemiological studies. Despite the fact that operating heavy equipment has been found to result in a high prevalence of musculoskeletal symptoms and injuries,⁽¹⁰⁾ there is a lack of quantitative data describing postural stresses among operators of construction equipment. This could be due to the time and complexity in collecting and analyzing postural data. The current study introduced a checklist for evaluating cab design and presented a case study using the checklist.

The checklist is a general assessment tool. The checklist was useful in identifying characteristics that needed improvement. One limitation of a checklist is that it is, at best, an analytical tool.⁽¹¹⁾ It can assist in the process of identifying potential problems within a system, but for quantifying the problems, a comprehensive and systematic methodology is required for evaluating the work system. The checklist provides a static, instantaneous snapshot of characteristics during

a specific time. Nevertheless, this and other checklists provide the critical point of departure in initiating the ergonomic analysis.^(9,12-14)

REFERENCES

1. Chaffin, D.B.: Localized Muscle Fatigue — Definition and Measurement. *J Occup Med* 15(4):346-354 (1973).
2. Punnett, L.; Fine, L.J.; Keyserling, W.M.; et al.: Back Disorders and Non-neutral Trunk Postures of Automobile Assembly Workers. *Scand J Work Environ Health* 17(5):337-346 (1991).
3. Magora, A.: Investigation of the Relation Between Low Back Pain and Occupation: Part I. *Indus Med Surg* 39(11):465-471 (1970).
4. Chaffin, D.B.; Andersson, G.B.J.: Occupational Biomechanics. John Wiley and Sons, New York, NY (1991).
5. Kelsey, J.L.; Hardy, R.J.: Driving of Motor Vehicles as a Risk Factor for Acute Herniated Lumbar Intervertebral Disc. *Am J Epidemiol* 102(1):63-73 (1975).
6. Hagberg, M.: Local Shoulder Muscular Strain — Symptoms and Disorders. *J Hum Ergol* 11(1):99-108 (1982).
7. Hagberg, M.: Occupational Musculoskeletal Stress and Disorders of the Neck and Shoulder: A Review of Possible Pathophysiology. *Int Arch Occup Environ Health* 53(3):269-278 (1984).
8. National Institute for Occupational Safety and Health: Musculoskeletal Disorders (MSDs) and Workplace Factors — A Review of Epidemiologic Evidence for Work-Related Musculoskeletal Disorders of the Neck, Upper Extremity, and Low Back. DHHS (NIOSH) Pub. No. 97-141. NIOSH, Washington, DC (1997).
9. Lifshitz, Y.; Armstrong, T.J.: A Design Checklist for Control and Prediction of Cumulative Trauma Disorders in Intensive Manual Jobs. In: Proceedings of the Human Factors Society 30th Annual Meeting. Human Factors and Ergonomics Society, Dayton, OH (1986).
10. Zimmermann, C.L.; Cook, T.M.; Rosecrance, J.C.: Operating Engineers: Work-Related Musculoskeletal Disorders and the Trade. *Appl Occup Environ Hyg* 12(10):670-680 (1997).
11. Easterby, R.S.: Ergonomics Checklist: An Appraisal. *Ergonomics* 10(5):549-556 (1967).
12. Kittusamy, N.K.; Okogbaa, O.G.; Babu, A.J.G.: A Preliminary Audit for Ergonomics Design in Manufacturing Environments. *Indus Eng* (July, 1992).
13. Kittusamy, N.K.; O'Reilly, J.T.: Ergonomics Program. In: *Accident Prevention Manual for Business & Industry: Administration & Programs (Occupational Safety and Health Series)*, 12th ed., chap. 16. P. Hagan; J.F. Montgomery; J.T. O'Reilly, eds., National Safety Council, Chicago, IL (2001).
14. Keyserling, W.M.; Brouwer, M.; Silverstein, B.A.: A Checklist for Evaluating Ergonomic Risk Factors Resulting from Awkward Postures of the Legs, Trunk and Neck. *Int J Indus Ergon* 9:283-301 (1992).

EDITORIAL NOTE: N. Kumar Kittusamy is a research engineer at NIOSH's Spokane, Washington, Research Lab. He conducts research related to safety and health issues in mining and construction industries. He holds a B.S. in Industrial Engineering and an M.S. in Public Health with concentration in Ergonomics and Industrial Hygiene from the University of South Florida, and a Doctor of Science (Sc.D.) with a major in Ergonomics and minors in Industrial Hygiene and Epidemiology/Biostatistics from the College of Engineering at the University of Massachusetts Lowell. His current research interests include whole-body vibration, musculoskeletal epidemiology, and workstation design.

For more information, Dr. Kittusamy can be contacted at NIOSH, Spokane Research Lab, 315 East Montgomery Avenue, Spokane, WA 99207; telephone: (509) 354-8127; fax: (509) 354-8099; e-mail: nkf8@cdc.gov.