

**Bureau of Mines Report of Investigations/1977**

# **Single-Entry Development for Longwall Mining**

**Research Approach and Results at Sunnyside  
No. 2 Mine, Carbon County, Utah**



**UNITED STATES DEPARTMENT OF THE INTERIOR**

**Report of Investigations 8252**

# **Single-Entry Development for Longwall Mining**

**Research Approach and Results at Sunnyside  
No. 2 Mine, Carbon County, Utah**

**By Melvin E. Poad, Galen G. Waddell, and Earl L. Phillips**



**UNITED STATES DEPARTMENT OF THE INTERIOR  
Cecil D. Andrus, Secretary  
BUREAU OF MINES**

This publication has been cataloged as follows:

**Poad, Melvin E**

Single-entry development for longwall mining. Research approach and results at Sunnyside No. 2 mine, Carbon County, Utah / by Melvin E. Poad, Galen G. Waddell, and Earl L. Phillips. [Washington] : U.S. Dept. of the Interior, Bureau of Mines, 1977.

29 p. : ill., maps, diagrams ; 27 cm. (Report of investigations • Bureau of Mines ; 8252)

Bibliography: p. 29.

1. Coal mines and mining. 2. Tunneling. I. Waddell, Galen G., joint author. II. Phillips, Earl L., joint author. III. United States. Bureau of Mines. IV. Title. V. Title: Longwall mining at Sunnyside No. 2 mine, Carbon County, Utah, Single-entry development for. VI. Series: United States. Bureau of Mines. Report of investigations • Bureau of Mines ; 8252.

TN23.U7 no. 8252 622.06173

U.S. Dept. of the Int. Library

## CONTENTS

	<u>Page</u>
Abstract.....	1
Introduction.....	1
Part 1.--Thesis of single-entry development.....	2
Background.....	2
Longwall mining.....	2
Longwall mining versus room-and-pillar mining.....	4
Single-entry development.....	6
Problem definition and research approach.....	7
Ground control.....	7
Support during development.....	8
Support during longwall retreating operation.....	8
Support of bleeder entry.....	9
Ventilation.....	9
Methane.....	9
Dust.....	10
Safety procedures.....	10
Part 2.--Field investigations at the Sunnyside No. 2 mine.....	10
Geologic investigations.....	12
Support system.....	13
Instrumentation.....	13
Instrumentation layout.....	19
Data collection and storage.....	19
Field results.....	20
Finite-element analysis.....	27
Conclusion.....	28
References.....	29

## ILLUSTRATIONS

1. Multiple-, double-, and single-entry longwall-development systems...	3
2. Location map of the Sunnyside mines.....	11
3. Stratigraphic section of the Mesaverde group.....	11
4. Plan map of Sunnyside mine No. 2.....	12
5. Major geologic structures, geologic section, and roof-fall zones....	13
6. Support layout for room No. 1.....	14
7. Modified full-bridge rock-bolt-load cell.....	15
8. Strain crib cell.....	15
9. Hydraulic roof-bolt cell.....	16
10. Hydraulic crib cell.....	16
11. Stainless steel extensometer.....	17
12. Wooden crib.....	18
13. Horizontal closure-measurement device.....	19
14. Instrumentation layout for room No. 1.....	20
15. Sample of underground recording sheet and associated data- processing card.....	21
16. Deformation profile through the centerline of the crosscut.....	22
17. Deformation profile across the entries at the centerline of the pillar.....	22

## ILLUSTRATIONS--Continued

	<u>Page</u>
18. Composite deformation profile at the test site.....	23
19. Roof-bolt-load profile through the centerline of the crosscut.....	24
20. Roof-bolt-load profile across the entries at the centerline of the pillar.....	25
21. Composite roof-bolt-load profile at the test site.....	26
22. Load profile of a wooden crib near the fall.....	26
23. Deformation profile across the entry where the fall occurred.....	27

# SINGLE-ENTRY DEVELOPMENT FOR LONGWALL MINING

Research Approach and Results at Sunnyside No. 2 Mine,  
Carbon County, Utah

by

Melvin E. Poad,<sup>1</sup> Galen G. Waddell,<sup>2</sup> and Earl L. Phillips<sup>3</sup>

---

---

## ABSTRACT

This Bureau of Mines report presents two phases of a research program to evaluate a single-entry system for longwall development. Organizations participating in the program, which began in July 1971, include the Bureau of Mines, the Mining Enforcement and Safety Administration, and the University of Utah, working under a cooperative agreement with Kaiser Steel Corp. at its Sunnyside mine in Utah. Part 1 of this report describes the present longwall mining practice, including a brief history, and discusses the advantages and disadvantages of a single-entry development system and its introduction in the United States. Part 2 of the report presents the research program, test design, instrumentation for ground and support evaluation, and the test results from the No. 2 mine. Subsequent reports will describe the research conducted in the No. 1 mine.

## INTRODUCTION

The Federal Coal Mine Health and Safety Act of 1969 (Public Law 91-173) is designed to improve the health and safety of miners with new or improved standards, strict enforcement of those standards, and new or improved mining technology accomplished through research. Although single-entry development and longwall mining have never been used in the United States, their use in other parts of the world has resulted in improved safety records compared with conventional types of mining (room-and-pillar, etc.) (8).<sup>4</sup>

Because the single entry has been used with success in Europe and other parts of the world, there is sufficient reason to believe that it will succeed under the deep cover and geologic conditions found at Sunnyside. The Federal

---

<sup>1</sup>Research civil engineer, Spokane Mining Research Center, Bureau of Mines, Spokane, Wash.

<sup>2</sup>Research director, Twin Cities Mining Research Center, Bureau of Mines, Twin Cities, Minn.

<sup>3</sup>Supervisor technician, Spokane Mining Research Center, Bureau of Mines, Spokane, Wash.

<sup>4</sup>Underlined numbers in parentheses refer to items in the list of references at the end of this report.

Coal Mine Health and Safety Act of 1969 specifies that there must be an alternate escapeway within 100 feet of an area in which miners are working. The question that is proposed and requires the subject research is, "Will a single entry, divided along the centerline by a fire-resistant support-divider, provide an alternate escapeway?" Title V of the act provides for exemptions under the law if research is directed by the Bureau of Mines. After meetings of the groups involved, the Single-Entry Research Program was initiated.

This Bureau of Mines paper explains the use and advantages of a single-entry system in development for longwall coal mining, defines the problems anticipated with single entries, and presents the research approach needed to evaluate and solve the problems. Under study are problems associated with ground control, ventilation (methane and dust), and safety procedures. Described are crib and roof-bolt loads as the entry heading advances, stress determinations, and preliminary structural analysis of the double entry. Some of the mine operation problems and waivers of mining laws (for experimental purposes) are discussed.

Although the field results reported in this publication are minimal, this report provides the background and rationale for the single-entry program. Additional publications will address the ground-control, ventilation, and safety problems during driving of the single entries and during retreat of the longwall panels. One report will describe detailed geologic parameters, stratigraphic columns, and structural properties of the immediate roof and floor. Another report will analyze the failure of the wooden cribs as a centerline support system, describe the design of the concrete cribs, and analyze the structural properties of the cribs in the laboratory and in the field.

The research program has progressed approximately 5 years in an 8-year program. If successful, single-entry longwall development would improve both safety and production. Cooperators in the study include the Federal Bureau of Mines, the Mining Enforcement and Safety Administration (MESA), Kaiser Steel Corp., and the University of Utah.

## PART 1.--THEESIS OF SINGLE-ENTRY DEVELOPMENT

### Background

Before describing the single-entry research project, a brief discussion of general coal mining practices will explain why single-entry development, together with longwall mining, constitutes a more efficient mining system.

### Longwall Mining

Longwall mining was tried in the United States prior to 1900 but was abandoned in favor of room-and-pillar mining because of the labor costs involved with manually moving the supports. Following the advent of self-advancing props, longwall mining was again introduced in the United States in 1960. The first installations were in southern West Virginia mines with ground-control problems. These mines had mudstone or friable-shale roof, which was easily caved; cover was shallow and props were light. The system

was next tried using the same-capacity jacks in seams overlaid with massive roof strata and shallow cover. Under such mining conditions, the support either failed or was operated with great difficulty. This discouraging experience stunted the growth of longwall mining for a considerable period of time.

In 1966 two longwall units were equipped with massive, heavy-duty supports. Both operations were under thick sandstone roof strata and one was in a deep mine. Both installations met with instant success and led to the first modest expansion of the longwall mining system (3). Although U.S. underground coal mine tonnage dropped from 347.1 to 302.4 million tons between 1969 and 1971, longwall mining increased from 6.3 to 8.4 million tons and accounted for about 4 percent of total underground production in coal mines. From August 1972 to June 1973, the number of longwalls increased from 30 to 43. As of January 1977, there were 72 operating longwall faces in the United States (4).

The fundamental principle of longwall mining is the complete removal of the entire seam in one operation by carrying a continuous working face, leaving no pillars, and allowing the roof to cave behind the face (8). Development consists of driving one or more gates or entries approximately 300 to 600 feet apart, providing an interconnection, and then mining the rib of the interconnection. Figure 1 shows multiple-entry, double-entry, and single-entry development.

The longwall mining system consists of three basic components: (1) a support system, (2) a coal-getting device, and (3) a haulage system. The support system comprises a series of hydraulically powered chocks that have a number of hydraulic legs (props or jacks), box-type steel canopy or canopies, single- or double-base plates, a push-pull cylinder, and a control valve that lowers, advances, and resets the unit (11). The trend is to heavier units; those used in this single-entry study are rated at 450 tons.




FIGURE 1. - Multiple-, double-, and single-entry longwall-development systems.



Two types of longwall mining are practiced--advance and retreat. In Europe and Japan where coal mining is at greater depths (down to 4,000 feet), it is almost impossible to drive and maintain entries for complete development of a longwall panel; thus, the advance type is used. Two entries are driven (headgate and tailgate) a short distance ahead of the advancing longwall face; hence, the term "advance longwall mining." In "retreat longwall mining," complete development of the longwall panel (entries and crosscut) takes place prior to mining. This system predominates in the United States where mining is conducted at lesser depths, except when an advancing tailgate is added to make a combination system.

Some advantages of advance longwall over retreat longwall mining include the following (11):

1. Development costs are reduced because coal is mined immediately.
2. An escapeway is provided immediately.

Some disadvantages are--

1. Air tends to short-circuit through the gob, causing ventilation problems.
2. Entries are subjected to increased ground pressure owing to caving of adjacent ground, and they must be constantly maintained.
3. Entries are subjected to heavy concentrations of methane from the gob.

#### Longwall Mining Versus Room-and-Pillar Mining

The longwall system provides several advantages over room-and-pillar operations.

1. Continuous support provides a safer environment. Only 2 fatalities occurred at longwall faces in 1972, compared with 121 for room-and-pillar mining; based on production, fatality rates were 1 per 7 million tons of coal mined by longwall, and 1 per 2 million tons by room-and-pillar mining (12). For the same period, there were 551 disabling injuries for longwall operations versus 14,237 for room-and-pillar; again, based on production, 25,000 tons per injury for longwall versus 18,000 tons per injury for room-and-pillar mining (13).

2. A high extraction ratio is possible. As the need for energy increases throughout the world, we can no longer afford to leave large amounts of our coal reserves underground because of out-dated and inefficient mining methods. Room-and-pillar methods extract an average of 55 percent of a minable seam, whereas conventional longwall methods average 75 percent recovery. From 90 to 95 percent is possible with single-entry development (6).

3. Supply, ventilation, supervision, and power are cheaper because activities are concentrated.

4. Supports are recovered.

5. Subsidence can be controlled. Visual subsidence is a primary concern of environmentalists. Europeans have been able to adjust their rate of advance to control subsidence, even under cities and harbors, with minimal effect. In most cases, delayed subsidence resulting from room-and-pillar operations may pose a greater problem (6).

6. There is no need to dust the face.

7. Coal extraction rates are higher. Faster and more economical methods of mining are required to insure the Nation of a dependable and reasonable resource. Development rates are relatively the same for both types of mining (200 tons per shift); however, longwall mining will average approximately 700 to 1,000 tons per shift during production versus 200 tons per shift for room-and-pillar operations (6).

Longwalling has been proven and is used almost exclusively in Europe for coal mining. Although European mines operate under more adverse conditions due to greater depth and poor roof conditions, their accident rate is relatively low and coal recovery high.

Longwall mining is not a panacea for all mining conditions. Problems that have to be considered in a longwall mining system include the following:

1. Where the floor is weak, supports may be driven in.

2. A strong roof may not cave properly, hanging up behind the chocks and making it necessary to induce caving.

3. Discontinuities in the seams (faults with significant displacement) are impossible for present mining systems to transverse.

4. Cutter and support systems can adapt to only a minimal variation in coal thickness.

5. A loss of production results from the time lost in changing locations.

6. The tailgate might be subjected to extensive ground pressures as the face abutment pressures from the active panel are superimposed on the existing abutment pressures from the adjacent mined panel.

7. If pillars are left in seams, they transfer their loads to lower seams, and mining of a lower seam may become impossible because of the danger of the pillars "punching" through the roof.

8. Equipment is moved with difficulty in inclined seams.

9. If one element of the longwall is inoperative, it closes the entire wall.

Some of these problems are being addressed at the present time. Solutions include introduction of shortwall mining, shield-type chocks that can adjust to the varying seam heights and navigate poor floor, and the advancing tailgate system.

#### Single-Entry Development

Coal bounces, bumps, or bursts have been a continuing problem in the Sunnyside District of Utah since mining began in the 1890's (7). As mining progresses to great depths, bounces can be expected to increase, with associated larger outburst of methane and worsening support problems in the entries, particularly at intersections. Because of these problems, Kaiser Steel was granted a variance from section 317(f)(4) of the law by MESA in April 1970; this permitted the use of a two-entry system for longwall development. (Normally three or more entries are used in this country.) As a result, roof problems improved, and bounces in the entries were reduced. The company reasoned that additional improvement could be gained with a single-entry system that would accomplish the following:

1. Reduce overall disturbance of virgin coal areas.--This is a big factor in minimizing bounces.

2. Eliminate chain pillars.--Chain pillars have always created a bounce environment at Sunnyside.

3. Eliminate crosscuts and intersections.--This will enhance safety by reducing exposed roof area.

4. Reduce float-coal dust.--Because coal ribs are never stable in deep cover, sloughing and dribbling adds to the dust problem.

5. Improve ventilation.--The total amount of air required to dilute the methane across one exposed coal face will be less than that across several faces where a substantial amount of the air is lost in leakage through curtains and line brattice. Dust control will be improved as dust-laden air goes directly to the return. The greater amount of air in a single face will afford better gas dilution and reduce the concentration of airborne dust.

6. Improve roof support.--Straight-line advance eliminates crosscuts, a major source of support problems.

7. Reduce electrical trouble and cable damage.--Straight-line advance eliminates the necessity of moving equipment through crosscuts.

8. Reduce the number of openings.--This will reduce the required inspection and maintenance.

9. Improve extraction ratio.--Elimination of chain pillars will increase recovery of the minable seam from 75 percent to 80-95 percent and extend our energy reserve. Superimposed seams will be more easily mined because the punch-out effect of chain pillars is eliminated.

10. Increase development rates.--A faster return on capital investment will result from reducing the amount of development equipment and time required to bring a block into production. This in turn should provide a cheaper energy source to the public.

11. Controlled subsidence.--Owing to uniform extraction subsidence gradients should be significantly smaller than those associated with a multiple-entry system.

Of course, the single-entry system will not accomplish all of these things. Numerous unknowns must be evaluated before it can become a workable system. Maintenance of an adequate escapeway, for instance, brings up several problems. Will the wider entry needed for mining equipment, centerline cribs, and an escapeway cause a higher stress concentration in the ribs, extending the failure zone into the standing ribs? The failed material would increase the roof span and possibly aggravate floor and roof convergence or failure. Will a single entry increase or decrease the frequency of bounces or bumps, and if they do occur, will a crib line with partition be strong enough to adequately maintain the escapeway, as well as its integrity as a fire-resistant barrier? And finally, will mining equipment be capable of operating safely in such a confined space?

Some of the problems anticipated with the mining of adjacent longwall panels include whether or not a line of cribs will be able to withstand the side-abutment load produced by the mined-out panels and still maintain the tailgate. Also, will the standing ribs emit a higher percentage of methane because of the absence of pillars, which bleed off faster? If methane is a problem, will ventilation be capable of diluting it to prescribed safety limits, or will the greater volume of air needed increase the velocity because of the smaller cross section and cause dust problems? And again, will bounces and bumps be more prevalent in the rib of the single entry since there will be no pillar to act as a cushion between the active and mined-out panels? Some of these situations are highly unlikely, but will still have to be evaluated.

#### Problem Definition and Research Approach

The objective of this section is to present the problems confronting the project and the approach to their solution. Problems are in three areas; namely, ground control, ventilation, and safety procedures.

#### Ground Control

The Sunnyside coal mines are among the deepest in the United States. In mining a longwall panel, the main support problems occur at the intersections of the entries with the crosscuts and at the head of the gates. Pillars crush or burst, and chocks, cribs, and posts punch into the roof and floor. Future

mining will be pursued at depths of 3,000 feet or more as the bed dips further beneath the mountainous topography, and support problems are expected to become more pronounced. To analyze the ground control of entries, we will look at three separate phases of panel development and extraction: (1) Driving of the entry, (2) mining of the longwall, and (3) long-term maintenance of bleeders.

#### Support During Development

A question with the single-entry drive is, "Will the single entry, divided by crib supports along the center, be stable enough to control the roof and, if a cave or burst occurs on one side of the split entry, will the other side be open for an escapeway?" With multiple entries, if one entry caves shut, miners can escape through another entry. Our approach is to compare the stability of the single and double entries by documenting the loads on supports (cribs, bolts, stulls) and measuring the rate of deformation as the entries advance. Microseismic stations installed during driving will monitor stress buildup in the ribs to identify possible burst conditions.

Structural analysis utilizing two- and three-dimensional finite-element techniques will (1) show the difference in stress between intersection and nonintersection, (2) show why the difference in geologic and structural properties of the roof might cause support problems at one place and not another, (3) determine what amount of support would allow a reasonable safety factor, and (4) determine the role of the pillar in roof support.

#### Support During Longwall Retreating Operation

The biggest question regarding the retreat operation is, "Will the entry, which becomes the tailgate adjacent to the old cave area, be adequately supported to prevent premature failure?" This entry must be maintained as an escapeway and also as an outby to supplement the bleeder ventilation. Our approach to this problem is to (1) study cases where the support system successfully and unsuccessfully limited the cave-line advance of the longwall, and (2) structurally analyze the ground and supports to determine the support rigidity and load-bearing capability needed to control the ground.

Experience and statistics show the tailgate entry presents a difficult support situation in multiple entries where chain pillars are left between the mined-out panel and the active longwall (7). The pillars are prone to bumps and the tailgate is difficult and dangerous to support. Eliminating the pillar by using the single-entry system may eliminate pillar bumps in both headgates and tailgates.

Our main approach to analyzing the structural competence of the tailgate will be structural analysis by means of complex two- and three-dimensional finite-element programs using data generated by the instrumentation described later in this report. The effectiveness of the wood cribs will be evaluated. Determinations will be made as to whether a more rigid crib would be beneficial or would create other problems, such as cracking of the roof and sill,

causing more rock-fall problems in the immediate vicinity. Both field data analyses and finite-element studies will be used for evaluation.

### Support of Bleeder Entry

Bleeders must be maintained during the life of that section of the mine. Since the bleeder's purpose is to drain methane from the gob area, the flow of air must be unobstructed. Longwall equipment is installed in the bleeder, which becomes the first cut area of the longwall advance. Therefore, it could be made as wide as desired if the cave line could be controlled with artificial supports. Plans call for single-entry development. Again, our approach will be data collection and structural and field analysis.

### Ventilation

One of the most important questions about the single-entry feasibility is, "Will the ventilation be good enough to meet standards for methane control during the driving of the single entry and subsequent longwall mining?" Dust control, particularly along the longwall cutting face, is critical with all longwall operations, and conditions may become worse with single entries.

### Methane

Methane concentrations below 1.0 volume-percent must be maintained, and if 1.5 volume-percent or greater is detected, miners must be withdrawn from the area. Cutting equipment automatically shuts down when methane concentrations reach 1.0 volume-percent methane. An explosive mixture exists within the range of 5 to 15 volume-percent methane. The Sunnyside mines are considered gassy mines; according to the company, 2,500 cubic feet of methane was liberated per ton of coal in the No. 1 mine, 16 left, during driving. With a two-entry system, there are separate entries for the inby and outby air. However, with the single entry, both air courses are restricted to one divided entry. Less coal is mined during single-entry development, which reduces the amount of methane liberated and the need for a large volume of air. Methane and air will be measured in both the single-entry portion and the double-entry portion as the entries are driven. This will define the amount of air needed to maintain safe methane dilution when one and two entries are being driven.

Another question is, "How far can a single entry be driven and proper methane drainage maintained without increasing the air velocity to the point where it causes a dust problem?" This will be resolved by regular measurements of methane and air velocity along the entries.

Will there be enough air flowing through the single entry during the longwall operation to maintain the minimum airflow across the longwall face and to keep the air flowing from the entry toward the bleeders? To determine this, methane and air volume will be monitored using portable and automatic recorders placed in the single entry, in the bleeders, and in the tailgate entry.

### Dust

The Mine Safety Act establishes a maximum airborne dust concentration of 5 milligrams per cubic meter, and as little as 0.5 milligram per cubic meter if all the dust is silica. As previously stated, the biggest dust problem with all longwalls, regardless of the entry system used, is the concentration of dust along the longwall face during cutting.

The company is interested in cutting down the airborne dust along the longwall face and has been working with the Bureau in demonstrating dust suppressants. Regular dust samples will be taken by MESA inspectors and company personnel.

### Safety Procedures

Normal preventative methods employed by the mine will be followed. Dusting will be done regularly. All potential causes of fires such as belts, power cables, etc., will be on the outby side of the single-entry divider. Flammable materials such as cribs, will be located on the outby, and the cribs will be treated with a fire-resistant material.

Metal brattice used to line the inby side of the entry will be fire-proofed and sealed. Escape doors will be located every 100 feet along the entry divider.

### PART 2.--FIELD INVESTIGATIONS AT THE SUNNYSIDE NO. 2 MINE

The Sunnyside Mining District of Kaiser Steel Corp. is located 27 miles northeast of Price, Utah, in Carbon County and consists of three mines, Nos. 1, 2, and 3 (fig. 2). The coal is mined from the lower and upper Sunnyside seams in the Blackhawk Formation (a part of the Mesaverde group of late Cretaceous Age). It is a high-volatile-bituminous, marginal-coking coal ranging in rank from A to B (fig. 3).

The test site selected was in the lower seam of the No. 2 mine and was to consist of three parallel entries, 3,500 feet long and 500 feet apart. The first of these was a 1,850-foot section of double entry to be followed by 1,500 feet of single entry. Instrumentation was to be placed at predetermined intervals in both sections (fig. 4); however, only part of the double entry section was driven and instrumented as a test site, and none of the single entry was driven in the No. 2 mine. The test was stopped because a minable seam was defined above the initial test site that previously was believed to be too thin and too close to the lower seam to be minable. This discovery made it necessary to mine the upper seam first or it would be lost. Consequently, a new test site was selected at the No. 1 mine. Although this move delayed the program somewhat, considerable knowledge (instrument design, layout and evaluation, installation procedure, training of personnel, and evaluation of an intersection) was gained, which is the subject of this report. Additional results will be published in succeeding reports.




FIGURE 2. - Location map of the Sunnyside mines.




FIGURE 3. - Stratigraphic section of the Mesaverde group.






FIGURE 4. - Plan map of Sunnyside mine No. 2.

#### Geologic Investigations

The roof at test site 1 in mine No. 2 was described by mine management as treacherous. Miners working daily in this area agreed. Two roof falls, one in the test room adjacent to several load and deformation instruments, and another approximately 120 feet along the entry, confirmed the opinions. Because of the adverse conditions, various geologic phenomena were observed and mapped. These include fractured roof, separations, joints with and without slickensides, bedding-plane shears, faults, joints, and roof falls. Major geologic structures, geologic section, and roof-fall zones are depicted in figure 5. A full discussion of the geology of the area and physical properties of the strata will follow in a later report.

Numerous factors can contribute to roof falls. These include (1) lateral stress or movement in the roof, (2) horizontal separations in the roof strata, (3) highly fractured roof rock, and (4) possibly closed joints running across the entries.




FIGURE 5. - Major geologic structures, geologic section, and roof-fall zones.

### Support System

The mine-approved support plan consisted of 3/4-inch roof bolts and mats installed on a 4-foot grid pattern. Seven- to ten-inch wooden stulls and 3-foot-square wooden cribs were installed alongside each rib according to localized ground conditions. Temporary hydraulic props were installed after each cut to provide support to the face until roof bolts, cribs, and stulls are installed. Figure 6 depicts the methods used for roof control, support types, and density pattern.

### Instrumentation

As in any field project, rugged, cheap, and reliable instrumentation was required. After an extensive search for "off-the-shelf" items for determining roof bolt and crib loads, it was determined that those available were not sensitive enough to identify initial load parameters. Therefore, an in-house task was undertaken to develop load-measuring devices for roof bolts, cribs, and stulls. Essentially, the instrumentation consisted of weldable strain gages on a titanium housing. The roof-bolt cells had a range of 32,000 pounds and a sensitivity of 5 pounds (2) (fig. 7). The crib and stull cells had a range of 250,000 pounds and a sensitivity of 20 pounds (2) (fig. 8). The electrical readout from both cells was obtained from a strain indicator.




FIGURE 6. - Support layout for room No. 1. Post diameters are indicated in inches ("").




FIGURE 7. - Modified full-bridge rock-bolt-load cell.




FIGURE 8. - Strain crib cell.

Hydraulic roof-bolt (fig. 9) and crib cells (fig. 10) were used although they were not sensitive enough for initial deformation. These cells (fabricated by MESA) had the advantage of direct dial readout, which the miner could use in evaluating roof-control problems.

Vertical deformation was measured with a telescoping, stainless-steel extensometer that gave a definition of 0.001 inch (fig. 11). To differentiate between roof and floor movement, precise level measurements were taken on selected points.

To record initial deformation and roof-bolt loads, closure points and roof-bolt-load cells were installed within 1 foot of each other. All instrumented roof-bolt cells were placed on standard mine bolts and installed as part of the normal mine support plan. Each of the bolts was itself a closure point and had an associated surface closure point alongside. Both of these points were referenced to a common down point, which was a 3-foot roof bolt imbedded 18 inches into the floor. The down points were countersunk 2 inches to prevent damage from mining equipment--even so, problems occurred where seam thickness varied or there was considerable floor or roof deformation. Inevitably, the floor had to be remined to regain sufficient clearance, and points had to be replaced.

Wooden cribs were normally placed approximately 100 to 150 feet from the face because no heavy loads were expected on the cribs until the longwall face approached. If heavy ground was encountered, they were placed as close to the




FIGURE 9. - Hydraulic roof-bolt cell.




FIGURE 10. - Hydraulic crib cell.




FIGURE 11. - Stainless steel extensometer.

face as possible (fig. 12). The cribs were built halfway up, and then cells were placed on each corner. After a zero was recorded for each cell, the crib was completed and blocked in. Another reading was taken to record the pre-loading pressure against the roof.

Horizontal closure points consisted of 3-foot bolts installed directly opposite each other in the rib and pillar. The hole was drilled with an air-operated auger, and the expansion anchor was coated with epoxy. A pulley arrangement on one bolt allowed the tape to ride over it. A weight was




FIGURE 12. - Wooden crib.





FIGURE 13. - Horizontal closure-measurement device.

attached to maintain a uniform tension (fig. 13).

Other instruments that were tried in the first test included the brass-rod extensometer installed in the ribs, hydraulic-jack rock-bolt-load cells, and Davis-Derby<sup>5</sup> deformation gages. The brass-rod extensometers were discarded because the rib coal sloughed away from the head, making it impossible to obtain a stable datum point. Hydraulic-jack rock-bolt-load cells were discontinued because an improper seal allowed the fluid to leak and bleed off the tension in the bolt. Davis-Derby motors were discarded due to the insensitivity, having only a one-to-one direct readout.

#### Instrumentation Layout

The instruments designed to document the loads and deformation were located at three different locations in each "room," which was designated as that location where banks or series of instrumentations were installed. Banks of instrumentation were placed across the entries at the midpoint of the pillars, at various points around the pillar, and through the intersection (crosscut). Figure 14 displays the instrument layout for room 1 in mine No. 2. Since hydraulic gages were cheaper than strain gages, they were generally installed in the entry that would cave as the longwall passed.

#### Data Collection and Storage

All data were recorded directly in the field onto preprinted sheets, which correspond to a computer data card. Field data sheets were shipped directly to data processing for key punching and computer storage, thus

---

<sup>5</sup>Reference to specific trade names is made for information only and does not imply endorsement by the Bureau of Mines.






FIGURE 14. - Instrumentation layout for room No. 1.

eliminating any error of transposing data (fig. 15). Data were placed on disk storage for subsequent retrieval, plotting, and analysis. The computer program corrected the data for temperature variations and established the zero point on the calibration curve for each instrument. Support loads and roof deformation could then be plotted with reference to time, entry advance, or longwall retreat.

### Field Results

Results of our first test room in Sunnyside mine No. 2, supported with 5-foot, 3/4-inch bolts on 4-foot centers, showed that even as the entries were being driven, support at the intersections was a problem. The greatest

EXPLANATION		* *			
* CC Crib load cell		C	1	2	3
* CL Closure		C	1	2	3
Field installed number		4	5	6	7
Date 1972		8	9	10	11
Julian date (Nov 6)		12	13	14	15
part of 24 hours		16	17	18	19
250 (p.s.i.)		20	21	22	23
3,471 extensometer reading in inches $\pm .001"$		24	25	26	27
Strain indicator reading (no load - dummy)		28	29	30	31
Distance to operating face from instrument or distance to longwall face during retreat		32	33	34	35
° F		36	37	38	39
Numbers associated to telescoping length of rod		40	41	42	43
		44	45	46	47
		48	49	50	51
		52	53	54	55
		56	57	58	59
		60	61	62	63
		64	65	66	67
		68	69	70	71
		72	73	74	75
		76	77	78	79
		80	81	82	83
		84	85	86	87
		88	89	90	91
		92	93	94	95
		96	97	98	99
		100	101	102	103
		104	105	106	107
		108	109	110	111
		112	113	114	115
		116	117	118	119
		120	121	122	123
		124	125	126	127
		128	129	130	131
		132	133	134	135
		136	137	138	139
		140	141	142	143
		144	145	146	147
		148	149	150	151
		152	153	154	155
		156	157	158	159
		160	161	162	163
		164	165	166	167
		168	169	170	171
		172	173	174	175
		176	177	178	179
		180	181	182	183
		184	185	186	187
		188	189	190	191
		192	193	194	195
		196	197	198	199
		200	201	202	203
		204	205	206	207
		208	209	210	211
		212	213	214	215
		216	217	218	219
		220	221	222	223
		224	225	226	227
		228	229	230	231
		232	233	234	235
		236	237	238	239
		240	241	242	243
		244	245	246	247
		248	249	250	251
		252	253	254	255
		256	257	258	259
		260	261	262	263
		264	265	266	267
		268	269	270	271
		272	273	274	275
		276	277	278	279
		280	281	282	283
		284	285	286	287
		288	289	290	291
		292	293	294	295
		296	297	298	299
		300	301	302	303
		304	305	306	307
		308	309	310	311
		312	313	314	315
		316	317	318	319
		320	321	322	323
		324	325	326	327
		328	329	330	331
		332	333	334	335
		336	337	338	339
		340	341	342	343
		344	345	346	347
		348	349	350	351
		352	353	354	355
		356	357	358	359
		360	361	362	363
		364	365	366	367
		368	369	370	371
		372	373	374	375
		376	377	378	379
		380	381	382	383
		384	385	386	387
		388	389	390	391
		392	393	394	395
		396	397	398	399
		400	401	402	403
		404	405	406	407
		408	409	410	411
		412	413	414	415
		416	417	418	419
		420	421	422	423
		424	425	426	427
		428	429	430	431
		432	433	434	435
		436	437	438	439
		440	441	442	443
		444	445	446	447
		448	449	450	451
		452	453	454	455
		456	457	458	459
		460	461	462	463
		464	465	466	467
		468	469	470	471
		472	473	474	475
		476	477	478	479
		480	481	482	483
		484	485	486	487
		488	489	490	491
		492	493	494	495
		496	497	498	499
		500	501	502	503
		504	505	506	507
		508	509	510	511
		512	513	514	515
		516	517	518	519
		520	521	522	523
		524	525	526	527
		528	529	530	531
		532	533	534	535
		536	537	538	539
		540	541	542	543
		544	545	546	547
		548	549	550	551
		552	553	554	555
		556	557	558	559
		560	561	562	563
		564	565	566	567
		568	569	570	571
		572	573	574	575
		576	577	578	579
		580	581	582	583
		584	585	586	587
		588	589	590	591
		592	593	594	595
		596	597	598	599
		600	601	602	603
		604	605	606	607
		608	609	610	611
		612	613	614	615
		616	617	618	619
		620	621	622	623
		624	625	626	627
		628	629	630	631
		632	633	634	635
		636	637	638	639
		640	641	642	643
		644	645	646	647
		648	649	650	651
		652	653	654	655
		656	657	658	659
		660	661	662	663
		664	665	666	667
		668	669	670	671
		672	673	674	675
		676	677	678	679
		680	681	682	683
		684	685	686	687
		688	689	690	691
		692	693	694	695
		696	697	698	699
		700	701	702	703
		704	705	706	707
		708	709	710	711
		712	713	714	715
		716	717	718	719
		720	721	722	723
		724	725	726	727
		728	729	730	731
		732	733	734	735
		736	737	738	739
		740	741	742	743
		744	745	746	747
		748	749	750	751
		752	753	754	755
		756	757	758	759
		760	761	762	763
		764	765	766	767
		768	769	770	771
		772	773	774	775
		776	777	778	779
		780	781	782	783
		784	785	786	787
		788	789	790	791
		792	793	794	795
		796	797	798	799
		800	801	802	803
		804	805	806	807
		808	809	810	811
		812	813	814	815
		816	817	818	819
		820	821	822	823
		824	825	826	827
		828	829	830	831
		832	833	834	835
		836	837	838	839
		840	841	842	843
		844	845	846	847
		848	849	850	851
		852	853	854	855
		856	857	858	859
		860	861	862	863
		864	865	866	867
		868	869	870	871
		872	873	874	875
		876	877	878	879
		880	881	882	883
		884	885	886	887
		888	889	890	891
		892	893	894	895
		896	897	898	899
		900	901	902	903
		904	905	906	907
		908	909	910	911
		912	913	914	915
		916	917	918	919
		920	921	922	923</




FIGURE 16. - Deformation profile through the centerline of the crosscut. Closure-measurement-location (CL) numbers are shown.




FIGURE 17. - Deformation profile across the entries at the centerline of the pillar. Closure-measurement-location (CL) numbers are shown.




FIGURE 18. - Composite deformation profile at the test site.




FIGURE 19. - Roof-bolt-load profile through the centerline of the crosscut. Roof-bolt (RB) location numbers are shown.




FIGURE 20. - Roof-bolt-load profile across the entries at the centerline of the pillar. Roof-bolt (RB) location numbers are shown.




FIGURE 21. - Composite roof-bolt-load profile at the test site.




FIGURE 22. - Load profile of a wooden crib near the fall. Crib-load cell (CC) numbers are shown.




FIGURE 23. - Deformation profile across the entry where the fall occurred:

and they would be unable to withstand the abutment load as the longwall face approached. Several bolts failed along the centerline soon after being installed, including one that was instrumented. Bolt-load and roof-deformation measurements in the immediate vicinity of the caves along the pillar corners showed low bolt loads and high roof closures, indicating anchor slippage or separation above the anchor (figs. 21-22). The pillar corner (filet) has a high differential stress with associated high stresses in the roof rock. The rock probably broke around the anchor, loosening it. Longer bolts, resin bolts, angled bolts at the corners, and pillar softening are areas in which research is being conducted that may alleviate the problem. The single entry, of course, eliminates the intersection corners. In the double entry of the No. 2 mine, cribs were installed adjacent to the

ribs. Because the wood cribs have high yield characteristics, they showed very little load during driving of the entry. They are not expected to bear much load until they become influenced by retreat of longwall.

Owing to the limited length of the test, no significant work was done on ventilation. The only comment that can be made is that no problems were encountered.

#### Fine-Element Analysis

The Bureau of Mines awarded a contract to Agbabian Associates to conduct a three-dimensional finite-element structural analysis of the intersection of a crosscut and entry at the Sunnyside No. 2 mine. Work was begun in June 1973 and completed June 1976 (1). The region of the mine considered in the analysis is part of a double entry instrumented under the Single Entry Project.



The calculation was performed using the computer code BMINES developed under an earlier contract with the Bureau. This code is a static, three-dimensional code with an extensive library of nonlinear, inelastic material behavior and is equipped with specially designed capabilities for simulating mining situations. In particular, excavation and installation of structural support systems during mining can be modeled.

#### CONCLUSION

Field evaluation verified the fact that the rock bolts in use were not satisfactory; some failed during entry development. The bolts were taxed to their limit and would not be able to take additional loading. Higher strength bolts, angled bolts, or fully grouted resin bolts may provide the needed support capacity to maintain the integrity of the entry as the longwall retreats.

It appears that roof-bolt-load profiles are not good indicators of roof falls; however, amount and/or rate of closure may provide advance warning of impending roof failure.

Although the test area had to be moved, valuable information was gained. Instruments were evaluated, with some being discarded as unsuitable. Installation procedure was perfected, good working relationships were developed with the mine personnel, and project personnel were in training. In addition, the computer program was rewritten to permit more selectivity in retrieval of stored data, more efficient coding of the instrumentation, and easier instrumentation.

Since this report, two single entries have been successfully driven at the second test site in mine No. 1 at Sunnyside. Results of these documentations will be published in subsequent reports. Reference 9 is a brief article covering some of the later work.

## REFERENCES

1. Balachandra, M. B. Three-Dimensional Finite-Element Analysis of Crosscut and Entry Intersection of a Double Entry Coal Mine. June 1976, 9 pp.; available for consultation at Bureau of Mines Mining Research Center, Spokane, Wash.
2. Beus, M. J., and E. L. Phillips. Development of Titanium Load Cells for Support Load Determination. BuMines RI 7972, 1974, pp. 6-18.
3. Kuti, J. Outlook of Longwall Mining Systems in the U.S. Coal Age, v. 77, No. 8, August 1972, pp. 64-73.
4. \_\_\_\_\_. 1976 U.S. Bureau of Mines Census of Operating American Longwall Installations. Coal Age, v. 82, No. 1, January 1977, pp. 99, 102, 107.
5. Mayberry, J. O. Sedimentary Features of the Blackhawk Formation (Cretaceous) in the Sunnyside District, Carbon County, Utah. U.S. Geol. Survey Prof. Paper 688, 1971, 44 pp.
6. Obert, L., and C. Rich. Feasibility Study for a Bureau of Mines Longwall Mining Research Program. February 1971, pp. 1-10; available for consultation at Bureau of Mines Mining Research Center, Spokane, Wash.
7. Osterwald, F. W., and C. R. Dunwood. Instrument Study of Coal Mine Bumps, Sunnyside District, Utah. Utah Geol. and Miner. Survey Bull. 80, 1966, pp. 97-111.
8. Peele, R. Mining Engineering Handbook. John Wiley & Sons, Inc., New York, 1945, 505 pp.
9. Poad, M. E., E. L. Phillips, and E. T. Bowers. Single Entry Development for Longwall Mining. Proc. 1st Symp. on Underground Mining. v. 1, Oct. 21-23, 1975, Louisville, Ky. 1975, pp. 135-151.
10. Schmidt, R. A. Underground Coal Mining, An Assessment of Technology. Hittman Associates, Inc., Columbia, Md., July 1976, pp. 22-23.
11. Stefanko, R. Longwall Mining. Pa. State Univ. Press, University Park, Pa., 1972, pp. 1-5.
12. U.S. Bureau of Mines. Coal Mining Industrial Fatalities in 1972. Mineral Industry Survey, 1973, pp. 1-10.
13. \_\_\_\_\_. Coal Mine Injuries and Worktime. Annual Summary 1972. Mineral Industry Survey, 1973, 11 pp.