

NIOSH/OSHA STANDARDS COMPLETION PROGRAM

DRAFT TECHNICAL STANDARD AND
SUPPORTING DOCUMENTATION FOR

*** SEC-BUTYL ACETATE ***

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

The basic text of this document contains the draft technical standard approved by the Joint Review Committee of the NIOSH/OSHA Standards Completion Program and the supporting documentation for the substance SEC-BUTYL ACETATE.

The SCP draft technical standards are recommendations to the Department of Labor for its consideration in rulemaking and have no legal status until final rules have been promulgated by that agency. This draft standard is provided for your information only.

The References and Sources, Respirator Table Documentation and Use/Exposure and Control Documentation are the working documents used by the various SCP working groups during the development of the draft technical standard and serve as the technical foundation for the standard. The classification for each substance and the regulatory statements were derived following a decision logic established for the various sections of the standard.

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

(a) DEFINITIONS

- (1) PERMISSIBLE EXPOSURE - "Permissible Exposure" means inhalation of sec-butyl acetate in concentrations not in excess of 200 parts per million (ppm) (950 milligrams per cubic meter, mg/cu.m.) averaged over an eight hour work shift, as stated in section 1910.93, Table G-1.
- (2) ACTION LEVEL - "Action Level" means one half (1/2) of the permissible exposure for sec-butyl acetate.

(b) EMPLOYEE INFORMATION - Each employer who has a workplace in which sec-butyl acetate is present shall:

- (1) STANDARD AVAILABILITY - Keep a copy of this section with its appendices A, B and C, at the workplace. This material shall be made readily available to affected employees; and
- (2) PRESENCE OF SEC-BUTYL ACETATE - Inform affected employees of the quantity, location, and manner of use or storage of sec-butyl acetate.

(c) EXPOSURE MEASUREMENT

- (1) INITIAL DETERMINATION - Each employer who has a place of employment in which sec-butyl acetate is released into the workplace air shall determine if any employee may be exposed to airborne concentrations of sec-butyl acetate at or above the action level. The determination shall be made each time there is a change in production, process, or control measures which could result in an increase in airborne concentrations of sec-butyl acetate. A written determination shall be made and it shall contain at least the following information:
 - (i) Any information, observations, or calculations which would indicate employee exposure to sec-butyl acetate;
 - (ii) Any measurements of airborne concentrations of sec-butyl acetate taken;
 - (iii) Any employee complaints of symptoms which may be attributable to exposure to sec-butyl acetate; and
 - (iv) Date of determination, work being performed at the time, location within work site, name, and social security number of each employee considered.
- (2) INITIAL EXPOSURE MEASUREMENT - If the employer determines that any employee may be exposed to airborne concentrations of sec-butyl acetate at or above the action level, the exposure of the employee believed to have the greatest exposure shall be measured. The exposure measurement shall be representative of the maximum exposure of the employee.
- (3) IDENTIFICATION OF EXPOSED EMPLOYEES - If the exposure measurement taken under paragraph (c)(2) of this section reveals employee exposure to airborne concentrations of sec-butyl acetate at or above the action level, the employer shall:
 - (i) Identify all employees who may be exposed at or above the action level; and
 - (ii) Measure the exposure of the employees so identified.
- (4) EXPOSURE ABOVE THE ACTION LEVEL - If an employee exposure measurement reveals that an employee is exposed to airborne concentrations of sec-butyl acetate at or above the action level,

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

but not above the permissible exposure, the exposure of that employee shall be measured at least every two months.

- (5) EXPOSURE ABOVE THE PERMISSIBLE EXPOSURE - If an employee exposure measurement reveals that an employee is exposed to airborne concentrations of sec-butyl acetate above the permissible exposure, the employer shall:

- (i) Inform the employee of the exposure as required by paragraph (N)(1) of this section; and
- (ii) Measure the exposure of the employee at least monthly; and
- (iii) Institute control measures as required by paragraph (E) of this section.

- (6) TERMINATION OF EXPOSURE MEASUREMENT - If two consecutive employee exposure measurements taken at least one week apart reveal that the employee is exposed to airborne concentrations of sec-butyl acetate below the action level, the employer may terminate measurement for the employee. For purposes of this subparagraph, use of respirators shall not constitute reduction of employee exposure below the action level.

- (d) METHODS OF MEASUREMENT - An employee's exposure shall be obtained by any combination of long term or short term samples which represents the employee's actual exposure averaged over an eight hour work shift (Appendix B (iv)). The method of measurement shall have an accuracy, to a confidence level of 95%, of not less than that given in Table 1 below.

Table 1

Concentration	Required Accuracy
Above permissible exposure	Plus or Minus 25%
At or below permissible exposure and above the action level	Plus or Minus 35%
At or below the action level	Plus or Minus 50%

- (e) Methods of Compliance

- (1) Engineering controls - No employee shall be exposed to sec-butyl acetate above the permissible limit as defined in paragraph (a)(1) of this section. Engineering and work practice controls shall be used to reduce exposure to sec-butyl acetate to at or below the permissible exposure.

- (i) When mechanical ventilation is used to control exposure, measurements which demonstrate system efficiency (for example: air velocity, static pressure, or air volume) shall be made at least every three months. Measurements of system efficiency shall also be made within five work days of any change in production, process or control which might result in a reduction in control.

- (ii) In the design of open surface tank ventilation for the purposes of compliance with section 1910.94 (d), operations involving sec-butyl acetate shall be classified as B-2 at 70 F.

- (iii) Where a fan is located in duct work and where sec-butyl acetate is present in concentrations greater than 4250 ppm, one fourth of the lower flammable limit, the fan rotating element shall consist of, or be lined with nonsparking material. There shall be sufficient clearance between the

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

fan rotating element and the fan casing so as to prevent contact.

(2) Respirators

- (i) Compliance with the permissible exposure may not be achieved by the use of respirators except:
 - (a) During the time period necessary to install engineering controls; or
 - (b) In work situations in which engineering controls are technically not feasible; or
 - (c) In work situations in which feasible engineering and work practice controls are insufficient to reduce employees exposure to at or below the permissible exposure. Where technically feasible engineering and work practice controls are not sufficient to reduce exposure to at or below permissible exposure, they shall be used to reduce exposure to the lowest level feasible; or
 - (d) For operations not exceeding 40 hours per year; or
 - (e) In emergencies.
- (ii) Respirators shall be jointly approved by the Mining Enforcement and Safety Administration (formerly Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR Part 11.
- (iii) Employers shall select and provide the appropriate respirator from Table 2 and shall ensure that the employee uses the respirator provided.
- (iv) Employers shall institute a respiratory protection program in accordance with sections 1910.134(b),(d),(e),(f) and (g).

TABLE 2. RESPIRATORY PROTECTION FOR sec-BUTYL ACETATE

Condition	Permissible Respiratory Protection
Vapor Concentration	
Equal to or Less than 1000 ppm	organic vapor cartridge(s).
Equal to or Less than 5000 ppm	
Equal to or Less than 10000 ppm	Any supplied-air respirator with a full facepiece, helmet or hood. Any self-contained breathing apparatus with a full facepiece.

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

Greater than 10000 ppm or, Entry and Escape from Unknown Concentrations	Self-contained breathing apparatus with a full facepiece operated in pressure-demand (positive pressure) mode. air respirator with a full facepiece operated in pressure- auxiliary self-contained air supply operated in pressure- demand mode.
Fire Fighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand (positive pressure) mode.
Escape	Any gas mask providing protection against organic vapors. Any escape self-contained breathing apparatus.

(f) Fire and Safety - Employers shall familiarize themselves with the information contained in the Substance Technical Guidelines for sec-butyl acetate which is contained in Appendix B in order to ensure the safe handling and use of sec-butyl acetate.

- (1) Electrical - For the purposes of compliance with section 1910.309, locations classified as hazardous locations due to the presence of sec-butyl acetate shall be Class I Group D.
- (2) Portable fire extinguishers - For the purposes of compliance with section 1910.157, sec-butyl acetate is classified as a Class B fire hazard.
- (3) Powered industrial trucks - For the purposes of compliance with section 1910.178, locations classified as hazardous locations due to the presence of sec-butyl acetate shall be Class I Group D.
- (4) Flammable liquids - For the purposes of compliance with section 1910.106, liquid sec-butyl acetate is classified as a Class IB flammable liquid. Spray finishing operations shall be performed in accordance with sections 1910.107 and 1910.94(c). Dip tank operations shall be performed in accordance with sections 1910.108 and 1910.94(d).
- (5) Sources of ignition - Sources of ignition such as smoking or open flames are prohibited where sec-butyl acetate is handled, used or stored in a manner so as to create a potential fire or explosion hazard.
- (6) Storage - Sec-butyl acetate shall be stored so as not to come in contact with nitrates, strong oxidizers, strong acids or strong alkalis.

(g) Personal Protective Equipment

(1) Skin Contact

- (i) Employers shall provide, and require employees to use, impervious clothing, gloves, face shields (8 inch minimum) and other appropriate protective clothing necessary to prevent repeated or prolonged skin contact to sec-butyl acetate. Face shields shall comply with section 1910.133(a)(6).

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

(ii) Employers shall ensure that clothing which becomes wet with liquid sec-butyl acetate be removed immediately and not reworn until the sec-butyl acetate is removed from the clothing.

(2) Eye Contact

(i) Employers shall provide, and require employees to use, splash-proof safety goggles (cup-cover type dust and splash safety goggles), which comply with section 1910.133(a)(6), where eye contact to liquid sec-butyl acetate may occur.

(h) Spills

(1) Spills of sec-butyl acetate shall be cleaned up immediately after eliminating potential sources of ignition and utilizing available ventilation.

(2) Sec-butyl acetate liquid may not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

(i) Sanitation

(1) Employers shall ensure that employees whose skin becomes wet with liquid sec-butyl acetate promptly wash or shower as necessary to remove any sec-butyl acetate from the skin.

(j) Training and Information - Each employer who has employees exposed to sec-butyl acetate in excess of the action level, or employees who may have skin or eye contact with liquid sec-butyl acetate, or employees who work where accidental release, spill, fire, or explosion of sec-butyl acetate may occur, shall annually:

(1) Substance Safety Data Sheet - Inform each employee of the information contained in the Substance Safety Data Sheet for sec-butyl acetate, which is contained in Appendix A; and

(2) Medical -

(I) Advise employees as to the signs and symptoms of exposure to sec-butyl acetate.

(II) Instruct the employees to advise the employer of the development of signs and symptoms of exposure to sec-butyl acetate which are listed in Appendix A.

(III) Instruct the employees to inform the employer if they develop any of the medical conditions listed in (k)(2) of this section; and

(3) Procedures -

(I) Provide training to ensure that employees understand the precautions of safe use, emergency procedures, and the correct use of protective equipment relative to sec-butyl acetate.

(II) The procedures required by (j)(1), (2), and (3)(I) shall be provided to employees at the expense of the employer during the employee's normal working hours.

(k) Medical Surveillance

- (1) The employer shall provide medical procedures as required by paragraph (k). These procedures shall be provided at no cost to the employee.

(2) Preplacement Questionnaire - The employer shall obtain from each employee who will be exposed to liquid sec-butyl acetate, or

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

airborne concentrations of sec-butyl acetate at or above the action level, a written statement as to whether such employee has a history of any of the following:

- (I) Skin disease
- (II) Chronic lung disease
- (III) Liver disease
- (IV) Kidney disease

- (3) Preplacement Medical Examination - The employer shall provide a medical examination for an employee if the employee provides a history of any of the conditions named in paragraph (k)(2).
- (4) Results of Preplacement Examination - The employer shall obtain a physician's written opinion based on the medical examination pursuant to paragraph (k)(3).
- (5) Periodic Medical Examinations - The employer shall provide a medical examination for an employee if the employee advises the employer of the development of (i) any of the medical conditions listed in (k)(2), (ii) signs and symptoms listed in Appendix A which the employee suspects may be caused by exposure to sec-butyl acetate.
- (6) Results of Periodic Examinations - The employer shall obtain a physician's written opinion based on the medical examination pursuant to paragraph (k)(5).
- (7) Exclusion or Removal from Exposure - No employee shall continue to be exposed to sec-butyl acetate if such exposure could place the employee at increased risk of material impairment of his health.
- (8) Emergency Procedures - The employer shall provide emergency and follow-up medical examinations and treatment for any employee injured through exposure to sec-butyl acetate.
- (9) Informing the Physician - The employer shall provide to the examining physician the following information:
 - (I) A copy of this section with its Appendices A, B and C for sec-butyl acetate;
 - (II) A description of the employee's duties as they relate to his exposure to sec-butyl acetate;
 - (III) A description of any personal protective equipment required to be used;
 - (IV) The results of any employee's exposure measurement, if available;
 - (V) The employee's anticipated exposure level; and
 - (VI) Upon request of the physician, information from previous medical examination of the employee.

- (10) Physician's Written Opinion

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

(I) The physician's written opinion shall be a signed statement by the examining physician specifically stating:

(A) Whether the employee has any detected medical conditions which could be directly or indirectly aggravated by exposure to sec-butyl acetate or which could significantly interfere with the ability of the employee to follow recommended or required procedures for protecting himself from unusual or emergency exposure.

(B) Any recommended limitations upon the employee's exposure to sec-butyl acetate.

(C) The employee has been informed by the physician of any detected medical conditions which require further medical examination or treatment.

(II) The written opinion shall not reveal medical information unrelated to exposure to sec-butyl acetate.

(11) Refusal to be Medically Examined - If an employee refuses any required medical examination, the employer shall inform the employee of the possible health consequences of such refusal and obtain a signed statement from the employee indicating that the employee understands the risks involved by refusing to be examined.

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

- (1) Recordkeeping.
 - (1) Initial determination.
 - (i) The employer shall keep an accurate record of all initial determinations required to be made pursuant to paragraph (c)(1) of this section.
 - (ii) The record shall include the written determination and any supporting documentation as required in paragraph (c)(1) of this section.
 - (iii) This record shall be maintained for at least one year.
 - (2) Exposure measurements.
 - (i) The employer shall keep an accurate record of all measurements taken to determine employee exposure to sec-butyl acetate.
 - (ii) This record shall include:
 - (a) The date of measurement;
 - (b) A reference to the subparagraph of this regulation which required the measurement, if any;
 - (c) Operations involving exposure to sec-butyl acetate which are being monitored;
 - (d) Sampling and analytical methods used and evidence of their accuracy;
 - (e) Number, duration, and results of samples taken;
 - (f) Name, Social Security number, and exposure of the employee monitored.
 - (iii) This record shall be maintained for one year.
 - (3) Mechanical ventilation.
 - (i) When mechanical ventilation is used as an engineering control, the employer shall maintain a record of measurements demonstrating the effectiveness of such ventilation as required by paragraph (e)(1)(i) of this section.
 - (ii) This record shall include:
 - (a) Date of measurement;
 - (b) Type of measurement taken;
 - (c) Result of measurement.
 - (iii) This record shall be maintained for one year.
 - (4) Training and information.
 - (i) The employer shall keep an accurate record of all employee training and advice required by paragraph (j) of this section.
 - (ii) The record shall include:
 - (a) Date of training;
 - (b) Name and Social Security number of employees trained;
 - (c) Substance of training provided.
 - (iii) This record shall be maintained for at least one year.
 - (5) Medical records.
 - (i) The employer shall keep an accurate medical record for each employee.
 - (ii) The record shall include:
 - (a) Physician's written opinion;
 - (b) Preplacement questionnaire;
 - (c) Any employee medical complaints relative to exposure to sec-
 - (d) A signed statement of any refusal to be examined;

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

- (e) A copy of information provided to the physician pursuant to paragraph (k)(9) (ii) through (vi) of this section.
- (iii) This record shall be maintained for the duration of the employment of the affected employee.
- (6) Access to records.
 - (i) All records required to be maintained by this section shall be made available upon request to authorized representatives of the Assistant Secretary and the Director.
 - (ii) Employee exposure measurement records required to be maintained by this section shall be made available to employees and former employees and their designated representatives.
 - (iii) Employee medical records required to be maintained by this section shall be made available upon written request to a physician designated by the employee or former employee.
- (m) Observation of monitoring.
 - (1) Duty.

The employer shall give affected employees or their representatives an opportunity to observe any monitoring of employee exposure to sec-butyl acetate which is conducted pursuant to this section.
 - (2) Exercise of opportunity to observe monitoring.
 - (i) When observation of the monitoring of employee exposure to sec-butyl acetate requires entry into an area where the use of personal protective devices is required, the observer shall use such equipment and comply with all other applicable safety procedures.
 - (ii) Without interfering with the measurement, observers shall be entitled to:
 - (a) Receive an explanation of the measurement procedures;
 - (b) Visually observe all steps related to the measurement of exposure to sec-butyl acetate that are being performed at the place of exposure.
 - (c) Record the results obtained.
- (n) Employee notification.
 - (1) The employer shall notify in writing, within five work days, every employee who is found to be exposed to sec-butyl acetate above the permissible exposure. The employee shall also be notified of the level of his exposure and the corrective action being taken to reduce the exposure to at or below the permissible exposure.
 - (2) Pursuant to paragraph (k) of this Section, when an employee is medically examined the employer shall provide the employee with a copy of the physician's written opinion.

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

Butyl Acetate

APPENDIX A

SUBSTANCE SAFETY DATA SHEET

I. SUBSTANCE IDENTIFICATION

SUBSTANCE: sec-Butyl acetate

PERMISSIBLE EXPOSURE: 200 parts of sec-butyl acetate vapor per million parts of air (ppm) or 950 milligrams of sec-butyl acetate vapor per cubic meter of air (mg/cu m)

APPEARANCE AND ODOR: Colorless liquid with a pleasant odor.

II. HEALTH HAZARD DATA

A. Ways in Which the Chemical Affects Your Body: Sec-butyl acetate can affect your body if you inhale it or if it comes in contact with your skin or eyes or if you swallow it.

B. Effects of Overexposure:

1. Short-Term Overexposure: Overexposure to sec-butyl acetate may cause irritation of eyes, nose and throat. Severe overexposure may cause weakness, drowsiness and unconsciousness.
2. Long-Term Overexposure: Prolonged overexposure may produce irritation of the skin.
3. Reporting Signs and Symptoms: You should inform your employer if you develop any signs or symptoms associated with sec-butyl acetate exposure.

III. EMERGENCY FIRST AID PROCEDURES

- A. Eye Exposure: If sec-butyl acetate gets into your eyes, wash the eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.
- B. Skin Exposure: If nonimpervious clothing becomes wet with sec-butyl acetate immediately remove and clean the clothing before wearing again. If sec-butyl acetate gets on your skin, flush the contaminated skin with water promptly. If there is skin irritation, get medical attention.

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

- C. Breathing: If you or any other person breathes in large amounts of sec-butyl acetate remove the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.
- D. Swallowing: When sec-butyl acetate has been swallowed get medical attention immediately. If medical attention is not immediately available get the affected person to vomit by having him touch the back of his throat with his finger or by giving him large amounts (one pint or more) of warm salt water (two tablespoons of salt per pint of water). Do not make an unconscious person vomit.
- E. Rescue: Move affected person from the hazardous exposure. If the exposed person has been overcome, notify someone else and put into effect the established emergency rescue procedures. Do not become a casualty yourself. Understand your emergency rescue procedures and know the locations of the equipment before the need arises.

IV. RESPIRATORS AND PROTECTIVE CLOTHING

- A. RESPIRATORS: Respirators are not the best way to control exposure to sec-butyl acetate. You can only be required to wear them for routine use if your employer is in the process of installing controls or other control measures prove inadequate. You may be required to wear respirators for non-routine activities or in emergencies. If respirators are worn, they must have a Mining Enforcement and Safety Administration (MESA)/National Institute for Occupational Safety and Health (NIOSH) approval label. (Older respirators may have a Bureau of Mines approval label.) If you can smell sec-butyl acetate while wearing a respirator, the respirator is not working correctly; go immediately to fresh air. If you experience difficulty breathing while wearing a respirator, tell your employer.
- B. PROTECTIVE CLOTHING: You must wear impervious clothing, gloves, face shield, and other appropriate protective clothing to prevent repeated or prolonged skin contact with liquid sec-butyl acetate.
- C. EYE PROTECTION: You must wear splash-proof safety goggles (cup-cover type dust and splash safety goggles) where eye contact with liquid sec-butyl acetate may occur.

V. PRECAUTIONS FOR SAFE USE, HANDLING AND STORAGE

sec-Butyl acetate is a flammable liquid and its vapors easily form explosive mixtures with air. It must be stored in tightly closed containers in a cool, well-ventilated area away from heat, sparks and flames. Store sec-butyl acetate away from nitrates, strong oxidizers, strong alkalies, and strong acids. Sources of ignition such as smoking and open flames are prohibited wherever sec-butyl acetate is handled, used or stored in a manner that could create a potential fire or explosion hazard. You must use non-sparking tools when opening or closing metal containers of sec-butyl acetate, and containers must be bonded and grounded when pouring or transferring liquid sec-butyl acetate. If your skin becomes wet with liquid sec-butyl acetate, you must promptly wash or shower as necessary to remove any sec-butyl acetate from the skin. You must immediately remove any clothing that becomes wet with liquid sec-butyl acetate and this clothing must not be reworn until

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

the sec-butyl acetate is removed from the clothing. Fire extinguishers and eye flushing facilities, where provided, must be readily available and you should know where they are and how to operate them. Ask your supervisor where sec-butyl acetate is used in your work area and for any additional plant safety rules.

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

APPENDIX B

SUBSTANCE TECHNICAL GUIDELINES
SEC-BUTYL ACETATE

I. PHYSICAL AND CHEMICAL DATA

A. Substance Identification

1. Synonyms: 1-Methylpropyl acetate
2. Formula: CH3COOCH(CH3)C2H5
3. Molecular weight: 116

B. Physical Data

1. Boiling point (760 mm Hg): 112 C (234 F)
2. Specific gravity (water=1): 0.86
3. Vapor density (air=1 at boiling point of sec-butyl acetate): 4.0
4. Melting point: -99 C (-146 F)
5. Vapor pressure at 20 C (68 F): 10 mm Hg
6. Solubility in water, % by weight at 20 C (68 F): 0.8
7. Evaporation rate (butyl acetate=1): 2.0
8. Appearance and odor: Colorless liquid with a pleasant odor

II. FIRE, EXPLOSION AND REACTIVITY HAZARD DATA

A. Fire

1. Flash point: 16.7 C (62 F) (closed cup)
2. Autoignition temperature: Data not available
3. Flammable limits in air, % by volume: Lower: 1.7; Upper 9.8
4. Extinguishing media: Dry chemical, carbon dioxide, foam
5. Special fire-fighting procedures: Do not use solid stream of water since stream will scatter and spread fire. Use water spray to cool containers exposed to a fire.
6. Unusual fire and explosion hazards: sec-Butyl acetate is a flammable liquid. Its vapors can easily form explosive mixtures with air. All ignition sources must be controlled where sec-butyl acetate is used, handled or stored. sec-Butyl acetate vapors are heavier than air and may travel along the ground and be ignited by sparks or open flames at locations remote from the site at which sec-butyl acetate is handled.
7. For purposes of conforming to the requirements of 29 CFR 1910.106, sec-butyl acetate is classified as a Class IB flammable liquid. At 4250 ppm, one-fourth of the lower flammable limit, sec-butyl acetate is considered to be a potential fire and explosion hazard.
8. For purposes of complying with 29 CFR 1910.309, the classification of hazardous locations as described in Article 500 of

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

the National Electrical Code for sec-butyl acetate shall be Class I, Group D.

B. Reactivity

1. Conditions contributing to instability: Heat
2. Incompatibilities: Contact with nitrates, strong oxidizers, strong alkalis, and strong acids may cause fire and explosion.
3. Hazardous decomposition products: Toxic gases and vapors (such as Carbon monoxide) may be released in a fire involving sec-butyl acetate.
4. Special precautions: Sec-butyl acetate will soften and dissolve many plastics.

III. SPILL, LEAK, AND DISPOSAL PROCEDURES

A. If sec-butyl acetate is spilled or leaked, the following steps should be taken:

1. Remove all ignition sources
2. Ventilate area of spill or leak
3. For small quantities, absorb on paper towels. Evaporate in a safe place (such as a fume hood) and burn the paper. Large quantities can be collected and atomized in a suitable combustion chamber. Sec-butyl acetate may not be allowed to enter a confined space, such as a sewer, because of the possibility of an explosion.

B. Persons not wearing protective equipment should be restricted from areas of spills or leaks until cleanup has been completed.

C. Waste Disposal Methods:

Sec-butyl acetate may be disposed of:

1. By absorbing it in vermiculite, dry sand, earth or a similar material and disposing in a sanitary land fill.
2. By atomizing in a suitable combustion chamber.

IV. MONITORING AND MEASUREMENT PROCEDURES

a. EXPOSURE ABOVE THE ACTION LEVEL: Measurements taken for the purpose of determining employee exposure under this section are best taken such that the average 8-hour exposure may be determined from a single sample or two (2) 4-hour samples. Short term interval samples (up to 30 minutes) may also be used to determine average exposure level if a minimum of five (5) measurements are taken in a random manner over the 8-hour work shift. Random sampling means that any portion of the work shift has the same chance of being sampled as any other. The arithmetic average of all such random equal duration samples taken on one (1) work shift is an estimate of an employee's average level of exposure for that work shift. Air samples should be taken in the employee's breathing zone (air that would most nearly represent that inhaled by the employee). Sampling and analyses may be performed by instruments such as detector tubes certified by NIOSH under 42 CFR Part 84, portable direct-reading instruments, gas and vapor adsorption tubes with subsequent chemical analyses or dosimeters. The method of measurement must determine the concentration of sec-Butyl acetate to plus or minus 35%.

b. EXPOSURE ABOVE THE PERMISSIBLE EXPOSURE: The monitoring under this section should be essentially the same as described under paragraph IV. a. Laboratories performing chemical analyses should be

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

accredited in Industrial Hygiene Chemistry by the American Industrial Hygiene Association (AIHA). The method of measurement must determine the concentration of sec-Butyl acetate to plus or minus 25%. Methods meeting these accuracy requirements are available in the "NIOSH Monitoring Methods Manual".

V. MISCELLANEOUS PRECAUTIONS

- A. Store sec-butyl acetate in tightly closed containers in a cool, well-ventilated area.
- B. High exposures to sec-butyl acetate can occur when transferring the liquid from one container to another.
- C. Non-sparking tools must be used to open and close metal sec-butyl acetate containers. These containers must be effectively grounded and bonded prior to pouring.
- D. Employers must advise employees of all plant areas and operations where exposure to sec-butyl acetate could occur.

VI. COMMON OPERATIONS

Common operations in which exposure to sec-butyl acetate is likely to occur are: operations involved in its manufacture and in its use as a solvent for lacquers in films, coatings, adhesives.

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

APPENDIX C - MEDICAL SURVEILLANCE GUIDELINES

I. ROUTE OF ENTRY

Inhalation; insignificant skin absorption.

II. TOXICOLOGY

The principal effects of overexposure to sec-butyl acetate are irritation of the eyes and nose and narcosis at high concentrations. No chronic systemic effects have been reported in humans. Anesthetic effects were not observed in man at levels of 400-600 ppm in exposures of 2-3 hours.

III. SIGNS AND SYMPTOMS

Irritation of the eyes; headache; drowsiness;
dryness of the upper respiratory tract and the skin.

IV. SPECIAL TESTS

None in common usage.

V. TREATMENT

None specific. Remove from exposure, give artificial resuscitation if indicated, and wash eyes and contaminated skin. Recovery is usually rapid and complete.

VI. SURVEILLANCE AND PREVENTIVE CONSIDERATIONS

A. GENERAL

Most reported effects of sec-butyl acetate are caused by its irritant properties. It is important that the physician become familiar with plant operating conditions in which exposure to sec-butyl acetate occurs. Those with skin disease may not tolerate the wearing of protective clothing and those with chronic respiratory disease may not tolerate the wearing of negative pressure respirators.

B. PREPLACEMENT

Routine medical histories and physical examinations are not required. However the employer must screen employees for history of certain medical conditions (listed below) which might place the employee at increased risk from sec-butyl acetate exposure. Only those giving a positive history of these conditions must be referred for further medical examinations.

1. Skin disease -- sec-Butyl acetate is a mild defatting agent and can cause dermatitis on prolonged exposure. Persons with

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

preexisting skin disorders may be more susceptible to the effects of sec-butyl acetate.

2. Kidney disease -- Although sec-butyl acetate is not known as a kidney toxin in humans, the importance of the organ in the elimination of toxic substances justifies special consideration in those with possible impairment of renal function.
3. Chronic respiratory disease -- In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of sec-butyl acetate might cause exacerbation of symptoms due to its irritant properties.
4. Liver disease -- Although sec-butyl acetate is not known as a liver toxin in humans, the importance of this organ in the biotransformation and detoxification of foreign substances should be considered before exposing persons with impaired liver function.

C. PERIODIC EXAMINATIONS

Routine periodic examinations are not required. However, if the employer becomes aware of an employee with the above listed conditions, he must refer such employee for further medical examination.

References

1. Patty, Frank A.: Industrial Hygiene and Toxicology, Vol. II - Toxicology (2d ed. revised), Interscience Publishers, New York, 1963, pp. 1847-1864.
2. American Conference of Governmental Industrial Hygienists: "sec-Butyl Acetate," (3d ed., 2d printing), Documentation of the Threshold Limits Values for Substances in Workroom Air, Cincinnati, 1974, p. 30.

NIOSH/OSHA Draft Technical Standard
and Supporting Documentation for SEC-BUTYL ACETATE

USE/EXPOSURE AND CONTROL DOCUMENT
TERTIARY-BUTYL ACETATE

	Use/Exposure	Principal Route of Entry	Currently Used Control Methods
1.	Inhalation of vapor and skin contact with liquid during use as a dry cleaning agent	A,B	General ventilation
2.	Inhalation of vapor during the manufacture of tertiary-butyl acetate	A	Process enclosure; general dilution ventilation
3.	Inhalation of vapor and skin contact with liquid during spray application of surface coating containing tertiary-butyl acetate	A,B	Local exhaust ventilation; personal protective equipment (gloves)
4.	Inhalation of vapor during the formulation of paint systems	A	Local exhaust ventilation
5.	Inhalation of vapors during use of additives containing tertiary-butyl acetate to improve the antiknock properties of leaded aliphatic gasoline	A	Process enclosure; general dilution ventilation
6.	Inhalation of vapors during the use of tertiary-butyl acetate as an activator in the alkaline polymerization of caprolacton	A	Process enclosure; general dilution ventilation
7.	Potential exposure to the same hazards in the same uses as those for n-butyl acetate and secondary-butyl acetate if the cost of tertiary-butyl acetate became competitive	A	General dilution ventilation

A -- Inhalation

B -- Skin contact resulting in localized irritation

C -- Ingestion

D -- Skin contact resulting in absorption and subsequent systemic poisoning