

Poster Presentations

Presenter	Title	Page
D. Wilder University of Iowa,	Head-trunk motion increase with arm-rest controls	130
L.Frey Law, University of Iowa	Arm and should muscle activity are greater with steering wheel vs. seat mounted controls	132
E.J. Wolf VA Medical Center	Evaluation of powered wheel-chairs with suspension and exposure to whole-body vibration.	134
N. Hosoya Saitama University	Establishment of biodynamic response measurement system of hand-arm	136
J. Wasserman University of Tennessee	Training simulators extend laboratory testing techniques for WBV analysis	138
D.E. Welcome NIOSH	Instrumented handles for studying hand-transmitted vibration exposure	140
R.G. Dong NIOSH	A novel theory: ellipse of grip force	142
S.D. Smith Wright-Patterson Air Force Base	Chest transmissibility characteristics during exposure to single- and combined-axis vibration	144
K. Harrer Naval Medical Center San Diego	A field study: Measurement and evaluation of whole-body vibration for MH-60S pilots	146
A. Joshi University of Missouri-Rolla	Modeling of hand-arm vibration	148
E. Johannig Occupational and Environmental Life Science	Railroad locomotive whole-body vibration study – Vibration, shocks and seat ergonomics	150
T. Jetzer Occupational Medicine Consultants	Clinical assessment and characteristics of men and women exposed to high-level of hand-arm vibration	152
D. Riley Medical College of Milwaukee	Acute effects of vibration on the rat-tail artery	154
O. Wirth NIOSH	Effects of repeated vibration exposures in muscle tissue	156
C. Johnson NIOSH	Vibration exposure reduced nitric oxide concentrations in the ventral artery of the rat tail	158
S. Waugh NIOSH	Acute vibration induces oxidative stress and changes in transcription in soft tissue of rat tail	160
Z.-M. Li University of Pittsburgh	Visualization of multi-digit manipulation mechanics	162
M. J. Jorgensen Wichita State University	Use of TUNGSTEN to reduce vibration exposure in aircraft manufacturing.	164
S. L. Tillim Bonsil Technologies, LLC	Handle design for optimal hand function.	166
J. P. Dickey University of Guelph	Vibration time and rest time during sinusoidal vibration experiments: Do these factors affect comfort ratings?	168

HEAD-TRUNK MOTION INCREASE WITH ARM-REST CONTROLS

D Wilder, S Rahmatalla, M Contratto+, T Xia, L Frey-Law, G Kopp+, N Grosland
University of Iowa, Iowa City, Iowa, U.S.A., +Caterpillar, Inc., Peoria, Illinois, U.S.A.

Introduction

Heavy equipment manufacturers have made a long-term commitment to minimize operator vibration exposure for comfort, performance, and health reasons. Domestic and international guidelines/standards and EC laws dictate exposure limits based on measurement of vibration at the interface between the seat and the operator's buttocks using seat-pad accelerometry.¹⁻⁴ This is historically based on the assumption that the only major source of vibration is transmitted through the seat pan. However, vibration may also be imparted to the head and neck via the steering wheel and/or arm-rest controls and a relatively rigid upper body.⁵ Unfortunately, little is known regarding the influence of arm position on head and neck motion. The purpose of this study was to investigate relative head and trunk motions during riding simulations of large construction equipment, using three different arm control options.

Methods

Five typical heavy equipment ride files were "played back" through a man-rated Servo Test 6-degree-of-freedom vibration system. An 8-camera Vicon motion capture system operating at 200 frames per second, recorded the motion of reflective surface markers on 5th, 50th, and 95th percentile right-handed male subjects, using 3 seat and control configurations (steering wheel (SW), floor mounted armrest controls (FM), seat-mounted armrest controls (SM)). Two trials were performed for each ride and seat control combination (each trial: 60 sec of 6-dof and 60 sec of vertical vibration). The relative motions (change in distances) from the marker over the xiphoid process (caudal end of sternum) to markers over each shoulder, each mid-clavicle, the presternal notch, and to each of four markers on a tight band around the head were calculated (12,001 frames, 6-dof motion only). As a rigid body control, distances between markers on the head band were also monitored. The standard deviation (SD) of the 12,001 distances between pairs of markers was normalized by the mean (L) of the associated distances producing: SD/L which was used as a measure of motion. Error assessments were also performed by analyzing the motion between relatively fixed markers (on the headband). A repeated measures analysis of variance was used to evaluate the results. While five ride files were used, only one ride file containing significant lateral acceleration components was analyzed for comparing the effects of two armrest controls versus use of a steering wheel for this part of our study.

Results

Values of SD/L between the points on the relatively rigid head band were consistently small and similar to each other for all conditions with one exception due to treatment (SM v SW, $p=0.0145$). SD/L between the markers over the xiphoid process and the presternal notch, another region that should be relatively rigid, were also similar to each other for all conditions. Use of floor-mounted, arm rest controls versus a steering wheel produced a significant increase in the value of SD/L between the xiphoid process and: the right shoulder marker (92%, $p=0.0316$), the right mid-clavicle marker (47%, $p=0.0478$), and the right-front marker on the head band (28%, $p=0.0182$). Use of floor-mounted, arm rest controls versus seat-mounted, arm rest controls

produced a significant increase in the value of SD/L between the xiphoid process and the right-back marker on the head band (14%, $p=0.0467$).

Discussion

During a pilot study to assess the efficacy of a motion capture system in whole-body vibration studies, the authors observed a large increase in head-trunk relative motion due to the use of armrest controls, raising a concern about an increased likelihood of injuries. With the use of a steering wheel, the trunk and arms can behave as active dampers, attenuating horizontal motions and maintaining a stable platform for the head-neck system (an inverted pendulum). Armrest controls more rigidly couple the shoulders, via the upper arms, to a vibration source and bypass the damping provided by the entire arm, potentially increasing the risk of motion-related musculoskeletal problems in the neck and upper trunk. While armrests may reduce arm and shoulder fatigue and reduce the effect of the vibrating trunk mass on the lower back, they may do so at the expense of increased motion at the neck and shoulders. The vibration community needs to consider the effect of and attenuation of vibration from sources other than the seat pan. The authors urge the standards and law making communities to consider vibration sources in addition to those at the operator's seat pan.

Acknowledgements

This study was funded by Caterpillar, Inc. of Peoria, IL and was conducted at Sears Manufacturing of Davenport, IA with the help of Mike Drinkall and Jason Boldt. Dean Macken of the Engineering Design and Prototyping Center at the College of Engineering at The University of Iowa helped a great deal with design and setup of specialized equipment. Brad Parker, of the Center for Computer-Aided Design at The University of Iowa provided vital help with computer hardware and software. The study was conducted through the Center for Computer-Aided Design (directed by Karim Abdel-Malek at The University of Iowa), where one of its goals is to optimize the Digital Human.

References

1. ANSI S3.18 2002/ISO 2631-1:1997 Nationally Adopted International Standard (NAIS): Mechanical vibration and shock - Evaluation of human exposure to whole body vibration Part 1: General requirements. *Acoustical Society of America, Melville, NY, 2002-05-13*.
2. European Commission (2002). Directive 2002/44/EC of the European Parliament and of the Council of 25 June 2002 on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents (vibration) (sixteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC) *Official Journal of the European Communities L177(45)13-19, 7 June 2002*
3. ISO 2631-1:1997(E) 2nd Ed 1997-05-01 Corrected and Reprinted 1997-07-15: Mechanical vibration and shock – Evaluation of human exposure to whole-body vibration – Part 1: General Requirements, *International Standards Organization, Geneva, Switzerland, 1997-07-15*.
4. ISO 2631-5:2004(E) 1st Ed 2004-02-15: Mechanical vibration and shock – Evaluation of human exposure to whole-body vibration – Part 5: Method for evaluation of vibration containing multiple shocks, *International Standards Organization, Geneva, Switzerland, 2004-02-15*.
5. National Research Council and the Institute of Medicine (2001) Biomechanics. Chapter 6 in: Musculoskeletal Disorders and the Workplace: Low Back and Upper Extremities. Panel on Musculoskeletal Disorders and the Workplace. Commission on Behavioral and Social Sciences and Education. National Academy Press, Washington, DC, pp219-286.